

# SAR Test Report

Report No. : SF200206C21

Applicant : Fibocom Wireless Inc.

Address : 5/F, Tower A, Technology Building II, 1057 Nanhai Blvd, Nanshan, Shenzhen, China

Product : LTE module

FCC ID : ZMOL850GL

Brand : Fibocom

Model No. : L850-GL

Standards : FCC 47 CFR Part 2 (2.1093), IEEE C95.1:1992, IEEE Std 1528:2013  
KDB 865664 D01 v01r04, KDB 865664 D02 v01r02  
KDB 248227 D01 v02r02, KDB 447498 D01 v06, KDB 616217 D04 v01r02  
KDB 941225 D01 v03r01, KDB 941225 D05 v02r05

Sample Received Date : Feb. 06, 2020

Date of Testing : Feb. 22, 2020 ~ Apr. 07, 2020

Lab Address : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location : No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City, Taiwan

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch–Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :

*Gina Liu*

Gina Liu / Specialist

Approved By :

*Gordon Lin*

Gordon Lin / Manager



FCC Accredited No.: TW0003

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

|                                                                                        |    |
|----------------------------------------------------------------------------------------|----|
| Release Control Record .....                                                           | 3  |
| 1. Summary of Maximum SAR Value .....                                                  | 4  |
| 2. Description of Equipment Under Test .....                                           | 5  |
| 3. SAR Measurement System .....                                                        | 7  |
| 3.1 Definition of Specific Absorption Rate (SAR) .....                                 | 7  |
| 3.2 SPEAG DASY6 System .....                                                           | 7  |
| Robot 8                                                                                |    |
| Probes 9                                                                               |    |
| Data Acquisition Electronics (DAE) .....                                               | 9  |
| Phantoms .....                                                                         | 9  |
| Device Holder .....                                                                    | 10 |
| System Validation Dipoles .....                                                        | 11 |
| Power Source .....                                                                     | 11 |
| Tissue Simulating Liquids .....                                                        | 12 |
| 3.3 SAR System Verification .....                                                      | 14 |
| 3.4 SAR Measurement Procedure .....                                                    | 15 |
| Area Scan and Zoom Scan Procedure .....                                                | 15 |
| Volume Scan Procedure .....                                                            | 16 |
| Power Drift Monitoring .....                                                           | 17 |
| Spatial Peak SAR Evaluation .....                                                      | 17 |
| SAR Averaged Methods .....                                                             | 17 |
| 4. SAR Measurement Evaluation .....                                                    | 18 |
| 6.1 EUT Configuration and Setting .....                                                | 18 |
| 6.2 EUT Testing Position .....                                                         | 22 |
| 6.2.1 Body Exposure Conditions .....                                                   | 22 |
| 6.3 Tissue Verification .....                                                          | 23 |
| 6.4 System Validation .....                                                            | 23 |
| 6.5 System Verification .....                                                          | 23 |
| 6.6 Maximum Output Power .....                                                         | 24 |
| 6.6.1 Maximum Target Conducted Power .....                                             | 24 |
| 6.6.2 Measured Conducted Power Result .....                                            | 24 |
| 6.7 SAR Testing Results .....                                                          | 34 |
| 6.7.1 SAR Test Reduction Considerations .....                                          | 34 |
| 6.7.2 SAR Results for Body Exposure Condition (Test Separation Distance is 0 mm) ..... | 36 |
| 6.7.3 SAR Measurement Variability .....                                                | 38 |
| 6.7.4 Simultaneous Multi-band Transmission Evaluation .....                            | 38 |
| 5. Calibration of Test Equipment .....                                                 | 39 |
| 6. Measurement Uncertainty .....                                                       | 40 |
| 7. Information of the Testing Laboratories .....                                       | 44 |
| Appendix A. SAR Plots of System Verification                                           |    |
| Appendix B. Calibration Certificate for Probe and Dipole                               |    |
| Appendix C. Photographs of EUT and Setup                                               |    |
| Appendix D. Intel WLAN SAR Test Report                                                 |    |

## SAR Test Report

### Release Control Record

| Report No.  | Reason for Change | Date Issued   |
|-------------|-------------------|---------------|
| SF200206C21 | Initial release   | Apr. 08, 2020 |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |
|             |                   |               |

# SAR Test Report

## 1. Summary of Maximum SAR Value

| Equipment Class | Mode     | Highest SAR-1g Body (W/kg) |
|-----------------|----------|----------------------------|
| PCB             | WCDMA II | 0.00                       |
|                 | WCDMA IV | 0.00                       |
|                 | WCDMA V  | 0.00                       |
|                 | LTE 2    | 0.00                       |
|                 | LTE 4    | 0.00                       |
|                 | LTE 5    | 0.00                       |
|                 | LTE 7    | 0.00                       |
|                 | LTE 12   | 0.00                       |
|                 | LTE 13   | 0.00                       |
|                 | LTE 17   | 0.00                       |
|                 | LTE 26   | 0.00                       |
|                 | LTE 30   | 0.00                       |
|                 | LTE 38   | 0.00                       |
|                 | LTE 41   | 0.00                       |
|                 | LTE 66   | 0.00                       |

### Note:

1. The SAR criteria (**Head & Body: SAR-1g1.6 W/kg, and Extremity: SAR-10g 4.0 W/kg**)for general population/uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.
2. The WLAN MAX SAR value please refer to Intel WLAN test report page. 8.

## SAR Test Report

### 2. Description of Equipment Under Test

|                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Type</b>                                        | LTE module                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>FCC ID</b>                                          | ZMOL850GL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Brand Name</b>                                      | Fibocom                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Model Name</b>                                      | L850-GL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>EUT Configurations</b>                              | Sample 1 : EUT with WNC Antenna<br>Sample 2 : EUT with Hong-Bo Antenna<br>Sample 3 : EUT with AWAN Antenna                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Tx Frequency Bands<br/>(Unit: MHz)</b>              | WCDMA Band II : 1852.4 ~ 1907.6<br>WCDMA Band IV : 1712.4 ~ 1752.6<br>WCDMA Band V : 826.4 ~ 846.6<br>LTE Band 2 : 1850.7 ~ 1909.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M)<br>LTE Band 4 : 1710.7 ~ 1754.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M)<br>LTE Band 5 : 824.7 ~ 848.3 (BW: 1.4M, 3M, 5M, 10M)<br>LTE Band 7 : 2502.5 ~ 2567.5 (BW: 5M, 10M, 15M, 20M)<br>LTE Band 12 : 699.7 ~ 715.3 (BW: 1.4M, 3M, 5M, 10M)<br>LTE Band 13 : 779.5 ~ 784.5 (BW: 5M, 10M)<br>LTE Band 17 : 706.5 ~ 713.5 (BW: 5M, 10M)<br>LTE Band 26 : 814.7 ~ 848.3 (BW: 1.4M, 3M, 5M, 10M, 15M)<br>LTE Band 29 : 717 ~ 728(Rx only)<br>LTE Band 30 : 2307.5 ~ 2312.5 (BW: 5M, 10M)<br>LTE Band 38 : 2572.5 ~ 2617.5 (BW: 5M, 10M, 15M, 20M)<br>LTE Band 41 : 2502.5 ~ 2687.5 (BW: 5M, 10M, 15M, 20M)<br>LTE Band 66 : 1710.7 ~ 1779.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M) |
| <b>Uplink Modulations</b>                              | WCDMA : QPSK<br>LTE : QPSK, 16QAM                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Maximum Tune-up Conducted Power<br/>(Unit: dBm)</b> | Please refer to section 4.6.1 of this report                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Antenna Type</b>                                    | Refer note as below                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>EUT Stage</b>                                       | Identical Prototype                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

#### Note:

- The EUT is authorized for use in specific End-product. Please refer to below for more details.

| Item              | Brand Name | Model Name |
|-------------------|------------|------------|
| Notebook Computer | HP         | HSN-I36C   |

- The information of module collocated in this End-product is listed as below.

| Item             | Brand Name | Model Name | Specification                                                   |
|------------------|------------|------------|-----------------------------------------------------------------|
| BT + WiFi module | Intel      | AX201NGW   | 2T2R 802.11 a/b/g/n/ac/ax WLAN + Bluetooth                      |
| WWAN module      | Fibocom    | L850-GL    | WCDMA Band II/IV/V, LTE Band 2/4/5/7/12/13/17/26/29/30/38/41/66 |
| NFC module       | WNC        | XRAV-1     | NFC                                                             |

## SAR Test Report

3. The WWAN antenna information is listed as below.

| LTE Band     | AWAN                           |                                | HONG-BO                     |                             | WNC                            |                                |
|--------------|--------------------------------|--------------------------------|-----------------------------|-----------------------------|--------------------------------|--------------------------------|
|              | NB Mode                        |                                | NB Mode                     |                             | NB Mode                        |                                |
|              | TX1                            | TX2                            | TX1                         | TX2                         | TX1                            | TX2                            |
| Parts number | 6036B0255901<br>(AUP6Y-100025) | 6036B0255301<br>(AUP6Y-100026) | 6036B0257701<br>(260-27365) | 6036B0258501<br>(260-27366) | 6036B0253201<br>(81EABB15.G35) | 6036B0253301<br>(81EABB15.G36) |
| FDD B2       | 1.68                           | -2.80                          | -0.81                       | -1.69                       | 0.22                           | -0.45                          |
| FDD B4       | -1.27                          | -1.93                          | -2.26                       | -0.61                       | -1.11                          | 0.63                           |
| FDD B5       | -3.75                          | -4.57                          | -0.78                       | -2.70                       | 0.08                           | -2.65                          |
| FDD B7       | -                              | -5.17                          | 0.22                        | -2.82                       | -0.19                          | -1.32                          |
| FDD B12      | -1.02                          | -1.97                          | -1.20                       | -4.12                       | -1.73                          | -3.12                          |
| FDD B13      | -2.50                          | -2.00                          | -2.13                       | -4.84                       | -1.47                          | -3.10                          |
| FDD B17      | -3.51                          | -1.97                          | -1.20                       | -4.12                       | -1.73                          | -3.12                          |
| FDD B26      | -3.75                          | -3.95                          | -0.78                       | -2.70                       | 0.08                           | -2.65                          |
| FDD B29      | -                              | -2.27                          | -                           | -                           | -                              | -                              |
| FDD B30      | -                              | -1.26                          | -                           | -2.21                       | -                              | 0.55                           |
| TDD B38      | -0.38                          | -4.73                          | 0.03                        | -2.82                       | -1.30                          | -2.14                          |
| TDD B41      | 0.74                           | -1.53                          | 0.22                        | -2.82                       | -0.19                          | -1.32                          |
| FDD B66      | -1.27                          | -1.93                          | -2.26                       | -0.61                       | -1.11                          | 0.63                           |
| WCDMA B2     | 1.68                           | -2.80                          | -0.81                       | -1.69                       | 0.22                           | -0.45                          |
| WCDMA B4     | -1.27                          | -1.93                          | -2.26                       | -0.61                       | -1.11                          | 0.63                           |
| WCDMA B5     | -3.75                          | -4.57                          | -0.78                       | -2.70                       | 0.08                           | -2.65                          |

4. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

### 3. SAR Measurement System

#### 3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

#### 3.2 SPEAG DASY6 System

DASY6 system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY6 software defined. The DASY6 software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

## SAR Test Report




**Fig-3.1 SPEAG DASY6 System Setup**

### Robot

The DASY6 systems use the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version of CS8c from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability  $\pm 0.035$  mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



**Fig-3.2 SPEAG DASY6 System**

## SAR Test Report

### Probes


The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

|                      |                                                                                                                                                          |                                                                                     |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>         | EX3DV4                                                                                                                                                   |  |
| <b>Construction</b>  | Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE). |                                                                                     |
| <b>Frequency</b>     | 4 MHz to 10 GHz<br>Linearity: $\pm 0.2$ dB                                                                                                               |                                                                                     |
| <b>Directivity</b>   | $\pm 0.1$ dB in TSL (rotation around probe axis)<br>$\pm 0.3$ dB in TSL (rotation normal to probe axis)                                                  |                                                                                     |
| <b>Dynamic Range</b> | 10 $\mu$ W/g to 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically $< 1$ $\mu$ W/g)                                                                   |                                                                                     |
| <b>Dimensions</b>    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                     |                                                                                     |


### Data Acquisition Electronics (DAE)

|                             |                                                                                                                                                                                                                                                     |                                                                                      |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>                | DAE3, DAE4                                                                                                                                                                                                                                          |  |
| <b>Construction</b>         | Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop. |                                                                                      |
| <b>Measurement Range</b>    | -100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)                                                                                                                                                                              |                                                                                      |
| <b>Input Offset Voltage</b> | $< 5\mu$ V (with auto zero)                                                                                                                                                                                                                         |                                                                                      |
| <b>Input Bias Current</b>   | $< 50$ fA                                                                                                                                                                                                                                           |                                                                                      |
| <b>Dimensions</b>           | 60 x 60 x 68 mm                                                                                                                                                                                                                                     |                                                                                      |

### Phantoms

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>           | SAM-Twin Phantom                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |  |
| <b>Construction</b>    | The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE Std 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body-mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot. |                                                                                       |
| <b>Material</b>        | Vinylester, fiberglass reinforced (VE-GF)                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                       |
| <b>Shell Thickness</b> | $2 \pm 0.2$ mm ( $6 \pm 0.2$ mm at ear point)                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                       |
| <b>Dimensions</b>      | Length: 1000 mm<br>Width: 500 mm<br>Height: adjustable feet                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                       |
| <b>Filling Volume</b>  | approx. 25 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                       |

## SAR Test Report

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                     |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>           | ELI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |
| <b>Construction</b>    | The ELI phantom is used for compliance testing of handheld and body-mounted wireless devices. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. |                                                                                     |
| <b>Material</b>        | Vinylester, fiberglass reinforced (VE-GF)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                     |
| <b>Shell Thickness</b> | $2.0 \pm 0.2$ mm (bottom plate)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                     |
| <b>Dimensions</b>      | Major axis: 600 mm<br>Minor axis: 400 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                     |
| <b>Filling Volume</b>  | approx. 30 liters                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                     |

### Device Holder

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>        | MD4HHTV5 - Mounting Device for Hand-Held Transmitters                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |
| <b>Construction</b> | In combination with the Twin SAM or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). |                                                                                      |
| <b>Material</b>     | Polyoxymethylene (POM)                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                      |

|                     |                                                                                                                                                                          |                                                                                       |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>        | MDA4WTV5 - Mounting Device Adaptor for Ultra Wide Transmitters                                                                                                           |  |
| <b>Construction</b> | An upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm. |                                                                                       |
| <b>Material</b>     | Polyoxymethylene (POM)                                                                                                                                                   |                                                                                       |

|                     |                                                                                                                                          |                                                                                       |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>        | MDA4SPV6 - Mounting Device Adaptor for Smart Phones                                                                                      |  |
| <b>Construction</b> | The solid low-density MDA4SPV6 adaptor assuring no impact on the DUT radiation performance and is conform with any DUT design and shape. |                                                                                       |
| <b>Material</b>     | ROHACELL                                                                                                                                 |                                                                                       |

## SAR Test Report

|                     |                                                                                                                                                                                                                                              |                                                                                     |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Model</b>        | MD4LAPV5 - Mounting Device for Laptops and other Body-Worn Transmitters                                                                                                                                                                      |  |
| <b>Construction</b> | In combination with the Twin SAM or ELI phantoms, the Mounting Device (Body-Worn) enables testing of transmitter devices according to IEC 62209-2 specifications. The device holder can be locked for positioning at a flat phantom section. |                                                                                     |
| <b>Material</b>     | Polyoxymethylene (POM), PET-G, Foam                                                                                                                                                                                                          |                                                                                     |

### System Validation Dipoles

|                         |                                                                                                                                                                      |                                                                                      |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Model</b>            | D-Serial                                                                                                                                                             |  |
| <b>Construction</b>     | Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions. |                                                                                      |
| <b>Frequency</b>        | 750 MHz to 5800 MHz                                                                                                                                                  |                                                                                      |
| <b>Return Loss</b>      | > 20 dB                                                                                                                                                              |                                                                                      |
| <b>Power Capability</b> | > 100 W (f < 1GHz), > 40 W (f > 1GHz)                                                                                                                                |                                                                                      |


### Power Source

|                              |                                                           |                                                                                       |
|------------------------------|-----------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Model</b>                 | Powersource1                                              |  |
| <b>Signal Type</b>           | Continuous Wave                                           |                                                                                       |
| <b>Operating Frequencies</b> | 600 MHz to 5850 MHz                                       |                                                                                       |
| <b>Output Power</b>          | -5.0 dBm to +17.0 dBm                                     |                                                                                       |
| <b>Power Supply</b>          | 5V DC, via USB jack                                       |                                                                                       |
| <b>Power Consumption</b>     | <3 W                                                      |                                                                                       |
| <b>Applications</b>          | System performance check and validation with a CW signal. |                                                                                       |

## SAR Test Report

### Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 10 % are listed in Table-3.1.

|                                          |                                                                                    |
|------------------------------------------|------------------------------------------------------------------------------------|
|                                          |  |
| Photo of Liquid Height for Head Position | Photo of Liquid Height for Body Position                                           |

**Table-3.1 Targets of Tissue Simulating Liquid**

| Frequency (MHz) | Target Permittivity | Range of $\pm 10\%$ | Target Conductivity | Range of $\pm 10\%$ |
|-----------------|---------------------|---------------------|---------------------|---------------------|
| 450             | 43.5                | 39.2 ~ 47.9         | 0.87                | 0.78 ~ 0.96         |
| 750             | 41.9                | 37.7 ~ 46.1         | 0.89                | 0.80 ~ 0.98         |
| 835             | 41.5                | 37.4 ~ 45.7         | 0.90                | 0.81 ~ 0.99         |
| 900             | 41.5                | 37.4 ~ 45.7         | 0.97                | 0.87 ~ 1.07         |
| 1450            | 40.5                | 36.5 ~ 44.6         | 1.20                | 1.08 ~ 1.32         |
| 1500            | 40.4                | 36.4 ~ 44.4         | 1.23                | 1.11 ~ 1.35         |
| 1640            | 40.2                | 36.2 ~ 44.2         | 1.31                | 1.18 ~ 1.44         |
| 1750            | 40.1                | 36.1 ~ 44.1         | 1.37                | 1.23 ~ 1.51         |
| 1800            | 40.0                | 36.0 ~ 44.0         | 1.40                | 1.26 ~ 1.54         |
| 1900            | 40.0                | 36.0 ~ 44.0         | 1.40                | 1.26 ~ 1.54         |
| 2000            | 40.0                | 36.0 ~ 44.0         | 1.40                | 1.26 ~ 1.54         |
| 2100            | 39.8                | 35.8 ~ 43.8         | 1.49                | 1.34 ~ 1.64         |
| 2300            | 39.5                | 35.6 ~ 43.5         | 1.67                | 1.50 ~ 1.84         |
| 2450            | 39.2                | 35.3 ~ 43.1         | 1.80                | 1.62 ~ 1.98         |
| 2600            | 39.0                | 35.1 ~ 42.9         | 1.96                | 1.76 ~ 2.16         |
| 3000            | 38.5                | 34.7 ~ 42.4         | 2.40                | 2.16 ~ 2.64         |
| 3500            | 37.9                | 34.1 ~ 41.7         | 2.91                | 2.62 ~ 3.20         |
| 4000            | 37.4                | 33.7 ~ 41.1         | 3.43                | 3.09 ~ 3.77         |
| 4500            | 36.8                | 33.1 ~ 40.5         | 3.94                | 3.55 ~ 4.33         |
| 5000            | 36.2                | 32.6 ~ 39.8         | 4.45                | 4.01 ~ 4.90         |
| 5200            | 36.0                | 32.4 ~ 39.6         | 4.66                | 4.19 ~ 5.13         |
| 5400            | 35.8                | 32.2 ~ 39.4         | 4.86                | 4.37 ~ 5.35         |
| 5600            | 35.5                | 32.0 ~ 39.1         | 5.07                | 4.56 ~ 5.58         |
| 5800            | 35.3                | 31.8 ~ 38.8         | 5.27                | 4.74 ~ 5.80         |
| 6000            | 35.1                | 31.6 ~ 38.6         | 5.48                | 4.93 ~ 6.03         |

## SAR Test Report

The dielectric properties of the tissue simulating liquids are defined in IEC 62209-1 and IEC 62209-2. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Since the range of  $\pm 10\%$  of the required target values is used to measure relative permittivity and conductivity, the SAR correction procedure is applied to correct measured SAR for the deviations in permittivity and conductivity. Only positive correction has been used to scale up the measured SAR, and SAR result would not be corrected if the correction  $\Delta$  SAR has a negative sign.


The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid**

| Tissue Type | Bactericide | DGBE | HEC | NaCl | Sucrose | Triton X-100 | Water | Diethylene Glycol Mono-hexylether |
|-------------|-------------|------|-----|------|---------|--------------|-------|-----------------------------------|
| H750        | 0.2         | -    | 0.2 | 1.5  | 56.0    | -            | 42.1  | -                                 |
| H835        | 0.2         | -    | 0.2 | 1.5  | 57.0    | -            | 41.1  | -                                 |
| H900        | 0.2         | -    | 0.2 | 1.4  | 58.0    | -            | 40.2  | -                                 |
| H1450       | -           | 43.3 | -   | 0.6  | -       | -            | 56.1  | -                                 |
| H1640       | -           | 45.8 | -   | 0.5  | -       | -            | 53.7  | -                                 |
| H1750       | -           | 47.0 | -   | 0.4  | -       | -            | 52.6  | -                                 |
| H1800       | -           | 44.5 | -   | 0.3  | -       | -            | 55.2  | -                                 |
| H1900       | -           | 44.5 | -   | 0.2  | -       | -            | 55.3  | -                                 |
| H2000       | -           | 44.5 | -   | 0.1  | -       | -            | 55.4  | -                                 |
| H2300       | -           | 44.9 | -   | 0.1  | -       | -            | 55.0  | -                                 |
| H2450       | -           | 45.0 | -   | 0.1  | -       | -            | 54.9  | -                                 |
| H2600       | -           | 45.1 | -   | 0.1  | -       | -            | 54.8  | -                                 |
| H3500       | -           | 8.0  | -   | 0.2  | -       | 20.0         | 71.8  | -                                 |
| H5G         | -           | -    | -   | -    | -       | 17.2         | 65.5  | 17.3                              |

## 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



**Fig-3.3 System Verification Setup**

The SPEAG Powersource1 is a portable and very stable RF source providing a continuous wave (CW) signal. It is designed for conducting SAR system checks and SAR system validation of DASY and is compatible with IEC 62209-1, IEC 62209-2 and IEEE Std 1528 standards. The Powersource1 has been calibrated by SPEAG's ISO/IEC 17025-accredited calibration center. When using Powersource1, the setup can be simplified, as shown in Fig-3.3. The signal purity is warranted by design. Since the Powersource1 is calibrated, no additional equipment is needed and the Powersource1 can directly be connected to the SMA connector of the dipole without a cable as all separate components (signal generator, amplifier, coupler and power meter) are built into the unit.

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The Powersource1 is adjusted for the desired forward power of 17 dBm at the dipole connector and the RF output power would be turned on. After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

## 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

### Area Scan and Zoom Scan Procedure

First area scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an area scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, zoom scan is required. The zoom scan is performed around the highest E-field value to determine the averaged SAR-distribution.

Measure the local SAR at a test point at 1.4 mm of the inner surface of the phantom recommended by SEPAG. The area scan (two-dimensional SAR distribution) is performed cover at least an area larger than the projection of the EUT or antenna. The measurement resolution and spatial resolution for interpolation shall be chosen to allow identification of the local peak locations to within one-half of the linear dimension of the corresponding side of the zoom scan volume. Following table provides the measurement parameters required for the area scan.

| Parameter                                                                                 | $f \leq 3 \text{ GHz}$                                                                | $3 \text{ GHz} < f \leq 6 \text{ GHz}$                                               |
|-------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Maximum distance from closest measurement point to phantom surface                        | $5 \pm 1$                                                                             | $\delta \ln(2)/2 \pm 0.5$                                                            |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location | $30^\circ \pm 1^\circ$                                                                | $20^\circ \pm 1^\circ$                                                               |
| Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$    | $\leq 2 \text{ GHz: } \leq 15 \text{ mm}$<br>$2 - 3 \text{ GHz: } \leq 12 \text{ mm}$ | $3 - 4 \text{ GHz: } \leq 12 \text{ mm}$<br>$4 - 6 \text{ GHz: } \leq 10 \text{ mm}$ |

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks. Additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g. 1 W/kg for 1.6 W/kg, 1 g limit; or 1.26 W/kg for 2 W/kg, 10 g limit).

## SAR Test Report

The zoom scan (three-dimensional SAR distribution) is performed at the local maxima locations identified in previous area scan procedure. The zoom scan volume must be larger than the required minimum dimensions. When graded grids are used, which only applies in the direction normal to the phantom surface, the initial grid separation closest to the phantom surface and subsequent graded grid increment ratios must satisfy the required protocols. The 1-g SAR averaging volume must be fully contained within the zoom scan measurement volume boundaries; otherwise, the measurement must be repeated by shifting or expanding the zoom scan volume. The similar requirements also apply to 10-g SAR measurements. Following table provides the measurement parameters required for the zoom scan.

| Parameter                                                                              |                                                             | $f \leq 3 \text{ GHz}$                                                              | $3 \text{ GHz} < f \leq 6 \text{ GHz}$                                                                                              |
|----------------------------------------------------------------------------------------|-------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Maximum zoom scan spatial resolution: $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$ |                                                             | $\leq 2 \text{ GHz: } \leq 8 \text{ mm}$<br>$2 - 3 \text{ GHz: } \leq 5 \text{ mm}$ | $3 - 4 \text{ GHz: } \leq 5 \text{ mm}$<br>$4 - 6 \text{ GHz: } \leq 4 \text{ mm}$                                                  |
| Maximum zoom scan spatial resolution, normal to phantom surface                        | <i>uniform grid: <math>\Delta z_{\text{zoom}}(n)</math></i> | $\leq 5 \text{ mm}$                                                                 | $3 - 4 \text{ GHz: } \leq 4 \text{ mm}$<br>$4 - 5 \text{ GHz: } \leq 3 \text{ mm}$<br>$5 - 6 \text{ GHz: } \leq 2 \text{ mm}$       |
|                                                                                        | <i>graded grids: <math>\Delta z_{\text{zoom}}(1)</math></i> | $\leq 4 \text{ mm}$                                                                 | $3 - 4 \text{ GHz: } \leq 3.0 \text{ mm}$<br>$4 - 5 \text{ GHz: } \leq 2.5 \text{ mm}$<br>$5 - 6 \text{ GHz: } \leq 2.0 \text{ mm}$ |
|                                                                                        | $\Delta z_{\text{zoom}}(n>1)$                               | $\leq 1.5 \cdot \Delta z_{\text{zoom}}(n-1) \text{ mm}$                             |                                                                                                                                     |
| Minimum zoom scan volume (x, y, z)                                                     |                                                             | $\geq 30 \text{ mm}$                                                                | $3 - 4 \text{ GHz: } \geq 28 \text{ mm}$<br>$4 - 5 \text{ GHz: } \geq 25 \text{ mm}$<br>$5 - 6 \text{ GHz: } \geq 22 \text{ mm}$    |

Per IEC 62209-2 AMD1, the successively higher resolution zoom scan is required if the zoom scan measured as defined above complies with both of the following criteria, or if the peak spatial-average SAR is below 0.1 W/kg, no additional measurements are needed:

- (1) The smallest horizontal distance from the local SAR peaks to all points 3 dB below the SAR peak shall be larger than the horizontal grid steps in both x and y directions ( $\Delta x, \Delta y$ ). This shall be checked for the measured zoom scan plane conformal to the phantom at the distance  $z_{M1}$ .
- (2) The ratio of the SAR at the second measured point (M2) to the SAR at the closest measured point (M1) at the x-y location of the measured maximum SAR value shall be at least 30 %.

If one or both of the above criteria are not met, the zoom scan measurement shall be repeated using a finer resolution. New horizontal and vertical grid steps shall be determined from the measured SAR distribution so that the above criteria are met. Compliance with the above two criteria shall be demonstrated for the new measured zoom scan.

### Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

## SAR Test Report

---

### Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

### Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

### SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

## 4. SAR Measurement Evaluation

### 5.1 EUT Configuration and Setting

#### <Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator. Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

#### <Considerations Related to WCDMA for Setup and Testing>

##### **Handsets with Release 5 HSDPA**

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the “Release 5 HSDPA Data Devices”, for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

##### **Handsets with Release 6 HSUPA**

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the “Release 6 HSPA Data Devices”, for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

##### **Release 5 HSDPA Data Devices**

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors ( $\beta_c$ ,  $\beta_d$ ), and HS-DPCCH power offset parameters ( $\Delta_{ACK}$ ,  $\Delta_{NACK}$ ,  $\Delta_{CQI}$ ) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

## SAR Test Report

| Sub-test | $\beta_c$            | $\beta_d$            | $\beta_d$<br>(SF) | $\beta_c/\beta_d$    | $\beta_{HS}^{(1)(2)}$ | CM <sup>(3)</sup><br>(dB) | MPR <sup>(3)</sup><br>(dB) |
|----------|----------------------|----------------------|-------------------|----------------------|-----------------------|---------------------------|----------------------------|
| 1        | 2/15                 | 15/15                | 64                | 2/15                 | 4/15                  | 0.0                       | 0.0                        |
| 2        | 12/15 <sup>(4)</sup> | 15/15 <sup>(4)</sup> | 64                | 12/15 <sup>(4)</sup> | 24/15                 | 1.0                       | 0.0                        |
| 3        | 15/15                | 8/15                 | 64                | 15/8                 | 30/15                 | 1.5                       | 0.5                        |
| 4        | 15/15                | 4/15                 | 64                | 15/4                 | 30/15                 | 1.5                       | 0.5                        |

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ .

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA,  $\Delta_{ACK}$  and  $\Delta_{NACK} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ , and  $\Delta_{CQI} = 24/15$  with  $\beta_{HS} = 24/15 * \beta_c$ .

Note 3: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{HS}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$ .

### Release 6 HSPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the  $\beta$  values indicated in below.

| Sub-test | $\beta_c$            | $\beta_d$            | $\beta_d$<br>(SF) | $\beta_c/\beta_d$    | $\beta_{HS}^{(1)}$ | $\beta_{ec}$ | $\beta_{ed}^{(4)(5)}$                        | $\beta_{ed}$<br>(SF) | $\beta_{ed}$<br>(Codes) | CM <sup>(2)</sup><br>(dB) | MPR <sup>(2)(6)</sup><br>(dB) | AG <sup>(5)</sup><br>Index | E-TFCI |
|----------|----------------------|----------------------|-------------------|----------------------|--------------------|--------------|----------------------------------------------|----------------------|-------------------------|---------------------------|-------------------------------|----------------------------|--------|
| 1        | 11/15 <sup>(3)</sup> | 15/15 <sup>(3)</sup> | 64                | 11/15 <sup>(3)</sup> | 22/15              | 209/225      | 1309/225                                     | 4                    | 1                       | 1.0                       | 0.0                           | 20                         | 75     |
| 2        | 6/15                 | 15/15                | 64                | 6/15                 | 12/15              | 12/15        | 94/75                                        | 4                    | 1                       | 3.0                       | 2.0                           | 12                         | 67     |
| 3        | 15/15                | 9/15                 | 64                | 15/9                 | 30/15              | 30/15        | $\beta_{ed1}: 47/15$<br>$\beta_{ed2}: 47/15$ | 4                    | 2                       | 2.0                       | 1.0                           | 15                         | 92     |
| 4        | 2/15                 | 15/15                | 64                | 2/15                 | 4/15               | 2/15         | 56/75                                        | 4                    | 1                       | 3.0                       | 2.0                           | 17                         | 71     |
| 5        | 15/15                | 0                    | -                 | -                    | 5/15               | 5/15         | 47/15                                        | 4                    | 1                       | 1.0                       | 0.0                           | 12                         | 67     |

Note 1: For sub-test 1 to 4,  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 30/15$  with  $\beta_{HS} = 30/15 * \beta_c$ . For sub-test 5,  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 5/15$  with  $\beta_{HS} = 5/15 * \beta_c$ .

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $\beta_{HS}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5:  $\beta_{ed}$  can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

## SAR Test Report

### <Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports both QPSK and 16QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK and 16QAM modulation. The results please refer to section 4.6 of this report.

| EUT Supported LTE Band and Channel Bandwidth |            |          |          |           |           |           |
|----------------------------------------------|------------|----------|----------|-----------|-----------|-----------|
| LTE Band                                     | BW 1.4 MHz | BW 3 MHz | BW 5 MHz | BW 10 MHz | BW 15 MHz | BW 20 MHz |
| 2                                            | V          | V        | V        | V         | V         | V         |
| 4                                            | V          | V        | V        | V         | V         | V         |
| 5                                            | V          | V        | V        | V         |           |           |
| 7                                            |            |          | V        | V         | V         | V         |
| 12                                           | V          | V        | V        | V         |           |           |
| 13                                           |            |          | V        | V         |           |           |
| 17                                           |            |          | V        | V         |           |           |
| 26                                           | V          | V        | V        | V         | V         |           |
| 30                                           |            |          | V        | V         |           |           |
| 38                                           |            |          | V        | V         | V         | V         |
| 41                                           |            |          | V        | V         | V         | V         |
| 66                                           | V          | V        | V        | V         | V         | V         |

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

| Modulation | Channel Bandwidth / RB Configurations |          |          |           |           |           | LTE MPR Setting (dB) |
|------------|---------------------------------------|----------|----------|-----------|-----------|-----------|----------------------|
|            | BW 1.4 MHz                            | BW 3 MHz | BW 5 MHz | BW 10 MHz | BW 15 MHz | BW 20 MHz |                      |
| QPSK       | > 5                                   | > 4      | > 8      | > 12      | > 16      | > 18      | 1                    |
| 16QAM      | <= 5                                  | <= 4     | <= 8     | <= 12     | <= 16     | <= 18     | 1                    |
| 16QAM      | > 5                                   | > 4      | > 8      | > 12      | > 16      | > 18      | 2                    |

**Note:** MPR is according to the standard and implemented in the circuit (mandatory).


In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

### TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.

## SAR Test Report



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

| Special Subframe Configuration | Normal Cyclic Prefix in Downlink |                                |                                  | Extended Cyclic Prefix in Downlink |                                |                                  |
|--------------------------------|----------------------------------|--------------------------------|----------------------------------|------------------------------------|--------------------------------|----------------------------------|
|                                | DwPTS                            | UpPTS                          |                                  | DwPTS                              | UpPTS                          |                                  |
|                                |                                  | Normal Cyclic Prefix in Uplink | Extended Cyclic Prefix in Uplink |                                    | Normal Cyclic Prefix in Uplink | Extended Cyclic Prefix in Uplink |
| 0                              | 6592 • Ts                        | 2192 • Ts                      | 2560 • Ts                        | 7680 • Ts                          | 2192 • Ts                      | 2560 • Ts                        |
| 1                              | 19760 • Ts                       |                                |                                  | 20480 • Ts                         |                                |                                  |
| 2                              | 21952 • Ts                       |                                |                                  | 23040 • Ts                         |                                |                                  |
| 3                              | 24144 • Ts                       |                                |                                  | 25600 • Ts                         |                                |                                  |
| 4                              | 26336 • Ts                       | 4384 • Ts                      | 5120 • Ts                        | 7680 • Ts                          | 4384 • Ts                      | 5120 • Ts                        |
| 5                              | 6592 • Ts                        |                                |                                  | 20480 • Ts                         |                                |                                  |
| 6                              | 19760 • Ts                       |                                |                                  | 23040 • Ts                         |                                |                                  |
| 7                              | 21952 • Ts                       |                                |                                  | 12800 • Ts                         |                                |                                  |
| 8                              | 24144 • Ts                       | -                              | -                                | -                                  | -                              | -                                |
| 9                              | 13168 • Ts                       |                                |                                  | -                                  | -                              | -                                |

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

| Uplink-Downlink Configuration | Downlink-to-Uplink Switch-Point Periodicity | Subframe Number |   |   |   |   |   |   |   |   |   |
|-------------------------------|---------------------------------------------|-----------------|---|---|---|---|---|---|---|---|---|
|                               |                                             | 0               | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 0                             | 5 ms                                        | D               | S | U | U | U | D | S | U | U | U |
| 1                             | 5 ms                                        | D               | S | U | U | D | D | S | U | U | D |
| 2                             | 5 ms                                        | D               | S | U | D | D | D | S | U | D | D |
| 3                             | 10 ms                                       | D               | S | U | U | U | D | D | D | D | D |
| 4                             | 10 ms                                       | D               | S | U | U | D | D | D | D | D | D |
| 5                             | 10 ms                                       | D               | S | U | D | D | D | D | D | D | D |
| 6                             | 5 ms                                        | D               | S | U | U | U | D | S | U | U | D |

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations


The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

| UL-DL Configuration | 0      | 1      | 2      | 3      | 4      | 5      | 6      |
|---------------------|--------|--------|--------|--------|--------|--------|--------|
| Highest Duty-Cycle  | 63.33% | 43.33% | 23.33% | 31.67% | 21.67% | 11.67% | 53.33% |

### 5.2 EUT Testing Position

#### 5.2.1 Body Exposure Conditions

For laptop PC, according to KDB 616217 D04, SAR evaluation is required for the bottom surface of the keyboard. This EUT was tested in the base of EUT directly against the flat phantom. The required minimum test separation distance for incorporating transmitters and antennas into laptop computer display is determined with the display screen opened at an angle of 90° to the keyboard compartment.



**Fig-4.1 Illustration for Laptop Setup**

## SAR Test Report

### 5.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

| Frequency (MHz) | Liquid Temp. (°C) | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Target Conductivity ( $\sigma$ ) | Target Permittivity ( $\epsilon_r$ ) | Conductivity Deviation (%) | Permittivity Deviation (%) | Test Date     |
|-----------------|-------------------|------------------------------------|----------------------------------------|----------------------------------|--------------------------------------|----------------------------|----------------------------|---------------|
| 750             | 23.2              | 0.897                              | 42.647                                 | 0.89                             | 41.9                                 | 0.79                       | 1.78                       | Feb. 22, 2020 |
| 835             | 23.2              | 0.945                              | 43.009                                 | 0.9                              | 41.5                                 | 5.00                       | 3.64                       | Feb. 22, 2020 |
| 1750            | 23.1              | 1.321                              | 39.593                                 | 1.37                             | 40.1                                 | -3.58                      | -1.26                      | Feb. 22, 2020 |
| 1750            | 23.3              | 1.321                              | 39.01                                  | 1.37                             | 40.1                                 | -3.58                      | -2.72                      | Apr. 07, 2020 |
| 1900            | 23.1              | 1.455                              | 39.103                                 | 1.4                              | 40                                   | 3.93                       | -2.24                      | Feb. 22, 2020 |
| 2300            | 23.3              | 1.73                               | 39.008                                 | 1.67                             | 39.5                                 | 3.59                       | -1.25                      | Feb. 23, 2020 |
| 2600            | 23.1              | 2.008                              | 37.939                                 | 1.96                             | 39                                   | 2.45                       | -2.72                      | Feb. 22, 2020 |
| 2600            | 23.3              | 2.036                              | 37.818                                 | 1.96                             | 39                                   | 3.88                       | -3.03                      | Feb. 23, 2020 |
| 2600            | 23.1              | 2.047                              | 38.553                                 | 1.96                             | 39                                   | 4.44                       | -1.15                      | Feb. 26, 2020 |

### 5.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

| Test Date     | Probe S/N | Calibration Point | Measured Conductivity ( $\sigma$ ) | Measured Permittivity ( $\epsilon_r$ ) | Validation for CW |                 |                | Validation for Modulation |             |     |
|---------------|-----------|-------------------|------------------------------------|----------------------------------------|-------------------|-----------------|----------------|---------------------------|-------------|-----|
|               |           |                   |                                    |                                        | Sensitivity Range | Probe Linearity | Probe Isotropy | Modulation Type           | Duty Factor | PAR |
| Feb. 22, 2020 | 7472      | 750               | 0.897                              | 42.647                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |
| Feb. 22, 2020 | 7472      | 835               | 0.945                              | 43.009                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |
| Feb. 22, 2020 | 7472      | 1750              | 1.321                              | 39.593                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |
| Apr. 07, 2020 | 3820      | 1750              | 1.321                              | 39.01                                  | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |
| Feb. 22, 2020 | 7472      | 1900              | 1.455                              | 39.103                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |
| Feb. 23, 2020 | 7472      | 2300              | 1.73                               | 39.008                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |
| Feb. 22, 2020 | 7472      | 2600              | 2.008                              | 37.939                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |
| Feb. 23, 2020 | 7472      | 2600              | 2.036                              | 37.818                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |
| Feb. 26, 2020 | 3971      | 2600              | 2.047                              | 38.553                                 | Pass              | Pass            | Pass           | N/A                       | N/A         | N/A |

### 5.5 System Verification

The measuring result for system verification is tabulated as below.

| Test Date     | Frequency (MHz) | 1W Target SAR-1g (W/kg) | Measured SAR-1g (W/kg) | Normalized to 1W SAR-1g (W/kg) | Deviation (%) | Dipole S/N | Probe S/N | DAE S/N |
|---------------|-----------------|-------------------------|------------------------|--------------------------------|---------------|------------|-----------|---------|
| Feb. 22, 2020 | 750             | 8.56                    | 0.394                  | 7.88                           | -7.94         | 1013       | 7472      | 1431    |
| Feb. 22, 2020 | 835             | 9.61                    | 0.47                   | 9.32                           | -3.02         | 4d121      | 7472      | 1431    |
| Feb. 22, 2020 | 1750            | 37.00                   | 1.85                   | 37.00                          | 0.00          | 1055       | 7472      | 1431    |
| Apr. 07, 2020 | 1750            | 37.00                   | 1.86                   | 37.20                          | 0.54          | 1055       | 3820      | 916     |
| Feb. 22, 2020 | 1900            | 40.30                   | 1.96                   | 39.20                          | -2.73         | 5d018      | 7472      | 1431    |
| Feb. 23, 2020 | 2300            | 47.90                   | 2.37                   | 47.40                          | -1.04         | 1092       | 7472      | 1431    |
| Feb. 22, 2020 | 2600            | 57.30                   | 2.83                   | 56.60                          | -1.22         | 1020       | 7472      | 1431    |
| Feb. 23, 2020 | 2600            | 57.30                   | 2.84                   | 56.80                          | -0.87         | 1020       | 7472      | 1431    |
| Feb. 26, 2020 | 2600            | 57.30                   | 2.83                   | 56.60                          | -1.22         | 1020       | 3971      | 1277    |

#### Note:

Comparing to the reference SAR value provided by SPEAG in dipole calibration certificate, the deviation of system check results is within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots please refer to **Appendix A** of this report.

## SAR Test Report

### 5.6 Maximum Output Power

#### 5.6.1 Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

| Mode                     | WCDMA Band II | WCDMA Band IV | WCDMA Band V |
|--------------------------|---------------|---------------|--------------|
| RMC 12.2K                | 23.5          | 23.5          | 23.5         |
| HSDPA / HSUPA / DC-HSDPA | 23.5          | 23.5          | 23.5         |

| Mode                 | LTE 2 | LTE 4 | LTE 5 | LTE 7 |
|----------------------|-------|-------|-------|-------|
| Maximum Target Power | 23.0  | 23.0  | 23.0  | 23.0  |

| Mode                 | LTE 12 | LTE 13 | LTE 17 | LTE 26 |
|----------------------|--------|--------|--------|--------|
| Maximum Target Power | 23.0   | 23.0   | 23.0   | 23.0   |

| Mode                 | LTE 30 | LTE 38 | LTE 41 | LTE 66 |
|----------------------|--------|--------|--------|--------|
| Maximum Target Power | 23.0   | 23.0   | 23.0   | 23.0   |

#### 5.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

| Band                       | WCDMA Band II |        |        | WCDMA Band IV |        |        | WCDMA Band V |       |       | 3GPP<br>MPR<br>(dB) |
|----------------------------|---------------|--------|--------|---------------|--------|--------|--------------|-------|-------|---------------------|
| Channel<br>Frequency (MHz) | 9262          | 9400   | 9538   | 1312          | 1413   | 1513   | 4132         | 4182  | 4233  |                     |
| RMC 12.2K                  | 1852.4        | 1880.0 | 1907.6 | 1712.4        | 1732.6 | 1752.6 | 826.4        | 836.4 | 846.6 | -                   |
| HSDPA Subtest-1            | 23.36         | 23.30  | 23.49  | 23.01         | 23.02  | 23.21  | 23.31        | 23.47 | 23.41 | 0                   |
| HSDPA Subtest-2            | 23.25         | 23.27  | 23.46  | 22.99         | 23.00  | 23.20  | 23.27        | 23.45 | 23.33 | 0                   |
| HSDPA Subtest-3            | 22.38         | 22.27  | 22.50  | 22.02         | 22.01  | 22.18  | 22.36        | 23.02 | 22.36 | 0                   |
| HSDPA Subtest-4            | 21.85         | 21.80  | 22.00  | 21.55         | 21.45  | 21.71  | 21.90        | 22.58 | 21.85 | 0.5                 |
| DC-HSDPA Subtest-1         | 21.59         | 21.55  | 21.76  | 21.32         | 21.22  | 21.48  | 21.66        | 22.35 | 21.59 | 0.5                 |
| DC-HSDPA Subtest-2         | 23.22         | 23.25  | 23.42  | 22.94         | 23.00  | 23.16  | 23.30        | 23.41 | 23.36 | 0                   |
| DC-HSDPA Subtest-3         | 22.31         | 22.27  | 22.48  | 22.01         | 22.00  | 22.12  | 22.32        | 23.02 | 22.32 | 0                   |
| DC-HSDPA Subtest-4         | 21.80         | 21.76  | 22.00  | 21.52         | 21.42  | 21.70  | 21.88        | 22.55 | 21.84 | 0.5                 |
| HSUPA Subtest-1            | 21.52         | 21.51  | 21.73  | 21.32         | 21.21  | 21.45  | 21.64        | 22.31 | 21.56 | 0.5                 |
| HSUPA Subtest-2            | 21.78         | 21.73  | 21.97  | 21.54         | 21.58  | 21.83  | 21.80        | 23.28 | 22.02 | 0                   |
| HSUPA Subtest-3            | 20.15         | 20.07  | 20.27  | 19.67         | 19.69  | 19.96  | 20.16        | 21.09 | 20.14 | 2                   |
| HSUPA Subtest-4            | 20.82         | 20.77  | 20.98  | 20.53         | 20.63  | 20.87  | 20.89        | 21.88 | 20.85 | 1                   |
| HSUPA Subtest-5            | 20.33         | 20.28  | 20.50  | 19.91         | 19.93  | 20.24  | 20.47        | 21.44 | 20.35 | 2                   |
| HSUPA Subtest-6            | 22.40         | 22.30  | 22.50  | 22.00         | 21.90  | 22.20  | 22.30        | 23.30 | 22.30 | 0                   |

# SAR Test Report

| LTE Band 2 |           |                 |           |        |        |        |               |      |           |                 |           |        |        |        |               |
|------------|-----------|-----------------|-----------|--------|--------|--------|---------------|------|-----------|-----------------|-----------|--------|--------|--------|---------------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) | BW   | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) |
|            |           | Channel         |           | 18700  | 18900  | 19100  |               |      |           | Channel         |           | 18675  | 18900  | 19125  |               |
|            |           | Frequency (MHz) |           | 1860.0 | 1880.0 | 1900.0 |               |      |           | Frequency (MHz) |           | 1857.5 | 1880.0 | 1902.5 |               |
| 20M        | QPSK      | 1               | 0         | 22.96  | 22.99  | 22.83  | 0             | 15M  | QPSK      | 1               | 0         | 22.93  | 22.97  | 22.76  | 0             |
|            |           | 1               | 50        | 22.87  | 22.90  | 22.72  | 0             |      |           | 1               | 37        | 22.83  | 22.85  | 22.68  | 0             |
|            |           | 1               | 99        | 22.80  | 22.84  | 22.65  | 0             |      |           | 1               | 74        | 22.77  | 22.81  | 22.60  | 0             |
|            |           | 50              | 0         | 21.95  | 21.97  | 21.81  | 1             |      |           | 36              | 0         | 21.92  | 21.92  | 21.71  | 1             |
|            |           | 50              | 25        | 21.82  | 21.86  | 21.70  | 1             |      |           | 36              | 19        | 21.80  | 21.83  | 21.70  | 1             |
|            |           | 50              | 50        | 21.80  | 21.83  | 21.70  | 1             |      |           | 36              | 39        | 21.75  | 21.77  | 21.68  | 1             |
|            |           | 100             | 0         | 21.90  | 21.92  | 21.77  | 1             |      |           | 75              | 0         | 21.89  | 21.82  | 21.75  | 1             |
|            | 16QAM     | 1               | 0         | 21.95  | 21.98  | 21.82  | 1             |      | 16QAM     | 1               | 0         | 21.93  | 21.97  | 21.80  | 1             |
|            |           | 1               | 50        | 21.89  | 21.93  | 21.77  | 1             |      |           | 1               | 37        | 21.83  | 21.83  | 21.72  | 1             |
|            |           | 1               | 99        | 21.74  | 21.77  | 21.63  | 1             |      |           | 1               | 74        | 21.68  | 21.75  | 21.56  | 1             |
|            |           | 50              | 0         | 20.63  | 20.67  | 20.52  | 2             |      |           | 36              | 0         | 20.55  | 20.67  | 20.49  | 2             |
|            |           | 50              | 25        | 20.52  | 20.55  | 20.39  | 2             |      |           | 36              | 19        | 20.43  | 20.47  | 20.39  | 2             |
|            |           | 50              | 50        | 20.48  | 20.52  | 20.40  | 2             |      |           | 36              | 39        | 20.42  | 20.44  | 20.36  | 2             |
|            |           | 100             | 0         | 20.62  | 20.68  | 20.52  | 2             |      |           | 75              | 0         | 20.60  | 20.63  | 20.50  | 2             |
| 10M        | QPSK      | 1               | 0         | 22.94  | 22.89  | 22.73  | 0             | 5M   | QPSK      | 1               | 0         | 22.86  | 22.92  | 22.77  | 0             |
|            |           | 1               | 24        | 22.78  | 22.80  | 22.70  | 0             |      |           | 1               | 12        | 22.81  | 22.85  | 22.66  | 0             |
|            |           | 1               | 49        | 22.78  | 22.81  | 22.61  | 0             |      |           | 1               | 24        | 22.71  | 22.80  | 22.58  | 0             |
|            |           | 25              | 0         | 21.89  | 21.95  | 21.75  | 1             |      |           | 12              | 0         | 21.91  | 21.93  | 21.74  | 1             |
|            |           | 25              | 12        | 21.76  | 21.80  | 21.65  | 1             |      |           | 12              | 6         | 21.76  | 21.86  | 21.60  | 1             |
|            |           | 25              | 25        | 21.73  | 21.79  | 21.69  | 1             |      |           | 12              | 13        | 21.72  | 21.81  | 21.65  | 1             |
|            |           | 50              | 0         | 21.84  | 21.89  | 21.75  | 1             |      |           | 25              | 0         | 21.84  | 21.82  | 21.75  | 1             |
|            | 16QAM     | 1               | 0         | 21.85  | 21.93  | 21.78  | 1             |      | 16QAM     | 1               | 0         | 21.91  | 21.93  | 21.80  | 1             |
|            |           | 1               | 24        | 21.89  | 21.91  | 21.76  | 1             |      |           | 1               | 12        | 21.87  | 21.84  | 21.71  | 1             |
|            |           | 1               | 49        | 21.71  | 21.75  | 21.56  | 1             |      |           | 1               | 24        | 21.70  | 21.72  | 21.56  | 1             |
|            |           | 25              | 0         | 20.56  | 20.64  | 20.47  | 2             |      |           | 12              | 0         | 20.56  | 20.62  | 20.44  | 2             |
|            |           | 25              | 12        | 20.46  | 20.52  | 20.31  | 2             |      |           | 12              | 6         | 20.46  | 20.47  | 20.32  | 2             |
|            |           | 25              | 25        | 20.45  | 20.45  | 20.30  | 2             |      |           | 12              | 13        | 20.43  | 20.42  | 20.31  | 2             |
|            |           | 50              | 0         | 20.57  | 20.62  | 20.50  | 2             |      |           | 25              | 0         | 20.54  | 20.61  | 20.48  | 2             |
| 3M         | QPSK      | 1               | 0         | 22.95  | 22.97  | 22.81  | 0             | 1.4M | QPSK      | 1               | 0         | 22.77  | 22.84  | 22.63  | 0             |
|            |           | 1               | 7         | 22.77  | 22.90  | 22.62  | 0             |      |           | 1               | 2         | 22.70  | 22.71  | 22.64  | 0             |
|            |           | 1               | 14        | 22.80  | 22.80  | 22.62  | 0             |      |           | 1               | 5         | 22.69  | 22.70  | 22.54  | 0             |
|            |           | 8               | 0         | 21.86  | 21.92  | 21.74  | 1             |      |           | 3               | 0         | 22.80  | 22.78  | 22.75  | 0             |
|            |           | 8               | 3         | 21.82  | 21.79  | 21.61  | 1             |      |           | 3               | 1         | 22.64  | 22.66  | 22.67  | 0             |
|            |           | 8               | 7         | 21.79  | 21.80  | 21.69  | 1             |      |           | 3               | 3         | 22.75  | 22.79  | 22.53  | 0             |
|            |           | 15              | 0         | 21.80  | 21.84  | 21.67  | 1             |      |           | 6               | 0         | 21.72  | 21.73  | 21.59  | 1             |
|            | 16QAM     | 1               | 0         | 21.91  | 21.92  | 21.77  | 1             |      | 16QAM     | 1               | 0         | 21.83  | 21.86  | 21.58  | 1             |
|            |           | 1               | 7         | 21.86  | 21.92  | 21.74  | 1             |      |           | 1               | 2         | 21.84  | 21.80  | 21.63  | 1             |
|            |           | 1               | 14        | 21.71  | 21.72  | 21.63  | 1             |      |           | 1               | 5         | 21.65  | 21.60  | 21.49  | 1             |
|            |           | 8               | 0         | 20.55  | 20.61  | 20.45  | 2             |      |           | 3               | 0         | 21.48  | 21.52  | 21.43  | 1             |
|            |           | 8               | 3         | 20.52  | 20.50  | 20.30  | 2             |      |           | 3               | 1         | 21.40  | 21.50  | 21.25  | 1             |
|            |           | 8               | 7         | 20.47  | 20.42  | 20.35  | 2             |      |           | 3               | 3         | 21.35  | 21.29  | 21.28  | 1             |
|            |           | 15              | 0         | 20.54  | 20.66  | 20.48  | 2             |      |           | 6               | 0         | 20.56  | 20.57  | 20.44  | 2             |

# SAR Test Report

| LTE Band 4 |           |                 |           |        |        |        |               |      |           |                 |           |        |        |        |               |
|------------|-----------|-----------------|-----------|--------|--------|--------|---------------|------|-----------|-----------------|-----------|--------|--------|--------|---------------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) | BW   | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) |
|            |           | Channel         |           | 20050  | 20175  | 20300  |               |      |           | Channel         |           | 20025  | 20175  | 20325  |               |
|            |           | Frequency (MHz) |           | 1720.0 | 1732.5 | 1745.0 |               |      |           | Frequency (MHz) |           | 1717.5 | 1732.5 | 1747.5 |               |
| 20M        | QPSK      | 1               | 0         | 22.88  | 22.92  | 22.71  | 0             | 15M  | QPSK      | 1               | 0         | 22.82  | 22.85  | 22.67  | 0             |
|            |           | 1               | 50        | 22.61  | 22.65  | 22.45  | 0             |      |           | 1               | 37        | 22.56  | 22.63  | 22.44  | 0             |
|            |           | 1               | 99        | 22.66  | 22.68  | 22.46  | 0             |      |           | 1               | 74        | 22.66  | 22.67  | 22.40  | 0             |
|            |           | 50              | 0         | 21.68  | 21.71  | 21.52  | 1             |      |           | 36              | 0         | 21.67  | 21.64  | 21.50  | 1             |
|            |           | 50              | 25        | 21.62  | 21.66  | 21.45  | 1             |      |           | 36              | 19        | 21.62  | 21.65  | 21.41  | 1             |
|            |           | 50              | 50        | 21.64  | 21.69  | 21.50  | 1             |      |           | 36              | 39        | 21.56  | 21.65  | 21.50  | 1             |
|            |           | 100             | 0         | 21.70  | 21.76  | 21.57  | 1             |      |           | 75              | 0         | 21.66  | 21.67  | 21.55  | 1             |
|            | 16QAM     | 1               | 0         | 21.90  | 21.95  | 21.74  | 1             |      | 16QAM     | 1               | 0         | 21.86  | 21.93  | 21.73  | 1             |
|            |           | 1               | 50        | 21.84  | 21.88  | 21.67  | 1             |      |           | 1               | 37        | 21.76  | 21.86  | 21.64  | 1             |
|            |           | 1               | 99        | 21.70  | 21.72  | 21.58  | 1             |      |           | 1               | 74        | 21.61  | 21.71  | 21.56  | 1             |
|            |           | 50              | 0         | 20.74  | 20.78  | 20.58  | 2             |      |           | 36              | 0         | 20.70  | 20.70  | 20.49  | 2             |
|            |           | 50              | 25        | 20.69  | 20.75  | 20.54  | 2             |      |           | 36              | 19        | 20.63  | 20.67  | 20.45  | 2             |
|            |           | 50              | 50        | 20.65  | 20.73  | 20.50  | 2             |      |           | 36              | 39        | 20.61  | 20.69  | 20.40  | 2             |
|            |           | 100             | 0         | 20.72  | 20.80  | 20.60  | 2             |      |           | 75              | 0         | 20.72  | 20.70  | 20.56  | 2             |
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) | BW   | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) |
|            |           | Channel         |           | 20000  | 20175  | 20350  |               |      |           | Channel         |           | 19975  | 20175  | 20375  |               |
|            |           | Frequency (MHz) |           | 1715.0 | 1732.5 | 1750.0 |               |      |           | Frequency (MHz) |           | 1712.5 | 1732.5 | 1752.5 |               |
| 10M        | QPSK      | 1               | 0         | 22.86  | 22.85  | 22.64  | 0             | 5M   | QPSK      | 1               | 0         | 22.82  | 22.82  | 22.65  | 0             |
|            |           | 1               | 24        | 22.59  | 22.58  | 22.40  | 0             |      |           | 1               | 12        | 22.56  | 22.64  | 22.43  | 0             |
|            |           | 1               | 49        | 22.63  | 22.60  | 22.38  | 0             |      |           | 1               | 24        | 22.57  | 22.66  | 22.41  | 0             |
|            |           | 25              | 0         | 21.61  | 21.62  | 21.47  | 1             |      |           | 12              | 0         | 21.67  | 21.67  | 21.52  | 1             |
|            |           | 25              | 12        | 21.53  | 21.63  | 21.40  | 1             |      |           | 12              | 6         | 21.52  | 21.56  | 21.36  | 1             |
|            |           | 25              | 25        | 21.59  | 21.66  | 21.46  | 1             |      |           | 12              | 13        | 21.57  | 21.66  | 21.43  | 1             |
|            |           | 50              | 0         | 21.61  | 21.69  | 21.54  | 1             |      |           | 25              | 0         | 21.63  | 21.69  | 21.48  | 1             |
|            | 16QAM     | 1               | 0         | 21.85  | 21.88  | 21.65  | 1             |      | 16QAM     | 1               | 0         | 21.87  | 21.92  | 21.68  | 1             |
|            |           | 1               | 24        | 21.78  | 21.85  | 21.64  | 1             |      |           | 1               | 12        | 21.82  | 21.78  | 21.61  | 1             |
|            |           | 1               | 49        | 21.63  | 21.63  | 21.52  | 1             |      |           | 1               | 24        | 21.70  | 21.68  | 21.51  | 1             |
|            |           | 25              | 0         | 20.71  | 20.75  | 20.51  | 2             |      |           | 12              | 0         | 20.71  | 20.74  | 20.48  | 2             |
|            |           | 25              | 12        | 20.66  | 20.72  | 20.47  | 2             |      |           | 12              | 6         | 20.59  | 20.66  | 20.52  | 2             |
|            |           | 25              | 25        | 20.61  | 20.68  | 20.50  | 2             |      |           | 12              | 13        | 20.64  | 20.70  | 20.45  | 2             |
|            |           | 50              | 0         | 20.63  | 20.75  | 20.60  | 2             |      |           | 25              | 0         | 20.65  | 20.73  | 20.54  | 2             |
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) | BW   | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) |
|            |           | Channel         |           | 19965  | 20175  | 20385  |               |      |           | Channel         |           | 19957  | 20175  | 20393  |               |
|            |           | Frequency (MHz) |           | 1711.5 | 1732.5 | 1753.5 |               |      |           | Frequency (MHz) |           | 1710.7 | 1732.5 | 1754.3 |               |
| 3M         | QPSK      | 1               | 0         | 22.84  | 22.88  | 22.62  | 0             | 1.4M | QPSK      | 1               | 0         | 22.77  | 22.85  | 22.54  | 0             |
|            |           | 1               | 7         | 22.57  | 22.65  | 22.44  | 0             |      |           | 1               | 2         | 22.51  | 22.53  | 22.33  | 0             |
|            |           | 1               | 14        | 22.63  | 22.66  | 22.38  | 0             |      |           | 1               | 5         | 22.54  | 22.57  | 22.31  | 0             |
|            |           | 8               | 0         | 21.60  | 21.63  | 21.47  | 1             |      |           | 3               | 0         | 22.52  | 22.68  | 22.39  | 0             |
|            |           | 8               | 3         | 21.56  | 21.57  | 21.38  | 1             |      |           | 3               | 1         | 22.49  | 22.62  | 22.29  | 0             |
|            |           | 8               | 7         | 21.63  | 21.63  | 21.44  | 1             |      |           | 3               | 3         | 22.61  | 22.51  | 22.31  | 0             |
|            |           | 15              | 0         | 21.70  | 21.69  | 21.50  | 1             |      |           | 6               | 0         | 21.63  | 21.60  | 21.54  | 1             |
|            | 16QAM     | 1               | 0         | 21.86  | 21.85  | 21.69  | 1             |      | 16QAM     | 1               | 0         | 21.69  | 21.82  | 21.64  | 1             |
|            |           | 1               | 7         | 21.84  | 21.78  | 21.62  | 1             |      |           | 1               | 2         | 21.62  | 21.69  | 21.61  | 1             |
|            |           | 1               | 14        | 21.64  | 21.66  | 21.49  | 1             |      |           | 1               | 5         | 21.57  | 21.59  | 21.38  | 1             |
|            |           | 8               | 0         | 20.69  | 20.68  | 20.49  | 2             |      |           | 3               | 0         | 21.65  | 21.76  | 21.46  | 1             |
|            |           | 8               | 3         | 20.61  | 20.70  | 20.50  | 2             |      |           | 3               | 1         | 21.57  | 21.64  | 21.37  | 1             |
|            |           | 8               | 7         | 20.55  | 20.66  | 20.45  | 2             |      |           | 3               | 3         | 21.53  | 21.59  | 21.44  | 1             |
|            |           | 15              | 0         | 20.72  | 20.70  | 20.56  | 2             |      |           | 6               | 0         | 20.65  | 20.73  | 20.47  | 2             |

# SAR Test Report

| LTE Band 5 |           |                 |           |       |       |       |               |      |           |                 |           |       |       |       |               |
|------------|-----------|-----------------|-----------|-------|-------|-------|---------------|------|-----------|-----------------|-----------|-------|-------|-------|---------------|
| BW         | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) | BW   | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) |
|            |           | Channel         |           | 20450 | 20525 | 20600 |               |      |           | Channel         |           | 20425 | 20525 | 20625 |               |
|            |           | Frequency (MHz) |           | 829.0 | 836.5 | 844.0 |               |      |           | Frequency (MHz) |           | 826.5 | 836.5 | 846.5 |               |
| 10M        | QPSK      | 1               | 0         | 22.57 | 22.84 | 22.74 | 0             | 5M   | QPSK      | 1               | 0         | 22.48 | 22.81 | 22.67 | 0             |
|            |           | 1               | 24        | 22.43 | 22.67 | 22.59 | 0             |      |           | 1               | 12        | 22.38 | 22.63 | 22.55 | 0             |
|            |           | 1               | 49        | 22.55 | 22.82 | 22.75 | 0             |      |           | 1               | 24        | 22.48 | 22.77 | 22.65 | 0             |
|            |           | 25              | 0         | 21.52 | 21.80 | 21.74 | 1             |      |           | 12              | 0         | 21.50 | 21.76 | 21.64 | 1             |
|            |           | 25              | 12        | 21.40 | 21.69 | 21.59 | 1             |      |           | 12              | 6         | 21.30 | 21.59 | 21.57 | 1             |
|            |           | 25              | 25        | 21.47 | 21.74 | 21.63 | 1             |      |           | 12              | 13        | 21.41 | 21.71 | 21.61 | 1             |
|            |           | 50              | 0         | 21.50 | 21.76 | 21.66 | 1             |      |           | 25              | 0         | 21.50 | 21.71 | 21.63 | 1             |
|            | 16QAM     | 1               | 0         | 21.66 | 21.93 | 21.83 | 1             |      | 16QAM     | 1               | 0         | 21.60 | 21.83 | 21.73 | 1             |
|            |           | 1               | 24        | 21.56 | 21.83 | 21.73 | 1             |      |           | 1               | 12        | 21.47 | 21.80 | 21.68 | 1             |
|            |           | 1               | 49        | 21.62 | 21.91 | 21.82 | 1             |      |           | 1               | 24        | 21.58 | 21.89 | 21.79 | 1             |
|            |           | 25              | 0         | 20.60 | 20.87 | 20.77 | 2             |      |           | 12              | 0         | 20.56 | 20.84 | 20.72 | 2             |
|            |           | 25              | 12        | 20.58 | 20.84 | 20.76 | 2             |      |           | 12              | 6         | 20.58 | 20.81 | 20.73 | 2             |
|            |           | 25              | 25        | 20.64 | 20.91 | 20.81 | 2             |      |           | 12              | 13        | 20.64 | 20.82 | 20.80 | 2             |
|            |           | 50              | 0         | 20.50 | 20.74 | 20.70 | 2             |      |           | 25              | 0         | 20.43 | 20.65 | 20.67 | 2             |
| BW         | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) | BW   | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) |
|            |           | Channel         |           | 20415 | 20525 | 20635 |               |      |           | Channel         |           | 20407 | 20525 | 20643 |               |
|            |           | Frequency (MHz) |           | 825.5 | 836.5 | 847.5 |               |      |           | Frequency (MHz) |           | 824.7 | 836.5 | 848.3 |               |
| 3M         | QPSK      | 1               | 0         | 22.50 | 22.79 | 22.65 | 0             | 1.4M | QPSK      | 1               | 0         | 22.45 | 22.62 | 22.52 | 0             |
|            |           | 1               | 7         | 22.37 | 22.60 | 22.58 | 0             |      |           | 1               | 2         | 22.40 | 22.56 | 22.46 | 0             |
|            |           | 1               | 14        | 22.48 | 22.75 | 22.68 | 0             |      |           | 1               | 5         | 22.42 | 22.78 | 22.70 | 0             |
|            |           | 8               | 0         | 21.49 | 21.78 | 21.64 | 1             |      |           | 3               | 0         | 22.49 | 22.72 | 22.65 | 0             |
|            |           | 8               | 3         | 21.39 | 21.60 | 21.54 | 1             |      |           | 3               | 1         | 22.31 | 22.64 | 22.52 | 0             |
|            |           | 8               | 7         | 21.41 | 21.72 | 21.62 | 1             |      |           | 3               | 3         | 22.39 | 22.63 | 22.53 | 0             |
|            |           | 15              | 0         | 21.45 | 21.67 | 21.65 | 1             |      |           | 6               | 0         | 21.29 | 21.72 | 21.52 | 1             |
|            | 16QAM     | 1               | 0         | 21.57 | 21.84 | 21.80 | 1             |      | 16QAM     | 1               | 0         | 21.56 | 21.83 | 21.63 | 1             |
|            |           | 1               | 7         | 21.50 | 21.78 | 21.72 | 1             |      |           | 1               | 2         | 21.53 | 21.68 | 21.63 | 1             |
|            |           | 1               | 14        | 21.58 | 21.85 | 21.73 | 1             |      |           | 1               | 5         | 21.50 | 21.71 | 21.73 | 1             |
|            |           | 8               | 0         | 20.52 | 20.78 | 20.73 | 2             |      |           | 3               | 0         | 21.38 | 21.80 | 21.58 | 1             |
|            |           | 8               | 3         | 20.56 | 20.80 | 20.67 | 2             |      |           | 3               | 1         | 21.48 | 21.71 | 21.73 | 1             |
|            |           | 8               | 7         | 20.60 | 20.90 | 20.74 | 2             |      |           | 3               | 3         | 21.45 | 21.83 | 21.67 | 1             |
|            |           | 15              | 0         | 20.42 | 20.73 | 20.61 | 2             |      |           | 6               | 0         | 20.34 | 20.60 | 20.56 | 2             |

# SAR Test Report

| LTE Band 7 |           |                 |           |        |        |        |               |     |           |                 |           |        |        |        |               |
|------------|-----------|-----------------|-----------|--------|--------|--------|---------------|-----|-----------|-----------------|-----------|--------|--------|--------|---------------|
| BW         | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) | BW  | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) |
|            |           | Channel         |           | 20850  | 21100  | 21350  |               |     |           | Channel         |           | 20825  | 21100  | 21375  |               |
|            |           | Frequency (MHz) |           | 2510.0 | 2535.0 | 2560.0 |               |     |           | Frequency (MHz) |           | 2507.5 | 2535.0 | 2562.5 |               |
| 20M        | QPSK      | 1               | 0         | 22.90  | 22.82  | 22.79  | 0             | 15M | QPSK      | 1               | 0         | 22.86  | 22.75  | 22.74  | 0             |
|            |           | 1               | 50        | 22.73  | 22.68  | 22.62  | 0             |     |           | 1               | 37        | 22.67  | 22.61  | 22.60  | 0             |
|            |           | 1               | 99        | 22.74  | 22.66  | 22.63  | 0             |     |           | 1               | 74        | 22.66  | 22.64  | 22.59  | 0             |
|            |           | 50              | 0         | 21.90  | 21.83  | 21.79  | 1             |     |           | 36              | 0         | 21.90  | 21.74  | 21.78  | 1             |
|            |           | 50              | 25        | 21.82  | 21.74  | 21.73  | 1             |     |           | 36              | 19        | 21.75  | 21.71  | 21.70  | 1             |
|            |           | 50              | 50        | 21.78  | 21.72  | 21.67  | 1             |     |           | 36              | 39        | 21.76  | 21.66  | 21.67  | 1             |
|            | 16QAM     | 100             | 0         | 21.91  | 21.86  | 21.76  | 1             |     |           | 75              | 0         | 21.90  | 21.86  | 21.68  | 1             |
|            |           | 1               | 0         | 21.98  | 21.90  | 21.87  | 1             |     | 16QAM     | 1               | 0         | 21.94  | 21.89  | 21.82  | 1             |
|            |           | 1               | 50        | 21.92  | 21.85  | 21.82  | 1             |     |           | 1               | 37        | 21.84  | 21.76  | 21.76  | 1             |
|            |           | 1               | 99        | 21.95  | 21.87  | 21.84  | 1             |     |           | 1               | 74        | 21.89  | 21.87  | 21.84  | 1             |
|            |           | 50              | 0         | 20.93  | 20.87  | 20.84  | 2             |     |           | 36              | 0         | 20.83  | 20.82  | 20.78  | 2             |
|            |           | 50              | 25        | 20.88  | 20.80  | 20.77  | 2             |     |           | 36              | 19        | 20.81  | 20.80  | 20.73  | 2             |
| 10M        | QPSK      | 50              | 50        | 20.90  | 20.88  | 20.80  | 2             | 5M  | QPSK      | 36              | 39        | 20.83  | 20.86  | 20.71  | 2             |
|            |           | 100             | 0         | 20.97  | 20.85  | 20.81  | 2             |     |           | 75              | 0         | 20.92  | 20.79  | 20.72  | 2             |
|            | 16QAM     | 1               | 0         | 22.83  | 22.79  | 22.76  | 0             |     | QPSK      | 1               | 0         | 22.85  | 22.72  | 22.64  | 0             |
|            |           | 1               | 24        | 22.64  | 22.61  | 22.54  | 0             |     |           | 1               | 12        | 22.61  | 22.52  | 22.49  | 0             |
|            |           | 1               | 49        | 22.69  | 22.66  | 22.55  | 0             |     |           | 1               | 24        | 22.60  | 22.52  | 22.43  | 0             |
|            |           | 25              | 0         | 21.90  | 21.81  | 21.76  | 1             |     |           | 12              | 0         | 21.87  | 21.80  | 21.62  | 1             |
|            |           | 25              | 12        | 21.78  | 21.71  | 21.70  | 1             |     |           | 12              | 6         | 21.81  | 21.67  | 21.56  | 1             |
|            |           | 25              | 25        | 21.68  | 21.72  | 21.57  | 1             |     |           | 12              | 13        | 21.72  | 21.68  | 21.56  | 1             |
|            | 16QAM     | 50              | 0         | 21.88  | 21.78  | 21.76  | 1             |     |           | 25              | 0         | 21.85  | 21.79  | 21.67  | 1             |
|            |           | 1               | 0         | 21.98  | 21.83  | 21.84  | 1             |     | 16QAM     | 1               | 0         | 21.87  | 21.83  | 21.77  | 1             |
|            |           | 1               | 24        | 21.83  | 21.75  | 21.79  | 1             |     |           | 1               | 12        | 21.86  | 21.78  | 21.76  | 1             |
|            |           | 1               | 49        | 21.90  | 21.82  | 21.84  | 1             |     |           | 1               | 24        | 21.79  | 21.71  | 21.75  | 1             |
|            |           | 25              | 0         | 20.87  | 20.86  | 20.84  | 2             |     |           | 12              | 0         | 20.73  | 20.79  | 20.74  | 2             |
|            |           | 25              | 12        | 20.88  | 20.74  | 20.77  | 2             |     |           | 12              | 6         | 20.72  | 20.68  | 20.66  | 2             |

| LTE Band 12 |           |                 |           |       |       |       |               |      |           |                 |           |       |       |       |               |
|-------------|-----------|-----------------|-----------|-------|-------|-------|---------------|------|-----------|-----------------|-----------|-------|-------|-------|---------------|
| BW          | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) | BW   | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) |
|             |           | Channel         |           | 23060 | 23095 | 23130 |               |      |           | Channel         |           | 23035 | 23095 | 23155 |               |
|             |           | Frequency (MHz) |           | 704.0 | 707.5 | 711.0 |               |      |           | Frequency (MHz) |           | 701.5 | 707.5 | 713.5 |               |
| 10M         | QPSK      | 1               | 0         | 22.61 | 22.52 | 22.48 | 0             | 5M   | QPSK      | 1               | 0         | 22.52 | 22.44 | 22.45 | 0             |
|             |           | 1               | 24        | 22.51 | 22.45 | 22.40 | 0             |      |           | 1               | 12        | 22.46 | 22.38 | 22.32 | 0             |
|             |           | 1               | 49        | 22.57 | 22.46 | 22.42 | 0             |      |           | 1               | 24        | 22.54 | 22.45 | 22.41 | 0             |
|             |           | 25              | 0         | 21.66 | 21.57 | 21.55 | 1             |      |           | 12              | 0         | 21.56 | 21.47 | 21.52 | 1             |
|             |           | 25              | 12        | 21.53 | 21.41 | 21.40 | 1             |      |           | 12              | 6         | 21.44 | 21.34 | 21.37 | 1             |
|             |           | 25              | 25        | 21.56 | 21.48 | 21.41 | 1             |      |           | 12              | 13        | 21.48 | 21.46 | 21.31 | 1             |
|             | 16QAM     | 50              | 0         | 21.61 | 21.55 | 21.49 | 1             |      |           | 25              | 0         | 21.56 | 21.49 | 21.42 | 1             |
|             |           | 1               | 0         | 21.98 | 21.89 | 21.85 | 1             |      | 16QAM     | 1               | 0         | 21.97 | 21.79 | 21.80 | 1             |
|             |           | 1               | 24        | 21.82 | 21.72 | 21.70 | 1             |      |           | 1               | 12        | 21.76 | 21.71 | 21.61 | 1             |
|             |           | 1               | 49        | 21.87 | 21.78 | 21.74 | 1             |      |           | 1               | 24        | 21.77 | 21.69 | 21.65 | 1             |
|             |           | 25              | 0         | 20.85 | 20.77 | 20.71 | 2             |      |           | 12              | 0         | 20.81 | 20.75 | 20.69 | 2             |
|             |           | 25              | 12        | 20.74 | 20.69 | 20.61 | 2             |      |           | 12              | 6         | 20.72 | 20.61 | 20.56 | 2             |
| 3M          | QPSK      | 25              | 25        | 20.76 | 20.67 | 20.62 | 2             | 1.4M | QPSK      | 12              | 13        | 20.70 | 20.61 | 20.58 | 2             |
|             |           | 50              | 0         | 20.68 | 20.62 | 20.55 | 2             |      |           | 25              | 0         | 20.62 | 20.53 | 20.55 | 2             |
|             | 16QAM     | 1               | 0         | 22.50 | 22.35 | 22.37 | 0             |      | QPSK      | 1               | 0         | 22.48 | 22.42 | 22.39 | 0             |
|             |           | 1               | 7         | 22.45 | 22.39 | 22.31 | 0             |      |           | 1               | 2         | 22.31 | 22.20 | 22.33 | 0             |
|             |           | 1               | 14        | 22.48 | 22.46 | 22.23 | 0             |      |           | 1               | 5         | 22.40 | 22.42 | 22.37 | 0             |
|             |           | 8               | 0         | 21.55 | 21.47 | 21.53 | 1             |      |           | 3               | 0         | 22.48 | 22.37 | 22.47 | 0             |
|             |           | 8               | 3         | 21.51 | 21.40 | 21.25 | 1             |      |           | 3               | 1         | 22.51 | 22.25 | 22.32 | 0             |
|             |           | 8               | 7         | 21.46 | 21.33 | 21.29 | 1             |      |           | 3               | 3         | 22.47 | 22.33 | 22.30 | 0             |
|             | 16QAM     | 15              | 0         | 21.47 | 21.36 | 21.36 | 1             |      |           | 6               | 0         | 21.50 | 21.46 | 21.41 | 1             |
|             |           | 1               | 0         | 21.90 | 21.88 | 21.76 | 1             |      | 16QAM     | 1               | 0         | 21.94 | 21.71 | 21.67 | 1             |
|             |           | 1               | 7         | 21.70 | 21.69 | 21.58 | 1             |      |           | 1               | 2         | 21.62 | 21.71 | 21.62 | 1             |
|             |           | 1               | 14        | 21.70 | 21.74 | 21.59 | 1             |      |           | 1               | 5         | 21.70 | 21.71 | 21.63 | 1             |
|             |           | 8               | 0         | 20.69 | 20.57 | 20.59 | 2             |      |           | 3               | 0         | 21.67 | 21.56 | 21.58 | 1             |
|             |           | 8               | 3         | 20.58 | 20.47 | 20.47 | 2             |      |           | 3               | 1         | 21.63 | 21.54 | 21.47 | 1             |

# SAR Test Report

| LTE Band 13 |           |                 |           |     |       |      |               |    |           |         |                 |       |       |       |               |       |       |       |  |
|-------------|-----------|-----------------|-----------|-----|-------|------|---------------|----|-----------|---------|-----------------|-------|-------|-------|---------------|-------|-------|-------|--|
| BW          | MCS Index | RB Size         | RB Offset | Low | Mid   | High | 3GPP MPR (dB) | BW | MCS Index | RB Size | RB Offset       | Low   | Mid   | High  | 3GPP MPR (dB) |       |       |       |  |
|             |           | Channel         |           |     |       |      |               |    |           | 23230   | Channel         |       |       |       |               | 23205 | 23230 | 23225 |  |
|             |           | Frequency (MHz) |           |     |       |      |               |    |           | 782.0   | Frequency (MHz) |       |       |       |               | 779.5 | 782.0 | 784.5 |  |
| 10M         | QPSK      | 1               | 0         |     | 22.86 |      | 0             | 5M | QPSK      | 1       | 0               | 22.74 | 22.77 | 22.79 | 0             |       |       |       |  |
|             |           | 1               | 24        |     | 22.83 |      | 0             |    |           | 1       | 12              | 22.70 | 22.74 | 22.77 | 0             |       |       |       |  |
|             |           | 1               | 49        |     | 22.79 |      | 0             |    |           | 1       | 24              | 22.68 | 22.72 | 22.74 | 0             |       |       |       |  |
|             |           | 25              | 0         |     | 21.86 |      | 1             |    |           | 12      | 0               | 21.72 | 21.75 | 21.78 | 1             |       |       |       |  |
|             |           | 25              | 12        |     | 21.84 |      | 1             |    |           | 12      | 6               | 21.72 | 21.74 | 21.77 | 1             |       |       |       |  |
|             |           | 25              | 25        |     | 21.76 |      | 1             |    |           | 12      | 13              | 21.60 | 21.64 | 21.66 | 1             |       |       |       |  |
|             |           | 50              | 0         |     | 21.92 |      | 1             |    |           | 25      | 0               | 21.65 | 21.71 | 21.72 | 1             |       |       |       |  |
|             | 16QAM     | 1               | 0         |     | 21.98 |      | 1             |    | 16QAM     | 1       | 0               | 21.92 | 21.95 | 21.97 | 1             |       |       |       |  |
|             |           | 1               | 24        |     | 21.97 |      | 1             |    |           | 1       | 12              | 21.80 | 21.85 | 21.90 | 1             |       |       |       |  |
|             |           | 1               | 49        |     | 21.93 |      | 1             |    |           | 1       | 24              | 21.84 | 21.87 | 21.90 | 1             |       |       |       |  |
|             |           | 25              | 0         |     | 20.96 |      | 2             |    |           | 12      | 0               | 20.82 | 20.84 | 20.86 | 2             |       |       |       |  |
|             |           | 25              | 12        |     | 20.94 |      | 2             |    |           | 12      | 6               | 20.78 | 20.81 | 20.84 | 2             |       |       |       |  |
|             |           | 25              | 25        |     | 20.83 |      | 2             |    |           | 12      | 13              | 20.65 | 20.71 | 20.76 | 2             |       |       |       |  |
|             |           | 50              | 0         |     | 20.95 |      | 2             |    |           | 25      | 0               | 20.66 | 20.72 | 20.74 | 2             |       |       |       |  |

| LTE Band 17 |           |                 |           |       |       |       |               |    |           |                 |           |       |       |       |               |
|-------------|-----------|-----------------|-----------|-------|-------|-------|---------------|----|-----------|-----------------|-----------|-------|-------|-------|---------------|
| BW          | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) | BW | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) |
|             |           | Channel         |           | 23780 | 23790 | 23800 |               |    |           | Channel         |           | 23755 | 23790 | 23825 |               |
|             |           | Frequency (MHz) |           | 709.0 | 710.0 | 711.0 |               |    |           | Frequency (MHz) |           | 706.5 | 710.0 | 713.5 |               |
| 10M         | QPSK      | 1               | 0         | 22.54 | 22.57 | 22.50 | 0             | 5M | QPSK      | 1               | 0         | 22.52 | 22.54 | 22.50 | 0             |
|             |           | 1               | 24        | 22.51 | 22.53 | 22.46 | 0             |    |           | 1               | 12        | 22.45 | 22.50 | 22.39 | 0             |
|             |           | 1               | 49        | 22.40 | 22.41 | 22.32 | 0             |    |           | 1               | 24        | 22.33 | 22.39 | 22.28 | 0             |
|             |           | 25              | 0         | 21.60 | 21.63 | 21.56 | 1             |    |           | 12              | 0         | 21.50 | 21.53 | 21.49 | 1             |
|             |           | 25              | 12        | 21.55 | 21.58 | 21.52 | 1             |    |           | 12              | 6         | 21.48 | 21.55 | 21.45 | 1             |
|             |           | 25              | 25        | 21.52 | 21.56 | 21.50 | 1             |    |           | 12              | 13        | 21.48 | 21.47 | 21.47 | 1             |
|             |           | 50              | 0         | 21.68 | 21.71 | 21.64 | 1             |    |           | 25              | 0         | 21.67 | 21.62 | 21.59 | 1             |
|             | 16QAM     | 1               | 0         | 21.94 | 21.96 | 21.89 | 1             |    | 16QAM     | 1               | 0         | 21.93 | 21.90 | 21.83 | 1             |
|             |           | 1               | 24        | 21.90 | 21.92 | 21.83 | 1             |    |           | 1               | 12        | 21.80 | 21.89 | 21.77 | 1             |
|             |           | 1               | 49        | 21.82 | 21.85 | 21.78 | 1             |    |           | 1               | 24        | 21.73 | 21.75 | 21.68 | 1             |
|             |           | 25              | 0         | 20.74 | 20.78 | 20.70 | 2             |    |           | 12              | 0         | 20.68 | 20.78 | 20.64 | 2             |
|             |           | 25              | 12        | 20.73 | 20.76 | 20.69 | 2             |    |           | 12              | 6         | 20.63 | 20.66 | 20.59 | 2             |
|             |           | 25              | 25        | 20.63 | 20.69 | 20.59 | 2             |    |           | 12              | 13        | 20.61 | 20.61 | 20.54 | 2             |
|             |           | 50              | 0         | 20.80 | 20.82 | 20.72 | 2             |    |           | 25              | 0         | 20.72 | 20.80 | 20.68 | 2             |

# SAR Test Report

| LTE Band 26 |                 |                 |           |         |           |       |                 |      |               |                 |               |       |           |         |               |       |     |
|-------------|-----------------|-----------------|-----------|---------|-----------|-------|-----------------|------|---------------|-----------------|---------------|-------|-----------|---------|---------------|-------|-----|
| BW          | MCS Index       | RB Size         | RB Offset | Low     | Mid       | High  | 3GPP MPR (dB)   | BW   | MCS Index     | RB Size         | RB Offset     | Low   | Mid       | High    | 3GPP MPR (dB) |       |     |
|             |                 | Channel         |           | 26765   | 26865     | 26965 |                 |      |               | Channel         |               | 26740 | 26865     | 26990   |               |       |     |
|             |                 | Frequency (MHz) |           | 821.5   | 831.5     | 841.5 |                 |      |               | Frequency (MHz) |               | 819.0 | 831.5     | 844.0   |               |       |     |
| 15M         | QPSK            | 1               | 0         | 22.55   | 22.52     | 22.49 | 0               | 10M  | QPSK          | 1               | 0             | 22.53 | 22.49     | 22.52   | 0             |       |     |
|             |                 | 1               | 37        | 22.52   | 22.48     | 22.48 | 0               |      |               | 1               | 24            | 22.46 | 22.45     | 22.41   | 0             |       |     |
|             |                 | 1               | 74        | 22.41   | 22.36     | 22.34 | 0               |      |               | 1               | 49            | 22.34 | 22.34     | 22.30   | 0             |       |     |
|             |                 | 36              | 0         | 21.61   | 21.58     | 21.58 | 1               |      |               | 25              | 0             | 21.51 | 21.48     | 21.51   | 1             |       |     |
|             |                 | 36              | 19        | 21.56   | 21.53     | 21.54 | 1               |      |               | 25              | 12            | 21.49 | 21.50     | 21.47   | 1             |       |     |
|             |                 | 36              | 39        | 21.53   | 21.51     | 21.52 | 1               |      |               | 25              | 25            | 21.49 | 21.42     | 21.49   | 1             |       |     |
|             |                 | 75              | 0         | 21.69   | 21.66     | 21.66 | 1               |      |               | 50              | 0             | 21.68 | 21.57     | 21.61   | 1             |       |     |
|             |                 | 16QAM           | 1         | 0       | 21.95     | 21.91 | 21.88           |      |               | 1               | 16QAM         | 1     | 0         | 21.94   | 21.85         | 21.85 | 1   |
|             | 1               |                 | 37        | 21.91   | 21.87     | 21.85 | 1               |      | 1             | 24              |               | 21.81 | 21.84     | 21.79   | 1             |       |     |
|             | 1               |                 | 74        | 21.83   | 21.80     | 21.80 | 1               |      | 1             | 49              |               | 21.74 | 21.70     | 21.70   | 1             |       |     |
|             | 36              |                 | 0         | 20.75   | 20.73     | 20.72 | 2               |      | 25            | 0               |               | 20.69 | 20.73     | 20.66   | 2             |       |     |
|             | 36              |                 | 19        | 20.74   | 20.71     | 20.71 | 2               |      | 25            | 12              |               | 20.64 | 20.61     | 20.61   | 2             |       |     |
|             | 36              |                 | 39        | 20.64   | 20.64     | 20.61 | 2               |      | 25            | 25              |               | 20.62 | 20.56     | 20.56   | 2             |       |     |
|             | 75              |                 | 0         | 20.81   | 20.77     | 20.74 | 2               |      | 50            | 0               |               | 20.73 | 20.75     | 20.70   | 2             |       |     |
|             | 64QAM           |                 | 1         | 0       | 22.55     | 22.52 | 22.49           |      | 2             | 64QAM           |               | 1     | 0         | 22.53   | 22.49         | 22.52 | 2   |
|             |                 | 1               | 37        | 22.52   | 22.48     | 22.48 | 2               |      | 1             |                 | 24            | 22.46 | 22.45     | 22.41   | 2             |       |     |
|             |                 | 1               | 74        | 22.41   | 22.36     | 22.34 | 2               |      | 1             |                 | 49            | 22.34 | 22.34     | 22.30   | 2             |       |     |
|             |                 | 36              | 0         | 21.61   | 21.58     | 21.58 | 3               |      | 25            |                 | 0             | 21.51 | 21.48     | 21.51   | 3             |       |     |
|             |                 | 36              | 19        | 21.56   | 21.53     | 21.54 | 3               |      | 25            |                 | 12            | 21.49 | 21.50     | 21.47   | 3             |       |     |
|             |                 | 36              | 39        | 21.53   | 21.51     | 21.52 | 3               |      | 25            |                 | 25            | 21.49 | 21.42     | 21.49   | 3             |       |     |
|             |                 | 75              | 0         | 21.69   | 21.66     | 21.66 | 3               |      | 50            |                 | 0             | 21.68 | 21.57     | 21.61   | 3             |       |     |
|             |                 | BW              | MCS Index | RB Size | RB Offset | Low   | Mid             |      | High          |                 | 3GPP MPR (dB) | BW    | MCS Index | RB Size | RB Offset     | Low   | Mid |
|             | Channel         |                 |           | 26715   | 26865     | 27015 | Channel         |      | 26705         | 26865           |               |       |           | 27025   |               |       |     |
|             | Frequency (MHz) |                 |           | 816.5   | 831.5     | 846.5 | Frequency (MHz) |      | 815.5         | 831.5           |               |       |           | 847.5   |               |       |     |
|             | 5M              | QPSK            | 1         | 0       | 22.51     | 22.30 | 22.39           |      | 0             | 3M              | QPSK          | 1     | 0         | 22.49   | 22.28         | 22.37 | 0   |
|             |                 |                 | 1         | 12      | 22.46     | 22.34 | 22.33           |      | 0             |                 |               | 1     | 7         | 22.47   | 22.35         | 22.34 | 0   |
|             |                 |                 | 1         | 24      | 22.49     | 22.41 | 22.25           |      | 0             |                 |               | 1     | 14        | 22.46   | 22.42         | 22.23 | 0   |
|             |                 |                 | 12        | 0       | 21.56     | 21.42 | 21.55           |      | 1             |                 |               | 8     | 0         | 21.53   | 21.43         | 21.53 | 1   |
| 12          |                 |                 | 6         | 21.52   | 21.35     | 21.27 | 1               | 8    | 3             |                 |               | 21.49 | 21.36     | 21.25   | 1             |       |     |
| 12          |                 |                 | 13        | 21.47   | 21.28     | 21.31 | 1               | 8    | 7             |                 |               | 21.44 | 21.29     | 21.29   | 1             |       |     |
| 25          |                 |                 | 0         | 21.48   | 21.31     | 21.38 | 1               | 15   | 0             |                 |               | 21.45 | 21.32     | 21.36   | 1             |       |     |
| 16QAM       |                 |                 | 1         | 0       | 21.91     | 21.83 | 21.78           | 1    | 16QAM         |                 |               | 1     | 0         | 21.88   | 21.84         | 21.76 | 1   |
|             |                 | 1               | 12        | 21.71   | 21.64     | 21.60 | 1               | 1    |               |                 | 7             | 21.68 | 21.65     | 21.58   | 1             |       |     |
|             |                 | 1               | 24        | 21.71   | 21.69     | 21.61 | 1               | 1    |               |                 | 14            | 21.68 | 21.70     | 21.59   | 1             |       |     |
|             |                 | 12              | 0         | 20.70   | 20.52     | 20.61 | 2               | 8    |               |                 | 0             | 20.67 | 20.53     | 20.59   | 2             |       |     |
|             |                 | 12              | 6         | 20.59   | 20.42     | 20.49 | 2               | 8    |               |                 | 3             | 20.56 | 20.43     | 20.47   | 2             |       |     |
|             |                 | 12              | 13        | 20.68   | 20.57     | 20.47 | 2               | 8    |               |                 | 7             | 20.65 | 20.58     | 20.45   | 2             |       |     |
|             |                 | 25              | 0         | 20.60   | 20.43     | 20.55 | 2               | 15   |               |                 | 0             | 20.57 | 20.44     | 20.53   | 2             |       |     |
|             |                 | 64QAM           | 1         | 0       | 22.51     | 22.30 | 22.39           | 2    |               |                 | 64QAM         | 1     | 0         | 22.49   | 22.28         | 22.37 | 2   |
| 1           |                 |                 | 12        | 22.46   | 22.34     | 22.33 | 2               | 1    | 7             |                 |               | 22.47 | 22.35     | 22.34   | 2             |       |     |
| 1           |                 |                 | 24        | 22.49   | 22.41     | 22.25 | 2               | 1    | 14            |                 |               | 22.46 | 22.42     | 22.23   | 2             |       |     |
| 12          |                 |                 | 0         | 21.56   | 21.42     | 21.55 | 3               | 8    | 0             |                 |               | 21.53 | 21.43     | 21.53   | 3             |       |     |
| 12          |                 |                 | 6         | 21.52   | 21.35     | 21.27 | 3               | 8    | 3             |                 |               | 21.49 | 21.36     | 21.25   | 3             |       |     |
| 12          |                 |                 | 13        | 21.47   | 21.28     | 21.31 | 3               | 8    | 7             |                 |               | 21.44 | 21.29     | 21.29   | 3             |       |     |
| 25          |                 |                 | 0         | 21.48   | 21.31     | 21.38 | 3               | 15   | 0             |                 |               | 21.45 | 21.32     | 21.36   | 3             |       |     |
| BW          |                 |                 | MCS Index | RB Size | RB Offset | Low   | Mid             | High | 3GPP MPR (dB) |                 |               | BW    | MCS Index | RB Size | RB Offset     | Low   | Mid |
|             |                 | Channel         |           | 26697   | 26865     | 27033 | Channel         |      |               |                 | 26697         |       |           | 26865   | 27033         |       |     |
|             |                 | Frequency (MHz) |           | 814.7   | 831.5     | 848.3 | Frequency (MHz) |      |               |                 | 814.7         |       |           | 831.5   | 848.3         |       |     |
| 1.4M        |                 | QPSK            | 1         | 0       | 22.53     | 22.49 | 22.52           | 0    |               |                 | QPSK          | 1     | 0         | 22.53   | 22.49         | 22.52 | 0   |
|             |                 |                 | 1         | 2       | 22.46     | 22.34 | 22.33           | 0    |               |                 |               | 1     | 2         | 22.46   | 22.34         | 22.33 | 0   |
|             |                 |                 | 1         | 5       | 22.49     | 22.41 | 22.25           | 0    |               |                 |               | 1     | 5         | 22.49   | 22.41         | 22.25 | 0   |
|             |                 |                 | 3         | 0       | 22.49     | 22.28 | 22.37           | 0    |               |                 |               | 3     | 0         | 22.49   | 22.28         | 22.37 | 0   |
|             | 3               |                 | 1         | 22.46   | 22.42     | 22.23 | 0               | 3    |               | 1               |               | 22.46 | 22.42     | 22.23   | 0             |       |     |
|             | 3               |                 | 3         | 22.51   | 22.30     | 22.39 | 0               | 3    |               | 3               |               | 22.51 | 22.30     | 22.39   | 0             |       |     |
|             | 6               |                 | 0         | 21.88   | 21.84     | 21.76 | 1               | 6    |               | 0               |               | 21.88 | 21.84     | 21.76   | 1             |       |     |
|             | 16QAM           |                 | 1         | 0       | 21.68     | 21.65 | 21.58           | 1    |               | 16QAM           |               | 1     | 0         | 21.68   | 21.65         | 21.58 | 1   |
|             |                 | 1               | 2         | 21.68   | 21.70     | 21.59 | 1               | 1    |               |                 | 2             | 21.68 | 21.70     | 21.59   | 1             |       |     |
|             |                 | 1               | 5         | 21.49   | 21.36     | 21.25 | 1               | 1    |               |                 | 5             | 21.49 | 21.36     | 21.25   | 1             |       |     |
|             |                 | 3               | 0         | 21.44   | 21.29     | 21.29 | 1               | 3    |               |                 | 0             | 21.44 | 21.29     | 21.29   | 1             |       |     |
|             |                 | 3               | 1         | 21.45   | 21.32     | 21.36 | 1               | 3    |               |                 | 1             | 21.45 | 21.32     | 21.36   | 1             |       |     |
|             |                 | 3               | 3         | 21.51   | 21.44     | 21.38 | 1               | 3    |               |                 | 3             | 21.51 | 21.44     | 21.38   | 1             |       |     |
|             |                 | 6               | 0         | 20.53   | 20.58     | 20.45 | 2               | 6    |               |                 | 0             | 20.53 | 20.58     | 20.45   | 2             |       |     |
|             |                 | 64QAM           | 1         | 0       | 22.53     | 22.49 | 22.52           | 2    |               |                 | 64QAM         | 1     | 0         | 22.53   | 22.49         | 22.52 | 2   |
|             | 1               |                 | 2         | 22.46   | 22.34     | 22.33 | 2               | 1    |               | 2               |               | 22.46 | 22.34     | 22.33   | 2             |       |     |
|             | 1               |                 | 5         | 22.49   | 22.41     | 22.25 | 2               | 1    |               | 5               |               | 22.49 | 22.41     | 22.25   | 2             |       |     |
|             | 3               |                 | 0         | 22.49   | 22.28     | 22.37 | 2               | 3    |               | 0               |               | 22.49 | 22.28     | 22.37   | 2             |       |     |
|             | 3               |                 | 1         | 22.46   | 22.42     | 22.23 | 2               | 3    |               | 1               |               | 22.46 | 22.42     | 22.23   | 2             |       |     |
|             | 3               |                 | 3         | 22.51   | 22.30     | 22.39 | 2               | 3    |               | 3               |               | 22.51 | 22.30     | 22.39   | 2             |       |     |
|             | 6               |                 | 0         | 21.88   | 21.84     | 21.76 | 3               | 6    |               | 0               |               | 21.88 | 21.84     | 21.76   | 3             |       |     |

# SAR Test Report

| LTE Band 30 |           |                 |           |       |               |    |           |         |                 |       |        |        |               |        |
|-------------|-----------|-----------------|-----------|-------|---------------|----|-----------|---------|-----------------|-------|--------|--------|---------------|--------|
| BW          | MCS Index | RB Size         | RB Offset | Mid   | 3GPP MPR (dB) | BW | MCS Index | RB Size | RB Offset       | Low   | Mid    | High   | 3GPP MPR (dB) |        |
|             |           | Channel         |           |       |               |    |           | 27710   | Channel         |       | 27685  | 27710  |               | 27735  |
|             |           | Frequency (MHz) |           |       |               |    |           | 2310.0  | Frequency (MHz) |       | 2307.5 | 2310.0 |               | 2312.5 |
| 10M         | QPSK      | 1               | 0         | 22.91 | 0             | 5M | QPSK      | 1       | 0               | 22.69 | 22.73  | 22.62  | 0             |        |
|             |           | 1               | 24        | 22.76 | 0             |    |           | 1       | 12              | 22.50 | 22.57  | 22.48  | 0             |        |
|             |           | 1               | 49        | 22.71 | 0             |    |           | 1       | 24              | 22.52 | 22.56  | 22.45  | 0             |        |
|             |           | 25              | 0         | 21.92 | 1             |    |           | 12      | 0               | 21.59 | 21.63  | 21.53  | 1             |        |
|             |           | 25              | 12        | 21.83 | 1             |    |           | 12      | 6               | 21.62 | 21.65  | 21.54  | 1             |        |
|             |           | 25              | 25        | 21.80 | 1             |    |           | 12      | 13              | 21.67 | 21.71  | 21.62  | 1             |        |
|             |           | 50              | 0         | 21.93 | 1             |    |           | 25      | 0               | 21.63 | 21.64  | 21.50  | 1             |        |
|             |           | 16QAM           | 1         | 0     | 21.99         |    |           | 1       | 16QAM           | 1     | 0      | 21.92  | 21.96         | 21.85  |
|             | 1         |                 | 24        | 21.95 | 1             |    | 1         | 12      |                 | 21.77 | 21.80  | 21.64  | 1             |        |
|             | 1         |                 | 49        | 21.93 | 1             |    | 1         | 24      |                 | 21.79 | 21.83  | 21.72  | 1             |        |
|             | 25        |                 | 0         | 20.93 | 2             |    | 12        | 0       |                 | 20.70 | 20.76  | 20.66  | 2             |        |
|             | 25        |                 | 12        | 20.90 | 2             |    | 12        | 6       |                 | 20.80 | 20.84  | 20.73  | 2             |        |
|             | 25        |                 | 25        | 20.85 | 2             |    | 12        | 13      |                 | 20.81 | 20.84  | 20.72  | 2             |        |
|             | 50        | 0               | 20.94     | 2     | 25            |    | 0         | 20.79   | 20.84           | 20.71 | 2      |        |               |        |

| LTE Band 38 |           |                 |           |       |       |       |               |       |           |                 |           |        |       |        |               |
|-------------|-----------|-----------------|-----------|-------|-------|-------|---------------|-------|-----------|-----------------|-----------|--------|-------|--------|---------------|
| BW          | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) | BW    | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   | 3GPP MPR (dB) |
|             |           | Channel         |           | 37850 | 38000 | 38150 |               |       |           | Channel         |           | 37825  | 38000 | 38175  |               |
|             |           | Frequency (MHz) |           | 2580  | 2595  | 2610  |               |       |           | Frequency (MHz) |           | 2577.5 | 2595  | 2612.5 |               |
| 20M         | QPSK      | 1               | 0         | 22.76 | 22.65 | 22.63 | 0             | 15M   | QPSK      | 1               | 0         | 22.71  | 22.59 | 22.63  | 0             |
|             |           | 1               | 50        | 22.62 | 22.50 | 22.49 | 0             |       |           | 1               | 37        | 22.54  | 22.46 | 22.49  | 0             |
|             |           | 1               | 99        | 22.57 | 22.42 | 22.40 | 0             |       |           | 1               | 74        | 22.57  | 22.38 | 22.40  | 0             |
|             |           | 50              | 0         | 21.73 | 21.62 | 21.60 | 1             |       |           | 36              | 0         | 21.67  | 21.62 | 21.53  | 1             |
|             |           | 50              | 25        | 21.67 | 21.55 | 21.52 | 1             |       |           | 36              | 19        | 21.62  | 21.47 | 21.51  | 1             |
|             |           | 50              | 50        | 21.63 | 21.57 | 21.53 | 1             |       |           | 36              | 39        | 21.59  | 21.57 | 21.45  | 1             |
|             |           | 100             | 0         | 21.71 | 21.62 | 21.56 | 1             |       |           | 75              | 0         | 21.63  | 21.57 | 21.56  | 1             |
|             |           | 16QAM           | 1         | 0     | 21.98 | 21.88 | 21.85         |       |           | 1               | 16QAM     | 1      | 0     | 21.88  | 21.86         |
|             | 1         |                 | 50        | 21.86 | 21.75 | 21.72 | 1             |       | 1         | 37              |           | 21.82  | 21.69 | 21.69  | 1             |
|             | 1         |                 | 99        | 21.81 | 21.73 | 21.68 | 1             |       | 1         | 74              |           | 21.77  | 21.71 | 21.68  | 1             |
|             | 50        |                 | 0         | 20.84 | 20.70 | 20.66 | 2             |       | 36        | 0               |           | 20.79  | 20.62 | 20.57  | 2             |
|             | 50        |                 | 25        | 20.81 | 20.70 | 20.68 | 2             |       | 36        | 19              |           | 20.73  | 20.67 | 20.67  | 2             |
| 50          | 50        |                 | 20.79     | 20.72 | 20.68 | 2     | 36            | 39    | 20.69     | 20.62           |           | 20.64  | 2     |        |               |
| 100         | 0         | 20.71           | 20.65     | 20.60 | 2     | 75    | 0             | 20.67 | 20.65     | 20.60           | 2         |        |       |        |               |
| BW          | MCS Index | RB Size         | RB Offset | Low   | Mid   | High  | 3GPP MPR (dB) | BW    | MCS Index | RB Size         | RB Offset | Low    | Mid   | High   | 3GPP MPR (dB) |
|             |           | Channel         |           | 37800 | 38000 | 38200 |               |       |           | Channel         |           | 37775  | 38000 | 38225  |               |
|             |           | Frequency (MHz) |           | 2575  | 2595  | 2615  |               |       |           | Frequency (MHz) |           | 2572.5 | 2595  | 2617.5 |               |
| 10M         | QPSK      | 1               | 0         | 22.71 | 22.56 | 22.59 | 0             | 5M    | QPSK      | 1               | 0         | 22.59  | 22.61 | 22.45  | 0             |
|             |           | 1               | 24        | 22.61 | 22.46 | 22.33 | 0             |       |           | 1               | 12        | 22.45  | 22.44 | 22.45  | 0             |
|             |           | 1               | 49        | 22.41 | 22.27 | 22.21 | 0             |       |           | 1               | 24        | 22.55  | 22.28 | 22.20  | 0             |
|             |           | 25              | 0         | 21.65 | 21.38 | 21.52 | 1             |       |           | 12              | 0         | 21.65  | 21.53 | 21.52  | 1             |
|             |           | 25              | 12        | 21.50 | 21.42 | 21.39 | 1             |       |           | 12              | 6         | 21.54  | 21.45 | 21.46  | 1             |
|             |           | 25              | 25        | 21.46 | 21.41 | 21.33 | 1             |       |           | 12              | 13        | 21.57  | 21.40 | 21.41  | 1             |
|             |           | 50              | 0         | 21.49 | 21.48 | 21.38 | 1             |       |           | 25              | 0         | 21.60  | 21.49 | 21.30  | 1             |
|             |           | 16QAM           | 1         | 0     | 21.91 | 21.76 | 21.75         |       |           | 1               | 16QAM     | 1      | 0     | 21.97  | 21.73         |
|             | 1         |                 | 24        | 21.69 | 21.57 | 21.55 | 1             |       | 1         | 12              |           | 21.74  | 21.57 | 21.68  | 1             |
|             | 1         |                 | 49        | 21.68 | 21.61 | 21.52 | 1             |       | 1         | 24              |           | 21.64  | 21.61 | 21.51  | 1             |
|             | 25        |                 | 0         | 20.77 | 20.55 | 20.62 | 2             |       | 12        | 0               |           | 20.73  | 20.49 | 20.56  | 2             |
|             | 25        |                 | 12        | 20.63 | 20.58 | 20.55 | 2             |       | 12        | 6               |           | 20.66  | 20.54 | 20.59  | 2             |
|             | 25        |                 | 25        | 20.71 | 20.60 | 20.61 | 2             |       | 12        | 13              |           | 20.66  | 20.49 | 20.47  | 2             |
|             | 50        |                 | 0         | 20.56 | 20.52 | 20.48 | 2             |       | 25        | 0               |           | 20.55  | 20.56 | 20.57  | 2             |

# SAR Test Report

| LTE Band 41 |           |                 |           |        |        |        |        |        |               |     |           |                 |           |        |        |        |        |        |               |
|-------------|-----------|-----------------|-----------|--------|--------|--------|--------|--------|---------------|-----|-----------|-----------------|-----------|--------|--------|--------|--------|--------|---------------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | Mid    | Mid    | High   | 3GPP MPR (dB) | BW  | MCS Index | RB Size         | RB Offset | Low    | Mid    | Mid    | Mid    | High   | 3GPP MPR (dB) |
|             |           | Channel         |           | 39750  | 40185  | 40620  | 41055  | 41490  |               |     |           | Channel         |           | 39725  | 40173  | 40620  | 41068  | 41515  |               |
|             |           | Frequency (MHz) |           | 2506.0 | 2549.5 | 2593.0 | 2636.5 | 2680.0 |               |     |           | Frequency (MHz) |           | 2503.5 | 2548.3 | 2593.0 | 2637.8 | 2682.5 |               |
| 20M         | QPSK      | 1               | 0         | 22.53  | 22.67  | 22.48  | 22.56  | 22.43  | 0             | 15M | QPSK      | 1               | 0         | 22.43  | 22.60  | 22.39  | 22.51  | 22.34  | 0             |
|             |           | 1               | 50        | 22.47  | 22.60  | 22.43  | 22.50  | 22.39  | 0             |     |           | 1               | 37        | 22.45  | 22.56  | 22.35  | 22.48  | 22.37  | 0             |
|             |           | 1               | 99        | 22.44  | 22.59  | 22.40  | 22.49  | 22.37  | 0             |     |           | 1               | 74        | 22.43  | 22.55  | 22.39  | 22.48  | 22.27  | 0             |
|             |           | 50              | 0         | 21.50  | 21.63  | 21.44  | 21.51  | 21.40  | 1             |     |           | 36              | 0         | 21.43  | 21.62  | 21.35  | 21.43  | 21.31  | 1             |
|             |           | 50              | 25        | 21.46  | 21.59  | 21.42  | 21.48  | 21.36  | 1             |     |           | 36              | 19        | 21.39  | 21.52  | 21.36  | 21.39  | 21.35  | 1             |
|             |           | 50              | 50        | 21.42  | 21.56  | 21.40  | 21.43  | 21.33  | 1             |     |           | 36              | 39        | 21.34  | 21.52  | 21.33  | 21.43  | 21.31  | 1             |
|             |           | 100             | 0         | 21.47  | 21.60  | 21.41  | 21.46  | 21.40  | 1             |     |           | 75              | 0         | 21.39  | 21.55  | 21.31  | 21.39  | 21.35  | 1             |
|             | 16QAM     | 1               | 0         | 21.69  | 21.83  | 21.63  | 21.72  | 21.58  | 1             |     | 16QAM     | 1               | 0         | 21.45  | 21.57  | 21.47  | 21.54  | 21.39  | 1             |
|             |           | 1               | 50        | 21.63  | 21.78  | 21.60  | 21.66  | 21.54  | 1             |     |           | 1               | 37        | 21.37  | 21.60  | 21.33  | 21.48  | 21.33  | 1             |
|             |           | 1               | 99        | 21.61  | 21.75  | 21.56  | 21.64  | 21.52  | 1             |     |           | 1               | 74        | 21.37  | 21.55  | 21.35  | 21.39  | 21.31  | 1             |
|             |           | 50              | 0         | 20.60  | 20.75  | 20.58  | 20.67  | 20.53  | 2             |     |           | 36              | 0         | 20.45  | 20.63  | 20.34  | 20.41  | 20.35  | 2             |
|             |           | 50              | 25        | 20.58  | 20.72  | 20.53  | 20.61  | 20.50  | 2             |     |           | 36              | 19        | 20.36  | 20.52  | 20.39  | 20.40  | 20.30  | 2             |
|             |           | 50              | 50        | 20.57  | 20.70  | 20.52  | 20.60  | 20.49  | 2             |     |           | 36              | 39        | 20.37  | 20.53  | 20.30  | 20.43  | 20.33  | 2             |
|             |           | 100             | 0         | 20.58  | 20.69  | 20.51  | 20.55  | 20.48  | 2             |     |           | 75              | 0         | 20.47  | 20.60  | 20.32  | 20.43  | 20.36  | 2             |
| 10M         | QPSK      | 1               | 0         | 22.44  | 22.58  | 22.37  | 22.49  | 22.24  | 0             | 5M  | QPSK      | 1               | 0         | 22.50  | 22.60  | 22.36  | 22.42  | 22.31  | 0             |
|             |           | 1               | 24        | 22.29  | 22.59  | 22.37  | 22.36  | 22.27  | 0             |     |           | 1               | 12        | 22.29  | 22.50  | 22.34  | 22.33  | 22.20  | 0             |
|             |           | 1               | 49        | 22.25  | 22.43  | 22.32  | 22.46  | 22.22  | 0             |     |           | 1               | 24        | 22.41  | 22.54  | 22.33  | 22.30  | 22.24  | 0             |
|             |           | 25              | 0         | 21.43  | 21.55  | 21.25  | 21.41  | 21.23  | 1             |     |           | 12              | 0         | 21.43  | 21.55  | 21.25  | 21.44  | 21.34  | 1             |
|             |           | 25              | 12        | 21.29  | 21.45  | 21.34  | 21.34  | 21.29  | 1             |     |           | 12              | 6         | 21.31  | 21.49  | 21.28  | 21.36  | 21.24  | 1             |
|             |           | 25              | 25        | 21.32  | 21.42  | 21.28  | 21.26  | 21.16  | 1             |     |           | 12              | 13        | 21.31  | 21.44  | 21.26  | 21.38  | 21.23  | 1             |
|             |           | 50              | 0         | 21.41  | 21.49  | 21.34  | 21.43  | 21.32  | 1             |     |           | 25              | 0         | 21.33  | 21.53  | 21.25  | 21.31  | 21.30  | 1             |
|             | 16QAM     | 1               | 0         | 21.38  | 21.61  | 21.29  | 21.49  | 21.32  | 1             |     | 16QAM     | 1               | 0         | 21.49  | 21.63  | 21.37  | 21.49  | 21.26  | 1             |
|             |           | 1               | 24        | 21.34  | 21.53  | 21.36  | 21.37  | 21.28  | 1             |     |           | 1               | 12        | 21.34  | 21.58  | 21.35  | 21.38  | 21.29  | 1             |
|             |           | 1               | 49        | 21.32  | 21.41  | 21.37  | 21.37  | 21.27  | 1             |     |           | 1               | 24        | 21.38  | 21.58  | 21.27  | 21.37  | 21.26  | 1             |
|             |           | 25              | 0         | 20.39  | 20.50  | 20.34  | 20.39  | 20.25  | 2             |     |           | 12              | 0         | 20.46  | 20.51  | 20.26  | 20.43  | 20.31  | 2             |
|             |           | 25              | 12        | 20.38  | 20.46  | 20.40  | 20.32  | 20.33  | 2             |     |           | 12              | 6         | 20.29  | 20.43  | 20.37  | 20.43  | 20.22  | 2             |
|             |           | 25              | 25        | 20.40  | 20.40  | 20.36  | 20.30  | 20.20  | 2             |     |           | 12              | 13        | 20.24  | 20.46  | 20.27  | 20.35  | 20.22  | 2             |
|             |           | 50              | 0         | 20.42  | 20.40  | 20.35  | 20.42  | 20.33  | 2             |     |           | 25              | 0         | 20.41  | 20.54  | 20.31  | 20.38  | 20.31  | 2             |

# SAR Test Report

| LTE Band 66 |           |                 |           |        |        |        |               |      |           |                 |           |        |        |        |               |
|-------------|-----------|-----------------|-----------|--------|--------|--------|---------------|------|-----------|-----------------|-----------|--------|--------|--------|---------------|
| BW          | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) | BW   | MCS Index | RB Size         | RB Offset | Low    | Mid    | High   | 3GPP MPR (dB) |
|             |           | Channel         |           | 132072 | 132322 | 132572 |               |      |           | Channel         |           | 132047 | 132322 | 132597 |               |
|             |           | Frequency (MHz) |           | 1720.0 | 1745.0 | 1770.0 |               |      |           | Frequency (MHz) |           | 1717.5 | 1745.0 | 1772.5 |               |
| 20M         | QPSK      | 1               | 0         | 22.70  | 22.72  | 22.96  | 0             | 15M  | QPSK      | 1               | 0         | 22.61  | 22.65  | 22.89  | 0             |
|             |           | 1               | 50        | 22.36  | 22.41  | 22.63  | 0             |      |           | 1               | 37        | 22.36  | 22.41  | 22.56  | 0             |
|             |           | 1               | 99        | 22.58  | 22.62  | 22.86  | 0             |      |           | 1               | 74        | 22.55  | 22.61  | 22.77  | 0             |
|             |           | 50              | 0         | 21.51  | 21.52  | 21.77  | 1             |      |           | 36              | 0         | 21.48  | 21.43  | 21.75  | 1             |
|             |           | 50              | 25        | 21.43  | 21.47  | 21.69  | 1             |      |           | 36              | 19        | 21.41  | 21.41  | 21.66  | 1             |
|             |           | 50              | 50        | 21.44  | 21.49  | 21.73  | 1             |      |           | 36              | 39        | 21.36  | 21.47  | 21.70  | 1             |
|             |           | 100             | 0         | 21.62  | 21.66  | 21.93  | 1             |      |           | 75              | 0         | 21.58  | 21.66  | 21.91  | 1             |
|             | 16QAM     | 1               | 0         | 21.72  | 21.74  | 21.98  | 1             |      | 16QAM     | 1               | 0         | 21.62  | 21.68  | 21.93  | 1             |
|             |           | 1               | 50        | 21.50  | 21.51  | 21.75  | 1             |      |           | 1               | 37        | 21.44  | 21.47  | 21.72  | 1             |
|             |           | 1               | 99        | 21.71  | 21.72  | 21.97  | 1             |      |           | 1               | 74        | 21.68  | 21.63  | 21.89  | 1             |
|             |           | 50              | 0         | 20.41  | 20.46  | 20.70  | 2             |      |           | 36              | 0         | 20.40  | 20.39  | 20.60  | 2             |
|             |           | 50              | 25        | 20.40  | 20.43  | 20.63  | 2             |      |           | 36              | 19        | 20.36  | 20.42  | 20.56  | 2             |
|             |           | 50              | 50        | 20.41  | 20.42  | 20.67  | 2             |      |           | 36              | 39        | 20.38  | 20.41  | 20.63  | 2             |
|             |           | 100             | 0         | 20.66  | 20.70  | 20.95  | 2             |      |           | 75              | 0         | 20.62  | 20.66  | 20.85  | 2             |
| 10M         | QPSK      | 1               | 0         | 22.50  | 22.65  | 22.77  | 0             | 5M   | QPSK      | 1               | 0         | 22.60  | 22.48  | 22.77  | 0             |
|             |           | 1               | 24        | 22.23  | 22.29  | 22.59  | 0             |      |           | 1               | 12        | 22.23  | 22.28  | 22.49  | 0             |
|             |           | 1               | 49        | 22.51  | 22.58  | 22.80  | 0             |      |           | 1               | 24        | 22.52  | 22.41  | 22.66  | 0             |
|             |           | 25              | 0         | 21.38  | 21.35  | 21.62  | 1             |      |           | 12              | 0         | 21.36  | 21.49  | 21.52  | 1             |
|             |           | 25              | 12        | 21.36  | 21.33  | 21.63  | 1             |      |           | 12              | 6         | 21.35  | 21.29  | 21.49  | 1             |
|             |           | 25              | 25        | 21.41  | 21.32  | 21.49  | 1             |      |           | 12              | 13        | 21.27  | 21.38  | 21.50  | 1             |
|             |           | 50              | 0         | 21.44  | 21.60  | 21.85  | 1             |      |           | 25              | 0         | 21.43  | 21.52  | 21.74  | 1             |
|             | 16QAM     | 1               | 0         | 21.66  | 21.58  | 21.80  | 1             |      | 16QAM     | 1               | 0         | 21.55  | 21.60  | 21.87  | 1             |
|             |           | 1               | 24        | 21.41  | 21.48  | 21.62  | 1             |      |           | 1               | 12        | 21.36  | 21.32  | 21.61  | 1             |
|             |           | 1               | 49        | 21.62  | 21.59  | 21.88  | 1             |      |           | 1               | 24        | 21.51  | 21.57  | 21.80  | 1             |
|             |           | 25              | 0         | 20.25  | 20.39  | 20.61  | 2             |      |           | 12              | 0         | 20.22  | 20.29  | 20.60  | 2             |
|             |           | 25              | 12        | 20.28  | 20.28  | 20.44  | 2             |      |           | 12              | 6         | 20.34  | 20.28  | 20.52  | 2             |
|             |           | 25              | 25        | 20.18  | 20.31  | 20.60  | 2             |      |           | 12              | 13        | 20.29  | 20.34  | 20.55  | 2             |
|             |           | 50              | 0         | 20.56  | 20.50  | 20.89  | 2             |      |           | 25              | 0         | 20.66  | 20.52  | 20.78  | 2             |
| 3M          | QPSK      | 1               | 0         | 22.58  | 22.71  | 22.79  | 0             | 1.4M | QPSK      | 1               | 0         | 22.64  | 22.57  | 22.85  | 0             |
|             |           | 1               | 7         | 22.27  | 22.29  | 22.51  | 0             |      |           | 1               | 2         | 22.15  | 22.25  | 22.62  | 0             |
|             |           | 1               | 14        | 22.46  | 22.49  | 22.72  | 0             |      |           | 1               | 5         | 22.39  | 22.52  | 22.80  | 0             |
|             |           | 8               | 0         | 21.41  | 21.39  | 21.67  | 1             |      |           | 3               | 0         | 22.38  | 22.49  | 22.71  | 0             |
|             |           | 8               | 3         | 21.23  | 21.32  | 21.60  | 1             |      |           | 3               | 1         | 22.31  | 22.41  | 22.62  | 0             |
|             |           | 8               | 7         | 21.21  | 21.38  | 21.73  | 1             |      |           | 3               | 3         | 22.26  | 22.37  | 22.59  | 0             |
|             |           | 15              | 0         | 21.41  | 21.53  | 21.77  | 1             |      |           | 6               | 0         | 21.56  | 21.56  | 21.71  | 1             |
|             | 16QAM     | 1               | 0         | 21.52  | 21.64  | 21.89  | 1             |      | 16QAM     | 1               | 0         | 21.53  | 21.70  | 21.95  | 1             |
|             |           | 1               | 7         | 21.35  | 21.41  | 21.60  | 1             |      |           | 1               | 2         | 21.38  | 21.34  | 21.65  | 1             |
|             |           | 1               | 14        | 21.65  | 21.65  | 21.91  | 1             |      |           | 1               | 5         | 21.55  | 21.51  | 21.83  | 1             |
|             |           | 8               | 0         | 20.20  | 20.30  | 20.58  | 2             |      |           | 3               | 0         | 21.24  | 21.36  | 21.56  | 1             |
|             |           | 8               | 3         | 20.27  | 20.30  | 20.45  | 2             |      |           | 3               | 1         | 21.27  | 21.39  | 21.55  | 1             |
|             |           | 8               | 7         | 20.35  | 20.29  | 20.56  | 2             |      |           | 3               | 3         | 21.27  | 21.22  | 21.59  | 1             |
|             |           | 15              | 0         | 20.52  | 20.61  | 20.80  | 2             |      |           | 6               | 0         | 20.65  | 20.60  | 20.84  | 2             |

### 5.7 SAR Testing Results

#### 5.7.1 SAR Test Reduction Considerations

##### <KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1)  $\leq 0.8$  W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\leq 100$  MHz
- (2)  $\leq 0.6$  W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3)  $\leq 0.4$  W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is  $\geq 200$  MHz

When SAR is not measured at the maximum power level allowed for production units, the measured SAR will be scaled to the maximum tune-up tolerance limit to determine compliance. The scaling factor for the tune-up power is defined as maximum tune-up limit (mW) / measured conducted power (mW). The reported SAR would be calculated by measured SAR x tune-up power scaling factor.

The SAR has been measured with highest transmission duty factor supported by the test mode tools for WLAN and/or Bluetooth. When the transmission duty factor could not achieve 100%, the reported SAR will be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up power. The scaling factor for the duty factor is defined as 100% / transmission duty cycle (%). The reported SAR would be calculated by measured SAR x tune-up power scaling factor x duty cycle scaling factor.

##### <KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is  $\leq 1/4$  dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is  $\leq 1.2$  W/kg, SAR measurement is not required for the secondary mode.

### <KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

#### (1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is  $> 1.45$  W/kg, SAR is required for all three RB offset configurations for that required test channel.

#### (2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.

#### (3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is  $> 1/2$  dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is  $> 1.45$  W/kg.

#### (4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is  $> 1/2$  dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is  $> 1.45$  W/kg.

# SAR Test Report

## 4.7.2 SAR Results for Body Exposure Condition (Test Separation Distance is 0 mm)

| Plot No. | Band     | Mode     | Test Position | Ch.  | Sample | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|----------|----------|---------------|------|--------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | WCDMA II | RMC12.2K | Bottom        | 9538 | 1      | 23.50                    | 23.49                          | 1.00           | 0                | 0                      | 0.00                 |
|          | WCDMA II | RMC12.2K | Bottom        | 9262 | 1      | 23.50                    | 23.36                          | 1.03           | 0                | 0                      | 0.00                 |
|          | WCDMA II | RMC12.2K | Bottom        | 9400 | 1      | 23.50                    | 23.30                          | 1.05           | 0                | 0                      | 0.00                 |
|          | WCDMA II | RMC12.2K | Bottom        | 9538 | 2      | 23.50                    | 23.49                          | 1.00           | 0                | 0                      | 0.00                 |
|          | WCDMA II | RMC12.2K | Bottom        | 9538 | 3      | 23.50                    | 23.49                          | 1.00           | 0                | 0                      | 0.00                 |
|          | WCDMA IV | RMC12.2K | Bottom        | 1513 | 1      | 23.50                    | 23.21                          | 1.07           | 0                | 0                      | 0.00                 |
|          | WCDMA IV | RMC12.2K | Bottom        | 1312 | 1      | 23.50                    | 23.01                          | 1.12           | 0                | 0                      | 0.00                 |
|          | WCDMA IV | RMC12.2K | Bottom        | 1413 | 1      | 23.50                    | 23.02                          | 1.12           | 0                | 0                      | 0.00                 |
|          | WCDMA IV | RMC12.2K | Bottom        | 1513 | 2      | 23.50                    | 23.21                          | 1.07           | 0                | 0                      | 0.00                 |
|          | WCDMA IV | RMC12.2K | Bottom        | 1513 | 3      | 23.50                    | 23.21                          | 1.07           | 0                | 0                      | 0.00                 |
|          | WCDMA V  | RMC12.2K | Bottom        | 4182 | 1      | 23.50                    | 23.47                          | 1.01           | 0                | 0                      | 0.00                 |
|          | WCDMA V  | RMC12.2K | Bottom        | 4132 | 1      | 23.50                    | 23.31                          | 1.04           | 0                | 0                      | 0.00                 |
|          | WCDMA V  | RMC12.2K | Bottom        | 4233 | 1      | 23.50                    | 23.41                          | 1.02           | 0                | 0                      | 0.00                 |
|          | WCDMA V  | RMC12.2K | Bottom        | 4182 | 2      | 23.50                    | 23.47                          | 1.01           | 0                | 0                      | 0.00                 |
|          | WCDMA V  | RMC12.2K | Bottom        | 4182 | 3      | 23.50                    | 23.47                          | 1.01           | 0                | 0                      | 0.00                 |

| Plot No. | Band   | Mode    | Test Position | Ch.   | RB# | RB Offset | Sample | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|--------|---------|---------------|-------|-----|-----------|--------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 2  | QPSK20M | Bottom        | 18900 | 1   | 0         | 1      | 23.00                    | 22.99                          | 1.00           | 0                | 0                      | 0.00                 |
|          | LTE 2  | QPSK20M | Bottom        | 18900 | 50  | 0         | 1      | 22.00                    | 21.97                          | 1.01           | 0                | 0                      | 0.00                 |
|          | LTE 2  | QPSK20M | Bottom        | 18700 | 1   | 0         | 1      | 23.00                    | 22.96                          | 1.01           | 0                | 0                      | 0.00                 |
|          | LTE 2  | QPSK20M | Bottom        | 19100 | 1   | 0         | 1      | 23.00                    | 22.83                          | 1.04           | 0                | 0                      | 0.00                 |
|          | LTE 2  | QPSK20M | Bottom        | 18900 | 1   | 0         | 2      | 23.00                    | 22.99                          | 1.00           | 0                | 0                      | 0.00                 |
|          | LTE 2  | QPSK20M | Bottom        | 18900 | 1   | 0         | 3      | 23.00                    | 22.99                          | 1.00           | 0                | 0                      | 0.00                 |
|          | LTE 4  | QPSK20M | Bottom        | 20175 | 1   | 0         | 1      | 23.00                    | 22.92                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 4  | QPSK20M | Bottom        | 20175 | 50  | 0         | 1      | 22.00                    | 21.71                          | 1.07           | 0                | 0                      | 0.00                 |
|          | LTE 4  | QPSK20M | Bottom        | 20050 | 1   | 0         | 1      | 23.00                    | 22.88                          | 1.03           | 0                | 0                      | 0.00                 |
|          | LTE 4  | QPSK20M | Bottom        | 20300 | 1   | 0         | 1      | 23.00                    | 22.71                          | 1.07           | 0                | 0                      | 0.00                 |
|          | LTE 4  | QPSK20M | Bottom        | 20175 | 1   | 0         | 2      | 23.00                    | 22.92                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 4  | QPSK20M | Bottom        | 20175 | 1   | 0         | 3      | 23.00                    | 22.92                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 5  | QPSK10M | Bottom        | 20525 | 1   | 0         | 1      | 23.00                    | 22.84                          | 1.04           | 0                | 0                      | 0.00                 |
|          | LTE 5  | QPSK10M | Bottom        | 20525 | 25  | 0         | 1      | 22.00                    | 21.80                          | 1.05           | 0                | 0                      | 0.00                 |
|          | LTE 5  | QPSK10M | Bottom        | 20450 | 1   | 0         | 1      | 23.00                    | 22.57                          | 1.10           | 0                | 0                      | 0.00                 |
|          | LTE 5  | QPSK10M | Bottom        | 20600 | 1   | 49        | 1      | 23.00                    | 22.75                          | 1.06           | 0                | 0                      | 0.00                 |
|          | LTE 5  | QPSK10M | Bottom        | 20525 | 1   | 0         | 2      | 23.00                    | 22.84                          | 1.04           | 0                | 0                      | 0.00                 |
|          | LTE 5  | QPSK10M | Bottom        | 20525 | 1   | 0         | 3      | 23.00                    | 22.84                          | 1.04           | 0                | 0                      | 0.00                 |
|          | LTE 7  | QPSK20M | Bottom        | 20850 | 1   | 0         | 1      | 23.00                    | 22.90                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 7  | QPSK20M | Bottom        | 20850 | 50  | 0         | 1      | 22.00                    | 21.90                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 7  | QPSK20M | Bottom        | 21100 | 1   | 0         | 1      | 23.00                    | 22.82                          | 1.04           | 0                | 0                      | 0.00                 |
|          | LTE 7  | QPSK20M | Bottom        | 21350 | 1   | 0         | 1      | 23.00                    | 22.79                          | 1.05           | 0                | 0                      | 0.00                 |
|          | LTE 7  | QPSK20M | Bottom        | 20850 | 1   | 0         | 2      | 23.00                    | 22.90                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 7  | QPSK20M | Bottom        | 20850 | 1   | 0         | 3      | 23.00                    | 22.90                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 12 | QPSK10M | Bottom        | 23060 | 1   | 0         | 1      | 23.00                    | 22.61                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 12 | QPSK10M | Bottom        | 23060 | 25  | 0         | 1      | 22.00                    | 21.66                          | 1.08           | 0                | 0                      | 0.00                 |
|          | LTE 12 | QPSK10M | Bottom        | 23095 | 1   | 0         | 1      | 23.00                    | 22.52                          | 1.12           | 0                | 0                      | 0.00                 |
|          | LTE 12 | QPSK10M | Bottom        | 23130 | 1   | 0         | 1      | 23.00                    | 22.48                          | 1.13           | 0                | 0                      | 0.00                 |
|          | LTE 12 | QPSK10M | Bottom        | 23060 | 1   | 0         | 2      | 23.00                    | 22.61                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 12 | QPSK10M | Bottom        | 23060 | 1   | 0         | 3      | 23.00                    | 22.61                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 13 | QPSK10M | Bottom        | 23230 | 1   | 0         | 1      | 23.00                    | 22.86                          | 1.03           | 0                | 0                      | 0.00                 |
|          | LTE 13 | QPSK10M | Bottom        | 23230 | 25  | 0         | 1      | 22.00                    | 21.86                          | 1.03           | 0                | 0                      | 0.00                 |
|          | LTE 13 | QPSK10M | Bottom        | 23230 | 1   | 0         | 2      | 23.00                    | 22.86                          | 1.03           | 0                | 0                      | 0.00                 |
|          | LTE 13 | QPSK10M | Bottom        | 23230 | 1   | 0         | 3      | 23.00                    | 22.86                          | 1.03           | 0                | 0                      | 0.00                 |
|          | LTE 17 | QPSK10M | Bottom        | 23790 | 1   | 0         | 1      | 23.00                    | 22.57                          | 1.10           | 0                | 0                      | 0.00                 |
|          | LTE 17 | QPSK10M | Bottom        | 23790 | 25  | 0         | 1      | 22.00                    | 21.63                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 17 | QPSK10M | Bottom        | 23780 | 1   | 0         | 1      | 23.00                    | 22.54                          | 1.11           | 0                | 0                      | 0.00                 |
|          | LTE 17 | QPSK10M | Bottom        | 23800 | 1   | 0         | 1      | 23.00                    | 22.50                          | 1.12           | 0                | 0                      | 0.00                 |
|          | LTE 17 | QPSK10M | Bottom        | 23790 | 1   | 0         | 2      | 23.00                    | 22.57                          | 1.10           | 0                | 0                      | 0.00                 |
|          | LTE 17 | QPSK10M | Bottom        | 23790 | 1   | 0         | 3      | 23.00                    | 22.57                          | 1.10           | 0                | 0                      | 0.00                 |

# SAR Test Report

| Plot No. | Band   | Mode    | Test Position | Ch.    | RB# | RB Offset | Sample | Max. Tune-up Power (dBm) | Measured Conducted Power (dBm) | Scaling Factor | Power Drift (dB) | Measured SAR-1g (W/kg) | Scaled SAR-1g (W/kg) |
|----------|--------|---------|---------------|--------|-----|-----------|--------|--------------------------|--------------------------------|----------------|------------------|------------------------|----------------------|
|          | LTE 26 | QPSK15M | Bottom        | 26765  | 1   | 0         | 1      | 23.00                    | 22.55                          | 1.11           | 0                | 0                      | 0.00                 |
|          | LTE 26 | QPSK15M | Bottom        | 26765  | 36  | 0         | 1      | 22.00                    | 21.61                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 26 | QPSK15M | Bottom        | 26865  | 1   | 0         | 1      | 23.00                    | 22.52                          | 1.12           | 0                | 0                      | 0.00                 |
|          | LTE 26 | QPSK15M | Bottom        | 26965  | 1   | 0         | 1      | 23.00                    | 22.49                          | 1.12           | 0                | 0                      | 0.00                 |
|          | LTE 26 | QPSK15M | Bottom        | 26765  | 1   | 0         | 2      | 23.00                    | 22.55                          | 1.11           | 0                | 0                      | 0.00                 |
|          | LTE 26 | QPSK15M | Bottom        | 26765  | 1   | 0         | 3      | 23.00                    | 22.55                          | 1.11           | 0                | 0                      | 0.00                 |
|          | LTE 30 | QPSK10M | Bottom        | 27710  | 1   | 0         | 1      | 23.00                    | 22.91                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 30 | QPSK10M | Bottom        | 27710  | 25  | 0         | 1      | 22.00                    | 21.92                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 30 | QPSK10M | Bottom        | 27710  | 1   | 0         | 2      | 23.00                    | 22.91                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 30 | QPSK10M | Bottom        | 27710  | 1   | 0         | 3      | 23.00                    | 22.91                          | 1.02           | 0                | 0                      | 0.00                 |
|          | LTE 38 | QPSK20M | Bottom        | 37850  | 1   | 0         | 1      | 23.00                    | 22.76                          | 1.06           | 0                | 0                      | 0.00                 |
|          | LTE 38 | QPSK20M | Bottom        | 37850  | 50  | 0         | 1      | 22.00                    | 21.73                          | 1.06           | 0                | 0                      | 0.00                 |
|          | LTE 38 | QPSK20M | Bottom        | 38000  | 1   | 0         | 1      | 23.00                    | 22.65                          | 1.08           | 0                | 0                      | 0.00                 |
|          | LTE 38 | QPSK20M | Bottom        | 38150  | 1   | 0         | 1      | 23.00                    | 22.63                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 38 | QPSK20M | Bottom        | 38150  | 1   | 0         | 2      | 23.00                    | 22.63                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 38 | QPSK20M | Bottom        | 38150  | 1   | 0         | 3      | 23.00                    | 22.63                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 41 | QPSK20M | Bottom        | 40185  | 1   | 0         | 1      | 23.00                    | 22.67                          | 1.08           | 0                | 0                      | 0.00                 |
|          | LTE 41 | QPSK20M | Bottom        | 40185  | 50  | 0         | 1      | 22.00                    | 21.63                          | 1.09           | 0                | 0                      | 0.00                 |
|          | LTE 41 | QPSK20M | Bottom        | 39750  | 1   | 0         | 1      | 23.00                    | 22.53                          | 1.11           | 0                | 0                      | 0.00                 |
|          | LTE 41 | QPSK20M | Bottom        | 40620  | 1   | 0         | 1      | 23.00                    | 22.48                          | 1.13           | 0                | 0                      | 0.00                 |
|          | LTE 41 | QPSK20M | Bottom        | 41055  | 1   | 0         | 1      | 23.00                    | 22.56                          | 1.11           | 0                | 0                      | 0.00                 |
|          | LTE 41 | QPSK20M | Bottom        | 41490  | 1   | 0         | 1      | 23.00                    | 22.43                          | 1.14           | 0                | 0                      | 0.00                 |
|          | LTE 41 | QPSK20M | Bottom        | 40185  | 1   | 0         | 2      | 23.00                    | 22.67                          | 1.08           | 0                | 0                      | 0.00                 |
|          | LTE 41 | QPSK20M | Bottom        | 40185  | 1   | 0         | 3      | 23.00                    | 22.67                          | 1.08           | 0                | 0                      | 0.00                 |
|          | LTE 66 | QPSK20M | Bottom        | 132572 | 1   | 0         | 1      | 23.00                    | 22.96                          | 1.01           | 0                | 0                      | 0.00                 |
|          | LTE 66 | QPSK20M | Bottom        | 132572 | 50  | 0         | 1      | 22.00                    | 21.77                          | 1.05           | 0                | 0                      | 0.00                 |
|          | LTE 66 | QPSK20M | Bottom        | 132072 | 1   | 0         | 1      | 23.00                    | 22.70                          | 1.07           | 0                | 0                      | 0.00                 |
|          | LTE 66 | QPSK20M | Bottom        | 132322 | 1   | 0         | 1      | 23.00                    | 22.72                          | 1.07           | 0                | 0                      | 0.00                 |
|          | LTE 66 | QPSK20M | Bottom        | 132572 | 1   | 0         | 2      | 23.00                    | 22.96                          | 1.01           | 0                | 0                      | 0.00                 |
|          | LTE 66 | QPSK20M | Bottom        | 132572 | 1   | 0         | 3      | 23.00                    | 22.96                          | 1.01           | 0                | 0                      | 0.00                 |

## SAR Test Report

---

### 4.7.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

Since all the measured SAR are less than 0.8 W/kg, the repeated measurement is not required.

### 4.7.4 Simultaneous Multi-band Transmission Evaluation

Due to the WWAN SAR Data is 0 in bottom position, there is no impact to co-location SAR between WWAN and WLAN

**Note :** WLAN SAR simultaneous multi-band transmission evaluation please refer to appendix D.

## SAR Test Report

### 5. Calibration of Test Equipment

| Equipment                            | Manufacturer | Model            | SN         | Cal. Date     | Cal. Interval |
|--------------------------------------|--------------|------------------|------------|---------------|---------------|
| System Validation Dipole             | SPEAG        | D750V3           | 1013       | Aug. 23, 2019 | 1 Year        |
| System Validation Dipole             | SPEAG        | D835V2           | 4d121      | Aug. 23, 2019 | 1 Year        |
| System Validation Dipole             | SPEAG        | D1750V2          | 1055       | Aug. 23, 2019 | 1 Year        |
| System Validation Dipole             | SPEAG        | D1900V2          | 5d018      | Jun. 27, 2019 | 1 Year        |
| System Validation Dipole             | SPEAG        | D2300V2          | 1092       | Dec. 13, 2019 | 1 Year        |
| System Validation Dipole             | SPEAG        | D2600V2          | 1020       | Aug. 26, 2019 | 1 Year        |
| Dosimetric E-Field Probe             | SPEAG        | EX3DV4           | 3971       | Mar. 29, 2019 | 1 Year        |
| Dosimetric E-Field Probe             | SPEAG        | EX3DV4           | 7472       | Aug. 30, 2019 | 1 Year        |
| Dosimetric E-Field Probe             | SPEAG        | EX3DV4           | 3820       | Jun. 25, 2019 | 1 Year        |
| Data Acquisition Electronics         | SPEAG        | DAE4             | 1431       | Mar. 25, 2019 | 1 Year        |
| Data Acquisition Electronics         | SPEAG        | DAE4             | 1277       | Jan. 24, 2020 | 1 Year        |
| Data Acquisition Electronics         | SPEAG        | DAE4             | 916        | Dec. 17, 2019 | 1 Year        |
| Radio Communication Analyzer         | Anritsu      | MT8821C          | 6201381727 | Jun. 14, 2019 | 1 Year        |
| Universal Radio Communication Tester | Anritsu      | MT8821C          | 6201502978 | Jun. 13, 2019 | 1 Year        |
| Spectrum Analyzer                    | R&S          | FSL6             | 102006     | Mar. 26, 2019 | 1 Year        |
| Spectrum Analyzer                    | Anritsu      | MS2720T          | 1513085    | May. 30, 2019 | 1 Year        |
| Thermometer                          | YFE          | YF-160A          | 130504591  | Mar. 22, 2019 | 1 Year        |
| Thermometer                          | YFE          | YF-160A          | 120702365  | Aug. 06, 2019 | 1 Year        |
| Dielectric Assessment Kit            | SPEAG        | DAK-3.5          | 1151       | Aug. 20, 2019 | 1 Year        |
| Dielectric Assessment Kit            | SPEAG        | DAKS-3.5         | 1092       | May. 07, 2019 | 1 Year        |
| Dielectric Assessment Kit            | SPEAG        | DAKS_VNA<br>R140 | 0010917    | May. 08, 2019 | 1 Year        |
| Powersource1                         | SPEAG        | SE_UMS_160<br>BA | 4010       | Aug. 21, 2019 | 1 Year        |

## SAR Test Report

### 6. Measurement Uncertainty

| Source of Uncertainty                                | Uncertainty<br>( $\pm$ %) | Probability<br>Distribution | Divisor    | Ci<br>(1g)   | Ci<br>(10g)  | Standard<br>Uncertainty<br>( $\pm$ %, 1g) | Standard<br>Uncertainty<br>( $\pm$ %, 10g) | Vi       |
|------------------------------------------------------|---------------------------|-----------------------------|------------|--------------|--------------|-------------------------------------------|--------------------------------------------|----------|
| <b>Measurement System</b>                            |                           |                             |            |              |              |                                           |                                            |          |
| Probe Calibration                                    | 6.0                       | Normal                      | 1          | 1            | 1            | 6.0                                       | 6.0                                        | $\infty$ |
| Axial Isotropy                                       | 4.7                       | Rectangular                 | $\sqrt{3}$ | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 1.9                                       | 1.9                                        | $\infty$ |
| Hemispherical Isotropy                               | 9.6                       | Rectangular                 | $\sqrt{3}$ | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 3.9                                       | 3.9                                        | $\infty$ |
| Boundary Effect                                      | 1.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.6                                       | 0.6                                        | $\infty$ |
| Linearity                                            | 4.7                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 2.7                                       | 2.7                                        | $\infty$ |
| Detection Limits                                     | 0.25                      | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.14                                      | 0.14                                       | $\infty$ |
| Probe Modulation Response                            | 4.8                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 2.8                                       | 2.8                                        | $\infty$ |
| Readout Electronics                                  | 0.3                       | Normal                      | 1          | 1            | 1            | 0.3                                       | 0.3                                        | $\infty$ |
| Response Time                                        | 0.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.0                                       | 0.0                                        | $\infty$ |
| Integration Time                                     | 1.7                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 1.0                                       | 1.0                                        | $\infty$ |
| RF Ambient Conditions – Noise                        | 3.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 1.7                                       | 1.7                                        | $\infty$ |
| RF Ambient Conditions – Reflections                  | 3.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 1.7                                       | 1.7                                        | $\infty$ |
| Probe Positioner Mechanical Tolerance                | 0.02                      | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.01                                      | 0.01                                       | $\infty$ |
| Probe Positioning with Respect to Phantom            | 0.4                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.2                                       | 0.2                                        | $\infty$ |
| Post-processing                                      | 2.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 1.2                                       | 1.2                                        | $\infty$ |
| <b>Test Sample Related</b>                           |                           |                             |            |              |              |                                           |                                            |          |
| Test Sample Positioning                              | 2.82 / 1.60               | Normal                      | 1          | 1            | 1            | 2.8                                       | 1.6                                        | 35       |
| Device Holder Uncertainty                            | 2.55 / 2.76               | Normal                      | 1          | 1            | 1            | 2.6                                       | 2.8                                        | 7        |
| Power Drift of Measurement                           | 5.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 2.9                                       | 2.9                                        | $\infty$ |
| PowerScaling                                         | 0.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.0                                       | 0.0                                        | $\infty$ |
| <b>Phantom and Setup</b>                             |                           |                             |            |              |              |                                           |                                            |          |
| Phantom Uncertainty (Shape and Thickness Tolerances) | 5.7                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 3.3                                       | 3.3                                        | $\infty$ |
| Liquid Conductivity (Temperature Uncertainty)        | 2.58                      | Rectangular                 | $\sqrt{3}$ | 0.78         | 0.71         | 1.2                                       | 1.1                                        | $\infty$ |
| Liquid Conductivity (Measured)                       | 2.95                      | Normal                      | 1          | 0.78         | 0.71         | 2.3                                       | 2.1                                        | 61       |
| Liquid Permittivity (Temperature Uncertainty)        | 1.97                      | Rectangular                 | $\sqrt{3}$ | 0.23         | 0.26         | 0.3                                       | 0.3                                        | $\infty$ |
| Liquid Permittivity (Measured)                       | 3.04                      | Normal                      | 1          | 0.23         | 0.26         | 0.7                                       | 0.8                                        | 47       |
| <b>Combined Standard Uncertainty</b>                 |                           |                             |            |              |              | $\pm 10.9$ %                              | $\pm 10.7$ %                               |          |
| <b>Expanded Uncertainty (K=2)</b>                    |                           |                             |            |              |              | $\pm 21.8$ %                              | $\pm 21.4$ %                               |          |

Head SAR Uncertainty Budget for Frequency Range of 300 MHz to 3 GHz

# SAR Test Report

| Source of Uncertainty                                | Uncertainty<br>( $\pm$ %) | Probability<br>Distribution | Divisor    | Ci<br>(1g) | Ci<br>(10g) | Standard<br>Uncertainty<br>( $\pm$ %, 1g) | Standard<br>Uncertainty<br>( $\pm$ %, 10g) | Vi       |
|------------------------------------------------------|---------------------------|-----------------------------|------------|------------|-------------|-------------------------------------------|--------------------------------------------|----------|
| <b>Measurement System</b>                            |                           |                             |            |            |             |                                           |                                            |          |
| Probe Calibration                                    | 6.55                      | Normal                      | 1          | 1          | 1           | 6.55                                      | 6.55                                       | $\infty$ |
| Axial Isotropy                                       | 4.7                       | Rectangular                 | $\sqrt{3}$ | 0.7        | 0.7         | 1.9                                       | 1.9                                        | $\infty$ |
| Hemispherical Isotropy                               | 9.6                       | Rectangular                 | $\sqrt{3}$ | 0.7        | 0.7         | 3.9                                       | 3.9                                        | $\infty$ |
| Boundary Effect                                      | 2.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 1.2                                       | 1.2                                        | $\infty$ |
| Linearity                                            | 4.7                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 2.7                                       | 2.7                                        | $\infty$ |
| Detection Limits                                     | 0.25                      | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.14                                      | 0.14                                       | $\infty$ |
| Probe Modulation Response                            | 4.8                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 2.8                                       | 2.8                                        | $\infty$ |
| Readout Electronics                                  | 0.3                       | Normal                      | 1          | 1          | 1           | 0.3                                       | 0.3                                        | $\infty$ |
| Response Time                                        | 0.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.0                                       | 0.0                                        | $\infty$ |
| Integration Time                                     | 1.7                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 1.0                                       | 1.0                                        | $\infty$ |
| RF Ambient Conditions – Noise                        | 3.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 1.7                                       | 1.7                                        | $\infty$ |
| RF Ambient Conditions – Reflections                  | 3.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 1.7                                       | 1.7                                        | $\infty$ |
| Probe Positioner Mechanical Tolerance                | 0.04                      | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.02                                      | 0.02                                       | $\infty$ |
| Probe Positioning with Respect to Phantom            | 0.8                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.5                                       | 0.5                                        | $\infty$ |
| Post-processing                                      | 4.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 2.3                                       | 2.3                                        | $\infty$ |
| <b>Test Sample Related</b>                           |                           |                             |            |            |             |                                           |                                            |          |
| Test Sample Positioning                              | 2.82 / 1.60               | Normal                      | 1          | 1          | 1           | 2.8                                       | 1.6                                        | 35       |
| Device Holder Uncertainty                            | 2.55 / 2.76               | Normal                      | 1          | 1          | 1           | 2.6                                       | 2.8                                        | 7        |
| Power Drift of Measurement                           | 5.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 2.9                                       | 2.9                                        | $\infty$ |
| PowerScaling                                         | 0.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.0                                       | 0.0                                        | $\infty$ |
| <b>Phantom and Setup</b>                             |                           |                             |            |            |             |                                           |                                            |          |
| Phantom Uncertainty (Shape and Thickness Tolerances) | 6.2                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 3.6                                       | 3.6                                        | $\infty$ |
| Liquid Conductivity (Temperature Uncertainty)        | 2.58                      | Rectangular                 | $\sqrt{3}$ | 0.78       | 0.71        | 1.2                                       | 1.1                                        | $\infty$ |
| Liquid Conductivity (Measured)                       | 2.95                      | Normal                      | 1          | 0.78       | 0.71        | 2.3                                       | 2.1                                        | 61       |
| Liquid Permittivity (Temperature Uncertainty)        | 1.97                      | Rectangular                 | $\sqrt{3}$ | 0.23       | 0.26        | 0.3                                       | 0.3                                        | $\infty$ |
| Liquid Permittivity (Measured)                       | 3.04                      | Normal                      | 1          | 0.23       | 0.26        | 0.7                                       | 0.8                                        | 47       |
| <b>Combined Standard Uncertainty</b>                 |                           |                             |            |            |             | $\pm 11.6$ %                              | $\pm 11.3$ %                               |          |
| <b>Expanded Uncertainty (K=2)</b>                    |                           |                             |            |            |             | $\pm 23.2$ %                              | $\pm 22.6$ %                               |          |

## Head SAR Uncertainty Budget for Frequency Range of 3 GHz to 6 GHz

# SAR Test Report

| Source of Uncertainty                                | Uncertainty<br>( $\pm$ %) | Probability<br>Distribution | Divisor    | Ci<br>(1g)   | Ci<br>(10g)  | Standard<br>Uncertainty<br>( $\pm$ %, 1g) | Standard<br>Uncertainty<br>( $\pm$ %, 10g) | Vi       |
|------------------------------------------------------|---------------------------|-----------------------------|------------|--------------|--------------|-------------------------------------------|--------------------------------------------|----------|
| <b>Measurement System</b>                            |                           |                             |            |              |              |                                           |                                            |          |
| Probe Calibration                                    | 6.0                       | Normal                      | 1          | 1            | 1            | 6.0                                       | 6.0                                        | $\infty$ |
| Axial Isotropy                                       | 4.7                       | Rectangular                 | $\sqrt{3}$ | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 1.9                                       | 1.9                                        | $\infty$ |
| Hemispherical Isotropy                               | 9.6                       | Rectangular                 | $\sqrt{3}$ | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 3.9                                       | 3.9                                        | $\infty$ |
| Boundary Effect                                      | 1.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.6                                       | 0.6                                        | $\infty$ |
| Linearity                                            | 4.7                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 2.7                                       | 2.7                                        | $\infty$ |
| Detection Limits                                     | 0.25                      | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.14                                      | 0.14                                       | $\infty$ |
| Probe Modulation Response                            | 4.8                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 2.8                                       | 2.8                                        | $\infty$ |
| Readout Electronics                                  | 0.3                       | Normal                      | 1          | 1            | 1            | 0.3                                       | 0.3                                        | $\infty$ |
| Response Time                                        | 0.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.0                                       | 0.0                                        | $\infty$ |
| Integration Time                                     | 1.7                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 1.0                                       | 1.0                                        | $\infty$ |
| RF Ambient Conditions – Noise                        | 3.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 1.7                                       | 1.7                                        | $\infty$ |
| RF Ambient Conditions – Reflections                  | 3.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 1.7                                       | 1.7                                        | $\infty$ |
| Probe Positioner Mechanical Tolerance                | 0.02                      | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.01                                      | 0.01                                       | $\infty$ |
| Probe Positioning with Respect to Phantom            | 0.4                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.2                                       | 0.2                                        | $\infty$ |
| Post-processing                                      | 2.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 1.2                                       | 1.2                                        | $\infty$ |
| <b>Test Sample Related</b>                           |                           |                             |            |              |              |                                           |                                            |          |
| Test Sample Positioning                              | 3.68 / 1.73               | Normal                      | 1          | 1            | 1            | 3.7                                       | 1.7                                        | 29       |
| Device Holder Uncertainty                            | 2.55 / 2.76               | Normal                      | 1          | 1            | 1            | 2.6                                       | 2.8                                        | 7        |
| Power Drift of Measurement                           | 5.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 2.9                                       | 2.9                                        | $\infty$ |
| PowerScaling                                         | 0.0                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 0.0                                       | 0.0                                        | $\infty$ |
| <b>Phantom and Setup</b>                             |                           |                             |            |              |              |                                           |                                            |          |
| Phantom Uncertainty (Shape and Thickness Tolerances) | 7.2                       | Rectangular                 | $\sqrt{3}$ | 1            | 1            | 4.2                                       | 4.2                                        | $\infty$ |
| Liquid Conductivity (Temperature Uncertainty)        | 2.58                      | Rectangular                 | $\sqrt{3}$ | 0.78         | 0.71         | 1.2                                       | 1.1                                        | $\infty$ |
| Liquid Conductivity (Measured)                       | 2.95                      | Normal                      | 1          | 0.78         | 0.71         | 2.3                                       | 2.1                                        | 61       |
| Liquid Permittivity (Temperature Uncertainty)        | 1.97                      | Rectangular                 | $\sqrt{3}$ | 0.23         | 0.26         | 0.3                                       | 0.3                                        | $\infty$ |
| Liquid Permittivity (Measured)                       | 3.04                      | Normal                      | 1          | 0.23         | 0.26         | 0.7                                       | 0.8                                        | 47       |
| <b>Combined Standard Uncertainty</b>                 |                           |                             |            |              |              | $\pm 11.5$ %                              | $\pm 11.0$ %                               |          |
| <b>Expanded Uncertainty (K=2)</b>                    |                           |                             |            |              |              | $\pm 23.0$ %                              | $\pm 22.0$ %                               |          |

## Body SAR Uncertainty Budget for Frequency Range of 300 MHz to 3 GHz

# SAR Test Report

| Source of Uncertainty                                | Uncertainty<br>( $\pm$ %) | Probability<br>Distribution | Divisor    | Ci<br>(1g) | Ci<br>(10g) | Standard<br>Uncertainty<br>( $\pm$ %, 1g) | Standard<br>Uncertainty<br>( $\pm$ %, 10g) | Vi       |
|------------------------------------------------------|---------------------------|-----------------------------|------------|------------|-------------|-------------------------------------------|--------------------------------------------|----------|
| <b>Measurement System</b>                            |                           |                             |            |            |             |                                           |                                            |          |
| Probe Calibration                                    | 6.55                      | Normal                      | 1          | 1          | 1           | 6.55                                      | 6.55                                       | $\infty$ |
| Axial Isotropy                                       | 4.7                       | Rectangular                 | $\sqrt{3}$ | 0.7        | 0.7         | 1.9                                       | 1.9                                        | $\infty$ |
| Hemispherical Isotropy                               | 9.6                       | Rectangular                 | $\sqrt{3}$ | 0.7        | 0.7         | 3.9                                       | 3.9                                        | $\infty$ |
| Boundary Effect                                      | 2.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 1.2                                       | 1.2                                        | $\infty$ |
| Linearity                                            | 4.7                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 2.7                                       | 2.7                                        | $\infty$ |
| Detection Limits                                     | 0.25                      | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.14                                      | 0.14                                       | $\infty$ |
| Probe Modulation Response                            | 4.8                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 2.8                                       | 2.8                                        | $\infty$ |
| Readout Electronics                                  | 0.3                       | Normal                      | 1          | 1          | 1           | 0.3                                       | 0.3                                        | $\infty$ |
| Response Time                                        | 0.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.0                                       | 0.0                                        | $\infty$ |
| Integration Time                                     | 1.7                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 1.0                                       | 1.0                                        | $\infty$ |
| RF Ambient Conditions – Noise                        | 3.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 1.7                                       | 1.7                                        | $\infty$ |
| RF Ambient Conditions – Reflections                  | 3.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 1.7                                       | 1.7                                        | $\infty$ |
| Probe Positioner Mechanical Tolerance                | 0.04                      | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.02                                      | 0.02                                       | $\infty$ |
| Probe Positioning with Respect to Phantom            | 0.8                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.5                                       | 0.5                                        | $\infty$ |
| Post-processing                                      | 4.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 2.3                                       | 2.3                                        | $\infty$ |
| <b>Test Sample Related</b>                           |                           |                             |            |            |             |                                           |                                            |          |
| Test Sample Positioning                              | 3.68 / 1.73               | Normal                      | 1          | 1          | 1           | 3.7                                       | 1.7                                        | 29       |
| Device Holder Uncertainty                            | 2.55 / 2.76               | Normal                      | 1          | 1          | 1           | 2.6                                       | 2.8                                        | 7        |
| Power Drift of Measurement                           | 5.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 2.9                                       | 2.9                                        | $\infty$ |
| PowerScaling                                         | 0.0                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 0.0                                       | 0.0                                        | $\infty$ |
| <b>Phantom and Setup</b>                             |                           |                             |            |            |             |                                           |                                            |          |
| Phantom Uncertainty (Shape and Thickness Tolerances) | 7.6                       | Rectangular                 | $\sqrt{3}$ | 1          | 1           | 4.4                                       | 4.4                                        | $\infty$ |
| Liquid Conductivity (Temperature Uncertainty)        | 2.58                      | Rectangular                 | $\sqrt{3}$ | 0.78       | 0.71        | 1.2                                       | 1.1                                        | $\infty$ |
| Liquid Conductivity (Measured)                       | 2.95                      | Normal                      | 1          | 0.78       | 0.71        | 2.3                                       | 2.1                                        | 61       |
| Liquid Permittivity (Temperature Uncertainty)        | 1.97                      | Rectangular                 | $\sqrt{3}$ | 0.23       | 0.26        | 0.3                                       | 0.3                                        | $\infty$ |
| Liquid Permittivity (Measured)                       | 3.04                      | Normal                      | 1          | 0.23       | 0.26        | 0.7                                       | 0.8                                        | 47       |
| <b>Combined Standard Uncertainty</b>                 |                           |                             |            |            |             | $\pm 12.1$ %                              | $\pm 11.6$ %                               |          |
| <b>Expanded Uncertainty (K=2)</b>                    |                           |                             |            |            |             | $\pm 24.2$ %                              | $\pm 23.2$ %                               |          |

## Body SAR Uncertainty Budget for Frequency Range of 3 GHz to 6 GHz

## SAR Test Report

---

### 7. Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Taiwan Huaya Lab:**

Add: No. 19, Huaya 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan

Tel: +886-(0)3-318-3232

Fax: +886-(0)3-211-5834

**Taiwan Linkou Lab:**

Add: No. 47-2, Baodoucuokeng, Linkou Dist., New Taipei City 244, Taiwan

Tel: +886-(0)2-2605-2180

Fax: +886-(0)2-2605-2943

**Taiwan Hsinchu Lab1:**

Add: E-2, No. 1, Lixing 1st Rd., East Dist., Hsinchu City 300, Taiwan

Tel: +886-(0)3-666-8565

Fax: +886-(0)3-666-8323

**Taiwan Hsinchu Lab2:**

Add: No. 49, Ln. 206, Wende Rd., Qionglin Township, Hsinchu County 307, Taiwan

Tel: +886-(0)3-512-0595

Fax: +886-(0)3-512-0568

**Taiwan Xindian Lab:**

Add: B2F., No. 215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel: +886-(0)2-8914-5882

Fax: +886-(0)2-8914-5840

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** <https://ee.bureauveritas.com.tw/BVInternet/Default>

The road map of all our labs can be found in our web site also.

---END---

### Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

## System Check\_H750\_200222

**DUT: Dipole 750 MHz; Type: D750V3; SN: 1013**

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: H06T09N1\_0222 Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.897$  S/m;  $\epsilon_r = 42.647$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(10.49, 10.49, 10.49); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2019/03/25
- Phantom: ELI Phantom\_1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (61x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.515 W/kg


**Pin=50mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.16 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.570 W/kg

**SAR(1 g) = 0.394 W/kg; SAR(10 g) = 0.266 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 0.514 W/kg



## System Check\_H835\_200222

**DUT: Dipole 835 MHz; Type: D835V2; SN: 4d121**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: H07T10N1\_0222 Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.945$  S/m;  $\epsilon_r = 43.009$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(10.18, 10.18, 10.18); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2019/03/25
- Phantom: ELI Phantom\_1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.619 W/kg


**Pin=50mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.84 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.698 W/kg

**SAR(1 g) = 0.466 W/kg; SAR(10 g) = 0.313 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 0.627 W/kg



## System Check\_H1750\_200407

**DUT: Dipole 1750 MHz; Type: D1750V2; SN: 1055**

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: H16T20N1\_0407 Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.321$  S/m;  $\epsilon_r = 39.01$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.7 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3820; ConvF(7.85, 7.85, 7.85); Calibrated: 2019/06/25
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn916; Calibrated: 2019/12/17
- Phantom: ELI Phantom\_1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.71 W/kg


**Pin=50mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 46.29 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 3.16 W/kg

**SAR(1 g) = 1.86 W/kg; SAR(10 g) = 1.02 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 2.69 W/kg



## System Check\_H1900\_200222

**DUT: Dipole 1900 MHz; Type: D1900V2; SN: 5d018**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: H16T20N1\_0222 Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.455$  S/m;  $\epsilon_r = 39.103$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(8.34, 8.34, 8.34); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2019/03/25
- Phantom: ELI Phantom\_1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (61x61x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.10 W/kg


**Pin=50mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 47.42 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 3.69 W/kg

**SAR(1 g) = 1.96 W/kg; SAR(10 g) = 1.05 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 3.12 W/kg



## System Check\_H2300\_200223

**DUT: Dipole 2300 MHz; Type: D2300V2; SN:1092**

Communication System: CW; Frequency: 2300 MHz; Duty Cycle: 1:1

Medium: H19T27N1\_0223 Medium parameters used:  $f = 2300$  MHz;  $\sigma = 1.73$  S/m;  $\epsilon_r = 39.008$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.6 °C ; Liquid Temperature : 23.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(8.11, 8.11, 8.11); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2019/03/25
- Phantom: ELI Phantom\_1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 3.91 W/kg


**Pin=50mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 48.96 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 4.77 W/kg

**SAR(1 g) = 2.37 W/kg; SAR(10 g) = 1.16 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 3.94 W/kg



## System Check\_H2600\_200222

**DUT: Dipole 2600 MHz; Type: D2600V2; SN: 1020**

Communication System: CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: H19T27N1\_0222 Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.008$  S/m;  $\epsilon_r = 37.939$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.8 °C ; Liquid Temperature : 23.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN7472; ConvF(7.64, 7.64, 7.64); Calibrated: 2019/08/30
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1431; Calibrated: 2019/03/25
- Phantom: ELI Phantom\_1206; Type: QDOVA002AA;
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)

**Pin=50mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 4.83 W/kg

**Pin=50mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 51.02 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 5.86 W/kg

**SAR(1 g) = 2.83 W/kg; SAR(10 g) = 1.31 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 4.78 W/kg

