FCC RF Test Report

APPLICANT	:	Fibocom Wireless Inc.
EQUIPMENT	:	LTE Module
BRAND NAME	:	Fibocom
MODEL NAME	:	L860-GL-16
FCC ID	:	ZMOL860GL16
STANDARD	:	47 CFR Part 2, 27
CLASSIFICATION	:	PCS Licensed Transmitter (PCB)

The product was received on Oct. 30, 2020 and completely tested on Jan. 10, 2021. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 5
1.6 Maximum Conducted Power, Frequency Tolerance and Emission Designator 6
1.7 Testing Site 6
1.8 Test Software 6
1.9 Applied Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 9
2.5 Frequency List of Low/Middle/High Channels 10
3 CONDUCTED TEST ITEMS **11**
3.1 Measuring Instruments 11
3.2 Test Setup 11
3.3 Test Result of Conducted Test 11
3.4 Conducted Output Power Measurement 12
3.5 Peak-to-Average Ratio 13
3.6 EIRP 14
3.7 Occupied Bandwidth 15
3.8 Conducted Band Edge Measurement 16
3.9 Conducted Spurious Emission Measurement 17
3.10 Frequency Stability Measurement 18
4 RADIATED TEST ITEMS **19**
4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 19
4.4 Radiated Spurious Emission Measurement 20
5 LIST OF MEASURING EQUIPMENT **21**
6 UNCERTAINTY OF EVALUATION **22**
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG0O3022E	Rev. 01	Initial issue of report	Feb. 07, 2021

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	-	Peak-to-Average Ratio	<13dB	N/A	Reporting only
3.6	§27.50 (a)(3)	EIRP	EIRP < 250mW/5MHz	PASS	-
3.7	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.8	§2.1051 §27.53 (a)(4)	Conducted Band Edge Measurement	Refer standard	PASS	-
3.9	§2.1051 §27.53 (a)(4)	Conducted Spurious Emission	< $70+10\log_{10}$(P[Watts])	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (a)(4)	Radiated Spurious Emission	< $70+10\log_{10}$(P[Watts])	PASS	Under limit 21.23 dB at 9234.000 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Fibocom Wireless Inc.
1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China

1.2 Manufacturer

Fibocom Wireless Inc.
1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan, Shenzhen, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	LTE Module
Brand Name	Fibocom
Model Name	L860-GL-16
FCC ID	ZMOL860GL16
EUT supports Radios application	WCDMA/LTE/GNSS
HW Version	V1.3
SW Version	18601.5001.00.01.01.01
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx Frequency	LTE Band 30 : 2305 MHz ~ 2315 MHz
Rx Frequency	LTE Band 30 : 2350 MHz ~ 2360 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	LTE Band 30 : 21.97 dBm
Antenna Gain	LTE Band 30 : 1.0 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power, Frequency Tolerance and Emission Designator

LTE Band 30		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum Conducted power (W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum Conducted power (W)
10	2310.0	9M03G7D	0.0017	0.1574	9M01W7D	-	0.1368

1.7 Testing Site

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH06-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH06-KS	AUDIX	E3	6.2009-8-24al

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, Part 27(D)
- ANSI C63.26-2015
- FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01
-

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	30	-	-	V		-	-	V	V	V	V	V	V	V	V	V
		-	-		V	-	-	V	V	V	V	V	V		V	
Peak-to-Average Ratio	30	-	-		V	-	-	V	V				V		V	
E.I.R.P	30	-	-	V		-	-	V	V		V			V	V	V
		-	-		V	-	-	V	V		V				V	
26dB and 99% Bandwidth	30	-	-		V	-	-	V	V				V		V	
Conducted Band Edge	30	-	-	V		-	-	V	V		V		V	V		V
		-	-		V	-	-	V	V		V		V	V		V
Conducted Spurious Emission	30	-	-	V		-	-	V	V		V			V	V	V
		-	-		V	-	-	V	V		V				V	
Frequency Stability	30	-	-		V	-	-	V					V		V	
Radiated Spurious Emission	30	-	-	V		-	-	V			V			V	V	V
					V			V			V				V	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. Based on engineering evaluation, only the maximum bandwidth and the worst modulation test results are shown in the report.															

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	Test jig	N/A	N/A	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.8 dB.

Example :

Offset(dB) = RF cable loss(dB).

= 5.8 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 30 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	27710	-
	Frequency	-	2310	-
5	Channel	27685	27710	27735
	Frequency	2307.5	2310	2312.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth ,Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP

For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

   P_T = transmitter output power in dBm

   G_T = gain of the transmitting antenna in dBi

   L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

27.53 (a)(4)

For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: 43 + 10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337 MHz;

(ii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2296 and 2300 MHz, 61 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz;

(iii) By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [70 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
    = -40dBm

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 70 + 10 log (P) dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
   EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
   ERP (dBm) = EIRP - 2.15
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 70 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [70 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [70 + 10log(P)] (dB)
    = -40dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 01, 2020	Dec. 11, 2020	Oct. 31, 2021	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 03, 2020	Dec. 11, 2020	Jul. 02, 2021	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44GHz	Apr. 14, 2020	Jan. 10, 2021	Apr.13, 2021	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz-1GHz	May. 29, 2020	Jan. 10, 2021	May. 28, 2021	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 27, 2020	Jan. 10, 2021	Apr. 26, 2021	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Jun. 05, 2020	Jan. 10, 2021	Jun. 04, 2021	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	187289	9KHz ~1GHZ	Apr. 14, 2020	Jan. 10, 2021	Apr. 13, 2021	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 07, 2021	Jan. 10, 2021	Jan. 06, 2022	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Jan. 07, 2021	Jan. 10, 2021	Jan. 06, 2022	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 15, 2020	Jan. 10, 2021	Apr. 14. 2021	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jan. 10, 2021	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jan. 10, 2021	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jan. 10, 2021	NCR	Radiation (03CH06-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.5dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.1dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.1dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.
Channel				27710		
Frequency (MHz)				2310		
10	QPSK	1	0		21.97	
10	QPSK	1	49		21.96	
10	QPSK	50	0		20.89	
10	16QAM	1	0		21.36	
10	64QAM	1	0		20.33	
Channel				27685	27710	27735
Frequency (MHz)				2307.5	2310	2312.5
5	QPSK	1	0	21.56	21.65	21.96
5	16QAM	1	0	20.78	20.36	20.63
5	64QAM	1	0	19.63	20.21	20.32

EIRP

LTE Band 30 (GT - LC =1.0 dB) QPSK (dBm/5MHz)			
Bandwidth	5M		
Channel	27685	27710	27735
	(Low)	(Mid)	(High)
Frequency (MHz)	2307.5	2310	2312.5
Conducted Power (dBm/5MHz)	21.56	21.65	21.96
Conducted Power (Watts/5MHz)	0.1432	0.1462	0.1570
EIRP(dBm/5MHz)	22.56	22.65	22.96
EIRP(Watts/5MHz)	0.1803	0.1841	0.1977
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS

LTE Band 30 (GT - LC = 1.0 dB) QPSK (dBm/5MHz)			
Bandwidth	10M		
Channel		27710	
		(Mid)	
Frequency (MHz)		2310	
Conducted Power (dBm/5MHz)		21.97	
Conducted Power (Watts/5MHz)		0.1574	
EIRP(dBm/5MHz)		22.97	
EIRP(Watts/5MHz)		0.1982	
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS

LTE Band 30 (GT - LC = 1.0 dB) 16QAM (dBm/5MHz)			
Bandwidth	5M		
Channel	27685	27710	27735
	(Low)	(Mid)	(High)
Frequency (MHz)	2307.5	2310	2312.5
Conducted Power (dBm/5MHz)	20.78	20.36	20.63
Conducted Power (Watts/5MHz)	0.1197	0.1086	0.1156
EIRP(dBm/5MHz)	21.78	21.36	21.63
EIRP(Watts/5MHz)	0.1507	0.1368	0.1455
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS

LTE Band 30 (GT - LC = 1.0 dB) 16QAM (dBm/5MHz)			
Bandwidth	10M		
Channel		27710	
		(Mid)	
Frequency (MHz)		2310	
Conducted Power (dBm/5MHz)		21.36	
Conducted Power (Watts/5MHz)		0.1368	
EIRP(dBm/5MHz)		22.36	
EIRP(Watts/5MHz)		0.1722	
Limit	250mW / 5MHz = 24dBm / 5MHz		PASS

Peak-to-Average Ratio

Mode	LTE Band 30 / 10MHz			
Mod.	QPSK	16QAM		Limit: 13dB
RB Size	Full RB	Full RB		Result
Middle CH	4.72	5.25		PASS

LTE Band 30 / 10MHz	
Middle Channel / Full RB / QPSK	**Middle Channel / Full RB / 16QAM**
	

26dB Bandwidt

Mode	LTE Band 30 : 26dB BW(MHz)	
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	10.15	9.79

LTE Band 30	
Middle Channel / 10MHz / QPSK	Middle Channel / 10MHz / 16QAM





Occupied Bandwidth

Mode	LTE Band 30 : 99%OBW(MHz)	
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	9.03	9.01

LTE Band 30	
Middle Channel / 5MHz / QPSK	Middle Channel / 5MHz / 16QAM
	

Conducted Band Edge

LTE Band 30 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29255 GHz	-48.48 dBm	-17.48 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29993 GHz	-45.46 dBm	-20.46 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30149 GHz	-26.67 dBm	-13.67 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-23.76 dBm	-10.76 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30534 GHz	18.93 dBm	-11.07 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31003 GHz	-53.30 dBm	-40.30 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31441 GHz	-33.14 dBm	-20.14 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32031 GHz	-50.82 dBm	-25.82 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32436 GHz	-52.89 dBm	-21.89 dB

Date: 11.DEC.2020 04:24:45

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29551 GHz	-53.83 dBm	-22.83 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29920 GHz	-50.22 dBm	-25.22 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30504 GHz	-37.89 dBm	-24.89 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30998 GHz	-53.87 dBm	-40.87 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31466 GHz	19.21 dBm	-10.79 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-23.08 dBm	-10.08 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31973 GHz	-31.38 dBm	-18.38 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32313 GHz	-33.58 dBm	-8.58 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32768 GHz	-47.29 dBm	-16.29 dB

Date: 11.DEC.2020 04:28:45

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29590 GHz	-45.94 dBm	-14.94 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29993 GHz	-30.83 dBm	-5.83 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30395 GHz	-21.49 dBm	-8.49 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30497 GHz	-32.11 dBm	-19.11 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30953 GHz	6.23 dBm	-23.77 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31001 GHz	-29.69 dBm	-16.69 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31109 GHz	-19.76 dBm	-6.76 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32389 GHz	-41.53 dBm	-16.53 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32603 GHz	-44.43 dBm	-13.43 dB

Date: 11.DEC.2020 04:17:26

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29452 GHz	-46.79 dBm	-15.79 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29943 GHz	-42.29 dBm	-17.29 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30899 GHz	-24.67 dBm	-11.67 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.31000 GHz	-31.02 dBm	-18.02 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31152 GHz	5.63 dBm	-24.37 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-31.72 dBm	-18.72 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31601 GHz	-24.21 dBm	-11.21 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32024 GHz	-32.31 dBm	-7.31 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32403 GHz	-43.15 dBm	-12.15 dB

Date: 12.DEC.2020 06:19:24

LTE Band 30 / 5MHz / 16QAM

Lowest Band Edge / 1RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29556 GHz	-45.04 dBm	-14.04 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29935 GHz	-33.26 dBm	-8.26 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30334 GHz	-25.76 dBm	-12.76 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-23.17 dBm	-10.17 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30538 GHz	18.38 dBm	-11.62 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31007 GHz	-53.74 dBm	-40.74 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31101 GHz	-30.80 dBm	-17.80 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32153 GHz	-40.53 dBm	-15.53 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32483 GHz	-51.84 dBm	-20.84 dB

Date: 11.DEC.2020 04:24:00

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29522 GHz	-53.79 dBm	-22.79 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29967 GHz	-50.98 dBm	-25.98 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30896 GHz	-45.05 dBm	-32.05 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30988 GHz	-54.93 dBm	-41.93 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31468 GHz	18.33 dBm	-11.67 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-22.05 dBm	-9.05 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31604 GHz	-32.50 dBm	-19.50 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32067 GHz	-33.76 dBm	-8.76 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32418 GHz	-40.98 dBm	-9.98 dB

Date: 11.DEC.2020 04:27:59

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29594 GHz	-47.03 dBm	-16.03 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29993 GHz	-30.31 dBm	-5.31 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30395 GHz	-20.63 dBm	-7.63 dB
2.304 GHz	2.305 GHz	50.000 kHz	2.30500 GHz	-32.30 dBm	-19.30 dB
2.305 GHz	2.310 GHz	100.000 kHz	2.30952 GHz	5.24 dBm	-24.76 dB
2.310 GHz	2.311 GHz	50.000 kHz	2.31000 GHz	-30.52 dBm	-17.52 dB
2.311 GHz	2.320 GHz	1.000 MHz	2.31114 GHz	-19.50 dBm	-6.50 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32010 GHz	-41.31 dBm	-16.31 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32470 GHz	-45.91 dBm	-14.91 dB

Date: 11.DEC.2020 04:23:07

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29576 GHz	-48.42 dBm	-17.42 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29979 GHz	-44.19 dBm	-19.19 dB
2.300 GHz	2.309 GHz	1.000 MHz	2.30897 GHz	-25.56 dBm	-12.56 dB
2.309 GHz	2.310 GHz	50.000 kHz	2.30999 GHz	-32.51 dBm	-19.51 dB
2.310 GHz	2.315 GHz	100.000 kHz	2.31176 GHz	4.55 dBm	-25.45 dB
2.315 GHz	2.316 GHz	50.000 kHz	2.31500 GHz	-32.92 dBm	-19.92 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31621 GHz	-25.54 dBm	-12.54 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32033 GHz	-35.89 dBm	-10.89 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32428 GHz	-44.75 dBm	-13.75 dB

Date: 12.DEC.2020 06:20:00

LTE Band 30 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29593 GHz	-51.32 dBm	-20.32 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29631 GHz	-44.53 dBm	-19.53 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30396 GHz	-34.39 dBm	-21.39 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30500 GHz	-17.87 dBm	-4.87 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30559 GHz	19.52 dBm	-10.48 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31513 GHz	-52.29 dBm	-39.29 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31613 GHz	-46.48 dBm	-33.48 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32112 GHz	-38.21 dBm	-13.21 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32454 GHz	-52.58 dBm	-21.58 dB

Date: 11.DEC.2020 04:59:41

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29432 GHz	-46.92 dBm	-15.92 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29840 GHz	-46.36 dBm	-21.36 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30272 GHz	-47.80 dBm	-34.80 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30483 GHz	-54.57 dBm	-41.57 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31443 GHz	19.68 dBm	-10.32 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31501 GHz	-16.95 dBm	-3.95 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31713 GHz	-29.75 dBm	-16.75 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32075 GHz	-31.45 dBm	-6.45 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32422 GHz	-50.25 dBm	-19.25 dB

Date: 11.DEC.2020 05:00:12

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29597 GHz	-40.60 dBm	-9.60 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29985 GHz	-30.68 dBm	-5.68 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30398 GHz	-22.27 dBm	-9.27 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30498 GHz	-29.46 dBm	-16.46 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31314 GHz	2.35 dBm	-27.65 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31504 GHz	-28.54 dBm	-15.54 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31631 GHz	-21.70 dBm	-8.70 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32001 GHz	-27.36 dBm	-2.36 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32401 GHz	-31.58 dBm	-0.58 dB

Date: 15.DEC.2020 01:53:35

LTE Band 30 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29590 GHz	-51.63 dBm	-20.63 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29834 GHz	-33.99 dBm	-8.99 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30329 GHz	-28.33 dBm	-15.33 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30499 GHz	-17.34 dBm	-4.34 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.30560 GHz	18.44 dBm	-11.56 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31530 GHz	-54.53 dBm	-41.53 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31795 GHz	-40.06 dBm	-27.06 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32331 GHz	-38.96 dBm	-13.96 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32413 GHz	-51.13 dBm	-20.13 dB

Date: 11.DEC.2020 04:59:10

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29394 GHz	-52.30 dBm	-21.30 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29907 GHz	-39.86 dBm	-14.86 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30395 GHz	-48.15 dBm	-35.15 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30489 GHz	-55.21 dBm	-42.21 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31440 GHz	18.92 dBm	-11.08 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31501 GHz	-17.79 dBm	-4.79 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31602 GHz	-25.68 dBm	-12.68 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32027 GHz	-43.41 dBm	-18.41 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32665 GHz	-45.82 dBm	-14.82 dB

Date: 11.DEC.2020 05:00:45

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
2.292 GHz	2.296 GHz	1.000 MHz	2.29593 GHz	-42.30 dBm	-11.30 dB
2.296 GHz	2.300 GHz	1.000 MHz	2.29990 GHz	-30.07 dBm	-5.07 dB
2.300 GHz	2.304 GHz	1.000 MHz	2.30387 GHz	-23.21 dBm	-10.21 dB
2.304 GHz	2.305 GHz	100.000 kHz	2.30500 GHz	-29.94 dBm	-16.94 dB
2.305 GHz	2.315 GHz	100.000 kHz	2.31355 GHz	2.21 dBm	-27.79 dB
2.315 GHz	2.316 GHz	100.000 kHz	2.31500 GHz	-29.34 dBm	-16.34 dB
2.316 GHz	2.320 GHz	1.000 MHz	2.31605 GHz	-22.47 dBm	-9.47 dB
2.320 GHz	2.324 GHz	1.000 MHz	2.32024 GHz	-26.44 dBm	-1.44 dB
2.324 GHz	2.328 GHz	1.000 MHz	2.32409 GHz	-32.13 dBm	-1.13 dB

Date: 15.DEC.2020 01:49:12

Conducted Spurious Emission

LTE Band 30 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	912.50125 MHz	-53.29 dBm	-13.29 dB
1.000 GHz	2.292 GHz	1.000 MHz	1.72995 GHz	-54.08 dBm	-14.08 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.94744 GHz	-53.59 dBm	-13.59 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.92376 GHz	-45.35 dBm	-5.35 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.16989 GHz	-51.99 dBm	-11.99 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.22660 GHz	-50.89 dBm	-10.89 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.90626 GHz	-48.78 dBm	-8.78 dB
18.000 GHz	24.000 GHz	1.000 MHz	18.26723 GHz	-48.27 dBm	-8.27 dB

Date: 11.DEC.2020 05:07:50

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	899.89755 MHz	-53.19 dBm	-13.19 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.15230 GHz	-54.09 dBm	-14.09 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.99647 GHz	-53.64 dBm	-13.64 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.92376 GHz	-45.97 dBm	-5.97 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.21688 GHz	-51.95 dBm	-11.95 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.19510 GHz	-50.93 dBm	-10.93 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.60380 GHz	-48.68 dBm	-8.68 dB
18.000 GHz	24.000 GHz	1.000 MHz	18.28323 GHz	-48.02 dBm	-8.02 dB

Date: 11.DEC.2020 05:08:38

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	969.21789 MHz	-53.53 dBm	-13.53 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.24314 GHz	-54.03 dBm	-14.03 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.99043 GHz	-53.60 dBm	-13.60 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.92376 GHz	-45.18 dBm	-5.18 dB
7.000 GHz	10.000 GHz	1.000 MHz	8.90043 GHz	-52.09 dBm	-12.09 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.20510 GHz	-50.79 dBm	-10.79 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.90126 GHz	-48.75 dBm	-8.75 dB
18.000 GHz	24.000 GHz	1.000 MHz	18.27173 GHz	-48.32 dBm	-8.32 dB

Date: 11.DEC.2020 05:06:37

LTE Band 30 / 10MHz	
Middle Channel / QPSK	



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	975.03498 MHz	-53.35 dBm	-13.35 dB
1.000 GHz	2.292 GHz	1.000 MHz	2.10537 GHz	-53.98 dBm	-13.98 dB
2.328 GHz	3.000 GHz	1.000 MHz	2.96457 GHz	-53.53 dBm	-13.53 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.91726 GHz	-46.55 dBm	-6.55 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.86177 GHz	-51.97 dBm	-11.97 dB
10.000 GHz	14.000 GHz	1.000 MHz	11.20360 GHz	-50.89 dBm	-10.89 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.90076 GHz	-48.62 dBm	-8.62 dB
18.000 GHz	24.000 GHz	1.000 MHz	18.28473 GHz	-48.19 dBm	-8.19 dB

Date: 11.DEC.2020 05:01:44

Frequency Stability

Test Conditions		LTE Band 30 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0007	PASS
40	Normal Voltage	0.0002	
30	Normal Voltage	0.0016	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0013	
0	Normal Voltage	0.0017	
-10	Normal Voltage	0.0016	
-20	Normal Voltage	0.0003	
-30	Normal Voltage	0.0001	
20	Maximum Voltage	0.0017	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0015	

Note:

1. Normal Voltage =3.3 V. ; Battery End Point (BEP) =3.135 V. ; Maximum Voltage =4.4 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

LTE Band 30 / 5MHz / QPSK / RB Size 1 Offset 0								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	4608	-63.86	-40	-23.86	-75.32	2.84	14.30	H
	6918	-62.21	-40	-22.21	-72.15	3.49	13.43	H
	9225	-61.68	-40	-21.68	-71.92	3.85	14.09	H
	4608	-62.98	-40	-22.98	-74.44	2.84	14.30	V
	6918	-62.39	-40	-22.39	-72.33	3.49	13.43	V
	9225	-61.84	-40	-21.84	-72.08	3.85	14.09	V
Middle	4614	-64.13	-40	-24.13	-75.59	2.84	14.30	H
	6924	-62.28	-40	-22.28	-72.22	3.49	13.43	H
	9234	-61.25	-40	-21.25	-71.49	3.85	14.09	H
	4614	-63.01	-40	-23.01	-74.47	2.84	14.30	V
	6924	-62.38	-40	-22.38	-72.32	3.49	13.43	V
	9234	-61.23	-40	-21.23	-71.47	3.85	14.09	V
Highest	4620	-63.87	-40	-23.87	-75.33	2.84	14.30	H
	6930	-62.34	-40	-22.34	-72.28	3.49	13.43	H
	9243	-61.42	-40	-21.42	-71.66	3.85	14.09	H
	4620	-62.36	-40	-22.36	-73.82	2.84	14.30	V
	6930	-62.24	-40	-22.24	-72.18	3.49	13.43	V
	9243	-61.57	-40	-21.57	-71.81	3.85	14.09	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 30 / 10MHz / QPSK / RB Size 1 Offset 0								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	4614	-63.96	-40	-23.96	-75.42	2.84	14.30	H
	6918	-62.48	-40	-22.48	-72.42	3.49	13.43	H
	9225	-61.50	-40	-21.50	-71.74	3.85	14.09	H
	4614	-63.72	-40	-23.72	-75.18	2.84	14.30	V
	6918	-62.50	-40	-22.50	-72.44	3.49	13.43	V
	9225	-61.42	-40	-21.42	-71.66	3.85	14.09	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.