


FCC RADIO TEST REPORT

Applicant..... : Fibocom Wireless Inc.
Address..... : 1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi
1st Rd, Nanshan ShenZhen China
Manufacturer..... : Fibocom Wireless Inc.
Address..... : 1101, Tower A, Building 6, Shenzhen International Innovation Valley, Dashi
1st Rd, Nanshan ShenZhen China
Factory..... : Huizhou HYE Technology Co., Ltd.
Address..... : No. 237, Sanhe group, Sanhe village, Tonghu Town, Zhongkai hi tech
Zone, Huizhou
Product Name..... : LTE Module
Brand Name..... : Fibocom
Model No. : SC138-NA
FCC ID..... : ZMOSC138NA
Measurement Standard..... : 47 CFR FCC Part 15, Subpart C (Section 15.247)
Receipt Date of Samples..... : November 28, 2025
Date of Tested..... : November 25, 2025 to December 16, 2025
Date of Report..... : January 13, 2026

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Alina Guo / Project Engineer



Iori Fan / Authorized Signatory

Table of Contents

1. Summary of Test Result.....	4
2. General Description of EUT	5
3. Test Channels and Modes Detail	8
4. Configuration of EUT	8
5. Modification of EUT	8
6. Description of Support Device.....	9
7. Test Facility and Location	10
8. Applicable Standards and References.....	11
9. Deviations and Abnormalities from Standard Conditions	11
10. Test Conditions	12
11. Measurement Uncertainty	13
12. Sample Calculations	14
13. Test Items and Results	15
13.1 Radiated Spurious Emissions and Restricted Bands Measurement.....	15
13.2 Antenna Requirement	22
14. Test Equipment List.....	23

Revision History

[illegible]

1. Summary of Test Result

FCC Rules	Description of Test	Result	Remarks
§15.207 (a)	AC Power Conducted Emission	N/A	---
§15.247(b)(3)	Maximum Conducted Output Power	N/A	---
§15.247(a)(2)	6dB Bandwidth	N/A	---
§15.247(e)	Power Spectral Density	N/A	---
§15.247(d)	Band Edge and Conducted Spurious Emissions	N/A	---
§15.247(d), §15.209, §15.205	Radiated Spurious Emissions and Restricted Bands	PASS	---
§15.203	Antenna Requirement	PASS	---
Note: N/A means not applicable.			

2. General Description of EUT

Product Information	
Product Name:	LTE Module
Main Model Name:	SC138-NA
Additional Model Name:	N/A
Model difference:	N/A
S/N:	N/A
Brand Name:	Fibocom
Hardware Version:	SC138-NA
Software Version:	SC138-NA-Q62.00.104
Rating:	DC 3.5V ~ 4.2V (DC Voltage supplied from external power supply)
Classification:	Class B
Typical Arrangement:	Table-top
I/O Port:	Refer to the user manual
Accessories Information	
Adapter:	N/A
Cable:	N/A
Other:	N/A
Additional Information	
Note:	N/A
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

Technical Specification (2.4GHz WLAN)	
Frequency Range:	2412-2462MHz for IEEE 802.11b/g/n(HT20) 2422-2452MHz for IEEE 802.11n(HT40)
Modulation Technology:	DSSS, OFDM
Modulation Type:	CCK, DQPSK, DBPSK, QPSK, BPSK, 16-QAM, 64-QAM
Number of Channel:	11 for IEEE 802.11b/g/n(HT20) 7 for IEEE 802.11n(HT40)
Channel Space:	5MHz
Antenna Type:	Rod antenna
Number of Antenna	1
Antenna Gain:	2.35 dBi (Declared by the manufacturer)
Note: This report is applicable to 2.4G wifi technology.	


Channel List			
IEEE 802.11b/ g/ n(HT20)		IEEE 802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	---	---
2	2417	---	---
3	2422	3	2422
4	2427	4	2427
5	2432	5	2432
6	2437	6	2437
7	2442	7	2442
8	2447	8	2447
9	2452	9	2452
10	2457	---	---
11	2462	---	---

3. Test Channels and Modes Detail

Mode		Channel	Frequency (MHz)	Remark
1	TX	1	2412	IEEE 802.11b/ g/ n(HT20)
		3	2422	IEEE 802.11n(HT40)
		6	2437	IEEE 802.11b/ g/ n(HT20)/ n(HT40)
		9	2452	IEEE 802.11n(HT40)
		11	2462	IEEE 802.11b/ g/ n(HT20)
2.	Normal	---	---	---

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

4. Configuration of EUT



5. Modification of EUT

No modifications are made to the EUT during all test items.

6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Brand	M/N	S/N	Cable Specification	Remarks
1.	Laptop	Lenovo	R720-15 1KBN	PF0Z35FH	I/P: AC 100-240V 50-60Hz, 1.5A O/P: DC 20V 6.75A Power cord: 1.10m unshielded DC Line: 1.15m unshielded with a core	Provided by the Lab
2.	Adapter of laptop	Delta	ADL135N DC3A	---		Provided by the Lab
3.	Test fixture	---	---	---	----	Provide by the manufacturer
4.	DC Source	MAYNUO	M8811	0800109601 60105048	----	Provided by the Lab

Software	Power Setting						
	Mode	Setting					
		2412MHz	2422MHz	2437MHz	2437MHz	2462MHz	2452MHz
Qualcomm Radio Control Toolkit v4.0	IEEE 802.11b	17.5	----	17	----	17	----
	IEEE 802.11g	14.5	----	17	----	17	----
	IEEE 802.11n(HT20)	15.0	----	17	----	16	----
	IEEE 802.11n(HT40)	----	15.5	----	16	----	12.5

7. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	The Laboratory has been assessed and proved to be in compliance with CNAS/CL01 Listed by CNAS, August 13, 2018 The Certificate Registration Number is L5795. The Certificate is valid until August 13, 2030 The Laboratory has been assessed and proved to be in compliance with ISO17025 Listed by A2LA, November 01, 2017 The Certificate Registration Number is 4429.01 The Certificate is valid until December 31, 2027 Listed by FCC, November 06, 2017 Test Firm Registration Number: 907417 Listed by ISED, June 08, 2017 The Certificate Registration Number. Is 46405-9743A The CAB identifier number: CN0015
Test Site Location	:	Room 101, 1101, Building 2, No. 61, Hongmei Section, Wangsha Road, Hongmei Town, Dongguan, Guangdong, People's Republic of China

8. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Test Standards:

47 CFR Part 15, Subpart C, 15.247

ANSI C63.10-2020

References Test Guidance:

DTS KDB 558074 D01 15.247 Meas Guidance v05r02

9. Deviations and Abnormalities from Standard Conditions

No additions, deviations and exclusions from the standard.

10. Test Conditions

No.	Test Item	Test Mode	Test Voltage	Tested by	Remarks
1.	AC Power Conducted Emission	---	---	---	---
2.	Max. Conducted Output Power	---	---	---	---
3.	6dB Bandwidth	---	---	---	---
4.	Power Spectral Density	---	---	---	---
5.	Band Edge and Conducted Spurious Emissions	---	---	---	---
6.	Radiated Spurious Emissions and Restricted Bands	1-2	DC 3.8V	Sean	See note 1
7.	Antenna Requirement	---	---	---	---

Note:

1. The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35℃, 30~70%, 86~106kPa
2. DC 3.8V come from DC Source, only the worst case was recorded in the report.

11. Measurement Uncertainty

No.	Test Item	Frequency	Uncertainty	Remarks
1.	Conducted Emission	150KHz ~ 30MHz	±2.46 dB	---
2.	Radiated Emission Test	9kHz ~ 30MHz	±5.63 dB	---
		30MHz ~ 1GHz	±5.63 dB	---
		1GHz ~ 18GHz	±5.16 dB	---
		18GHz ~ 40GHz	±5.16 dB	---
3.	Conducted Spurious Emissions	10Hz ~ 40GHz	±1.06 dB	---
4.	RF Output Power	10Hz ~ 40GHz	±1.08 dB	---
5.	Power Spectral Density	10Hz ~ 40GHz	±1.08 dB	---
6.	Occupied Channel Bandwidth	---	±1.05%	---

Note:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

12. Sample Calculations

Conducted Emission						
Freq. (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
0.1620	17.64	20.56	38.20	55.36	-17.16	QP
Where, Freq. = Emission frequency in MHz Reading Level = Spectrum Analyzer/Receiver reading Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation Measurement = Reading + Corrector Factor Limit = Limit stated in standard Margin = Measurement - Limit Detector = Reading for Quasi-Peak / Average / Peak						

Radiated Spurious Emissions and Restricted Bands						
Freq. (MHz)	Reading Level (dBuV)	Correct Factor (dB/m)	Measurement (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
186.1700	39.33	-8.63	30.70	43.50	-12.80	QP
Where, Freq. = Emission frequency in MHz Reading Level = Spectrum Analyzer/Receiver reading Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier Measurement = Reading + Corrector Factor Limit = Limit stated in standard Over = Margin, which calculated by Measurement - Limit Detector = Reading for Quasi-Peak / Average / Peak						

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

13. Test Items and Results

13.1 Radiated Spurious Emissions and Restricted Bands Measurement

LIMIT of Radiated Band Edges and non-restricted bands

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB.

LIMIT of Restricted bands


In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below:

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)
		$\mu\text{V/m}$
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500


- Remark:
- (1) Emission level (dB) μV = 20 log Emission level $\mu\text{V/m}$
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
 - (5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

BLOCK DIAGRAM OF TEST SETUP


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.



TEST PROCEDURES

- a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.

- b. For the radiated emission test above 1GHz:

The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, deSEC5000CAM2/RP on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Detector	Resolution Bandwidth	Video Bandwidth
0.009~0.15	QP & AVG	200 Hz	1 kHz
0.15~30	QP & AVG	10 kHz	30 kHz
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

TEST RESULTS

PASS


Please refer to the following pages of the worst case.

M/N: SC138-NA	Testing Voltage: DC 3.8V
Polarization: Horizontal	Detector: QP
Test Mode: 1	Distance: 3m

Radiated Emission Measurement

Date: 2025/12/10

Time: 13:07:47



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		296.7500	45.17	-6.87	38.30	46.00	-7.70	QP	
2		320.0300	46.04	-6.24	39.80	46.00	-6.20	QP	
3	*	385.9900	45.22	-4.72	40.50	46.00	-5.50	QP	
4		748.7700	29.68	2.02	31.70	46.00	-14.30	QP	
5		893.3000	26.14	3.96	30.10	46.00	-15.90	QP	
6		927.2500	26.51	4.09	30.60	46.00	-15.40	QP	


Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: SC138-NA	Testing Voltage: DC 3.8V
Polarization: Vertical	Detector: QP
Test Mode: 1	Distance: 3m

Radiated Emission Measurement

Date: 2025/12/10

Time: 13:00:27



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		31.9400	41.66	-10.46	31.20	40.00	-8.80	QP	
2	*	46.4900	43.81	-7.51	36.30	40.00	-3.70	QP	
3		385.0200	40.85	-4.75	36.10	46.00	-9.90	QP	
4		872.9300	29.90	3.80	33.70	46.00	-12.30	QP	
5		903.0000	27.90	4.00	31.90	46.00	-14.10	QP	
6		957.3200	27.84	4.26	32.10	46.00	-13.90	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

Modulation: TX (IEEE 802.11b)				Test Result: PASS			Test frequency range: 1-25GHz			
Freq. (MHz)	Ant. Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)										
4824	V	44.97	30.57	3.92	48.89	34.49	74.00	54.00	-25.11	-19.51
7236	V	45.42	31.49	8.75	54.17	40.24	74.00	54.00	-19.83	-13.76

4824	H	45.36	30.51	3.92	49.28	34.43	74.00	54.00	-24.72	-19.57
7236	H	45.51	31.42	8.75	54.26	40.17	74.00	54.00	-19.74	-13.83

Operation Mode: TX Mode (Mid)										
4874	V	45.18	31.16	4.02	49.20	35.18	74.00	54.00	-24.80	-18.82
7311	V	44.65	31.76	8.97	53.62	40.73	74.00	54.00	-20.38	-13.27

4874	H	44.74	30.91	4.02	48.76	34.93	74.00	54.00	-25.24	-19.07
7311	H	44.84	31.89	8.97	53.81	40.86	74.00	54.00	-20.19	-13.14

Operation Mode: TX Mode (High)										
4924	V	44.95	31.60	4.12	49.07	35.72	74.00	54.00	-24.93	-18.28
7386	V	45.38	31.62	9.19	54.57	40.81	74.00	54.00	-19.43	-13.19

4924	H	44.68	30.82	4.12	48.80	34.94	74.00	54.00	-25.20	-19.06
7386	H	44.56	31.38	9.19	53.75	40.57	74.00	54.00	-20.25	-13.43

Spurious Emission in restricted band										
2390.000	V	61.17	33.88	-2.98	58.19	30.90	74.00	54.00	-15.81	-23.10
2390.000	H	56.81	33.48	-2.98	53.83	30.50	74.00	54.00	-20.17	-23.50
2483.500	V	49.72	36.58	-2.84	46.88	33.74	74.00	54.00	-27.12	-20.26
2483.500	H	48.64	36.42	-2.84	45.80	33.58	74.00	54.00	-28.20	-20.42

Remark: 1. All the points within the restricted band are lower than the edge punctuation of the restricted band shown in the data.

2. Data of measurement within this frequency range shown "----" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits.

13.2 Antenna Requirement

STANDARD APPLICABLE

According to of FCC part 15C section 15.203 and 15.247:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

ANTENNA CONNECTED CONSTRUCTION

The antenna is Rod antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is 2.35dBi, Therefore, the antenna is considered to meet the requirement.

14. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	101152	Aug. 21, 2025	1 Year
2.	L.I.S.N	Rohde & Schwarz	ENV 216	101317	Aug. 21, 2025	1 Year
3.	L.I.S.N	Schwarzbeck	NNLK8129	00558	Aug. 23, 2025	1 Year
4.	RF Switching Unit	Compliance Direction Systems Inc.	RSU-M2	38311	Aug. 21, 2025	1 Year
5.	Test Receiver	Rohde & Schwarz	ESCI7	100837	Aug. 21, 2025	1 Year
6.	Spectrum Analyzer	Keysight	N9020A	MY50510314	Aug. 21, 2025	1 Year
7.	Spectrum Analyzer	Keysight	N9020A	MY54200831	Aug. 22, 2025	1 Year
8.	Spectrum Analyzer	Keysight	N9010B	MY62170254	Aug. 21, 2025	1 Year
9.	Antenna	Schwarzbeck	VULB9163	01552	Aug. 16, 2025	2 Year
10.	Loop Antenna	Schwarzbeck	FMZB 1513	1513-272	Aug. 16, 2025	2 Year
11.	Horn Antenna	COM-Power	AH-118	071078	Aug. 16, 2025	2 Year
12.	Pre-Amplifier	HP	HP 8447D	1145A00203	Aug. 21, 2025	1 Year
13.	Pre-Amplifier	HP	HP 8449B	3008A00964	Aug. 23, 2025	1 Year
14.	Communication Tester	Rohde & Schwarz	CMW500	109851	Aug. 28, 2025	1 Year
15.	Power Sensor	DARE	RPR3006W	15I00041SNO 64	Aug. 28, 2025	1 Year
16.	Power Meter	Agilent	N1912A	MY41497159	Aug. 21, 2025	1 Year
17.	Power Sensor	Agilent	N1921A	MY48251036	Aug. 21, 2025	1 Year
18.	Horn Antenna	COM-Power	AH-840	10100020	Aug. 28, 2025	2 Year
19.	Temperature & Humidity Chamber	Wanshun	SS-HWHS-80	N/A	Aug. 09, 2025	1 Year
20.	DC Source	ZHAOXIN	KXN305D	N/A	Aug. 23, 2025	1 Year
21.	Temporary antenna connector	TESCOM	SS402	N/A	N/A	N/A
22.	Chamber	YIHENG	9*6*6m	N/A	Sep. 22, 2025	2 Year
23.	Test Software	MWRF	MTS 8310, V2.0.0.0	N/A	N/A	N/A
24.	Test Software	EZ	EZ EMC, NTC-3A1.1	N/A	N/A	N/A

Note: For photographs of EUT and measurement, please refer to appendix in separate documents.

---End---