



深圳市博格斯通信技术有限公司
shenzhen bogesi communication technology co., ltd

Product specification

客 户: Shenzhen Fibocom Wireless Co., Ltd.

客户编码: _____

产品描述: 5G external rubber sleeve antenna

制造商编码: GHT-019A (RA version)

产品制造商: Shenzhen Bogesi Communication Technology Co., Ltd.

承认日期: 2021/8/9

Supplier signature	Customer signature
	

Note: 1. After the electronic file or paper file that has been stamped by Bogesi is provided to the demander, the demander shall sign the paper or electronic file back to Bogesi before placing the formal order to Boggs. If there is no formal change or change notification, Bogesi defaults to the requester's approval and acceptance of the product described in the specification.

2. The related intellectual property rights of this product belong to Shenzhen Bogus Communication Technology Co., Ltd. Without our permission, please do not apply for patent rights for this product in other names, and please do not disclose this product and related information to others Or provide third-party reading and use.



深圳市博格斯通信技术有限公司

shenzhen bogesi communication technology co.,ltd

Use range:

Applicable to Shenzhen Fibocom Wireless Co., Ltd. 5G antenna solution.

Antenna Model Name:GHT-019A

Antenna Type: Dipole

Antenna Gain: 2.4GHz: 1.63dBi, 5.2GHz: 4.29dBi, 5.3GHz: 4.43dBi, 5.6GHz: 3.68dBi

Electrical Specifications:

Electrical Specifications	700-1000MHz;1400-6000MHz	Material	ABS
input resistance	50 Ω	Plastic material	Rubber cap:ABS
Standing wave ratio	≤ 3.0		Adapter 1: ABS
Polarization mode	Linear polarization		Adapter 2:ABS
Operating temperature	- 40 $^{\circ}\text{C}$ ~ + 65 $^{\circ}\text{C}$	RF cable specifications	RG-178
Storage temperature	- 40 $^{\circ}\text{C}$ ~ + 80 $^{\circ}\text{C}$	Connector specifications	SMA Male J
Connector torque test	200 ~ 1000 g.cm	Joint tension test	SMA $\geq$ 3 Kg
Gain	700-1000MHz:1.17dBi	Connector torque test	200 ~ 1000 g.cm
	1400-1690MHz:3.21dBi		
	1700-2000MHz:3.10dBi		
	2010-2480MHz:3.36dBi		
	2490-2750/3350-3570MHz:2.56dBi		
	3580-3850MHz:2.99dBi		
	5000-5490MHz:4.49dBi		
	5500-6000MHz:3.32dBi		

Test conditions and methods:

Test conditions and instruments	Test Methods	Test Results
Microwave anechoic chamber far-field test system Aglient E5071B network analyzer	1. Assemble the antenna to be tested on the prototype and make a passive test fixture 2. Put the passive fixture on the test fixture in the dark room and establish a connection with the network analyzer 3. Use test software to test antenna passive data	See test data



深圳市博格斯通信技术有限公司

shenzhen bogesi communication technology co.,ltd

Test data:

BGS-036(700-1000)_30du	Frequency (MHz)	Directivity (dBi)	Avg Gain(dBi)	Efficiency (%)	Peak Gain(dBi)
	700	4.06	-4.12	38.75	-0.06
	710	4.27	-4.09	39.04	0.19
	720	4.40	-3.87	41.02	0.53
	730	4.42	-3.71	42.52	0.71
	740	4.49	-3.75	42.14	0.74
	750	4.52	-3.91	40.62	0.60
	760	4.60	-3.93	40.44	0.66
	770	4.65	-3.90	40.76	0.76
	780	4.57	-3.65	43.11	0.92
	790	4.29	-3.34	46.32	0.94
	800	3.85	-3.12	48.71	0.72
	810	3.38	-2.97	50.49	0.41
	820	2.98	-2.82	52.19	1.42
	830	2.64	-2.65	54.28	1.55
	840	2.33	-2.35	58.15	1.61
	850	2.03	-1.91	64.47	1.66
	860	1.72	-1.46	71.43	1.61
	870	1.85	-1.13	77.15	1.55
	880	2.20	-1.02	79.03	1.17
	890	2.30	-1.21	75.66	1.91
	900	2.24	-1.58	69.49	0.66
	910	2.08	-1.83	65.60	0.25
	920	1.94	-2.10	61.70	-0.16
	930	2.01	-2.33	58.51	-0.32
	940	2.29	-2.63	54.60	-0.34
	950	2.63	-3.17	48.21	-0.54
	960	2.84	-4.02	39.59	-1.19
	970	2.86	-5.11	30.86	-2.25
	980	2.83	-6.14	24.34	-3.31
	990	2.96	-7.09	19.55	-4.13
	1000	3.30	-7.55	17.57	-4.26

BGS-036(1400-1690)_30du	Frequency (MHz)	Directivity (dBi)	Avg Gain(dBi)	Efficiency (%)	Peak Gain(dBi)
	1400	3.67	-0.82	82.77	1.85
	1410	3.49	-0.88	81.60	1.61
	1420	3.34	-0.92	80.85	1.42
	1430	3.35	-0.76	83.95	1.59
	1440	3.51	-0.57	87.70	1.94
	1450	3.71	-0.49	89.24	1.22
	1460	3.88	-0.51	88.83	1.36
	1470	3.90	-0.74	84.33	1.16
	1480	3.81	-0.89	81.41	1.92
	1490	3.68	-0.98	79.86	1.70
	1500	3.63	-0.85	82.17	1.78
	1510	3.70	-0.76	84.04	2.94
	1520	3.84	-0.73	84.47	3.10
	1530	3.92	-0.71	84.83	3.21
	1540	3.91	-1.01	79.19	2.90
	1550	3.87	-1.21	75.68	2.66
	1560	3.81	-1.33	73.68	2.48
	1570	3.80	-1.28	74.45	2.52
	1580	3.87	-1.10	77.67	2.77
	1590	3.99	-0.96	80.24	3.04
	1600	4.09	-0.99	79.62	3.10
	1610	4.13	-1.14	76.92	2.99
	1620	4.13	-1.32	73.76	2.81
	1630	4.12	-1.53	70.25	2.59
	1640	4.16	-1.56	69.82	2.60
	1650	4.31	-1.43	71.93	2.88
	1660	4.46	-1.27	74.63	2.19
	1670	4.60	-1.10	77.58	2.50
	1680	4.72	-1.09	77.74	2.62
	1690	4.79	-1.16	76.54	2.63

BGS-036(1700-2000)_30du	Frequency (MHz)	Directivity (dBi)	Avg Gain(dBi)	Efficiency (%)	Peak Gain(dBi)
	1700	4.84	-0.99	79.71	1.81
	1710	4.87	-1.13	77.05	1.88
	1720	4.89	-1.03	78.81	1.86
	1730	4.88	-1.00	79.47	1.89
	1740	4.86	-0.92	80.92	1.94
	1750	4.80	-0.98	79.75	1.82
	1760	4.70	-1.12	77.25	1.58
	1770	4.64	-1.35	73.33	1.29
	1780	4.59	-1.48	71.12	1.11
	1790	4.58	-1.48	71.06	2.10
	1800	4.59	-1.51	70.55	3.08
	1810	4.60	-1.50	70.86	3.10
	1820	4.60	-1.61	68.98	2.99
	1830	4.59	-1.78	66.43	2.81
	1840	4.56	-1.92	64.24	2.64
	1850	4.57	-2.07	62.06	2.50
	1860	4.59	-2.09	61.82	2.50
	1870	4.63	-2.03	62.66	2.63
	1880	4.66	-1.89	64.75	1.77
	1890	4.64	-1.79	66.19	1.85
	1900	4.58	-1.84	65.45	1.74
	1910	4.50	-1.92	64.22	1.80
	1920	4.41	-2.13	61.20	1.33
	1930	4.31	-2.25	59.50	1.44
	1940	4.23	-2.36	58.01	1.42
	1950	4.18	-2.23	59.88	1.33
	1960	4.10	-2.27	59.32	1.33
	1970	3.97	-2.35	58.17	1.42
	1980	3.89	-2.49	56.35	1.40
	1990	3.85	-2.70	53.71	1.15
	2000	3.89	-2.82	52.24	1.07

BGS-036(2010-2480)_30du	Frequency (MHz)	Directivity (dBi)	Avg Gain(dBi)	Efficiency (%)	Peak Gain(dBi)
	2010	3.96	-2.82	52.22	1.14
	2020	4.09	-2.69	53.82	1.40
	2030	4.18	-2.53	55.84	1.65
	2040	4.19	-2.45	56.95	1.75
	2050	4.17	-2.46	56.74	1.71
	2060	4.14	-2.49	56.37	1.65
	2070	4.16	-2.60	54.96	1.56
	2080	4.21	-2.67	54.13	1.54
	2090	4.29	-2.74	53.26	1.55
	2100	4.35	-2.68	53.90	1.67
	2110	4.36	-2.83	52.08	1.53
	2120	4.30	-3.00	50.09	1.30
	2130	4.23	-3.16	48.29	1.07
	2140	4.20	-3.32	46.54	0.88
	2150	4.25	-3.33	46.42	0.92
	2160	4.36	-3.30	46.80	1.07
	2170	4.47	-3.16	48.33	1.31
	2180	4.52	-2.98	50.40	1.54
	2190	4.50	-2.84	52.00	1.66
	2200	4.46	-2.70	53.68	1.76
	2210	4.43	-2.66	54.21	1.77
	2220	4.50	-2.51	56.17	2.00
	2230	4.60	-2.22	60.04	2.39
	2240	4.69	-1.81	65.86	2.88
	2250	4.66	-1.39	72.60	3.27
	2260	4.53	-1.17	76.43	3.36
	2270	4.34	-1.06	78.36	3.28
	2280	4.19	-1.18	76.19	3.01
	2290	4.14	-1.23	75.29	2.91
	2300	4.13	-1.38	72.78	2.75
	2310	4.15	-1.45	71.54	2.70
	2320	4.12	-1.47	71.23	2.65
	2330	3.96	-1.55	69.94	2.40
	2340	3.74	-1.59	69.41	2.15
	2350	3.57	-1.76	66.70	1.81
	2360	3.47	-1.87	65.07	1.60
	2370	3.48	-1.89	64.71	1.59
	2380	3.51	-1.89	64.65	1.62
	2390	3.55	-1.84	65.49	1.71
	2400	3.50	-1.87	65.04	1.63
	2410	3.37	-1.87	65.08	1.51
	2420	3.30	-1.96	63.67	1.34
	2430	3.26	-2.10	61.64	1.16
	2440	3.28	-2.08	61.89	1.20
	2450	3.39	-2.03	62.62	1.35
	2460	3.48	-1.86	65.23	1.62
	2470	3.49	-1.66	68.19	1.83
	2480	3.47	-1.43	71.97	1.04

	Frequency (MHz)	Directivity (dBi)	Avg Gain(dBi)	Efficiency (%)	Peak Gain(dBi)
BGS- 036(2490- 2750,3350- 3570)_30du	2490	3.36	-1.27	74.58	1.08
	2500	3.34	-1.24	75.22	1.10
	2510	3.40	-1.25	74.91	1.14
	2520	3.42	-1.30	74.20	1.13
	2530	3.44	-1.30	74.18	1.52
	2540	3.47	-1.20	75.86	1.27
	2550	3.56	-1.16	76.53	0.98
	2560	3.61	-1.17	76.46	1.07
	2570	3.64	-1.29	74.23	1.35
	2580	3.64	-1.36	73.06	1.28
	2590	3.52	-1.48	71.18	1.04
	2600	3.40	-1.56	69.79	1.83
	2610	3.34	-1.69	67.81	1.66
	2620	3.31	-1.79	66.17	1.52
	2630	3.38	-1.84	65.48	1.54
	2640	3.43	-1.98	63.45	1.46
	2650	3.42	-2.09	61.79	1.33
	2660	3.37	-2.13	61.27	1.24
	2670	3.30	-2.23	59.78	1.06
	2680	3.25	-2.22	60.02	1.04
	2690	3.27	-2.18	60.47	1.09
	2700	3.30	-2.17	60.62	1.12
	2710	3.36	-2.07	62.04	1.29
	2720	3.37	-2.07	62.06	1.30
	2730	3.34	-2.12	61.36	1.22
	2740	3.30	-2.19	60.42	1.12
	2750	3.45	-2.13	61.18	1.32
	3350	3.25	-1.77	66.50	1.48
	3360	3.27	-1.70	67.67	1.57
	3370	3.26	-1.68	67.85	1.58
	3380	3.19	-1.72	67.31	1.47
	3390	3.11	-1.65	68.38	1.46
	3400	3.02	-1.61	68.98	1.41
	3410	2.98	-1.57	69.71	1.41
	3420	2.90	-1.51	70.65	1.39
	3430	2.80	-1.53	70.38	1.27
	3440	2.88	-1.53	70.26	1.35
	3450	3.03	-1.50	70.84	1.54
	3460	3.26	-1.45	71.60	1.81
	3470	3.59	-1.39	72.61	2.25
	3480	3.91	-1.35	73.33	2.56
	3490	4.12	-1.37	73.01	1.75
	3500	4.32	-1.40	72.46	1.93
	3510	4.44	-1.51	70.69	1.94
	3520	4.53	-1.64	68.60	1.89
	3530	4.71	-1.63	68.66	1.07
	3540	4.87	-1.63	68.76	1.24
	3550	5.01	-1.50	70.78	1.51
	3560	5.15	-1.34	73.44	1.81
	3570	5.20	-1.22	75.57	1.99

	Frequency (MHz)	Directivity (dBi)	Avg Gain(dBi)	Efficiency (%)	Peak Gain(dBi)
BGS- 036(3580- 3850)_30du	3580	5.21	-1.17	76.38	2.04
	3590	5.08	-1.24	75.16	1.84
	3600	5.02	-1.28	74.56	1.74
	3610	4.92	-1.36	73.07	1.56
	3620	4.90	-1.40	72.47	1.50
	3630	4.85	-1.45	71.69	1.41
	3640	4.86	-1.51	70.57	1.35
	3650	4.79	-1.60	69.23	1.19
	3660	4.76	-1.64	68.51	1.12
	3670	4.76	-1.70	67.68	1.07
	3680	4.76	-1.67	68.15	1.09
	3690	4.86	-1.65	68.36	1.21
	3700	4.86	-1.70	67.53	1.16
	3710	4.75	-1.85	65.26	1.90
	3720	4.65	-1.88	64.90	1.77
	3730	4.56	-1.97	63.58	1.99
	3740	4.58	-1.95	63.80	2.33
	3750	4.58	-1.90	64.59	2.55
	3760	4.76	-1.80	66.04	2.99
	3770	4.89	-1.66	68.18	2.88
	3780	4.88	-1.60	69.21	2.21
	3790	4.75	-1.59	69.31	1.99
	3800	4.71	-1.61	69.07	1.10
	3810	4.49	-1.70	67.61	2.79
	3820	4.41	-1.69	67.72	2.72
	3830	4.40	-1.72	67.30	2.68
	3840	4.44	-2.01	62.88	2.43
	3850	4.41	-1.70	67.58	2.70

	Frequency	Directivi	Avg	Efficienc	Peak
	(MHz)	ty (dBi)	Gain(dBi)	y (%)	Gain(dBi)
BCS-036 (5000-5490)_30da	5000	6.12	-1.81	65.87	4.31
	5010	6.15	-1.83	65.59	4.32
	5020	6.13	-1.80	66.05	4.32
	5030	6.12	-1.89	64.65	4.23
	5040	6.14	-2.09	61.78	4.05
	5050	6.09	-2.09	61.74	3.99
	5060	6.09	-2.09	61.74	4.00
	5070	6.02	-2.04	62.56	3.98
	5080	6.11	-2.07	62.13	4.04
	5090	6.12	-2.07	62.07	4.05
	5100	6.13	-2.04	62.55	4.09
	5110	6.17	-2.00	63.11	4.17
	5120	6.17	-2.08	61.96	4.09
	5130	6.21	-2.08	61.90	4.13
	5140	6.26	-2.14	61.05	4.12
	5150	6.32	-2.26	59.39	4.06
	5160	6.31	-2.13	61.26	4.18
	5170	6.34	-2.20	60.31	4.15
	5180	6.29	-2.20	60.32	4.09
	5190	6.39	-2.20	60.28	4.19
	5200	6.41	-2.23	59.77	4.17
	5210	6.40	-2.244	59.67	4.15
	5220	6.40	-2.12	61.40	4.29
	5230	6.42	-2.20	60.32	4.22
	5240	6.45	-2.22	59.91	4.22
	5250	6.49	-2.28	59.18	4.21
	5260	6.47	-2.33	58.45	4.14
	5270	6.45	-2.37	57.99	4.08
	5280	6.52	-2.31	58.73	4.21
	5290	6.60	-2.34	58.33	4.25
	5300	6.66	-2.36	58.13	4.30
	5310	6.68	-2.37	57.89	4.31
	5320	6.68	-2.31	58.70	4.36
	5330	6.69	-2.26	59.47	4.43
	5340	6.71	-2.28	59.10	4.43
	5350	6.70	-2.29	58.97	4.40
	5360	6.73	-2.26	59.37	4.46
	5370	6.74	-2.25	59.59	4.49
	5380	6.77	-2.31	58.79	4.47
	5390	6.78	-2.35	58.26	4.44
	5400	6.79	-2.45	56.87	4.34
	5410	6.79	-2.50	56.20	4.29
	5420	6.74	-2.58	55.27	4.17
	5430	6.70	-2.61	54.81	4.09
	5440	6.70	-2.73	53.32	3.97
	5450	6.61	-2.72	53.49	3.89
	5460	6.57	-2.80	52.53	3.77
	5470	6.51	-2.83	52.14	3.68
	5480	6.49	-2.83	52.08	3.66
	5490	6.36	-2.88	51.49	3.47


	Frequency	Directivi	Avg	Efficienc	Peak
	(MHz)	ty (dBi)	Gain(dBi)	y (%)	Gain(dBi)
BCS-036 (5500-6000)_30da	5500	6.30	-2.98	50.41	3.32
	5510	6.24	-3.07	49.35	3.17
	5520	6.17	-3.15	48.37	3.02
	5530	6.07	-3.18	48.14	2.89
	5540	5.97	-3.19	48.00	2.78
	5550	5.83	-3.18	48.05	2.65
	5560	5.75	-3.18	48.05	2.56
	5570	5.61	-3.25	47.30	2.36
	5580	5.56	-3.26	47.21	2.30
	5590	5.42	-3.30	46.82	2.12
	5600	5.26	-3.32	46.61	1.94
	5620	4.85	-3.19	47.96	1.66
	5630	4.65	-3.19	47.94	1.45
	5640	4.55	-3.20	47.84	1.34
	5650	4.48	-3.27	47.15	1.21
	5660	4.33	-3.21	47.72	1.12
	5670	4.25	-3.10	48.94	1.15
	5680	3.97	-2.98	50.33	0.99
	5690	3.90	-2.93	50.99	0.98
	5700	3.90	-2.89	51.42	1.01
	5710	4.11	-2.94	50.81	1.17
	5720	4.10	-2.97	50.42	1.13
	5730	4.02	-3.00	50.08	1.01
	5740	4.03	-2.89	51.42	1.14
	5750	4.03	-2.86	51.74	1.17
	5760	4.14	-2.83	52.08	1.31
	5770	4.02	-2.84	52.04	1.19
	5780	4.01	-2.88	51.54	1.13
	5790	4.05	-2.92	51.07	1.14
	5800	4.11	-2.92	51.01	1.19
	5810	4.09	-2.93	50.94	1.16
	5820	4.12	-2.90	51.27	1.22
	5830	4.17	-2.90	51.32	1.28
	5840	4.05	-2.83	52.12	1.22
	5850	4.18	-2.71	53.63	1.47
	5860	4.22	-2.78	52.69	1.44
	5870	4.27	-2.80	52.43	1.46
	5880	4.17	-2.83	52.15	1.34
	5890	4.07	-2.76	52.93	1.30
	5900	4.03	-2.70	53.67	1.33
	5910	3.97	-2.65	54.27	1.31
	5920	3.92	-2.71	53.52	1.21
	5930	3.92	-2.85	51.93	1.08
	5940	3.84	-2.91	51.14	0.92
	5950	3.71	-2.95	50.66	0.76
	5960	3.80	-2.90	51.24	0.90
	5970	3.83	-2.81	52.36	1.02
	5980	3.81	-2.78	52.76	1.04
	5990	3.77	-2.81	52.31	0.96
	6000	3.80	-2.83	52.07	0.96




深圳市博格斯通信技术有限公司


shenzhen bogesi communication technology co.,ltd

Direction map:









2170 MHz




2170 MHz




2170 MHz




2170MHZ






2690 MHz






2690 MHz




2690 MHz




2690MHZ




3350MHZ






3350 MHz






3350 MHz




3350 MHz




3350MHZ




3350MHZ




E1




E2




H




3800MHZ




E1




E2




H




5370MHZ




E1



E2



H






6000MHZ






Direction map:




700






750






800






850






1570






2170






2400






2500






3000






3500






4000






4500






5000



5500



6000






深圳市博格斯通信技术有限公司

shenzhen bogesi communication technology co.,ltd

Sample Pictures:





深圳市博格斯通信技术有限公司
shenzhen bogesi communication technology co.,ltd

Antenna packaging instructions

1. Outer packaging: carton packaging

Front view:



side view:



2. Inner packaging (1PCS/PE ziplock bag, 50PCS/bag, the size of the bag depends on the product size)

