



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Fibocom Wireless Inc.

Address: 1101, Tower A, Building 6, Shenzhen International Innovation Valley,
Dashi 1st Rd, Nanshan, ShenZhen, China

FCC ID: ZMQSQ808NA

Product Name: LTE Module

Standard(s): 47 CFR Part 15, Subpart C(15.247)

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR231167139-00A

Date Of Issue: 2024/3/16

Reviewed By: Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,

Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

DOCUMENT REVISION HISTORY	5
1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	6
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.1 EUT Operation Condition:.....	8
1.2.2 Support Equipment List and Details	8
1.2.3 Support Cable List and Details	8
1.2.4 Block Diagram of Test Setup.....	8
1.3 MEASUREMENT UNCERTAINTY	10
2. SUMMARY OF TEST RESULTS	11
3. REQUIREMENTS AND TEST PROCEDURES	12
3.1 AC LINE CONDUCTED EMISSIONS.....	12
3.1.1 Applicable Standard.....	12
3.1.2 EUT Setup.....	13
3.1.3 EMI Test Receiver Setup	13
3.1.4 Test Procedure	14
3.1.5 Corrected Amplitude & Margin Calculation.....	14
3.2 RADIATION SPURIOUS EMISSIONS.....	15
3.2.1 Applicable Standard.....	15
3.2.2 EUT Setup.....	15
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
3.2.4 Test Procedure	17
3.2.5 Corrected Amplitude & Margin Calculation.....	17
3.3 MINIMUM 6 DB BANDWIDTH.....	18
3.3.1 Applicable Standard.....	18
3.3.2 EUT Setup.....	18
3.3.3 Test Procedure	18
3.4 MAXIMUM CONDUCTED OUTPUT POWER.....	19
3.4.1 Applicable Standard.....	19
3.4.2 EUT Setup.....	19
3.5.3 Test Procedure	19
3.5 MAXIMUM POWER SPECTRAL DENSITY.....	20
3.5.1 Applicable Standard.....	20
3.5.2 EUT Setup.....	20
3.5.3 Test Procedure	20
3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE.....	21
3.6.1 Applicable Standard.....	21
3.6.2 EUT Setup.....	21
3.6.3 Test Procedure	21
3.7 DUTY CYCLE	22
3.7.1 EUT Setup.....	22
3.7.2 Test Procedure	22

3.8 ANTENNA REQUIREMENT.....	22
3.8.1 Applicable Standard.....	22
3.8.2 Judgment.....	22
4. Test DATA AND RESULTS.....	23
4.1 AC LINE CONDUCTED EMISSIONS.....	23
4.2 RADIATION SPURIOUS EMISSIONS.....	26
4.3 SPOT CHECK FOR MAXIMUM CONDUCTED OUTPUT POWER:	41
4.4 DUTY CYCLE:.....	42
5. RF EXPOSURE EVALUATION	43
5.1 APPLICABLE STANDARD.....	43
6. EUT PHOTOGRAPHS	44
7. TEST SETUP PHOTOGRAPHS	45

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR231167139-00A	Class II Permissive Change Report	2024/3/16

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	LTE Module
EUT Model:	SQ808-NA
Operation Frequency:	2402-2480 MHz
Maximum Peak Output Power (Conducted):	1.87 dBm
Modulation Type:	GFSK
Rated Input Voltage:	5Vdc from Adapter or 7.4Vdc from battery
Serial Number:	2DS1-1 (For RF Conducted Test&Screen 1#) 2DS1-6 (For RE/CE Test&Screen 1#)
EUT Received Date:	2023/11/17
EUT Received Status:	Good
Test Purpose:	
This is Class II permissive Change application for FCC ID: ZMOSQ808NA certified on 08/05/2020. The change was below, which was provided by manufacturer ▲ :	
1. Build the module into the certified host, host FCC ID: XKB-DX4CL4GWBT.	
Per Spot check with the RF output power, the change not affect the RF parameters, so AC line conducted emission and radiated spurious emission were tested in this report.	

Operation Frequency Detail: For BLE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2402	
Middle		2440	
Highest		2480	

Antenna Information Detail▲:

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Fuzhou ZHONGTIANXUN communication technology Co., Ltd	IFA	50	2.4~2.5GHz	3.66 dBi
The Method of §15.203 Compliance:				
☒ Antenna was permanently attached to the unit. ☐ Antenna use a unique type of connector to attach to the EUT. ☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

Host Configuration Detail:

Configuration	Item	Manufacturer	Model
1#	Screen	GuangDonghongbosheng Optoelectronic Technology Co.,Ltd.	MDT0500L
2#	Screen	GuangDonghongbosheng Optoelectronic Technology Co.,Ltd.	MDT0500M
3#	Screen	Shenzhen Great Prospect Optoelectronics Co.,Ltd.	MDT0500N

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter 1#	Xiamen Keli Electronics Co.,Ltd.	SW-0983	Input: 100-240V~50/60Hz, 0.5A Output: 5.0V, 2.0A
Adapter 2#	Jiangxi Jian Aohai Technology Co.,Ltd.	A319-050200U-US2	Input: 100-240V~50/60Hz,0.3A Output: 5.0V, 2.0A
Adapter 3#	SHENZHEN KEYU POWER SUPPLY TECHNOLOGY CO.,LTD.	KA12C-0502000US	Input: 100-240V~50/60Hz, 0.35A Output: 5.0V, 2000mA

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For BLE:

EUT Operation Mode:	The system was configured for testing in Engineering Mode, which was provided by the manufacturer. Tests was performed with the Screen 1#+Adapter 1# , because it was the worst which was base on Host test report:CR231167140-00B.		
Equipment Modifications:	No		
EUT Exercise Software:	QRCT3		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
BLE	Default	Default	Default

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1.2	Adapter 1#	EUT

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Radiated Spurious Emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 4.12dB, 30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result	Note
§15.207(a)	AC line conducted emissions	Compliant	/
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant	/
§15.247 (a)(2)	Minimum 6 dB Bandwidth	Note*	Original report page 17~20
§15.247(b)(3)	Maximum Conducted Output Power	Compliant	Reporting
§15.247(e)	Power Spectral Density	Note*	Original report page 21~23
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Note*	Original report page 24~26
§15.203	Antenna Requirement	Compliant	/
§15.247 (i) & §1.1310	RF Exposure Evaluation	Compliant	/

Note*: per spot check with the output power, the RF parameters identical with the original module, the result please refer to the original report: ZR/2020/6002803, which was released by SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided in the original report.

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


3.2.2 EUT Setup

9kHz~30MHz:



30MHz-1GHz:



Above 1GHz:

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz- 1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W
9 kHz – 150 kHz	QP/AV	300 Hz	1 kHz	200 Hz
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz
30 MHz – 1000 MHz	QP	/	/	120 kHz
	PK	100 kHz	300 kHz	/

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

The spurious emissions which below the limit more than 20dB was not be recorded.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9 – 90 kHz, 110 – 490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

The spurious emissions which below the limit more than 20dB was not be recorded.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 Minimum 6 dB Bandwidth

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3.4 Maximum Conducted Output Power

3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.4.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.


3.5 Maximum power spectral density

3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.6 100 kHz Bandwidth of Frequency Band Edge

3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.6.2 EUT Setup



3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.7 Duty Cycle

3.7.1 EUT Setup



3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.8 Antenna Requirement

3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.8.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	2DS1-6	Test Date:	2023/12/11
Test Site:	CE	Test Mode:	Transmitting (maximum output power mode (Middle channel) was tested)
Tester:	David Huang	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	27.1	Relative Humidity: (%)	52	ATM Pressure: (kPa)	100.9
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2023/3/31	2024/3/30
R&S	EMI Test Receiver	ESR3	102726	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2023/8/6	2024/8/5
Audix	Test Software	E3	190306 (V9)	N/A	N/A


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Project No.: CR231167139-RF
Tester: David Huang
Port: Line
Note: Transmitting(BLE)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.152	24.79	9.61	34.40	55.91	21.51	Average
2	0.152	38.84	9.61	48.45	65.91	17.46	QP
3	0.259	21.29	9.61	30.90	51.46	20.56	Average
4	0.259	37.41	9.61	47.02	61.46	14.44	QP
5	0.303	25.13	9.61	34.74	50.16	15.42	Average
6	0.303	40.27	9.61	49.88	60.16	10.28	QP
7	0.454	24.94	9.61	34.55	46.80	12.25	Average
8	0.454	37.87	9.61	47.48	56.80	9.32	QP
9	0.606	25.71	9.62	35.33	46.00	10.67	Average
10	0.606	39.96	9.62	49.58	56.00	6.42	QP
11	0.752	25.72	9.62	35.34	46.00	10.66	Average
12	0.752	38.47	9.62	48.09	56.00	7.91	QP

Project No.: CR231167139-RF
 Tester: David Huang
 Port: neutral
 Note: Transmitting(BLE)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.151	26.37	9.61	35.98	55.92	19.94	Average
2	0.151	41.51	9.61	51.12	65.92	14.80	QP
3	0.192	24.92	9.61	34.53	53.94	19.41	Average
4	0.192	40.88	9.61	50.49	63.94	13.45	QP
5	0.257	22.20	9.61	31.81	51.54	19.73	Average
6	0.257	38.69	9.61	48.30	61.54	13.24	QP
7	0.301	25.14	9.61	34.75	50.21	15.46	Average
8	0.301	40.77	9.61	50.38	60.21	9.83	QP
9	0.603	25.88	9.62	35.50	46.00	10.50	Average
10	0.603	39.64	9.62	49.26	56.00	6.74	QP
11	0.764	21.72	9.62	31.34	46.00	14.66	Average
12	0.764	33.97	9.62	43.59	56.00	12.41	QP

4.2 Radiation Spurious Emissions

Serial Number:	2DS1-6	Test Date:	2024/1/4
Test Site:	966-1/966-2	Test Mode:	Transmitting
Tester:	Jeff Luo, Mack Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.2~25.7	Relative Humidity: (%)	43~59	ATM Pressure: (kPa)	101.5
----------------------	-----------	---------------------------	-------	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2023/12/1	2026/11/30
BACL	Loop Antenna	1313-1P	3092721	2023/10/20	2026/10/19
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
Audix	Test Software	E3	201021 (V9)	N/A	N/A
AH	Double Ridge Guide Horn Antenna	SAS-571	1394	2023/2/22	2026/2/21
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2023/11/8	2024/11/7
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2023/9/15	2024/9/14
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2023/8/6	2024/8/5
Mini Circuits	High Pass Filter	VHF-6010+	31119	2023/8/6	2024/8/5

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:


1) 9kHz~30MHz:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

2) 30MHz-1GHz


Low channel:

Project No.: CR231167139-RF
Tester: Jeff Luo
Polarization: horizontal
Note: Transmitting(BLE 1Mbps Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.000	28.29	-3.87	24.42	40.00	15.58	Peak
2	86.503	41.94	-17.24	24.70	40.00	15.30	Peak
3	119.018	40.53	-11.41	29.12	43.50	14.38	Peak
4	195.137	51.96	-13.33	38.63	43.50	4.87	Peak
5	346.809	50.49	-9.66	40.83	46.00	5.17	QP
6	443.294	37.42	-6.89	30.53	46.00	15.47	Peak


Project No.: CR231167139-RF
Tester: Jeff Luo
Polarization: vertical
Note: Transmitting(BLE 1Mbps Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.105	29.39	-3.93	25.46	40.00	14.54	Peak
2	86.503	37.77	-17.24	20.53	40.00	19.47	Peak
3	118.601	33.89	-11.45	22.44	43.50	21.06	Peak
4	184.490	45.20	-13.78	31.42	43.50	12.08	Peak
5	354.183	45.70	-9.47	36.23	46.00	9.77	Peak
6	447.982	37.01	-6.89	30.12	46.00	15.88	Peak


Middle channel:

Project No.: CR231167139-RF
Tester: Jeff Luo
Polarization: horizontal
Note: Transmitting(BLE 1Mbps Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.317	28.10	-4.06	24.04	40.00	15.96	Peak
2	88.033	42.39	-17.13	25.26	43.50	18.24	Peak
3	117.773	40.15	-11.51	28.64	43.50	14.86	Peak
4	191.235	48.46	-13.55	34.91	43.50	8.59	QP
5	351.504	51.42	-9.54	41.88	46.00	4.12	QP
6	413.271	38.81	-7.87	30.94	46.00	15.06	Peak


Project No.: CR231167139-RF
Tester: Jeff Luo
Polarization: vertical
Note: Transmitting(BLE 1Mbps Mode)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	33.095	30.49	-6.14	24.35	40.00	15.65	Peak
2	87.725	37.45	-17.16	20.29	40.00	19.71	Peak
3	117.773	33.95	-11.51	22.44	43.50	21.06	Peak
4	183.844	42.53	-13.76	28.77	43.50	14.73	Peak
5	350.477	45.84	-9.57	36.27	46.00	9.73	Peak
6	451.135	37.27	-6.87	30.40	46.00	15.60	Peak


High channel:

Project No.: CR231167139-RF
Tester: Jeff Luo
Polarization: horizontal
Note: Transmitting(BLE 1Mbps Mode)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	89.590	43.02	-17.06	25.96	43.50	17.54	Peak
2	118.186	40.02	-11.49	28.53	43.50	14.97	Peak
3	182.559	49.23	-13.64	35.59	43.50	7.91	QP
4	196.510	49.80	-13.09	36.71	43.50	6.79	QP
5	346.809	50.60	-9.66	40.94	46.00	5.06	QP
6	413.271	38.68	-7.87	30.81	46.00	15.19	Peak

Project No.: CR231167139-RF
Tester: Jeff Luo
Polarization: vertical
Note: Transmitting(BLE 1Mbps Mode)




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	32.179	29.34	-5.40	23.94	40.00	16.06	Peak
2	89.590	37.48	-17.06	20.42	43.50	23.08	Peak
3	117.360	35.43	-11.52	23.91	43.50	19.59	Peak
4	183.201	42.96	-13.70	29.26	43.50	14.24	Peak
5	369.405	45.34	-9.15	36.19	46.00	9.81	Peak
6	447.982	37.23	-6.89	30.34	46.00	15.66	Peak

3) 1-25GHz:
BLE 1Mbps:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2402 MHz							
2390.000	26.54	PK	H	31.71	58.25	74.00	15.75
2390.000	15.31	AV	H	31.71	47.02	54.00	6.98
2390.000	25.46	PK	V	31.71	57.17	74.00	16.83
2390.000	13.22	AV	V	31.71	44.93	54.00	9.07
4804.000	34.12	PK	H	11.19	45.31	74.00	28.69
4804.000	23.76	AV	H	11.19	34.95	54.00	19.05
4804.000	33.83	PK	V	11.19	45.02	74.00	28.98
4804.000	22.31	AV	V	11.19	33.50	54.00	20.50
7206.000	34.35	PK	H	15.03	49.38	74.00	24.62
7206.000	23.31	AV	H	15.03	38.34	54.00	15.66
7206.000	34.39	PK	V	15.03	49.42	74.00	24.58
7206.000	22.91	AV	V	15.03	37.94	54.00	16.06
Middle Channel: 2440 MHz							
4880.000	34.49	PK	H	11.48	45.97	74.00	28.03
4880.000	23.81	AV	H	11.48	35.29	54.00	18.71
4880.000	34.94	PK	V	11.48	46.42	74.00	27.58
4880.000	21.88	AV	V	11.48	33.36	54.00	20.64
7320.000	34.44	PK	H	15.58	50.02	74.00	23.98
7320.000	23.08	AV	H	15.58	38.66	54.00	15.34
7320.000	34.38	PK	V	15.58	49.96	74.00	24.04
7320.000	22.05	AV	V	15.58	37.63	54.00	16.37
High Channel: 2480 MHz							
2483.500	26.27	PK	H	32.19	58.46	74.00	15.54
2483.500	15.33	AV	H	32.19	47.52	54.00	6.48
2483.500	26.01	PK	V	32.19	58.20	74.00	15.80
2483.500	13.22	AV	V	32.19	45.41	54.00	8.59
4960.000	34.30	PK	H	11.77	46.07	74.00	27.93
4960.000	23.64	AV	H	11.77	35.41	54.00	18.59
4960.000	34.78	PK	V	11.77	46.55	74.00	27.45
4960.000	23.52	AV	V	11.77	35.29	54.00	18.71
7440.000	33.55	PK	H	15.98	49.53	74.00	24.47
7440.000	23.53	AV	H	15.98	39.51	54.00	14.49
7440.000	34.76	PK	V	15.98	50.74	74.00	23.26
7440.000	22.16	AV	V	15.98	38.14	54.00	15.86


Worst Test plots (High channel)



Horizontal

Project No.: CR231167139-RF
Tester: Mack Huang
Polarization: horizontal
Note: BLE 1M High Channel

Date: 2024-01-04




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7440.000	23.53	15.98	39.51	54.00	14.49	Average
2	7440.000	33.55	15.98	49.53	74.00	24.47	Peak
3	15686.400	23.12	24.77	47.89	54.00	6.11	Average
4	15686.400	35.07	24.77	59.84	74.00	14.16	Peak

Horizontal

Project No.: CR231167139-RF
Tester: Mack Huang
Polarization: Horizontal
Note: BLE 1M High Channel




18-25GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	24294.400	39.03	5.09	44.12	54.00	9.88	Average
2	24294.400	51.50	5.09	56.59	74.00	17.41	Peak

Vertical

Project No.: CR231167139-RF
Tester: Mack Huang
Polarization: vertical
Note: BLE 1M High Channel




1-6GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	4960.000	23.52	11.77	35.29	54.00	18.71	Average
2	4960.000	34.78	11.77	46.55	74.00	27.45	Peak

Vertical

Project No.: CR231167139-RF
Tester: Mack Huang
Polarization: vertical
Note: BLE 1M High Channel




6-18GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	7440.000	22.16	15.98	38.14	54.00	15.86	Average
2	7440.000	34.76	15.98	50.74	74.00	23.26	Peak
3	16375.200	22.16	25.71	47.87	54.00	6.13	Average
4	16375.200	34.33	25.71	60.04	74.00	13.96	Peak

Vertical

Project No.: CR231167139-RF
Tester: Mack Huang
Polarization: Vertical
Note: BLE 1M High Channel



18-25GHz

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	24141.800	39.24	4.88	44.12	54.00	9.88	Average
2	24141.800	51.32	4.88	56.20	74.00	17.80	Peak

4.3 Spot Check for Maximum Conducted Output Power:

Serial Number:	2DS1-1	Test Date:	2023/12/2
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jou Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	36	ATM Pressure: (kPa)	101.7
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Power Meter	ML2495A	1106009	2023/8/4	2024/8/3
Anritsu	Pulse Power Sensor	MA2411A	10780	2023/8/4	2024/8/3
zhuoxiang	Coaxial Cable	SMA-178	211002	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Channel	Test Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	Limit (dBm)
Lowest	2402	0.73	≤30
Middle	2440	1.87	≤30
Highest	2480	-0.84	≤30

4.4 Duty Cycle:

Serial Number:	2DS1-1	Test Date:	2024/3/15
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jou Zhou	Test Result:	N/A

Environmental Conditions:					
Temperature: (°C)	24.5	Relative Humidity: (%)	37	ATM Pressure: (kPa)	100.9


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	Each time	N/A
zhuoxiang	Coaxial Cable	SMA-178	211002	Each time	N/A
Mini-Circuits	DC Block	BLK-18-S+	1554403	Each time	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Channel	Ton (ms)	Ton+off (ms)	Duty cycle (%)	1/T (Hz)	VBW Setting (kHz)
Middle	0.416	0.638	65.20	2404	3



5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

5.2 Measurement Result

The max conducted power including tune-up tolerance is 2.0 dBm (1.58 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 1.58/5 \cdot (\sqrt{2.480}) = 0.5 < 3.0$

Result: Compliant. The stand-alone SAR evaluation is not necessary.

6. EUT PHOTOGRAPHS

Please refer to the attachment CR231167139-EXP EUT EXTERNAL PHOTOGRAPHS and
CR231167139-INP EUT INTERNAL PHOTOGRAPHS

7. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR231167139-00A-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====