FCC RF Test Report

APPLICANT	:	Fibocom Wireless Inc.
EQUIPMENT	:	5G Dongle
BRAND NAME	:	Fibocom
MODEL NAME	:	ST151L-GL
FCC ID	:	ZMOST151LGL
STANDARD	:	FCC Part 15 Subpart E §15.407
CLASSIFICATION	:	(NII) Unlicensed National Information Infrastructure
TEST DATE(S)	:	Mar. 19, 2026 ~ Apr. 15, 2026

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang

ACCREDITED
Cert #5145.01

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Testing Location 7
1.7 Test Software 7
1.8 Applicable Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Carrier Frequency and Channel 8
2.2 Test Mode 9
2.3 Connection Diagram of Test System 10
2.4 Support Unit used in test configuration and system 11
2.5 EUT Operation Test Setup 11
2.6 Measurement Results Explanation Example 11

3 TEST RESULT **12**

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 12
3.2 Maximum Conducted Output Power Measurement 17
3.3 Power Spectral Density Measurement 19
3.4 Unwanted Emissions Measurement 23
3.5 AC Conducted Emission Measurement 28
3.6 Antenna Requirements 30

4 LIST OF MEASURING EQUIPMENT **31**

5 MEASUREMENT UNCERTAINTY **32**

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR620905B	Rev. 01	Initial issue of report	Apr. 24, 2026

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit for U-NII-1/2A/2C	Limit for U-NII-3	Result	Remark
3.1	2.1049 & 15.403(i)	6dB, 26dB & 99% Bandwidth	-	6dB Bandwidth > 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm/MHz	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	15.407(b)(4)(i) &15.209(a)	Pass	Under limit 6.19 dB at 438.37 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	15.207(a)	Pass	Under limit 11.74 dB at 0.21 MHz
3.6	15.203 & 15.407(a)	Antenna Requirement	15.203 & 15.407(a)	15.203 & 15.407(a)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Fibocom Wireless Inc.
1101,Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan,Shenzhen, China.

1.2 Manufacturer

Fibocom Wireless Inc.
1101,Tower A, Building 6, Shenzhen International Innovation Valley, Dashi 1st Rd, Nanshan,Shenzhen, China.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	5G Dongle
Brand Name	Fibocom
Model Name	ST151L-GL
FCC ID	ZMOST151LGL
SN Code	Conducted: ZR60SB0017 Conduction: eab5620 Radiation: 6271d087
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna	**<5180 MHz ~ 5240 MHz>** 802.11a : 17.22 dBm / 0.0527 W 802.11n HT20 : 17.34 dBm / 0.0542 W 802.11n HT40 : 16.09 dBm / 0.0406 W 802.11ac VHT20: 17.22 dBm / 0.0527 W 802.11ac VHT40: 16.05 dBm / 0.0403 W 802.11ac VHT80: 11.14 dBm / 0.0130 W **<5745 MHz ~ 5825 MHz>** 802.11a : 17.29 dBm / 0.0536 W 802.11n HT20 : 17.36 dBm / 0.0545 W 802.11n HT40 : 16.36 dBm / 0.0433 W 802.11ac VHT20: 17.31 dBm / 0.0538 W 802.11ac VHT40: 16.29 dBm / 0.0426 W 802.11ac VHT80: 16.16 dBm / 0.0413 W
99% Occupied Bandwidth	**<5180 MHz ~ 5240 MHz>** 802.11a : 16.79 MHz 802.11n HT20 : 17.97 MHz 802.11n HT40 : 36.35 MHz 802.11ac VHT80 : 75.69 MHz **<5745 MHz ~ 5825 MHz>** 802.11a : 16.77 MHz 802.11n HT20 : 17.98 MHz 802.11n HT40 : 36.41 MHz 802.11ac VHT80 : 75.72 MHz
Antenna Type / Gain	**<5180 MHz ~ 5240 MHz>** PIFA Antenna type with gain 0.24 dBi **<5745 MHz ~ 5825 MHz>** PIFA Antenna type with gain 1.73 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

Note: For 802.11n HT20 / ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing has assessed only 802.11n HT20/ HT40 by referring to their higher conducted power.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-SZ CO02-SZ ; 03CH01-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24
2.	CO02-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ANSI C63.10-2020+Cor.1-2023

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5180-5240 MHz U-NII-1	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42#	5210	-	-

Frequency Band	Channel	Freq.(MHz)	Channel	Freq. (MHz)
5745-5825 MHz U-NII-3	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

1. The above Frequency and Channel in "*" are 40MHz bandwidth.
2. The above Frequency and Channel in "#" are 80MHz bandwidth.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

SISO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : LTE Band 5 Idle + WLAN Link(5G) + USB Cable Charging with NB
Remark: For Radiated Test Cases, The tests were performance with Notebook.	

Ch. #		U-NII-1	U-NII-3
		20M BW	20M BW
L	Low	36	149
M	Middle	44	157
H	High	48	165

Ch. #		U-NII-1	U-NII-3
		40M BW	40M BW
L	Low	38	151
M	Middle	-	-
H	High	46	159

Ch. #		U-NII-1	U-NII-3
		80M BW	80M BW
L	Low	-	-
M	Middle	42	155
H	High	-	-

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	IPod	Apple	MC525 ZP/A	Fcc DoC	N/A	Shielded, 1.0m
2.	Notebook	Thinkpad	Thinkpad E14	N/A	N/A	N/A
3.	WLAN AP	ASUSTek	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,2.7m with Core
4.	Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 1.50 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 1.50 + 10 = 11.50 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 & ANSI C63.10-2020 clause 12.5.1 for 6dB BW and 12.5.2 for 26dB BW and 6.9.3 for 99% occupied bandwidth measurements.

☒	Section C) Bandwidth Measurement 1. Emission Bandwidth (EBW) and 99% OBW
	1. Set RBW = shall be in the range of 1% to 5% of the emission bandwidth. **2.** Set the VBW > RBW. **3.** Detector = Peak. **4.** Trace mode = max hold **5.** Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%. **6.** For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set to 1%~5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW. **7.** Measure and record the results in the test report.
☒	Section C) Bandwidth Measurement 2. Minimum Emission Bandwidth for the band 5.725 - 5.85 GHz
	1. Set RBW = 100 kHz. **2.** Set the VBW ≥ 3 x RBW. **3.** Detector = Peak. **4.** Trace mode = max hold **5.** Measure the maximum width of the emission that is 6 dB down from the peak of the emission. **6.** Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth



Maximum 26dB Bandwidth for 20M BW



Maximum 26dB Bandwidth for 40M BW



Maximum 26dB Bandwidth for 80M BW



Maximum 99% Occupied Bandwidth for 20M BW



Maximum 99% Occupied Bandwidth for 40M BW



Maximum 99% Occupied Bandwidth for 80M BW



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, 10 log(1/x), where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

For devices operating in the bands UNII-1/2A/2C

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW ≥ 3 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

For devices operating in the band UNII-3

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500KHz (or 300 kHz if the SA can’t set RBW=500KHz).
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- If the SA can’t set RBW=500KHz, then add 10 log(500kHz/RBW) to the test result.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

For devices operating in the bands UNII-1

Worst Case Power Density (dBm/MHz)



Note: Average Power Density (dB) = Measured value+ Duty Factor

For devices operating in the band UNII-3

Worst Case Power Density (dBm/300kHz)



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of –27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band:
15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(3) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

EIRP (dBm)	Field Strength at 3m (dBµV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log(d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBµV/m

d_{Meas} is the measurement distance, in m

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000MHz

   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Dec. 24, 2025	Apr. 15, 2026	Dec. 23, 2026	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2025	Apr. 15, 2026	Jul. 02, 2026	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 26, 2025	Apr. 15, 2026	Dec. 25, 2026	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Dec. 23, 2025	Apr. 15, 2026	Dec. 22, 2026	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 16, 2025	Apr. 15, 2026	Jul. 15, 2026	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 03,2025	Apr. 15, 2026	Apr. 02,2027	Radiation (03CH01-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz-3GHz	Dec. 24, 2025	Apr. 15, 2026	Dec. 23, 2026	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 13,2025	Apr. 15, 2026	Oct. 12,2026	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 13,2025	Apr. 15, 2026	Oct. 12,2026	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 02, 2025	Apr. 15, 2026	Jul. 01, 2026	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	Oct. 14,2025	Apr. 15, 2026	Oct. 13,2026	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Apr. 15, 2026	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Apr. 15, 2026	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	102297	9kHz~7GHz;	Jul. 02, 2025	Mar. 19, 2026	Jul. 01, 2026	Conduction (CO02-SZ)
AC LISN	R&S	ENV216	101499	9kHz~30MHz	Jul. 03, 2025	Mar. 19, 2026	Jul. 02, 2026	Conduction (CO02-SZ)
AC Power Source	CHROMA	61601	616010002470	100Vac~250Vac	Dec.14, 2025	Mar. 19, 2026	Dec. 13, 2026	Conduction (CO02-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Mar. 26, 2026	Mar. 27, 2026	Mar. 25, 2027	Conducted (TH01-SZ)
Pulse Power Senor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 24, 2025	Mar. 27, 2026	Dec. 23, 2026	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct.13,2025	Mar. 27, 2026	Oct. 12, 2026	Conducted (TH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Conducted Power Spectral Density	±1.32 dB
Frequency	±1.3 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5 dB

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.2 dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.3 dB

---------- THE END ----------

Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Cheng Lin	Temperature:	21~25	°C
Test Date:	2026/3/27	Relative Humidity:	51~54	%

Report Number : FR620905B

TEST RESULTS DATA
Average Power Table

FCC Band I											
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail	Power Setting
11a	6Mbps	1	36	5180	0.06	16.77	23.98	0.24		Pass	19
11a	6Mbps	1	44	5220	0.06	17.22	23.98	0.24		Pass	19.5
11a	6Mbps	1	48	5240	0.06	17.15	23.98	0.24		Pass	19.5
HT20	MCS0	1	36	5180	0.08	17.34	23.98	0.24		Pass	19.5
HT20	MCS0	1	44	5220	0.08	17.26	23.98	0.24		Pass	19.5
HT20	MCS0	1	48	5240	0.08	17.16	23.98	0.24		Pass	19.5
HT40	MCS0	1	38	5190	0.18	12.88	23.98	0.24		Pass	14
HT40	MCS0	1	46	5230	0.18	16.09	23.98	0.24		Pass	17.5
VHT20	MCS0	1	36	5180	0.08	17.22	23.98	0.24		Pass	19.5
VHT20	MCS0	1	44	5220	0.08	17.04	23.98	0.24		Pass	19.5
VHT20	MCS0	1	48	5240	0.08	17.02	23.98	0.24		Pass	19.5
VHT40	MCS0	1	38	5190	0.18	12.83	23.98	0.24		Pass	14
VHT40	MCS0	1	46	5230	0.18	16.05	23.98	0.24		Pass	17.5
VHT80	MCS0	1	42	5210	0.36	11.14	23.98	0.24		Pass	12.5

Report Number : FR620905B

TEST RESULTS DATA
Average Power Table

Band IV											
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail	Setting
11a	6M bps	1	149	5745	0.06	17.29	30.00	1.73		Pass	20
11a	6Mbps	1	157	5785	0.06	17.03	30.00	1.73		Pass	20
11a	6Mbps	1	165	5825	0.06	17.02	30.00	1.73		Pass	20.5
HT20	MCS 0	1	149	5745	0.08	17.36	30.00	1.73		Pass	20.5
HT20	MCS 0	1	157	5785	0.08	17.24	30.00	1.73		Pass	20.5
HT20	MCS 0	1	165	5825	0.08	17.06	30.00	1.73		Pass	20.5
HT40	MCS 0	1	151	5755	0.18	16.31	30.00	1.73		Pass	18.5
HT40	MCS 0	1	159	5795	0.18	16.36	30.00	1.73		Pass	18.5
VHT20	MCS 0	1	149	5745	0.08	17.31	30.00	1.73		Pass	20.5
VHT20	MCS 0	1	157	5785	0.08	17.17	30.00	1.73		Pass	20.5
VHT20	MCS 0	1	165	5825	0.08	17.04	30.00	1.73		Pass	20.5
VHT40	MCS 0	1	151	5755	0.18	16.29	30.00	1.73		Pass	18.5
VHT40	MCS 0	1	159	5795	0.18	16.26	30.00	1.73		Pass	18.5
VHT80	MCS 0	1	155	5775	0.36	16.16	30.00	1.73		Pass	18.5

Report Number : FR620905B

TEST RESULTS DATA
26dB and 99% OBW

Band I								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)		
11a	6Mbps	1	36	5180	16.78	24.66		
11a	6Mbps	1	44	5220	16.74	25.20		
11a	6Mbps	1	48	5240	16.79	25.14		
HT20	MCS0	1	36	5180	17.96	25.14		
HT20	MCS0	1	44	5220	17.97	25.20		
HT20	MCS0	1	48	5240	17.96	25.32		
HT40	MCS0	1	38	5190	36.32	42.12		
HT40	MCS0	1	46	5230	36.35	42.12		
VHT80	MCS0	1	42	5210	75.69	96.00		

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	16.77	24.18	15.15	0.5	Pass
11a	6Mbps	1	157	5785	16.76	24.42	15.20	0.5	Pass
11a	6Mbps	1	165	5825	16.76	23.64	16.15	0.5	Pass
HT20	MCS 0	1	149	5745	17.98	24.06	15.20	0.5	Pass
HT20	MCS 0	1	157	5785	17.96	25.68	15.70	0.5	Pass
HT20	MCS 0	1	165	5825	17.95	25.20	15.70	0.5	Pass
HT40	MCS 0	1	151	5755	36.41	42.60	35.73	0.5	Pass
HT40	MCS 0	1	159	5795	36.37	42.36	35.91	0.5	Pass
VHT80	MCS 0	1	155	5775	75.72	108.96	75.52	0.5	Pass

Report Number : FR620905B

TEST RESULTS DATA
Power Spectral Density

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)	-	Pass/Fail
11a	6Mbps	1	36	5180	0.06	6.21	11.00	0.24		Pass
11a	6Mbps	1	44	5220	0.06	6.09	11.00	0.24		Pass
11a	6Mbps	1	48	5240	0.06	5.97	11.00	0.24		Pass
HT20	MCS0	1	36	5180	0.08	5.73	11.00	0.24		Pass
HT20	MCS0	1	44	5220	0.08	5.62	11.00	0.24		Pass
HT20	MCS0	1	48	5240	0.08	5.46	11.00	0.24		Pass
HT40	MCS0	1	38	5190	0.18	1.71	11.00	0.24		Pass
HT40	MCS0	1	46	5230	0.18	1.65	11.00	0.24		Pass
VHT80	MCS0	1	42	5210	0.36	-1.57	11.00	0.24		Pass

Report Number : FR620905B

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.06	2.22	3.05	30.00	1.73	Pass
11a	6Mbps	1	157	5785	0.06	2.22	2.84	30.00	1.73	Pass
11a	6Mbps	1	165	5825	0.06	2.22	2.70	30.00	1.73	Pass
HT20	MCS 0	1	149	5745	0.08	2.22	3.19	30.00	1.73	Pass
HT20	MCS 0	1	157	5785	0.08	2.22	2.91	30.00	1.73	Pass
HT20	MCS 0	1	165	5825	0.08	2.22	2.51	30.00	1.73	Pass
HT40	MCS 0	1	151	5755	0.18	2.22	-0.91	30.00	1.73	Pass
HT40	MCS 0	1	159	5795	0.18	2.22	-1.01	30.00	1.73	Pass
VHT80	MCS 0	1	155	5775	0.36	2.22	-3.88	30.00	1.73	Pass

Appendix B. AC Conducted Emission Test Results

Test Engineer :	XuRuibin	**Temperature :**	22~24℃
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO02-SZ
Condition : FCC 15E_QP LISN-L_2026 LINE

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.17	31.31	-23.55	54.86	11.40	9.73	10.18	Average
2		0.17	52.41	-12.45	64.86	32.50	9.73	10.18	QP
3		0.21	36.10	-17.04	53.14	16.20	9.72	10.18	Average
4	*	0.21	51.40	-11.74	63.14	31.50	9.72	10.18	QP
5		0.49	27.17	-19.02	46.19	7.20	9.73	10.24	Average
6		0.49	35.77	-20.42	56.19	15.80	9.73	10.24	QP
7		0.59	25.69	-20.31	46.00	5.70	9.75	10.24	Average
8		0.59	33.59	-22.41	56.00	13.60	9.75	10.24	QP
9		3.68	26.78	-19.22	46.00	6.79	9.72	10.27	Average
10		3.68	33.18	-22.82	56.00	13.19	9.72	10.27	QP
11		4.57	26.87	-19.13	46.00	6.90	9.70	10.27	Average
12		4.57	33.37	-22.63	56.00	13.40	9.70	10.27	QP

Test Engineer :	XuRuibin	**Temperature :**	22~24℃
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO02-SZ
Condition : FCC 15E_QP LISN-N_2026 NEUTRAL

		Freq MHz	Level dBuV	Over Limit dB	Limit Line dBuV	Read Level dBuV	LISN Factor dB	Cable Loss dB	Remark
1		0.16	33.67	-22.02	55.69	13.69	9.79	10.19	Average
2	*	0.16	52.77	-12.92	65.69	32.79	9.79	10.19	QP
3		0.18	32.76	-21.70	54.46	12.80	9.78	10.18	Average
4		0.18	46.56	-17.90	64.46	26.60	9.78	10.18	QP
5		0.49	19.65	-26.49	46.14	-0.30	9.71	10.24	Average
6		0.49	30.55	-25.59	56.14	10.60	9.71	10.24	QP
7		0.62	22.51	-23.49	46.00	2.49	9.78	10.24	Average
8		0.62	30.51	-25.49	56.00	10.49	9.78	10.24	QP
9		3.64	26.01	-19.99	46.00	6.00	9.74	10.27	Average
10		3.64	32.31	-23.69	56.00	12.30	9.74	10.27	QP
11		5.03	26.63	-23.37	50.00	6.60	9.76	10.27	Average
12		5.03	34.83	-25.17	60.00	14.80	9.76	10.27	QP

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

Appendix C Radiated Spurious Emission Test Data

Test Engineer :	Zhaohui Liang	Relative Humidity :	48~49%
		Temperature :	24-25℃

Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	U-NII-1	5.15-5.25	SISO	802.11a	36	5180	6Mbps	-	-
Mode 2	U-NII-1	5.15-5.25	SISO	802.11a	44	5220	6Mbps	-	-
Mode 3	U-NII-1	5.15-5.25	SISO	802.11a	48	5240	6Mbps	-	-
Mode 4	U-NII-1	5.15-5.25	SISO	802.11n HT20	36	5180	MCS0	Full	-
Mode 5	U-NII-1	5.15-5.25	SISO	802.11n HT20	44	5220	MCS0	Full	-
Mode 6	U-NII-1	5.15-5.25	SISO	802.11n HT20	48	5240	MCS0	Full	-
Mode 7	U-NII-1	5.15-5.25	SISO	802.11n HT40	38	5190	MCS0	Full	-
Mode 8	U-NII-1	5.15-5.25	SISO	802.11n HT40	46	5230	MCS0	Full	-
Mode 9	U-NII-1	5.15-5.25	SISO	802.11ac VHT80	42	5210	MCS0	Full	-
Mode 10	U-NII-3	5.725-5.85	SISO	802.11a	149	5745	6Mbps	-	-
Mode 11	U-NII-3	5.725-5.85	SISO	802.11a	157	5785	6Mbps	-	-
Mode 12	U-NII-3	5.725-5.85	SISO	802.11a	165	5825	6Mbps	-	-
Mode 13	U-NII-3	5.725-5.85	SISO	802.11n HT20	149	5745	MCS0	Full	-
Mode 14	U-NII-3	5.725-5.85	SISO	802.11n HT20	157	5785	MCS0	Full	-
Mode 15	U-NII-3	5.725-5.85	SISO	802.11n HT20	165	5825	MCS0	Full	-
Mode 16	U-NII-3	5.725-5.85	SISO	802.11n HT40	151	5755	MCS0	Full	-
Mode 17	U-NII-3	5.725-5.85	SISO	802.11n HT40	159	5795	MCS0	Full	-
Mode 18	U-NII-3	5.725-5.85	SISO	802.11ac VHT80	155	5775	MCS0	Full	-
Mode 19	U-NII-1	5.15-5.25	SISO	802.11ac VHT80-LF	42	5210	MCS0	Full	-
Mode 20	U-NII-3	5.725-5.85	SISO	802.11ac VHT80-LF	155	5775	MCS0	Full	-

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	802.11a	36	5149.40	46.65	54.00	-7.35	H	AVERAGE	Pass	Band Edge
1	802.11a	36	10360.00	48.82	68.30	-19.48	V	Peak	Pass	Harmonic
2	802.11a	44	-	-	-	-	-	-	-	Band Edge
2	802.11a	44	10440.00	48.89	68.30	-19.41	H	Peak	Pass	Harmonic
3	802.11a	48	-	-	-	-	-	-	-	Band Edge
3	802.11a	48	10480.00	48.37	68.30	-19.93	V	Peak	Pass	Harmonic
4	802.11n HT20	36	5149.94	45.88	54.00	-8.12	H	AVERAGE	Pass	Band Edge
4	802.11n HT20	36	10360.00	49.25	68.30	-19.05	H	Peak	Pass	Harmonic
5	802.11n HT20	44	-	-	-	-	-	-	-	Band Edge
5	802.11n HT20	44	10440.00	48.79	68.30	-19.51	H	Peak	Pass	Harmonic
6	802.11n HT20	48	-	-	-	-	-	-	-	Band Edge
6	802.11n HT20	48	10480.00	48.23	68.30	-20.07	V	Peak	Pass	Harmonic
7	802.11n HT40	38	5149.53	47.28	54.00	-6.72	H	AVERAGE	Pass	Band Edge
7	802.11n HT40	38	10380.00	48.31	68.30	-19.99	H	Peak	Pass	Harmonic
8	802.11n HT40	46	5390.77	43.69	54.00	-10.31	H	AVERAGE	Pass	Band Edge
8	802.11n HT40	46	10460.00	49.70	68.30	-18.60	V	Peak	Pass	Harmonic
9	802.11ac VHT80	42	5134.82	47.44	54.00	-6.56	H	AVERAGE	Pass	Band Edge

9	802.11ac VHT80	42	10420.00	49.09	68.30	-19.21	V	Peak	Pass	Harmonic
10	802.11a	149	5646.55	54.10	68.30	-14.20	V	PEAK	Pass	Band Edge
10	802.11a	149	17235.00	49.32	68.30	-18.98	V	Peak	Pass	Harmonic
11	802.11a	157	-	-	-	-	-	-	-	Band Edge
11	802.11a	157	17355.00	49.91	68.30	-18.39	H	Peak	Pass	Harmonic
12	802.11a	165	5928.50	53.07	68.30	-15.23	V	PEAK	Pass	Band Edge
12	802.11a	165	17475.00	49.75	68.30	-18.55	V	Peak	Pass	Harmonic
13	802.11n HT20	149	5649.88	54.13	68.30	-14.17	V	PEAK	Pass	Band Edge
13	802.11n HT20	149	17235.00	49.56	68.30	-18.74	V	Peak	Pass	Harmonic
14	802.11n HT20	157	-	-	-	-	-	-	-	Band Edge
14	802.11n HT20	157	17355.00	49.17	68.30	-19.13	H	Peak	Pass	Harmonic
15	802.11n HT20	165	5927.88	53.55	68.30	-14.75	V	PEAK	Pass	Band Edge
15	802.11n HT20	165	17475.00	49.19	68.30	-19.11	H	Peak	Pass	Harmonic
16	802.11n HT40	151	5637.98	55.17	68.30	-13.13	V	PEAK	Pass	Band Edge
16	802.11n HT40	151	17265.00	49.24	68.30	-19.06	V	Peak	Pass	Harmonic
17	802.11n HT40	159	5929.54	53.79	68.30	-14.51	H	PEAK	Pass	Band Edge
17	802.11n HT40	159	17385.00	49.74	68.30	-18.56	V	Peak	Pass	Harmonic
18	802.11ac VHT80	155	5656.00	65.43	72.75	-7.32	V	PEAK	Pass	Band Edge
18	802.11ac VHT80	155	17325.00	48.96	68.30	-19.34	V	Peak	Pass	Harmonic
19	802.11ac VHT80-LF	42	438.37	39.81	46.00	-6.19	H	Peak	Pass	LF
20	802.11ac VHT80-LF	155	442.25	39.93	46.00	-6.97	H	Peak	Pass	LF

Mode	1	
	Band Edge	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5136.80 56.60 74.00 -17.40 42.84 35.85 10.54 32.63 387 66 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5180.00 109.27 ------ ------ 95.58 35.87 10.46 32.64 387 66 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5149.40 46.65 54.00 -7.35 32.91 35.86 10.51 32.63 387 66 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5180.00 102.68 ------ ------ 89.01 35.87 10.44 32.64 387 66 AVERAGE

Mode	1	
	Band Edge	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5066.24 53.56 74.00 -20.44 39.80 35.83 10.54 32.61 362 235 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5180.00 104.69 ------ ------ 91.00 35.87 10.46 32.64 362 235 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5149.22 43.59 54.00 -10.41 29.85 35.86 10.51 32.63 362 235 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5180.00 97.68 ------ ------ 83.99 35.87 10.46 32.64 362 235 AVERAGE

Mode	1	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10360.00 47.99 68.30 -20.31 46.93 37.90 14.59 51.43 --- --- Peak 2 15540.00 47.17 74.00 -26.83 41.40 40.79 17.17 52.19 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10360.00 48.82 68.30 -19.48 47.76 37.90 14.59 51.43 --- --- Peak 2 15540.00 47.46 74.00 -26.54 41.69 40.79 17.17 52.19 --- --- Peak

Mode	2	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10440.00 48.89 68.30 -19.41 47.81 37.90 14.59 51.41 --- --- Peak 2 15660.00 47.64 74.00 -26.36 42.01 40.89 17.19 52.45 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10440.00 48.17 68.30 -20.13 47.09 37.90 14.59 51.41 --- --- Peak 2 15660.00 47.49 74.00 -26.51 41.86 40.89 17.19 52.45 --- --- Peak

Mode	3	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10480.00 47.73 68.30 -20.57 46.64 37.90 14.59 51.40 --- --- Peak 2 15720.00 47.93 74.00 -26.07 42.37 40.95 17.19 52.58 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10480.00 48.37 68.30 -19.93 47.28 37.90 14.59 51.40 --- --- Peak 2 15720.00 47.61 74.00 -26.39 42.05 40.95 17.19 52.58 --- --- Peak

Mode	4	
	Band Edge	
	U-NII-1_5.15-5.25_802.11n HT20_CH36_Full_5180MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5144.90 54.74 74.00 -19.26 40.99 35.86 10.52 32.63 343 51 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5180.00 110.03 ------ ------ 96.36 35.87 10.44 32.64 343 51 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5149.94 45.88 54.00 -8.12 32.14 35.86 10.51 32.63 343 51 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5180.00 102.38 ------ ------ 88.71 35.87 10.44 32.64 343 51 AVERAGE

Mode	4	
	Band Edge	
	U-NII-1_5.15-5.25_802.11n HT20_CH36_Full_5180MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5148.32 53.76 74.00 -20.24 40.02 35.86 10.51 32.63 369 122 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5180.00 106.31 ------ ------ 92.64 35.87 10.44 32.64 369 122 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5149.94 44.06 54.00 -9.94 30.32 35.86 10.51 32.63 369 122 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5180.00 98.76 ------ ------ 85.07 35.87 10.46 32.64 369 122 AVERAGE

Mode	4	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT20_CH36_Full_5180MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10360.00 49.25 68.30 -19.05 48.19 37.90 14.59 51.43 --- --- Peak 2 15540.00 47.81 74.00 -26.19 42.04 40.79 17.17 52.19 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10360.00 48.28 68.30 -20.02 47.22 37.90 14.59 51.43 --- --- Peak 2 15540.00 47.98 74.00 -26.02 42.21 40.79 17.17 52.19 --- --- Peak

Mode	5	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT20_CH44_Full_5220MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10440.00 48.79 68.30 -19.51 47.71 37.90 14.59 51.41 --- --- Peak 2 15660.00 47.76 74.00 -26.24 42.13 40.89 17.19 52.45 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10440.00 48.07 68.30 -20.23 46.99 37.90 14.59 51.41 --- --- Peak 2 15660.00 47.39 74.00 -26.61 41.76 40.89 17.19 52.45 --- --- Peak

Mode	6	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT20_CH48_Full_5240MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10480.00 47.86 68.30 -20.44 46.77 37.90 14.59 51.40 --- --- Peak 2 15720.00 47.26 74.00 -26.74 41.70 40.95 17.19 52.58 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10480.00 48.23 68.30 -20.07 47.14 37.90 14.59 51.40 --- --- Peak 2 15720.00 47.47 74.00 -26.53 41.91 40.95 17.19 52.58 --- --- Peak

Mode	7
	Band Edge - L
	U-NII-1_5.15-5.25_802.11n HT40_CH38_Full_5190MHz
ANT	SISO

Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5149.91 56.90 74.00 -17.10 43.16 35.86 10.51 32.63 366 52 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5190.00 101.76 ------ ------ 88.09 35.88 10.43 32.64 366 52 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5149.53 47.28 54.00 -6.72 33.54 35.86 10.51 32.63 366 52 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5190.00 94.61 ------ ------ 80.94 35.88 10.43 32.64 366 52 AVERAGE

Mode	7	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11n HT40_CH38_Full_5190MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5433.00 51.77 74.00 -22.23 37.97 35.97 10.52 32.69 366 52 PEAK	Blank
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5434.35 42.90 54.00 -11.10 29.10 35.97 10.52 32.69 366 52 AVERAGE	Blank

Mode	7	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11n HT40_CH38_Full_5190MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5145.35 53.88 74.00 -20.12 40.13 35.86 10.52 32.63 361 233 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5190.00 98.70 ------ ------ 85.03 35.88 10.43 32.64 361 233 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5149.91 45.22 54.00 -8.78 31.48 35.86 10.51 32.63 361 233 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5190.00 90.67 ------ ------ 77.00 35.88 10.43 32.64 361 233 AVERAGE

Mode	7	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11n HT40_CH38_Full_5190MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5368.47 51.96 74.00 -22.04 38.15 35.95 10.53 32.67 361 233 PEAK	Blank
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5386.83 43.03 54.00 -10.97 29.24 35.95 10.52 32.68 361 233 AVERAGE	Blank

Mode	7	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT40_CH38_Full_5190MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10380.00 48.31 68.30 -19.99 47.24 37.90 14.59 51.42 --- --- Peak 2 15570.00 47.82 74.00 -26.18 42.09 40.81 17.17 52.25 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10380.00 48.29 68.30 -20.01 47.22 37.90 14.59 51.42 --- --- Peak 2 15570.00 46.87 74.00 -27.13 41.14 40.81 17.17 52.25 --- --- Peak

Mode	8	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11n HT40_CH46_Full_5230MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5131.10 52.46 74.00 -21.54 38.69 35.85 10.55 32.63 335 50 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5230.00 104.70 ------ ------ 90.96 35.90 10.49 32.65 335 50 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5127.65 43.48 54.00 -10.52 29.70 35.85 10.56 32.63 335 50 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5230.00 97.49 ------ ------ 83.78 35.89 10.47 32.65 335 50 AVERAGE

Mode	8	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11n HT40_CH46_Full_5230MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5418.14 52.60 74.00 -21.40 38.80 35.97 10.51 32.68 335 50 PEAK	Blank
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5390.77 43.69 54.00 -10.31 29.90 35.96 10.51 32.68 335 50 AVERAGE	Blank

Mode	8	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11n HT40_CH46_Full_5230MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5098.90 52.56 74.00 -21.44 38.72 35.84 10.62 32.62 372 235 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5230.00 99.88 ------ ------ 86.14 35.90 10.49 32.65 372 235 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5109.71 43.34 54.00 -10.66 29.53 35.84 10.59 32.62 372 235 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5230.00 92.11 ------ ------ 78.40 35.89 10.47 32.65 372 235 AVERAGE

Mode	8	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11n HT40_CH46_Full_5230MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5350.29 52.57 74.00 -21.43 38.75 35.94 10.55 32.67 372 235 PEAK	Blank
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5356.04 42.99 54.00 -11.01 29.17 35.94 10.55 32.67 372 235 AVERAGE	Blank

Mode	8	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT40_CH46_Full_5230MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10460.00 47.84 68.30 -20.46 46.76 37.90 14.59 51.41 --- --- Peak 2 15690.00 47.11 74.00 -26.89 41.52 40.92 17.19 52.52 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10460.00 49.70 68.30 -18.60 48.62 37.90 14.59 51.41 --- --- Peak 2 15690.00 47.55 74.00 -26.45 41.96 40.92 17.19 52.52 --- --- Peak

Mode	9	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_Full_5210MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5142.59 57.54 74.00 -16.46 43.78 35.86 10.53 32.63 350 55 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5210.00 92.96 ------ ------ 79.25 35.89 10.47 32.65 350 55 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5134.82 47.44 54.00 -6.56 33.68 35.85 10.54 32.63 350 55 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5210.00 86.17 ------ ------ 72.43 35.90 10.49 32.65 350 55 AVERAGE

Mode	9	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_Full_5210MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5358.25 52.45 74.00 -21.55 38.64 35.94 10.54 32.67 350 55 PEAK	Blank
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5368.75 42.88 54.00 -11.12 29.07 35.95 10.53 32.67 350 55 AVERAGE	Blank

Mode	9
	Band Edge - L
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_Full_5210MHz
ANT	SISO

Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5141.33 52.72 74.00 -21.28 38.96 35.86 10.53 32.63 383 124 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5210.00 94.18 ------ ------ 80.53 35.88 10.41 32.64 383 124 PEAK
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5126.84 43.41 54.00 -10.59 29.63 35.85 10.56 32.63 383 124 AVERAGE	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5210.00 86.54 ------ ------ 72.88 35.88 10.42 32.64 383 124 AVERAGE

Mode	9	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_Full_5210MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5365.25 52.13 74.00 -21.87 38.31 35.95 10.54 32.67 383 124 PEAK	Blank
Avg	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5455.75 43.00 54.00 -11.00 29.17 35.98 10.54 32.69 383 124 AVERAGE	Blank

Mode	9	
	Harmonic	
	U-NII-1_5.15-5.25_802.11ac VHT80_CH42_Full_5210MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10420.00 48.00 68.30 -20.30 46.93 37.90 14.59 51.42 --- --- Peak 2 15630.00 47.08 74.00 -26.92 41.42 40.87 17.18 52.39 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 10420.00 49.09 68.30 -19.21 48.02 37.90 14.59 51.42 --- --- Peak 2 15630.00 47.73 74.00 -26.27 42.07 40.87 17.18 52.39 --- --- Peak

Mode	10	
	Band Edge	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5613.34 53.56 68.30 -14.74 39.41 36.18 10.72 32.75 100 303 PEAK 2 5650.46 52.67 68.64 -15.97 38.38 36.24 10.81 32.76 100 303 PEAK 3 5712.23 67.00 108.63 -41.63 52.56 36.34 10.88 32.78 100 303 PEAK 4 5722.82 74.51 117.22 -42.71 60.06 36.36 10.88 32.79 100 303 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5745.00 110.36 ------ ------ 95.91 36.39 10.86 32.80 100 303 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5745.00 103.23 ------ ------ 88.78 36.39 10.86 32.80 100 303 AVERAGE

Mode	10	
	Band Edge	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5646.55 MHz 54.10 dBuV/m 68.30 -14.20 39.83 dBuV 36.23 dB/m 10.80 dB 32.76 dB 107 cm 247 deg PEAK 2 5650.03 53.21 68.32 -15.11 38.92 36.24 10.81 32.76 107 247 PEAK 3 5710.20 69.39 108.06 -38.67 54.94 36.34 10.89 32.78 107 247 PEAK 4 5720.64 73.24 112.26 -39.02 58.80 36.35 10.88 32.79 107 247 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5745.00 MHz 113.20 dBuV/m ------ ------ dBuV 98.75 dB/m 36.39 dB 10.86 dB 32.80 cm 107 deg 247 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5745.00 MHz 106.89 dBuV/m ------ ------ dBuV 92.44 dB/m 36.39 dB 10.86 dB 32.80 cm 107 deg 247 AVERAGE

Mode	10	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11490.00 47.34 74.00 -26.66 44.49 38.24 14.92 50.31 --- --- Peak 2 17235.00 48.35 68.30 -19.95 40.53 42.82 18.02 53.02 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11490.00 47.45 74.00 -26.55 44.60 38.24 14.92 50.31 --- --- Peak 2 17235.00 49.32 68.30 -18.98 41.50 42.82 18.02 53.02 --- --- Peak

Mode	11	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11570.00 47.80 74.00 -26.20 44.77 38.30 14.97 50.24 --- --- Peak 2 17355.00 49.91 68.30 -18.39 42.36 42.84 17.99 53.28 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11570.00 47.33 74.00 -26.67 44.30 38.30 14.97 50.24 --- --- Peak 2 17355.00 49.57 68.30 -18.73 42.02 42.84 17.99 53.28 --- --- Peak

Mode	12	
	Band Edge	
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5855.00 61.38 110.80 -49.42 46.82 36.57 10.83 32.84 100 306 PEAK 2 5857.88 60.79 109.99 -49.20 46.23 36.57 10.83 32.84 100 306 PEAK 3 5924.75 51.78 68.38 -16.60 37.08 36.68 10.89 32.87 100 306 PEAK 4 5932.50 52.21 68.30 -16.09 37.49 36.69 10.90 32.87 100 306 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5825.00 107.09 ------ ------ 92.56 36.53 10.83 32.83 100 306 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5825.00 100.06 ------ ------ 85.54 36.52 10.83 32.83 100 306 AVERAGE

Mode	12	
	Band Edge	
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5854.63 67.42 111.65 -44.23 52.86 36.57 10.83 32.84 107 247 PEAK 2 5855.38 65.93 110.69 -44.76 51.37 36.57 10.83 32.84 107 247 PEAK 3 5924.63 51.86 68.48 -16.62 37.17 36.68 10.88 32.87 107 247 PEAK 4 5928.50 53.07 68.30 -15.23 38.36 36.69 10.89 32.87 107 247 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5825.00 111.50 ------ ------ 96.98 36.52 10.83 32.83 107 247 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5825.00 104.93 ------ ------ 90.41 36.52 10.83 32.83 107 247 AVERAGE

Mode	12	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11650.00 47.45 74.00 -26.55 44.26 38.35 15.02 50.18 --- --- Peak 2 17475.00 49.40 68.30 -18.90 42.13 42.85 17.96 53.54 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11650.00 47.64 74.00 -26.36 44.45 38.35 15.02 50.18 --- --- Peak 2 17475.00 49.75 68.30 -18.55 42.48 42.85 17.96 53.54 --- --- Peak

Mode	13	
	Band Edge	
	U-NII-3_5.725-5.85_802.11n HT20_CH149_Full_5745MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5633.35 53.39 68.30 -14.91 39.16 36.21 10.77 32.75 100 303 PEAK 2 5650.17 52.54 68.43 -15.89 38.25 36.24 10.81 32.76 100 303 PEAK 3 5719.63 70.58 110.70 -40.12 56.14 36.35 10.88 32.79 100 303 PEAK 4 5721.08 74.67 113.25 -38.58 60.23 36.35 10.88 32.79 100 303 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5745.00 110.89 ------ ------ 96.45 36.38 10.86 32.80 100 303 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5745.00 103.13 ------ ------ 88.68 36.39 10.86 32.80 100 303 AVERAGE

Mode	13	
	Band Edge	
	U-NII-3_5.725-5.85_802.11n HT20_CH149_Full_5745MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5649.88 54.13 68.30 -14.17 39.84 36.24 10.81 32.76 108 247 PEAK 2 5650.90 53.72 68.96 -15.24 39.43 36.24 10.81 32.76 108 247 PEAK 3 5719.92 73.83 110.78 -36.95 59.39 36.35 10.88 32.79 108 247 PEAK 4 5720.79 76.50 112.59 -36.09 62.06 36.35 10.88 32.79 108 247 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5745.00 114.18 ------ ------ 99.73 36.39 10.86 32.80 108 247 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5745.00 106.74 ------ ------ 92.29 36.39 10.86 32.80 108 247 AVERAGE

Mode	13	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT20_CH149_Full_5745MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11490.00 47.78 74.00 -26.22 44.93 38.24 14.92 50.31 --- --- Peak 2 17235.00 49.45 68.30 -18.85 41.63 42.82 18.02 53.02 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11490.00 47.96 74.00 -26.04 45.11 38.24 14.92 50.31 --- --- Peak 2 17235.00 49.56 68.30 -18.74 41.74 42.82 18.02 53.02 --- --- Peak

Mode	14	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT20_CH157_Full_5785MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11570.00 47.99 74.00 -26.01 44.96 38.30 14.97 50.24 --- --- Peak 2 17355.00 49.17 68.30 -19.13 41.62 42.84 17.99 53.28 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11570.00 47.90 74.00 -26.10 44.87 38.30 14.97 50.24 --- --- Peak 2 17355.00 49.00 68.30 -19.30 41.45 42.84 17.99 53.28 --- --- Peak

Mode	15	
	Band Edge	
	U-NII-3_5.725-5.85_802.11n HT20_CH165_Full_5825MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5854.50 62.80 111.94 -49.14 48.24 36.57 10.83 32.84 100 303 PEAK 2 5855.88 62.51 110.55 -48.04 47.95 36.57 10.83 32.84 100 303 PEAK 3 5925.00 51.89 68.20 -16.31 37.19 36.68 10.89 32.87 100 303 PEAK 4 5933.50 52.78 68.30 -15.52 38.06 36.69 10.90 32.87 100 303 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5825.00 107.51 ------ ------ 92.99 36.52 10.83 32.83 100 303 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5825.00 100.20 ------ ------ 85.68 36.52 10.83 32.83 100 303 AVERAGE

Mode	15	
	Band Edge	
	U-NII-3_5.725-5.85_802.11n HT20_CH165_Full_5825MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5855.00 66.76 110.80 -44.04 52.20 36.57 10.83 32.84 105 244 PEAK 2 5855.63 67.31 110.62 -43.31 52.75 36.57 10.83 32.84 105 244 PEAK 3 5925.00 51.44 68.20 -16.76 36.74 36.68 10.89 32.87 105 244 PEAK 4 5927.88 53.55 68.30 -14.75 38.85 36.68 10.89 32.87 105 244 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5825.00 112.34 ------ ------ 97.82 36.52 10.83 32.83 105 244 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5825.00 104.96 ------ ------ 90.44 36.52 10.83 32.83 105 244 AVERAGE

Mode	15	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT20_CH165_Full_5825MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11650.00 47.38 74.00 -26.62 44.19 38.35 15.02 50.18 --- --- Peak 2 17475.00 49.19 68.30 -19.11 41.92 42.85 17.96 53.54 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11650.00 47.95 74.00 -26.05 44.76 38.35 15.02 50.18 --- --- Peak 2 17475.00 49.05 68.30 -19.25 41.78 42.85 17.96 53.54 --- --- Peak

Mode	16
	Band Edge - L
	U-NII-3_5.725-5.85_802.11n HT40_CH151_Full_5755MHz
ANT	SISO

Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5648.98 53.15 68.30 -15.15 38.87 36.24 10.80 32.76 100 306 PEAK 2 5650.07 53.06 68.35 -15.29 38.77 36.24 10.81 32.76 100 306 PEAK 3 5719.04 74.40 110.53 -36.13 59.96 36.35 10.88 32.79 100 306 PEAK 4 5720.13 73.29 111.09 -37.80 58.85 36.35 10.88 32.79 100 306 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5755.00 105.57 ------ ------ 91.12 36.39 10.86 32.80 100 306 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5755.00 97.75 ------ ------ 83.30 36.39 10.86 32.80 100 306 AVERAGE

Mode	16	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11n HT40_CH151_Full_5755MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5854.65 51.69 111.61 -59.92 37.13 36.57 10.83 32.84 100 306 PEAK 2 5874.54 51.66 105.33 -53.67 37.07 36.60 10.84 32.85 100 306 PEAK 3 5924.85 51.94 68.31 -16.37 37.24 36.68 10.89 32.87 100 306 PEAK 4 5933.43 52.57 68.30 -15.73 37.85 36.69 10.90 32.87 100 306 PEAK	Blank

Mode	16	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11n HT40_CH151_Full_5755MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5637.98 55.17 68.30 -13.13 40.93 36.22 10.78 32.76 103 247 PEAK 2 5650.53 53.87 68.69 -14.82 39.58 36.24 10.81 32.76 103 247 PEAK 3 5718.58 77.95 110.40 -32.45 63.51 36.35 10.88 32.79 103 247 PEAK 4 5721.06 78.20 113.21 -35.01 63.76 36.35 10.88 32.79 103 247 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5755.00 110.11 ------ ------ 95.66 36.40 10.85 32.80 103 247 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5755.00 102.55 ------ ------ 88.09 36.41 10.85 32.80 103 247 AVERAGE

Mode	16	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11n HT40_CH151_Full_5755MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5854.65 53.71 111.61 -57.90 39.15 36.57 10.83 32.84 103 247 PEAK 2 5874.54 52.90 105.33 -52.43 38.31 36.60 10.84 32.85 103 247 PEAK 3 5924.07 51.93 68.89 -16.96 37.24 36.68 10.88 32.87 103 247 PEAK 4 5942.98 52.46 68.30 -15.84 37.72 36.71 10.91 32.88 103 247 PEAK	Blank

Mode	16	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT40_CH151_Full_5755MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11510.00 47.79 74.00 -26.21 44.89 38.26 14.93 50.29 --- --- Peak 2 17265.00 48.66 68.30 -19.64 40.89 42.83 18.02 53.08 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11510.00 47.94 74.00 -26.06 45.04 38.26 14.93 50.29 --- --- Peak 2 17265.00 49.24 68.30 -19.06 41.47 42.83 18.02 53.08 --- --- Peak

Mode	17	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11n HT40_CH159_Full_5795MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5648.36 53.09 68.30 -15.21 38.81 36.24 10.80 32.76 191 33 PEAK 2 5650.90 53.27 68.96 -15.69 38.98 36.24 10.81 32.76 191 33 PEAK 3 5716.03 59.25 109.69 -50.44 44.81 36.35 10.88 32.79 191 33 PEAK 4 5720.12 58.36 111.07 -52.71 43.92 36.35 10.88 32.79 191 33 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5795.00 106.99 ------ ------ 92.53 36.46 10.82 32.82 191 33 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5795.00 99.98 ------ ------ 85.51 36.47 10.82 32.82 191 33 AVERAGE

Mode	17	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11n HT40_CH159_Full_5795MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5854.68 61.25 111.54 -50.29 46.69 36.57 10.83 32.84 191 33 PEAK 2 5856.07 60.48 110.50 -50.02 45.92 36.57 10.83 32.84 191 33 PEAK 3 5923.03 53.99 69.65 -15.66 39.30 36.68 10.88 32.87 191 33 PEAK 4 5929.54 53.79 68.30 -14.51 39.08 36.69 10.89 32.87 191 33 PEAK	Blank

Mode	17	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11n HT40_CH159_Full_5795MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5608.39 MHz 53.00 dBuV/m 68.30 dBuV/m -15.30 38.86 dBuV 36.17 dB/m 10.71 dB 32.74 dB 204 cm 75 deg PEAK 2 5650.51 52.73 68.67 -15.94 38.44 36.24 10.81 32.76 204 75 PEAK 3 5718.76 60.07 110.45 -50.38 45.63 36.35 10.88 32.79 204 75 PEAK 4 5720.12 59.60 111.07 -51.47 45.16 36.35 10.88 32.79 204 75 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5795.00 MHz 110.77 dBuV/m ------ ------ 96.29 dBuV 36.48 dB/m 10.82 dB 32.82 dB 204 cm 75 deg PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5795.00 MHz 103.23 dBuV/m ------ ------ 88.75 dBuV 36.48 dB/m 10.82 dB 32.82 dB 204 cm 75 deg AVERAGE

Mode	17	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11n HT40_CH159_Full_5795MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5854.99 60.92 110.83 -49.91 46.36 36.57 10.83 32.84 204 75 PEAK 2 5857.16 62.36 110.20 -47.84 47.80 36.57 10.83 32.84 204 75 PEAK 3 5924.89 52.95 68.28 -15.33 38.25 36.68 10.89 32.87 204 75 PEAK 4 5936.83 53.70 68.30 -14.60 38.97 36.70 10.90 32.87 204 75 PEAK	Blank

Mode	17	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT40_CH159_Full_5795MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11590.00 47.51 74.00 -26.49 44.45 38.31 14.98 50.23 --- --- Peak 2 17385.00 48.35 68.30 -19.95 40.88 42.84 17.98 53.35 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11590.00 47.69 74.00 -26.31 44.63 38.31 14.98 50.23 --- --- Peak 2 17385.00 49.74 68.30 -18.56 42.27 42.84 17.98 53.35 --- --- Peak

Mode	18	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_Full_5775MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5647.95 59.13 68.30 -9.17 44.85 36.24 10.80 32.76 244 36 PEAK 2 5655.83 64.34 72.62 -8.28 50.03 36.25 10.82 32.76 244 36 PEAK 3 5700.10 76.74 105.23 -28.49 62.31 36.32 10.89 32.78 244 36 PEAK 4 5720.05 76.30 110.91 -34.61 61.86 36.35 10.88 32.79 244 36 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5775.00 104.54 ------ ------ 90.08 36.44 10.83 32.81 244 36 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5775.00 96.75 ------ ------ 82.29 36.43 10.84 32.81 244 36 AVERAGE

Mode	18	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_Full_5775MHz	
ANT	SISO	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5854.63 65.19 111.65 -46.46 50.63 36.57 10.83 32.84 244 36 PEAK 2 5870.38 64.49 106.49 -42.00 49.92 36.59 10.83 32.85 244 36 PEAK 3 5924.80 53.52 68.35 -14.83 38.82 36.68 10.89 32.87 244 36 PEAK 4 5928.83 53.57 68.30 -14.73 38.86 36.69 10.89 32.87 244 36 PEAK	Blank

Mode	18	
	Band Edge - L	
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_Full_5775MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5646.90 60.03 68.30 -8.27 45.75 36.24 10.80 32.76 104 248 PEAK 2 5656.00 65.43 72.75 -7.32 51.12 36.25 10.82 32.76 104 248 PEAK 3 5702.03 79.42 105.77 -26.35 64.99 36.32 10.89 32.78 104 248 PEAK 4 5720.05 79.14 110.91 -31.77 64.70 36.35 10.88 32.79 104 248 PEAK	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5775.00 107.42 ------ ------ 92.97 36.42 10.84 32.81 104 248 PEAK
Avg	Blank	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark 1 5775.00 99.11 ------ ------ 84.65 36.43 10.84 32.81 104 248 AVERAGE

Mode	18	
	Band Edge - R	
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_Full_5775MHz	
ANT	SISO	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin (dB) Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dBuV dB/m dB dB cm deg 1 5854.80 70.04 111.26 -41.22 55.48 36.57 10.83 32.84 104 248 PEAK 2 5866.18 70.75 107.67 -36.92 56.18 36.59 10.83 32.85 104 248 PEAK 3 5923.93 54.14 68.99 -14.85 39.45 36.68 10.88 32.87 104 248 PEAK 4 5927.60 54.57 68.30 -13.73 39.87 36.68 10.89 32.87 104 248 PEAK	Blank

Mode	18	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_Full_5775MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11550.00 47.44 74.00 -26.56 44.46 38.28 14.96 50.26 --- --- Peak 2 17325.00 48.36 68.30 -19.94 40.75 42.83 18.00 53.22 --- --- Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB cm deg 1 11550.00 47.57 74.00 -26.43 44.59 38.28 14.96 50.26 --- --- Peak 2 17325.00 48.96 68.30 -19.34 41.35 42.83 18.00 53.22 --- --- Peak

Mode	19	
	LF	
	U-NII-1_5.15-5.25_802.11ac VHT80-LF_CH42_Full_5210MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
QP/ Peak		

Horizontal:

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	71.71	19.54	40.00	-20.46	36.68	12.65	1.55	31.34	---	---	Peak
2	214.30	26.18	43.50	-17.32	39.01	15.42	2.65	30.90	---	---	Peak
3	318.09	33.79	46.00	-12.21	41.64	19.80	3.21	30.86	---	---	Peak
4	438.37	39.81	46.00	-6.19	43.99	22.75	3.77	30.70	---	---	Peak
5	535.37	35.90	46.00	-10.10	38.03	24.62	4.16	30.91	---	---	Peak
6	797.27	35.51	46.00	-10.49	35.44	26.09	5.07	31.09	---	---	Peak

Vertical:

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	175.50	19.77	43.50	-23.73	32.83	15.53	2.41	31.00	---	---	Peak
2	325.85	25.22	46.00	-20.78	32.85	19.97	3.25	30.85	---	---	Peak
3	439.34	30.05	46.00	-15.95	34.21	22.77	3.77	30.70	---	---	Peak
4	533.43	29.03	46.00	-16.97	31.20	24.57	4.16	30.90	---	---	Peak
5	626.55	29.19	46.00	-16.81	30.57	25.06	4.51	30.95	---	---	Peak
6	838.01	30.12	46.00	-15.88	29.58	26.41	5.19	31.06	---	---	Peak

Mode	20	
	LF	
	U-NII-3_5.725-5.85_802.11ac VHT80-LF_CH155_Full_5775MHz	
ANT	SISO	
Pol.	Horizontal	Vertical
QP/ Peak		

Horizontal:

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	70.74	18.77	40.00	-21.23	36.00	12.57	1.54	31.34	---	---	Peak
2	217.21	26.79	46.00	-19.21	39.66	15.36	2.67	30.90	---	---	Peak
3	310.33	34.92	46.00	-11.08	43.00	19.63	3.17	30.88	---	---	Peak
4	442.25	39.03	46.00	-6.97	43.11	22.83	3.79	30.70	---	---	Peak
5	537.31	36.50	46.00	-9.50	38.58	24.67	4.17	30.92	---	---	Peak
6	796.30	35.24	46.00	-10.76	35.18	26.08	5.07	31.09	---	---	Peak

Vertical:

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	34.85	17.25	40.00	-22.75	25.06	22.30	1.09	31.20	---	---	Peak
2	191.02	19.31	43.50	-24.19	32.51	15.23	2.51	30.94	---	---	Peak
3	442.25	30.19	46.00	-15.81	34.27	22.83	3.79	30.70	---	---	Peak
4	534.40	29.70	46.00	-16.30	31.86	24.59	4.16	30.91	---	---	Peak
5	623.64	28.60	46.00	-17.40	30.00	25.04	4.51	30.95	---	---	Peak
6	816.67	31.41	46.00	-14.59	31.13	26.23	5.13	31.08	---	---	Peak

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	98.54	-	-	10Hz
802.11n HT20	98.10	-	-	10Hz
802.11n HT40	95.89	0.84	1.190	3KHz
802.11ac VHT80	92.04	0.416	2.404	3KHz

802.11a



802.11n HT20



802.11n HT40



802.11ac VHT80