

ES3DV3- SN:3327

September 18, 2017

|           |                                                                     |   |       |        |       |       |       |         |
|-----------|---------------------------------------------------------------------|---|-------|--------|-------|-------|-------|---------|
| 10303-AAA | IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)                 | X | 6.05  | 69.28  | 19.90 | 4.96  | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 5.86  | 69.13  | 19.26 |       | 80.0  |         |
|           |                                                                     | Z | 5.72  | 69.31  | 19.60 |       | 80.0  |         |
| 10304-AAA | IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)                 | X | 5.68  | 68.47  | 19.01 | 4.17  | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 5.51  | 68.51  | 18.52 |       | 80.0  |         |
|           |                                                                     | Z | 5.42  | 68.81  | 18.90 |       | 80.0  |         |
| 10305-AAA | IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)    | X | 8.90  | 82.64  | 26.81 | 6.02  | 50.0  | ± 9.6 % |
|           |                                                                     | Y | 10.24 | 84.42  | 26.04 |       | 50.0  |         |
|           |                                                                     | Z | 8.13  | 81.10  | 25.22 |       | 50.0  |         |
| 10306-AAA | IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)    | X | 6.52  | 72.41  | 22.10 | 6.02  | 50.0  | ± 9.6 % |
|           |                                                                     | Y | 7.29  | 76.07  | 23.16 |       | 50.0  |         |
|           |                                                                     | Z | 6.04  | 71.95  | 21.29 |       | 50.0  |         |
| 10307-AAA | IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)     | X | 6.63  | 73.21  | 22.29 | 6.02  | 50.0  | ± 9.6 % |
|           |                                                                     | Y | 7.59  | 77.28  | 23.50 |       | 50.0  |         |
|           |                                                                     | Z | 6.62  | 75.37  | 23.03 |       | 50.0  |         |
| 10308-AAA | IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)                | X | 6.71  | 73.72  | 22.54 | 6.02  | 50.0  | ± 9.6 % |
|           |                                                                     | Y | 7.86  | 78.26  | 23.94 |       | 50.0  |         |
|           |                                                                     | Z | 6.80  | 76.23  | 23.44 |       | 50.0  |         |
| 10309-AAA | IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols) | X | 6.65  | 72.80  | 22.31 | 6.02  | 50.0  | ± 9.6 % |
|           |                                                                     | Y | 7.35  | 76.27  | 23.30 |       | 50.0  |         |
|           |                                                                     | Z | 6.09  | 72.14  | 21.44 |       | 50.0  |         |
| 10310-AAA | IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)  | X | 6.54  | 72.70  | 22.14 | 6.02  | 50.0  | ± 9.6 % |
|           |                                                                     | Y | 7.44  | 76.67  | 23.34 |       | 50.0  |         |
|           |                                                                     | Z | 6.05  | 72.19  | 21.34 |       | 50.0  |         |
| 10311-AAC | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                            | X | 3.29  | 69.79  | 16.61 | 0.00  | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 2.99  | 68.72  | 16.15 |       | 150.0 |         |
|           |                                                                     | Z | 3.30  | 70.83  | 17.40 |       | 150.0 |         |
| 10313-AAA | iDEN 1:3                                                            | X | 8.07  | 79.86  | 19.14 | 6.99  | 70.0  | ± 9.6 % |
|           |                                                                     | Y | 8.83  | 81.65  | 20.11 |       | 70.0  |         |
|           |                                                                     | Z | 15.21 | 90.66  | 22.90 |       | 70.0  |         |
| 10314-AAA | iDEN 1:6                                                            | X | 11.11 | 87.33  | 24.20 | 10.00 | 30.0  | ± 9.6 % |
|           |                                                                     | Y | 12.39 | 89.84  | 25.45 |       | 30.0  |         |
|           |                                                                     | Z | 33.08 | 108.48 | 30.94 |       | 30.0  |         |
| 10315-AAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)           | X | 1.16  | 65.10  | 15.99 | 0.17  | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 1.18  | 64.55  | 15.38 |       | 150.0 |         |
|           |                                                                     | Z | 1.23  | 66.36  | 16.95 |       | 150.0 |         |
| 10316-AAB | IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)       | X | 4.73  | 67.03  | 16.54 | 0.17  | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 4.57  | 67.10  | 16.39 |       | 150.0 |         |
|           |                                                                     | Z | 4.58  | 67.49  | 16.75 |       | 150.0 |         |
| 10317-AAB | IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)             | X | 4.73  | 67.03  | 16.54 | 0.17  | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 4.57  | 67.10  | 16.39 |       | 150.0 |         |
|           |                                                                     | Z | 4.58  | 67.49  | 16.75 |       | 150.0 |         |
| 10400-AAC | IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)                 | X | 4.83  | 67.28  | 16.45 | 0.00  | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 4.59  | 67.22  | 16.28 |       | 150.0 |         |
|           |                                                                     | Z | 4.63  | 67.67  | 16.67 |       | 150.0 |         |
| 10401-AAC | IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)                 | X | 5.49  | 67.42  | 16.59 | 0.00  | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 5.31  | 67.33  | 16.45 |       | 150.0 |         |
|           |                                                                     | Z | 5.32  | 67.62  | 16.73 |       | 150.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                                                |   |        |        |       |      |       |         |
|-----------|--------------------------------------------------------------------------------|---|--------|--------|-------|------|-------|---------|
| 10402-AAC | IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)                            | X | 5.77   | 67.84  | 16.63 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 5.58   | 67.64  | 16.47 |      | 150.0 |         |
|           |                                                                                | Z | 5.61   | 67.94  | 16.75 |      | 150.0 |         |
| 10403-AAB | CDMA2000 (1xEV-DO, Rev. 0)                                                     | X | 1.73   | 70.88  | 15.41 | 0.00 | 115.0 | ± 9.6 % |
|           |                                                                                | Y | 1.22   | 67.33  | 12.63 |      | 115.0 |         |
|           |                                                                                | Z | 2.22   | 75.74  | 16.43 |      | 115.0 |         |
| 10404-AAB | CDMA2000 (1xEV-DO, Rev. A)                                                     | X | 1.73   | 70.88  | 15.41 | 0.00 | 115.0 | ± 9.6 % |
|           |                                                                                | Y | 1.22   | 67.33  | 12.63 |      | 115.0 |         |
|           |                                                                                | Z | 2.22   | 75.74  | 16.43 |      | 115.0 |         |
| 10406-AAB | CDMA2000, RC3, SO32, SCH0, Full Rate                                           | X | 100.00 | 122.28 | 30.90 | 0.00 | 100.0 | ± 9.6 % |
|           |                                                                                | Y | 100.00 | 118.47 | 28.84 |      | 100.0 |         |
|           |                                                                                | Z | 100.00 | 118.59 | 28.66 |      | 100.0 |         |
| 10410-AAC | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                 | X | 100.00 | 119.85 | 30.23 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                                | Y | 100.00 | 122.08 | 31.09 |      | 80.0  |         |
|           |                                                                                | Z | 100.00 | 125.17 | 32.17 |      | 80.0  |         |
| 10415-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)                      | X | 1.01   | 63.51  | 15.07 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 1.04   | 63.14  | 14.54 |      | 150.0 |         |
|           |                                                                                | Z | 1.08   | 64.75  | 16.03 |      | 150.0 |         |
| 10416-AAA | IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)                  | X | 4.63   | 66.88  | 16.38 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 4.46   | 66.93  | 16.23 |      | 150.0 |         |
|           |                                                                                | Z | 4.50   | 67.36  | 16.60 |      | 150.0 |         |
| 10417-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)                      | X | 4.63   | 66.88  | 16.38 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 4.46   | 66.93  | 16.23 |      | 150.0 |         |
|           |                                                                                | Z | 4.50   | 67.36  | 16.60 |      | 150.0 |         |
| 10418-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)  | X | 4.62   | 67.02  | 16.38 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 4.46   | 67.11  | 16.27 |      | 150.0 |         |
|           |                                                                                | Z | 4.50   | 67.57  | 16.66 |      | 150.0 |         |
| 10419-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble) | X | 4.64   | 66.98  | 16.39 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 4.48   | 67.05  | 16.27 |      | 150.0 |         |
|           |                                                                                | Z | 4.51   | 67.50  | 16.65 |      | 150.0 |         |
| 10422-AAA | IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)                                   | X | 4.77   | 66.98  | 16.41 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 4.58   | 67.04  | 16.28 |      | 150.0 |         |
|           |                                                                                | Z | 4.62   | 67.46  | 16.64 |      | 150.0 |         |
| 10423-AAA | IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)                                | X | 4.96   | 67.35  | 16.54 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 4.72   | 67.31  | 16.38 |      | 150.0 |         |
|           |                                                                                | Z | 4.76   | 67.74  | 16.74 |      | 150.0 |         |
| 10424-AAA | IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)                                | X | 4.87   | 67.29  | 16.51 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 4.65   | 67.27  | 16.35 |      | 150.0 |         |
|           |                                                                                | Z | 4.68   | 67.70  | 16.72 |      | 150.0 |         |
| 10425-AAA | IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)                                    | X | 5.47   | 67.66  | 16.69 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 5.28   | 67.54  | 16.56 |      | 150.0 |         |
|           |                                                                                | Z | 5.30   | 67.87  | 16.86 |      | 150.0 |         |
| 10426-AAA | IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)                                  | X | 5.47   | 67.67  | 16.70 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                                | Y | 5.30   | 67.63  | 16.60 |      | 150.0 |         |
|           |                                                                                | Z | 5.32   | 67.97  | 16.91 |      | 150.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                                |   |        |        |       |      |       |         |
|-----------|----------------------------------------------------------------|---|--------|--------|-------|------|-------|---------|
| 10427-AAA | IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)                 | X | 5.48   | 67.65  | 16.68 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 5.28   | 67.47  | 16.52 |      | 150.0 |         |
|           |                                                                | Z | 5.30   | 67.79  | 16.81 |      | 150.0 |         |
| 10430-AAB | LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)                               | X | 4.27   | 70.32  | 18.07 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 4.18   | 71.48  | 18.11 |      | 150.0 |         |
|           |                                                                | Z | 4.34   | 72.56  | 18.76 |      | 150.0 |         |
| 10431-AAB | LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)                              | X | 4.35   | 67.46  | 16.43 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 4.09   | 67.47  | 16.14 |      | 150.0 |         |
|           |                                                                | Z | 4.15   | 68.09  | 16.61 |      | 150.0 |         |
| 10432-AAB | LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)                              | X | 4.64   | 67.34  | 16.47 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 4.41   | 67.34  | 16.28 |      | 150.0 |         |
|           |                                                                | Z | 4.46   | 67.84  | 16.69 |      | 150.0 |         |
| 10433-AAB | LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)                              | X | 4.88   | 67.33  | 16.53 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 4.67   | 67.30  | 16.37 |      | 150.0 |         |
|           |                                                                | Z | 4.70   | 67.73  | 16.74 |      | 150.0 |         |
| 10434-AAA | W-CDMA (BS Test Model 1, 64 DPCH)                              | X | 4.35   | 71.06  | 18.04 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 4.27   | 72.31  | 17.96 |      | 150.0 |         |
|           |                                                                | Z | 4.52   | 73.72  | 18.74 |      | 150.0 |         |
| 10435-AAC | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9) | X | 100.00 | 119.68 | 30.15 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                | Y | 100.00 | 121.88 | 31.00 |      | 80.0  |         |
|           |                                                                | Z | 100.00 | 124.93 | 32.06 |      | 80.0  |         |
| 10447-AAB | LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)                 | X | 3.66   | 67.53  | 15.89 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 3.34   | 67.34  | 15.17 |      | 150.0 |         |
|           |                                                                | Z | 3.46   | 68.32  | 15.83 |      | 150.0 |         |
| 10448-AAB | LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)                | X | 4.17   | 67.23  | 16.28 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 3.95   | 67.26  | 16.01 |      | 150.0 |         |
|           |                                                                | Z | 4.01   | 67.90  | 16.49 |      | 150.0 |         |
| 10449-AAB | LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)                | X | 4.44   | 67.16  | 16.36 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 4.24   | 67.16  | 16.17 |      | 150.0 |         |
|           |                                                                | Z | 4.29   | 67.68  | 16.60 |      | 150.0 |         |
| 10450-AAB | LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)                | X | 4.62   | 67.08  | 16.38 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 4.45   | 67.07  | 16.22 |      | 150.0 |         |
|           |                                                                | Z | 4.49   | 67.52  | 16.61 |      | 150.0 |         |
| 10451-AAA | W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)                | X | 3.58   | 67.79  | 15.60 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 3.18   | 67.28  | 14.57 |      | 150.0 |         |
|           |                                                                | Z | 3.32   | 68.40  | 15.29 |      | 150.0 |         |
| 10456-AAA | IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)           | X | 6.33   | 68.22  | 16.84 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 6.23   | 68.24  | 16.81 |      | 150.0 |         |
|           |                                                                | Z | 6.25   | 68.51  | 17.06 |      | 150.0 |         |
| 10457-AAA | UMTS-FDD (DC-HSDPA)                                            | X | 3.83   | 65.50  | 16.10 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 3.79   | 65.63  | 15.94 |      | 150.0 |         |
|           |                                                                | Z | 3.81   | 66.04  | 16.33 |      | 150.0 |         |
| 10458-AAA | CDMA2000 (1xEV-DO, Rev. B, 2 carriers)                         | X | 3.99   | 70.32  | 17.52 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 3.82   | 71.13  | 16.98 |      | 150.0 |         |
|           |                                                                | Z | 4.09   | 72.71  | 17.84 |      | 150.0 |         |
| 10459-AAA | CDMA2000 (1xEV-DO, Rev. B, 3 carriers)                         | X | 5.08   | 67.72  | 17.95 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                | Y | 4.90   | 68.78  | 17.85 |      | 150.0 |         |
|           |                                                                | Z | 4.95   | 69.25  | 18.16 |      | 150.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                                   |   |        |        |       |      |       |         |
|-----------|-------------------------------------------------------------------|---|--------|--------|-------|------|-------|---------|
| 10460-AAA | UMTS-FDD (WCDMA, AMR)                                             | X | 1.00   | 70.54  | 17.39 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                   | Y | 0.89   | 67.63  | 15.73 |      | 150.0 |         |
|           |                                                                   | Z | 1.29   | 75.71  | 20.27 |      | 150.0 |         |
| 10461-AAA | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)   | X | 100.00 | 123.73 | 32.09 | 3.29 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 126.11 | 33.00 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 133.47 | 35.95 |      | 80.0  |         |
| 10462-AAA | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9) | X | 100.00 | 108.15 | 24.66 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 109.08 | 24.89 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 111.50 | 25.54 |      | 80.0  |         |
| 10463-AAA | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | X | 31.96  | 93.47  | 20.50 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 29.26  | 93.31  | 20.41 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 106.95 | 23.40 |      | 80.0  |         |
| 10464-AAA | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | X | 100.00 | 121.71 | 30.99 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 124.09 | 31.91 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 131.36 | 34.79 |      | 80.0  |         |
| 10465-AAA | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | X | 100.00 | 107.66 | 24.42 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 108.57 | 24.64 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 110.83 | 25.23 |      | 80.0  |         |
| 10466-AAA | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | X | 17.31  | 86.93  | 18.72 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 13.43  | 85.13  | 18.19 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 106.32 | 23.11 |      | 80.0  |         |
| 10467-AAC | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | X | 100.00 | 121.92 | 31.09 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 124.35 | 32.03 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 131.68 | 34.94 |      | 80.0  |         |
| 10468-AAC | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | X | 100.00 | 107.81 | 24.49 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 108.76 | 24.73 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 111.09 | 25.34 |      | 80.0  |         |
| 10469-AAC | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | X | 17.75  | 87.20  | 18.79 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 14.00  | 85.57  | 18.31 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 106.37 | 23.13 |      | 80.0  |         |
| 10470-AAC | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | X | 100.00 | 121.94 | 31.09 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 124.37 | 32.03 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 131.73 | 34.95 |      | 80.0  |         |
| 10471-AAC | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | X | 100.00 | 107.76 | 24.46 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 108.72 | 24.71 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 111.03 | 25.31 |      | 80.0  |         |
| 10472-AAC | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | X | 17.66  | 87.12  | 18.76 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 13.95  | 85.51  | 18.28 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 106.29 | 23.09 |      | 80.0  |         |
| 10473-AAC | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | X | 100.00 | 121.91 | 31.08 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 124.35 | 32.02 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 131.71 | 34.94 |      | 80.0  |         |
| 10474-AAC | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | X | 100.00 | 107.77 | 24.46 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 100.00 | 108.72 | 24.71 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 111.04 | 25.31 |      | 80.0  |         |
| 10475-AAC | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | X | 17.40  | 86.97  | 18.72 | 3.23 | 80.0  | ± 9.6 % |
|           |                                                                   | Y | 13.69  | 85.34  | 18.23 |      | 80.0  |         |
|           |                                                                   | Z | 100.00 | 106.31 | 23.09 |      | 80.0  |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                                     |   |        |        |       |      |      |         |
|-----------|---------------------------------------------------------------------|---|--------|--------|-------|------|------|---------|
| 10477-AAC | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)    | X | 100.00 | 107.61 | 24.38 | 3.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 100.00 | 108.54 | 24.62 |      | 80.0 |         |
|           |                                                                     | Z | 100.00 | 110.80 | 25.20 |      | 80.0 |         |
| 10478-AAC | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)    | X | 17.05  | 86.74  | 18.65 | 3.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 13.36  | 85.05  | 18.15 |      | 80.0 |         |
|           |                                                                     | Z | 100.00 | 106.23 | 23.06 |      | 80.0 |         |
| 10479-AAA | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)   | X | 16.38  | 96.25  | 26.55 | 3.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 67.88  | 117.63 | 31.48 |      | 80.0 |         |
|           |                                                                     | Z | 100.00 | 127.65 | 34.56 |      | 80.0 |         |
| 10480-AAA | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9) | X | 16.32  | 90.60  | 23.14 | 3.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 50.74  | 104.65 | 25.94 |      | 80.0 |         |
|           |                                                                     | Z | 100.00 | 115.88 | 28.82 |      | 80.0 |         |
| 10481-AAA | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | X | 13.22  | 86.87  | 21.66 | 3.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 27.03  | 95.30  | 23.07 |      | 80.0 |         |
|           |                                                                     | Z | 100.00 | 113.38 | 27.67 |      | 80.0 |         |
| 10482-AAA | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | X | 6.63   | 81.21  | 20.60 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 5.02   | 76.82  | 18.00 |      | 80.0 |         |
|           |                                                                     | Z | 15.01  | 92.87  | 23.34 |      | 80.0 |         |
| 10483-AAA | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | X | 8.49   | 81.37  | 20.38 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 7.54   | 78.76  | 18.15 |      | 80.0 |         |
|           |                                                                     | Z | 35.01  | 99.36  | 24.35 |      | 80.0 |         |
| 10484-AAA | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | X | 7.78   | 79.92  | 19.89 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 6.47   | 76.62  | 17.39 |      | 80.0 |         |
|           |                                                                     | Z | 20.63  | 92.43  | 22.48 |      | 80.0 |         |
| 10485-AAC | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | X | 6.69   | 81.72  | 21.56 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 5.83   | 79.61  | 20.17 |      | 80.0 |         |
|           |                                                                     | Z | 12.75  | 92.98  | 24.87 |      | 80.0 |         |
| 10486-AAC | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | X | 4.98   | 74.19  | 18.44 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 4.45   | 72.65  | 16.90 |      | 80.0 |         |
|           |                                                                     | Z | 6.10   | 78.25  | 19.23 |      | 80.0 |         |
| 10487-AAC | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | X | 4.89   | 73.60  | 18.21 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 4.34   | 71.99  | 16.61 |      | 80.0 |         |
|           |                                                                     | Z | 5.72   | 76.98  | 18.74 |      | 80.0 |         |
| 10488-AAC | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | X | 6.16   | 79.05  | 21.16 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 5.43   | 77.51  | 20.38 |      | 80.0 |         |
|           |                                                                     | Z | 7.50   | 84.30  | 23.25 |      | 80.0 |         |
| 10489-AAC | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | X | 4.90   | 72.90  | 18.94 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 4.67   | 72.57  | 18.39 |      | 80.0 |         |
|           |                                                                     | Z | 5.24   | 75.60  | 19.93 |      | 80.0 |         |
| 10490-AAC | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | X | 4.95   | 72.51  | 18.81 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 4.72   | 72.25  | 18.27 |      | 80.0 |         |
|           |                                                                     | Z | 5.22   | 75.01  | 19.69 |      | 80.0 |         |
| 10491-AAC | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | X | 5.72   | 75.84  | 20.07 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 5.20   | 74.82  | 19.59 |      | 80.0 |         |
|           |                                                                     | Z | 6.10   | 78.75  | 21.47 |      | 80.0 |         |
| 10492-AAC | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | X | 5.06   | 71.53  | 18.65 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                     | Y | 4.83   | 71.25  | 18.27 |      | 80.0 |         |
|           |                                                                     | Z | 5.09   | 73.11  | 19.35 |      | 80.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                                      |   |      |       |       |      |      |         |
|-----------|----------------------------------------------------------------------|---|------|-------|-------|------|------|---------|
| 10493-AAC | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | X | 5.11 | 71.29 | 18.57 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 4.87 | 71.04 | 18.18 |      | 80.0 |         |
|           |                                                                      | Z | 5.10 | 72.78 | 19.21 |      | 80.0 |         |
| 10494-AAC | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | X | 6.48 | 77.93 | 20.67 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 5.71 | 76.40 | 20.08 |      | 80.0 |         |
|           |                                                                      | Z | 7.06 | 81.21 | 22.25 |      | 80.0 |         |
| 10495-AAC | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | X | 5.17 | 72.11 | 18.89 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 4.89 | 71.61 | 18.49 |      | 80.0 |         |
|           |                                                                      | Z | 5.16 | 73.55 | 19.61 |      | 80.0 |         |
| 10496-AAC | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | X | 5.18 | 71.63 | 18.73 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 4.93 | 71.25 | 18.37 |      | 80.0 |         |
|           |                                                                      | Z | 5.15 | 72.98 | 19.40 |      | 80.0 |         |
| 10497-AAA | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)   | X | 5.04 | 76.98 | 18.31 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 3.11 | 70.04 | 14.27 |      | 80.0 |         |
|           |                                                                      | Z | 7.13 | 80.83 | 18.17 |      | 80.0 |         |
| 10498-AAA | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9) | X | 3.32 | 68.67 | 14.12 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 1.86 | 62.15 | 9.60  |      | 80.0 |         |
|           |                                                                      | Z | 1.91 | 63.20 | 10.07 |      | 80.0 |         |
| 10499-AAA | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | X | 3.19 | 67.89 | 13.65 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 1.77 | 61.49 | 9.11  |      | 80.0 |         |
|           |                                                                      | Z | 1.75 | 62.15 | 9.39  |      | 80.0 |         |
| 10500-AAA | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | X | 6.19 | 79.93 | 21.18 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 5.54 | 78.44 | 20.15 |      | 80.0 |         |
|           |                                                                      | Z | 9.37 | 88.20 | 23.88 |      | 80.0 |         |
| 10501-AAA | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | X | 4.93 | 73.55 | 18.58 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 4.60 | 72.81 | 17.53 |      | 80.0 |         |
|           |                                                                      | Z | 5.75 | 77.30 | 19.53 |      | 80.0 |         |
| 10502-AAA | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | X | 4.94 | 73.24 | 18.41 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 4.60 | 72.48 | 17.33 |      | 80.0 |         |
|           |                                                                      | Z | 5.68 | 76.71 | 19.23 |      | 80.0 |         |
| 10503-AAC | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | X | 6.08 | 78.83 | 21.06 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 5.35 | 77.27 | 20.28 |      | 80.0 |         |
|           |                                                                      | Z | 7.35 | 83.97 | 23.12 |      | 80.0 |         |
| 10504-AAC | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | X | 4.88 | 72.81 | 18.90 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 4.64 | 72.45 | 18.33 |      | 80.0 |         |
|           |                                                                      | Z | 5.21 | 75.46 | 19.86 |      | 80.0 |         |
| 10505-AAC | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | X | 4.92 | 72.42 | 18.76 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 4.69 | 72.14 | 18.21 |      | 80.0 |         |
|           |                                                                      | Z | 5.18 | 74.89 | 19.63 |      | 80.0 |         |
| 10506-AAC | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | X | 8.42 | 77.77 | 20.60 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 5.66 | 76.23 | 20.00 |      | 80.0 |         |
|           |                                                                      | Z | 6.98 | 81.00 | 22.16 |      | 80.0 |         |
| 10507-AAC | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | X | 5.15 | 72.05 | 18.85 | 2.23 | 80.0 | ± 9.6 % |
|           |                                                                      | Y | 4.87 | 71.55 | 18.45 |      | 80.0 |         |
|           |                                                                      | Z | 5.14 | 73.48 | 19.57 |      | 80.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                                     |   |      |       |       |      |       |         |
|-----------|---------------------------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10508-AAC | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | X | 5.17 | 71.57 | 18.70 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 4.91 | 71.17 | 18.33 |      | 80.0  |         |
|           |                                                                     | Z | 5.13 | 72.90 | 19.35 |      | 80.0  |         |
| 10509-AAC | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)   | X | 6.19 | 75.06 | 19.59 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 5.68 | 74.12 | 19.23 |      | 80.0  |         |
|           |                                                                     | Z | 6.37 | 77.07 | 20.71 |      | 80.0  |         |
| 10510-AAC | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9) | X | 5.54 | 71.31 | 18.62 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 5.25 | 70.80 | 18.30 |      | 80.0  |         |
|           |                                                                     | Z | 5.40 | 72.14 | 19.15 |      | 80.0  |         |
| 10511-AAC | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | X | 5.54 | 70.92 | 18.51 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 5.29 | 70.52 | 18.22 |      | 80.0  |         |
|           |                                                                     | Z | 5.40 | 71.73 | 19.01 |      | 80.0  |         |
| 10512-AAC | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)   | X | 6.86 | 77.40 | 20.31 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 6.07 | 75.81 | 19.75 |      | 80.0  |         |
|           |                                                                     | Z | 7.22 | 79.78 | 21.58 |      | 80.0  |         |
| 10513-AAC | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9) | X | 5.49 | 71.84 | 18.82 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 5.17 | 71.11 | 18.43 |      | 80.0  |         |
|           |                                                                     | Z | 5.35 | 72.60 | 19.35 |      | 80.0  |         |
| 10514-AAC | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | X | 5.43 | 71.22 | 18.64 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                                     | Y | 5.16 | 70.64 | 18.29 |      | 80.0  |         |
|           |                                                                     | Z | 5.29 | 71.94 | 19.13 |      | 80.0  |         |
| 10515-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)           | X | 0.98 | 63.75 | 15.16 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 1.00 | 63.29 | 14.58 |      | 150.0 |         |
|           |                                                                     | Z | 1.05 | 65.08 | 16.19 |      | 150.0 |         |
| 10516-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)         | X | 0.83 | 76.97 | 20.27 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 0.59 | 68.72 | 16.49 |      | 150.0 |         |
|           |                                                                     | Z | 1.51 | 88.84 | 26.21 |      | 150.0 |         |
| 10517-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)          | X | 0.85 | 66.36 | 16.14 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 0.84 | 64.88 | 15.08 |      | 150.0 |         |
|           |                                                                     | Z | 0.96 | 68.59 | 17.81 |      | 150.0 |         |
| 10518-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)           | X | 4.63 | 66.95 | 16.36 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 4.45 | 67.02 | 16.22 |      | 150.0 |         |
|           |                                                                     | Z | 4.49 | 67.46 | 16.60 |      | 150.0 |         |
| 10519-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)          | X | 4.83 | 67.23 | 16.49 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 4.61 | 67.21 | 16.32 |      | 150.0 |         |
|           |                                                                     | Z | 4.64 | 67.64 | 16.69 |      | 150.0 |         |
| 10520-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)          | X | 4.68 | 67.20 | 16.42 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 4.47 | 67.14 | 16.23 |      | 150.0 |         |
|           |                                                                     | Z | 4.50 | 67.60 | 16.62 |      | 150.0 |         |
| 10521-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)          | X | 4.62 | 67.21 | 16.40 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 4.40 | 67.12 | 16.21 |      | 150.0 |         |
|           |                                                                     | Z | 4.44 | 67.58 | 16.61 |      | 150.0 |         |
| 10522-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)          | X | 4.67 | 67.23 | 16.46 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                     | Y | 4.46 | 67.25 | 16.31 |      | 150.0 |         |
|           |                                                                     | Z | 4.49 | 67.72 | 16.71 |      | 150.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                            |   |      |       |       |      |       |         |
|-----------|------------------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10523-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle) | X | 4.54 | 67.10 | 16.30 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.37 | 67.19 | 16.20 |      | 150.0 |         |
|           |                                                            | Z | 4.41 | 67.68 | 16.61 |      | 150.0 |         |
| 10524-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle) | X | 4.62 | 67.18 | 16.44 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.40 | 67.18 | 16.29 |      | 150.0 |         |
|           |                                                            | Z | 4.44 | 67.66 | 16.69 |      | 150.0 |         |
| 10525-AAA | IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)          | X | 4.58 | 66.20 | 16.02 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.42 | 66.27 | 15.90 |      | 150.0 |         |
|           |                                                            | Z | 4.47 | 66.74 | 16.29 |      | 150.0 |         |
| 10526-AAA | IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)          | X | 4.78 | 66.60 | 16.17 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.55 | 66.57 | 16.02 |      | 150.0 |         |
|           |                                                            | Z | 4.60 | 67.05 | 16.42 |      | 150.0 |         |
| 10527-AAA | IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)          | X | 4.69 | 66.56 | 16.12 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.48 | 66.53 | 15.96 |      | 150.0 |         |
|           |                                                            | Z | 4.53 | 67.03 | 16.37 |      | 150.0 |         |
| 10528-AAA | IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)          | X | 4.71 | 66.58 | 16.15 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.50 | 66.55 | 15.99 |      | 150.0 |         |
|           |                                                            | Z | 4.55 | 67.04 | 16.40 |      | 150.0 |         |
| 10529-AAA | IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)          | X | 4.71 | 66.58 | 16.15 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.50 | 66.55 | 15.99 |      | 150.0 |         |
|           |                                                            | Z | 4.55 | 67.04 | 16.40 |      | 150.0 |         |
| 10531-AAA | IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)          | X | 4.72 | 66.72 | 16.18 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.47 | 66.59 | 15.98 |      | 150.0 |         |
|           |                                                            | Z | 4.52 | 67.10 | 16.39 |      | 150.0 |         |
| 10532-AAA | IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)          | X | 4.57 | 66.58 | 16.11 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.35 | 66.45 | 15.91 |      | 150.0 |         |
|           |                                                            | Z | 4.40 | 66.96 | 16.33 |      | 150.0 |         |
| 10533-AAA | IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)          | X | 4.72 | 66.61 | 16.13 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 4.50 | 66.62 | 15.99 |      | 150.0 |         |
|           |                                                            | Z | 4.56 | 67.13 | 16.40 |      | 150.0 |         |
| 10534-AAA | IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)          | X | 5.23 | 66.71 | 16.20 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 5.06 | 66.61 | 16.08 |      | 150.0 |         |
|           |                                                            | Z | 5.09 | 66.98 | 16.40 |      | 150.0 |         |
| 10535-AAA | IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)          | X | 5.30 | 66.87 | 16.26 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 5.11 | 66.77 | 16.15 |      | 150.0 |         |
|           |                                                            | Z | 5.15 | 67.15 | 16.48 |      | 150.0 |         |
| 10536-AAA | IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)          | X | 5.17 | 66.84 | 16.23 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 5.00 | 66.75 | 16.12 |      | 150.0 |         |
|           |                                                            | Z | 5.04 | 67.15 | 16.46 |      | 150.0 |         |
| 10537-AAA | IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)          | X | 5.23 | 66.82 | 16.22 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 5.05 | 66.72 | 16.11 |      | 150.0 |         |
|           |                                                            | Z | 5.09 | 67.11 | 16.44 |      | 150.0 |         |
| 10538-AAA | IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)          | X | 5.34 | 66.88 | 16.30 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 5.13 | 66.71 | 16.14 |      | 150.0 |         |
|           |                                                            | Z | 5.16 | 67.07 | 16.46 |      | 150.0 |         |
| 10540-AAA | IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)          | X | 5.25 | 66.84 | 16.29 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                            | Y | 5.06 | 66.68 | 16.14 |      | 150.0 |         |
|           |                                                            | Z | 5.09 | 67.05 | 16.47 |      | 150.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                    |   |      |       |       |      |       |         |
|-----------|----------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10541-AAA | IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)  | X | 5.22 | 66.72 | 16.22 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.03 | 66.57 | 16.07 |      | 150.0 |         |
|           |                                                    | Z | 5.07 | 66.94 | 16.40 |      | 150.0 |         |
| 10542-AAA | IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)  | X | 5.38 | 66.79 | 16.27 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.19 | 66.68 | 16.14 |      | 150.0 |         |
|           |                                                    | Z | 5.22 | 67.03 | 16.46 |      | 150.0 |         |
| 10543-AAA | IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)  | X | 5.47 | 66.81 | 16.30 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.26 | 66.71 | 16.19 |      | 150.0 |         |
|           |                                                    | Z | 5.29 | 67.07 | 16.50 |      | 150.0 |         |
| 10544-AAA | IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)  | X | 5.52 | 66.80 | 16.18 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.40 | 66.71 | 16.07 |      | 150.0 |         |
|           |                                                    | Z | 5.43 | 67.03 | 16.37 |      | 150.0 |         |
| 10545-AAA | IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)  | X | 5.74 | 67.26 | 16.35 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.59 | 67.17 | 16.26 |      | 150.0 |         |
|           |                                                    | Z | 5.62 | 67.51 | 16.56 |      | 150.0 |         |
| 10546-AAA | IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)  | X | 5.62 | 67.08 | 16.28 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.43 | 66.84 | 16.11 |      | 150.0 |         |
|           |                                                    | Z | 5.47 | 67.17 | 16.41 |      | 150.0 |         |
| 10547-AAA | IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)  | X | 5.71 | 67.17 | 16.31 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.51 | 66.94 | 16.15 |      | 150.0 |         |
|           |                                                    | Z | 5.55 | 67.27 | 16.45 |      | 150.0 |         |
| 10548-AAA | IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)  | X | 6.05 | 68.39 | 16.90 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.70 | 67.70 | 16.51 |      | 150.0 |         |
|           |                                                    | Z | 5.74 | 68.06 | 16.82 |      | 150.0 |         |
| 10550-AAA | IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)  | X | 5.63 | 67.05 | 16.27 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.49 | 67.01 | 16.21 |      | 150.0 |         |
|           |                                                    | Z | 5.53 | 67.36 | 16.51 |      | 150.0 |         |
| 10551-AAA | IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)  | X | 5.64 | 67.11 | 16.26 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.45 | 66.86 | 16.09 |      | 150.0 |         |
|           |                                                    | Z | 5.47 | 67.17 | 16.38 |      | 150.0 |         |
| 10552-AAA | IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)  | X | 5.55 | 66.87 | 16.16 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.40 | 66.80 | 16.06 |      | 150.0 |         |
|           |                                                    | Z | 5.44 | 67.13 | 16.36 |      | 150.0 |         |
| 10553-AAA | IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)  | X | 5.64 | 66.93 | 16.21 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.47 | 66.77 | 16.08 |      | 150.0 |         |
|           |                                                    | Z | 5.49 | 67.09 | 16.37 |      | 150.0 |         |
| 10554-AAB | IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle) | X | 5.93 | 67.19 | 16.27 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.82 | 67.06 | 16.16 |      | 150.0 |         |
|           |                                                    | Z | 5.85 | 67.36 | 16.43 |      | 150.0 |         |
| 10555-AAB | IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle) | X | 6.08 | 67.52 | 16.42 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.93 | 67.32 | 16.28 |      | 150.0 |         |
|           |                                                    | Z | 5.96 | 67.63 | 16.55 |      | 150.0 |         |
| 10556-AAB | IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle) | X | 6.09 | 67.55 | 16.42 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.96 | 67.41 | 16.31 |      | 150.0 |         |
|           |                                                    | Z | 5.99 | 67.73 | 16.59 |      | 150.0 |         |
| 10557-AAB | IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle) | X | 6.07 | 67.49 | 16.41 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                    | Y | 5.91 | 67.27 | 16.26 |      | 150.0 |         |
|           |                                                    | Z | 5.94 | 67.58 | 16.53 |      | 150.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                                 |   |        |        |       |      |       |         |
|-----------|-----------------------------------------------------------------|---|--------|--------|-------|------|-------|---------|
| 10558-AAB | IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)              | X | 6.13   | 67.68  | 16.53 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 5.94   | 67.39  | 16.34 |      | 150.0 |         |
|           |                                                                 | Z | 5.97   | 67.69  | 16.61 |      | 150.0 |         |
| 10560-AAB | IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)              | X | 6.12   | 67.49  | 16.47 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 5.94   | 67.27  | 16.31 |      | 150.0 |         |
|           |                                                                 | Z | 5.97   | 67.57  | 16.58 |      | 150.0 |         |
| 10561-AAB | IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)              | X | 6.03   | 67.47  | 16.50 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 5.88   | 67.27  | 16.34 |      | 150.0 |         |
|           |                                                                 | Z | 5.91   | 67.57  | 16.62 |      | 150.0 |         |
| 10562-AAB | IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)              | X | 6.20   | 67.97  | 16.75 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 5.95   | 67.47  | 16.45 |      | 150.0 |         |
|           |                                                                 | Z | 5.98   | 67.78  | 16.73 |      | 150.0 |         |
| 10563-AAB | IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)              | X | 6.58   | 68.66  | 17.04 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 6.04   | 67.41  | 16.38 |      | 150.0 |         |
|           |                                                                 | Z | 6.07   | 67.70  | 16.65 |      | 150.0 |         |
| 10564-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)  | X | 4.97   | 67.09  | 16.55 | 0.46 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 4.79   | 67.11  | 16.40 |      | 150.0 |         |
|           |                                                                 | Z | 4.82   | 67.50  | 16.74 |      | 150.0 |         |
| 10565-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle) | X | 5.21   | 67.54  | 16.86 | 0.46 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 4.99   | 67.51  | 16.70 |      | 150.0 |         |
|           |                                                                 | Z | 5.01   | 67.89  | 17.03 |      | 150.0 |         |
| 10566-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle) | X | 5.05   | 67.42  | 16.70 | 0.46 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 4.83   | 67.35  | 16.52 |      | 150.0 |         |
|           |                                                                 | Z | 4.86   | 67.74  | 16.86 |      | 150.0 |         |
| 10567-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle) | X | 5.07   | 67.76  | 17.01 | 0.46 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 4.86   | 67.73  | 16.87 |      | 150.0 |         |
|           |                                                                 | Z | 4.89   | 68.12  | 17.21 |      | 150.0 |         |
| 10568-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle) | X | 4.97   | 67.22  | 16.49 | 0.46 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 4.74   | 67.15  | 16.30 |      | 150.0 |         |
|           |                                                                 | Z | 4.77   | 67.57  | 16.67 |      | 150.0 |         |
| 10569-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle) | X | 5.01   | 67.80  | 17.03 | 0.46 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 4.85   | 67.94  | 17.00 |      | 150.0 |         |
|           |                                                                 | Z | 4.88   | 68.35  | 17.35 |      | 150.0 |         |
| 10570-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle) | X | 5.06   | 67.67  | 16.99 | 0.46 | 150.0 | ± 9.6 % |
|           |                                                                 | Y | 4.85   | 67.73  | 16.90 |      | 150.0 |         |
|           |                                                                 | Z | 4.88   | 68.13  | 17.24 |      | 150.0 |         |
| 10571-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)       | X | 1.35   | 66.65  | 16.75 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 1.36   | 65.85  | 16.03 |      | 130.0 |         |
|           |                                                                 | Z | 1.42   | 67.88  | 17.67 |      | 130.0 |         |
| 10572-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)       | X | 1.38   | 67.37  | 17.15 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 1.38   | 66.47  | 16.39 |      | 130.0 |         |
|           |                                                                 | Z | 1.45   | 68.73  | 18.16 |      | 130.0 |         |
| 10573-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)     | X | 33.02  | 127.11 | 34.22 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 2.78   | 86.95  | 23.34 |      | 130.0 |         |
|           |                                                                 | Z | 100.00 | 153.11 | 41.78 |      | 130.0 |         |
| 10574-AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)      | X | 1.76   | 75.44  | 20.83 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 1.57   | 72.37  | 19.24 |      | 130.0 |         |
|           |                                                                 | Z | 2.03   | 79.09  | 22.93 |      | 130.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                                 |   |      |       |       |      |       |         |
|-----------|-----------------------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10575-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)  | X | 4.78 | 66.97 | 16.66 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.62 | 67.03 | 16.50 |      | 130.0 |         |
|           |                                                                 | Z | 4.63 | 67.40 | 16.85 |      | 130.0 |         |
| 10576-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)  | X | 4.81 | 67.11 | 16.71 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.65 | 67.21 | 16.58 |      | 130.0 |         |
|           |                                                                 | Z | 4.66 | 67.60 | 16.93 |      | 130.0 |         |
| 10577-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle) | X | 5.03 | 67.42 | 16.88 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.82 | 67.44 | 16.72 |      | 130.0 |         |
|           |                                                                 | Z | 4.83 | 67.81 | 17.06 |      | 130.0 |         |
| 10578-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle) | X | 4.92 | 67.58 | 16.97 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.72 | 67.60 | 16.83 |      | 130.0 |         |
|           |                                                                 | Z | 4.74 | 67.98 | 17.18 |      | 130.0 |         |
| 10579-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle) | X | 4.71 | 67.00 | 16.38 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.49 | 66.86 | 16.13 |      | 130.0 |         |
|           |                                                                 | Z | 4.51 | 67.28 | 16.51 |      | 130.0 |         |
| 10580-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle) | X | 4.75 | 67.00 | 16.39 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.53 | 66.92 | 16.16 |      | 130.0 |         |
|           |                                                                 | Z | 4.55 | 67.35 | 16.54 |      | 130.0 |         |
| 10581-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle) | X | 4.83 | 67.65 | 16.92 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.64 | 67.69 | 16.81 |      | 130.0 |         |
|           |                                                                 | Z | 4.66 | 68.11 | 17.18 |      | 130.0 |         |
| 10582-AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle) | X | 4.66 | 66.79 | 16.19 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.42 | 66.63 | 15.91 |      | 130.0 |         |
|           |                                                                 | Z | 4.44 | 67.06 | 16.31 |      | 130.0 |         |
| 10583-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)       | X | 4.78 | 66.97 | 16.66 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.62 | 67.03 | 16.50 |      | 130.0 |         |
|           |                                                                 | Z | 4.63 | 67.40 | 16.85 |      | 130.0 |         |
| 10584-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)       | X | 4.81 | 67.11 | 16.71 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.65 | 67.21 | 16.58 |      | 130.0 |         |
|           |                                                                 | Z | 4.66 | 67.60 | 16.93 |      | 130.0 |         |
| 10585-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)      | X | 5.03 | 67.42 | 16.88 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.82 | 67.44 | 16.72 |      | 130.0 |         |
|           |                                                                 | Z | 4.83 | 67.81 | 17.06 |      | 130.0 |         |
| 10586-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)      | X | 4.92 | 67.58 | 16.97 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.72 | 67.60 | 16.83 |      | 130.0 |         |
|           |                                                                 | Z | 4.74 | 67.98 | 17.18 |      | 130.0 |         |
| 10587-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)      | X | 4.71 | 67.00 | 16.38 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.49 | 66.86 | 16.13 |      | 130.0 |         |
|           |                                                                 | Z | 4.51 | 67.28 | 16.51 |      | 130.0 |         |
| 10588-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)      | X | 4.75 | 67.00 | 16.39 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.53 | 66.92 | 16.16 |      | 130.0 |         |
|           |                                                                 | Z | 4.55 | 67.35 | 16.54 |      | 130.0 |         |
| 10589-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)      | X | 4.83 | 67.65 | 16.92 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.64 | 67.69 | 16.81 |      | 130.0 |         |
|           |                                                                 | Z | 4.66 | 68.11 | 17.18 |      | 130.0 |         |
| 10590-AAA | IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)      | X | 4.66 | 66.79 | 16.19 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                                 | Y | 4.42 | 66.63 | 15.91 |      | 130.0 |         |
|           |                                                                 | Z | 4.44 | 67.06 | 16.31 |      | 130.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                       |   |      |       |       |      |       |         |
|-----------|-------------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10591-AAA | IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle) | X | 4.93 | 67.00 | 16.74 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 4.77 | 67.09 | 16.61 |      | 130.0 |         |
|           |                                                       | Z | 4.78 | 67.43 | 16.94 |      | 130.0 |         |
| 10592-AAA | IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle) | X | 5.10 | 67.34 | 16.86 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 4.90 | 67.39 | 16.73 |      | 130.0 |         |
|           |                                                       | Z | 4.91 | 67.74 | 17.06 |      | 130.0 |         |
| 10593-AAA | IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle) | X | 5.03 | 67.29 | 16.77 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 4.82 | 67.28 | 16.60 |      | 130.0 |         |
|           |                                                       | Z | 4.83 | 67.64 | 16.94 |      | 130.0 |         |
| 10594-AAA | IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle) | X | 5.08 | 67.43 | 16.90 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 4.87 | 67.45 | 16.76 |      | 130.0 |         |
|           |                                                       | Z | 4.89 | 67.81 | 17.10 |      | 130.0 |         |
| 10595-AAA | IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle) | X | 5.05 | 67.41 | 16.81 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 4.84 | 67.43 | 16.67 |      | 130.0 |         |
|           |                                                       | Z | 4.86 | 67.81 | 17.02 |      | 130.0 |         |
| 10596-AAA | IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle) | X | 4.99 | 67.42 | 16.82 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 4.78 | 67.41 | 16.67 |      | 130.0 |         |
|           |                                                       | Z | 4.79 | 67.80 | 17.03 |      | 130.0 |         |
| 10597-AAA | IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle) | X | 4.94 | 67.35 | 16.73 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 4.73 | 67.29 | 16.53 |      | 130.0 |         |
|           |                                                       | Z | 4.74 | 67.68 | 16.89 |      | 130.0 |         |
| 10598-AAA | IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle) | X | 4.92 | 67.56 | 16.96 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 4.71 | 67.51 | 16.79 |      | 130.0 |         |
|           |                                                       | Z | 4.73 | 67.89 | 17.14 |      | 130.0 |         |
| 10599-AAA | IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle) | X | 5.60 | 67.58 | 16.94 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 5.44 | 67.55 | 16.84 |      | 130.0 |         |
|           |                                                       | Z | 5.45 | 67.84 | 17.12 |      | 130.0 |         |
| 10600-AAA | IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle) | X | 5.80 | 68.21 | 17.23 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 5.56 | 67.97 | 17.02 |      | 130.0 |         |
|           |                                                       | Z | 5.58 | 68.29 | 17.33 |      | 130.0 |         |
| 10601-AAA | IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle) | X | 5.85 | 67.84 | 17.06 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 5.45 | 67.71 | 16.91 |      | 130.0 |         |
|           |                                                       | Z | 5.47 | 68.02 | 17.21 |      | 130.0 |         |
| 10602-AAA | IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle) | X | 5.74 | 67.84 | 16.98 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 5.59 | 67.90 | 16.92 |      | 130.0 |         |
|           |                                                       | Z | 5.60 | 68.22 | 17.23 |      | 130.0 |         |
| 10603-AAA | IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle) | X | 5.82 | 68.10 | 17.23 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 5.67 | 68.21 | 17.21 |      | 130.0 |         |
|           |                                                       | Z | 5.68 | 68.52 | 17.51 |      | 130.0 |         |
| 10604-AAA | IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle) | X | 5.60 | 67.54 | 16.94 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 5.54 | 67.84 | 17.01 |      | 130.0 |         |
|           |                                                       | Z | 5.55 | 68.13 | 17.30 |      | 130.0 |         |
| 10605-AAA | IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle) | X | 5.73 | 67.92 | 17.14 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 5.56 | 67.86 | 17.02 |      | 130.0 |         |
|           |                                                       | Z | 5.57 | 68.17 | 17.32 |      | 130.0 |         |
| 10606-AAA | IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle) | X | 5.49 | 67.32 | 16.71 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                       | Y | 5.31 | 67.21 | 16.55 |      | 130.0 |         |
|           |                                                       | Z | 5.33 | 67.53 | 16.86 |      | 130.0 |         |

Certificate No: ES3-3327\_Sep17

Page 35 of 38

ES3DV3- SN:3327

September 18, 2017

|           |                                                   |   |      |       |       |      |       |         |
|-----------|---------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10607-AAA | IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle) | X | 4.76 | 66.29 | 16.34 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.61 | 66.41 | 16.24 |      | 130.0 |         |
|           |                                                   | Z | 4.63 | 66.82 | 16.60 |      | 130.0 |         |
| 10608-AAA | IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle) | X | 4.97 | 66.72 | 16.51 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.76 | 66.75 | 16.39 |      | 130.0 |         |
|           |                                                   | Z | 4.79 | 67.17 | 16.75 |      | 130.0 |         |
| 10609-AAA | IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle) | X | 4.86 | 66.60 | 16.37 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.65 | 66.60 | 16.22 |      | 130.0 |         |
|           |                                                   | Z | 4.69 | 67.03 | 16.60 |      | 130.0 |         |
| 10610-AAA | IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle) | X | 4.91 | 66.74 | 16.52 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.70 | 66.76 | 16.38 |      | 130.0 |         |
|           |                                                   | Z | 4.73 | 67.18 | 16.75 |      | 130.0 |         |
| 10611-AAA | IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle) | X | 4.83 | 66.58 | 16.39 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.62 | 66.57 | 16.23 |      | 130.0 |         |
|           |                                                   | Z | 4.65 | 67.00 | 16.61 |      | 130.0 |         |
| 10612-AAA | IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle) | X | 4.85 | 66.75 | 16.44 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.62 | 66.71 | 16.28 |      | 130.0 |         |
|           |                                                   | Z | 4.65 | 67.17 | 16.67 |      | 130.0 |         |
| 10613-AAA | IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle) | X | 4.86 | 66.67 | 16.34 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.61 | 66.55 | 16.13 |      | 130.0 |         |
|           |                                                   | Z | 4.65 | 66.99 | 16.52 |      | 130.0 |         |
| 10614-AAA | IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle) | X | 4.79 | 66.81 | 16.54 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.58 | 66.76 | 16.37 |      | 130.0 |         |
|           |                                                   | Z | 4.61 | 67.20 | 16.76 |      | 130.0 |         |
| 10615-AAA | IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle) | X | 4.84 | 66.43 | 16.19 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 4.62 | 66.41 | 16.01 |      | 130.0 |         |
|           |                                                   | Z | 4.65 | 66.86 | 16.40 |      | 130.0 |         |
| 10616-AAA | IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle) | X | 5.42 | 66.82 | 16.53 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 5.24 | 66.73 | 16.41 |      | 130.0 |         |
|           |                                                   | Z | 5.26 | 67.06 | 16.72 |      | 130.0 |         |
| 10617-AAA | IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle) | X | 5.48 | 66.95 | 16.57 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 5.31 | 66.93 | 16.49 |      | 130.0 |         |
|           |                                                   | Z | 5.33 | 67.26 | 16.80 |      | 130.0 |         |
| 10618-AAA | IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle) | X | 5.37 | 67.00 | 16.61 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 5.21 | 66.97 | 16.52 |      | 130.0 |         |
|           |                                                   | Z | 5.23 | 67.32 | 16.84 |      | 130.0 |         |
| 10619-AAA | IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle) | X | 5.40 | 66.85 | 16.48 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 5.22 | 66.76 | 16.35 |      | 130.0 |         |
|           |                                                   | Z | 5.24 | 67.11 | 16.67 |      | 130.0 |         |
| 10620-AAA | IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle) | X | 5.50 | 66.93 | 16.57 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 5.29 | 66.77 | 16.40 |      | 130.0 |         |
|           |                                                   | Z | 5.31 | 67.11 | 16.71 |      | 130.0 |         |
| 10621-AAA | IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle) | X | 5.47 | 66.95 | 16.68 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 5.30 | 66.89 | 16.58 |      | 130.0 |         |
|           |                                                   | Z | 5.31 | 67.19 | 16.87 |      | 130.0 |         |
| 10622-AAA | IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle) | X | 5.48 | 67.11 | 16.76 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                   | Y | 5.29 | 66.99 | 16.62 |      | 130.0 |         |
|           |                                                   | Z | 5.31 | 67.32 | 16.93 |      | 130.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                    |   |      |       |       |      |       |         |
|-----------|----------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10623-AAA | IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)  | X | 5.37 | 66.68 | 16.43 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.18 | 66.53 | 16.27 |      | 130.0 |         |
|           |                                                    | Z | 5.19 | 66.86 | 16.57 |      | 130.0 |         |
| 10624-AAA | IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)  | X | 5.56 | 66.88 | 16.59 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.37 | 66.78 | 16.45 |      | 130.0 |         |
|           |                                                    | Z | 5.39 | 67.09 | 16.75 |      | 130.0 |         |
| 10625-AAA | IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)  | X | 6.01 | 68.09 | 17.25 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.53 | 67.13 | 16.69 |      | 130.0 |         |
|           |                                                    | Z | 5.53 | 67.40 | 16.96 |      | 130.0 |         |
| 10626-AAA | IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)  | X | 5.68 | 66.84 | 16.46 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.56 | 66.77 | 16.37 |      | 130.0 |         |
|           |                                                    | Z | 5.58 | 67.06 | 16.64 |      | 130.0 |         |
| 10627-AAA | IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)  | X | 5.95 | 67.47 | 16.74 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.81 | 67.41 | 16.66 |      | 130.0 |         |
|           |                                                    | Z | 5.83 | 67.72 | 16.95 |      | 130.0 |         |
| 10628-AAA | IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)  | X | 5.75 | 67.03 | 16.46 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.57 | 66.78 | 16.27 |      | 130.0 |         |
|           |                                                    | Z | 5.59 | 67.08 | 16.56 |      | 130.0 |         |
| 10629-AAA | IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)  | X | 5.83 | 67.08 | 16.48 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.66 | 66.92 | 16.34 |      | 130.0 |         |
|           |                                                    | Z | 5.68 | 67.24 | 16.63 |      | 130.0 |         |
| 10630-AAA | IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)  | X | 6.46 | 69.14 | 17.51 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.98 | 68.08 | 16.93 |      | 130.0 |         |
|           |                                                    | Z | 6.01 | 68.42 | 17.23 |      | 130.0 |         |
| 10631-AAA | IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)  | X | 6.24 | 68.58 | 17.40 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.90 | 67.96 | 17.05 |      | 130.0 |         |
|           |                                                    | Z | 5.92 | 68.25 | 17.32 |      | 130.0 |         |
| 10632-AAA | IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)  | X | 5.91 | 67.45 | 16.85 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.79 | 67.52 | 16.85 |      | 130.0 |         |
|           |                                                    | Z | 5.81 | 67.82 | 17.13 |      | 130.0 |         |
| 10633-AAA | IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)  | X | 5.82 | 67.19 | 16.56 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.63 | 66.97 | 16.40 |      | 130.0 |         |
|           |                                                    | Z | 5.64 | 67.25 | 16.68 |      | 130.0 |         |
| 10634-AAA | IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)  | X | 5.79 | 67.17 | 16.61 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.61 | 67.01 | 16.47 |      | 130.0 |         |
|           |                                                    | Z | 5.63 | 67.30 | 16.75 |      | 130.0 |         |
| 10635-AAA | IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)  | X | 5.70 | 66.61 | 16.09 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.48 | 66.31 | 15.86 |      | 130.0 |         |
|           |                                                    | Z | 5.50 | 66.62 | 16.16 |      | 130.0 |         |
| 10636-AAB | IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle) | X | 6.10 | 67.24 | 16.56 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 5.99 | 67.13 | 16.46 |      | 130.0 |         |
|           |                                                    | Z | 6.01 | 67.39 | 16.71 |      | 130.0 |         |
| 10637-AAB | IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle) | X | 6.27 | 67.65 | 16.75 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 6.13 | 67.48 | 16.62 |      | 130.0 |         |
|           |                                                    | Z | 6.15 | 67.76 | 16.88 |      | 130.0 |         |
| 10638-AAB | IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle) | X | 6.27 | 67.63 | 16.72 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                    | Y | 6.14 | 67.48 | 16.60 |      | 130.0 |         |
|           |                                                    | Z | 6.16 | 67.77 | 16.86 |      | 130.0 |         |

ES3DV3- SN:3327

September 18, 2017

|           |                                                        |   |        |        |       |      |       |         |
|-----------|--------------------------------------------------------|---|--------|--------|-------|------|-------|---------|
| 10639-AAB | IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)     | X | 6.26   | 67.59  | 16.75 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                        | Y | 6.10   | 67.38  | 16.59 |      | 130.0 |         |
|           |                                                        | Z | 6.12   | 67.65  | 16.85 |      | 130.0 |         |
| 10640-AAB | IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)     | X | 6.29   | 67.69  | 16.74 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                        | Y | 6.08   | 67.35  | 16.52 |      | 130.0 |         |
|           |                                                        | Z | 6.10   | 67.63  | 16.78 |      | 130.0 |         |
| 10641-AAB | IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)     | X | 6.29   | 67.45  | 16.64 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                        | Y | 6.17   | 67.38  | 16.56 |      | 130.0 |         |
|           |                                                        | Z | 6.19   | 67.66  | 16.82 |      | 130.0 |         |
| 10642-AAB | IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)     | X | 6.34   | 67.72  | 16.93 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                        | Y | 6.18   | 67.55  | 16.80 |      | 130.0 |         |
|           |                                                        | Z | 6.20   | 67.81  | 17.05 |      | 130.0 |         |
| 10643-AAB | IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)     | X | 6.18   | 67.45  | 16.71 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                        | Y | 6.04   | 67.28  | 16.56 |      | 130.0 |         |
|           |                                                        | Z | 6.06   | 67.56  | 16.83 |      | 130.0 |         |
| 10644-AAB | IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)     | X | 6.41   | 68.15  | 17.08 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                        | Y | 6.11   | 67.52  | 16.70 |      | 130.0 |         |
|           |                                                        | Z | 6.13   | 67.79  | 16.97 |      | 130.0 |         |
| 10645-AAB | IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)     | X | 6.89   | 69.09  | 17.50 | 0.46 | 130.0 | ± 9.6 % |
|           |                                                        | Y | 6.27   | 67.66  | 16.74 |      | 130.0 |         |
|           |                                                        | Z | 6.29   | 67.94  | 17.01 |      | 130.0 |         |
| 10646-AAB | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)  | X | 64.19  | 131.45 | 42.80 | 9.30 | 60.0  | ± 9.6 % |
|           |                                                        | Y | 39.44  | 122.26 | 40.64 |      | 60.0  |         |
|           |                                                        | Z | 100.00 | 149.64 | 48.88 |      | 60.0  |         |
| 10647-AAC | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7) | X | 68.56  | 133.96 | 43.63 | 9.30 | 60.0  | ± 9.6 % |
|           |                                                        | Y | 38.11  | 122.47 | 40.87 |      | 60.0  |         |
|           |                                                        | Z | 100.00 | 151.09 | 49.52 |      | 60.0  |         |
| 10648-AAA | CDMA2000 (1x Advanced)                                 | X | 0.78   | 64.98  | 11.92 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                        | Y | 0.62   | 63.02  | 9.83  |      | 150.0 |         |
|           |                                                        | Z | 0.79   | 66.75  | 12.01 |      | 150.0 |         |
| 10652-AAB | LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)         | X | 4.43   | 69.08  | 17.63 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                        | Y | 4.33   | 69.22  | 17.26 |      | 80.0  |         |
|           |                                                        | Z | 4.47   | 70.61  | 18.13 |      | 80.0  |         |
| 10653-AAB | LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)        | X | 4.88   | 68.18  | 17.64 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                        | Y | 4.77   | 68.18  | 17.37 |      | 80.0  |         |
|           |                                                        | Z | 4.79   | 68.93  | 17.94 |      | 80.0  |         |
| 10654-AAB | LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)        | X | 4.81   | 67.82  | 17.62 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                        | Y | 4.74   | 67.78  | 17.39 |      | 80.0  |         |
|           |                                                        | Z | 4.74   | 68.41  | 17.91 |      | 80.0  |         |
| 10655-AAB | LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)        | X | 4.87   | 67.84  | 17.67 | 2.23 | 80.0  | ± 9.6 % |
|           |                                                        | Y | 4.81   | 67.69  | 17.41 |      | 80.0  |         |
|           |                                                        | Z | 4.79   | 68.28  | 17.91 |      | 80.0  |         |

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## **Attachment 2. – Dipole Calibration Data**

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **DT&C (Dymstec)**

Certificate No: D835V2-464\_Sep17

## CALIBRATION CERTIFICATE

Object **D835V2 - SN:464**

Calibration procedure(s) **QA CAL-05.v9**  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **September 21, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter NRP             | SN: 104778         | 04-Apr-17 (No. 217-02521/02522)   | Apr-18                 |
| Power sensor NRP-Z91        | SN: 103244         | 04-Apr-17 (No. 217-02521)         | Apr-18                 |
| Power sensor NRP-Z91        | SN: 103245         | 04-Apr-17 (No. 217-02522)         | Apr-18                 |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 07-Apr-17 (No. 217-02528)         | Apr-18                 |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 07-Apr-17 (No. 217-02529)         | Apr-18                 |
| Reference Probe EX3DV4      | SN: 7349           | 31-May-17 (No. EX3-7349_May17)    | May-18                 |
| DAE4                        | SN: 601            | 28-Mar-17 (No. DAE4-601_Mar17)    | Mar-18                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power meter EPM-442A        | SN: GB37480704     | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| Power sensor HP 8481A       | SN: US37292783     | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| Power sensor HP 8481A       | SN: MY41092317     | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| RF generator R&S SMT-06     | SN: 100972         | 15-Jun-15 (in house check Oct-16) | In house check: Oct-18 |
| Network Analyzer HP 8753E   | SN: US37390585     | 18-Oct-01 (in house check Oct-16) | In house check: Oct-17 |

Calibrated by: **Name** **Michael Weber** **Function** **Laboratory Technician**

Signature



Approved by: **Katja Pokovic** **Technical Manager**



Issued: September 21, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of**  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

#### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Additional Documentation:

- DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.10.0    |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 15 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 835 MHz $\pm$ 1 MHz    |             |

### Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 41.5           | 0.90 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 40.9 $\pm$ 6 % | 0.93 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Head TSL

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 2.41 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 9.38 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 1.54 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 6.03 W/kg $\pm$ 16.5 % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 55.2           | 0.97 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 55.3 $\pm$ 6 % | 0.98 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Body TSL

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 2.38 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 9.45 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 1.55 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 6.16 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.6 $\Omega$ - 1.4 j $\Omega$ |
| Return Loss                          | - 36.5 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 47.4 $\Omega$ - 3.9 j $\Omega$ |
| Return Loss                          | - 26.3 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.380 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                |
|-----------------|----------------|
| Manufactured by | SPEAG          |
| Manufactured on | March 27, 2002 |

## DASY5 Validation Report for Head TSL

Date: 21.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:464**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.93$  S/m;  $\epsilon_r = 40.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.07, 10.07, 10.07); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 4.9 (front); Type: QD 00L P49 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 62.00 V/m; Power Drift = -0.01 dB


Peak SAR (extrapolated) = 3.75 W/kg

**SAR(1 g) = 2.41 W/kg; SAR(10 g) = 1.54 W/kg**

Maximum value of SAR (measured) = 3.29 W/kg



### Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 21.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:464**

Communication System: UID 0 - CW; Frequency: 835 MHz

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.98 \text{ S/m}$ ;  $\epsilon_r = 55.3$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(10.2, 10.2, 10.2); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 4.9 (Back); Type: QD 00R P49 AA; Serial: 1005
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=15mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ 

Reference Value = 59.50 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 3.58 W/kg

**SAR(1 g) = 2.38 W/kg; SAR(10 g) = 1.55 W/kg**

Maximum value of SAR (measured) = 3.14 W/kg



## Impedance Measurement Plot for Body TSL



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **DT&C (Dymstec)**

Certificate No: **D1900V2-5d029\_Sep17**

## CALIBRATION CERTIFICATE

Object **D1900V2 - SN:5d029**

Calibration procedure(s) **QA CAL-05.v9**  
**Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **September 20, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 04-Apr-17 (No. 217-02521/02522) | Apr-18                |
| Power sensor NRP-Z91        | SN: 103244         | 04-Apr-17 (No. 217-02521)       | Apr-18                |
| Power sensor NRP-Z91        | SN: 103245         | 04-Apr-17 (No. 217-02522)       | Apr-18                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 07-Apr-17 (No. 217-02528)       | Apr-18                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 07-Apr-17 (No. 217-02529)       | Apr-18                |
| Reference Probe EX3DV4      | SN: 7349           | 31-May-17 (No. EX3-7349_May17)  | May-18                |
| DAE4                        | SN: 601            | 28-Mar-17 (No. DAE4-601_Mar17)  | Mar-18                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Oct-16) | In house check: Oct-18 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-16) | In house check: Oct-17 |

Calibrated by: **Name** **Function**  
**Jeton Kastrati** **Laboratory Technician**

Approved by: **Name** **Technical Manager**  
**Katja Pokovic**

Signature

Issued: September 21, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

### Glossary:

TSL tissue simulating liquid  
 ConvF sensitivity in TSL / NORM x,y,z  
 N/A not applicable or not measured

### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

### Additional Documentation:

- DASY4/5 System Handbook

### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.10.0    |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 1900 MHz $\pm$ 1 MHz   |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 40.0           | 1.40 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 39.0 $\pm$ 6 % | 1.38 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Head TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 9.78 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 39.2 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.13 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 20.6 W/kg $\pm$ 16.5 % (k=2) |

## Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 53.3           | 1.52 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 54.3 $\pm$ 6 % | 1.47 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

## SAR result with Body TSL

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
| SAR measured                                          | 250 mW input power | 9.66 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 39.6 W/kg $\pm$ 17.0 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 5.15 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 20.9 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.7 $\Omega$ + 3.4 j $\Omega$ |
| Return Loss                          | - 27.3 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 48.9 $\Omega$ + 5.8 j $\Omega$ |
| Return Loss                          | - 24.5 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.201 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | December 17, 2002 |

## DASY5 Validation Report for Head TSL

Date: 20.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d029**

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.38 \text{ S/m}$ ;  $\epsilon_r = 39$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.43, 8.43, 8.43); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ 

Reference Value = 106.6 V/m; Power Drift = -0.03 dB


Peak SAR (extrapolated) = 18.3 W/kg

**SAR(1 g) = 9.78 W/kg; SAR(10 g) = 5.13 W/kg**

Maximum value of SAR (measured) = 14.8 W/kg



### Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 20.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d029**

Communication System: UID 0 - CW; Frequency: 1900 MHz

Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.47 \text{ S/m}$ ;  $\epsilon_r = 54.3$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.2, 8.2, 8.2); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$ 

Reference Value = 101.8 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 17.0 W/kg


**SAR(1 g) = 9.66 W/kg; SAR(10 g) = 5.15 W/kg**

Maximum value of SAR (measured) = 14.1 W/kg



0 dB = 14.1 W/kg = 11.49 dBW/kg

### Impedance Measurement Plot for Body TSL



**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **DT&C (Dymstec)**

Certificate No: D2450V2-726\_Sep17

## CALIBRATION CERTIFICATE

Object **D2450V2 - SN:726**

Calibration procedure(s) **QA CAL-05.v9**  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **September 19, 2017**


This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 04-Apr-17 (No. 217-02521/02522) | Apr-18                |
| Power sensor NRP-Z91        | SN: 103244         | 04-Apr-17 (No. 217-02521)       | Apr-18                |
| Power sensor NRP-Z91        | SN: 103245         | 04-Apr-17 (No. 217-02522)       | Apr-18                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 07-Apr-17 (No. 217-02528)       | Apr-18                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 07-Apr-17 (No. 217-02529)       | Apr-18                |
| Reference Probe EX3DV4      | SN: 7349           | 31-May-17 (No. EX3-7349_May17)  | May-18                |
| DAE4                        | SN: 601            | 28-Mar-17 (No. DAE4-601_Mar17)  | Mar-18                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Oct-16) | In house check: Oct-18 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-16) | In house check: Oct-17 |

|                |                |                       |                                                                                       |
|----------------|----------------|-----------------------|---------------------------------------------------------------------------------------|
|                | Name           | Function              | Signature                                                                             |
| Calibrated by: | Jeton Kastrati | Laboratory Technician |   |
| Approved by:   | Katja Pokovic  | Technical Manager     |  |

Issued: September 19, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

#### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Additional Documentation:

- DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.10.0    |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2450 MHz $\pm$ 1 MHz   |             |

### Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.2           | 1.80 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 37.8 $\pm$ 6 % | 1.86 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Head TSL

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 13.3 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 51.9 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 6.22 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 24.5 W/kg $\pm$ 16.5 % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.7           | 1.95 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 51.9 $\pm$ 6 % | 2.04 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Body TSL

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 250 mW input power | 12.9 W/kg                    |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 50.3 W/kg $\pm$ 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 250 mW input power | 6.05 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 23.9 W/kg $\pm$ 16.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $52.6 \Omega + 4.0 j\Omega$ |
| Return Loss                          | - 26.6 dB                   |

### Antenna Parameters with Body TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $49.4 \Omega + 6.5 j\Omega$ |
| Return Loss                          | - 23.7 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.160 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                  |
|-----------------|------------------|
| Manufactured by | SPEAG            |
| Manufactured on | January 09, 2003 |

## DASY5 Validation Report for Head TSL

Date: 19.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:726**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.86$  S/m;  $\epsilon_r = 37.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.12, 8.12, 8.12); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 110.8 V/m; Power Drift = -0.06 dB


Peak SAR (extrapolated) = 26.9 W/kg

**SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.22 W/kg**

Maximum value of SAR (measured) = 21.0 W/kg



### Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 19.09.2017

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:726**

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.04$  S/m;  $\epsilon_r = 51.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.1, 8.1, 8.1); Calibrated: 31.05.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 28.03.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.9 V/m; Power Drift = -0.08 dB


Peak SAR (extrapolated) = 25.4 W/kg

**SAR(1 g) = 12.9 W/kg; SAR(10 g) = 6.05 W/kg**

Maximum value of SAR (measured) = 20.3 W/kg



## Impedance Measurement Plot for Body TSL



**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **DT&C (Dymstec)**

Certificate No: **D5GHzV2-1103\_Mar17**

## CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1103**

Calibration procedure(s) **QA CAL-22.v2**  
**Calibration procedure for dipole validation kits between 3-6 GHz**

Calibration date: **March 17, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)      | Scheduled Calibration |
|-----------------------------|--------------------|---------------------------------|-----------------------|
| Power meter NRP             | SN: 104778         | 06-Apr-16 (No. 217-02288/02289) | Apr-17                |
| Power sensor NRP-Z91        | SN: 103244         | 06-Apr-16 (No. 217-02288)       | Apr-17                |
| Power sensor NRP-Z91        | SN: 103245         | 06-Apr-16 (No. 217-02289)       | Apr-17                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 05-Apr-16 (No. 217-02292)       | Apr-17                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 05-Apr-16 (No. 217-02295)       | Apr-17                |
| Reference Probe EX3DV4      | SN: 3503           | 31-Dec-16 (No. EX3-3503_Dec16)  | Dec-17                |
| DAE4                        | SN: 601            | 04-Jan-17 (No. DAE4-601_Jan17)  | Jan-18                |

| Secondary Standards       | ID #           | Check Date (in house)             | Scheduled Check        |
|---------------------------|----------------|-----------------------------------|------------------------|
| Power meter EPM-442A      | SN: GB37480704 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| Power sensor HP 8481A     | SN: US37292783 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| Power sensor HP 8481A     | SN: MY41092317 | 07-Oct-15 (in house check Oct-16) | In house check: Oct-18 |
| RF generator R&S SMT-06   | SN: 100972     | 15-Jun-15 (in house check Oct-16) | In house check: Oct-18 |
| Network Analyzer HP 8753E | SN: US37390585 | 18-Oct-01 (in house check Oct-16) | In house check: Oct-17 |

|                |                               |                                          |                                                                                                    |
|----------------|-------------------------------|------------------------------------------|----------------------------------------------------------------------------------------------------|
| Calibrated by: | Name<br><b>Jeton Kastrati</b> | Function<br><b>Laboratory Technician</b> | Signature<br>  |
| Approved by:   | Name<br><b>Katja Pokovic</b>  | Function<br><b>Technical Manager</b>     | Signature<br> |

Issued: March 17, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: **D5GHzV2-1103\_Mar17**

Page 1 of 16

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                                                                                                                      |                                  |
|------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------|
| DASY Version                 | DASY5                                                                                                                | V52.8.8                          |
| Extrapolation                | Advanced Extrapolation                                                                                               |                                  |
| Phantom                      | Modular Flat Phantom V5.0                                                                                            |                                  |
| Distance Dipole Center - TSL | 10 mm                                                                                                                | with Spacer                      |
| Zoom Scan Resolution         | dx, dy = 4.0 mm, dz = 1.4 mm                                                                                         | Graded Ratio = 1.4 (Z direction) |
| Frequency                    | 5200 MHz $\pm$ 1 MHz<br>5300 MHz $\pm$ 1 MHz<br>5500 MHz $\pm$ 1 MHz<br>5600 MHz $\pm$ 1 MHz<br>5800 MHz $\pm$ 1 MHz |                                  |

### Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 36.0           | 4.66 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 35.0 $\pm$ 6 % | 4.52 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Head TSL at 5200 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                          | 100 mW input power | 8.00 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 79.5 W/kg $\pm$ 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR measured                                            | 100 mW input power | 2.29 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 22.7 W/kg $\pm$ 19.5 % (k=2) |

### Head TSL parameters at 5300 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.9         | 4.76 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.8 ± 6 %   | 4.62 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5300 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                            |
|-------------------------------------------------------|--------------------|----------------------------|
| SAR measured                                          | 100 mW input power | 8.47 W/kg                  |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 84.1 W / kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.42 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 24.0 W/kg ± 19.5 % (k=2) |

### Head TSL parameters at 5500 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.6         | 4.96 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.5 ± 6 %   | 4.81 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5500 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.38 W/kg                |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 83.2 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.38 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.6 W/kg ± 19.5 % (k=2) |

### Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.5         | 5.07 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.4 ± 6 %   | 4.92 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5600 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.52 W/kg                |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 84.5 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.43 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 24.1 W/kg ± 19.5 % (k=2) |

### Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.3         | 5.27 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.1 ± 6 %   | 5.13 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Head TSL at 5800 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.18 W/kg                |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 81.1 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.33 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.1 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5200 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 49.0         | 5.30 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 48.2 ± 6 %   | 5.45 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5200 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 7.43 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 74.1 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.09 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 20.8 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5300 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.9         | 5.42 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 48.0 ± 6 %   | 5.58 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5300 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 7.69 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 76.7 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.17 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.6 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5500 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.6         | 5.65 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.7 ± 6 %   | 5.85 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5500 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.12 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 81.0 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.25 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 22.4 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.5         | 5.77 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.5 ± 6 %   | 5.99 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5600 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.03 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 80.1 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.25 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 22.4 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5800 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.2         | 6.00 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.2 ± 6 %   | 6.28 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5800 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 7.77 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 77.5 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.16 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.5 W/kg ± 19.5 % (k=2) |

## Appendix (Additional assessments outside the scope of SCS 0108)

### Antenna Parameters with Head TSL at 5200 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.4 $\Omega$ - 5.8 j $\Omega$ |
| Return Loss                          | - 24.3 dB                      |

### Antenna Parameters with Head TSL at 5300 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 48.8 $\Omega$ - 0.2 j $\Omega$ |
| Return Loss                          | - 38.0 dB                      |

### Antenna Parameters with Head TSL at 5500 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.2 $\Omega$ - 2.8 j $\Omega$ |
| Return Loss                          | - 30.9 dB                      |

### Antenna Parameters with Head TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 55.1 $\Omega$ + 0.9 j $\Omega$ |
| Return Loss                          | - 26.2 dB                      |

### Antenna Parameters with Head TSL at 5800 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 52.2 $\Omega$ + 0.9 j $\Omega$ |
| Return Loss                          | - 32.5 dB                      |

### Antenna Parameters with Body TSL at 5200 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.7 $\Omega$ - 4.9 j $\Omega$ |
| Return Loss                          | - 25.9 dB                      |

### Antenna Parameters with Body TSL at 5300 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.8 $\Omega$ + 0.6 j $\Omega$ |
| Return Loss                          | - 43.6 dB                      |

### Antenna Parameters with Body TSL at 5500 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.8 $\Omega$ - 1.6 j $\Omega$ |
| Return Loss                          | - 35.6 dB                      |

### Antenna Parameters with Body TSL at 5600 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $57.5 \Omega + 1.5 j\Omega$ |
| Return Loss                          | - 22.9 dB                   |

### Antenna Parameters with Body TSL at 5800 MHz

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $52.5 \Omega + 1.5 j\Omega$ |
| Return Loss                          | - 30.9 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.209 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                    |
|-----------------|--------------------|
| Manufactured by | SPEAG              |
| Manufactured on | September 24, 2010 |

## DASY5 Validation Report for Head TSL

Date: 17.03.2017

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1103**

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used:  $f = 5200 \text{ MHz}$ ;  $\sigma = 4.52 \text{ S/m}$ ;  $\epsilon_r = 35$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used:  $f = 5300 \text{ MHz}$ ;  $\sigma = 4.62 \text{ S/m}$ ;  $\epsilon_r = 34.8$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used:  $f = 5500 \text{ MHz}$ ;  $\sigma = 4.81 \text{ S/m}$ ;  $\epsilon_r = 34.5$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used:  $f = 5600 \text{ MHz}$ ;  $\sigma = 4.92 \text{ S/m}$ ;  $\epsilon_r = 34.4$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used:  $f = 5800 \text{ MHz}$ ;  $\sigma = 5.13 \text{ S/m}$ ;  $\epsilon_r = 34.1$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.76, 5.76, 5.76); Calibrated: 31.12.2016, ConvF(5.35, 5.35, 5.35); Calibrated: 31.12.2016, ConvF(5.2, 5.2, 5.2); Calibrated: 31.12.2016, ConvF(5.09, 5.09, 5.09); Calibrated: 31.12.2016, ConvF(5.01, 5.01, 5.01); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.01.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.95 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 29.3 W/kg

**SAR(1 g) = 8 W/kg; SAR(10 g) = 2.29 W/kg**

Maximum value of SAR (measured) = 17.9 W/kg

### Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 72.36 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 30.5 W/kg

**SAR(1 g) = 8.47 W/kg; SAR(10 g) = 2.42 W/kg**

Maximum value of SAR (measured) = 19.0 W/kg

### Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 70.89 V/m; Power Drift = -0.07 dB


Peak SAR (extrapolated) = 32.7 W/kg

**SAR(1 g) = 8.38 W/kg; SAR(10 g) = 2.38 W/kg**


Maximum value of SAR (measured) = 19.4 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
 Reference Value = 71.46 V/m; Power Drift = -0.06 dB  
 Peak SAR (extrapolated) = 33.2 W/kg  
 SAR(1 g) = 8.52 W/kg; SAR(10 g) = 2.43 W/kg  
 Maximum value of SAR (measured) = 19.6 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
 Reference Value = 69.17 V/m; Power Drift = -0.08 dB  
 Peak SAR (extrapolated) = 33.1 W/kg  
 SAR(1 g) = 8.18 W/kg; SAR(10 g) = 2.33 W/kg  
 Maximum value of SAR (measured) = 19.2 W/kg



## Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 16.03.2017

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1103**

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used:  $f = 5200 \text{ MHz}$ ;  $\sigma = 5.45 \text{ S/m}$ ;  $\epsilon_r = 48.2$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used:  $f = 5300 \text{ MHz}$ ;  $\sigma = 5.58 \text{ S/m}$ ;  $\epsilon_r = 48$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used:  $f = 5500 \text{ MHz}$ ;  $\sigma = 5.85 \text{ S/m}$ ;  $\epsilon_r = 47.7$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used:  $f = 5600 \text{ MHz}$ ;  $\sigma = 5.99 \text{ S/m}$ ;  $\epsilon_r = 47.5$ ;  $\rho = 1000 \text{ kg/m}^3$ ,

Medium parameters used:  $f = 5800 \text{ MHz}$ ;  $\sigma = 6.28 \text{ S/m}$ ;  $\epsilon_r = 47.2$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.29, 5.29, 5.29); Calibrated: 31.12.2016, ConvF(5.04, 5.04, 5.04); Calibrated: 31.12.2016, ConvF(4.62, 4.62, 4.62); Calibrated: 31.12.2016, ConvF(4.57, 4.57, 4.57); Calibrated: 31.12.2016, ConvF(4.48, 4.48, 4.48); Calibrated: 31.12.2016;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 04.01.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.8.8(1258); SEMCAD X 14.6.10(7372)

### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.58 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 28.4 W/kg

**SAR(1 g) = 7.43 W/kg; SAR(10 g) = 2.09 W/kg**

Maximum value of SAR (measured) = 17.8 W/kg

### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.42 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 30.0 W/kg

**SAR(1 g) = 7.69 W/kg; SAR(10 g) = 2.17 W/kg**

Maximum value of SAR (measured) = 18.6 W/kg

### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.66 V/m; Power Drift = -0.04 dB


Peak SAR (extrapolated) = 33.6 W/kg

**SAR(1 g) = 8.12 W/kg; SAR(10 g) = 2.25 W/kg**


Maximum value of SAR (measured) = 20.0 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
 Reference Value = 65.60 V/m; Power Drift = -0.05 dB  
 Peak SAR (extrapolated) = 33.9 W/kg  
**SAR(1 g) = 8.03 W/kg; SAR(10 g) = 2.25 W/kg**  
 Maximum value of SAR (measured) = 19.6 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
 Reference Value = 63.69 V/m; Power Drift = -0.04 dB  
 Peak SAR (extrapolated) = 34.6 W/kg  
**SAR(1 g) = 7.77 W/kg; SAR(10 g) = 2.16 W/kg**  
 Maximum value of SAR (measured) = 19.8 W/kg



## Impedance Measurement Plot for Body TSL



## **Attachment 3. – SAR SYSTEM VALIDATION**

## SAR System Validation

Per FCC KDB 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

**Table Attachment 3.1 SAR System Validation Summary**

| SAR System | Freq. [MHz] | Date       | Probe SN | Probe Type | Probe CAL. Point |      | PERM.            | COND.        | CW Validation    |                    |                   | MOD. Validation |                |      |
|------------|-------------|------------|----------|------------|------------------|------|------------------|--------------|------------------|--------------------|-------------------|-----------------|----------------|------|
|            |             |            |          |            |                  |      | ( $\epsilon_r$ ) | ( $\sigma$ ) | Sensi-<br>tivity | Probe<br>Linearity | Probe<br>Isotropy | MOD. Type       | Duty<br>Factor | PAR  |
| C          | 835         | 2017.04.05 | 3328     | ES3DV3     | 835              | Head | 40.885           | 0.875        | PASS             | PASS               | PASS              | GMSK            | PASS           | N/A  |
| C          | 835         | 2017.10.03 | 3327     | ES3DV3     | 835              | Head | 40.645           | 0.869        | PASS             | PASS               | PASS              | GMSK            | PASS           | N/A  |
| C          | 1900        | 2017.04.07 | 3328     | ES3DV3     | 1900             | Head | 39.545           | 1.443        | PASS             | PASS               | PASS              | GMSK            | PASS           | N/A  |
| D          | 1900        | 2017.04.07 | 3328     | ES3DV3     | 1900             | Head | 39.551           | 1.442        | PASS             | PASS               | PASS              | GMSK            | PASS           | N/A  |
| D          | 2450        | 2017.08.08 | 3930     | EX3DV4     | 2450             | Head | 37.885           | 1.818        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| D          | 5200        | 2017.08.10 | 3930     | EX3DV4     | 5200             | Head | 35.051           | 4.719        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| D          | 5300        | 2017.08.11 | 3930     | EX3DV4     | 5300             | Head | 34.515           | 4.887        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| D          | 5600        | 2017.08.15 | 3930     | EX3DV4     | 5600             | Head | 34.228           | 5.236        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| D          | 5800        | 2017.08.16 | 3930     | EX3DV4     | 5800             | Head | 34.001           | 5.378        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| C          | 835         | 2017.04.05 | 3328     | ES3DV3     | 835              | Body | 54.228           | 0.985        | PASS             | PASS               | PASS              | GMSK            | PASS           | N/A  |
| C          | 835         | 2017.10.03 | 3327     | ES3DV3     | 835              | Body | 54.223           | 0.954        | PASS             | PASS               | PASS              | GMSK            | PASS           | N/A  |
| C          | 1900        | 2017.04.07 | 3328     | ES3DV3     | 1900             | Body | 51.775           | 1.575        | PASS             | PASS               | PASS              | GMSK            | PASS           | N/A  |
| D          | 1900        | 2017.04.07 | 3328     | ES3DV3     | 1900             | Body | 51.774           | 1.546        | PASS             | PASS               | PASS              | GMSK            | PASS           | N/A  |
| D          | 2450        | 2017.08.08 | 3930     | EX3DV4     | 2450             | Body | 51.116           | 2.015        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| D          | 5200        | 2017.08.10 | 3930     | EX3DV4     | 5200             | Body | 48.051           | 5.448        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| D          | 5300        | 2017.08.11 | 3930     | EX3DV4     | 5300             | Body | 47.797           | 5.567        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| D          | 5600        | 2017.08.15 | 3930     | EX3DV4     | 5600             | Body | 47.445           | 5.911        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |
| D          | 5800        | 2017.08.16 | 3930     | EX3DV4     | 5800             | Body | 47.016           | 6.214        | PASS             | PASS               | PASS              | OFDM            | N/A            | PASS |

NOTE: While the probes have been calibrated for both a CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to KDB 865664.