

**MEASUREMENT REPORT**  
**FCC PART 15.247 Bluetooth****Applicant Name:**LG Electronics MobileComm U.S.A  
1000 Sylvan Avenue  
Englewood Cliffs, NJ 07632  
United States**Date of Testing:**

8/09/2017-8/30/2017

**Test Site/Location:**

PCTEST Lab. Columbia, MD, USA

**Test Report Serial No.:**

1M1708030234-08.ZNF

**FCC ID:****ZNFG011C****APPLICANT:****LG Electronics MobileComm U.S.A****Application Type:**

Class II Permissive Change

**Model:**

G011C

**EUT Type:**

Portable Handset

**Frequency Range:**

2402 – 2480MHz (Bluetooth for US)

**Type of Modulation:**GFSK,  $\pi/4$ -DQPSK, 8DPSK**FCC Classification:**

FCC Part 15 Spread Spectrum Transmitter (DSS)

**FCC Rule Part(s):**

Part 15 Subpart C (15.247)

**Test Procedure(s):**

ANSI C63.10-2013

**Class II Permissive Change:**

Please see FCC change document

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
Randy Ortanez  
President

|                                                |                                                                                     |                                                                                    |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT</b><br><b>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017                                           | <b>EUT Type:</b><br>Portable Handset                                               |                                                                                       | Page 1 of 26                           |

## T A B L E O F C O N T E N T S


|                                                                 |    |
|-----------------------------------------------------------------|----|
| FCC PART 15.247 MEASUREMENT REPORT .....                        | 3  |
| 1.0 INTRODUCTION .....                                          | 4  |
| 1.1 Scope .....                                                 | 4  |
| 1.2 PCTEST Test Location .....                                  | 4  |
| 2.0 PRODUCT INFORMATION .....                                   | 5  |
| 2.1 Equipment Description .....                                 | 5  |
| 2.2 Device Capabilities .....                                   | 5  |
| 2.3 Test Configuration .....                                    | 5  |
| 2.4 EMI Suppression Device(s)/Modifications .....               | 5  |
| 3.0 DESCRIPTION OF TESTS .....                                  | 6  |
| 3.1 Evaluation Procedure .....                                  | 6  |
| 3.2 Radiated Emissions .....                                    | 6  |
| 3.3 Environmental Conditions .....                              | 6  |
| 4.0 ANTENNA REQUIREMENTS .....                                  | 7  |
| 5.0 MEASUREMENT UNCERTAINTY .....                               | 8  |
| 6.0 TEST EQUIPMENT CALIBRATION DATA .....                       | 9  |
| 7.0 TEST RESULTS .....                                          | 10 |
| 7.1 Summary .....                                               | 10 |
| 7.2 Radiated Spurious Emission Measurements – Above 1GHz .....  | 11 |
| 7.3 Radiated Restricted Band Edge Measurements .....            | 20 |
| 7.4 Radiated Spurious Emissions Measurements – Below 1GHz ..... | 22 |
| 8.0 CONCLUSION .....                                            | 26 |

|                                                |                                                                                     |                                                                              |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017                                           | <b>EUT Type:</b><br>Portable Handset                                         |                                                                                       | Page 2 of 26                           |



# MEASUREMENT REPORT

## FCC Part 15.247



### § 2.1033 General Information

**APPLICANT:** LG Electronics MobileComm U.S.A  
**APPLICANT ADDRESS:** 1000 Sylvan Avenue  
 Englewood Cliffs, NJ 07632, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 7185 Oakland Mills Road, Columbia, MD 21046 USA  
**FCC RULE PART(S):** Part 15 Subpart C (15.247)  
**BASE MODEL:** G011C  
**FCC ID:** ZNFG011C  
**FCC CLASSIFICATION:** FCC Part 15 Spread Spectrum Transmitter (DSS)  
**Test Device Serial No.:** 35400, 35392 ☐ Production ☒ Pre-Production ☐ Engineering  
**Method/System:** Frequency Hopping Spread Spectrum (FHSS)  
**DATE(S) OF TEST:** 8/09/2017-8/30/2017  
**TEST REPORT S/N:** 1M1708030234-08.ZNF

### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 3 of 26                    |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

|                                         |                                               |                                                                      |           |                                 |
|-----------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|-----------|---------------------------------|
| FCC ID: ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>LG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017            | EUT Type:<br>Portable Handset                                        |           | Page 4 of 26                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **LG Portable Handset FCC ID: ZNFG011C**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- This Bluetooth module has been tested by a Bluetooth Qualification Lab, and we confirm the following:
  - A) The hopping sequence is pseudorandom
  - B) All channels are used equally on average
  - C) The receiver input bandwidth equals the transmit bandwidth
  - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO Rev0/A, 1x Advanced (BC0, BC1, BC10), 850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ac WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

| Ch. | Frequency (MHz) |
|-----|-----------------|
| 00  | 2402            |
| :   | :               |
| 39  | 2441            |
| :   | :               |
| 78  | 2480            |

**Table 2-1. Frequency/ Channel Operations**

**Note:** This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

### 2.3 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was also used to reference the appropriate EUT setup for radiated spurious emissions testing. See Section 3.2 for radiated emissions test setups.

### 2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

|                                                |                                                                                     |                                                                              |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017                                           | <b>EUT Type:</b><br>Portable Handset                                         |                                                                                       | Page 5 of 26                           |

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

### 3.2 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. A 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm. For measurements above 1GHz, a high density expanded polystyrene block is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

### 3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 6 of 26                    |

## 4.0 ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

### Conclusion:

The EUT complies with the requirement of §15.203.

|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 7 of 26                    |

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution                  | Expanded Uncertainty ( $\pm$ dB) |
|-------------------------------|----------------------------------|
| Radiated Disturbance (<1GHz)  | 4.98                             |
| Radiated Disturbance (>1GHz)  | 5.07                             |
| Radiated Disturbance (>18GHz) | 5.09                             |

|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 8 of 26                    |

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2006.

| Manufacturer    | Model    | Description                          | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|-----------------|----------|--------------------------------------|------------|--------------|------------|---------------|
| Agilent         | N9020A   | MXA Signal Analyzer                  | 10/28/2016 | Annual       | 10/28/2017 | US46470561    |
| Agilent         | N4010A   | Wireless Connectivity Test Set       | N/A        |              |            | GB46170464    |
| Com-Power       | PAM-103  | Pre-Amplifier (1-1000MHz)            | 6/21/2017  | Annual       | 6/21/2018  | 441112        |
| Emco            | 3115     | Horn Antenna (1-18GHz)               | 3/10/2016  | Biennial     | 3/10/2018  | 9704-5182     |
| Emco            | 3116     | Horn Antenna (18 - 40GHz)            | 3/27/2015  | Triennial    | 3/27/2018  | 9203-2178     |
| EMCO            | 3160-09  | Small Horn (18 - 26.5GHz)            | 8/23/2016  | Biennial     | 8/23/2018  | 135427        |
| ETS-Lindgren    | 3816/2NM | Line Impedance Stabilization Network | 12/27/2016 | Biennial     | 12/27/2018 | 114451        |
| Pasternack      | NMLC-1   | Line Conducted Emissions Cable (NM)  | 5/31/2017  | Annual       | 5/31/2018  | NMLC-1        |
| PCTEST          | -        | EMC Switch System                    | 6/21/2017  | Annual       | 6/21/2018  | NM1           |
| Rohde & Schwarz | CMU200   | Base Station Simulator               | N/A        |              |            | 107826        |
| Rohde & Schwarz | TS-PR18  | 1-18 GHz Pre-Amplifier               | 3/7/2017   | Annual       | 3/7/2018   | 100071        |
| Rohde & Schwarz | TS-PR26  | 18-26.5 GHz Pre-Amplifier            | 5/11/2017  | Annual       | 5/11/2018  | 100040        |
| Rohde & Schwarz | ESU26    | EMI Test Receiver (26.5GHz)          | 4/19/2017  | Annual       | 4/19/2018  | 100342        |
| Sunol           | JB5      | Bi-Log Antenna (30M - 5GHz)          | 3/14/2016  | Biennial     | 3/14/2018  | A051107       |

**Table 6-1. Annual Test Equipment Calibration Schedule**

### Notes:

- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        | Page 9 of 26                                                                          |                                 |

## 7.0 TEST RESULTS

### 7.1 Summary

Company Name: LG Electronics MobileComm U.S.A  
 FCC ID: ZNFG011C  
 Method/System: Frequency Hopping Spread Spectrum (FHSS)  
 Number of Channels: 79

| FCC Part Section(s) | Test Description                                                                    | Test Limit                                                                           | Test Condition | Test Result | Reference                                   |
|---------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|----------------|-------------|---------------------------------------------|
| 15.205<br>15.209    | General Field Strength Limits<br>(Restricted Bands and<br>Radiated Emission Limits) | Emissions in restricted bands<br>must meet the radiated limits<br>detailed in 15.209 | RADIATED       | PASS        | Section 7.2,<br>Section 7.3,<br>Section 7.4 |

**Table 7-1. Summary of Test Results**

**Notes:**

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.

|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 10 of 26                   |

## 7.2 Radiated Spurious Emission Measurements – Above 1GHz

§15.205 §15.209 §15.247 (d)

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-2 per Section 15.209.***

| Frequency       | Field Strength<br>[μV/m] | Measured Distance<br>[Meters] |
|-----------------|--------------------------|-------------------------------|
| Above 960.0 MHz | 500                      | 3                             |

**Table 7-2. Radiated Limits**

### Test Procedure Used

ANSI C63.10-2013 – Section 6.6.4.3

### Test Settings

#### Average Field Strength Measurements per Section 4.1.4.2.3 of ANSI C63.10-2013

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 1kHz  $\geq 1/\tau$  Hz, where  $\tau$  = pulse width in seconds
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to stabilize

#### Peak Field Strength Measurements per Section 4.1.4.2.2 of ANSI C63.10-2013

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-3 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize


|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 11 of 26                   |

| Frequency    | RBW          |
|--------------|--------------|
| 9 – 150kHz   | 200 – 300Hz  |
| 0.15 – 30MHz | 9 – 10kHz    |
| 30 – 1000MHz | 100 – 120kHz |
| > 1000MHz    | 1MHz         |

**Table 7-3. RBW as a Function of Frequency**

### **Test Setup**

The EUT and measurement equipment were set up as shown in the diagram below.



**Figure 7-1. Radiated Test Setup >1GHz**

### **Test Notes**

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-2.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic and the worst-case emissions are reported.
6. The duty cycle correction factor was not applied to noise floor measurements.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

|                                         |                                               |                                                                      |    |                                 |
|-----------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|----|---------------------------------|
| FCC ID: ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) | LG | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017            | EUT Type:<br>Portable Handset                                        |    | Page 12 of 26                   |

### Sample Calculation

- o Field Strength Level  $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]} + \text{Duty Cycle Correction }_{[dB]}$
- o  $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- o  $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$


### Duty Cycle Correction Factor Calculation

- o Channel hop rate = 800 hops/second (AFH Mode)
- o Adjusted channel hop rate for DH5 mode = 133.33 hops/second
- o Time per channel hop =  $1 / 133.33 \text{ hops/second} = 7.50 \text{ ms}$
- o Time to cycle through all channels =  $7.50 \times 20 \text{ channels} = 150 \text{ ms}$
- o Number of times transmitter hits on one channel =  $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$
- o Worst case dwell time = 7.5 ms
- o Duty cycle correction factor =  $20\log_{10}(7.5\text{ms}/100\text{ms}) = -22.5 \text{ dB}$


|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 13 of 26                   |

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d)




**Plot 7-1. Radiated Spurious Plot above 1GHz (BT – Ch. 0, Ant. Pol. H)**




**Plot 7-2. Radiated Spurious Plot above 1GHz (BT – Ch. 0, Ant. Pol. V)**

|                                                |                                               |                                                                             |                                        |
|------------------------------------------------|-----------------------------------------------|-----------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT</b><br>(CLASS II PERMISSIVE CHANGE) | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017     | <b>EUT Type:</b><br>Portable Handset                                        | <b>Page 14 of 26</b>                   |




**Plot 7-3. Radiated Spurious Plot above 1GHz (BT – Ch. 39, Ant. Pol. H)**




**Plot 7-4. Radiated Spurious Plot above 1GHz (BT – Ch. 39, Ant. Pol. V)**

|                                                |                                               |                                                                             |                                        |
|------------------------------------------------|-----------------------------------------------|-----------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT</b><br>(CLASS II PERMISSIVE CHANGE) | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017     | <b>EUT Type:</b><br>Portable Handset                                        | <b>Page 15 of 26</b>                   |



**Plot 7-5. Radiated Spurious Plot above 1GHz (BT – Ch. 78, Ant. Pol. H)**




**Plot 7-6. Radiated Spurious Plot above 1GHz (BT – Ch. 78, Ant. Pol. V)**


|                                                |                                               |                                                                             |                                        |
|------------------------------------------------|-----------------------------------------------|-----------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT</b><br>(CLASS II PERMISSIVE CHANGE) | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017     | <b>EUT Type:</b><br>Portable Handset                                        | Page 16 of 26                          |

## Radiated Spurious Emissions Measurements (Above 18GHz)

**\$15.209**



**Plot 7-7. Radiated Spurious Plot above 18GHz (Pol. H)**



**Plot 7-8. Radiated Spurious Plot above 18GHz (Pol. V)**

|                                         |                                               |                                                                      |    |                                 |
|-----------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|----|---------------------------------|
| FCC ID: ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) | LG | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017            | EUT Type:<br>Portable Handset                                        |    | Page 17 of 26                   |

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d)

Worst Case Mode: Bluetooth  
Worst Case Data Rate: 1 Mbps  
Measurement Distance: 3 Meters  
Operating Frequency: 2402MHz  
Channel: 0

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Duty Cycle Correction [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|----------------------------|-------------------------|----------------|-------------|
| 4804.00         | Avg      | H               | -                   | -                          | -71.42               | 2.15        | 0.00                       | 37.73                   | 53.98          | -16.25      |
| 4804.00         | Peak     | H               | -                   | -                          | -58.17               | 2.15        | 0.00                       | 50.98                   | 73.98          | -23.00      |
| 12010.00        | Avg      | H               | -                   | -                          | -72.94               | 15.78       | 0.00                       | 49.84                   | 53.98          | -4.14       |
| 12010.00        | Peak     | H               | -                   | -                          | -59.21               | 15.78       | 0.00                       | 63.57                   | 73.98          | -10.41      |

**Table 7-4. Radiated Measurements**

Worst Case Mode: Bluetooth  
Worst Case Data Rate: 1 Mbps  
Measurement Distance: 3 Meters  
Operating Frequency: 2441MHz  
Channel: 39

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Duty Cycle Correction [dB] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|----------------------------|-------------------------|----------------|-------------|
| 4882.00         | Avg      | H               | -                   | -                          | -72.05               | 2.61        | 0.00                       | 37.56                   | 53.98          | -16.42      |
| 4882.00         | Peak     | H               | -                   | -                          | -58.29               | 2.61        | 0.00                       | 51.32                   | 73.98          | -22.66      |
| 7323.00         | Avg      | H               | -                   | -                          | -72.61               | 8.81        | 0.00                       | 43.20                   | 53.98          | -10.78      |
| 7323.00         | Peak     | H               | -                   | -                          | -59.84               | 8.81        | 0.00                       | 55.97                   | 73.98          | -18.01      |
| 12205.00        | Avg      | H               | -                   | -                          | -73.48               | 15.72       | 0.00                       | 49.24                   | 53.98          | -4.74       |
| 12205.00        | Peak     | H               | -                   | -                          | -60.78               | 15.72       | 0.00                       | 61.94                   | 73.98          | -12.04      |

**Table 7-5. Radiated Measurements**

|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 18 of 26                   |

## Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247 (d)

|                       |           |
|-----------------------|-----------|
| Worst Case Mode:      | Bluetooth |
| Worst Case Data Rate: | 1 Mbps    |
| Measurement Distance: | 3 Meters  |
| Operating Frequency:  | 2480MHz   |
| Channel:              | 78        |

| Frequency [MHz] | Detector | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Duty Cycle Correction [dB] | Field Strength [dBμV/m] | Limit [dBμV/m] | Margin [dB] |
|-----------------|----------|-----------------|---------------------|----------------------------|----------------------|-------------|----------------------------|-------------------------|----------------|-------------|
| 4960.00         | Avg      | H               | -                   | -                          | -71.56               | 2.20        | 0.00                       | 37.64                   | 53.98          | -16.34      |
| 4960.00         | Peak     | H               | -                   | -                          | -57.78               | 2.20        | 0.00                       | 51.42                   | 73.98          | -22.56      |
| 7440.00         | Avg      | H               | -                   | -                          | -71.83               | 9.07        | 0.00                       | 44.24                   | 53.98          | -9.74       |
| 7440.00         | Peak     | H               | -                   | -                          | -58.28               | 9.07        | 0.00                       | 57.79                   | 73.98          | -16.19      |
| 12400.00        | Avg      | H               | -                   | -                          | -72.59               | 16.16       | 0.00                       | 50.57                   | 53.98          | -3.40       |
| 12400.00        | Peak     | H               | -                   | -                          | -59.61               | 16.16       | 0.00                       | 63.55                   | 73.98          | -10.42      |

Table 7-6. Radiated Measurements

|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 19 of 26                   |


### 7.3 Radiated Restricted Band Edge Measurements §15.205 §15.209 §15.247 (d)

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting. Two different amplitude offsets were used depending on whether peak or average measurements were measured. The average measurements use a duty cycle correction factor (DCCF).

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain} + \text{DCCF}$$

|                       |           |
|-----------------------|-----------|
| Worst Case Mode:      | Bluetooth |
| Worst Case Data Rate: | 1 Mbps    |
| Measurement Distance: | 3 Meters  |
| Operating Frequency:  | 2480MHz   |
| Channel:              | 78        |



Date: 21.AUG.2017 16:49:12

**Plot 7-9. Radiated Restricted Upper Band Edge Measurement (Average)**


|                                         |                                               |                                                                      |           |                                 |
|-----------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|-----------|---------------------------------|
| FCC ID: ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) | <b>LG</b> | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017            | EUT Type:<br>Portable Handset                                        |           | Page 20 of 26                   |

## Radiated Restricted Band Edge Measurements

\$15.205 \$15.209 \$15.247 (d)

The amplitude offset shown in the following plots for peak measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$



Date: 21.AUG.2017 16:47:47

**Plot 7-10. Radiated Restricted Upper Band Edge Measurement (Peak)**

|                                         |                                               |                                                                      |    |                                 |
|-----------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|----|---------------------------------|
| FCC ID: ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) | LG | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017            | EUT Type:<br>Portable Handset                                        |    | Page 21 of 26                   |

## 7.4 Radiated Spurious Emissions Measurements – Below 1GHz

### §15.209

#### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

***All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-7 per Section 15.209.***

| Frequency         | Field Strength<br>[ $\mu\text{V/m}$ ] | Measured Distance<br>[Meters] |
|-------------------|---------------------------------------|-------------------------------|
| 0.009 – 0.490 MHz | 2400/F (kHz)                          | 300                           |
| 0.490 – 1.705 MHz | 24000/F (kHz)                         | 30                            |
| 1.705 – 30.00 MHz | 30                                    | 30                            |
| 30.00 – 88.00 MHz | 100                                   | 3                             |
| 88.00 – 216.0 MHz | 150                                   | 3                             |
| 216.0 – 960.0 MHz | 200                                   | 3                             |
| Above 960.0 MHz   | 500                                   | 3                             |

**Table 7-7. Radiated Limits**

#### Test Procedures Used

ANSI C63.10-2013

#### Test Settings


##### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


|                                         |                                                                                     |                                                                      |                                                                                       |                                 |
|-----------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ZNFG011C                        |  | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) |  | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017                                                  | EUT Type:<br>Portable Handset                                        |                                                                                       | Page 22 of 26                   |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



**Figure 7-2. Radiated Test Setup < 30Mhz**



**Figure 7-3. Radiated Test Setup < 1GHz**

|                                         |                                               |                                                                      |    |                                 |
|-----------------------------------------|-----------------------------------------------|----------------------------------------------------------------------|----|---------------------------------|
| FCC ID: ZNFG011C                        | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 15.247 BLUETOOTH TEST REPORT<br>(CLASS II PERMISSIVE CHANGE) | LG | Approved by:<br>Quality Manager |
| Test Report S/N:<br>1M1708030234-08.ZNF | Test Dates:<br>8/09/2017-8/30/2017            | EUT Type:<br>Portable Handset                                        |    | Page 23 of 26                   |


## Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-7.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.


|                                                |                                                                                     |                                                                              |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017                                           | <b>EUT Type:</b><br>Portable Handset                                         |                                                                                       | Page 24 of 26                          |

## Radiated Spurious Emissions Measurements (Below 1GHz)

**§15.209**



**Plot 7-11. Radiated Spurious Plot below 1GHz (Pol. H)**



**Plot 7-12. Radiated Spurious Plot below 1GHz (Pol. V)**

|                                                |                                                                                     |                                                                              |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017                                           | <b>EUT Type:</b><br>Portable Handset                                         |                                                                                       | Page 25 of 26                          |

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LG Portable Handset FCC ID: ZNFG011C** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

|                                                |                                                                                     |                                                                              |                                                                                       |                                        |
|------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> ZNFG011C                        |  | <b>FCC Pt. 15.247 BLUETOOTH TEST REPORT<br/>(CLASS II PERMISSIVE CHANGE)</b> |  | <b>Approved by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>1M1708030234-08.ZNF | <b>Test Dates:</b><br>8/09/2017-8/30/2017                                           | <b>EUT Type:</b><br>Portable Handset                                         |                                                                                       | Page 26 of 26                          |