

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No. : DREFCC1804-0113
2. Client / Applicant
 - Name : LG Electronics MobileComm USA, Inc.
 - Address : 1000 Sylvan Ave. Englewood Cliffs NJ 07632
3. Use of Report : Grant of Certification
4. Product Name / Model Name : Mobile phone / LM-G710V
5. Test Standard : CAN/CSA CISPR 22-10
ANSI C 63.4 : 2014
ICES-003 : 2016
FCC Part 15 Subpart B
(Class B personal computers and peripherals)
6. Date of Test : Mar. 30. 2018 ~ Apr. 02. 2018
7. Testing Environment : Temperature (20 ~ 21) °C , Humidity 45 % R.H.
8. Test Result : Refer to the attached Test Result

Affirmation	Tested by	Reviewed by
	Name : JinYoung Park (Signature)	Name : MyungJin Song (Signature)

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose.

This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

Apr. 10. 2018

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

CONTENTS

1. General Remarks	3
2. Test Laboratory.....	3
3. General Information of EUT.....	4
4. EUT Operations and Test Configurations	5
4.1 Principle of Configuration Selection	5
4.2 EUT Operation Mode	5
4.3 Test Configuration Mode.....	5
4.4 Supported Equipment	5
4.5 EUT In/Output Port	6
4.6 Test Voltage and Frequency	6
5. Test Summary	7
6. Test Environment.....	7
7. Test Results : Emission.....	8
7.1 Conducted Disturbance	8
7.2 Radiated Disturbance	12
8. Revision History.....	24

1. General Remarks

This report contains the result of tests performed by :

DT&C Co., Ltd.

42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042

<http://www.dtnet.net>

Tel: +82-31-321-2664 Fax: +82-31-321-1664

2. Test Laboratory

DT&C Co., Ltd. has been accredited / filed / authorized by the agencies listed in the following table;

Certificate	Nation	Agency	Code	Remark
Accreditation	Korea	KOLAS	393	ISO/IEC 17025
	South Africa	SABS	0006	ISO/IEC 17025
Site Filing	USA	FCC	KR0034 101842 678747, 596748, 804488, 165783	Accredited 2.948 Listed
	Canada	IC	5740A-3 5740A-4	Registered
	Japan	VCCI	C-1427 R-1364, R-3385, R-4076, R-4180, T-1442, G-10338, G-754, G-10815	Registered
Certification	Korea	KC	KR0034	Designation
	Germany	TUV	CARAT 17 11 89112 005	ISO/IEC 17025

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competent of calibration and testing laboratory".

3. General Information of EUT

Applicant	LG Electronics MobileComm USA, Inc. 1000 Sylvan Ave. Englewood Cliffs NJ 07632
Manufacturer	LG Electronics MobileComm USA, Inc. 1000 Sylvan Ave. Englewood Cliffs NJ 07632
Product Name	Mobile phone
Model Name	LM-G710V
Add Model Name	None
RF Module Name	None
FCC ID	ZNFG710V
IC ID	2703C-G710V
Rated Power	DC 3.85 V
Remarks	None

Related Submittal(s) / Grant(s)
Original submittal only

4. EUT Operations and Test Configurations

4.1 Principle of Configuration Selection

Emission :

The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use. For each testing mode different configurations were used, Refer to the individual tests.

4.2 EUT Operation Mode

No.	Mode	Description
1	PC LINK	The EUT is reading, writing, and erasing internal storage.

4.3 Test Configuration Mode

No.	Mode	Description
1	'READ' & 'WRITE' & 'DELETE'	EUT was connected PC by USB cable and continuously operated.

4.4 Supported Equipment

Used*	Product Type	Manufacturer	Model	Remarks
AE	KEYBOARD	LITEON Technology	KB25	None
AE	MOUSE	LG	SM-9023	None
AE	LCD MONITOR	DELL	UP2414Qt	None
AE	PC	DELL	DCNE	None
AE	SSD 3.0	SAMSUNG	MU-PT250B	None
AE	PRINTER	Bixelon	SRP-770	None
AE	Headset	COSY	COV909	None

*Abbreviations:

AE - Auxiliary/Associated Equipment, or
SIM - Simulator

4.5 EUT In/Output Port

Name	Type*	Cable Max. >3m	Cable Shielded	Cable Back shell	Remarks
USB OUT	I/O	1.7	Shield	Plastic	KEYBOARD
USB OUT	I/O	1.7	Shield	Plastic	MOUSE
POWER IN	AC	1.8	Non-Shield	Plastic	LCD MONITOR
DSUB OUT	I/O	1.8	Shield	Plastic	LCD MONITOR
POWER IN	AC	1.8	Non-Shield	Plastic	PC
DSUB IN	I/O	1.8	Shield	Plastic	PC
PARALLEL IN	I/O	2.0	Shield	Plastic	PC
SERIAL IN	I/O	1.9	Shield	Plastic	PC
USB IN	I/O	1.7	Shield	Plastic	PC
USB IN	I/O	1.7	Shield	Plastic	PC
USB IN	I/O	1.0	Shield	Plastic	PC
STEREO IN/OUT	I/O	2.0	Non-Shield	Plastic	PC
USB OUT	I/O	1.0	Shield	Plastic	SSD 3.0
POWER IN	DC	1.8	Non-Shield	Plastic	PRINTER
PARALLEL OUT	I/O	2.0	Shield	Plastic	PRINTER
SERIAL OUT	I/O	1.9	Shield	Plastic	PRINTER
STEREO IN/OUT	I/O	2.0	Non-Shield	Plastic	Headset
*Abbreviations: AC = AC Power Port DC = DC Power Port N/E = Non-Electrical I/O = Signal Input or Output Port TP = Telecommunication Ports					

4.6 Test Voltage and Frequency

Case	Voltage (V)	Frequency (Hz)	Phases	Remarks
1	AC 120	60 Hz	Single	None

5. Test Summary

Test Items	Applied Standards	Results
Conducted Disturbance	ANSI C63.4 : 2014 CAN/CSA CISPR 22-10	C
Radiated Disturbance	ANSI C63.4 : 2014 CAN/CSA CISPR 22-10	C
C=Comply N/C=Not Comply N/T=Not Tested N/A=Not Applicable		

The data in this test report are traceable to the national or international standards.

-Conducted Disturbance

Frequency [MHz]	Phase	Result [dBμV]	Detector	Limit [dBμV]	Margin [dB]
11.43097	L1	44.52	CAV	50.00	5.48

-Radiated Disturbance

Frequency [MHz]	Pol.	Result [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]
789.686	Horizontal	38.56	QP	46.00	7.44

6. Test Environment

Test Items	Test date (YYYY-MM-DD)	Temp. (°C)	Humidity (% R.H.)	Pressure (kPa)
Conducted Disturbance	2018-03-30	21	45	100.1
Radiated Disturbance	2018-04-02	20	45	-

7. Test Results : Emission

7.1 Conducted Disturbance

ANSI C63.4, CAN/CSA-CI SPR 22	Mains terminal disturbance voltage		Result
<u>Method:</u> The AMN placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane. This distance was between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment were at least 0,8 m from the AMN. All power was connected to the system through Artificial Mains Network (AMN). Conducted voltage measurements on mains lines were made at the output of the AMN. The measuring port of the LISN for EUT was connected to spectrum analyzer. Using conducted emission test software, the emissions were scanned with peak detector mode. After scanning over the frequency range, suspected emissions were selected to perform final measurement. When performing final measurement, the receiver was used which has Quasi-Peak detector and CISPR Average detector. For (0.15 ~ 30) MHz frequency range, Quasi-Peak detector with 10 kHz RBW and 30 kHz VBW was used. By varying the configuration of the test sample and the cable routing it was attempted to maximize the emission.			Comply
Fully configured sample scanned over the following frequency range	Frequency range on each side of line	Measurement Point	
	150 kHz to 30 MHz	Mains	
EUT mode (Refer to clauses 4)	Test configuration mode	1	
	EUT Operation mode	1	
Limits – Class A			
Frequency (MHz)	Limit dBµV		
	Quasi-Peak	Average	
0.15 to 0.50	79	66	
0.50 to 30	73	60	
Limits – Class B			
Frequency (MHz)	Limit dBµV		
	Quasi-Peak	Average	
0.15 to 0.50	66 to 56	56 to 46	
0.50 to 5	56	46	
5 to 30	60	50	
Measurement uncertainty			
Expended uncertainty <i>U</i> (95 %, Confidence level, <i>k</i> = 2)		2.36 dB	

Measurement Instrument					
Description	Model	Manufacturer	Identifier	Cal. Date	Cal. Due
MEASUREMENT SOFTWARE	EMI-C VER. 2.00.0171	TSJ	N/A	N/A	N/A
EMI TEST RECEIVER	ESR7	ROHDE & SCHWARZ	101109	2017.11.16	2018.11.16
TWO-LINE V-NETWORK	ENV216	ROHDE & SCHWARZ	101979	2017.12.18	2018.12.18
LISN	LISN1600	TTI	197204	2017.06.07	2018.06.07
TRANSIENT LIMITER	TL-B0930A	EMCIS	11002	2017.09.07	2018.09.07
50 OHM TERMINATOR	CT-01	TME	N/A	2017.12.26	2018.12.26

Mains terminal disturbance voltage _Measurement data			
Test configuration mode	1	EUT Operation mode	1
Test voltage (V)	120	Test Frequency (Hz)	60

Results of Conducted Emission


DT&C

Date 2018-03-30

Order No. DTNC1803-02406, 02407
Power Supply 120 V 60 Hz
Temp/Humi/Atm 21 °C 45 % R.H. 100.1 kPa
Test Condition PC LINK

Model Name LM-G710V

LIMIT : CISPR22_B QP
CISPR22_B AV



Results of Conducted Emission

DT&C

Date 2018-03-30

Order No. DTNC1803-02406, 02407
Power Supply 120 V 60 Hz
Temp/Humi/Atm 21 'C 45 % R.H. 100.1 kPa
Test Condition PC LINK

Model Name LM-G710V

LIMIT : CISPR22_B QP
CISPR22_B AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	11.43097	25.98	23.58	20.94	46.92	44.52	60.00	50.00	13.08	5.48	N
2	0.19248	21.73	21.30	20.01	41.74	41.31	63.93	53.93	22.19	12.62	N
3	0.83250	16.78	9.94	20.05	36.83	29.99	56.00	46.00	19.17	16.01	N
4	2.65096	9.90	3.80	20.05	29.95	23.85	56.00	46.00	26.05	22.15	N
5	4.96786	18.34	9.11	20.21	38.55	29.32	56.00	46.00	17.45	16.68	N
6	15.33826	18.24	12.67	21.17	39.41	33.84	60.00	50.00	20.59	16.16	N
7	21.93242	17.15	11.27	20.95	38.10	32.22	60.00	50.00	21.90	17.78	N
8	0.19230	19.76	18.13	20.04	39.80	38.17	63.94	53.94	24.14	15.77	L1
9	0.83734	17.61	10.87	20.15	37.76	31.02	56.00	46.00	18.24	14.98	L1
10	2.50769	13.46	8.74	20.13	33.59	28.87	56.00	46.00	22.41	17.13	L1
11	4.96149	15.63	10.90	20.31	35.94	31.21	56.00	46.00	20.06	14.79	L1
12	11.43066	26.09	23.26	21.01	47.10	44.27	60.00	50.00	12.90	5.73	L1
13	15.30352	17.51	12.16	21.17	38.68	33.33	60.00	50.00	21.32	16.67	L1
14	22.01433	9.66	4.37	20.94	30.60	25.31	60.00	50.00	29.40	24.69	L1

Calculation

N : Neutral phase, L1 : Live phase
C.FACTOR(dB) : Pulse Limiter(dB) + Cable loss(dB) + Insertion loss of LISN(dB)
Result(dBuV) : Reading Value(dBuV) + C.FACTOR(dB)
Margin(dB) : Limit(dBuV) - Result(dBuV)

7.2 Radiated Disturbance

ANSI C63.4, CAN/CSA-CI SPR 22	Radiated disturbance 30 MHz –18 GHz			Result
Method: Preliminary (peak) measurements were performed at an antenna to EUT separation distance of 10 meter below 1GHz and 3 meter above 1GHz. The EUT was rotated 360° about its azimuth with the receive antenna located at various heights in horizontal and vertical polarities. Final measurements were then performed by rotating the EUT 360° and adjusting the receive antenna height from 1 to 4 m. All frequencies were investigated in both horizontal and vertical antenna polarity, where applicable. For final measurement below 1 GHz frequency range, Quasi-Peak detector with (RBW = 120 kHz Bandwidth) was used. For final measurement above 1 GHz frequency range, Peak detector with (RBW = 1 MHz Bandwidth) and CISPR Average detector with (RBW = 1 MHz Bandwidth) were used.				Comply
EUT mode (Refer to clauses 4)		Test configuration mode	1	
		EUT Operation mode	1	
Radiated Disturbance below 1 000 MHz				
Frequency range (MHz)		Quasi-peak limit dBµV/m		
		Class A (10 m distance)	Class B (3 m distance)	
30 to 88		39.1	40	
88 to 216		43.5	43.5	
216 to 960		46.4	46	
960 to 1 000		49.5	54	
According to 15.109(g), as an alternative to the radiated emission limit shown above, digital devices may be shown to comply with the standards(CISPR), Pub. 22 shown as below.				
Frequency range (MHz)		Quasi-peak limit dBµV/m		
		Class A (10 m distance)	Class B (10 m distance)	
30 to 230		40	30	
230 to 1 000		47	37	
Radiated Disturbance for above 1 000 MHz at a measurement distance of 3 m				
Frequency range (GHz)		Peak limit dBµV/m		Average limit dBµV/m
		Class A	Class B	Class A Class B
1 to 40		80	74	60 54
The test frequency range of Radiated Disturbance measurements are listed below.				
Highest frequency generated or used in the device or on which the device operates or tunes (MHz)			Upper frequency of measurement range (MHz)	
Below 108			1 000	
108 – 500			2 000	
500 – 1 000			5 000	
Above 1 000			5 th harmonic of the highest frequency or 40 GHz, whichever is lower	
Measurement uncertainty				
Expended uncertainty <i>U</i> (95 %, Confidence level, <i>k</i> = 2)			4.16 dB, (30 ~ 1 000) MHz 3.74 dB, (1 ~ 6) GHz	

Measurement Instrument					
Description	Model	Manufacturer	Identifier	Cal. Date	Cal. Due
MEASUREMENT SOFTWARE	EMI-R VER. 2.00.0177	TSJ	N/A	N/A	N/A
EMI TEST RECEIVER	ESU	ROHDE & SCHWARZ	100469	2017.07.06	2018.07.06
TRILOG BROAD BAND ANTENNA	VULB9160	SCHWARZBECK	9160-3339	2017.04.21	2019.04.21
LOW NOISE PRE AMPLIFIER	MLA-100K01-B01-26	TSJ	1252741	2018.02.19	2019.02.19
PRE AMPLIFIER	8449B	H.P	3008A00887	2017.09.06	2018.09.06
BROAD-BAND HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1014	2016.08.05	2018.08.05
HORN ANTENNA	EM-6969	ELECTRO-METRICS	156	2018.01.02	2019.01.02
PREAMPLIFIER	MLA-0618-B03-34	TSJ	1785642	2017.03.02	2019.03.02
LOW NOISE PRE AMPLIFIER	MLA-1840-J02-40	TSJ	13184	2017.10.10	2018.10.10
HORN ANTENNA	SAS-574	A.H.SYSTEMS INC.	155	2017.07.31	2019.07.31
(NOTE : THE MEASUREMENT ANTENNAS WERE CALIBRATED IN ACCORDANCE TO THE REQUIREMENTS OF C63.5-2017.)					

Radiated disturbance at (30 ~ 1000) MHz _Measurement data			
Test configuration mode	1	EUT Operation mode	1
Test voltage (V)	120	Test Frequency (Hz)	60


RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406, 02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK

Model Name LM-G710V

LIMIT : FCC Part15 Subpart B Class B (3m)
MARGIN: 3 dB



RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406, 02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK

Model Name LM-G710V

LIMIT : FCC Part15 Subpart.B Class B (3m)
MARGIN: 3 dB

No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	351.653	44.20	14.45	3.10	25.43	36.32	46.00	9.68	195	11
2	789.686	36.50	22.40	5.05	25.39	38.56	46.00	7.44	150	152
----- Vertical -----										
3	30.485	41.20	9.33	0.84	25.47	25.90	40.00	14.10	305	349
4	216.114	44.30	10.01	2.49	25.54	31.26	46.00	14.74	200	358
5	239.030	45.00	11.58	2.68	25.56	33.70	46.00	12.30	120	358
6	350.612	45.70	14.42	3.09	25.43	37.78	46.00	8.22	115	358
7	359.301	45.30	14.68	3.16	25.43	37.71	46.00	8.29	110	235


Radiated disturbance at (1 ~ 6) GHz _Peak measurement data			
Test configuration mode	1	EUT Operation mode	1
Test voltage (V)	120	Test Frequency (Hz)	60

RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406, 02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK
Model Name LM-G710V

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
FCC Part15 Subpart B Class B (3m) - 18G(Avg)



RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406, 02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK

Model Name LM-G710V

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)

No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	PEAK [dBuV]	FACTOR [dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	1000.625	54.20	25.40	3.30	32.10	50.80	74.0	23.2	100	212
2	1207.500	54.00	25.62	3.84	32.19	51.27	74.0	22.73	100	235
3	1496.250	53.60	25.51	4.26	32.31	51.06	74.0	22.94	100	152
4	1597.500	54.30	25.31	4.17	32.35	51.43	74.0	22.57	100	203
5	1703.750	55.80	25.20	4.32	32.40	52.92	74.0	21.08	100	203
6	1996.875	52.00	26.08	4.82	32.52	50.38	74.0	23.62	100	358
----- Vertical -----										
7	1121.250	51.40	25.44	3.62	32.15	48.31	74.0	25.69	100	155
8	1210.000	50.90	25.63	3.85	32.19	48.19	74.0	25.81	100	0


Radiated disturbance at (1 ~ 6) GHz _Average measurement data			
Test configuration mode	1	EUT Operation mode	1
Test voltage (V)	120	Test Frequency (Hz)	60

RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406, 02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK
Model Name LM-G710V

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Avg)
FCC Part15 Subpart B Class B (3m) - 18G(Peak)



RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406, 02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK

Model Name LM-G710V

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)

No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
	[MHz]	CAV [dBuV]	FACTOR [dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	1000.325	31.50	25.40	3.30	32.10	28.10	54.00	25.90	105	15
2	1207.567	35.20	25.62	3.84	32.19	32.47	54.00	21.53	130	13
3	1496.212	37.50	25.51	4.26	32.31	34.96	54.00	19.04	110	132
4	1597.547	37.10	25.30	4.17	32.35	34.22	54.00	19.78	100	115
5	1703.732	36.20	25.20	4.32	32.40	33.32	54.00	20.68	105	137
6	1996.905	32.10	26.08	4.82	32.52	30.48	54.00	23.52	115	23
----- Vertical -----										
7	1121.213	32.70	25.44	3.62	32.15	29.61	54.00	24.39	120	186
8	1210.117	33.70	25.63	3.85	32.19	30.99	54.00	23.01	125	23


Radiated disturbance at (6 ~ 18) GHz _Peak measurement data			
Test configuration mode	1	EUT Operation mode	1
Test voltage (V)	120	Test Frequency (Hz)	60

RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406,02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK
Model Name LM-G710V

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Peak)
FCC Part15 Subpart B Class B (3m) - 18G(Avg)



* The measurement is performed above 18 GHz up to 30 GHz and not found emissions above 18 GHz.

RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406,02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK

Model Name LM-G710V

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Peak)
FCC Part15 Subpart.B Class B (3m) - 18G(Avg)

No.	FREQ	READING	ANT	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
		PEAK	FACTOR							
	[MHz]	[dBuV]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	6743.250	42.00	31.40	8.90	38.77	43.53	74.0	30.47	100	171
2	12073.500	33.60	33.27	12.45	38.31	41.01	74.0	32.99	100	1
----- Vertical -----										
3	6741.750	40.40	31.40	8.90	38.77	41.93	74.0	32.07	100	358
4	16459.500	32.70	36.85	13.27	36.36	46.46	74.0	27.54	100	121


Radiated disturbance at (6 ~ 18) GHz _Average measurement data			
Test configuration mode	1	EUT Operation mode	1
Test voltage (V)	120	Test Frequency (Hz)	60

RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406,02407
Power Supply 120 V 60 Hz
Temp/Humi 20 °C 45 % R.H.
Test Condition PC LINK
Model Name LM-G710V

LIMIT : FCC Part15 Subpart B Class B (3m) - 18G(Avg)
FCC Part15 Subpart B Class B (3m) - 18G(Peak)



* The measurement is performed above 18 GHz up to 30 GHz and not found emissions above 18 GHz.

RADIATED EMISSION

Date 2018-04-02

Order No. DTNC1803-02406,02407
Power Supply 120 V 60 Hz
Temp/Humi 20 'C 45 % R.H.
Test Condition PC LINK

Model Name LM-G710V

LIMIT : FCC Part15 Subpart.B Class B (3m) - 18G(Avg)
FCC Part15 Subpart.B Class B (3m) - 18G(Peak)

No.	FREQ [MHz]	READING CAV [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	6743.213	25.40	31.40	8.90	38.77	26.93	54.00	27.07	105	13
2	12073.690	21.50	33.27	12.45	38.31	28.91	54.00	25.09	110	223
----- Vertical -----										
3	6741.357	26.10	31.40	8.90	38.77	27.63	54.00	26.37	120	15
4	16458.250	20.70	36.84	13.27	36.36	34.45	54.00	19.55	115	153

Calculation

N : Neutral phase, L1 : Live phase
C.FACTOR(dB) : Pulse Limiter(dB) + Cable loss(dB) + Insertion loss of LISN(dB)
Result(dBμV) : Reading Value(dBμV) + C.FACTOR(dB)
Margin(dB) : Limit(dBμV) - Result(dBμV)

8. Revision History

Date	Description	Revised By	Reviewed By
Apr. 10. 2018	Initial report	JinYoung Park	MyungJin Song

-End of test report-