

DIPOLE CALIBRATION EXTENSION



Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:

1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.


The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:

Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Head (1g) W/kg @ 20.0 dBm	Measured Head SAR (1g) W/kg @ 20.0 dBm	Deviation 1g (%)	Certificate SAR Target Head (10g) W/kg @ 20.0 dBm	Measured Head SAR (10g) W/kg @ 20.0 dBm	Deviation 10g (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
1/11/2018	1/16/2019	1.136	6.46	6.23	-3.56%	2.44	2.34	-4.10%	53.2	52.9	0.3	-7.1	-5.9	1.2	-22.4	-24	-7.20%	PASS
Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Body (1g) W/kg @ 20.0 dBm	Measured Body SAR (1g) W/kg @ 20.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 20.0 dBm	Measured Body SAR (10g) W/kg @ 20.0 dBm	Deviation 10g (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL
1/11/2018	1/16/2019	1.136	6.51	6	-7.83%	2.42	2.26	-6.61%	53.4	49.8	3.6	-4.5	-5	0.5	-25.3	-25.9	-2.40%	PASS

Impedance & Return-Loss Measurement Plot for Head TSL



Impedance & Return-Loss Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **PC Test**

Certificate No: **D3700V2-1018_Jan18**

CALIBRATION CERTIFICATE

Object **D3700V2 - SN:1018**

Calibration procedure(s) **QA CAL-22.v2**
Calibration procedure for dipole validation kits between 3-6 GHz

Calibration date: **January 11, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02522)	Apr-18
Reference 20 dB Attenuator	SN: 5058 (20k)	07-Apr-17 (No. 217-02528)	Apr-18
Type-N mismatch combination	SN: 5047.2 / 06327	07-Apr-17 (No. 217-02529)	Apr-18
Reference Probe EX3DV4	SN: 3503	30-Dec-17 (No. EX3-3503_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by: **Michael Weber** Name
 Laboratory Technician Function

Approved by: **Katja Pokovic** Name
 Technical Manager Function

Signature

Issued: January 16, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy = 4 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	3700 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	37.7	3.12 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	38.3 $\pm$ 6 %	3.07 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	6.54 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	65.8 W/kg $\pm$ 19.9 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.41 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.2 W/kg $\pm$ 19.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	51.0	3.55 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	49.7 $\pm$ 6 %	3.53 mho/m $\pm$ 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	6.46 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	64.3 W/kg $\pm$ 19.9 % (k=2)

SAR averaged over 10 cm³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.32 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.1 W/kg $\pm$ 19.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	53.0 Ω - 8.3 j Ω
Return Loss	- 21.4 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	51.5 Ω - 6.3 j Ω
Return Loss	- 23.9 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.144 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	December 18, 2015

DASY5 Validation Report for Head TSL

Date: 11.01.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 3700 MHz; Type: D3700V2; Serial: D3700V2 - SN:1018

Communication System: UID 0 - CW; Frequency: 3700 MHz

Medium parameters used: $f = 3700$ MHz; $\sigma = 3.07$ S/m; $\epsilon_r = 38.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(7.5, 7.5, 7.5); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=100 mW, d=10mm/Zoom Scan, dist=1.4mm


(8x8x8)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 69.40 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 18.5 W/kg

SAR(1 g) = 6.54 W/kg; SAR(10 g) = 2.41 W/kg


Maximum value of SAR (measured) = 12.6 W/kg



Impedance Measurement Plot for Head TSL

11 Jan 2018 16:39:21
[CH1] S11 1 U FS 1: 52.961 Ω -8.3184 Ω 5.1711 pF 3 700.000 000 MHz


*
De1
CA



Avg
16
H1d

CH2 S11 LOG 5 dB/ REF -20 dB 1:-21.361 dB 3 700.000 000 MHz

CA
Avg
16
H1d



DASY5 Validation Report for Body TSL

Date: 10.01.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 3700 MHz; Type: D3700V2; Serial: D3700V2 - SN:1018

Communication System: UID 0 - CW; Frequency: 3700 MHz

Medium parameters used: $f = 3700$ MHz; $\sigma = 3.53$ S/m; $\epsilon_r = 49.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(7.28, 7.28, 7.28); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=100 mW, d=10mm/Zoom Scan , dist=1.4mm


(8x8x8)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.16 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 18.4 W/kg

SAR(1 g) = 6.46 W/kg; SAR(10 g) = 2.32 W/kg


Maximum value of SAR (measured) = 12.6 W/kg



Impedance Measurement Plot for Body TSL

10 Jan 2018 11:46:43
CH1 S11 1 U FS 1: 51.508 Ω -6.3027 Ω 6.8248 pF 3 700.000 000 MHz

*
Del
CA




Avg
16
H1d

CH2 S11 LOG 5 dB/REF -20 dB 1:-23.913 dB 3 700.000 000 MHz

CA

Avg
16

H1d



Certification of Calibration

Object D3700V2 – SN: 1018

Calibration procedure(s) Procedure for Calibration Extension for SAR Dipoles.

Extension Calibration date: 1/11/2019

Description: SAR Validation Dipole at 3500 MHz.

Calibration Equipment used:

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	2/8/2018	Annual	2/8/2019	US39170122
Agilent	N5182A	MXG Vector Signal Generator	4/18/2018	Annual	4/18/2019	MY47420800
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433971
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1207364
Anritsu	MA2411B	Pulse Power Sensor	3/2/2018	Annual	3/2/2019	1339018
Anritsu	ML2495A	Power Meter	10/21/2018	Annual	10/21/2019	941001
Control Company	4040	Therm./Clock/Humidity Monitor	3/31/2017	Biennial	3/31/2019	170232394
Control Company	4352	Ultra Long Stem Thermometer	5/2/2017	Biennial	5/2/2019	170330156
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	6/4/2018	Annual	6/4/2019	MY53401181
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Seekonk	NC-100	Torque Wrench	7/11/2018	Annual	7/11/2019	N/A
SPEAG	DAE4	Dasy Data Acquisition Electronics	10/3/2018	Annual	10/3/2019	1558
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/18/2018	Annual	6/18/2019	1334
SPEAG	DAK-3.5	Dielectric Assessment Kit	9/11/2018	Annual	9/11/2019	1091
SPEAG	EX3DV4	SAR Probe	2/14/2018	Annual	2/14/2019	3914
SPEAG	EX3DV4	SAR Probe	8/24/2018	Annual	8/24/2019	3949

Measurement Uncertainty = $\pm 23\%$ (k=2)

	Name	Function	Signature
Calibrated By:	Brodie Halfoster	Test Engineer	<i>BRODIE HALFOSTER</i>
Approved By:	Kaitlin O'Keefe	Senior Technical Manager	<i>KOK</i>

DIPOLE CALIBRATION EXTENSION



Per KDB 865664 D01, calibration intervals of up to three years may be considered for reference dipoles when it is demonstrated that the SAR target, impedance and return loss of a dipole have remained stable according to the following requirements:

1. The measured SAR does not deviate more than 10% from the target on the calibration certificate.
2. The return-loss does not deviate more than 20% from the previous measurement and meets the required 20dB minimum return-loss requirement.
3. The measurement of real or imaginary parts of impedance does not deviate more than 5Ω from the previous measurement.


The following dipole was checked to pass the above 3 requirements to have 2-year calibration period from the calibration date:

Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Head (1g) W/kg @ 20.0 dBm	Measured Head SAR (1g) W/kg @ 20.0 dBm	Deviation 1g (%)	Certificate SAR Target Head (10g) W/kg @ 20.0 dBm	Measured Head SAR (10g) W/kg @ 20.0 dBm	Deviation 10g (%)	Certificate Impedance Head (Ohm) Real	Measured Impedance Head (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Head (Ohm) Imaginary	Measured Impedance Head (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Head (dB)	Measured Return Loss Head (dB)	Deviation (%)	PASS/FAIL
1/11/2018	1/11/2019	1.144	6.58	6.22	-5.47%	2.42	2.27	-6.20%	53	51.1	1.9	-8.3	-5.5	2.8	-21.4	-25.1	-17.20%	PASS
Calibration Date	Extension Date	Certificate Electrical Delay (ns)	Certificate SAR Target Body (1g) W/kg @ 20.0 dBm	Measured Body SAR (1g) W/kg @ 20.0 dBm	Deviation 1g (%)	Certificate SAR Target Body (10g) W/kg @ 20.0 dBm	Measured Body SAR (10g) W/kg @ 20.0 dBm	Deviation 10g (%)	Certificate Impedance Body (Ohm) Real	Measured Impedance Body (Ohm) Real	Difference (Ohm) Real	Certificate Impedance Body (Ohm) Imaginary	Measured Impedance Body (Ohm) Imaginary	Difference (Ohm) Imaginary	Certificate Return Loss Body (dB)	Measured Return Loss Body (dB)	Deviation (%)	PASS/FAIL
1/11/2018	1/11/2019	1.144	6.43	6.08	-5.44%	2.31	2.21	-4.33%	51.5	54.2	2.7	-6.3	-2.3	4	-23.9	-20.9	-12.40%	PASS

Impedance & Return-Loss Measurement Plot for Head TSL



Impedance & Return-Loss Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **EX3-7417_Feb19**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:7417**

Calibration procedure(s) **QA CAL-01-V3 QA CAL-23-V5 QA CAL-25-V7**
 Calibration procedure for dosimetric E-field probes

Calibration date: **February 19, 2019**

02-26-2019

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-18 (No. 217-02682)	Apr-19
DAE4	SN: 660	19-Dec-18 (No. DAE4-660_Dec18)	Dec-19
Reference Probe ES3DV2	SN: 3013	31-Dec-18 (No. ES3-3013_Dec18)	Dec-19
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-18)	In house check: Oct-19

Calibrated by:	Name	Function	Signature
	Claudio Leubler	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: February 20, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E^2 -field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7417

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.54	0.43	0.53	± 10.1 %
DCP (mV) ^B	98.7	97.4	100.4	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB μV	C	D dB	VR mV	Max dev.	Max Unc ^E (k=2)
0	CW	X	0.00	0.00	1.00	0.00	144.6	± 3.3 %	± 4.7 %
		Y	0.00	0.00	1.00		149.7		
		Z	0.00	0.00	1.00		143.1		
10352-AAA	Pulse Waveform (200Hz, 10%)	X	15.00	88.38	19.65	10.00	60.0	± 3.3 %	± 9.6 %
		Y	4.33	71.38	13.30		60.0		
		Z	7.40	77.44	14.95		60.0		
10353-AAA	Pulse Waveform (200Hz, 20%)	X	15.00	92.19	20.43	6.99	80.0	± 2.2 %	± 9.6 %
		Y	5.53	76.01	13.64		80.0		
		Z	15.00	85.74	16.43		80.0		
10354-AAA	Pulse Waveform (200Hz, 40%)	X	15.00	107.68	26.54	3.98	95.0	± 1.3 %	± 9.6 %
		Y	9.05	79.53	12.66		95.0		
		Z	15.00	90.71	17.41		95.0		
10355-AAA	Pulse Waveform (200Hz, 60%)	X	15.00	127.17	33.83	2.22	120.0	± 1.2 %	± 9.6 %
		Y	0.26	60.00	4.45		120.0		
		Z	15.00	99.84	20.30		120.0		
10387-AAA	QPSK Waveform, 1 MHz	X	0.56	60.62	7.74	0.00	150.0	± 3.6 %	± 9.6 %
		Y	0.42	60.00	4.69		150.0		
		Z	0.44	60.00	5.48		150.0		
10388-AAA	QPSK Waveform, 10 MHz	X	2.27	69.09	16.46	0.00	150.0	± 1.3 %	± 9.6 %
		Y	1.94	67.43	15.43		150.0		
		Z	2.06	68.27	16.05		150.0		
10396-AAA	64-QAM Waveform, 100 kHz	X	3.15	72.71	19.95	3.01	150.0	± 2.5 %	± 9.6 %
		Y	2.04	67.08	18.19		150.0		
		Z	2.07	66.03	16.88		150.0		
10399-AAA	64-QAM Waveform, 40 MHz	X	3.52	67.53	16.10	0.00	150.0	± 2.4 %	± 9.6 %
		Y	3.32	66.83	15.68		150.0		
		Z	3.38	67.15	15.89		150.0		
10414-AAA	WLAN CCDF, 64-QAM, 40MHz	X	4.80	65.90	15.74	0.00	150.0	± 4.4 %	± 9.6 %
		Y	4.58	65.58	15.59		150.0		
		Z	4.60	65.76	15.65		150.0		

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7417

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 $ms.V^{-2}$	T2 $ms.V^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
X	37.6	279.10	35.33	9.45	0.00	5.09	1.69	0.14	1.01
Y	29.6	227.60	37.50	5.19	0.43	5.04	0.00	0.16	1.01
Z	28.8	214.34	35.37	6.91	0.00	5.04	0.00	0.24	1.00

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	120.5
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7417

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	41.9	0.89	10.36	10.36	10.36	0.54	0.99	± 12.0 %
835	41.5	0.90	10.07	10.07	10.07	0.48	0.84	± 12.0 %
1750	40.1	1.37	8.39	8.39	8.39	0.38	0.85	± 12.0 %
1900	40.0	1.40	8.11	8.11	8.11	0.39	0.84	± 12.0 %
2300	39.5	1.67	7.73	7.73	7.73	0.30	0.93	± 12.0 %
2450	39.2	1.80	7.46	7.46	7.46	0.39	0.95	± 12.0 %
2600	39.0	1.96	7.17	7.17	7.17	0.31	1.05	± 12.0 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

DASY/EASY - Parameters of Probe: EX3DV4 - SN:7417

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	55.5	0.96	10.35	10.35	10.35	0.63	0.84	± 12.0 %
835	55.2	0.97	10.11	10.11	10.11	0.43	0.84	± 12.0 %
1750	53.4	1.49	8.21	8.21	8.21	0.43	0.88	± 12.0 %
1900	53.3	1.52	7.86	7.86	7.86	0.43	0.87	± 12.0 %
2300	52.9	1.81	7.64	7.64	7.64	0.41	0.93	± 12.0 %
2450	52.7	1.95	7.51	7.51	7.51	0.40	0.95	± 12.0 %
2600	52.5	2.16	7.37	7.37	7.37	0.33	1.05	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-9 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM





f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ (k=2)

Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f_{\text{eval}} = 1900 \text{ MHz}$)





Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, ϑ), $f = 900 \text{ MHz}$



Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^F (k=2)
0		CW	CW	0.00	± 4.7 %
10010	CAA	SAR Validation (Square, 100ms, 10ms)	Test	10.00	± 9.6 %
10011	CAB	UMTS-FDD (WCDMA)	WCDMA	2.91	± 9.6 %
10012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	± 9.6 %
10013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	± 9.6 %
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	± 9.6 %
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	± 9.6 %
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	± 9.6 %
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	± 9.6 %
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	± 9.6 %
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4.80	± 9.6 %
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	GSM	3.55	± 9.6 %
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	± 9.6 %
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	± 9.6 %
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Bluetooth	1.87	± 9.6 %
10032	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluetooth	1.16	± 9.6 %
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	± 9.6 %
10034	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Bluetooth	4.53	± 9.6 %
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	± 9.6 %
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	± 9.6 %
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	± 9.6 %
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10	± 9.6 %
10039	CAB	CDMA2000 (1xRTT, RC1)	CDMA2000	4.57	± 9.6 %
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	± 9.6 %
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0.00	± 9.6 %
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	± 9.6 %
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	± 9.6 %
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	± 9.6 %
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	± 9.6 %
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	± 9.6 %
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	± 9.6 %
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	± 9.6 %
10062	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	± 9.6 %
10063	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	WLAN	8.63	± 9.6 %
10064	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	± 9.6 %
10065	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9.00	± 9.6 %
10066	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	9.38	± 9.6 %
10067	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	± 9.6 %
10068	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	± 9.6 %
10069	CAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	WLAN	10.56	± 9.6 %
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	± 9.6 %
10072	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.62	± 9.6 %
10073	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9.94	± 9.6 %
10074	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10.30	± 9.6 %
10075	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.77	± 9.6 %
10076	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	WLAN	10.94	± 9.6 %
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	WLAN	11.00	± 9.6 %
10081	CAB	CDMA2000 (1xRTT, RC3)	CDMA2000	3.97	± 9.6 %
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	AMPS	4.77	± 9.6 %
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	GSM	6.56	± 9.6 %
10097	CAB	UMTS-FDD (HSDPA)	WCDMA	3.98	± 9.6 %
10098	CAB	UMTS-FDD (HSUPA, Subtest 2)	WCDMA	3.98	± 9.6 %
10099	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	GSM	9.55	± 9.6 %
10100	CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-FDD	5.67	± 9.6 %
10101	CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	± 9.6 %
10102	CAE	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	± 9.6 %
10103	CAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-TDD	9.29	± 9.6 %
10104	CAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-TDD	9.97	± 9.6 %
10105	CAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-TDD	10.01	± 9.6 %
10108	CAG	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-FDD	5.80	± 9.6 %

10109	CAG	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	± 9.6 %
10110	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-FDD	5.75	± 9.6 %
10111	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-FDD	6.44	± 9.6 %
10112	CAG	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-FDD	6.59	± 9.6 %
10113	CAG	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FDD	6.62	± 9.6 %
10114	CAC	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	WLAN	8.10	± 9.6 %
10115	CAC	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	± 9.6 %
10116	CAC	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8.15	± 9.6 %
10117	CAC	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8.07	± 9.6 %
10118	CAC	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8.59	± 9.6 %
10119	CAC	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	WLAN	8.13	± 9.6 %
10140	CAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FDD	6.49	± 9.6 %
10141	CAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-FDD	6.53	± 9.6 %
10142	CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10143	CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6.35	± 9.6 %
10144	CAE	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	6.65	± 9.6 %
10145	CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	5.76	± 9.6 %
10146	CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.41	± 9.6 %
10147	CAF	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.72	± 9.6 %
10149	CAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	± 9.6 %
10150	CAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	± 9.6 %
10151	CAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-TDD	9.28	± 9.6 %
10152	CAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-TDD	9.92	± 9.6 %
10153	CAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-TDD	10.05	± 9.6 %
10154	CAG	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-FDD	5.75	± 9.6 %
10155	CAG	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.43	± 9.6 %
10156	CAG	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-FDD	5.79	± 9.6 %
10157	CAG	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-FDD	6.49	± 9.6 %
10158	CAG	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	± 9.6 %
10159	CAG	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-FDD	6.56	± 9.6 %
10160	CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-FDD	5.82	± 9.6 %
10161	CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-FDD	6.43	± 9.6 %
10162	CAE	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-FDD	6.58	± 9.6 %
10166	CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-FDD	5.46	± 9.6 %
10167	CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.21	± 9.6 %
10168	CAF	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.79	± 9.6 %
10169	CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10170	CAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10171	AAE	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-FDD	6.49	± 9.6 %
10172	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-TDD	9.21	± 9.6 %
10173	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10174	CAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10175	CAG	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-FDD	5.72	± 9.6 %
10176	CAG	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10177	CAI	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10178	CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10179	CAG	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10180	CAG	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10181	CAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-FDD	5.72	± 9.6 %
10182	CAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10183	AAD	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10184	CAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10185	CAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-FDD	6.51	± 9.6 %
10186	AAE	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10187	CAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-FDD	5.73	± 9.6 %
10188	CAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.52	± 9.6 %
10189	AAF	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.50	± 9.6 %
10193	CAC	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	± 9.6 %
10194	CAC	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	WLAN	8.12	± 9.6 %
10195	CAC	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	WLAN	8.21	± 9.6 %
10196	CAC	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.10	± 9.6 %
10197	CAC	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8.13	± 9.6 %
10198	CAC	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	WLAN	8.27	± 9.6 %
10219	CAC	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	WLAN	8.03	± 9.6 %

10220	CAC	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	WLAN	8.13	± 9.6 %
10221	CAC	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.27	± 9.6 %
10222	CAC	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	WLAN	8.06	± 9.6 %
10223	CAC	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8.48	± 9.6 %
10224	CAC	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	8.08	± 9.6 %
10225	CAB	UMTS-FDD (HSPA+)	WCDMA	5.97	± 9.6 %
10226	CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.49	± 9.6 %
10227	CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.26	± 9.6 %
10228	CAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	9.22	± 9.6 %
10229	CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10230	CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10231	CAC	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-TDD	9.19	± 9.6 %
10232	CAF	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10233	CAF	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10234	CAF	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-TDD	9.21	± 9.6 %
10235	CAF	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10236	CAF	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10237	CAF	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-TDD	9.21	± 9.6 %
10238	CAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-TDD	9.48	± 9.6 %
10239	CAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-TDD	10.25	± 9.6 %
10240	CAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-TDD	9.21	± 9.6 %
10241	CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.82	± 9.6 %
10242	CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-TDD	9.86	± 9.6 %
10243	CAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-TDD	9.46	± 9.6 %
10244	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	10.06	± 9.6 %
10245	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.06	± 9.6 %
10246	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	9.30	± 9.6 %
10247	CAF	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-TDD	9.91	± 9.6 %
10248	CAF	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-TDD	10.09	± 9.6 %
10249	CAF	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-TDD	9.29	± 9.6 %
10250	CAF	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-TDD	9.81	± 9.6 %
10251	CAF	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-TDD	10.17	± 9.6 %
10252	CAF	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-TDD	9.24	± 9.6 %
10253	CAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-TDD	9.90	± 9.6 %
10254	CAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-TDD	10.14	± 9.6 %
10255	CAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-TDD	9.20	± 9.6 %
10256	CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.96	± 9.6 %
10257	CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.08	± 9.6 %
10258	CAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	9.34	± 9.6 %
10259	CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	9.98	± 9.6 %
10260	CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	± 9.6 %
10261	CAC	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	± 9.6 %
10262	CAF	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TDD	9.83	± 9.6 %
10263	CAF	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-TDD	10.16	± 9.6 %
10264	CAF	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	± 9.6 %
10265	CAF	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	± 9.6 %
10266	CAF	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TDD	10.07	± 9.6 %
10267	CAF	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TDD	9.30	± 9.6 %
10268	CAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-TDD	10.06	± 9.6 %
10269	CAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-TDD	10.13	± 9.6 %
10270	CAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-TDD	9.58	± 9.6 %
10274	CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	WCDMA	4.87	± 9.6 %
10275	CAB	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	WCDMA	3.96	± 9.6 %
10277	CAA	PHS (QPSK)	PHS	11.81	± 9.6 %
10278	CAA	PHS (QPSK, BW 884MHz, Rolloff 0.5)	PHS	11.81	± 9.6 %
10279	CAA	PHS (QPSK, BW 884MHz, Rolloff 0.38)	PHS	12.18	± 9.6 %
10290	AAB	CDMA2000, RC1, SO55, Full Rate	CDMA2000	3.91	± 9.6 %
10291	AAB	CDMA2000, RC3, SO55, Full Rate	CDMA2000	3.46	± 9.6 %
10292	AAB	CDMA2000, RC3, SO32, Full Rate	CDMA2000	3.39	± 9.6 %
10293	AAB	CDMA2000, RC3, SO3, Full Rate	CDMA2000	3.50	± 9.6 %
10295	AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	CDMA2000	12.49	± 9.6 %
10297	AAD	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FDD	5.81	± 9.6 %
10298	AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	5.72	± 9.6 %
10299	AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	± 9.6 %

10300	AAD	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6.60	± 9.6 %
10301	AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC)	WiMAX	12.03	± 9.6 %
10302	AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, QPSK, PUSC, 3 CTRL symbols)	WiMAX	12.57	± 9.6 %
10303	AAA	IEEE 802.16e WiMAX (31:15, 5ms, 10MHz, 64QAM, PUSC)	WiMAX	12.52	± 9.6 %
10304	AAA	IEEE 802.16e WiMAX (29:18, 5ms, 10MHz, 64QAM, PUSC)	WiMAX	11.86	± 9.6 %
10305	AAA	IEEE 802.16e WiMAX (31:15, 10ms, 10MHz, 64QAM, PUSC, 15 symbols)	WiMAX	15.24	± 9.6 %
10306	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 64QAM, PUSC, 18 symbols)	WiMAX	14.67	± 9.6 %
10307	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, PUSC, 18 symbols)	WiMAX	14.49	± 9.6 %
10308	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, PUSC)	WiMAX	14.46	± 9.6 %
10309	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, 16QAM, AMC 2x3, 18 symbols)	WiMAX	14.58	± 9.6 %
10310	AAA	IEEE 802.16e WiMAX (29:18, 10ms, 10MHz, QPSK, AMC 2x3, 18 symbols)	WiMAX	14.57	± 9.6 %
10311	AAD	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	± 9.6 %
10313	AAA	IDEN 1:3	IDEN	10.51	± 9.6 %
10314	AAA	IDEN 1:6	IDEN	13.48	± 9.6 %
10315	AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	WLAN	1.71	± 9.6 %
10316	AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	± 9.6 %
10317	AAC	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	± 9.6 %
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	± 9.6 %
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	± 9.6 %
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3.98	± 9.6 %
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	± 9.6 %
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	0.97	± 9.6 %
10387	AAA	QPSK Waveform, 1 MHz	Generic	5.10	± 9.6 %
10388	AAA	QPSK Waveform, 10 MHz	Generic	5.22	± 9.6 %
10396	AAA	64-QAM Waveform, 100 kHz	Generic	6.27	± 9.6 %
10399	AAA	64-QAM Waveform, 40 MHz	Generic	6.27	± 9.6 %
10400	AAD	IEEE 802.11ac WiFi (20MHz, 64-QAM, 99pc duty cycle)	WLAN	8.37	± 9.6 %
10401	AAD	IEEE 802.11ac WiFi (40MHz, 64-QAM, 99pc duty cycle)	WLAN	8.60	± 9.6 %
10402	AAD	IEEE 802.11ac WiFi (80MHz, 64-QAM, 99pc duty cycle)	WLAN	8.53	± 9.6 %
10403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.76	± 9.6 %
10404	AAB	CDMA2000 (1xEV-DO, Rev. A)	CDMA2000	3.77	± 9.6 %
10406	AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	CDMA2000	5.22	± 9.6 %
10410	AAF	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	LTE-TDD	7.82	± 9.6 %
10414	AAA	WLAN CCDF, 64-QAM, 40MHz	Generic	8.54	± 9.6 %
10415	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	WLAN	1.54	± 9.6 %
10416	AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	± 9.6 %
10417	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	± 9.6 %
10418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	WLAN	8.14	± 9.6 %
10419	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	WLAN	8.19	± 9.6 %
10422	AAB	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	WLAN	8.32	± 9.6 %
10423	AAB	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	WLAN	8.47	± 9.6 %
10424	AAB	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	± 9.6 %
10425	AAB	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	WLAN	8.41	± 9.6 %
10426	AAB	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	WLAN	8.45	± 9.6 %
10427	AAB	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	WLAN	8.41	± 9.6 %
10430	AAD	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	LTE-FDD	8.28	± 9.6 %
10431	AAD	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	LTE-FDD	8.38	± 9.6 %
10432	AAC	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	LTE-FDD	8.34	± 9.6 %
10433	AAC	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	LTE-FDD	8.34	± 9.6 %
10434	AAA	W-CDMA (BS Test Model 1, 64 DPCH)	WCDMA	8.60	± 9.6 %
10435	AAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10447	AAD	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.56	± 9.6 %
10448	AAD	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.53	± 9.6 %
10449	AAC	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.51	± 9.6 %
10450	AAC	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	± 9.6 %

10451	AAA	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	WCDMA	7.59	± 9.6 %
10456	AAB	IEEE 802.11ac WiFi (160MHz, 64-QAM, 99pc duty cycle)	WLAN	8.63	± 9.6 %
10457	AAA	UMTS-FDD (DC-HSDPA)	WCDMA	6.62	± 9.6 %
10458	AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	CDMA2000	6.55	± 9.6 %
10459	AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	CDMA2000	8.25	± 9.6 %
10460	AAA	UMTS-FDD (WCDMA, AMR)	WCDMA	2.39	± 9.6 %
10461	AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10462	AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.30	± 9.6 %
10463	AAA	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	± 9.6 %
10464	AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10465	AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10466	AAB	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	± 9.6 %
10467	AAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10468	AAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10469	AAE	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	± 9.6 %
10470	AAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10471	AAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10472	AAE	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	± 9.6 %
10473	AAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	± 9.6 %
10474	AAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10475	AAE	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	± 9.6 %
10477	AAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	± 9.6 %
10478	AAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	± 9.6 %
10479	AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %
10480	AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.18	± 9.6 %
10481	AAA	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	± 9.6 %
10482	AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.71	± 9.6 %
10483	AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.39	± 9.6 %
10484	AAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.47	± 9.6 %
10485	AAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.59	± 9.6 %
10486	AAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.38	± 9.6 %
10487	AAE	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.60	± 9.6 %
10488	AAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.70	± 9.6 %
10489	AAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	± 9.6 %
10490	AAE	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	± 9.6 %
10491	AAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %

10492	AAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.41	± 9.6 %
10493	AAE	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	± 9.6 %
10494	AAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %
10495	AAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.37	± 9.6 %
10496	AAF	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	± 9.6 %
10497	AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	± 9.6 %
10498	AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.40	± 9.6 %
10499	AAA	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.68	± 9.6 %
10500	AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	± 9.6 %
10501	AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.44	± 9.6 %
10502	AAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.52	± 9.6 %
10503	AAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.72	± 9.6 %
10504	AAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	± 9.6 %
10505	AAE	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	± 9.6 %
10506	AAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %
10507	AAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.36	± 9.6 %
10508	AAE	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	± 9.6 %
10509	AAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.99	± 9.6 %
10510	AAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.49	± 9.6 %
10511	AAE	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.51	± 9.6 %
10512	AAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	± 9.6 %
10513	AAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.42	± 9.6 %
10514	AAF	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	± 9.6 %
10515	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	WLAN	1.58	± 9.6 %
10516	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	WLAN	1.57	± 9.6 %
10517	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	WLAN	1.58	± 9.6 %
10518	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.23	± 9.6 %
10519	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.39	± 9.6 %
10520	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.12	± 9.6 %
10521	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	WLAN	7.97	± 9.6 %
10522	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.45	± 9.6 %
10523	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.08	± 9.6 %
10524	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.27	± 9.6 %
10525	AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 99pc duty cycle)	WLAN	8.36	± 9.6 %
10526	AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 99pc duty cycle)	WLAN	8.42	± 9.6 %
10527	AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 99pc duty cycle)	WLAN	8.21	± 9.6 %
10528	AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 99pc duty cycle)	WLAN	8.36	± 9.6 %
10529	AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 99pc duty cycle)	WLAN	8.36	± 9.6 %
10531	AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 99pc duty cycle)	WLAN	8.43	± 9.6 %
10532	AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 99pc duty cycle)	WLAN	8.29	± 9.6 %
10533	AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 99pc duty cycle)	WLAN	8.38	± 9.6 %
10534	AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 99pc duty cycle)	WLAN	8.45	± 9.6 %

10535	AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 99pc duty cycle)	WLAN	8.45	± 9.6 %
10536	AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 99pc duty cycle)	WLAN	8.32	± 9.6 %
10537	AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 99pc duty cycle)	WLAN	8.44	± 9.6 %
10538	AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 99pc duty cycle)	WLAN	8.54	± 9.6 %
10540	AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 99pc duty cycle)	WLAN	8.39	± 9.6 %
10541	AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 99pc duty cycle)	WLAN	8.46	± 9.6 %
10542	AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 99pc duty cycle)	WLAN	8.65	± 9.6 %
10543	AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 99pc duty cycle)	WLAN	8.65	± 9.6 %
10544	AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 99pc duty cycle)	WLAN	8.47	± 9.6 %
10545	AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 99pc duty cycle)	WLAN	8.55	± 9.6 %
10546	AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 99pc duty cycle)	WLAN	8.35	± 9.6 %
10547	AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 99pc duty cycle)	WLAN	8.49	± 9.6 %
10548	AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 99pc duty cycle)	WLAN	8.37	± 9.6 %
10550	AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 99pc duty cycle)	WLAN	8.38	± 9.6 %
10551	AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 99pc duty cycle)	WLAN	8.50	± 9.6 %
10552	AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 99pc duty cycle)	WLAN	8.42	± 9.6 %
10553	AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 99pc duty cycle)	WLAN	8.45	± 9.6 %
10554	AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 99pc duty cycle)	WLAN	8.48	± 9.6 %
10555	AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 99pc duty cycle)	WLAN	8.47	± 9.6 %
10556	AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 99pc duty cycle)	WLAN	8.50	± 9.6 %
10557	AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 99pc duty cycle)	WLAN	8.52	± 9.6 %
10558	AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 99pc duty cycle)	WLAN	8.61	± 9.6 %
10560	AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 99pc duty cycle)	WLAN	8.73	± 9.6 %
10561	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 99pc duty cycle)	WLAN	8.56	± 9.6 %
10562	AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 99pc duty cycle)	WLAN	8.69	± 9.6 %
10563	AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 99pc duty cycle)	WLAN	8.77	± 9.6 %
10564	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.25	± 9.6 %
10565	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.45	± 9.6 %
10566	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.13	± 9.6 %
10567	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	WLAN	8.00	± 9.6 %
10568	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.37	± 9.6 %
10569	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.10	± 9.6 %
10570	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.30	± 9.6 %
10571	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	WLAN	1.99	± 9.6 %
10572	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	WLAN	1.99	± 9.6 %
10573	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	WLAN	1.98	± 9.6 %
10574	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	WLAN	1.98	± 9.6 %
10575	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	± 9.6 %
10576	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	± 9.6 %
10577	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	± 9.6 %
10578	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	± 9.6 %
10579	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	± 9.6 %
10580	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	± 9.6 %
10581	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	± 9.6 %
10582	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	± 9.6 %
10583	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	± 9.6 %
10584	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	± 9.6 %
10585	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	± 9.6 %
10586	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	± 9.6 %
10587	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	± 9.6 %

10588	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	± 9.6 %
10589	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	± 9.6 %
10590	AAB	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	± 9.6 %
10591	AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	WLAN	8.63	± 9.6 %
10592	AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	WLAN	8.79	± 9.6 %
10593	AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	WLAN	8.64	± 9.6 %
10594	AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	WLAN	8.74	± 9.6 %
10595	AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	WLAN	8.74	± 9.6 %
10596	AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	WLAN	8.71	± 9.6 %
10597	AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	WLAN	8.72	± 9.6 %
10598	AAB	IEEE 802.11n (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	WLAN	8.50	± 9.6 %
10599	AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	WLAN	8.79	± 9.6 %
10600	AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	WLAN	8.88	± 9.6 %
10601	AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	WLAN	8.82	± 9.6 %
10602	AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	WLAN	8.94	± 9.6 %
10603	AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	WLAN	9.03	± 9.6 %
10604	AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	WLAN	8.76	± 9.6 %
10605	AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	WLAN	8.97	± 9.6 %
10606	AAB	IEEE 802.11n (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	WLAN	8.82	± 9.6 %
10607	AAB	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	WLAN	8.64	± 9.6 %
10608	AAB	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	WLAN	8.77	± 9.6 %
10609	AAB	IEEE 802.11ac WiFi (20MHz, MCS2, 90pc duty cycle)	WLAN	8.57	± 9.6 %
10610	AAB	IEEE 802.11ac WiFi (20MHz, MCS3, 90pc duty cycle)	WLAN	8.78	± 9.6 %
10611	AAB	IEEE 802.11ac WiFi (20MHz, MCS4, 90pc duty cycle)	WLAN	8.70	± 9.6 %
10612	AAB	IEEE 802.11ac WiFi (20MHz, MCS5, 90pc duty cycle)	WLAN	8.77	± 9.6 %
10613	AAB	IEEE 802.11ac WiFi (20MHz, MCS6, 90pc duty cycle)	WLAN	8.94	± 9.6 %
10614	AAB	IEEE 802.11ac WiFi (20MHz, MCS7, 90pc duty cycle)	WLAN	8.59	± 9.6 %
10615	AAB	IEEE 802.11ac WiFi (20MHz, MCS8, 90pc duty cycle)	WLAN	8.82	± 9.6 %
10616	AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	WLAN	8.82	± 9.6 %
10617	AAB	IEEE 802.11ac WiFi (40MHz, MCS1, 90pc duty cycle)	WLAN	8.81	± 9.6 %
10618	AAB	IEEE 802.11ac WiFi (40MHz, MCS2, 90pc duty cycle)	WLAN	8.58	± 9.6 %
10619	AAB	IEEE 802.11ac WiFi (40MHz, MCS3, 90pc duty cycle)	WLAN	8.86	± 9.6 %
10620	AAB	IEEE 802.11ac WiFi (40MHz, MCS4, 90pc duty cycle)	WLAN	8.87	± 9.6 %
10621	AAB	IEEE 802.11ac WiFi (40MHz, MCS5, 90pc duty cycle)	WLAN	8.77	± 9.6 %
10622	AAB	IEEE 802.11ac WiFi (40MHz, MCS6, 90pc duty cycle)	WLAN	8.68	± 9.6 %
10623	AAB	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	WLAN	8.82	± 9.6 %
10624	AAB	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	WLAN	8.96	± 9.6 %
10625	AAB	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	WLAN	8.96	± 9.6 %
10626	AAB	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	WLAN	8.83	± 9.6 %
10627	AAB	IEEE 802.11ac WiFi (80MHz, MCS1, 90pc duty cycle)	WLAN	8.88	± 9.6 %
10628	AAB	IEEE 802.11ac WiFi (80MHz, MCS2, 90pc duty cycle)	WLAN	8.71	± 9.6 %
10629	AAB	IEEE 802.11ac WiFi (80MHz, MCS3, 90pc duty cycle)	WLAN	8.85	± 9.6 %
10630	AAB	IEEE 802.11ac WiFi (80MHz, MCS4, 90pc duty cycle)	WLAN	8.72	± 9.6 %
10631	AAB	IEEE 802.11ac WiFi (80MHz, MCS5, 90pc duty cycle)	WLAN	8.81	± 9.6 %
10632	AAB	IEEE 802.11ac WiFi (80MHz, MCS6, 90pc duty cycle)	WLAN	8.74	± 9.6 %
10633	AAB	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	WLAN	8.83	± 9.6 %
10634	AAB	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	WLAN	8.80	± 9.6 %
10635	AAB	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	WLAN	8.81	± 9.6 %
10636	AAC	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	WLAN	8.83	± 9.6 %
10637	AAC	IEEE 802.11ac WiFi (160MHz, MCS1, 90pc duty cycle)	WLAN	8.79	± 9.6 %
10638	AAC	IEEE 802.11ac WiFi (160MHz, MCS2, 90pc duty cycle)	WLAN	8.86	± 9.6 %
10639	AAC	IEEE 802.11ac WiFi (160MHz, MCS3, 90pc duty cycle)	WLAN	8.85	± 9.6 %
10640	AAC	IEEE 802.11ac WiFi (160MHz, MCS4, 90pc duty cycle)	WLAN	8.98	± 9.6 %
10641	AAC	IEEE 802.11ac WiFi (160MHz, MCS5, 90pc duty cycle)	WLAN	9.06	± 9.6 %
10642	AAC	IEEE 802.11ac WiFi (160MHz, MCS6, 90pc duty cycle)	WLAN	9.06	± 9.6 %
10643	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	WLAN	8.89	± 9.6 %
10644	AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	WLAN	9.05	± 9.6 %
10645	AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	WLAN	9.11	± 9.6 %
10646	AAF	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	± 9.6 %
10647	AAF	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	± 9.6 %
10648	AAA	CDMA2000 (1x Advanced)	CDMA2000	3.45	± 9.6 %
10652	AAD	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.91	± 9.6 %
10653	AAD	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.42	± 9.6 %
10654	AAD	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.96	± 9.6 %

10655	AAE	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.21	± 9.6 %
10658	AAA	Pulse Waveform (200Hz, 10%)	Test	10.00	± 9.6 %
10659	AAA	Pulse Waveform (200Hz, 20%)	Test	6.99	± 9.6 %
10660	AAA	Pulse Waveform (200Hz, 40%)	Test	3.98	± 9.6 %
10661	AAA	Pulse Waveform (200Hz, 60%)	Test	2.22	± 9.6 %
10662	AAA	Pulse Waveform (200Hz, 80%)	Test	0.97	± 9.6 %
10670	AAA	Bluetooth Low Energy	Bluetooth	2.19	± 9.6 %

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

APPENDIX D: SAR TISSUE SPECIFICATIONS

Measurement Procedure for Tissue verification:

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the tissue. The tissue was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity ϵ' can be calculated from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

3 Composition / Information on ingredients

3.2 Mixtures

Description: Aqueous solution with surfactants and inhibitors

Declarable, or hazardous components:

CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 01-2119456816-28-0000	Ethanediol STOT RE 2, H373; Acute Tox. 4, H302	>1.0-4.9%
CAS: 68608-26-4 EINECS: 271-781-5 Reg.nr.: 01-2119527859-22-0000	Sodium petroleum sulfonate Eye Irrit. 2, H319	< 2.9%
CAS: 107-41-5 EINECS: 203-489-0 Reg.nr.: 01-2119539582-35-0000	Hexylene Glycol / 2-Methyl-pentane-2,4-diol Skin Irrit. 2, H315; Eye Irrit. 2, H319	< 2.9%
CAS: 68920-66-1 NLP: 500-236-9 Reg.nr.: 01-2119489407-26-0000	Alkoxyated alcohol, > C₁₆ Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319	< 2.0%

Additional information:

For the wording of the listed risk phrases refer to section 16.

Not mentioned CAS-, EINECS- or registration numbers are to be regarded as Proprietary/Confidential.

The specific chemical identity and/or exact percentage concentration of proprietary components is withheld as a trade secret.

Figure D-I

Note: Liquid recipes are proprietary SPEAG. Since the composition is approximate to the actual liquids utilized, the manufacturer tissue-equivalent liquid data sheets are provided below.

FCC ID: ZNFG850UM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Test Dates: 08/21/19 – 09/12/19	DUT Type: Portable Handset			APPENDIX D: Page 1 of 3

Measurement Certificate / Material Test

Item Name **Body Tissue Simulating Liquid (MBBL600-6000V6)**
 Product No. SL AAM U16 BC (Batch: 181029-1)
 Manufacturer SPEAG

Measurement Method

TSL dielectric parameters measured using calibrated DAK probe.

Target Parameters

Target parameters as defined in the KDB 865864 compliance standard.

Test Condition



Ambient Condition 22°C ; 30% humidity
 TSL Temperature 22°C
 Test Date 30-Oct-18
 Operator CL

Additional Information

TSL Density
 TSL Heat-capacity

Results

f [MHz]	Measured			Target		Diff.to Target [%]	
	e'	e''	sigma	eps	sigma	Δ-eps	Δ-sigma
800	55.1	21.3	0.95	55.3	0.97	-0.4	-2.1
825	55.1	20.8	0.96	55.2	0.98	-0.3	-2.0
835	55.1	20.6	0.96	55.1	0.99	0.0	-2.5
850	55.1	20.4	0.96	55.2	0.99	-0.1	-3.0
900	55.0	19.7	0.98	55.0	1.05	0.0	-6.7
1400	54.2	15.6	1.22	54.1	1.28	0.2	-4.7
1450	54.1	15.4	1.24	54.0	1.30	0.2	-4.6
1500	54.1	15.3	1.27	53.9	1.33	0.3	-4.5
1550	54.0	15.1	1.30	53.9	1.36	0.2	-4.4
1600	53.9	15.0	1.33	53.8	1.39	0.2	-4.3
1625	53.9	14.9	1.35	53.8	1.41	0.3	-4.3
1640	53.9	14.9	1.36	53.7	1.42	0.3	-4.2
1650	53.8	14.9	1.36	53.7	1.43	0.2	-4.9
1700	53.8	14.8	1.40	53.6	1.46	0.4	-4.1
1750	53.7	14.7	1.43	53.4	1.49	0.5	-4.0
1800	53.7	14.6	1.46	53.3	1.52	0.8	-3.9
1810	53.7	14.6	1.47	53.3	1.52	0.8	-3.3
1825	53.7	14.6	1.48	53.3	1.52	0.8	-2.6
1850	53.6	14.5	1.50	53.3	1.52	0.6	-1.3
1900	53.5	14.5	1.53	53.3	1.52	0.4	0.7
1950	53.5	14.5	1.57	53.3	1.52	0.4	3.3
2000	53.4	14.4	1.60	53.3	1.52	0.2	5.3
2050	53.4	14.4	1.64	53.2	1.57	0.3	4.5
2100	53.3	14.4	1.68	53.2	1.62	0.2	3.7
2150	53.3	14.4	1.72	53.1	1.66	0.4	3.6
2200	53.2	14.4	1.76	53.0	1.71	0.3	2.9
2250	53.1	14.4	1.81	53.0	1.76	0.2	2.8
2300	53.1	14.4	1.85	52.9	1.81	0.4	2.2
2350	53.0	14.5	1.89	52.8	1.85	0.3	2.2
2400	52.9	14.5	1.94	52.8	1.90	0.2	2.1
2450	52.9	14.5	1.98	52.7	1.95	0.4	1.5
2500	52.8	14.6	2.03	52.6	2.02	0.3	0.5
2550	52.7	14.6	2.07	52.6	2.09	0.2	-1.0
2600	52.6	14.7	2.12	52.5	2.16	0.2	-1.9



3500	51.1	15.5	3.02	51.3	3.31	-0.4	-8.8
3700	50.8	15.7	3.24	51.1	3.55	-0.5	-8.8
5200	48.1	18.2	5.27	49.0	5.30	-1.8	-0.6
5250	48.0	18.3	5.34	49.0	5.36	-1.9	-0.4
5300	47.9	18.4	5.41	48.9	5.42	-2.0	-0.2
5500	47.5	18.6	5.70	48.6	5.65	-2.2	0.8
5600	47.3	18.8	5.84	48.5	5.77	-2.3	1.3
5700	47.1	18.9	5.99	48.3	5.88	-2.5	1.8
5800	47.0	19.0	6.14	48.2	6.00	-2.6	2.3

TSL Dielectric Parameters

1

Figure D-1
 750 – 5800 MHz Body Tissue Equivalent Matter

FCC ID: ZNFG850UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 08/21/19 – 09/12/19	DUT Type: Portable Handset			APPENDIX D: Page 2 of 3

Measurement Certificate / Material Test

Item Name	Head Tissue Simulating Liquid (HBBL600-10000V6)
Product No.	SL AAH U16 BC (Batch: 181031-2)
Manufacturer	SPEAG

Measurement Method

TSL dielectric parameters measured using calibrated DAK probe.

Target Parameters

Target parameters as defined in the IEEE 1528 and IEC 62209 compliance standards.

Test Condition



Ambient Condition	22°C ; 30% humidity
TSL Temperature	22°C
Test Date	31-Oct-18
Operator	CL

Additional Information

TSL Density
TSL Heat-capacity

Results

f [MHz]	Measured			Target		Diff.to Target [%]	
	e'	e''	sigma	eps	sigma	Δ-eps	Δ-sigma
800	43.8	20.5	0.91	41.7	0.90	5.1	1.4
825	43.8	20.1	0.92	41.6	0.91	5.3	1.5
835	43.8	19.9	0.93	41.5	0.91	5.4	2.0
850	43.7	19.7	0.93	41.5	0.92	5.3	1.5
900	43.5	18.9	0.95	41.5	0.97	4.8	-2.1
1400	42.5	15.0	1.17	40.6	1.18	4.7	-0.8
1450	42.5	14.8	1.19	40.5	1.20	4.9	-0.8
1600	42.2	14.3	1.27	40.3	1.28	4.7	-1.1
1625	42.2	14.2	1.29	40.3	1.30	4.8	-0.7
1640	42.2	14.2	1.30	40.3	1.31	4.8	-0.5
1650	42.1	14.2	1.30	40.2	1.31	4.6	-1.0
1700	42.1	14.0	1.33	40.2	1.34	4.8	-0.9
1750	42.0	13.9	1.36	40.1	1.37	4.8	-0.8
1800	41.9	13.9	1.39	40.0	1.40	4.7	-0.7
1810	41.9	13.8	1.40	40.0	1.40	4.7	0.0
1825	41.9	13.8	1.41	40.0	1.40	4.7	0.7
1850	41.8	13.8	1.42	40.0	1.40	4.5	1.4
1900	41.8	13.7	1.45	40.0	1.40	4.5	3.6
1950	41.7	13.7	1.48	40.0	1.40	4.3	5.7
2000	41.6	13.6	1.51	40.0	1.40	4.0	7.9
2050	41.6	13.6	1.55	39.9	1.44	4.2	7.3
2100	41.5	13.5	1.58	39.8	1.49	4.2	6.1
2150	41.4	13.5	1.62	39.7	1.53	4.2	5.7
2200	41.4	13.5	1.65	39.6	1.58	4.4	4.6
2250	41.3	13.5	1.69	39.6	1.62	4.4	4.2
2300	41.2	13.5	1.72	39.5	1.67	4.4	3.2
2350	41.1	13.5	1.76	39.4	1.71	4.4	2.9
2400	41.1	13.5	1.80	39.3	1.76	4.6	2.5
2450	41.0	13.5	1.84	39.2	1.80	4.6	2.2
2500	40.9	13.5	1.88	39.1	1.85	4.5	1.4
2550	40.8	13.5	1.92	39.1	1.91	4.4	0.6
2600	40.8	13.6	1.96	39.0	1.96	4.6	-0.2
3500	39.2	14.1	2.74	37.9	2.91	3.3	-5.8
3700	38.9	14.2	2.93	37.7	3.12	3.1	-6.1



5200	36.3	15.8	4.57	36.0	4.66	0.9	-1.7
5250	36.2	15.9	4.63	35.9	4.71	0.8	-1.6
5300	36.1	15.9	4.69	35.9	4.76	0.7	-1.4
5500	35.8	16.1	4.92	35.6	4.96	0.3	-0.9
5600	35.6	16.2	5.04	35.5	5.07	0.1	-0.6
5700	35.4	16.2	5.15	35.4	5.17	0.0	-0.3
5800	35.2	16.3	5.27	35.3	5.27	-0.2	0.0
6000	34.9	16.5	5.50	35.1	5.48	-0.6	0.5
6500	34.0	16.9	6.12	34.5	6.07	-1.4	0.9
7000	33.1	17.3	6.74	33.9	6.65	-2.3	1.3
7500	32.2	17.6	7.36	33.3	7.24	-3.2	1.6
8000	31.4	17.9	7.97	32.7	7.84	-4.1	1.7
8500	30.5	18.2	8.59	32.1	8.45	-5.0	1.6
9000	29.7	18.4	9.20	31.5	9.08	-5.9	1.3
9500	28.9	18.5	9.80	31.0	9.71	-6.8	0.9
10000	28.1	18.7	10.40	30.4	10.36	-7.6	0.4

Figure D-2
750 – 5800 MHz Head Tissue Equivalent Matter

FCC ID: ZNFG850UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 08/21/19 – 09/12/19	DUT Type: Portable Handset			APPENDIX D: Page 3 of 3

APPENDIX E: SAR SYSTEM VALIDATION

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table E-1
SAR System Validation Summary – 1g

SAR SYSTEM #	FREQ. [MHz]	DATE	PROBE SN	PROBE CAL. POINT	COND.	PERM.	CW VALIDATION			MOD. VALIDATION		
					(σ)	(ε _r)	SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
O	750	8/27/2019	7538	750	Head	0.885	41.820	PASS	PASS	PASS	N/A	N/A
O	835	8/7/2019	7538	835	Head	0.926	42.299	PASS	PASS	PASS	GMSK	PASS
H	835	6/6/2019	7406	835	Head	0.930	43.800	PASS	PASS	PASS	GMSK	PASS
H	1750	6/19/2019	7406	1750	head	1.362	39.781	PASS	PASS	PASS	N/A	N/A
O	1900	8/29/2019	7538	1900	Head	1.430	39.112	PASS	PASS	PASS	GMSK	PASS
G	1900	7/3/2019	7409	1900	Head	1.460	40.732	PASS	PASS	PASS	GMSK	PASS
H	1900	7/16/2019	7406	1900	Head	1.437	38.944	PASS	PASS	PASS	GMSK	PASS
O	2300	8/27/2019	7538	2300	Head	1.718	39.026	PASS	PASS	PASS	N/A	N/A
E	2450	8/8/2019	7547	2450	Head	1.802	37.944	PASS	PASS	PASS	OFDM/TDD	PASS
L	2450	9/5/2019	7410	2450	Head	1.850	39.320	PASS	PASS	PASS	OFDM/TDD	PASS
E	2600	8/8/2019	7547	2600	Head	1.925	37.709	PASS	PASS	PASS	TDD	PASS
L	2600	9/5/2019	7410	2600	Head	1.980	39.106	PASS	PASS	PASS	TDD	PASS
E	3500	6/13/2019	3589	3500	Head	2.781	39.174	PASS	PASS	PASS	TDD	PASS
E	3700	8/31/2019	3589	3700	Head	3.006	38.703	PASS	PASS	PASS	TDD	PASS
H	5250	6/10/2019	7406	5250	Head	4.590	36.819	PASS	PASS	PASS	OFDM	N/A
H	5600	6/10/2019	7406	5600	Head	4.978	34.167	PASS	PASS	PASS	OFDM	N/A
H	5750	6/10/2019	7406	5750	Head	5.150	33.901	PASS	PASS	PASS	OFDM	N/A
I	750	5/16/2019	7357	750	Body	0.937	56.547	PASS	PASS	PASS	N/A	N/A
H	835	7/11/2019	7406	835	Body	0.978	54.026	PASS	PASS	PASS	GMSK	PASS
J	835	3/10/2019	7488	835	Body	0.988	53.868	PASS	PASS	PASS	GMSK	PASS
G	1750	7/11/2019	7409	1750	Body	1.445	53.920	PASS	PASS	PASS	N/A	N/A
I	1750	5/21/2019	7357	1750	Body	1.442	55.384	PASS	PASS	PASS	N/A	N/A
J	1900	2/8/2019	7488	1900	Body	1.571	52.538	PASS	PASS	PASS	GMSK	PASS
I	1900	4/29/2019	7357	1900	Body	1.584	51.771	PASS	PASS	PASS	GMSK	PASS
K	2300	3/6/2019	7417	2300	Body	1.860	51.114	PASS	PASS	PASS	N/A	N/A
I	2450	5/16/2019	7357	2450	Body	2.014	53.910	PASS	PASS	PASS	OFDM/TDD	PASS
K	2450	3/6/2019	7417	2450	Body	2.039	50.670	PASS	PASS	PASS	OFDM/TDD	PASS
L	2450	8/15/2019	7410	2450	Body	2.018	52.505	PASS	PASS	PASS	OFDM/TDD	PASS
I	2600	5/15/2019	7357	2600	Body	2.162	53.620	PASS	PASS	PASS	TDD	PASS
L	2600	8/16/2019	7410	2600	Body	2.161	52.297	PASS	PASS	PASS	TDD	PASS
P	3500	9/10/2019	3589	3500	Body	3.179	51.426	PASS	PASS	PASS	TDD	PASS
P	3700	9/10/2019	3589	3700	Body	3.432	51.050	PASS	PASS	PASS	TDD	PASS
L	5250	7/31/2019	7410	5250	Body	5.165	47.068	PASS	PASS	PASS	OFDM	N/A
L	5600	7/31/2019	7410	5600	Body	5.629	46.485	PASS	PASS	PASS	OFDM	N/A
L	5750	7/31/2019	7410	5750	Body	5.842	46.222	PASS	PASS	PASS	OFDM	N/A

FCC ID: ZNFG850UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 08/21/19 – 09/12/19	DUT Type: Portable Handset			APPENDIX E: Page 1 of 2

Table E-2
SAR System Validation Summary – 10g

SAR SYSTEM #	FREQ. [MHz]	DATE	PROBE SN	PROBE CAL. POINT	COND.	PERM.	CW VALIDATION			MOD. VALIDATION		
					(σ)	(ε _r)	SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
I	1750	5/21/2019	7357	1750	Body	1.442	55.384	PASS	PASS	PASS	N/A	N/A
P	1750	9/4/2019	3288	1750	Body	1.455	54.66	PASS	PASS	PASS	N/A	N/A
I	1900	4/29/2019	7357	1900	Body	1.584	51.771	PASS	PASS	PASS	GMSK	PASS
G	1900	8/15/2019	7409	1900	Body	1.585	50.851	PASS	PASS	PASS	GMSK	PASS
L	5250	7/31/2019	7410	5250	Body	5.165	47.068	PASS	PASS	PASS	OFDM	N/A
L	5600	7/31/2019	7410	5600	Body	5.629	46.485	PASS	PASS	PASS	OFDM	N/A
L	5750	7/31/2019	7410	5750	Body	5.842	46.222	PASS	PASS	PASS	OFDM	N/A

NOTE: While the probes have been calibrated for both CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: ZNFG850UM		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 08/21/19 – 09/12/19	DUT Type: Portable Handset			APPENDIX E: Page 2 of 2

APPENDIX G POWER REDUCTION VERIFICATION

Per the May 2017 TCBC Workshop Notes, demonstration of proper functioning of the power reduction mechanisms is required to support the corresponding SAR configurations. The verification process was divided into two parts: (1) evaluation of output power levels for individual or multiple triggering mechanisms and (2) evaluation of the triggering distances for proximity-based sensors.

G.1 Power Verification Procedure

The power verification was performed according to the following procedure:

1. A base station simulator was used to establish a conducted RF connection and the output power was monitored. The power measurements were confirmed to be within expected tolerances for all states before and after a power reduction mechanism was triggered.
2. Step 1 was repeated for all relevant modes and frequency bands for the mechanism being investigated.
3. Steps 1 and 2 were repeated for all individual power reduction mechanisms and combinations thereof. For the combination cases, one mechanism was switched to a 'triggered' state at a time; powers were confirmed to be within tolerances after each additional mechanism was activated.

G.2 Distance Verification Procedure

The distance verification procedure was performed according to the following procedure:

1. A base station simulator was used to establish an RF connection and to monitor the power levels. The device being tested was placed below the relevant section of the phantom with the relevant side or edge of the device facing toward the phantom.
2. The device was moved toward and away from the phantom to determine the distance at which the mechanism triggers and the output power is reduced, per KDB Publication 616217 D04v01r02 and FCC Guidance. Each applicable test position was evaluated. The distances were confirmed to be the same or larger (more conservative) than the minimum distances provided by the manufacturer.
3. Steps 1 and 2 were repeated for low, mid, and high bands, as appropriate (see note below Table G-2 for more details).
4. Steps 1 through 3 were repeated for all distance-based power reduction mechanisms.

FCC ID: ZNFG850UM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/19 – 09/12/19	DUT Type: Portable Handset			APPENDIX G: Page 1 of 3

G.3 Main Antenna Verification Summary

Table G-1
Power Measurement Verification for Main Antenna

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
1st		Un-triggered (Max)	Mechanism #1 (Reduced)
Grip	UMTS 1750	24.89	22.47
Grip	UMTS 1900	24.02	22.42
Grip	PCS CDMA	23.85	22.42
Grip	LTE FDD Band 66	25.00	22.23
Grip	LTE FDD Band 4	24.95	22.16
Grip	LTE FDD Band 25	24.11	22.14
Grip	LTE FDD Band 2	24.15	22.18

Table G-2
Distance Measurement Verification for Main Antenna

Mechanism(s)	Test Condition	Band	Distance Measurements (mm)		Minimum Distance per Manufacturer (mm)
			Moving Toward	Moving Away	
Grip	Phablet - Back Side	Mid	2	4	2
Grip	Phablet - Front Side	Mid	2	3	2
Grip	Phablet - Bottom Edge	Mid	4	5	4

*Note: Mid band refers to: CDMA BC1, UMTS B2/4, LTE B2/4/25/66

FCC ID: ZNFG850UM	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Test Dates: 08/21/19 – 09/12/19	DUT Type: Portable Handset	APPENDIX G: Page 2 of 3

G.4 WIFI Verification Summary

Table G-3
Power Measurement Verification WIFI – Antenna 1

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
1st		Un-triggered (Max)	Mechanism #1 (Reduced)
Held-to-Ear	802.11b	19.55	17.44
Held-to-Ear	802.11g	17.61	16.36
Held-to-Ear	802.11n (2.4GHz)	16.25	15.68
Held-to-Ear	802.11a	19.35	15.96
Held-to-Ear	802.11n (5GHz, 20MHz BW)	19.47	15.84
Held-to-Ear	802.11ac (20MHz BW)	19.15	15.97

*Note: 802.11ac 2.4 GHz and MIMO WIFI modes were not evaluated due to equipment limitations.

Table G-4
Power Measurement Verification WIFI – Antenna 2

Mechanism(s)	Mode/Band	Conducted Power (dBm)	
1st		Un-triggered (Max)	Mechanism #1 (Reduced)
Held-to-Ear	802.11b	19.63	17.08
Held-to-Ear	802.11g	19.43	17.44
Held-to-Ear	802.11n (2.4GHz)	18.50	17.41
Held-to-Ear	802.11a	19.58	15.99
Held-to-Ear	802.11n (5GHz, 20MHz BW)	19.44	15.94
Held-to-Ear	802.11ac (20MHz BW)	19.51	15.89

*Note: 802.11ac 2.4 GHz and MIMO WIFI modes were not evaluated due to equipment limitations.

FCC ID: ZNFG850UM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/19 – 09/12/19	DUT Type: Portable Handset			APPENDIX G: Page 3 of 3

APPENDIX H: DOWNLINK LTE CA RF CONDUCTED POWERS

1.1 LTE Downlink Only Carrier Aggregation Test Reduction Methodology

SAR test exclusion for LTE downlink Carrier Aggregation is determined by power measurements according to the number of component carriers (CCs) supported by the product implementation. Per April 2018 TCBC Workshop Notes, the following test reduction methodology was applied to determine the combinations required for conducted power measurements.

LTE DLCA Test Reduction Methodology:

- The supported combinations were arranged by the number of component carriers in columns.
- Any limitations on the PCC or SCC for each combination were identified alongside the combination (e.g. CA_2A-2A-4A-12A, but B12 can only be configured as a SCC).
- Power measurements were performed for "supersets" (LTE CA combinations with multiple components carriers) and any "subsets" (LTE CA combinations with fewer component carriers) that were not completely covered by the supersets.
- Only subsets that have the exact same components as a superset were excluded for measurement.
- When there were certain restrictions on component carriers that existed in the superset that were not applied for the subset, the subset configuration was additionally evaluated.
- Both inter-band and intra-band downlink carrier aggregation scenarios were considered.
- Downlink CA combinations for SISO and 4x4 Downlink MIMO operations were measured independently, per May 2017 TCBC Workshop notes.

Table 1 – Example of Exclusion Table for SISO Configurations

[illegible]

Table 2 – Example of Exclusion Table for 4x4 Downlink MIMO Configurations

Table 1: 5.8 GHz Channel Allocation					Table 2: 5.8 GHz Channel Allocation					Table 3: 5.8 GHz Channel Allocation										
Index	ACC	Supported Channel Bandwidth [MHz]		Restriction	Completely Covered by Measurement SuperSet	Index	ACC	Supported Channel Bandwidth [MHz]			Restriction	Completely Covered by Measurement SuperSet	Index	ACC	Supported Channel Bandwidth [MHz]				Restriction	Completely Covered by Measurement SuperSet
		C11	C12					C11	C12	C13					C11	C12	C3	C4		
ACC #M1	CA [2C]	5, 10, 15, 20	5, 10, 15, 20		ACC #M6	ACC #M1	CA [2A] 5B-66A	5, 10, 15, 20	5, 10	5, 10, 15, 20	No	ACC #M1	CA [2A] 5B-66A	5, 10, 15, 20	5, 10	5, 10	5, 10, 15, 20		No	
ACC #M2	CA [2A] 2A	5, 10, 15, 20	5, 10, 15, 20		ACC #M1	ACC #M2	CA [2A] 5A	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M2	CA 2A-5B (66A)	5, 10, 15, 20	5, 10	5, 10	5, 10, 15, 20		No		
ACC #M3	CA [2A] 12A	5, 10, 15, 20	5, 10, 15, 20	No	ACC #M3	ACC #M3	CA [2A] 5A-12A	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M3	CA [2A] 5A-66B	5, 10, 15, 20	5, 10	5, 10, 15	5, 10, 15		No		
ACC #M4	CA [2A] 4A (2)	5, 10, 15, 20	5, 10, 15, 20	ACC #M1	ACC #M4	ACC #M4	CA [2A] 2A-13A	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M4	CA 2A-5A (66B)	5, 10, 15, 20	5, 10	5, 10, 15	5, 10, 15		No		
ACC #M5	CA [2A] 4A [2]	5, 10, 15, 20	5, 10, 15, 20	No	ACC #M5	ACC #M5	CA [2A] 30A	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M5	CA [2A] 5A-66C	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M6	CA [2A] 5A	5, 10, 15, 20	5, 10	ACC #M3	ACC #M6	CA [2C] 66A	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M6	CA 2A-5A (66C)	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M7	CA [2A] 2A (1)	5, 10, 15, 20	5, 10	ACC #M4	ACC #M7	ACC (66B)	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M7	ACC (66B)	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M8	CA [2A] 13A	5, 10, 15, 20	5, 10	ACC #M4	ACC #M8	CA [2C] (66A)	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M8	CA [2A] 5A-66D	5, 10, 15, 20	5, 10	5, 10, 15	5, 10, 15		No		
ACC #M9	CA [2A] 17A	5, 10	5, 10	No	ACC #M9	CA [2A] 2A-66A	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M9	CA [2A] 5A-66E	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M10	CA [2A] 29A (2)	5, 10, 15, 20	5, 10	B29 SEC Only	ACC #M10	CA 2A-26A (66A)	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M10	CA [2A] 5A-66F	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M11	CA [2A] 12A (2)	5, 10, 15, 20	5, 10	No	ACC #M11	CA [2A] 21A	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M11	CA [2A] 5A-66G	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M12	CA [2A] 66A (2)	5, 10, 15, 20	5, 10, 15, 20	ACC #M1	ACC #M12	CA [2A] 4A-29A	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10	B29 SEC Only	ACC #M12	CA [2A] 5A-66H	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No	
ACC #M13	CA 2A (66A) (2)	5, 10, 15, 20	5, 10, 15, 20	ACC #M2	ACC #M13	CA [2A] 4A-71A	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10	ACC #M13	CA [2A] 5A-66I	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M14	CA [2A] (66A) (2)	5, 10, 15, 20	5, 10, 15, 20	No	ACC #M14	CA [2A] 5B	5, 10, 15, 20	5, 10	5, 10	5, 10	ACC #M14	ACC #M14	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M15	CA [2A] 71A	5, 10, 15, 20	5, 10, 15, 20	ACC #M1	ACC #M15	CA [2A] 5A-66A	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10	ACC #M15	CA [2A] 5A-66J	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M16	CA 5A (66A)	5, 10	5, 10, 15, 20	ACC #M16	ACC #M16	CA 2A-5A (66A)	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10	ACC #M16	CA [2A] 5A-66K	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M17	CA [2A] (66A) (4)	5, 10	5, 10, 15, 20	No	ACC #M17	CA 2A-12A (66A)	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10	ACC #M17	CA [2A] 5A-66L	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M18	CA [2A] (66A)	5, 10	5, 10, 15, 20	No	ACC #M18	CA [2A] 13A-66A	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10	ACC #M18	CA [2A] 5A-66M	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M19	CA 2A (66A)	5, 10, 15, 20	5, 10, 15, 20	ACC #M20	ACC #M19	CA 2A-13A (66A)	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10	ACC #M19	CA [2A] 5A-66N	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M20	CA (66B)	5, 10, 15	5, 10, 15	ACC #M4	ACC #M20	CA 2A-30A (66A)	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10	ACC #M20	CA [2A] 5A-66O	5, 10, 15, 20	5, 10	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M21	CA (66C)	5, 10, 15, 20	5, 10, 15, 20	ACC #M6	ACC #M21	CA [2A] 66B	5, 10, 15, 20	5, 10, 15	5, 10, 15	5, 10, 15	ACC #M21	ACC #M21	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M22	CA (66A) (66A)	5, 10, 15, 20	5, 10, 15, 20	ACC #M20	ACC #M22	CA 2A (66B)	5, 10, 15, 20	5, 10, 15	5, 10, 15	5, 10, 15	ACC #M22	CA 2A (66B)	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20		No		
ACC #M23	CA (66A) (66A)	5, 10, 15, 20	5, 10, 15, 20	No	ACC #M23	CA [2A] (66B)	5, 10, 15, 20	5, 10, 15	5, 10, 15	5, 10, 15	ACC #M23	CA [2A] (66B)	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20	5, 10, 15, 20		No		

Note: [CC] indicates component carrier with 4x4 DL MIMO antenna configuration

FCC ID: ZNFG850UM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 LG	Reviewed by: Quality Manager
Test Dates: 08/21/19 - 09/12/19	DUT Type: Portable Handset	APPENDIX H: Page 1 of 13		

1.2 LTE Downlink Only Carrier Aggregation Test Selection and Setup

SAR test exclusion for LTE downlink Carrier Aggregation is determined by power measurements according to the number component carriers (CCs) supported by the product implementation. For those configurations required by April 2018 TCBC Workshop Notes, conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.

This device supports LAA with downlink carrier aggregation only. It uses carrier aggregation in the downlink to combine LTE in the unlicensed spectrum (i.e. LTE Band 46) with LTE in the licensed band (served as PCC). All uplink communications and acknowledgements on the PCC remain identical to specifications when downlink carrier aggregation is inactive.

Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the maximum average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive. All bands required for SAR testing per FCC KDB procedures were considered. Based on the measured maximum powers below, no additional SAR tests were required for DLCA SAR configurations.

General PCC and SCC configuration selection procedure

- PCC uplink channel, channel bandwidth, modulation and RB configurations were selected based on section C)3)b)iii) of KDB 941225 D05 V01r02. The downlink PCC channel was paired with the selected PCC uplink channel according to normal configurations without carrier aggregation.
- To maximize aggregated bandwidth, highest channel bandwidth available for that CA combination was selected for SCC. For inter-band CA, the SCC downlink channels were selected near the middle of their transmission bands. For contiguous intra-band CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing defined in section 5.4.1A of 3GPP TS 36.521. For non-contiguous intra-band CA, the downlink channel spacing between the component carriers was set to be larger than the nominal channel spacing and provided maximum separation between the component carriers.
- All selected PCC and SCC(s) remained fully within the uplink/downlink transmission band of the respective component carrier.




Figure 1
DL CA Power Measurement Setup

FCC ID: ZNFG850UM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/19 - 09/12/19	DUT Type: Portable Handset			APPENDIX H: Page 2 of 13




Figure 2
DL CA with DL 4x4 MIMO Power Measurement Setup

1.3 Downlink Carrier Aggregation RF Conducted Powers

1.3.1 LTE Band 71 as PCC

Table 1
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC				SCC 1				SCC 2				SCC 3				Power				
			PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)	
CA 2A-4A-71A	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	LTE B2	20	900	1980	LTE B4	20	2175	2132.5	-	-	-	-	25.30	25.43
CA 4A-4A-71A	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	-	-	-	-	25.32	25.43
CA 2A-2A-66A-71A	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	LTE B2	20	900	1980	LTE B2	20	700	1940	LTE B66	20	66786	2145	25.22	25.43
CA 2A-66A-66A-71A	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	LTE B2	20	900	1980	LTE B66	20	66786	2145	LTE B66	20	67236	2190	25.24	25.43
CA 2A-66C-71A	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	LTE B2	20	900	1980	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	25.26	25.43

1.3.2 LTE Band 12 as PCC

Table 2
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC 1			SCC 2			SCC 3			SCC 4			Power	
										SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 12A-25A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B25	20	8365	1902.5	-	-	-	-	-	-	-	-	25.18	25.38
CA 12A-66A (1)	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	25.15	25.38
CA 12A-66A (2)	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	25.15	25.38
CA 2A-12A (1)	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	-	-	-	-	-	-	-	-	25.09	25.38
CA 4A-12A (1)	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B4	20	2175	2132.5	-	-	-	-	-	-	-	-	25.23	25.38
CA 4A-12A (2)	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B4	20	2175	2132.5	-	-	-	-	-	-	-	-	25.23	25.38
CA 4A-12A-12B	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	-	-	-	-	25.18	25.38
CA 2A-12A-66C	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	25.22	25.38
CA 2A-2A-4A-12A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	LTE B2	20	700	1940	LTE B4	20	2175	2132.5	25.24	25.38
CA 2A-4A-12A-30A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	LTE B4	20	2175	2132.5	LTE B30	10	4650	2355	25.21	25.38
CA 2A-4A-12B	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B12	5	5107	738.7	LTE B4	20	900	1980	LTE B4	20	2175	2132.5	25.22	25.38
CA 2A-4A-7A-12A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	LTE B4	20	2175	2132.5	LTE B7	20	3100	2605	25.24	25.38
CA 4A-6A-12B	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B12	5	5107	738.7	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	25.20	25.38
CA 12B-66A-66A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B12	5	5107	738.7	LTE B66	20	66786	2145	LTE B66	20	67236	2190	25.24	25.38
CA 2A-12A-30A-66A-66A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	LTE B30	10	4650	2355	LTE B66	20	66786	2145	25.25	25.38
CA 2A-2A-12A-30A-66A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	LTE B2	20	700	1940	LTE B30	10	4650	2355	25.24	25.38
CA 2A-2A-12A-66A-66A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	LTE B2	20	700	1940	LTE B66	20	66786	2145	25.26	25.38
CA 2A-2A-12B-66A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B12	5	5107	738.7	LTE B2	20	900	1980	LTE B2	20	700	1940	25.30	25.38
CA 2A-2A-7A-12A-66A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1980	LTE B2	20	700	1940	LTE B66	20	66786	2145	25.21	25.38
CA 2A-7A-12B-66A	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B12	5	5107	738.7	LTE B2	20	900	1980	LTE B7	20	3100	2605	25.24	25.38

FCC ID: ZNFG850UM		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/19 - 09/12/19	DUT Type: Portable Handset			APPENDIX H: Page 3 of 13

1.3.3 LTE Band 13 as PCC

Table 3
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC 1				SCC 2				SCC 3				SCC 4				Power	
										SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 13A-46A-66A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B46	20	60065	5537.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	23.15	23.08
CA 2A-13A-46A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	-	-	-	-	-	-	-	-	23.19	23.08
CA 2A-13A-13A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B4	20	2175	2132.5	-	-	-	-	-	-	-	-	23.14	23.08
CA 4A-4A-13A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B4	20	2175	2132.5	LTE B4	10	2380	2150	-	-	-	-	-	-	-	-	23.16	23.08
CA 2A-13A-46C	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	-	-	-	-	23.22	23.08
CA 2A-13A-66C	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	66786	2145	LTE B66	20	66984	2164.9	-	-	-	-	23.26	23.08
CA 13A-46C-66A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B66	20	60065	5537.5	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	-	-	-	-	23.26	23.08
CA 13A-46A-66B	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B46	20	60065	5537.5	LTE B66	15	66786	2145	LTE B66	5	66984	2164.9	-	-	-	-	23.20	23.08
CA 13A-46A-66C	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B46	20	60065	5537.5	LTE B66	20	66786	2145	LTE B66	20	66984	2164.9	-	-	-	-	23.24	23.08
CA 2A-13A-46A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.15	23.08
CA 2A-13A-46A-66A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.19	23.08
CA 2A-13A-46A-66B	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.21	23.08
CA 2A-13A-46A-66C	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.23	23.08
CA 2A-13A-46A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.25	23.08
CA 2A-13A-46A-66B	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B66	15	67261	2162.5	23.25	23.08
CA 2A-13A-46A-66A-66B	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B66	20	67261	2162.5	23.27	23.08
CA 13A-46A-46C-66A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B46	20	50095	5537.5	LTE B62	20	700	1940	LTE B66	20	66786	2145	LTE B66	20	67261	2162.5	23.28	23.08
CA 13A-46A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B66	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.28	23.08
CA 13A-46A-46C	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B66	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.28	23.08
CA 13A-46A-46C-66A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B66	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.28	23.08
CA 13A-46A-46C	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B66	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.28	23.08
CA 13A-46A-46C-66A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B66	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.28	23.08
CA 13A-46A-46C	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B66	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.28	23.08
CA 13A-46A-46C-66A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B66	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.28	23.08
CA 13A-46A	LTE B13	10	23230	762	QPSK	1	25	6230	761	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	23.28	23.08

1.3.4 LTE Band 14 as PCC

Table 4
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC 1				SCC 2				SCC 3				SCC 4				Power	
										SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 2A-14A-30A-66A-66A	LTE B14	5	23330	793	QPSK	1	12	6330	763	LTE B62	20	900	1960	LTE B30	10	9820	2355	LTE B66	20	66786	2145	LTE B66	20	67236	2190	23.31	23.28
CA 5A-66A (1)	LTE B14	5	23330	793	QPSK	1	12	6330	763	LTE B62	20	900	1960	LTE B66	20	66536	2120	LTE B66	20	66786	2145	LTE B66	20	67236	2190	23.31	23.28
CA 2A-2A-14A-30A-66A	LTE B14	5	23330	793	QPSK	1	12	6330	763	LTE B62	20	900	1960	LTE B62	20	700	1940	LTE B30	10	9820	2355	LTE B66	20	66786	2145	23.34	23.33
CA 2A-2A-14A-66A-66A	LTE B14	5	23330	793	QPSK	1	12	6330	763	LTE B62	20	900	1960	LTE B62	20	700	1940	LTE B66	20	66786	2145	LTE B66	20	67236	2190	23.34	23.33

1.3.5 LTE Band 5 as PCC

Table 5
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC					SCC 1				SCC 2				SCC 3				SCC 4				Power			
			CC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	LTE Tx Power with CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)	
CA 5A-25A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B25	20	8165	1942.5	-	-	-	-	-	-	-	-	-	-	-	-	23.22	23.20
CA 5A-41A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B41	20	40620	2593	-	-	-	-	-	-	-	-	-	-	-	-	23.22	23.20
CA 5A-66A (1)	LTE B5	5	20625	846.5	QPSK	1	14	2525	891.5	LTE B46	20	50665	5537.5	-	-	-	-	-	-	-	-	-	-	-	-	23.24	23.28
CA 5A-6A (1)	LTE B5	5	20625	846.5	QPSK	1	14	2525	891.5	LTE B6	5	2625	891.5	-	-	-	-	-	-	-	-	-	-	-	-	23.24	23.28
CA 5A-7A	LTE B5	1.4	20625	846.5	QPSK	3	2	2525	891.5	LTE B7	20	3100	2655	-	-	-	-	-	-	-	-	-	-	-	-	23.30	23.31
CA 2A-5A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	-	-	-	-	-	-	-	-	23.03	23.20
CA 5A-6A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	23.04	23.20
CA 5A-46C (1)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	-	-	-	-	-	-	-	-	23.23	23.20
CA 5A-46A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B66	20	66786	2145	-	-	-	-	-	-	-	-	23.03	23.20
CA 5A-46C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	-	-	-	-	-	-	-	-	23.24	23.20
CA 5A-7A-7A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B7	20	3100	2655	LTE B7	20	2650	2630	-	-	-	-	-	-	-	-	23.25	23.20
CA 5A-7C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B7	20	3100	2655	LTE B7	20	2650	2630	-	-	-	-	-	-	-	-	23.25	23.20
CA 5B-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	10	2563	884.3	LTE B46	20	50095	5537.5	-	-	-	-	-	-	-	-	23.26	23.20
CA 2A-2A-5A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B62	20	700	1940	LTE B4	20	2175	2132.5	-	-	-	-	23.03	23.20
CA 2A-2A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B62	20	700	1940	LTE B4	20	2175	2132.5	-	-	-	-	23.03	23.20
CA 2A-4A-5A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	-	-	-	-	23.03	23.20
CA 2A-4A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B4	20	2175	2132.5	LTE B30	10	9620	2305	-	-	-	-	23.03	23.20
CA 2A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B4	20	2175	2132.5	LTE B4	10	9620	2305	-	-	-	-	23.03	23.20
CA 2A-5A-46C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	-	-	-	-	23.03	23.20
CA 4A-5A-38	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	10	2563	884.3	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	-	-	-	-	23.08	23.20
CA 5A-6C-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B66	20	66786	2145	-	-	-	-	23.08	23.20
CA 5A-6D (1)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50095	5537.5	-	-	-	-	23.23	23.20
CA 5A-6B	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50095	5537.5	-	-	-	-	23.23	23.20
CA 5A-6A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	10	2425	871.5	LTE B66	20	66786	2145	LTE B66	20	66786	2145	-	-	-	-	23.07	23.20
CA 5A-5A-66B	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	5	2425	871.5	LTE B66	15	66786	2145	LTE B66	5	66970	2154.3	-	-	-	-	23.08	23.20
CA 5A-5A-6C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	5	2425	871.5	LTE B66	15	66786	2145	LTE B66	20	66984	2164.8	-	-	-	-	23.04	23.20
CA 5A-6C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	5	2425	871.5	LTE B46	15	66786	2145	LTE B46	20	66984	2164.8	-	-	-	-	23.04	23.20
CA 2A-2A-5A-3A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B62	20	700	1940	LTE B30	10	9620	2355	LTE B66	20	66786	2145	23.06	23.20
CA 2A-2A-5A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B62	20	700	1940	LTE B66	20	66786	2145	LTE B66	20	66786	2145	23.07	23.20
CA 2A-5A-5A-66B	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B62	20	700	1940	LTE B66	15	66786	2145	LTE B66	5	66879	2154.3	23.07	23.20
CA 2A-5A-6C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B62	20	700	1940	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	23.08	23.20
CA 2A-5A-3A-66A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B30	10	9620	2355	LTE B66	20	66786	2145	LTE B66	20	66786	2145	23.04	23.20
CA 2A-5A-46C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B62	20	900	1960	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50095	5537.5	23.02	23.20
CA 3B-5B-66A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	10	2563	884.3	LTE B62	20	700	1940	LTE B30	10	9620	2355	LTE B66	20	66786	2145	23.06	23.20
CA 3B-66A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	10	2553	884.3	LTE B62	20	900	1960	LTE B66	20	66786	2145	LTE B66	20	66786	2145	23.06	23.20
CA 2A-5B-66B	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	10	2553	884.3	LTE B62	20	900	1960	LTE B66	15	66786	2145	LTE B66	5	66879	2154.3	23.06	23.20
CA 2A-6A-6C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B62	20	700	1940	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	23.07	23.20
CA 5A-6D-56A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50095	5537.5	LTE B46	20	50095	5537.5	23.18	23.20
CA 5A-46C (1)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50095	5537.5	LTE B46	20	50095	5537.5	23.18	23.20
CA 5B-2B-66A-66A	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	10	2553	884.3	LTE B62	20	700	1940	LTE B66	20	66786	2145	LTE B66	20	66786	2145	23.06	23.20
CA 5B-66C	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	LTE B5	10	2553	884.3	LTE B46	20	50095	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50095	5537.5	23.14	23.20

1.3.6 LTE Band 26 as PCC

Table 6
Maximum Output Powers

	PCC								SCC 1			SCC 2				Power			
Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx Power with DL CA Enabled [dBm]	LTE Single Carrier Tx Power [dBm]
CA 25A-26A	LTE B26	10	26990	844	QPSK	1	0	8990	889	LTE B25	20	8365	1962.5	-	-	-	-	24.75	25.18
LTE B26	10	26990	844	QPSK	1	0	8990	889	LTE B41	20	40620	2593	-	-	-	-	25.14	25.18	
CA 25A-25A-26A	LTE B26	3	26865	831.5	QPSK	1	14	8865	876.5	LTE B25	20	8365	1962.5	LTE B25	20	8590	1985	25.14	25.17
LTE B26	10	26990	844	QPSK	1	0	8990	889	LTE B41	20	40620	2593	LTE B41	20	40422	2573.2	25.21	25.18	

1.3.7 LTE Band 66 as PCC

Table 7
Maximum Output Powers

[illegible]

FCC ID: ZNFG850UM	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Test Dates: 08/21/19 - 09/12/19	DUT Type: Portable Handset	APPENDIX H: Page 5 of 13

1.3.8 LTE Band 25 as PCC

Table 8
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC				SCC 1				SCC 2				SCC 3				Power					
				PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)		
CA 12A-25A	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B12	10	5095	737.5	-	-	-	-	-	-	-	-	-	24.17	24.20	
CA 25A-26A	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B26	15	8865	876.5	-	-	-	-	-	-	-	-	-	24.19	24.20	
CA 25A-41A	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B41	20	40620	2593	-	-	-	-	-	-	-	-	-	24.12	24.20	
CA 25A-46A	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B46	20	50665	5537.5	-	-	-	-	-	-	-	-	-	24.19	24.20	
CA 6A-25A	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B5	10	2525	881.5	-	-	-	-	-	-	-	-	-	24.17	24.20	
CA 25A-25A-26A	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B25	20	8140	1940	LTE B26	5	8865	876.5	-	-	-	-	-	-	24.13	24.20
CA 25A-41C	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B41	20	40620	2593	LTE B41	20	40422	2573.2	-	-	-	-	-	-	24.15	24.20
CA 25A-46C	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	-	-	-	-	-	-	24.15	24.20
CA 25A-41D	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B41	20	40422	2573.2	LTE B41	20	40620	2593	LTE B41	20	40818	2612.8	24.19	24.20		
CA 25A-46D	LTE B25	20	26365	1882.5	QPSK	1	0	8365	1962.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50863	5557.3	24.18	24.20		

1.3.9 LTE Band 30 as PCC

Table 9
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch	PCC					SCC 1			SCC 2			SCC 3			SCC 4			Power				
				PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	LTE Tx Power with CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 2A-30A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	800	1960	LTE B66	20	68786	2145	-	-	-	-	-	-	23.26	23.38
CA 2A-25A-30A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B25	10	9715	722.5	LTE B66	20	68786	2145	-	23.26	23.38	
CA 2A-25A-30A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B25	10	9715	722.5	-	23.26	23.38	
CA 2A-4A-12A-30A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B12	10	8095	737.5	-	23.28	23.38	
CA 2A-4A-25A-30A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B25	10	9715	722.5	-	23.28	23.38	
CA 2A-4A-30A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B5	10	8025	881.5	-	23.34	23.38	
CA 25A-30A-66A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B25	10	9715	722.5	LTE B66	20	68786	2145	LTE B66	20	67736	2190	-	23.30	23.38	
CA 2A-12A-30A-66A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B12	10	8095	737.5	LTE B66	20	68786	2145	-	23.26	23.38	
CA 2A-12A-30A-66A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B12	10	8095	737.5	LTE B66	20	68786	2145	-	23.26	23.38	
CA 2A-25A-12A-30A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B12	10	8095	737.5	-	23.33	23.38	
CA 2A-25A-12A-30A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B14	10	1330	76	-	23.31	23.38	
CA 2A-30A-30A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B2	20	700	1940	LTE B5	10	8025	881.5	-	23.34	23.38	
CA 2A-30A-30A-66A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B2	20	900	1960	LTE B5	10	8025	881.5	LTE B66	20	68786	2145	-	23.31	23.38	
CA 2A-30A-66A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B5	10	2525	881.5	LTE B5	10	2525	881.5	LTE B66	20	68786	2145	-	23.30	23.38	
CA 30A-30A-66A-66A	LTE B30	5	27710	2310	QPSK	1	12	9820	2355	LTE B5	10	2525	881.5	LTE B5	10	2525	881.5	LTE B66	20	68786	2145	-	23.30	23.38	

1.3.10 LTE Band 7 as PCC

Table 10
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC [DL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC 1			SCC 2			SCC 3			SCC 4			Power		
										SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel
CA 5A-7A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B5	10	2525	881.5	-	-	-	-	-	-	-	-	-	23.05	23.70
CA 7A-66A (1)	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B46	20	50665	5537.5	-	-	-	-	-	-	-	-	-	23.03	23.70
CA 7B	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	5	2918	2636.8	-	-	-	-	-	-	-	-	-	23.03	23.70
CA 4A-4A-7A (1)	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B4	20	2175	2132.5	LTE B4	10	2350	2150	-	-	-	-	-	23.07	23.70
CA 5A-7A-7A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	3350	2650	LTE B5	10	2525	881.5	-	-	-	-	-	23.70	23.70
CA 5A-7C	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	2996	2644.6	LTE B5	10	2525	881.5	-	-	-	-	-	23.66	23.70
CA 7A-46C (1)	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	-	-	-	-	-	23.03	23.70
CA 7A-66A-66A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B66	20	68786	2145	LTE B66	20	67736	2190	-	-	-	-	-	23.63	23.70
CA 7A-7A-66A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	3350	2650	LTE B46	20	50665	5537.5	-	-	-	-	-	23.07	23.70
CA 2A-4A-7A-12A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B2	20	800	1960	LTE B4	20	2175	2132.5	LTE B12	10	8095	737.5	-	23.64	23.70
CA 2A-4A-7A-7A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	3350	2650	LTE B2	20	800	1960	LTE B4	20	2175	2132.5	-	23.69	23.70
CA 2A-4A-7C	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	2996	2644.6	LTE B2	20	800	1960	LTE B4	20	2175	2132.5	-	23.69	23.70
CA 7A-46C (1)	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50863	5557.3	-	23.07	23.70
CA 7A-7A-46C	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	3350	2650	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	-	23.07	23.70
CA 7C-46C	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	2996	2644.6	LTE B46	20	50467	5517.7	LTE B46	20	50467	5517.7	-	23.66	23.70
CA 7C-66A-66A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	2996	2644.6	LTE B66	20	68786	2145	LTE B66	20	67736	2190	-	23.67	23.70
CA 2A-3A-7A-12A-66A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B2	20	800	1960	LTE B2	20	700	1940	LTE B12	10	8095	737.5	-	23.69	23.70
CA 2A-7A-12A-66A	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B2	20	800	1960	LTE B2	20	700	1940	LTE B12	10	8095	737.5	-	23.70	23.70
CA 7A-46E	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	LTE B46	20	50863	5557.3	-	23.07	23.70
CA 7C-46D	LTE B7	15	20825	2507.5	QPSK	1	74	2825	2627.5	LTE B7	20	2996	2644.6	LTE B46	20	50665	5537.5	LTE B46	20	50467	5517.7	-	23.66	23.70

1.3.11 LTE Band 48 as PCC

Table 11
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC				SCC 1				SCC 2				SCC 3				SCC 4				Power			
				PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	LTE Tx Power with CA Enabled [dBm]	LTE Single Carrier Tx Power [dBm]
CA 4B+4B	LTE B48	20	56207	3646.7	QPSK	1	99	56207	3646.7	LTE B48	20	55340	3560	-	-	-	-	-	-	-	-	-	-	-	-	24.20	24.20
CA 4B	LTE B48	20	56207	3646.7	QPSK	1	99	56207	3646.7	LTE B48	20	55009	3620.9	LTE B48	20	55011	3607.1	LTE B48	20	55013	3597.3	-	-	-	-	24.08	24.20
CA 4B+4B	LTE B48	20	56207	3646.7	QPSK	1	99	56207	3646.7	LTE B48	20	55340	3560	LTE B48	20	55340	3560	LTE B48	20	55338	3579.8	LTE B48	20	55376	3599.6	24.19	24.20
CA 4B+4B	LTE B48	20	56207	3646.7	QPSK	1	99	56207	3646.7	LTE B48	20	55009	3626.9	LTE B48	20	55011	3602.1	LTE B48	20	55040	3590	LTE B48	20	56442	3670.2	24.20	24.20

1.3.12 LTE Band 41 PC3 as PCC

Table 12
Maximum Output Powers

Combination	PCC Band	PCC								SCC 1				SCC 2				SCC 3				SCC 4				Power		
		PCC BW [MHz]	PCC [UL] Ch.	PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	LTE Tx Power with DL CA Enabled [dBm]	LTE Single Carrier Tx Power [dBm]	
CA_41A-41A(1)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	39750	2506	-	-	-	-	-	-	-	-	-	-	-	-	25.17	25.16	
CA_41A-41C	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	39948	2525.8	LTE B41	20	39750	2506	-	-	-	-	-	-	-	-	25.20	25.16	
CA_41C-41A	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41319	2662.9	LTE B41	20	39750	2506	-	-	-	-	-	-	-	-	25.20	25.16	
CA_41A-41D	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	40146	2545.6	LTE B41	20	39948	2525.8	LTE B41	20	39750	2506	-	-	-	-	-	25.09	25.16
CA_41D-41A	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41319	2662.9	LTE B41	20	41121	2643.1	LTE B41	20	39750	2506	-	-	-	-	-	25.10	25.16
CA_41C-41C	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41319	2662.9	LTE B41	20	39948	2525.8	LTE B41	20	39750	2506	-	-	-	-	-	25.18	25.16
CA_41E	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41319	2662.9	LTE B41	20	41121	2643.1	LTE B41	20	40923	2623.3	-	-	-	-	-	25.13	25.16
CA_41C-41D	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41319	2662.9	LTE B41	20	40146	2545.6	LTE B41	20	39948	2525.8	LTE B41	20	39750	2506	25.11	25.16	
CA_41D-41C	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	LTE B41	20	41319	2662.9	LTE B41	20	41121	2643.1	LTE B41	20	39948	2525.8	LTE B41	20	39750	2506	25.15	25.16	

1.3.13 LTE Band 41 PC2 as PCC

Table 13
Maximum Output Powers

Combination	PCC								SCC 1				SCC 2				SCC 3				SCC 4				Power			
	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Channel	PCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Channel	SCC [DL] Freq. [MHz]	LTE Tx Power with CA Enabled [dBm]	LTE Single Carrier Tx Power [dBm]	
CA_41A-41A(1)	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	39750	2506	-	-	-	-	-	-	-	-	-	-	-	-	-	27.63	27.70
CA_41A-41C	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	39948	2525.8	LTE B41 PC2	20	39750	2506	-	-	-	-	-	-	-	-	-	27.64	27.70
CA_41C-41A	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	41292	2660.2	LTE B41 PC2	20	39750	2506	-	-	-	-	-	-	-	-	-	27.63	27.70
CA_41A-41D	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	40146	2545.6	LTE B41 PC2	20	39948	2525.8	LTE B41 PC2	20	39750	2506	-	-	-	-	-	27.59	27.70
CA_41D-41A	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	41292	2660.2	LTE B41 PC2	20	41094	2640.4	LTE B41 PC2	20	39750	2506	-	-	-	-	-	27.61	27.70
CA_41C-41C	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	41292	2660.2	LTE B41 PC2	20	39948	2525.8	LTE B41 PC2	20	39750	2506	-	-	-	-	-	27.62	27.70
CA_41E	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	41292	2660.2	LTE B41 PC2	20	41094	2640.4	LTE B41 PC2	20	40996	2620.6	-	-	-	-	-	27.58	27.70
CA_41C-41D	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	41292	2660.2	LTE B41 PC2	20	40146	2545.6	LTE B41 PC2	20	39948	2525.8	LTE B41 PC2	20	39750	2506	27.63	27.70	
CA_41D-41C	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	LTE B41 PC2	20	41292	2660.2	LTE B41 PC2	20	41094	2640.4	LTE B41 PC2	20	39948	2525.8	LTE B41 PC2	20	39750	2506	27.63	27.70	

FCC ID: ZNFG850UM		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/19 - 09/12/19	DUT Type: Portable Handset			APPENDIX H: Page 7 of 13

1.4 DL CA with DL 4x4 MIMO RF Conduction Powers

This device supports downlink 4x4 MIMO operations for some LTE bands. Uplink transmission is limited to a single output stream. When carrier aggregation was applicable, the general test selection and setup procedures described in Section 1.2 were applied.

Per May 2017 TCB Workshop Notes, SAR for 4x4 DL MIMO was not needed since the maximum average output power in 4x4 DL MIMO mode was not more than 0.25 dB higher than the maximum output power with 4x4 DL MIMO inactive. Additionally, SAR for 4x4 MIMO Downlink Carrier Aggregation was not needed since the maximum average output power in 4x4 MIMO Downlink Carrier Aggregation mode was not more than 0.25 dB higher than the maximum output power with 4x4 MIMO Downlink and downlink carrier aggregation inactive.

1.4.1 LTE 4x4 MIMO DL Standalone Powers

Table 14
Maximum Output Powers

LTE Band	Bandwidth [MHz]	Channel	Frequency [MHz]	Modulation	RB Size	RB Offset	4x4 DL MIMO Tx. Power [dBm]	Single Antenna Tx. Power [dBm]	Target Power [dBm]
66	15	132047	1717.5	QPSK	1	0	24.96	25.00	24.5
25	20	26365	1882.5	QPSK	1	0	24.13	24.20	23.7
7	15	20825	2507.5	QPSK	1	74	23.66	23.70	23.2
41	15	41490	2680	QPSK	1	0	25.15	25.16	24.7
41 PC2	20	41490	2680	QPSK	1	0	27.65	27.70	27.2

1.4.2 LTE Band 71 as PCC

Table 15
Maximum Output Powers

		PCC										SCC 1				SCC 2				SCC 3				Power			
Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Ch.	PCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	DL Ant. Config.	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA [2A]-[4A]-[71A]	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	2x2	LTE B2	20	900	1960	2x2	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	25.12	25.43
CA [2A]-[66A]-[71A]	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	2x2	LTE B2	20	900	1960	2x2	LTE B66	20	66786	2145	4x4	-	-	-	-	-	25.14	25.43
CA [2A]-[4A]-[71A]	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	25.16	25.43
CA [4A]-[4A]-[71A]	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	2x2	LTE B4	20	2175	2132.5	4x4	LTE B4	10	2350	2150	4x4	-	-	-	-	-	25.17	25.43
CA [2A]-[2A]-[66A]-[71A]	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	4x4	LTE B66	20	66786	2145	4x4	25.18	25.43
CA [2A]-[66A]-[66A]-[71A]	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	2x2	LTE B2	20	900	1960	4x4	LTE B66	20	66786	2145	4x4	LTE B66	20	67236	2190	4x4	25.16	25.43
CA [2A]-[66C]-[71A]	LTE B71	15	133297	680.5	QPSK	1	36	68761	634.5	2x2	LTE B2	20	900	1960	4x4	LTE B66	20	66786	2145	4x4	LTE B66	20	66984	2164.8	4x4	25.12	25.43

FCC ID: ZNFG850UM	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/19 - 09/12/19	DUT Type: Portable Handset	APPENDIX H: Page 8 of 13		

1.4.3 LTE Band 12 as PCC

Table 16
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Freq. [MHz]	PCC				DL Ant. Config.	SCC 1				DL Ant. Config.	SCC 2				DL Ant. Config.	SCC 3				DL Ant. Config.	SCC 4				Power				
				Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Ch.		SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)			
CA (2A)(2A)(1)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	-	-	-	-	-	-	-	-	-	-	-	-	-	25.29	25.38		
CA (4A)(4A)(1)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	-	-	-	-	-	25.18	25.38		
CA (4A)(4A)(2)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	-	-	-	-	-	25.18	25.38		
CA (12A)(6A)(1)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B06	20	66786	2145	4x4	-	-	-	-	-	-	-	-	-	-	-	-	-	25.21	25.38		
CA (12A)(6A)(2)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B06	20	66786	2145	4x4	-	-	-	-	-	-	-	-	-	-	-	-	-	25.22	25.38		
CA (2A)(4A)(1A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	2x2	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	-	25.38	25.38	
CA (2A)(4A)(2A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	2x2	-	-	-	-	-	-	-	-	-	25.30	25.38	
CA (4A)(2A)(1A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B4	20	2175	2132.5	2x2	LTE B2	20	900	1960	4x4	-	-	-	-	-	-	-	-	-	25.39	25.38	
CA (4A)(2A)(2A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B4	20	2175	2132.5	4x4	LTE B2	20	900	1960	2x2	-	-	-	-	-	-	-	-	-	25.31	25.38	
CA (4A)(4A)(1A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B4	20	2175	2132.5	4x4	LTE B4	10	2350	2150	2x2	-	-	-	-	-	-	-	-	-	25.31	25.38	
CA (4A)(4A)(2A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B4	20	2175	2132.5	4x4	LTE B4	10	2350	2150	4x4	-	-	-	-	-	-	-	-	-	25.36	25.38	
CA (4A)(7A)(1A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B4	20	2175	2132.5	4x4	LTE B7	20	3100	2655	2x2	-	-	-	-	-	-	-	-	-	25.29	25.38	
CA (12A)(6A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B06	20	66786	2145	4x4	LTE B06	20	67236	2150	2x2	-	-	-	-	-	-	-	-	-	25.42	25.38	
CA (2A)(12A)(6A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B06	20	66786	2145	2x2	LTE B06	20	67236	2150	2x2	-	-	-	-	25.42	25.38	
CA (2A)(12A)(6A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B06	20	66786	2145	4x4	LTE B06	20	67236	2150	4x4	-	-	-	-	25.39	25.38	
CA (2A)(2A)(12A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B06	20	66786	2145	4x4	LTE B06	20	66984	2154.8	4x4	-	-	-	-	25.20	25.38	
CA (2A)(4A)(1A)(1A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	-	25.26	25.38	
CA (2A)(4A)(1A)(1A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	-	25.29	25.38	
CA (2A)(4A)(1A)(2A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	-	25.35	25.38	
CA (2A)(12A)(12A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B7	20	3100	2655	4x4	LTE B06	20	66786	2145	4x4	-	-	-	-	25.37	25.38	
CA (2A)(12A)(12A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B7	20	3100	2655	2x2	-	-	-	-	-	-	-	-	-	25.34	25.38	
CA (7A)(12A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B12	5	51537	738.7	2x2	LTE B7	20	3100	2655	4x4	LTE B06	20	66786	2145	4x4	-	-	-	-	25.20	25.38	
CA (2A)(2A)(12A)(12A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	2x2	LTE B30	10	9820	2385	2x2	LTE B06	20	66786	2145	4x4	25.32	25.38
CA (2A)(2A)(12A)(12A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	4x4	LTE B30	10	9820	2385	2x2	LTE B06	20	66786	2145	4x4	25.31	25.38
CA (2A)(2A)(12A)(12A)(6A)	LTE B12	5	23135	731.5	QPSK	1	0	5155	743.5	2x2	LTE B12	5	51537	738.7	2x2	LTE B2	20	900	1960	4x4	LTE B7	20	3100	2655	4x4	LTE B06	20	66786	2145	4x4	25.19	25.38

1.4.4 LTE Band 13 as PCC

Table 17
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	Mod.	PCC UL		PCC [DL] Ch.	DL Ant. Config.	SCC 1				SCC 2				SCC 3				SCC 4				Power							
					PCC UL RB Offset	PCC UL#			SCC Band	SCC BW [MHz]	SCC [DL] Ch.	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	DL Ant. Config.	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)						
CA (2A)(13A)(6A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B2	20	900	1960	2x2	LTE B06	20	66786	2145	4x4	-	-	-	-	-	-	-	-	25.19	25.08		
CA (2A)(2A)(13A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B2	20	900	1960	4x4	LTE B06	20	66786	2145	2x2	-	-	-	-	-	-	-	-	25.17	25.08		
CA (2A)(4A)(13A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	2x2	-	-	-	-	-	-	-	-	25.17	25.08		
CA (2A)(4A)(13A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	25.18	25.08		
CA (4A)(4A)(13A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B4	20	2175	2132.5	4x4	LTE B4	20	2350	2150	2x2	-	-	-	-	-	-	-	-	25.19	25.08		
CA (13A)(6A)(6A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B06	20	66786	2145	4x4	LTE B06	20	67236	2150	2x2	-	-	-	-	-	-	-	-	25.16	25.08		
CA (2A)(13A)(6A)(6A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B2	20	900	1960	4x4	LTE B06	20	66786	2145	4x4	LTE B06	20	67236	2150	4x4	-	-	-	-	25.20	25.08	
CA (2A)(2A)(13A)(6A)(6A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B2	20	900	1960	4x4	LTE B06	20	66786	2145	4x4	LTE B06	20	66984	2154.8	4x4	-	-	-	-	25.23	25.08	
CA (2A)(2A)(13A)(6A)(6A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	4x4	LTE B06	20	66786	2145	4x4	-	-	-	-	25.23	25.08	
CA (2A)(2A)(13A)(6A)(6A)	LTE B13	10	52320	782	QPSK	1	25	52320	751	2x2	LTE B2	20	900	1960	4x4	LTE B06	20	66786	2145	4x4	LTE B06	15	66786	2154.8	4x4	LTE B06	15	66786	2154.8	4x4	25.22	25.08

1.4.5 LTE Band 5 as PCC

Table 18
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch. [MHz]	Mod.	PCC UL# RB	PCC UL# RB Offset	PCC [DL] Ch. [MHz]	PCC [DL] Freq. [MHz]	DL Ant. Config.	SCC 1				DL Ant. Config.	SCC 2				DL Ant. Config.	SCC 3				DL Ant. Config.	SCC 4				Power			
										SCC Band	SCC BW [MHz]	SCC [DL] Ch. [MHz]	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch. [MHz]	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch. [MHz]	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch. [MHz]	SCC [DL] Freq. [MHz]	LTE Tx Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)		
CA (2A)(4A)(5A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	2x2	LTE B4	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	24.92	25.20		
CA (2A)(4A)(5A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	2x2	-	-	-	-	-	-	-	-	24.95	25.20		
CA (2A)(4A)(5A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B30	10	9620	2355	2x2	-	-	-	-	-	-	-	-	24.99	25.20		
CA (2A)(4A)(5A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	24.99	25.20		
CA (4A)(5A)(5A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B4	20	2175	2132.5	4x4	LTE B30	10	9620	2355	2x2	-	-	-	-	-	-	-	-	24.98	25.20		
CA (4A)(5A)(5A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B4	20	2175	2132.5	4x4	LTE B30	20	2175	2132.5	4x4	-	-	-	-	-	-	-	-	24.98	25.20		
CA (4A)(7A)(7A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B7	20	3100	2655	4x4	LTE B7	20	2850	2650	2x2	-	-	-	-	-	-	-	-	25.14	25.20		
CA (4A)(7A)(7A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B7	20	3100	2655	4x4	LTE B7	20	2850	2650	4x4	-	-	-	-	-	-	-	-	25.16	25.20		
CA (2A)(2A)(4A)(5A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	25.02	25.20	
CA (2A)(2A)(5A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	4x4	LTE B6B	20	6678B	2145	4x4	-	-	-	-	25.03	25.20	
CA (2A)(2A)(5A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	25.03	25.20	
CA (2A)(2A)(5A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B5	10	2153	884.3	2x2	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	25.08	25.20	
CA (2A)(2A)(6A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B6B	20	6678B	2145	4x4	LTE B6B	20	6723B	2150	4x4	-	-	-	-	24.97	25.20	
CA (2A)(4A)(4A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	4x4	LTE B4	20	2175	2132.5	4x4	-	-	-	-	25.03	25.20	
CA (2A)(4A)(4A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B5	20	2153	884.3	2x2	LTE B4	20	2175	2132.5	4x4	LTE B4	20	2150	2150	4x4	-	-	-	-	24.93	25.20	
CA (5A)(5A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B5	20	2153	884.3	2x2	LTE B6B	20	6678B	2145	4x4	LTE B6B	20	6678B	2145	4x4	-	-	-	-	24.99	25.20	
CA (5A)(5A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B5	5	2425	871.5	2x2	LTE B6B	15	6678B	2145	4x4	LTE B6B	5	6687B	2154.3	4x4	-	-	-	-	24.99	25.20	
CA (5A)(6A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B5	20	2425	871.5	2x2	LTE B6B	20	6678B	2145	4x4	LTE B6B	20	6687B	2154.3	4x4	-	-	-	-	24.99	25.20	
CA (5A)(6A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B5	20	2153	884.3	2x2	LTE B6B	20	6678B	2145	4x4	LTE B6B	20	6723B	2150	4x4	-	-	-	-	24.99	25.20	
CA (2A)(2A)(5A)(6A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	2x2	LTE B6B	20	6678B	2145	4x4	LTE B6B	20	6723B	2150	2x2	25.01	25.20
CA (2A)(2A)(5A)(6A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	2x2	LTE B6B	20	6678B	2145	2x2	LTE B6B	20	6723B	2150	2x2	25.01	25.20
CA (2A)(2A)(5A)(6A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	2x2	LTE B6B	20	6678B	2145	4x4	LTE B6B	5	6687B	2154.3	4x4	25.04	25.20
CA (2A)(2A)(5A)(6A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	2x2	LTE B6B	20	6678B	2145	4x4	LTE B6B	5	6687B	2154.3	4x4	25.04	25.20
CA (2A)(2A)(5A)(6A)(6A)	LTE B5	5	20625	846.5	QPSK	1	0	2625	891.5	2x2	LTE B2	20	900	1960	4x4	LTE B2	20	700	1940	2x2	LTE B6B	20	6678B	2145	4x4	LTE B6B	5	6687B	2154.3	4x4	25.04	25.20

1.4.8 LTE Band 30 as PCC

Table 21
Maximum Output Powers

PCC															SCC1				SCC2				SCC3				SCC4				Power	
Combination	PCC Band	PCC BW [MHz]	PCC [UL] Freq. [MHz]	PCC [UL] Mod.	PCC UL# RB	PCC UL RB Offset	PCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Freq. [MHz]	DL Ant. Config.	LTE Tx Power with SC CA (dBm)	LTE Single Carrier Tx Power (dBm)						
CA 244A-30A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B2	20	900	1960	242	LTE B4	20	2175	2122.5	4x4	4	2175	2122.5	2x2	21.58	23.38						
CA 12A-4A-30A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B2	20	900	1960	4x4	LTE B4	20	2175	2122.5	2x2	4	2175	2122.5	2x2	21.26	23.38						
CA 12A-5A-30A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B2	20	900	1960	4x4	LTE B5	10	2525	881.5	2x2	4	2175	2122.5	2x2	21.29	23.38						
CA 12A-6A-30A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B2	20	900	1960	4x4	LTE B3	10	2145	1813.5	2x2	4	2175	2122.5	2x2	21.35	23.38						
CA 14A-3A-30A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B4	20	2175	2122.5	4x4	LTE B5	10	2525	881.5	2x2	4	2175	2122.5	2x2	21.35	23.38						
CA 5A-30A-66A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B5	10	2525	881.5	2x2	LTE B6	20	9670	2145	4x4	4	2175	2122.5	2x2	21.35	23.38						
CA 12A-12A-30A-30A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B2	20	900	1960	4x4	LTE B2	20	2175	2122.5	4x4	4	2175	2122.5	2x2	21.30	23.38						
CA 12A-12A-12A-30A-66A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B2	20	900	1960	4x4	LTE B2	20	2175	2122.5	4x4	4	2175	2122.5	2x2	21.30	23.38						
CA 12A-12A-12A-30A-46A	LTE B20	5	27710	2310	QPSK	1	12	9820	2355	242	LTE B2	20	900	1960	4x4	LTE B2	20	2175	2122.5	4x4	4	LTE B12	20	5095	737.5	2x2	21.37	23.38				

1.4.9 LTE Band 7 as PCC

Table 22
Maximum Output Powers

Combination	PCB Band	PCB BW [MHz]	PCB [DU] Freq. [MHz]	Mod.	PCF CUI	PCF UI Band Offset	PCF [DU] Freq. [MHz]	DU Ant. Config.	SCC 1				SCC 2				SCC 3				SCC 4				Power				
									SCC [DU] Ch.	SCC [DU] Freq. [MHz]	DU Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DU] Ch.	SCC [DU] Freq. [MHz]	DU Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DU] Ch.	SCC [DU] Freq. [MHz]	DU Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DU] Ch.	SCC [DU] Freq. [MHz]	DU Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DU] Ch.
CA [2A]4A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	-	-	-	-	-	-	-
CA 2A-4A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B2	20	900	1960	2x2	LTE B4	20	2175	2132.5	2x2	-	-	-	-	-	-	-	23.69	23.70
CA 2A-4A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B2	20	900	1960	4A4	LTE B4	20	2175	2132.5	4A4	-	-	-	-	-	-	-	23.69	23.70
CA [2A]4A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B2	20	900	1960	4A4	LTE B4	20	2175	2132.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B2	20	900	1960	4A4	LTE B4	20	2175	2132.5	4A4	-	-	-	-	-	-	-	23.68	23.70
CA 4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B4	20	2175	2132.5	2x2	LTE B12	10	5095	717.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA 4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B4	20	2175	2132.5	2x2	LTE B4	20	2175	2132.5	2x2	-	-	-	-	-	-	-	23.67	23.70
CA 4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B4	20	2175	2132.5	4A4	LTE B4	20	2175	2132.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA 4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B4	20	2175	2132.5	4A4	LTE B4	20	2175	2132.5	4A4	-	-	-	-	-	-	-	23.65	23.70
CA 4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B5	10	2525	881.5	2x2	-	-	-	-	-	-	-	23.62	23.70
CA 4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	4A4	LTE B5	10	2525	881.5	2x2	-	-	-	-	-	-	-	23.63	23.70
CA 5A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	2096	2644.6	4A4	LTE B5	10	2525	881.5	2x2	-	-	-	-	-	-	-	23.61	23.70
CA 5A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	2096	2644.6	4A4	LTE B5	10	2525	881.5	2x2	-	-	-	-	-	-	-	23.61	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2	-	-	-	-	-	-	-	23.68	23.70
CA [2A]4A(1A)-2A(1A)	LTE BT	15	2026.5	2507.5	QPSK	1	74	2625	2627.5	4A4	LTE B7	20	3160	2080	2x2	LTE B46	20	50665	50577.5	2x2									

FCC ID: ZNFG850UM	 SAR EVALUATION REPORT 	Reviewed by: Quality Manager
Test Dates: 08/21/19 - 09/12/19	DUT Type: Portable Handset	APPENDIX H: Page 11 of 13

1.4.10 LTE Band 41 PC3 as PCC

Table 23
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Freq. [MHz]	Mod.	PCC				DL Ant. Config.	SCC 1				DL Ant. Config.	SCC 2				DL Ant. Config.	SCC 3				DL Ant. Config.	SCC 4				Power					
					PCC UL RB	PCC UL RB Offset	PCC [DL] Ch.	PCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]		SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	LTE Tx Power with DL CA Enabled [dBm]	LTE Single Carrier Tx Power [dBm]				
CA 41A(41A)(1)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41	20	39750	2506	2x2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25.16	25.16		
CA 41A(41A)(1)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	2x2	LTE B41	20	39750	2506	4x4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25.17	25.16		
CA 41A(41A)(1)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41	20	39750	2506	2x2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	25.17	25.16		
CA 41A(41C)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	2x2	LTE B41	20	39948	2525.8	4x4	LTE B41	20	39750	2506	4x4	-	-	-	-	-	-	-	-	-	-	-	25.17	25.16	
CA 41C(41A)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41	20	41319	2662.9	4x4	LTE B41	20	39750	2506	2x2	-	-	-	-	-	-	-	-	-	-	-	25.13	25.16	
CA 41A(41C)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41	20	39948	2525.8	2x2	LTE B41	20	39750	2506	2x2	-	-	-	-	-	-	-	-	-	-	-	25.16	25.16	
CA 41A(41C)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41	20	40246	2545.6	4x4	LTE B41	20	39948	2525.8	4x4	LTE B41	20	39750	2506	4x4	-	-	-	-	-	-	25.17	25.16	
CA 41C(41C)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41	20	41319	2662.9	4x4	LTE B41	20	39948	2525.8	4x4	LTE B41	20	39750	2506	4x4	-	-	-	-	-	-	25.10	25.16	
CA 41C(41C)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41	20	41319	2662.9	4x4	LTE B41	20	40246	2545.6	4x4	LTE B41	20	39948	2525.8	4x4	LTE B41	20	39750	2506	4x4	-	-	25.15	25.16
CA 41D(41C)	LTE B41	15	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41	20	41319	2662.9	4x4	LTE B41	20	41121	2643.1	4x4	LTE B41	20	39750	2506	4x4	-	-	-	-	-	-	25.13	25.16	

1.4.11 LTE Band 41 PC2 as PCC

Table 24
Maximum Output Powers

Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC [UL] Freq. [MHz]	PCC				DL Ant. Config.	SCC 1				DL Ant. Config.	SCC 2				DL Ant. Config.	SCC 3				DL Ant. Config.	SCC 4				Power					
					Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Ch.		PCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Ch.		SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Ch.		SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Ch.		SCC [DL] Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	LTE Tx Power with DL CA Enabled [dBm]	LTE Single Carrier Tx Power [dBm]			
CA_41A_41A (1)	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	39750	2506	2x2	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	27.69	27.70		
CA_41A_41A (1)	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	2x2	LTE B41 PC2	20	39750	2506	4x4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	27.70	27.70		
CA_41A_41A (1)	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	39750	2506	4x4	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	27.68	27.70		
CA_41A_41C	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	2x2	LTE B41 PC2	20	39948	2525.8	4x4	LTE B41 PC2	20	39750	2506	4x4	-	-	-	-	-	-	-	-	-	-	-	27.69	27.70	
CA_41C_41A	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	41292	2660.2	4x4	LTE B41 PC2	20	39750	2506	2x2	-	-	-	-	-	-	-	-	-	-	-	27.68	27.70	
CA_41A_41C	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	39948	2525.8	2x2	LTE B41 PC2	20	39750	2506	2x2	-	-	-	-	-	-	-	-	-	-	-	27.66	27.70	
CA_41C_41A	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	2x2	LTE B41 PC2	20	41292	2660.2	2x2	LTE B41 PC2	20	39750	2506	4x4	-	-	-	-	-	-	-	-	-	-	-	27.70	27.70	
CA_41A_41D	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	40146	2545.6	4x4	LTE B41 PC2	20	39948	2525.8	4x4	LTE B41 PC2	20	39750	2506	4x4	-	-	-	-	-	-	27.69	27.70	
CA_41D_41A	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	41292	2660.2	4x4	LTE B41 PC2	20	41094	2640.4	4x4	LTE B41 PC2	20	39750	2506	4x4	-	-	-	-	-	-	27.68	27.70	
CA_41C_41C	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	41292	2660.2	4x4	LTE B41 PC2	20	39948	2525.8	4x4	LTE B41 PC2	20	39750	2506	4x4	-	-	-	-	-	-	27.65	27.70	
CA_41C_41D	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	41292	2660.2	4x4	LTE B41 PC2	20	41094	2640.4	4x4	LTE B41 PC2	20	40896	2620.6	4x4	-	-	-	-	-	-	27.64	27.70	
CA_41D_41C	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	41292	2660.2	4x4	LTE B41 PC2	20	40146	2545.6	4x4	LTE B41 PC2	20	39948	2525.8	4x4	LTE B41 PC2	20	39750	2506	4x4	-	-	27.69	27.70
CA_41D_41C	LTE B41 PC2	20	41490	2680	QPSK	1	0	41490	2680	4x4	LTE B41 PC2	20	41292	2660.2	4x4	LTE B41 PC2	20	41094	2640.4	4x4	LTE B41 PC2	20	39948	2525.8	4x4	LTE B41 PC2	20	39750	2506	4x4	-	-	27.66	27.70

FCC ID: ZNFG850UM



SAR EVALUATION REPORT



Reviewed by:
Quality Manager

Test Dates:
08/21/19 - 09/12/19

DUT Type:
Portable Handset

APPENDIX H:
Page 12 of 13

1.5 Downlink Carrier Aggregation with Uplink Carrier Aggregation enabled

This device supports uplink carrier aggregation (ULCA) with additional Carrier Aggregation configurations active in the downlink. Power measurements were performed with ULCA active and additional CA configurations active in the downlink for the configuration per Fall 2017 TCB Workshop Notes.

Per FCC Guidance, additional SAR measurements for these configurations were not required since their maximum output power was not more than 0.25 dB higher than the maximum output power for with only ULCA active.

1.5.1 DL Carrier Aggregation RF Conducted Powers

Table 25
Maximum Output Powers

		PCC										SCC 1				SCC 2				Power		
Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Modulation	PCC UL RB	PCC UL RB Offset	PCC (DL) Ch.	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (UL/DL) Ch.	SCC (UL/DL) Freq. [MHz]	Modulation	SCC UL RB	SCC UL RB Offset	SCC Band	SCC BW [MHz]	SCC (DL) Ch.	SCC (DL) Freq. [MHz]	ULCA Tx. Power with add'l CA config. Active on DL (dBm)	ULCA Tx. Power (dBm)
CA 41D	LTE B41	20	40620	2593	QPSK	1	0	40620	2593	LTE B41	20	40422	2573.2	QPSK	1	99	LTE B41	20	40818	2612.8	25.15	25.20
CA 41D	LTE B41 PC2	20	40620	2593	QPSK	1	0	40620	2593	LTE B41 PC2	20	40422	2573.2	QPSK	1	99	LTE B41 PC2	20	40818	2612.8	27.51	27.52
		PCC										SCC 1				SCC 2				Power		
Combination	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Modulation	PCC UL RB	PCC UL RB Offset	PCC (DL) Ch.	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (UL/DL) Ch.	SCC (UL/DL) Freq. [MHz]	Modulation	SCC UL RB	SCC UL RB Offset	SCC Band	SCC BW [MHz]	SCC (DL) Ch.	SCC (DL) Freq. [MHz]	ULCA Tx. Power with add'l CA config. Active on DL (dBm)	ULCA Tx. Power (dBm)
CA 41E	LTE B41	20	40620	2593	QPSK	1	0	40620	2593	LTE B41	20	40422	2573.2	QPSK	1	99	LTE B41	20	40818	2612.8	25.17	25.20
CA 41E	LTE B41 PC2	20	40620	2593	QPSK	1	0	40620	2593	LTE B41 PC2	20	40422	2573.2	QPSK	1	99	LTE B41 PC2	20	40818	2612.8	27.54	27.54

1.5.2 DL Carrier Aggregation with DL 4x4 MIMO RF Conducted Powers

Note: 4x4 DL MIMO is only operating in the downlink. Uplink transmission is limited to a single output stream for each component carrier of ULCA.

Table 26
Maximum Output Powers

Combination	PCC										SCC 1				SCC 2				Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Ch.	PCC (DL) Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC (UL/DL) Ch.	SCC (UL/DL) Freq. [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	DL Ant. Config.	ULCA Tx. Power with add'l CA config. Active on DL (dBm)	ULCA Tx. Power (dBm)
CA 41C	LTE B41	20	40620	2593	QPSK	1	0	40620	2593	4x4	LTE B41	20	40422	2573.2	QPSK	1	99	4x4	25.20	25.20
CA 41C	LTE B41 PC2	20	40620	2593	QPSK	1	0	40620	2593	4x4	LTE B41 PC2	20	40422	2573.2	QPSK	1	99	4x4	27.48	27.52

Combination	PCC										SCC 1				SCC 2				Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Ch.	PCC (DL) Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC (UL/DL) Ch.	SCC (UL/DL) Freq. [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	DL Ant. Config.	ULCA Tx. Power with add'l CA config. Active on DL (dBm)	ULCA Tx. Power (dBm)
CA 41D	LTE B41	20	40620	2593	QPSK	1	0	40620	2593	4x4	LTE B41	20	40422	2573.2	QPSK	1	99	4x4	25.15	25.20
CA 41D	LTE B41 PC2	20	40620	2593	QPSK	1	0	40620	2593	4x4	LTE B41 PC2	20	40422	2573.2	QPSK	1	99	4x4	27.52	27.52

Combination	PCC										SCC 1				SCC 2				Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Ch.	PCC (UL) Freq. [MHz]	Mod.	PCC UL# RB	PCC UL RB Offset	PCC (DL) Ch.	PCC (DL) Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC (UL/DL) Ch.	SCC (UL/DL) Freq. [MHz]	Modulation	SCC UL# RB	SCC UL RB Offset	DL Ant. Config.	ULCA Tx. Power with add'l CA config. Active on DL (dBm)	ULCA Tx. Power (dBm)
CA 41E	LTE B41	20	40620	2593	QPSK	1	0	40620	2593	4x4	LTE B41	20	40422	2573.2	QPSK	1	99	4x4	25.10	25.20
CA 41E	LTE B41 PC2	20	40620	2593	QPSK	1	0	40620	2593	4x4	LTE B41 PC2	20	40422	2573.2	QPSK	1	99	4x4	27.50	27.50

FCC ID: ZNFG850UM		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Test Dates: 08/21/19 - 09/12/19	DUT Type: Portable Handset	APPENDIX H: Page 13 of 13		