

On your side



TEST REPORT

EMI Test for FCC Certification of LM-G900UM Model

APPLICANT

LG Electronics USA, Inc.

REPORT NO.

HCT-EM-2004-FI003

DATE OF ISSUE

April 23, 2020

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 645 6300 Fax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

EMI Test for
FCC Certification

REPORT NO.

HCT-EM-2004-FI003

DATE OF ISSUE

April 23, 2020

FCC ID.

ZNFG900UM

Applicant

LG Electronics USA, Inc.

1000 Sylvan Avenue, Englewood Cliffs NJ 07632 United States

Product Name

Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth and NFC

Model Name

LM-G900UM

Series Model Name

Refer to the clause 1.1 Description of EUT

Date of Test

April 03, 2020 to April 06, 2020

Test Standard Used

FCC CFR 47 PART 15 Subpart B Class B
ANSI C63.4-2014

Test Results

Refer to the present document

Manufacturer

LG Electronics Inc.

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Tested by

Ki-Min Lee

(signature)

Technical Manager

Kyoung-Hee Yoon

(signature)

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	April 23, 2020	Initial Release

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

This Test Report is not related to the accredited test result by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation), which signed the ILAC-MRA.

CONTENTS

1. GENERAL INFORMATION	5
1.1 Description of EUT	5
1.2 Tested System Details	6
1.3 Cable Description	7
1.4 Noise Suppression Parts on Cable. (I/O Cable)	7
1.5 Test Facility	8
1.6 Calibration of Measuring Instrument	8
1.7 Measurement Uncertainty	8
2. DESCRIPTION OF TEST	9
2.1 Measurement of Conducted Emission	9
2.2 Measurement of Radiated Emission	10
2.3 Configuration of Tested System	11
3. PRELIMINARY TEST	12
3.1 Conducted Emission	12
3.2 Radiated Emission	12
4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY	13
4.1 Conducted Emission	13
4.2 Radiated Emission Below 1 GHz	20
4.3 Radiated Emission Above 1 GHz	22
5. CONCLUSION	25
6. APPENDIX A. TEST SETUP PHOTO	26

1. GENERAL INFORMATION

1.1 Description of EUT

FCC ID	ZNFG900UM	
Model Name	LM-G900UM	
Series Model Name	LM-G900UM, LMG900UM, G900UM, LM-G900QM, LMG900QM, G900QM, LM-G901V, LMG901V, G901V	
Product Name	Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth and NFC	
Frequency Range	RX Frequency	TX Frequency
CDMA BC0	869.70 MHz to 893.31 MHz	824.70 MHz to 848.31 MHz
CDMA BC1	1 931.25 MHz to 1 988.75 MHz	1 851.25 MHz to 1 908.75 MHz
GSM 850	869.20 MHz to 893.80 MHz	824.20 MHz to 848.80 MHz
GSM 1 900	1 930.20 MHz to 1 989.80 MHz	1 850.20 MHz to 1 909.80 MHz
WCDMA B2	1 932.4 MHz to 1 987.6 MHz	1 852.4 MHz to 1 907.6 MHz
WCDMA B4	2 112.4 MHz to 2 152.6 MHz	1712.4 MHz to 1752.6 MHz
WCDMA B5	871.40 MHz to 891.60 MHz	826.40 MHz to 846.60 MHz
LTE B2	1 930 MHz to 1 990 MHz	1 850 MHz to 1 910 MHz
LTE B4	2 110 MHz to 2 155 MHz	1 710 MHz to 1 755 MHz
LTE B5	869 MHz to 894 MHz	824 MHz to 849 MHz
LTE B7	2 516 MHz to 2 690 MHz	2 496 MHz to 2 570 MHz
LTE B12	729 MHz to 746 MHz	699 MHz to 716 MHz
LTE B13	746 MHz to 756 MHz	777 MHz to 787 MHz
LTE B14	758 MHz to 768 MHz	788 MHz to 798 MHz
LTE B17	734 MHz to 746 MHz	704 MHz to 716 MHz
LTE B25	1 925 MHz to 1 990 MHz	1 850 MHz to 1 915 MHz
LTE B29	717 MHz to 728 MHz	-
LTE B30	2 350 MHz to 2 360 MHz	2 305 MHz to 2 315 MHz
LTE B41	2 496 MHz to 2 690 MHz	2 496 MHz to 2 690 MHz
LTE B46	5 150 MHz to 5 925 MHz	-
LTE B66	2 110 MHz to 2 200 MHz	1 710 MHz to 1 780 MHz
LTE B71	617 MHz to 652 MHz	663 MHz to 698 MHz
Bluetooth	2 402 MHz to 2 480 MHz	2 402 MHz to 2 480 MHz
WiFi 2.4 GHz	2 412 MHz to 2 462 MHz	2 412 MHz to 2 462 MHz
WiFi 5 GHz_UNII 1	5 180 MHz to 5 240 MHz	5 180 MHz to 5 240 MHz
WiFi 5 GHz_UNII 2A	5 260 MHz to 5 320 MHz	5 260 MHz to 5 320 MHz
WiFi 5 GHz_UNII 2C	5 500 MHz to 5 720 MHz	5 500 MHz to 5 720 MHz
WiFi 5 GHz_UNII 3	5 745 MHz to 5 825 MHz	5 745 MHz to 5 825 MHz
NFC	13.56 MHz	13.56 MHz
5G NR n2	1 930 MHz to 1 990 MHz	1 850 MHz to 1 910 MHz
5G NR n5	869 MHz to 894 MHz	824 MHz to 849 MHz
5G NR n25	1 930 MHz to 1 995 MHz	1 850 MHz to 1 915 MHz
5G NR n41	2 496 MHz to 2 690 MHz	2 496 MHz to 2 690 MHz
5G NR n66	2 110 MHz to 2 200 MHz	1 710 MHz to 1 780 MHz
5G NR n71	617 MHz to 652 MHz	663 MHz to 698 MHz

1.2 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer
EUT	LM-G900UM	-	LG
Notebook PC	ProBook6560b	5CB2053MXF	HP
Notebook PC Adaptor	Series PPP009L-E	-	LITE-ON Technology (CHANGZHOU)
Gateway	DIR-806M	-	D-Link
Gateway Adaptor	AMS1-0501200FK	-	D-Link
Serial Mouse	Serial 2 Button mouse	02031069	Radio Shack
RJ45 Cable	-	-	-
Data Cable	EAD64746101	-	NINGBO
Data Cable	EAD64746102	-	LUXSHARE
Earphone	EAB63728252	-	BUJEON
Micro SD Card	SAMSUNG EVO+microSDXC CLASS10 UHS-I (256 GB)	-	SAMSUNG

1.3 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	USB Type C	Y	Y	(P,D) 1.0
	Earphone	N/A	N	(D) 1.2
Notebook PC	RJ 45	N/A	N	(D) 1.6
	Serial (Mouse)	N/A	Y	(D) 1.8
	DC IN	N	N/A	(P) 1.8
Gateway	DC IN	N	N/A	(P) 1.8

NOTE. The marked "(D)" means the data cable and "(P)" means the power cable.

1.4 Noise Suppression Parts on Cable (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	USB Type C	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook End

1.5 Test Facility

Test site is located at 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, South Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

Measurement Facilities	Designation No.
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	KR0032
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #1	
Radiated Field strength measurement facility 10 m Semi Anechoic chamber #2	

1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5:2017

1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty
Conducted Emission (0.15 MHz to 30 MHz)	1.8 dB
Radiated Emissions (30 MHz to 1 GHz)	4.8 dB
Radiated Emissions (1 GHz to 18 GHz)	5.4 dB
Radiated Emissions (18 GHz to 40 GHz)	5.7 dB

2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).

If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).

Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

Conducted Emission Limits

Frequency (MHz)	Resolution Bandwidth (kHz)	Class A		Class B	
		Quasi-Peak (dB μ V)	Average (dB μ V)	Quasi-Peak (dB μ V)	Average (dB μ V)
0.15 to 0.5	9	79	66	66 to 56*	56 to 46*
0.5 to 5	9	73	60	56	46
5 to 30	9	73	60	60	50

NOTE. Decreases with the logarithm of the frequency.

2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber.

The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

(1 GHz to 40 GHz)

Radiated Emission Limits


Frequency (MHz)	Class A			Class B		
	Antenna Distance (m)	Field Strength (μV/m)	Quasi-Peak (dBμV/m)	Antenna Distance (m)	Field Strength (μV/m)	Quasi-Peak (dBμV/m)
30 to 88	10	90	39.0	3	100	40.0
88 to 216	10	150	43.5	3	150	43.5
216 to 960	10	210	46.4	3	200	46.0
Above 960	10	300	49.5	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Class A		Class B		
		Peak (dBμV/m)	Average (dBμV/m)	Peak (dBμV/m)	Average (dBμV/m)	
Above 1 000	3	80	60	74	54	

2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



3. PRELIMINARY TEST

3.1 Conducted Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes: Data Communication mode

3.2 Radiated Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes: Data Communication mode

4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission

4.1.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	06.18.2019
☒	LISN	Rohde & Schwarz	ENV216	102245	1 year	09.11.2019
☒	LISN	Rohde & Schwarz	ENV216	100073	1 year	04.30.2019
☒	Software	Rohde & Schwarz	EMC32	-	-	-


4.1.2 Operating Condition

The test results of conducted emission at mains ports provide the following information:

Test Standard Used	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Frequency Range	150 kHz to 30 MHz
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operating Mode	Data Communication mode
Worst Case of Data Cable	LUXSHARE (EAD64746102)
Kind of Test Site	EMI Shielded Room
Temperature	25.1 °C
Relative Humidity	46.2 %
Test Date	April 03, 2020

4.1.3 Measuring Data

Figure 1: Conducted Emission, AC Main Port, Line (L1)



QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.180000	48.2	9.000	L1	9.7	16.3	64.5
0.192000	57.5	9.000	L1	9.7	6.5	63.9
0.196000	54.2	9.000	L1	9.7	9.6	63.8
0.200000	56.3	9.000	L1	9.7	7.3	63.6
0.304000	47.1	9.000	L1	9.7	13.0	60.1
0.310000	43.8	9.000	L1	9.7	16.1	60.0
0.906000	27.4	9.000	L1	9.7	28.6	56.0
4.188000	40.0	9.000	L1	9.8	16.0	56.0
4.256000	38.7	9.000	L1	9.8	17.3	56.0
4.270000	38.5	9.000	L1	9.8	17.5	56.0
4.394000	37.7	9.000	L1	9.8	18.3	56.0
4.436000	38.9	9.000	L1	9.8	17.1	56.0
9.006000	37.7	9.000	L1	9.9	22.3	60.0
9.024000	34.7	9.000	L1	9.9	25.3	60.0
9.130000	37.7	9.000	L1	9.9	22.3	60.0
9.150000	37.3	9.000	L1	9.9	22.8	60.0
9.154000	36.0	9.000	L1	9.9	24.0	60.0
9.200000	36.7	9.000	L1	9.9	23.3	60.0


Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.186000	36.4	9.000	L1	9.7	17.8	54.2
0.190000	38.1	9.000	L1	9.7	15.9	54.0
0.196000	36.5	9.000	L1	9.7	17.3	53.8
0.200000	37.0	9.000	L1	9.7	16.6	53.6
0.250000	30.4	9.000	L1	9.7	21.4	51.8
0.310000	27.6	9.000	L1	9.7	22.3	50.0
4.268000	29.4	9.000	L1	9.8	16.6	46.0
4.294000	27.4	9.000	L1	9.8	18.6	46.0
4.340000	27.8	9.000	L1	9.8	18.2	46.0
4.394000	27.9	9.000	L1	9.8	18.1	46.0
4.436000	27.9	9.000	L1	9.8	18.1	46.0
4.530000	25.4	9.000	L1	9.8	20.6	46.0
9.024000	25.5	9.000	L1	9.9	24.5	50.0
9.030000	26.7	9.000	L1	9.9	23.3	50.0
9.130000	27.7	9.000	L1	9.9	22.3	50.0
9.150000	27.0	9.000	L1	9.9	23.0	50.0
9.200000	28.1	9.000	L1	9.9	22.0	50.0
9.230000	27.5	9.000	L1	9.9	22.5	50.0

Figure 2: Conducted Emission, AC Main Port, Line (N)



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.182000	52.7	9.000	N	9.7	11.7	64.4
0.186000	55.8	9.000	N	9.7	8.4	64.2
0.192000	55.5	9.000	N	9.7	8.4	63.9
0.196000	55.4	9.000	N	9.7	8.3	63.8
0.202000	55.8	9.000	N	9.7	7.7	63.5
0.250000	49.1	9.000	N	9.7	12.7	61.8
3.648000	39.2	9.000	N	9.8	16.8	56.0
3.802000	37.8	9.000	N	9.8	18.2	56.0
3.854000	39.2	9.000	N	9.8	16.8	56.0
3.860000	37.2	9.000	N	9.8	18.8	56.0
3.878000	39.4	9.000	N	9.8	16.6	56.0
3.992000	35.9	9.000	N	9.8	20.1	56.0
8.956000	36.3	9.000	N	9.9	23.7	60.0
9.022000	36.1	9.000	N	9.9	23.9	60.0
9.092000	36.0	9.000	N	9.9	24.0	60.0
9.098000	35.1	9.000	N	9.9	24.9	60.0
9.174000	34.7	9.000	N	9.9	25.3	60.0
9.228000	34.8	9.000	N	9.9	25.2	60.0

CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.186000	37.1	9.000	N	9.7	17.1	54.2
0.192000	37.8	9.000	N	9.7	16.2	53.9
0.196000	37.1	9.000	N	9.7	16.7	53.8
0.200000	36.5	9.000	N	9.7	17.1	53.6
0.250000	30.0	9.000	N	9.7	21.8	51.8
0.334000	27.1	9.000	N	9.7	22.2	49.4
3.650000	29.1	9.000	N	9.8	16.9	46.0
3.756000	28.2	9.000	N	9.8	17.8	46.0
3.788000	30.9	9.000	N	9.8	15.1	46.0
3.802000	30.0	9.000	N	9.8	16.0	46.0
3.860000	28.6	9.000	N	9.8	17.4	46.0
3.992000	26.8	9.000	N	9.8	19.2	46.0
8.958000	25.6	9.000	N	9.9	24.4	50.0
9.020000	26.1	9.000	N	9.9	23.9	50.0
9.060000	26.2	9.000	N	9.9	23.8	50.0
9.082000	25.8	9.000	N	9.9	24.2	50.0
9.098000	24.2	9.000	N	9.9	25.8	50.0
9.122000	26.3	9.000	N	9.9	23.7	50.0

.2 Radiated Emission Below 1 GHz

4.2.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI test receiver	Rohde & Schwarz	ESU40	100524	1 year	05.17.2019
☒	Bi-Log antenna	Schwarzbeck	VULB9168	255	2 year	03.26.2019
☒	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒	Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
☒	Turn table	INNCO Systems	1060	-	N/A	-
☒	Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
☒	Software	Rohde & Schwarz	EMC32	-	-	-

4.2.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Frequency Range	30 MHz to 1 000 MHz
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operating Mode	Data Communication mode
Worst Case of Data Cable	LUXSHARE (EAD64746102)
Kind of Test Site	3 m semi anechoic chamber
Temperature	25.5 °C
Relative Humidity	45.8 %
Test Date	April 03, 2020

4.2.3 Measuring Data

Frequency (MHz)	Quasi Peak (dB μ V/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)
30.686957	29.0	100.0	V	323.0	18.4	11.0	40.0
84.693600	32.6	225.0	H	289.0	15.1	7.4	40.0
143.058400	26.2	208.7	H	0.0	19.2	17.3	43.5
266.506600	32.7	100.0	H	0.0	19.3	13.3	46.0
299.895400	30.1	100.0	H	332.0	20.6	15.9	46.0
999.857400	43.3	206.8	H	39.0	32.3	10.7	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak

4.3 Radiated Emission Above 1 GHz

4.3.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI test receiver	Rohde & Schwarz	ESU40	100524	1 year	05.17.2019
☒	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒	Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
☒	Turn table	INNCO Systems	1060	-	N/A	-
☒	Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
☒	Low Noise amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.03.2020
☒	Low Noise amplifier	TESTEK	TK-PA1840H	170030-L	1 year	02.13.2020
☒	Horn antenna	Schwarzbeck	BBHA 9120D	01836	1 year	07.19.2019
☒	Horn antenna	Schwarzbeck	BBHA 9170	BBHA9170#786	1 year	12.03.2019
☒	Software	Rohde & Schwarz	EMC32	-	-	-

4.3.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	5 825 MHz
Tested Frequency Range	1 GHz to 30 GHz
Operation Mode	Data Communication mode
Worst Case of Data Cable	LUXSHARE (EAD64746102)
Kind of Test Site	3 m semi anechoic chamber
Temperature	24.3 / 26.2 °C
Relative Humidity	46.1 / 47.5 %
Test Date	April 04 / April 06, 2020

4.3.3 Measuring Data

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1007.486680	50.5	100.0	H	204.0	-29.5	23.5	74.0
1410.405000	53.0	215.4	H	191.0	-28.2	21.0	74.0
2015.320000	47.8	100.0	V	47.0	-26.6	26.2	74.0
2590.670000	53.1	349.8	V	48.0	-24.0	20.9	74.0
4480.155000	42.8	202.4	V	0.0	-19.3	31.2	74.0
15089.730000	46.9	260.4	V	11.0	-1.5	27.1	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1007.486680	20.4	100.0	H	204.0	-29.5	33.6	54.0
1410.405000	36.3	215.4	H	191.0	-28.2	17.7	54.0
2015.320000	33.1	100.0	V	47.0	-26.6	20.9	54.0
2590.670000	33.6	349.8	V	48.0	-24.0	20.4	54.0
4480.155000	24.8	202.4	V	0.0	-19.3	29.2	54.0
15089.730000	34.3	260.4	V	11.0	-1.5	19.7	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage

5. CONCLUSION

The data collected shows that the **Product Name: Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth and NFC and Model: LM-G900UM** complies with §15.107 and §15.109 of the FCC rules.

6. APPENDIX A. TEST SETUP PHOTO

Please refer to Appendix. A and test setup photo file no. as follows;

File No.	Date of Issue	Description
HCT-EM-2004-FI003-P	April 23, 2020	Initial Release

End of report