HCT CO.,LTD
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, South Korea
TEL: +82-31-645-6300 FAX: +82-31-645-6401

EMI CERTIFICATION REPORT

Applicant: **LG Electronics MobileComm U.S.A., Inc.** **1000 Sylvan Avenue, Englewood Cliffs NJ 07632**	**Date of Receipt: January 30, 2015** **Date of Issue: February 26, 2015** **Test Report No. HCT-E-1502-F044** **HCT FRN: 0005866421**

FCC ID: **ZNFH500F**

Rule Part(s) / Standard(s):	FCC CFR 47 PART 15 Subpart B Class B
FCC Classification:	JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type:	Cellular/PCS GSM/WCDMA Phone with WLAN and Bluetooth
Model Name:	LG-H500f
Additional Model Name:	LGH500f, H500f, LG-H500F, LGH500F, H500F
Test Port:	USB / Earphone Port
Date of Test:	February 03, 2015 - February 06, 2015

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)
I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denial the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Kyoung-Hee Yoon
Test Engineer
EMC Team
Certification Division

Reviewed By

Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1502-F044	February 26, 2015	Initial Release

TABLE OF CONTENTS

PAGE

1. GENERAL INFORMATION 4
1.1 Description of EUT 4
1.2 Related Submittal(s) / Grant(s) 4
1.3 Test Facility 5
1.4 Tested System Details 6
1.5 Cable Description 7
1.6 Noise Suppression Parts on Cable. (I/O Cable) 7
2. DESCRIPTION OF TEST 8
3. PRELIMINARY TEST 11
3.1 Conducted Emission Test 11
3. 2 Radiated Emission Test 11
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY 12
4.1 Conducted Emission Test 12
4.2 Radiated Emission Test 19
5. LIST OF TEST EQUIPMENT 21
6. CONCLUSION 22

ATTACHMENT: TEST SETUP PHOTOGRAPHS

1. GENERAL INFORMATION

1.1 Description of EUT

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model	LG-H500f
FCC ID	ZNFH500F
Additional Model	LGH500f, H500f, LG-H500F, LGH500F, H500F
EUT Type	Cellular/PCS GSM/WCDMA Phone with WLAN and Bluetooth
TX Frequency	824.20 ㎒ to 848.80 ㎒ (GSM 850) 1 850.20 ㎒ to 1 909.80 ㎒ (GSM 1 900) 826.40 ㎒ to 846.60 ㎒ (WCDMA 850)
RX Frequency	869.20 ㎒ to 893.80 ㎒ (GSM 850) 1 930.20 ㎒ to 1 989.80 ㎒ (GSM 1 900) 871.40 ㎒ to 891.60 ㎒ (WCDMA 850)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2003.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3 m)	90661 (February 28, 2014)
Radiated Field strength measurement facility (10 m)	90661 (February 28, 2014)

1.4 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-H500f	LG	ZNFH500F	Notebook PC, Earphone
USB cable	EAD62377902	Ningbo Broad	-	EUT, Notebook PC
Earphone	EAB62808211	I-SOUND	-	EUT
Notebook PC	ProBook6560b	HP	DoC	EUT, Notebook PC adaptor
Notebook PC adaptor	PPP009D	DELTA Electronics (Jiangsu) LTD	-	Notebook PC
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	8 GB	SanDisk	-	EUT

1.5 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.1
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.6 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End

2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 7

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*

2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2003, Clause 8

a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a 3 m shield room. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
g. The antenna height scans apply for both horizontal and vertical polarizations, except that for vertical polarization, the minimum height of the center of the antenna shall be increased so that the lowest point of the bottom of the lowest antenna element clears the site reference ground plane by at least 25 cm. (below 1 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength (μV/m)	Quasi-Peak (dB(μV)/m)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	**Antenna Distance (m)**	**Peak (dB(μV)/m)**	**Average (dB(μV)/m)**
Above 1 000	3	74	54

2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5th harmonic of the highest frequency or 40 ㎓, whichever is lower

2.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz

3. PRELIMINARY TEST

3.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

3. 2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
Kind of Test Site	Shielded Room
Temperature	20.4 °C
Relative Humidity	25.5 %
Test Date	February 06, 2015

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)



QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	42.6	9.000	L1	9.6	23.4	66.0
0.194000	48.7	9.000	L1	9.6	15.2	63.9
0.200000	48.2	9.000	L1	9.7	15.4	63.6
0.204000	47.7	9.000	L1	9.7	15.7	63.4
0.208000	46.9	9.000	L1	9.7	16.4	63.3
0.212000	46.2	9.000	L1	9.7	16.9	63.1
3.678000	38.5	9.000	L1	9.8	17.5	56.0
3.830000	38.0	9.000	L1	9.9	18.0	56.0
3.890000	39.0	9.000	L1	9.9	17.0	56.0
3.962000	38.7	9.000	L1	9.9	17.3	56.0
4.114000	37.7	9.000	L1	9.9	18.3	56.0
4.598000	37.9	9.000	L1	9.9	18.1	56.0
16.412000	32.1	9.000	L1	10.2	27.9	60.0
16.906000	31.4	9.000	L1	10.2	28.6	60.0
17.330000	31.9	9.000	L1	10.2	28.1	60.0
19.310000	32.8	9.000	L1	10.3	27.2	60.0
19.378000	32.1	9.000	L1	10.3	27.9	60.0
19.880000	30.1	9.000	L1	10.3	29.9	60.0

CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	25.7	9.000	L1	9.6	30.3	56.0
0.158000	24.5	9.000	L1	9.6	31.1	55.6
0.196000	33.9	9.000	L1	9.6	19.9	53.8
0.204000	33.6	9.000	L1	9.7	19.8	53.4
0.212000	31.3	9.000	L1	9.7	21.8	53.1
0.262000	30.4	9.000	L1	9.7	21.0	51.4
3.756000	29.1	9.000	L1	9.9	16.9	46.0
3.820000	29.6	9.000	L1	9.9	16.4	46.0
3.874000	29.4	9.000	L1	9.9	16.6	46.0
3.890000	29.4	9.000	L1	9.9	16.6	46.0
4.488000	29.4	9.000	L1	9.9	16.6	46.0
4.598000	29.4	9.000	L1	9.9	16.6	46.0
16.412000	24.8	9.000	L1	10.2	25.2	50.0
16.906000	24.1	9.000	L1	10.2	25.9	50.0
17.330000	23.3	9.000	L1	10.2	26.7	50.0
19.310000	24.6	9.000	L1	10.3	25.4	50.0
19.378000	24.2	9.000	L1	10.3	25.8	50.0
19.880000	20.0	9.000	L1	10.3	30.0	50.0

Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	42.1	9.000	N	9.6	23.9	66.0
0.158000	39.5	9.000	N	9.6	26.1	65.6
0.190000	46.4	9.000	N	9.6	17.6	64.0
0.198000	49.9	9.000	N	9.6	13.8	63.7
0.206000	49.0	9.000	N	9.6	14.4	63.4
0.212000	47.5	9.000	N	9.6	15.6	63.1
3.960000	38.6	9.000	N	9.8	17.4	56.0
4.060000	37.4	9.000	N	9.8	18.6	56.0
4.100000	38.7	9.000	N	9.8	17.3	56.0
4.316000	38.2	9.000	N	9.8	17.8	56.0
4.456000	38.0	9.000	N	9.9	18.0	56.0
4.524000	37.7	9.000	N	9.9	18.3	56.0
15.634000	30.6	9.000	N	10.2	29.4	60.0
16.338000	31.7	9.000	N	10.2	28.3	60.0
16.624000	31.9	9.000	N	10.2	28.1	60.0
16.840000	30.6	9.000	N	10.2	29.4	60.0
19.948000	29.3	9.000	N	10.3	30.7	60.0
21.500000	31.8	9.000	N	10.3	28.2	60.0

CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	26.7	9.000	N	9.6	29.3	56.0
0.162000	24.6	9.000	N	9.6	30.8	55.4
0.196000	34.0	9.000	N	9.6	19.8	53.8
0.206000	33.6	9.000	N	9.6	19.8	53.4
0.212000	31.5	9.000	N	9.6	21.6	53.1
0.258000	30.9	9.000	N	9.7	20.6	51.5
3.734000	29.2	9.000	N	9.8	16.8	46.0
3.892000	28.5	9.000	N	9.8	17.5	46.0
3.960000	28.8	9.000	N	9.8	17.2	46.0
4.100000	29.6	9.000	N	9.8	16.4	46.0
4.114000	28.7	9.000	N	9.8	17.3	46.0
4.524000	29.5	9.000	N	9.9	16.5	46.0
16.338000	24.3	9.000	N	10.2	25.7	50.0
16.906000	23.6	9.000	N	10.2	26.4	50.0
19.948000	19.7	9.000	N	10.3	30.3	50.0
20.702000	25.6	9.000	N	10.3	24.4	50.0
21.288000	26.2	9.000	N	10.3	23.8	50.0
21.422000	24.9	9.000	N	10.3	25.1	50.0

4.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 ㎓

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.7 °C
Relative Humidity	25.1 %
Test Date	February 03, 2015

Frequency (MHz)	Quasi Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
375.012024	37.8	124.0	V	145.0	20.1	8.2	46.0
625.029659	37.8	100.0	V	5.0	25.8	8.2	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak

-For Measurement Above 1 ㎓

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 ㎒, VBW: 3 ㎒) CISPR-Average mode: Peak (RBW: 1 ㎒, VBW: 10 ㎐)
Highest Operating Frequency	1.3 GHz
Testing Frequency Range	1 GHz to 7 GHz
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	21.7 °C
Relative Humidity	25.1 %
Test Date	February 03, 2015

Frequency (MHz)	Peak (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1331.913828	50.2	150.0	V	13.0	-9.3	23.8	74.0
1994.438878	56.1	100.0	V	29.0	-7.8	17.9	74.0
2661.072144	48.4	142.0	V	1.0	-4.8	25.6	74.0

Frequency (MHz)	CAverage (dBuV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1331.913828	31.8	150.0	V	13.0	-9.3	22.2	54.0
1994.438878	38.3	100.0	V	29.0	-7.8	15.7	54.0
2661.072144	32.6	142.0	V	1.0	-4.8	21.4	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage

5. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	CAL Date
Conducted Emission					
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	01.13.2015
☒ LISN	EMCO	3816/2SH	9706-1070	1 year	04.07.2014
☒ LISN	Rohde & Schwarz	ENV216	100073	1 year	01.13.2015
☒ Software	Rohde & Schwarz	EMC32	-	-	-
Radiated Emission					
-For measurement below 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07. 2014
☒ Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	11.17 2014
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒ Turn Table	EMCO	1060-2M	-	N/A	-
☒ Turn Table controller	EMCO	2090	9702-1224	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18.2014
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	04.07. 2014
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒ Turn Table	EMCO	1060-2M	-	N/A	-
☒ Turn Table controller	EMCO	2090	9702-1224	N/A	-
☐ Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.11.2014
☒ Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.11. 2014
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	12.13. 2012
☐ Horn Antenna	Schwarzbeck	BBHA 9120D	1151	2 year	07.05.2013
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	06.18. 2014
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☐ Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170124	2 year	10.30. 2013
☐ Power Amplifier	CERNEX	CBL18265035	22966	1 year	07.23. 2014
☐ Power Amplifier	CERNEX	CBL26405040	19660	1 year	04.04. 2014
☒ Software	Rohde & Schwarz	EMC32	-	-	-

6. CONCLUSION

The data collected shows that the **EUT Type: Cellular/PCS GSM/WCDMA Phone with WLAN and Bluetooth**, **FCC ID: ZNFH500F, Model: LG-H500f** complies with §15.107 and §15.109 of the FCC rules.