

FCC/IC WLAN DTS REPORT

FCC/IC Certification

Applicant Name:

LG Electronics MobileComm U.S.A., Inc.

Address:

1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Issue:

April 28, 2015

Test Site/Location:

HCT CO., LTD., 74,Seoicheon-ro 578beon-gil,Majang-myeo,Icheon-si, Gyeonggi-do, Korea

Report No.: HCT-R-1504-F012-2

HCT FRN: 0005866421

IC Recognition No.: 5944A-3

FCC ID**ZNFH815****IC****2703C-H815****APPLICANT****LG Electronics MobileComm U.S.A., Inc.****FCC/IC Model(s):**

LG-H815

FCC/IC Additional Model(s):

LGH815, H815, LG-H815P, LGH815P, H815P, LG-H815p, LGH815p, H815p, LG-H815L, LGH815L, H815L, LG-H815I, LGH815I, H815I, LG-H815AR, LGH815AR, H815AR, LG-H815ar, LGH815ar, H815ar, LG-H815K, LGH815K, H815K, LG-H815k, LGH815k, H815k

EUT Type:

Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/LTE Phone with Bluetooth, WLAN, NFC

Max. RF Output Power:

Wi-Fi 802.11b (22.82 dBm) / Wi-Fi 802.11g (21.61 dBm)/

Frequency Range:

Wi-Fi 802.11n _20MHz (21.30 dBm)/ Wi-Fi 802.11ac _20MHz (20.74 dBm)

Modulation type:

2412 MHz - 2462 MHz (2.4 GHz Band)

FCC Classification:

CCK/DSSS/OFDM

FCC Rule Part(s):

Digital Transmission System(DTS)

IC Rule :

Part 15.247

RSS-210 Issue 8(February 2015), RSS-GEN Issue 4(November 2014)

Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)



Report prepared by

: Kyung Soo Kang

Test engineer of RF Team



Approved by

: Sang Jun Lee

Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1504-F012	April 20, 2015	- First Approval Report
HCT-R-1504-F012-1	April 23, 2015	- Revised the Test Mode for Radiated Emissions and EUT Type
HCT-R-1504-F012-2	April 28, 2015	- Revised the Test Description on page 4 - Revised the Test Mode for Radiated Emissions

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE	5
3.3 GENERAL TEST PROCEDURES	5
3.4 DESCRIPTION OF TEST MODES	5
4. INSTRUMENT CALIBRATION.....	6
5. FACILITIES AND ACCREDITATIONS	6
5.1 FACILITIES	6
5.2 EQUIPMENT	6
6. ANTENNA REQUIREMENTS	7
7. SUMMARY TEST OF RESULTS	8
7.1 FCC Part	8
7.2 IC Part	9
8. TEST RESULT	10
8.1 DUTY CYCLE (802.11b/g/n/ac)	10
8.2 6dB BANDWIDTH (802.11b/g/n/ac)	12
8.3 99% BANDWIDTH (802.11b/g/n/ac).....	16
8.4 OUTPUT POWER(802.11b/g/n/ac).....	20
8.5 POWER SPECTRAL DENSITY (802.11b/g/n/ac).....	29
8.6 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS ...	33
8.7 RADIATED MEASUREMENT.....	47
8.7.1 RADIATED SPURIOUS EMISSIONS.....	47
8.7.2 RECEIVER SPURIOUS EMISSIONS	77
8.7.3 RADIATED RESTRICTED BAND EDGES	78
8.8 POWERLINE CONDUCTED EMISSIONS	85
9. LIST OF TEST EQUIPMENT	94
9.1 LIST OF TEST EQUIPMENT(Conducted Test)	94
9.2 LIST OF TEST EQUIPMENT(Radiated Test).....	95

1. GENERAL INFORMATION

Applicant: LG Electronics MobileComm U.S.A., Inc
Address: 1000 Sylvan Avenue, Englewood Cliffs NJ 07632
FCC ID: ZNFH815
IC: 2703C-H815
EUT Type: Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/LTE Phone with Bluetooth, WLAN, NFC
FCC/ IC Model name(s): LG-H815
FCC/ IC Additional Model name(s): LGH815, H815, LG-H815P, LGH815P, H815P, LG-H815p, LGH815p, H815p, LG-H815L, LGH815L, H815L, LG-H815I, LGH815I, H815I, LG-H815AR, LGH815AR, H815AR, LG-H815ar, LGH815ar, H815ar, LG-H815K, LGH815K, H815K, LG-H815k, LGH815k, H815k
Date(s) of Tests: March 27, 2015 ~ April 06, 2015
Place of Tests: HCT Co., Ltd.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea.
(IC Recognition No. : 5944A-3)

2. EUT DESCRIPTION

EUT Type	Cellular/PCS GSM/GPRS/EDGE/WCDMA/HSDPA/HSUPA/LTE Phone with Bluetooth, WLAN, NFC	
FCC/IC Model Name	LG-H815	
FCC/IC Additional Model Name	LGH815, H815, LG-H815P, LGH815P, H815P, LG-H815p, LGH815p, H815p, LG-H815L, LGH815L, H815L, LG-H815I, LGH815I, H815I, LG-H815AR, LGH815AR, H815AR, LG-H815ar, LGH815ar, H815ar, LG-H815K, LGH815K, H815K, LG-H815k, LGH815k, H815k	
Power Supply	DC 3.8 V	
Frequency Range	TX	: 2412 MHz~2462 MHz
	RX	: 2412 MHz~2462 MHz
Max. RF Output Power	Peak	Wi-Fi 802.11b(22.82 dBm) / Wi-Fi 802.11g (21.61 dBm) / Wi-Fi 802.11n_20MHz (21.30 dBm) / Wi-Fi 802.11ac_20MHz (20.74 dBm)
	Average	Wi-Fi 802.11b(16.86 dBm) / Wi-Fi 802.11g (13.84dBm) / Wi-Fi 802.11n_20MHz (12.82 dBm) / Wi-Fi 802.11ac_20MHz (12.41 dBm)
Modulation Type	DSSS/CCK(802.11b), OFDM(802.11g, 802.11n, 802.11ac)	
Antenna Specification	Manufacturer: Koma-tech.com Antenna type:FPCB Antenna Peak Gain : 0.03 dBi	

3. TEST METHODOLOGY

FCC KDB 558074 D01 DTS Meas Guidance v03r02 dated June 05, 2014 entitled "Guidance for Performing Compliance Measurements on Digital Transmission Systems(DTS) Operating Under §15.247" and the measurement procedure described in the American National Standard for Testing Unlicensed Wireless Devices(ANSI C63.4-2003) were used in the measurement.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version :2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average Measurement Type or modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4. (Version: 2003)

Conducted Antenna Terminal

See Section from 9.1 to 9.2.(KDB 558074)

3.4 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel low, mid and high with highest data rate (worst case) is chosen for full testing.

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2003) and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated February 28, 2014 (Registration Number: 90661)

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak Measurement Typeors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

6. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

* The antennas of this E.U.T are permanently attached.

*The E.U.T Complies with the requirement of §15.203

7. SUMMARY TEST OF RESULTS

7.1 FCC Part

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§15.247(a)(2)	> 500 kHz	CONDUCTED	PASS
Conducted Maximum Peak Output Power	§15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	§15.247(d)	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	cf. Section 8.8		PASS
Radiated Spurious Emissions	§15.205, 15.209	cf. Section 8.7.1	RADIATED	PASS
Radiated Restricted Band Edge	§15.205, 15.209	cf. Section 8.7.3		PASS

7.2 IC Part

Test Description	IC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	RSS-210, A8.2(a)	> 500 kHz	CONDUCTED	PASS
99% Bandwidth	RSS-GEN, 6.6	N/A		N/A
Conducted Maximum Peak Output Power And e.i.r.p.	RSS-210, A8.4(4)	< 1 Watt <4 Watt(e.i.r.p.)		PASS
Power Spectral Density	RSS-210, A8.2(b)	< 8 dBm / 3 kHz Band		PASS
Band Edge(Out of Band Emissions)	RSS-210, A8.5	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	RSS-GEN, 8.8	cf. Section 8.8		PASS
Radiated Spurious Emissions	RSS-210, 2.2, RSS-GEN, 8.9, 8.10	cf. Section 8.7.1	RADIATED	PASS
Receiver Spurious Emissions	RSS-GEN, 7.1.2	cf. Section 8.7.2		PASS
Radiated Restricted Band Edge	RSS-210, 2.2, RSS-GEN, 8.9, 8.10	cf. Section 8.7.3		PASS

8. TEST RESULT


8.1 DUTY CYCLE (802.11b/g/n/ac)

■ TEST PROCEDURE

According to KDB558074(6)b), issued 06/05/2014)

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set Measurement Type or = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0)b) in KDB 558074(issued 06/05/2014)

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz ($\geq$ RBW)
3. SPAN = 0 Hz
4. Measurement Type or = Peak
5. Number of points in sweep > 100
6. Trace mode = Clear write
7. Measure T_{total} and T_{on}
8. Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor = $10 \cdot \log(1/\text{Duty Cycle})$

Duty Cycle Factor

Mode	Data Rate	T _{on} (ms)	T _{total} (ms)	Duty Cycle	Duty Cycle Factor (dB)
2.4 GHz Band 802.11b	1	12.360	12.510	0.98800959	0.052
	2	6.150	6.300	0.97619048	0.105
	5.5	2.313	2.418	0.95657568	0.193
	11	1.198	1.303	0.91941673	0.365
2.4 GHz Band 802.11g	6	2.058	2.167	0.94970005	0.224
	9	1.367	1.483	0.92178018	0.354
	12	1.038	1.146	0.90575916	0.430
	18	0.702	0.807	0.86988848	0.605
	24	0.528	0.633	0.83412322	0.788
	36	0.364	0.467	0.77944325	1.082
	48	0.275	0.378	0.72751323	1.382
	54	0.247	0.351	0.70370370	1.526
2.4 GHz Band 802.11n_20 MHz BW	6.5	1.910	2.020	0.94554455	0.243
	13	0.970	1.080	0.89814815	0.467
	19.5	0.655	0.765	0.85620915	0.674
	26	0.504	0.610	0.82622951	0.829
	39	0.348	0.452	0.76991150	1.136
	52	0.268	0.374	0.71657754	1.447
	58.5	0.244	0.350	0.69714286	1.567
	65	0.226	0.330	0.68484848	1.644
2.4 GHz Band 802.11ac_ 20 MHz BW	6.5	1.921	2.034	0.94444444	0.248
	13	0.986	1.092	0.90293040	0.443
	19.5	0.668	0.774	0.86304910	0.640
	26	0.512	0.618	0.82847896	0.817
	39	0.354	0.458	0.77292576	1.119
	52	0.278	0.382	0.72774869	1.380
	58.5	0.250	0.354	0.70621469	1.511
	65	0.228	0.334	0.68263473	1.658
	78	0.198	0.302	0.65562914	1.833


8.2 6dB BANDWIDTH (802.11b/g/n/ac)

Test Requirements and limit, §15.247(a)(2)

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Page 5 in KDB 558074, issued 06/05/2014)

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Measurement Type or = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize

Note : We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.

TEST RESULTS

2.4 GHz Band

Conducted 6dB Bandwidth Measurements for 802.11b

802.11b Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	8.09	0.500	Pass
2437	6	8.08	0.500	Pass
2462	11	7.61	0.500	Pass

Conducted 6dB Bandwidth Measurements for 802.11g

802.11g Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	15.15	0.500	Pass
2437	6	16.42	0.500	Pass
2462	11	15.08	0.500	Pass

Conducted 6dB Bandwidth Measurements for 802.11n_20 MHz BW

802.11n Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	15.17	0.500	Pass
2437	6	17.66	0.500	Pass
2462	11	15.11	0.500	Pass

Conducted 6dB Bandwidth Measurements for 802.11ac_20 MHz BW


802.11n Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
Frequency [MHz]	Channel No.			
2412	1	15.70	0.500	Pass
2437	6	17.66	0.500	Pass
2462	11	15.12	0.500	Pass

Note : In order to simplify the report, attached plots were only the most wide 6 dB BW channel.


RESULT PLOTS

2.4 GHz Band


6dB Bandwidth plot (802.11b-CH 1)




6dB Bandwidth plot (802.11g-CH 6)



6dB Bandwidth plot (802.11n-CH 6)_20 MHz BW



6dB Bandwidth plot (802.11ac-CH 6)_20 MHz BW




8.3 99% BANDWIDTH (802.11b/g/n/ac)

limit

None; for IC reporting purposes only

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to as close to 1% of the selected span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RBW = 1% of the total span

VBW $\geq 3 \times$ RBW

Measurement Type or = Peak

Trace mode = max hold

Sweep = auto couple

Allow the trace to stabilize

TEST RESULTS

2.4 GHz Band

Conducted 99% Bandwidth Measurements for 802.11b

802.11b Mode		Measured Bandwidth [MHz]
Frequency [MHz]	Channel No.	
2412	1	10.811
2437	6	10.668
2462	11	10.379

Conducted 99% Bandwidth Measurements for 802.11g

802.11g Mode		Measured Bandwidth [MHz]
Frequency [MHz]	Channel No.	
2412	1	16.631
2437	6	17.312
2462	11	16.308

Conducted 99% Bandwidth Measurements for 802.11n_20 MHz BW

802.11n Mode		Measured Bandwidth [MHz]
Frequency [MHz]	Channel No.	
2412	1	17.752
2437	6	18.341
2462	11	17.373

Conducted 99% Bandwidth Measurements for 802.11ac_20 MHz BW


802.11n Mode		Measured Bandwidth [MHz]
Frequency [MHz]	Channel No.	
2412	1	17.731
2437	6	18.299
2462	11	17.414

Note : In order to simplify the report, attached plots were only the most wide 99 % BW channel.


RESULT PLOTS

2.4 GHz Band


99% Bandwidth plot (802.11b-CH1)




99% Bandwidth plot (802.11g-CH6)



99% Bandwidth plot (802.11n-CH6)_20 MHz BW



99% Bandwidth plot (802.11ac-CH6)_20 MHz BW




8.4 OUTPUT POWER(802.11b/g/n/ac)

Test Requirements and limit, §15.247(b)(3)

The transmitter output is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

■ TEST CONFIGURATION(20 MHz BW)



■ TEST PROCEDURE(20 MHz BW)

- Peak Power (Procedure 9.1.3 in KDB 558074, issued 06/05/2014)
 1. Measure the peak power of the transmitter.
- Average Power (Procedure 9.2.3.1 in KDB 558074, issued 06/05/2014)
 1. Measure the duty cycle.
 2. Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
 3. Add $10 \log (1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

Note :

1. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.2 dB is offset for 2.4 GHz Band.

Actual value of loss for the attenuator and cable combination is below table.

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.21
	2437	10.24
	2462	10.24

(Actual value of loss for the attenuator and cable combination)

2.4 GHz Band

■ TEST RESULTS

Conducted Output Power Measurements (802.11b Mode)

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	1 Mbps	18.14	30
		2 Mbps	19.12	30
		5.5 Mbps	20.29	30
		11 Mbps	21.87	30
2437	6	1 Mbps	18.88	30
		2 Mbps	19.39	30
		5.5 Mbps	20.99	30
		11 Mbps	22.57	30
2462	11	1 Mbps	19.33	30
		2 Mbps	19.72	30
		5.5 Mbps	20.81	30
		11 Mbps	22.82	30

■ TEST RESULTS

Conducted Output Power Measurements (802.11g Mode)

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6 Mbps	21.25	30
		9 Mbps	21.17	30
		12 Mbps	20.83	30
		18 Mbps	20.96	30
		24 Mbps	21.46	30
		36 Mbps	21.61	30
		48 Mbps	21.42	30
		54 Mbps	21.30	30
2437	6	6 Mbps	21.31	30
		9 Mbps	21.24	30
		12 Mbps	21.02	30
		18 Mbps	20.98	30
		24 Mbps	21.58	30
		36 Mbps	21.49	30
		48 Mbps	21.46	30
		54 Mbps	21.44	30
2462	11	6 Mbps	20.48	30
		9 Mbps	20.33	30
		12 Mbps	20.14	30
		18 Mbps	20.23	30
		24 Mbps	20.79	30
		36 Mbps	20.99	30
		48 Mbps	20.71	30
		54 Mbps	20.72	30

TEST RESULTS

Conducted Output Power Measurements (802.11n Mode)_ 20 MHz BW

802.11n Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6.5 Mbps	19.68	30
		13 Mbps	19.79	30
		19.5 Mbps	19.72	30
		26 Mbps	20.65	30
		39 Mbps	20.58	30
		52 Mbps	20.55	30
		58.5 Mbps	20.73	30
		65 Mbps	20.48	30
2437	6	6.5 Mbps	20.56	30
		13 Mbps	20.55	30
		19.5 Mbps	20.46	30
		26 Mbps	21.30	30
		39 Mbps	21.25	30
		52 Mbps	21.17	30
		58.5 Mbps	21.24	30
		65 Mbps	21.27	30
2462	11	6.5 Mbps	19.12	30
		13 Mbps	19.02	30
		19.5 Mbps	19.01	30
		26 Mbps	19.89	30
		39 Mbps	19.96	30
		52 Mbps	19.96	30
		58.5 Mbps	20.05	30
		65 Mbps	20.06	30

TEST RESULTS

Conducted Output Power Measurements (802.11ac Mode)_ 20 MHz BW

802.11ac Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6.5 Mbps	19.21	30
		13 Mbps	19.13	30
		19.5 Mbps	18.99	30
		26 Mbps	19.93	30
		39 Mbps	19.96	30
		52 Mbps	19.88	30
		58.5 Mbps	19.92	30
		65 Mbps	19.76	30
2437	6	6.5 Mbps	19.85	30
		13 Mbps	19.87	30
		19.5 Mbps	19.64	30
		26 Mbps	19.88	30
		39 Mbps	20.74	30
		52 Mbps	20.54	30
		58.5 Mbps	20.52	30
		65 Mbps	20.60	30
2462	11	6.5 Mbps	20.57	30
		13 Mbps	20.58	30
		19.5 Mbps	19.47	30
		26 Mbps	19.24	30
		39 Mbps	19.26	30
		52 Mbps	20.23	30
		58.5 Mbps	20.14	30
		65 Mbps	20.13	30

■ TEST RESULTS-Average

2.4 GHz Band

■ TEST RESULTS

Conducted Output Power Measurements (802.11b Mode)

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	1 Mbps	15.65	0.052	15.70	30
		2 Mbps	15.78	0.105	15.88	30
		5.5 Mbps	15.63	0.193	15.82	30
		11 Mbps	15.53	0.365	15.89	30
2437	6	1 Mbps	16.27	0.052	16.32	30
		2 Mbps	16.24	0.105	16.34	30
		5.5 Mbps	16.28	0.193	16.48	30
		11 Mbps	16.06	0.365	16.43	30
2462	11	1 Mbps	16.58	0.052	16.63	30
		2 Mbps	16.76	0.105	16.86	30
		5.5 Mbps	16.44	0.193	16.63	30
		11 Mbps	16.48	0.365	16.84	30

■ TEST RESULTS

Conducted Output Power Measurements (802.11g Mode)

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	6 Mbps	13.05	0.224	13.27	30
		9 Mbps	12.84	0.354	13.20	30
		12 Mbps	12.79	0.430	13.22	30
		18 Mbps	12.92	0.605	13.52	30
		24 Mbps	12.62	0.788	13.41	30
		36 Mbps	12.37	1.082	13.45	30
		48 Mbps	12.15	1.382	13.53	30
		54 Mbps	11.77	1.526	13.30	30
2437	6	6 Mbps	13.08	0.224	13.31	30
		9 Mbps	13.21	0.354	13.57	30
		12 Mbps	13.24	0.430	13.67	30
		18 Mbps	12.60	0.605	13.21	30
		24 Mbps	13.05	0.788	13.84	30
		36 Mbps	12.32	1.082	13.40	30
		48 Mbps	12.21	1.382	13.59	30
		54 Mbps	11.91	1.526	13.44	30
2462	11	6 Mbps	12.48	0.224	12.70	30
		9 Mbps	12.20	0.354	12.55	30
		12 Mbps	12.48	0.430	12.91	30
		18 Mbps	12.04	0.605	12.65	30
		24 Mbps	12.07	0.788	12.86	30
		36 Mbps	11.86	1.082	12.94	30
		48 Mbps	11.80	1.382	13.18	30
		54 Mbps	11.68	1.526	13.21	30

TEST RESULTS

Conducted Output Power Measurements (802.11n Mode)

802.11n Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	6.5 Mbps	12.09	0.243	12.33	30
		13 Mbps	11.54	0.467	12.01	30
		19.5 Mbps	11.32	0.674	11.99	30
		26 Mbps	11.54	0.829	12.37	30
		39 Mbps	11.30	1.136	12.44	30
		52 Mbps	11.17	1.447	12.62	30
		58.5 Mbps	10.93	1.567	12.50	30
		65 Mbps	10.95	1.644	12.59	30
2437	6	6.5 Mbps	12.24	0.243	12.48	30
		13 Mbps	12.05	0.467	12.52	30
		19.5 Mbps	11.88	0.674	12.55	30
		26 Mbps	11.97	0.829	12.80	30
		39 Mbps	11.60	1.136	12.73	30
		52 Mbps	11.37	1.447	12.82	30
		58.5 Mbps	11.24	1.567	12.81	30
		65 Mbps	11.15	1.644	12.79	30
2462	11	6.5 Mbps	10.89	0.243	11.14	30
		13 Mbps	11.03	0.467	11.49	30
		19.5 Mbps	10.62	0.674	11.29	30
		26 Mbps	10.75	0.829	11.58	30
		39 Mbps	10.62	1.136	11.76	30
		52 Mbps	10.20	1.447	11.64	30
		58.5 Mbps	10.14	1.567	11.71	30
		65 Mbps	10.10	1.644	11.74	30

TEST RESULTS

Conducted Output Power Measurements (802.11ac Mode) _20 MHz BW

802.11ac Mode		Rate (Mbps)	Measured Power(dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	6.5 Mbps	10.88	0.248	11.12	30
		13 Mbps	10.71	0.443	11.16	30
		19.5 Mbps	10.58	0.640	11.22	30
		26 Mbps	10.77	0.817	11.59	30
		39 Mbps	10.49	1.119	11.61	30
		52 Mbps	10.15	1.380	11.53	30
		58.5 Mbps	9.99	1.511	11.51	30
		65 Mbps	9.85	1.658	11.51	30
2437	6	6.5 Mbps	9.73	1.833	11.57	30
		13 Mbps	11.51	0.248	11.75	30
		19.5 Mbps	11.32	0.443	11.77	30
		26 Mbps	11.26	0.640	11.90	30
		39 Mbps	11.35	0.817	12.17	30
		52 Mbps	11.03	1.119	12.15	30
		58.5 Mbps	10.65	1.380	12.03	30
		65 Mbps	10.46	1.511	11.97	30
2462	11	6.5 Mbps	10.47	1.658	12.13	30
		13 Mbps	10.57	1.833	12.41	30
		19.5 Mbps	11.14	0.248	11.39	30
		26 Mbps	10.92	0.443	11.36	30
		39 Mbps	10.71	0.640	11.35	30
		52 Mbps	10.96	0.817	11.77	30
		58.5 Mbps	10.70	1.119	11.82	30
		65 Mbps	10.38	1.380	11.76	30


8.5 POWER SPECTRAL DENSITY (802.11b/g/n/ac)

Test Requirements and limit, §15.247(e)

The peak power spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard – the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

■ TEST CONFIGURATION



■ TEST PROCEDURE

We tested according to Procedure 10.2 in KDB 558074, issued 06/05/2014

The spectrum analyzer is set to :

Set analyzer center frequency to DTS channel center frequency.

Span = 1.5 times the DTS channel bandwidth.

RBW = 3 kHz ≤ RBW ≤ 100 kHz.

VBW ≥ 3 x RBW.

Sweep = auto couple

Detector = peak

Trace Mode = max hold

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

■ Sample Calculation

PSD = Reading Value + ATT loss + Cable loss(1 ea)

Output Power = -5 dBm + 10 dB + 0.8 dB = 5.8 dBm

Note :

1. Spectrum reading values are not plot data. The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. So, 10.2 dB is offset for 2.4 GHz Band.

Actual value of loss for the attenuator and cable combination is below table.

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.21
	2437	10.24
	2462	10.24

(Actual value of loss for the attenuator and cable combination)

TEST RESULTS

Conducted Power Density Measurements

Frequency (MHz)	Channel No.	Mode	Test Result		
			PSD (dBm)	Limit (dBm)	Pass/Fail
2412	1	802.11b	-5.246	8	Pass
2437	6		-6.239		Pass
2462	11		-5.321		Pass
2412	1	802.11g	-12.154		Pass
2437	6		-11.735		Pass
2462	11		-11.796		Pass
2412	1	802.11n (20 MHz BW)	-11.969		Pass
2437	6		-13.356		Pass
2462	11		-11.838		Pass
2412	1	802.11ac (20 MHz BW)	-14.224		Pass
2437	6		-13.055		Pass
2462	11		-11.477		Pass


Note :

- In order to simplify the report, attached plots were only the highest PSD channel.


RESULT PLOTS

2.4 GHz Band


Power Spectral Density (802.11b-CH 1)




Power Spectral Density (802.11g-CH 6)



Power Spectral Density (802.11n-CH 11)_ 20 MHz BW



Power Spectral Density (802.11ac-CH 11)_ 20 MHz BW




8.6 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit : 20 dBc

■ TEST CONFIGURATION



■ TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. (Procedure 11.0 in KDB 558074, issued 06/05/2014)

RBW = 100 kHz

VBW $\geq 3 \times$ RBW

Set span to encompass the spectrum to be examined

Measurement Type or = Peak

Trace Mode = max hold

Sweep time = auto couple

Ensure that the number of measurement points $\geq$ Span/RBW

Allow trace to fully stabilize.

Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 10th harmonic range with the transmitter set to the lowest, middle, and highest channels.

Note :

1. The band edge results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss

3. We apply to the offset in the 2.4 GHz range that was rounded off to the closest tenth dB. Actual value of loss for the attenuator and cable combination is below table.

Band	Loss(dB)
2.4 GHz	10.2

(Actual value of loss for the attenuator and cable combination)

4. In order to simplify the report, attached plots were only the worst case channel and data rate.

■ FACTORS FOR FREQUENCY

Freq(MHz)	Factor(dB)
30	9.95
100	10.01
200	10.03
300	10.04
400	10.05
500	10.04
600	10.03
700	10.09
800	10.10
900	10.08
1000	10.11
2000	10.25
2400*	10.19
2500*	10.24
3000	10.27
4000	10.22
5000	10.48
5700*	10.42
5800*	10.44
6000	10.48
7000	10.57
8000	10.45
9000	10.50
10000	10.64
11000	10.69
12000	10.75
13000	10.92
14000	11.90

15000	11.00
16000	11.03
17000	10.93
18000	10.96
19000	10.85
20000	12.11
21000	11.17
22000	10.99
23000	11.12
24000	11.10
25000	11.42
26000	11.28


Note : 1. '*' is fundamental frequency range.

2. Factor = Cable loss + Attenuator loss


RESULT PLOTS

2.4 GHz Band


BandEdge (802.11b-CH1)




BandEdge (802.11b-CH11)




BandEdge (802.11g-CH1)




BandEdge (802.11g-CH11)




Band Edge (802.11n-CH1) _20 MHz BW




Band Edge (802.11n-CH11) _20 MHz BW



Band Edge (802.11ac-CH1) _20 MHz BW




Band Edge (802.11ac-CH11) _20 MHz BW




2.4 GHz Band
30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11b-CH11)




1 GHz ~ 3 GHz

Conducted Spurious Emission (802.11b-CH11)




3 GHz ~ 5 GHz

Conducted Spurious Emission (802.11b-CH11)




5 GHz ~ 7 GHz

Conducted Spurious Emission (802.11b-CH11)




7 GHz ~ 9 GHz

Conducted Spurious Emission (802.11b-CH11)




9 GHz ~ 11 GHz

Conducted Spurious Emission (802.11b-CH11)




11 GHz ~ 13 GHz

Conducted Spurious Emission (802.11b-CH11)




13 GHz ~ 15 GHz

Conducted Spurious Emission (802.11b-CH11)




15 GHz ~ 17 GHz

Conducted Spurious Emission (802.11b-CH11)




17 GHz ~ 19 GHz

Conducted Spurious Emission (802.11b-CH11)




19 GHz ~ 21 GHz

19nducted Spurious Emission (802.11b-CH11)




21 GHz ~ 23 GHz

Conducted Spurious Emission (802.11b-CH11)



23 GHz ~ 25 GHz

Conducted Spurious Emission (802.11b-CH11)



8.7 RADIATED MEASUREMENT

8.7.1 RADIATED SPURIOUS EMISSIONS.

Test Requirements and limit, §15.205, §15.209


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Mode


- Standalone with normal cover
- Standalone with wireless charging cover (open)
- Standalone with wireless charging cover (close)
- With wireless charging pad

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE USED

Method 12.1 in KDB 558074, issued 06/05/2014

Spectrum Setting

- Peak

Peak emission levels are measured by setting the instrument as follows:

RBW = cf. Table 1.

VBW $\geq 3 \times$ RBW.

Measurement Type or = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes.

(Note that the required measurement time may be longer for low duty cycle applications).

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

- Average

Set RBW = 1 MHz

Set VBW $\geq 1/T$. (at least 100 times less than the resolution bandwidth, but no less than 10 Hz.)

Select spectrum analyzer linear display mode.

Measurement Type or = Peak.

Sweep time = auto.

Trace mode = max hold.

Note : The actual setting value of VBW for 802.11b/g/n.

Mode	Worst Data rate (Mbps)	T _{on} (ms)	T _{total} (ms)	Duty Cycle (%)	VBW(1/T) (Hz)	The actual setting value of VBW (Hz)
b	1	12.360	12.510	98.80	81	1000
g	6	2.058	2.167	94.97	486	1000
n_20 MHz BW	6.5	1.910	2.020	94.55	524	1000
ac_20 MHz BW	6.5	1.921	2.034	94.44	521	1000

TEST RESULTS**9 kHz – 30MHz****Operation Mode:** Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V/m	dBm /m	dBm	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
4. Limit line = specific Limits (dB μ V) + Distance extrapolation factor
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typing antenna.

TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	$\text{dB}\mu\text{V}/\text{m}$	dBm/m	dBm	(H/V)	$\text{dB}\mu\text{V}/\text{m}$	$\text{dB}\mu\text{V}/\text{m}$	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak Measurement Type or mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

Standalone with normal cover

Above 1 GHz

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	48.84	-1.98	V	46.86	73.98	27.12	PK
4824	35.63	-1.98	V	33.65	53.98	20.33	AV
7236	47.05	7.60	V	54.65	73.98	19.33	PK
7236	32.69	7.60	V	40.29	53.98	13.69	AV
4824	48.98	-1.98	H	47.00	73.98	26.98	PK
4824	35.66	-1.98	H	33.68	53.98	20.30	AV
7236	47.32	7.60	H	54.92	73.98	19.06	PK
7236	32.69	7.60	H	40.29	53.98	13.69	AV

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	50.13	-1.92	V	48.21	73.98	25.77	PK
4874	36.13	-1.92	V	34.21	53.98	19.77	AV
7311	46.94	7.38	V	54.32	73.98	19.66	PK
7311	32.88	7.38	V	40.26	53.98	13.72	AV
4874	50.52	-1.92	H	48.60	73.98	25.38	PK
4874	36.14	-1.92	H	34.22	53.98	19.76	AV
7311	47.34	7.38	H	54.72	73.98	19.26	PK
7311	32.90	7.38	H	40.28	53.98	13.70	AV

Operation Mode: 802.11 b
Transfer Rate: 1 Mbps
Operating Frequency: 2462
Channel No.: 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.92	-1.93	V	46.99	73.98	26.99	PK
4924	35.12	-1.93	V	33.19	53.98	20.79	AV
7386	45.76	7.28	V	53.04	73.98	20.94	PK
7386	32.09	7.28	V	39.37	53.98	14.61	AV
4924	49.34	-1.93	H	47.41	73.98	26.57	PK
4924	35.15	-1.93	H	33.22	53.98	20.76	AV
7386	46.10	7.28	H	53.38	73.98	20.60	PK
7386	32.13	7.28	H	39.41	53.98	14.57	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11b mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

Operation Mode: 802.11 g
Transfer Rate: 6 Mbps
Operating Frequency: 2412
Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	48.87	-1.98	V	46.89	73.98	27.09	PK
4824	35.65	-1.98	V	33.67	53.98	20.31	AV
7236	46.76	7.60	V	54.36	73.98	19.62	PK
7236	32.65	7.60	V	40.25	53.98	13.73	AV
4824	49.54	-1.98	H	47.56	73.98	26.42	PK
4824	35.71	-1.98	H	33.73	53.98	20.25	AV
7236	47.49	7.60	H	55.09	73.98	18.89	PK
7236	32.69	7.60	H	40.29	53.98	13.69	AV

Operation Mode: 802.11 g
Transfer Rate: 6 Mbps
Operating Frequency: 2437
Channel No.: 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.96	-1.92	V	48.04	73.98	25.94	PK
4874	36.12	-1.92	V	34.20	53.98	19.78	AV
7311	47.14	7.38	V	54.52	73.98	19.46	PK
7311	32.94	7.38	V	40.32	53.98	13.66	AV
4874	50.38	-1.92	H	48.46	73.98	25.52	PK
4874	36.18	-1.92	H	34.26	53.98	19.72	AV
7311	47.16	7.38	H	54.54	73.98	19.44	PK
7311	32.95	7.38	H	40.33	53.98	13.65	AV

Operation Mode:	802.11 g
Transfer Rate:	6 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.40	-1.93	V	46.47	73.98	27.51	PK
4924	35.16	-1.93	V	33.23	53.98	20.75	AV
7386	45.75	7.28	V	53.03	73.98	20.95	PK
7386	32.08	7.28	V	39.36	53.98	14.62	AV
4924	48.79	-1.93	H	46.86	73.98	27.12	PK
4924	35.28	-1.93	H	33.35	53.98	20.63	AV
7386	46.41	7.28	H	53.69	73.98	20.29	PK
7386	32.11	7.28	H	39.39	53.98	14.59	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11g mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

Operation Mode: 802.11 n_20 MHz BW
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2412
 Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	49.07	-1.98	V	47.09	73.98	26.89	PK
4824	35.64	-1.98	V	33.66	53.98	20.32	AV
7236	46.55	7.60	V	54.15	73.98	19.83	PK
7236	32.65	7.60	V	40.25	53.98	13.73	AV
4824	49.15	-1.98	H	47.17	73.98	26.81	PK
4824	35.66	-1.98	H	33.68	53.98	20.30	AV
7236	46.75	7.60	H	54.35	73.98	19.63	PK
7236	32.73	7.60	H	40.33	53.98	13.65	AV

Operation Mode: 802.11 n_20 MHz BW
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2437
 Channel No.: 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.91	-1.92	V	47.99	73.98	25.99	PK
4874	36.13	-1.92	V	34.21	53.98	19.77	AV
7311	46.83	7.38	V	54.21	73.98	19.77	PK
7311	32.96	7.38	V	40.34	53.98	13.64	AV
4874	50.11	-1.92	H	48.19	73.98	25.79	PK
4874	36.15	-1.92	H	34.23	53.98	19.75	AV
7311	47.09	7.38	H	54.47	73.98	19.51	PK
7311	33.07	7.38	H	40.45	53.98	13.53	AV

Operation Mode:	802.11 n_20 MHz BW
Transfer Rate:	6.5 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.95	-1.93	V	47.02	73.98	26.96	PK
4924	35.11	-1.93	V	33.18	53.98	20.80	AV
7386	46.31	7.28	V	53.59	73.98	20.39	PK
7386	32.15	7.28	V	39.43	53.98	14.55	AV
4924	49.16	-1.93	H	47.23	73.98	26.75	PK
4924	35.26	-1.93	H	33.33	53.98	20.65	AV
7386	46.54	7.28	H	53.82	73.98	20.16	PK
7386	32.19	7.28	H	39.47	53.98	14.51	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11n mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

Operation Mode: 802.11 ac_20 MHz BW
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2412
 Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	48.95	-1.98	V	46.97	73.98	27.01	PK
4824	35.67	-1.98	V	33.69	53.98	20.29	AV
7236	46.85	7.60	V	54.45	73.98	19.53	PK
7236	32.63	7.60	V	40.23	53.98	13.75	AV
4824	49.17	-1.98	H	47.19	73.98	26.79	PK
4824	35.70	-1.98	H	33.72	53.98	20.26	AV
7236	47.17	7.60	H	54.77	73.98	19.21	PK
7236	32.70	7.60	H	40.30	53.98	13.68	AV

Operation Mode: 802.11 ac_20 MHz BW
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2437
 Channel No.: 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.76	-1.92	V	47.84	73.98	26.14	PK
4874	36.15	-1.92	V	34.23	53.98	19.75	AV
7311	46.93	7.38	V	54.31	73.98	19.67	PK
7311	32.97	7.38	V	40.35	53.98	13.63	AV
4874	50.12	-1.92	H	48.20	73.98	25.78	PK
4874	36.17	-1.92	H	34.25	53.98	19.73	AV
7311	47.06	7.38	H	54.44	73.98	19.54	PK
7311	32.98	7.38	H	40.36	53.98	13.62	AV

Operation Mode:	802.11 ac_20 MHz BW
Transfer Rate:	6.5 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.79	-1.93	V	46.86	73.98	27.12	PK
4924	35.10	-1.93	V	33.17	53.98	20.81	AV
7386	45.86	7.28	V	53.14	73.98	20.84	PK
7386	32.09	7.28	V	39.37	53.98	14.61	AV
4924	48.99	-1.93	H	47.06	73.98	26.92	PK
4924	35.14	-1.93	H	33.21	53.98	20.77	AV
7386	45.89	7.28	H	53.17	73.98	20.81	PK
7386	32.18	7.28	H	39.46	53.98	14.52	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11ac mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

Standalone with wireless charging cover (open)

Above 1 GHz

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	49.60	-1.98	V	47.62	73.98	26.36	PK
4824	35.71	-1.98	V	33.73	53.98	20.25	AV
7236	46.61	7.60	V	54.21	73.98	19.77	PK
7236	32.37	7.60	V	39.97	53.98	14.01	AV
4824	49.72	-1.98	H	47.74	73.98	26.24	PK
4824	35.84	-1.98	H	33.86	53.98	20.12	AV
7236	46.43	7.60	H	54.03	73.98	19.95	PK
7236	32.52	7.60	H	40.12	53.98	13.86	AV

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.87	-1.92	V	47.95	73.98	26.03	PK
4874	36.04	-1.92	V	34.12	53.98	19.86	AV
7311	46.59	7.38	V	53.97	73.98	20.01	PK
7311	32.99	7.38	V	40.37	53.98	13.61	AV
4874	49.92	-1.92	H	48.00	73.98	25.98	PK
4874	36.22	-1.92	H	34.30	53.98	19.68	AV
7311	46.61	7.38	H	53.99	73.98	19.99	PK
7311	32.96	7.38	H	40.34	53.98	13.64	AV

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	49.18	-1.93	V	47.25	73.98	26.73	PK
4924	35.79	-1.93	V	33.86	53.98	20.12	AV
7386	45.82	7.28	V	53.10	73.98	20.88	PK
7386	32.35	7.28	V	39.63	53.98	14.35	AV
4924	48.81	-1.93	H	46.88	73.98	27.10	PK
4924	35.82	-1.93	H	33.89	53.98	20.09	AV
7386	45.74	7.28	H	53.02	73.98	20.96	PK
7386	32.24	7.28	H	39.52	53.98	14.46	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11b mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.
7. We were attached the results of standalone with wireless charging cover (open). Because the results of open condition is higher than close condition.

Operation Mode: 802.11 g
Transfer Rate: 6 Mbps
Operating Frequency: 2412
Channel No. 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	49.03	-1.98	V	47.05	73.98	26.93	PK
4824	35.92	-1.98	V	33.94	53.98	20.04	AV
7236	46.02	7.60	V	53.62	73.98	20.36	PK
7236	32.61	7.60	V	40.21	53.98	13.77	AV
4824	49.38	-1.98	H	47.40	73.98	26.58	PK
4824	35.64	-1.98	H	33.66	53.98	20.32	AV
7236	46.31	7.60	H	53.91	73.98	20.07	PK
7236	32.29	7.60	H	39.89	53.98	14.09	AV

Operation Mode: 802.11 g
Transfer Rate: 6 Mbps
Operating Frequency: 2437
Channel No. 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.53	-1.92	V	47.61	73.98	26.37	PK
4874	36.37	-1.92	V	34.45	53.98	19.53	AV
7311	46.37	7.38	V	53.75	73.98	20.23	PK
7311	32.38	7.38	V	39.76	53.98	14.22	AV
4874	49.13	-1.92	H	47.21	73.98	26.77	PK
4874	36.15	-1.92	H	34.23	53.98	19.75	AV
7311	46.05	7.38	H	53.43	73.98	20.55	PK
7311	32.48	7.38	H	39.86	53.98	14.12	AV

Operation Mode:	802.11 g
Transfer Rate:	6 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.84	-1.93	V	46.91	73.98	27.07	PK
4924	35.61	-1.93	V	33.68	53.98	20.30	AV
7386	46.08	7.28	V	53.36	73.98	20.62	PK
7386	32.73	7.28	V	40.01	53.98	13.97	AV
4924	48.83	-1.93	H	46.90	73.98	27.08	PK
4924	35.61	-1.93	H	33.68	53.98	20.30	AV
7386	45.79	7.28	H	53.07	73.98	20.91	PK
7386	32.13	7.28	H	39.41	53.98	14.57	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11g mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typing antenna.
7. We were attached the results of standalone with wireless charging cover (open). Because the results of open condition is higher than close condition.

Operation Mode: 802.11 n_20 MHz BW

Transfer Rate: 6.5 Mbps

Operating Frequency: 2412

Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	49.25	-1.98	V	47.27	73.98	26.71	PK
4824	36.13	-1.98	V	34.15	53.98	19.83	AV
7236	46.38	7.60	V	53.98	73.98	20.00	PK
7236	32.19	7.60	V	39.79	53.98	14.19	AV
4824	49.57	-1.98	H	47.59	73.98	26.39	PK
4824	35.38	-1.98	H	33.40	53.98	20.58	AV
7236	46.28	7.60	H	53.88	73.98	20.10	PK
7236	32.42	7.60	H	40.02	53.98	13.96	AV

Operation Mode: 802.11 n_20 MHz BW

Transfer Rate: 6.5 Mbps

Operating Frequency: 2437

Channel No.: 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.10	-1.92	V	47.18	73.98	26.80	PK
4874	36.22	-1.92	V	34.30	53.98	19.68	AV
7311	46.14	7.38	V	53.52	73.98	20.46	PK
7311	32.67	7.38	V	40.05	53.98	13.93	AV
4874	49.60	-1.92	H	47.68	73.98	26.30	PK
4874	36.13	-1.92	H	34.21	53.98	19.77	AV
7311	46.18	7.38	H	53.56	73.98	20.42	PK
7311	32.58	7.38	H	39.96	53.98	14.02	AV

Operation Mode:	802.11 n_20 MHz BW
Transfer Rate:	6.5 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	49.52	-1.93	V	47.59	73.98	26.39	PK
4924	36.50	-1.93	V	34.57	53.98	19.41	AV
7386	45.87	7.28	V	53.15	73.98	20.83	PK
7386	32.47	7.28	V	39.75	53.98	14.23	AV
4924	49.29	-1.93	H	47.36	73.98	26.62	PK
4924	35.73	-1.93	H	33.80	53.98	20.18	AV
7386	45.81	7.28	H	53.09	73.98	20.89	PK
7386	32.73	7.28	H	40.01	53.98	13.97	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11n mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typing antenna.
7. We were attached the results of standalone with wireless charging cover (open). Because the results of open condition is higher than close condition.

Operation Mode: 802.11 ac_20 MHz BW

Transfer Rate: 6.5 Mbps

Operating Frequency: 2412

Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	49.36	-1.98	V	47.38	73.98	26.60	PK
4824	35.42	-1.98	V	33.44	53.98	20.54	AV
7236	45.54	7.60	V	53.14	73.98	20.84	PK
7236	32.20	7.60	V	39.80	53.98	14.18	AV
4824	48.83	-1.98	H	46.85	73.98	27.13	PK
4824	35.58	-1.98	H	33.60	53.98	20.38	AV
7236	45.43	7.60	H	53.03	73.98	20.95	PK
7236	32.05	7.60	H	39.65	53.98	14.33	AV

Operation Mode: 802.11 n_20 MHz BW

Transfer Rate: 6.5 Mbps

Operating Frequency: 2437

Channel No.: 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.49	-1.92	V	47.57	73.98	26.41	PK
4874	35.88	-1.92	V	33.96	53.98	20.02	AV
7311	46.15	7.38	V	53.53	73.98	20.45	PK
7311	32.73	7.38	V	40.11	53.98	13.87	AV
4874	49.52	-1.92	H	47.60	73.98	26.38	PK
4874	35.97	-1.92	H	34.05	53.98	19.93	AV
7311	46.32	7.38	H	53.70	73.98	20.28	PK
7311	32.76	7.38	H	40.14	53.98	13.84	AV

Operation Mode:	802.11 n_20 MHz BW
Transfer Rate:	6.5 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	49.61	-1.93	V	47.68	73.98	26.30	PK
4924	35.67	-1.93	V	33.74	53.98	20.24	AV
7386	46.25	7.28	V	53.53	73.98	20.45	PK
7386	32.47	7.28	V	39.75	53.98	14.23	AV
4924	49.50	-1.93	H	47.57	73.98	26.41	PK
4924	35.76	-1.93	H	33.83	53.98	20.15	AV
7386	46.11	7.28	H	53.39	73.98	20.59	PK
7386	32.58	7.28	H	39.86	53.98	14.12	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11ac mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.
7. We were attached the results of standalone with wireless charging cover (open). Because the results of open condition is higher than close condition.

With wireless Charging Pad

Above 1 GHz

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	48.87	-1.98	V	46.89	73.98	27.09	PK
4824	36.24	-1.98	V	34.26	53.98	19.72	AV
7236	46.02	7.60	V	53.62	73.98	20.36	PK
7236	32.27	7.60	V	39.87	53.98	14.11	AV
4824	49.29	-1.98	H	47.31	73.98	26.67	PK
4824	37.04	-1.98	H	35.06	53.98	18.92	AV
7236	46.39	7.60	H	53.99	73.98	19.99	PK
7236	32.29	7.60	H	39.89	53.98	14.09	AV

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.65	-1.92	V	47.73	73.98	26.25	PK
4874	35.79	-1.92	V	33.87	53.98	20.11	AV
7311	46.43	7.38	V	53.81	73.98	20.17	PK
7311	33.03	7.38	V	40.41	53.98	13.57	AV
4874	49.71	-1.92	H	47.79	73.98	26.19	PK
4874	35.82	-1.92	H	33.90	53.98	20.08	AV
7311	46.31	7.38	H	53.69	73.98	20.29	PK
7311	33.08	7.38	H	40.46	53.98	13.52	AV

Operation Mode: 802.11 b
 Transfer Rate: 1 Mbps
 Operating Frequency: 2462
 Channel No.: 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.74	-1.93	V	46.81	73.98	27.17	PK
4924	34.87	-1.93	V	32.94	53.98	21.04	AV
7386	45.81	7.28	V	53.09	73.98	20.89	PK
7386	32.09	7.28	V	39.37	53.98	14.61	AV
4924	48.60	-1.93	H	46.67	73.98	27.31	PK
4924	34.99	-1.93	H	33.06	53.98	20.92	AV
7386	45.67	7.28	H	52.95	73.98	21.03	PK
7386	32.13	7.28	H	39.41	53.98	14.57	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11b mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

Operation Mode: 802.11 g
Transfer Rate: 6 Mbps
Operating Frequency: 2412
Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	48.47	-1.98	V	46.49	73.98	27.49	PK
4824	35.61	-1.98	V	33.63	53.98	20.35	AV
7236	46.40	7.60	V	54.00	73.98	19.98	PK
7236	32.31	7.60	V	39.91	53.98	14.07	AV
4824	48.28	-1.98	H	46.30	73.98	27.68	PK
4824	35.63	-1.98	H	33.65	53.98	20.33	AV
7236	46.33	7.60	H	53.93	73.98	20.05	PK
7236	32.27	7.60	H	39.87	53.98	14.11	AV

Operation Mode: 802.11 g
Transfer Rate: 6 Mbps
Operating Frequency: 2437
Channel No.: 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.52	-1.92	V	47.60	73.98	26.38	PK
4874	35.77	-1.92	V	33.85	53.98	20.13	AV
7311	46.22	7.38	V	53.60	73.98	20.38	PK
7311	32.98	7.38	V	40.36	53.98	13.62	AV
4874	49.43	-1.92	H	47.51	73.98	26.47	PK
4874	35.80	-1.92	H	33.88	53.98	20.10	AV
7311	46.74	7.38	H	54.12	73.98	19.86	PK
7311	33.04	7.38	H	40.42	53.98	13.56	AV

Operation Mode: 802.11 g

Transfer Rate: 6 Mbps

Operating Frequency: 2462

Channel No.: 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.77	-1.93	V	46.84	73.98	27.14	PK
4924	34.88	-1.93	V	32.95	53.98	21.03	AV
7386	45.73	7.28	V	53.01	73.98	20.97	PK
7386	32.04	7.28	V	39.32	53.98	14.66	AV
4924	48.52	-1.93	H	46.59	73.98	27.39	PK
4924	34.94	-1.93	H	33.01	53.98	20.97	AV
7386	45.66	7.28	H	52.94	73.98	21.04	PK
7386	32.11	7.28	H	39.39	53.98	14.59	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11g mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

Operation Mode: 802.11 n_20 MHz BW
Transfer Rate: 6.5 Mbps
Operating Frequency: 2412
Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	48.27	-1.98	V	46.29	73.98	27.69	PK
4824	35.59	-1.98	V	33.61	53.98	20.37	AV
7236	46.33	7.60	V	53.93	73.98	20.05	PK
7236	32.28	7.60	V	39.88	53.98	14.10	AV
4824	48.32	-1.98	H	46.34	73.98	27.64	PK
4824	35.61	-1.98	H	33.63	53.98	20.35	AV
7236	46.28	7.60	H	53.88	73.98	20.10	PK
7236	32.24	7.60	H	39.84	53.98	14.14	AV

Operation Mode: 802.11 n_20 MHz BW
Transfer Rate: 6.5 Mbps
Operating Frequency: 2437
Channel No.: 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.33	-1.92	V	47.41	73.98	26.57	PK
4874	35.74	-1.92	V	33.82	53.98	20.16	AV
7311	46.28	7.38	V	53.66	73.98	20.32	PK
7311	32.96	7.38	V	40.34	53.98	13.64	AV
4874	49.25	-1.92	H	47.33	73.98	26.65	PK
4874	32.78	-1.92	H	30.86	53.98	23.12	AV
7311	46.45	7.38	H	53.83	73.98	20.15	PK
7311	33.03	7.38	H	40.41	53.98	13.57	AV

Operation Mode:	802.11 n_20 MHz BW
Transfer Rate:	6.5 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.65	-1.93	V	46.72	73.98	27.26	PK
4924	34.87	-1.93	V	32.94	53.98	21.04	AV
7386	45.67	7.28	V	52.95	73.98	21.03	PK
7386	32.01	7.28	V	39.29	53.98	14.69	AV
4924	48.22	-1.93	H	46.29	73.98	27.69	PK
4924	32.91	-1.93	H	30.98	53.98	23.00	AV
7386	45.72	7.28	H	53.00	73.98	20.98	PK
7386	32.07	7.28	H	39.35	53.98	14.63	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11n mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

Operation Mode: 802.11 ac_20 MHz BW
Transfer Rate: 6.5 Mbps
Operating Frequency: 2412
Channel No.: 01 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	48.32	-1.98	V	46.34	73.98	27.64	PK
4824	35.57	-1.98	V	33.59	53.98	20.39	AV
7236	46.27	7.60	V	53.87	73.98	20.11	PK
7236	32.26	7.60	V	39.86	53.98	14.12	AV
4824	48.43	-1.98	H	46.45	73.98	27.53	PK
4824	35.60	-1.98	H	33.62	53.98	20.36	AV
7236	46.22	7.60	H	53.82	73.98	20.16	PK
7236	32.23	7.60	H	39.83	53.98	14.15	AV

Operation Mode: 802.11 n_20 MHz BW
Transfer Rate: 6.5 Mbps
Operating Frequency: 2437
Channel No.: 06 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	49.43	-1.92	V	47.51	73.98	26.47	PK
4874	35.73	-1.92	V	33.81	53.98	20.17	AV
7311	46.01	7.38	V	53.39	73.98	20.59	PK
7311	32.94	7.38	V	40.32	53.98	13.66	AV
4874	49.22	-1.92	H	47.30	73.98	26.68	PK
4874	32.77	-1.92	H	30.85	53.98	23.13	AV
7311	46.48	7.38	H	53.86	73.98	20.12	PK
7311	33.00	7.38	H	40.38	53.98	13.60	AV

Operation Mode:	802.11 n_20 MHz BW
Transfer Rate:	6.5 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL-AMP G [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	48.25	-1.93	V	46.32	73.98	27.66	PK
4924	34.87	-1.93	V	32.94	53.98	21.04	AV
7386	45.87	7.28	V	53.15	73.98	20.83	PK
7386	31.99	7.28	V	39.27	53.98	14.71	AV
4924	48.43	-1.93	H	46.50	73.98	27.48	PK
4924	32.89	-1.93	H	30.96	53.98	23.02	AV
7386	45.63	7.28	H	52.91	73.98	21.07	PK
7386	32.05	7.28	H	39.33	53.98	14.65	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak Measurement Type or mode and average Measurement Type or mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. We have done 802.11ac mode and all data rate. Worst data rate is the lowest data of each mode.
6. We have done x, y, z planes in EUT and horizontal and vertical polarization in Measurement Typeing antenna.

8.7.2 RECEIVER SPURIOUS EMISSIONS

IC Rule(s) RSS-GEN
Test Requirements: Below the table
Operating conditions: Under normal test conditions
Method of testing: Radiated

S/A. Settings: F < 1 GHz: RBW: 120 kHz, VBW: 300 kHz (Quasi Peak)
 F > 1 GHz: RBW: 1 MHz, VBW: 1 MHz (Peak)
Mode of operation: Receive

Frequency (MHz)	Field Strength (microvolts/m at 3 meters)
30 – 88	100
88 - 216	150
216 – 960	200
Above 960	500

Operation Mode: Receive:

30 MHz ~ 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Above 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

8.7.3 RADIATED RESTRICTED BAND EDGES

Test Requirements and limit, §15.247(d) §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Standalone with normal cover

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.64	31.47	H	57.11	73.98	16.87	PK
2390.0	12.34	31.47	H	43.81	53.98	10.17	AV
2390.0	25.64	31.47	V	57.11	73.98	16.87	PK
2390.0	12.53	31.47	V	44.00	53.98	9.98	AV
2483.5	30.09	31.46	H	61.55	73.98	12.43	PK
2483.5	16.45	31.46	H	47.91	53.98	6.07	AV
2483.5	28.68	31.46	V	60.14	73.98	13.84	PK
2483.5	14.41	31.46	V	45.87	53.98	8.11	AV

Operation Mode: 802.11g
Transfer Rate: 6 Mbps
Operating Frequency: 2412 MHz, 2462 MHz
Channel No.: 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.71	31.47	H	57.18	73.98	16.80	PK
2390.0	12.37	31.47	H	43.84	53.98	10.14	AV
2390.0	25.39	31.47	V	56.86	73.98	17.12	PK
2390.0	12.28	31.47	V	43.75	53.98	10.23	AV
2483.5	28.05	31.46	H	59.51	73.98	14.47	PK
2483.5	14.07	31.46	H	45.53	53.98	8.45	AV
2483.5	25.03	31.46	V	56.49	73.98	17.49	PK
2483.5	12.52	31.46	V	43.98	53.98	10.00	AV

Operation Mode: 802.11n_ 20 MHz BW
Transfer Rate: 6.5 Mbps
Operating Frequency: 2412 MHz, 2462 MHz
Channel No.: 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.11	31.47	H	56.58	73.98	17.40	PK
2390.0	12.28	31.47	H	43.75	53.98	10.23	AV
2390.0	25.08	31.47	V	56.55	73.98	17.43	PK
2390.0	12.30	31.47	V	43.77	53.98	10.21	AV
2483.5	29.38	31.46	H	60.84	73.98	13.14	PK
2483.5	13.55	31.46	H	45.01	53.98	8.97	AV
2483.5	25.62	31.46	V	57.08	73.98	16.90	PK
2483.5	12.40	31.46	V	43.86	53.98	10.12	AV

Operation Mode: 802.11ac_ 20 MHz BW

Transfer Rate: 6.5 Mbps

Operating Frequency 2412 MHz, 2462 MHz

Channel No. 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.55	31.47	H	57.02	73.98	16.96	PK
2390.0	12.34	31.47	H	43.81	53.98	10.17	AV
2390.0	25.53	31.47	V	57.00	73.98	16.98	PK
2390.0	12.32	31.47	V	43.79	53.98	10.19	AV
2483.5	28.76	31.46	H	60.22	73.98	13.76	PK
2483.5	13.34	31.46	H	44.80	53.98	9.18	AV
2483.5	25.48	31.46	V	56.94	73.98	17.04	PK
2483.5	12.04	31.46	V	43.50	53.98	10.48	AV

Standalone with wireless charging cover (open)

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.83	31.47	H	57.30	73.98	16.68	PK
2390.0	12.54	31.47	H	44.01	53.98	9.97	AV
2390.0	25.97	31.47	V	57.44	73.98	16.54	PK
2390.0	12.71	31.47	V	44.18	53.98	9.80	AV
2483.5	30.51	31.46	H	61.97	73.98	12.01	PK
2483.5	16.27	31.46	H	47.73	53.98	6.25	AV
2483.5	28.82	31.46	V	60.28	73.98	13.70	PK
2483.5	14.38	31.46	V	45.84	53.98	8.14	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	26.19	31.47	H	57.66	73.98	16.32	PK
2390.0	12.54	31.47	H	44.01	53.98	9.97	AV
2390.0	25.74	31.47	V	57.21	73.98	16.77	PK
2390.0	12.31	31.47	V	43.78	53.98	10.20	AV
2483.5	25.91	31.46	H	57.37	73.98	16.61	PK
2483.5	13.09	31.46	H	44.55	53.98	9.43	AV
2483.5	25.24	31.46	V	56.70	73.98	17.28	PK
2483.5	12.73	31.46	V	44.19	53.98	9.79	AV

Operation Mode: 802.11n_20 MHz BW
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2412 MHz, 2462 MHz
 Channel No.: 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.29	31.47	H	56.76	73.98	17.22	PK
2390.0	12.37	31.47	H	43.84	53.98	10.14	AV
2390.0	25.24	31.47	V	56.71	73.98	17.27	PK
2390.0	12.40	31.47	V	43.87	53.98	10.11	AV
2483.5	29.61	31.46	H	61.07	73.98	12.91	PK
2483.5	13.29	31.46	H	44.75	53.98	9.23	AV
2483.5	26.13	31.46	V	57.59	73.98	16.39	PK
2483.5	12.58	31.46	V	44.04	53.98	9.94	AV

Operation Mode: 802.11ac_20 MHz BW
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2412 MHz, 2462 MHz
 Channel No.: 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.67	31.47	H	57.14	73.98	16.84	PK
2390.0	12.53	31.47	H	44.00	53.98	9.98	AV
2390.0	25.67	31.47	V	57.14	73.98	16.84	PK
2390.0	12.28	31.47	V	43.75	53.98	10.23	AV
2483.5	28.57	31.46	H	60.03	73.98	13.95	PK
2483.5	13.10	31.46	H	44.56	53.98	9.42	AV
2483.5	25.63	31.46	V	57.09	73.98	16.89	PK
2483.5	12.15	31.46	V	43.61	53.98	10.37	AV

Wireless Charging Pad

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.57	31.47	H	57.04	73.98	16.94	PK
2390.0	12.30	31.47	H	43.77	53.98	10.21	AV
2390.0	25.39	31.47	V	56.86	73.98	17.12	PK
2390.0	12.27	31.47	V	43.74	53.98	10.24	AV
2483.5	32.16	31.46	H	63.62	73.98	10.36	PK
2483.5	16.37	31.46	H	47.83	53.98	6.15	AV
2483.5	27.02	31.46	V	58.48	73.98	15.50	PK
2483.5	13.34	31.46	V	44.80	53.98	9.18	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	26.19	31.47	H	57.66	73.98	16.32	PK
2390.0	12.28	31.47	H	43.75	53.98	10.23	AV
2390.0	26.02	31.47	V	57.49	73.98	16.49	PK
2390.0	12.27	31.47	V	43.74	53.98	10.24	AV
2483.5	27.05	31.46	H	58.51	73.98	15.47	PK
2483.5	13.36	31.46	H	44.82	53.98	9.16	AV
2483.5	25.17	31.46	V	56.63	73.98	17.35	PK
2483.5	11.91	31.46	V	43.37	53.98	10.61	AV

Operation Mode: 802.11n_20 MHz BW
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2412 MHz, 2462 MHz
 Channel No.: 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	26.15	31.47	H	57.62	73.98	16.36	PK
2390.0	12.30	31.47	H	43.77	53.98	10.21	AV
2390.0	25.61	31.47	V	57.08	73.98	16.90	PK
2390.0	12.28	31.47	V	43.75	53.98	10.23	AV
2483.5	26.47	31.46	H	57.93	73.98	16.05	PK
2483.5	12.90	31.46	H	44.36	53.98	9.62	AV
2483.5	24.79	31.46	V	56.25	73.98	17.73	PK
2483.5	11.90	31.46	V	43.36	53.98	10.62	AV

Operation Mode: 802.11ac_20 MHz BW
 Transfer Rate: 6.5 Mbps
 Operating Frequency: 2412 MHz, 2462 MHz
 Channel No.: 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV/m]	AN.+CL [dBm]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	25.99	31.47	H	57.46	73.98	16.52	PK
2390.0	12.45	31.47	H	43.92	53.98	10.06	AV
2390.0	25.83	31.47	V	57.30	73.98	16.68	PK
2390.0	12.31	31.47	V	43.78	53.98	10.20	AV
2483.5	25.45	31.46	H	56.91	73.98	17.07	PK
2483.5	12.81	31.46	H	44.27	53.98	9.71	AV
2483.5	24.99	31.46	V	56.45	73.98	17.53	PK
2483.5	11.92	31.46	V	43.38	53.98	10.60	AV

8.8 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.
5. We performed the AC Power Line Conducted Emission test for 11 Mbps, Ch.11 and 802.11b .
Because 802.11b mode is worst case.

Stand alone

RESULT PLOTS

Conducted Emissions (Line 1)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG-H815
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: WLAN MODE(2.4 G)
 Operator Name: KS KANG

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	29.6	9.000	Off	N	9.6	36.4	66.0
0.158000	29.2	9.000	Off	N	9.6	36.4	65.6
0.168000	28.1	9.000	Off	N	9.6	37.0	65.1
0.172000	27.2	9.000	Off	N	9.6	37.7	64.9
0.184000	26.7	9.000	Off	N	9.6	37.6	64.3
0.214000	27.0	9.000	Off	N	9.6	36.0	63.0
2.128000	38.0	9.000	Off	N	9.8	18.0	56.0
2.176000	36.2	9.000	Off	N	9.8	19.8	56.0
2.180000	36.5	9.000	Off	N	9.8	19.5	56.0
2.278000	30.7	9.000	Off	N	9.8	25.3	56.0
2.284000	31.1	9.000	Off	N	9.8	24.9	56.0
2.292000	32.4	9.000	Off	N	9.8	23.6	56.0
15.404000	36.2	9.000	Off	N	10.2	23.8	60.0
15.536000	36.0	9.000	Off	N	10.2	24.0	60.0
15.638000	36.8	9.000	Off	N	10.2	23.2	60.0
15.658000	36.2	9.000	Off	N	10.2	23.8	60.0

4/2/2015

1:14:03

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
15.728000	36.5	9.000	Off	N	10.2	23.5	60.0
15.754000	37.4	9.000	Off	N	10.2	22.6	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	16.8	9.000	Off	N	9.6	39.2	56.0
0.158000	17.0	9.000	Off	N	9.6	38.6	55.6
0.174000	16.1	9.000	Off	N	9.6	38.7	54.8
0.180000	15.5	9.000	Off	N	9.6	39.0	54.5
0.184000	14.9	9.000	Off	N	9.6	39.4	54.3
0.214000	15.7	9.000	Off	N	9.6	37.3	53.0
2.132000	28.6	9.000	Off	N	9.8	17.4	46.0
2.180000	27.0	9.000	Off	N	9.8	19.0	46.0
2.196000	24.3	9.000	Off	N	9.8	21.7	46.0
2.278000	21.3	9.000	Off	N	9.8	24.7	46.0
2.282000	21.6	9.000	Off	N	9.8	24.4	46.0
2.292000	22.6	9.000	Off	N	9.8	23.4	46.0
15.654000	26.4	9.000	Off	N	10.2	23.6	50.0
15.728000	26.8	9.000	Off	N	10.2	23.2	50.0
15.754000	27.3	9.000	Off	N	10.2	22.7	50.0
17.256000	24.6	9.000	Off	N	10.2	25.4	50.0
17.536000	24.6	9.000	Off	N	10.2	25.4	50.0
19.426000	19.9	9.000	Off	N	10.3	30.1	50.0

4/2/2015

1:14:03

Conducted Emissions (Line 2)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG-H815
Manufacturer: LG
Test Site: SHIELD ROOM
Operating Conditions: WLAN MODE(2.4 G)
Operator Name: KS KANG

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.458000	37.5	9.000	Off	L1	9.7	19.2	56.7
0.762000	34.2	9.000	Off	L1	9.7	21.8	56.0
0.774000	36.7	9.000	Off	L1	9.7	19.3	56.0
0.810000	35.6	9.000	Off	L1	9.7	20.4	56.0
0.860000	38.2	9.000	Off	L1	9.7	17.8	56.0
0.884000	39.7	9.000	Off	L1	9.7	16.3	56.0
1.982000	37.4	9.000	Off	L1	9.8	18.6	56.0
1.992000	35.0	9.000	Off	L1	9.8	21.0	56.0
2.012000	34.4	9.000	Off	L1	9.8	21.6	56.0
2.018000	34.0	9.000	Off	L1	9.8	22.0	56.0
2.120000	33.1	9.000	Off	L1	9.8	22.9	56.0
2.142000	38.6	9.000	Off	L1	9.8	17.4	56.0
14.492000	33.6	9.000	Off	L1	10.2	26.4	60.0
14.858000	34.8	9.000	Off	L1	10.2	25.2	60.0
14.880000	35.1	9.000	Off	L1	10.2	24.9	60.0
14.940000	35.0	9.000	Off	L1	10.2	25.0	60.0

4/2/2015

1:23:26

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
15.174000	34.9	9.000	Off	L1	10.2	25.1	60.0
15.274000	34.9	9.000	Off	L1	10.2	25.1	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.468000	24.2	9.000	Off	L1	9.7	22.5	46.7
0.760000	27.0	9.000	Off	L1	9.7	19.0	46.0
0.774000	27.5	9.000	Off	L1	9.7	18.5	46.0
0.808000	26.0	9.000	Off	L1	9.7	20.0	46.0
0.860000	27.5	9.000	Off	L1	9.7	18.5	46.0
0.884000	26.7	9.000	Off	L1	9.7	19.3	46.0
1.982000	25.9	9.000	Off	L1	9.8	20.1	46.0
1.992000	25.5	9.000	Off	L1	9.8	20.5	46.0
2.012000	25.1	9.000	Off	L1	9.8	20.9	46.0
2.018000	24.6	9.000	Off	L1	9.8	21.4	46.0
2.120000	23.4	9.000	Off	L1	9.8	22.6	46.0
2.142000	28.5	9.000	Off	L1	9.8	17.5	46.0
14.492000	24.0	9.000	Off	L1	10.2	26.0	50.0
14.890000	25.0	9.000	Off	L1	10.2	25.0	50.0
14.940000	24.5	9.000	Off	L1	10.2	25.5	50.0
15.174000	24.7	9.000	Off	L1	10.2	25.3	50.0
15.274000	24.1	9.000	Off	L1	10.2	25.9	50.0
15.420000	24.4	9.000	Off	L1	10.2	25.6	50.0

4/2/2015

1:23:26

Note : The worst case of Conducted Emission is standalone mode.

With wireless Charging pad

■ RESULT PLOTS

Conducted Emissions (Line 1)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG-H815
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: WLAN MODE(2.4 G)_WIRELESS CHARGING
 Operator Name: KS KANG

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.466000	40.0	9.000	Off	N	9.7	16.6	56.6
0.794000	38.6	9.000	Off	N	9.7	17.4	56.0
0.820000	39.9	9.000	Off	N	9.7	16.1	56.0
0.846000	40.3	9.000	Off	N	9.7	15.7	56.0
0.850000	39.3	9.000	Off	N	9.7	16.7	56.0
0.874000	40.5	9.000	Off	N	9.7	15.5	56.0
1.992000	43.9	9.000	Off	N	9.8	12.1	56.0
1.998000	44.9	9.000	Off	N	9.8	11.1	56.0
2.020000	44.0	9.000	Off	N	9.8	12.0	56.0
2.028000	44.1	9.000	Off	N	9.8	11.9	56.0
2.046000	43.9	9.000	Off	N	9.8	12.1	56.0
2.102000	43.7	9.000	Off	N	9.8	12.3	56.0
16.334000	38.8	9.000	Off	N	10.2	21.2	60.0
16.340000	38.5	9.000	Off	N	10.2	21.5	60.0
16.528000	38.7	9.000	Off	N	10.2	21.3	60.0
16.548000	38.6	9.000	Off	N	10.2	21.4	60.0

4/2/2015

3:48:30

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
16.714000	35.4	9.000	Off	N	10.2	24.6	60.0
16.722000	35.0	9.000	Off	N	10.2	25.0	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.462000	29.0	9.000	Off	N	9.7	17.7	46.7
0.710000	27.7	9.000	Off	N	9.7	18.3	46.0
0.736000	28.2	9.000	Off	N	9.7	17.8	46.0
0.820000	29.9	9.000	Off	N	9.7	16.1	46.0
0.846000	30.6	9.000	Off	N	9.7	15.4	46.0
0.872000	31.0	9.000	Off	N	9.7	15.0	46.0
1.992000	33.6	9.000	Off	N	9.8	12.4	46.0
2.040000	33.7	9.000	Off	N	9.8	12.3	46.0
2.046000	33.8	9.000	Off	N	9.8	12.2	46.0
2.100000	33.5	9.000	Off	N	9.8	12.5	46.0
2.132000	34.3	9.000	Off	N	9.8	11.7	46.0
2.154000	32.7	9.000	Off	N	9.8	13.3	46.0
15.180000	26.8	9.000	Off	N	10.2	23.2	50.0
16.334000	28.8	9.000	Off	N	10.2	21.2	50.0
16.340000	29.0	9.000	Off	N	10.2	21.0	50.0
16.508000	28.7	9.000	Off	N	10.2	21.3	50.0
16.528000	28.6	9.000	Off	N	10.2	21.4	50.0
16.722000	23.1	9.000	Off	N	10.2	26.9	50.0

4/2/2015

3:48:30

Conducted Emissions (Line 2)

EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG-H815
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: WLAN MODE(2.4 G)_WIRELESS CHARGING
 Operator Name: KS KANG

FCC CLASS B



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.460000	40.2	9.000	Off	L1	9.7	16.5	56.7
0.464000	39.5	9.000	Off	L1	9.7	17.1	56.6
0.788000	35.7	9.000	Off	L1	9.7	20.3	56.0
0.800000	41.2	9.000	Off	L1	9.7	14.8	56.0
0.816000	37.0	9.000	Off	L1	9.7	19.0	56.0
0.846000	37.3	9.000	Off	L1	9.7	18.7	56.0
2.012000	34.5	9.000	Off	L1	9.8	21.5	56.0
2.018000	33.0	9.000	Off	L1	9.8	23.0	56.0
2.066000	30.1	9.000	Off	L1	9.8	25.9	56.0
2.072000	33.7	9.000	Off	L1	9.8	22.3	56.0
2.088000	44.3	9.000	Off	L1	9.8	11.7	56.0
2.138000	43.9	9.000	Off	L1	9.8	12.1	56.0
14.762000	36.1	9.000	Off	L1	10.2	23.9	60.0
15.374000	34.2	9.000	Off	L1	10.2	25.8	60.0
15.734000	34.0	9.000	Off	L1	10.2	26.0	60.0
15.904000	33.7	9.000	Off	L1	10.2	26.3	60.0

4/2/2015

4:02:23

EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
16.486000	31.8	9.000	Off	L1	10.2	28.2	60.0
16.602000	31.1	9.000	Off	L1	10.2	28.9	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.460000	30.3	9.000	Off	L1	9.7	16.4	46.7
0.786000	26.3	9.000	Off	L1	9.7	19.7	46.0
0.802000	27.6	9.000	Off	L1	9.7	18.4	46.0
0.816000	28.5	9.000	Off	L1	9.7	17.5	46.0
0.846000	28.1	9.000	Off	L1	9.7	17.9	46.0
0.860000	28.3	9.000	Off	L1	9.7	17.7	46.0
1.972000	26.7	9.000	Off	L1	9.8	19.3	46.0
2.012000	25.2	9.000	Off	L1	9.8	20.8	46.0
2.064000	21.9	9.000	Off	L1	9.8	24.1	46.0
2.090000	33.4	9.000	Off	L1	9.8	12.6	46.0
2.114000	34.0	9.000	Off	L1	9.8	12.0	46.0
2.138000	35.5	9.000	Off	L1	9.8	10.5	46.0
14.816000	25.4	9.000	Off	L1	10.2	24.6	50.0
14.942000	25.1	9.000	Off	L1	10.2	24.9	50.0
15.374000	23.8	9.000	Off	L1	10.2	26.2	50.0
15.734000	23.7	9.000	Off	L1	10.2	26.3	50.0
15.872000	23.9	9.000	Off	L1	10.2	26.1	50.0
16.486000	22.4	9.000	Off	L1	10.2	27.6	50.0

4/2/2015

4:02:23

9. LIST OF TEST EQUIPMENT

9.1 LIST OF TEST EQUIPMENT(Conducted Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216/ LISN	01/13/2015	Annual	100073
Agilent	E4440A/ Spectrum Analyzer	03/18/2015	Annual	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	05/23/2014	Annual	MY51110063
Agilent	N1911A/Power Meter	01/15/2015	Annual	MY45100523
Agilent	N1921A /POWER SENSOR	07/09/2014	Annual	MY45241059
Agilent	87300B/Directional Coupler	12/08/2014	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	05/19/2014	Annual	11275
ITECH	IT6720 / DC POWER SUPPLY	11/04/2014	Annual	010002156287001199
Agilent	8493C / Attenuator(10 dB)	07/21/2014	Annual	76649

9.2 LIST OF TEST EQUIPMENT(Radiated Test)

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Schwarzbeck	VULB 9160/ TRILOG Antenna	10/10/2014	Biennial	3368
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	09/04/2014	Annual	10094
CERNEX	CBL18265035 / POWER AMP	07/23/2014	Annual	22966
Schwarzbeck	BBHA 9120D/ Horn Antenna	07/05/2013	Biennial	1151
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	07/05/2013	Biennial	BBHA9170541
Rohde & Schwarz	FSP / Spectrum Analyzer	10/23/2014	Annual	836650/016
Wainwright Instrument	WHF3.0/18G-10EF / High Pass Filter	06/23/2014	Annual	8
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	06/17/2014	Annual	1
Rohde & Schwarz	LOOP ANTENNA	09/03/2014	Biennial	1513-175
CERNEX	CBL06185030 / POWER AMP	07/21/2014	Annual	22965
CERNEX	CBLU1183540 / POWER AMP	07/21/2014	Annual	22964
Wireless Charging Pad	WCD-110	-	-	FCC ID : BEJWCD110