

On your side



TEST REPORT

EMI Test for FCC Certification of LM-K420TM Model

APPLICANT

LG Electronics USA, Inc.

REPORT NO.

HCT-EM-2012-FC012

DATE OF ISSUE

December 18, 2020

Tested by

Yeong-Moo Kim

A handwritten signature in black ink, appearing to be 'Y.M. Kim', written over a horizontal line.

Technical Manager

Jeong-Hyun Choi

A handwritten signature in black ink, appearing to be 'J.H. Choi', written over a horizontal line.

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA

Tel. +82 31 645 6300 Fax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

EMI Test for
FCC Certification

REPORT NO.

HCT-EM-2012-FC012

DATE OF ISSUE

December 18, 2020

FCC ID.

ZNFK420TM

Applicant

LG Electronics USA, Inc.

111 Sylvan Avenue, North Building , Englewood Cliffs NJ 07632 United States

Product Name

Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth

Model Name

LM-K420TM

Series Model Name

Refer to the clause 1.1 Description of EUT

Date of Test

December 03, 2020 to December 17, 2020

Test Standard Used

FCC CFR 47 PART 15 Subpart B Class B
ANSI C63.4-2014

Test Results

Refer to the present document

Manufacturer

LG Electronics Inc.

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	December 18, 2020	Initial Release

The above Test Report is not related to the accredited test result by (KS Q) ISO/IEC 17025 and KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation), which signed the ILAC-MRA.

* The report shall not be reproduced except in full (only partly) without approval of the laboratory.

CONTENTS

1. GENERAL INFORMATION	5
1.1 Description of EUT	5
1.2 Tested System Details	5
1.3 Cable Description	8
1.4 Noise Suppression Parts on Cable. (I/O Cable)	8
1.5 Test Facility	9
1.6 Calibration of Measuring Instrument	9
1.7 Measurement Uncertainty	9
2. DESCRIPTION OF TEST	10
2.1 Measurement of Conducted Emission	10
2.2 Measurement of Radiated Emission	11
2.3 Configuration of Tested System	12
3. PRELIMINARY TEST	13
3.1 Conducted Emission	13
3.2 Radiated Emission	13
4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY	14
4.1 Conducted Emission	14
4.2 Radiated Emission Below 1 GHz	21
4.3 Radiated Emission Above 1 GHz	23
5. CONCLUSION	25
6. APPENDIX A. TEST SETUP PHOTO	26

1. GENERAL INFORMATION

1.1 Description of EUT

FCC ID	ZNFK420TM
Model Name	LM-K420TM
Series Model Name	LMK420TM, K420TM, LM-K420MM, LMK420MM, K420MM, LM-K420PM, LMK420PM, K420PM, LG L560DL, LGL560DL, L560DL, LM-K420QM, LMK420QM, K420QM, LM-K420QM5, LMK420QM5, K420QM5, LM-K420QM6, LMK420QM6, K420QM6, LM-K420QA, LMK420QA, K420QA
Product Name	Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth
Frequency Range TX	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 817.90 MHz to 823.10 MHz (CDMA BC10) 824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 1 852.4 MHz to 1 907.6 MHz (WCDMA B2) 1712.4 MHz to 1752.6 MHz (WCDMA B4) 826.40 MHz to 846.60 MHz (WCDMA B5) 1 850 MHz to 1 910 MHz (LTE B2) 1 710 MHz to 1 755 MHz (LTE B4) 824 MHz to 849 MHz (LTE B5) 699 MHz to 716 MHz (LTE B12) 777 MHz to 787 MHz (LTE B13) 1 850 MHz to 1 915 MHz (LTE B25) 814 MHz to 849 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41) 2 496 MHz to 2 690 MHz (LTE B41 HPUE) 1 710 MHz to 1 780 MHz (LTE B66) 663 MHz to 698 MHz (LTE B71) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz) 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1) 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3)

**Frequency Range
RX**

869.70 MHz to 893.31 MHz (CDMA BC0)
1 931.25 MHz to 1 988.75 MHz (CDMA BC1)
862.00 MHz to 894.00 MHz (CDMA BC10)
869.20 MHz to 893.80 MHz (GSM 850)
1 930.20 MHz to 1 989.80 MHz (GSM 1 900)
1 932.4 MHz to 1 987.6 MHz (WCDMA B2)
2 112.4 MHz to 2 152.6 MHz (WCDMA B4)
871.40 MHz to 891.60 MHz (WCDMA B5)
1 930 MHz to 1 990 MHz (LTE B2)
2 110 MHz to 2 155 MHz (LTE B4)
869 MHz to 894 MHz (LTE B5)
729 MHz to 746 MHz (LTE B12)
746 MHz to 756 MHz (LTE B13)
1 925 MHz to 1 990 MHz (LTE B25)
859 MHz to 894 MHz (LTE B26)
2 496 MHz to 2 690 MHz (LTE B41)
2 496 MHz to 2 690 MHz (LTE B41 HPUE)
2 110 MHz to 2 200 MHz (LTE B66)
617 MHz to 652 MHz (LTE B71)
2 402 MHz to 2 480 MHz (Bluetooth)
2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)
5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1)
5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A)
5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C)
5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3)

1.2 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Serial Number	Manufacturer
EUT	LM-K420TM	-	LG
Notebook PC	ProBook6560b	5CB2053MXF	HP
Notebook PC Adaptor	Series PPP009L-E	-	LITE-ON TECHNOLOGY (CHANGZHOU)
Gateway	DIR-806M	-	D-Link
Gateway Adaptor	AMS1-0501200FK	-	D-Link
Serial Mouse	Serial 2 Button mouse	02031069	Radio Shack
RJ45 cable	-	-	-
DATA Cable	EAD64746101 (EAD64746103)	-	NINGBO
DATA Cable	EAD64746102		LUXSHARE
Earphone	EAB64468444	-	CRESYN
Micro SD Card	SAMSUNG EVO+ microSDXC CLASS10 UHS- I (256 GB)	-	SAMSUNG

1.3 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	USB Type C	Y	Y	(P,D) 1.0
	Earphone	N/A	N	(D) 1.2
Notebook PC	RJ 45	N/A	N	(D) 1.6
	Serial(Mouse)	N/A	Y	(D) 1.8
	DC IN	N	N/A	(P) 1.8
Gateway	DC IN	N	N/A	(P) 1.8

NOTE. The marked "(D)" means the data cable and "(P)" means the power cable.

1.4 Noise Suppression Parts on Cable (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	USB Type C	N	N/A	Y	Both End
	Earphone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial(Mouse)	N	N/A	Y	Notebook PC End

1.5 Test Facility

Test site is located at 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea.
Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014.
The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014.
Our laboratories are accredited and designated in accordance with the provisions of Radio Waves ACT and International Standard ISO/IEC 17025:2017. (National Radio Research Agency, Designation No. KR0032)

1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5:2017

1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty
Conducted Emission (0.15 MHz to 30 MHz)	1.58 dB
Radiated Emissions (30 MHz to 1 GHz)	4.86 dB
Radiated Emissions (1 GHz to 18 GHz)	4.58 dB
Radiated Emissions (18 GHz to 40 GHz)	5.54 dB

2. DESCRIPTION OF TEST

2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

Conducted Emission Limits

Frequency (MHz)	Resolution Bandwidth (kHz)	Class A		Class B	
		Quasi-Peak (dBμV)	Average (dBμV)	Quasi-Peak (dBμV)	Average (dBμV)
0.15 to 0.5	9	79	66	66 to 56*	56 to 46*
0.5 to 5	9	73	60	56	46
5 to 30	9	73	60	60	50

NOTE. Decreases with the logarithm of the frequency.

2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber.
The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
(1 GHz to 40 GHz)

Radiated Emission Limits


Frequency (MHz)	Class A			Class B		
	Antenna Distance (m)	Field Strength ($\mu\text{V/m}$)	Quasi-Peak (dB $\mu\text{V/m}$)	Antenna Distance (m)	Field Strength ($\mu\text{V/m}$)	Quasi-Peak (dB $\mu\text{V/m}$)
30 to 88	10	90	39.0	3	100	40.0
88 to 216	10	150	43.5	3	150	43.5
216 to 960	10	210	46.4	3	200	46.0
Above 960	10	300	49.5	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Class A		Class B		
		Peak (dB $\mu\text{V/m}$)	Average (dB $\mu\text{V/m}$)	Peak (dB $\mu\text{V/m}$)	Average (dB $\mu\text{V/m}$)	
Above 1 000	3	80	60	74	54	

2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

2.3 Configuration of Tested System



3. PRELIMINARY TEST

3.1 Conducted Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes: Data Communication mode

3.2 Radiated Emission

It was tested the following operating mode, after connecting all peripheral devices.

Operating Modes: Data Communication mode

4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission

4.1.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI Test Receiver	Rohde & Schwarz	ESR7	101910	1 year	09.16.2020
☒	LISN	Rohde & Schwarz	ENV216	102245	1 year	09.04.2020
☒	LISN	Rohde & Schwarz	ENV216	100073	1 year	04.27.2020
☒	Software	Rohde & Schwarz	EMC32	-	-	-


4.1.2 Operating Condition

The test results of conducted emission at mains ports provide the following information:

Test Standard Used	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Frequency Range	150 kHz to 30 MHz
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Worst Case of Data Cable	EAD64746101 (NINGBO)
Kind of Test Site	EMI Shielded Room
Temperature	21.8 °C
Relative Humidity	45.1 %
Test Date	December 17, 2020

4.1.3 Measuring Data

Figure 1: Conducted Emission, AC Main Port, Line (L1)



QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.152250	47.5	9.000	L1	9.8	18.4	65.9
0.159000	46.9	9.000	L1	9.8	18.6	65.5
0.188250	52.5	9.000	L1	9.8	11.6	64.1
0.242250	44.1	9.000	L1	9.7	17.9	62.0
0.249000	44.1	9.000	L1	9.7	17.6	61.8
0.377250	38.1	9.000	L1	9.7	20.3	58.3
4.106750	38.6	9.000	L1	9.8	17.4	56.0
4.111250	38.6	9.000	L1	9.8	17.4	56.0
4.151750	37.9	9.000	L1	9.8	18.1	56.0
4.237250	38.2	9.000	L1	9.8	17.8	56.0
4.280000	37.3	9.000	L1	9.8	18.7	56.0
4.408250	36.6	9.000	L1	9.9	19.4	56.0
5.193500	36.2	9.000	L1	9.9	23.8	60.0
9.421250	35.4	9.000	L1	10.0	24.6	60.0
9.529250	35.0	9.000	L1	10.0	25.0	60.0
9.542750	35.7	9.000	L1	10.0	24.3	60.0
9.610250	35.8	9.000	L1	10.0	24.2	60.0
9.675500	35.1	9.000	L1	10.0	24.9	60.0


Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	26.6	9.000	L1	9.8	29.4	56.0
0.188250	36.8	9.000	L1	9.8	17.3	54.1
0.228750	22.8	9.000	L1	9.7	29.7	52.5
0.246750	30.7	9.000	L1	9.7	21.1	51.9
0.314250	26.5	9.000	L1	9.7	23.4	49.9
0.375000	25.3	9.000	L1	9.7	23.1	48.4
4.023500	32.1	9.000	L1	9.8	13.9	46.0
4.046000	32.0	9.000	L1	9.8	14.0	46.0
4.109000	30.9	9.000	L1	9.8	15.1	46.0
4.154000	29.5	9.000	L1	9.8	16.5	46.0
4.167500	30.2	9.000	L1	9.8	15.8	46.0
4.228250	30.2	9.000	L1	9.8	15.8	46.0
9.405500	24.7	9.000	L1	10.0	25.3	50.0
9.421250	26.6	9.000	L1	10.0	23.4	50.0
9.540500	27.0	9.000	L1	10.0	23.0	50.0
9.574250	27.0	9.000	L1	10.0	23.0	50.0
9.621500	26.4	9.000	L1	10.0	23.6	50.0
9.675500	26.4	9.000	L1	10.0	23.6	50.0

Figure 2: Conducted Emission, AC Main Port, Line (N)



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.154500	47.7	9.000	N	9.7	18.1	65.8
0.188250	51.6	9.000	N	9.7	12.5	64.1
0.201750	47.3	9.000	N	9.7	16.3	63.5
0.224250	39.8	9.000	N	9.7	22.8	62.7
0.264750	43.1	9.000	N	9.7	18.2	61.3
0.273750	40.7	9.000	N	9.7	20.3	61.0
3.501500	39.9	9.000	N	9.8	16.2	56.0
3.562250	40.0	9.000	N	9.8	16.0	56.0
3.623000	39.4	9.000	N	9.8	16.6	56.0
3.683750	39.7	9.000	N	9.8	16.3	56.0
3.773750	38.9	9.000	N	9.8	17.1	56.0
3.897500	38.9	9.000	N	9.8	17.1	56.0
8.496500	31.2	9.000	N	9.9	28.8	60.0
8.627000	31.8	9.000	N	9.9	28.2	60.0
8.694500	31.7	9.000	N	9.9	28.3	60.0
8.757500	31.9	9.000	N	9.9	28.1	60.0
8.885750	32.0	9.000	N	9.9	28.0	60.0
9.016250	31.7	9.000	N	9.9	28.3	60.0

CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	26.9	9.000	N	9.7	29.1	56.0
0.190500	37.6	9.000	N	9.7	16.4	54.0
0.197250	37.0	9.000	N	9.7	16.7	53.7
0.226500	24.5	9.000	N	9.7	28.0	52.6
0.246750	30.6	9.000	N	9.7	21.2	51.9
0.260250	30.1	9.000	N	9.7	21.4	51.4
3.078500	30.1	9.000	N	9.8	15.9	46.0
3.200000	29.9	9.000	N	9.8	16.1	46.0
3.440750	30.3	9.000	N	9.8	15.7	46.0
3.501500	30.2	9.000	N	9.8	15.8	46.0
3.593750	30.2	9.000	N	9.8	15.8	46.0
3.773750	30.6	9.000	N	9.8	15.4	46.0
8.496500	20.6	9.000	N	9.9	29.4	50.0
8.627000	21.1	9.000	N	9.9	28.9	50.0
8.757500	21.6	9.000	N	9.9	28.4	50.0
8.825000	22.2	9.000	N	9.9	27.8	50.0
8.890250	22.3	9.000	N	9.9	27.7	50.0
9.016250	21.2	9.000	N	9.9	28.8	50.0

4.2 Radiated Emission Below 1 GHz

4.2.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI test receiver	Rohde & Schwarz	ESU40	100524	1 year	05.12.2020
☒	Bi-Log antenna	Schwarzbeck	VULB 9168	255	2 year	03.26.2019
☒	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒	Antenna master controller	INNCO Systems	CO3000	CO3000/870/ 35990515/L	N/A	-
☒	Turn table	INNCO Systems	1060	-	N/A	-
☒	Turn table controller	INNCO Systems	CO2000	CO2000/095/ 7590304/L	N/A	-
☒	Software	Rohde & Schwarz	EMC32	-	-	-

4.2.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Frequency Range	30 MHz to 1 000 MHz
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Worst Case of Data Cable	EAD64746101 (NINGBO)
Kind of Test Site	3 m semi anechoic chamber
Temperature	22.2 °C
Relative Humidity	46.5 %
Test Date	December 03, 2020

4.2.3 Measuring Data

Frequency (MHz)	Quasi Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
30.124280	29.8	117.8	V	71.0	18.3	10.2	40.0
66.427760	28.3	100.0	V	36.0	18.5	11.7	40.0
83.787040	31.7	225.1	H	290.0	15.2	8.3	40.0
132.832160	29.9	174.8	H	284.0	18.4	13.6	43.5
265.533520	32.2	125.0	H	0.0	19.3	13.8	46.0
804.843280	31.5	174.9	H	236.0	30.3	14.5	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak

4.3 Radiated Emission Above 1 GHz

4.3.1 Measuring instruments

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Calibration Date
☒	EMI test receiver	Rohde & Schwarz	ESU40	100524	1 year	05.12.2020
☒	Antenna master	INNCO Systems	MA4640-XP-ET	-	N/A	-
☒	Antenna master controller	INNCO Systems	CO3000	CO3000/870/35990515/L	N/A	-
☒	Turn table	INNCO Systems	1060	-	N/A	-
☒	Turn table controller	INNCO Systems	CO2000	CO2000/095/7590304/L	N/A	-
☒	Low noise amplifier	TESTEK	TK-PA18H	170034-L	1 year	03.03.2020
☒	Low noise amplifier	TESTEK	TK-PA1840H	170030-L	1 year	02.13.2020
☒	Horn antenna	Schwarzbeck	BBHA 9120D	01836	1 year	07.23.2020
☒	Horn antenna	Schwarzbeck	BBHA 9170	BBHA9170#786	1 year	11.18.2020
☒	Software	Rohde & Schwarz	EMC32	-	-	-

4.3.2 Operating Condition

The test results of radiated emission provide the following information:

Used Test Standard	FCC CFR 47 PART 15 Subpart B Class B ANSI C63.4-2014
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Frequency	5 825 MHz
Tested Frequency Range	1 GHz to 30 GHz
Worst Case of Data Cable	EAD64746101 (NINGBO)
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.7 °C
Relative Humidity	45.2 %
Test Date	December 16, 2020

4.3.3 Measuring Data

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1328.990000	44.4	299.5	H	327.0	-28.1	29.6	74.0
2009.255000	49.0	100.0	V	50.0	-26.4	25.0	74.0
2594.315000	53.2	349.8	V	53.0	-23.7	20.8	74.0
4481.250000	41.5	113.4	V	1.0	-19.2	32.5	74.0
5995.575000	42.5	100.0	V	323.0	-16.2	31.5	74.0
17984.878100	55.6	249.6	H	218.0	9.4	18.4	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1328.990000	26.8	299.5	H	327.0	-28.1	27.2	54.0
2009.255000	34.2	100.0	V	50.0	-26.4	19.8	54.0
2594.315000	33.8	349.8	V	53.0	-23.7	20.2	54.0
4481.250000	25.6	113.4	V	1.0	-19.2	28.4	54.0
5995.575000	26.1	100.0	V	323.0	-16.2	27.9	54.0
17984.878100	42.9	249.6	H	218.0	9.4	11.1	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage

5. CONCLUSION

The data collected shows that the **Product Name: Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth, Model: LM-K420TM** complies with §15.107 and §15.109 of the FCC rules.

6. APPENDIX A. TEST SETUP PHOTO

Please refer to Appendix. A and test setup photo file no. as follows;

File No.	Date of Issue	Description
HCT-EM-2012-FC012-P	December 18, 2020	Initial Release

End of report