



HCT CO., LTD.

CERTIFICATION DIVISION

74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, KOREA
TEL: +82 31 645 6300 FAX: +82 31 645 6401

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.

1000 Sylvan Avenue, Englewood Cliffs NJ 07632

Date of Issue: July 10, 2013

Test Report No.: HCTE1307FE13

Test Site: HCT CO., LTD.

HCT FRN: 0005-8664-21

FCC ID:

ZNFL39C

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B Class B
Equipment Type : CDMA Phone with Bluetooth3.0, WIFI802.11 b/g/n(2.4GHz only)
supported, BC0/BC1 EVDO Rev.0/Rev.A supported
Model Name : L39C
Additional Model Name : LG-L39C, LGL39C
Port / Connector(s) : USB / Earphone Port
Date of Test : July 05, 2013 - July 09, 2013

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862


Report prepared by
: Gu-Cheol Yoon
Test Engineer of EMC Team


Approved by
: Jin-Pyo Hong
Manager of EMC Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCTE1307FE13	July 10, 2013	Initial Release

TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Product Description.....	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Tested System Details.....	5
1.4 Cable Description	6
1.5 Noise Suppression Parts on Cable. (I/O cable)	6
1.6 Test Methodology	7
1.7 Test Facility	7
1.8 Frequency Range of Radiated Measurements	7
2. SYSTEM TEST CONFIGURATION.....	8
2.1 Configuration of Test System.....	8
3. PRELIMINARY TEST	9
3.1 Conducted Emission Test	9
3. 2 Radiated Emission Test	9
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	10
4.1 Conducted Emission Test	10
4.2 Radiated Emission Test	11
5. FIELD STRENGTH CALCULATION	17
6. TEST EQUIPMENT	18
7. CONCLUSION	19

ATTACHMENT: TEST SETUP PHOTOGRAPHS

1. GENERAL INFORMATION

1.1 Product Description

Equipment Under Test is **EUT type: CDMA Phone with Bluetooth3.0, WIFI802.11 b/g/n(2.4GHz only) supported, BC0/BC1 EVDO Rev.0/Rev.A supported, Model: L39C** manufactured by **LG Electronics MobileComm U.S.A., Inc.** Its basic purpose is used for communications.

Model Name	L39C
FCC ID	ZNFL39C
Additional Model Name	LG-L39C, LGL39C
EUT Type	CDMA Phone with Bluetooth3.0, WIFI802.11 b/g/n(2.4GHz only) supported, BC0/BC1 EVDO Rev.0/Rev.A supported
TX Frequency	824.70 MHz to 848.31 MHz (CDMA 835) 1 851.25 MHz to 1 908.75 MHz (CDMA 1 900)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA 835) 1 931.25 MHz to 1 988.75 MHz (CDMA 1 900)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	L39C	LG	ZNFL39C	Notebook PC Ear-phone
USB cable	EAD61965801	BD	-	E.U.T Notebook PC
Ear-phone	SGEY0003744	I-SOUND	-	E.U.T
Notebook PC	ProBook6560b	H.P	DoC	EUT Notebook PC adaptor
Notebook PC adaptor	PPP009D	DELTA Electronics (JIANGSU)LTD	-	Notebook PC
Mouse	Serial mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
Gateway	MV440R	Axesstel	-	Notebook PC, Adaptor
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	8 GB	SanDisk	-	E.U.T

1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.2
	Ear-phone	N/A	Y	(D)1.1
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.5 Noise Suppression Parts on Cable. (I/O cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Ear-phone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End

1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to EUT distance of 3 m

1.7 Test Facility

Chamber used to collect the test data is located at the 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3m)	90661(Mar. 02, 2011)
Radiated Field strength measurement facility (10m)	90661 (Sep. 03, 2010)

1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

2. SYSTEM TEST CONFIGURATION

2.1 Configuration of Test System


2.1.1 Conducted Emission Test

EUT was connected to LISN via Notebook PC adaptor and Base Station. Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

2.1.2 Radiated Emission Test

Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 m semi-anechoic chamber.

[Configuration of Tested System]



Non-Conductive Table
Power Line: 120 VAC

3. PRELIMINARY TEST

3.1 Conducted Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

3. 2 Radiated Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit Apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Operation Mode	: Data Communication mode
Temperature	: 23.6 °C
Humidity Level	: 52.4 %
Test Date	: July 05, 2013

Frequency (MHz)	Transd (dB)	Conductor	Quasi-Peak			Average		
			Limit (dBuV)	Measurement Level (dBuV)	Result Level (dBuV)	Limit (dBuV)	Measurement Level (dBuV)	Result Level (dBuV)
0.194	10.0	N	64	40.9	50.9	54	-	-
0.206	9.8	H	63	39.8	49.6	53	-	-
0.258	10.0	N	62	33.3	43.3	52	-	-
0.266	9.8	H	61	32.9	42.7	51	-	-
4.184	10.1	H	56	-	-	46	17.9	28.0
4.452	10.3	N	56	-	-	46	17.7	28.0

※ **NOTE:** Refer to page 11 to page 14 for details.

1. Line H = Hot, Line N = Neutral
2. Transd = LISN factor + Cable Loss factor


HCT

EMC

EUT: L39C
Manufacturer: LG
Operating Condition: DATA MODE
Test Site: SHIELD ROOM
Operator: GC YOON
Test Specification: FCC PART15 B
Comment: H

SCAN TABLE: "FCC CLASS B(H)"

Short Description:			KN22 CLASS B			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin QP"

2013-07-05 6:33오 후

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.150001	44.80	9.8	66	21.2	---	---
0.206001	49.60	9.8	63	13.8	---	---
0.266001	42.70	9.8	61	18.6	---	---
1.064000	34.50	9.8	56	21.5	---	---
1.140000	33.70	9.9	56	22.3	---	---
4.228000	34.80	10.1	56	21.2	---	---
19.668000	29.80	10.9	60	30.2	---	---
20.580000	34.50	10.9	60	25.5	---	---
21.008000	33.70	11.0	60	26.3	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

2013-07-05 6:33 오후

Frequency MHz	Level dB _{μV}	Transd dB	Limit dB _{μV}	Margin dB	Line	PE
0.210001	30.10	9.8	53	23.1	---	---
0.266001	26.60	9.8	51	24.7	---	---
0.458001	18.80	9.8	47	27.9	---	---
0.744000	24.90	9.8	46	21.1	---	---
1.128000	25.90	9.9	46	20.1	---	---
4.184000	28.00	10.1	46	18.0	---	---
18.244000	28.50	10.9	50	21.5	---	---
20.260000	28.60	10.9	50	21.4	---	---
20.808000	28.00	11.0	50	22.0	---	---


HCT

EMC

EUT: L39C
Manufacturer: LG
Operating Condition: DATA MODE
Test Site: SHIELD ROOM
Operator: GC YOON
Test Specification: FCC PART15 B
Comment: N

SCAN TABLE: "FCC CLASS B(N)"

Short Description:			KN22 CLASS B			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin QP"

2013-07-05 6:37오후

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dB	dB	dB	dB		
0.178001	39.50	10.0	65	25.1	---	---
0.194001	50.90	10.0	64	12.9	---	---
0.258001	43.30	10.0	62	18.2	---	---
1.056000	34.10	10.1	56	21.9	---	---
2.200000	34.80	10.2	56	21.2	---	---
4.176000	35.10	10.3	56	20.9	---	---
18.940000	33.50	11.2	60	26.5	---	---
20.256000	34.70	11.3	60	25.3	---	---
21.004000	34.10	11.3	60	25.9	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

2013-07-05 6:37 오후

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.194001	30.20	10.0	54	23.7	---	---
0.206001	31.90	10.0	53	21.4	---	---
0.258001	23.50	10.0	52	28.0	---	---
1.064000	24.80	10.1	46	21.2	---	---
1.100000	25.70	10.1	46	20.3	---	---
4.452000	28.00	10.3	46	18.0	---	---
20.256000	28.50	11.3	50	21.5	---	---
21.664000	28.40	11.3	50	21.6	---	---
23.128000	29.70	11.4	50	20.3	---	---

4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

-For measurement below 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Quasi-Peak (6 dB Bandwidth: 120 kHz)

Operation Mode : Data Communication mode

Temperature : 22.9 °C

Humidity Level : 57.2 %

Test Date : July 09, 2013

Frequency (MHz)	Reading (dBuV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBuV/m)	Level (dBuV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
80.100	15.32	H	1.0	8.02	3.76	40.0	27.1	12.9
93.900	17.13	H	1.2	8.15	3.82	43.5	29.1	14.4
125.000	16.07	H	1.2	12.01	4.02	43.5	32.1	11.4
276.000	12.20	H	1.0	12.62	4.57	46.0	29.4	16.6
376.700	10.87	H	1.0	15.11	4.92	46.0	30.9	15.1
624.000	5.53	V	1.0	19.96	5.51	46.0	31.0	15.0

-For measurement above 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Peak mode: Peak (RBW: 1 MHz, VBW: 1 MHz)
: Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)

Operation Mode : Data Communication mode

Temperature : 23.7 °C

Humidity Level : 55.8 %

Test Date : July 09, 2013

Frequency (GHz)	Peak			POL	Average		
	Total (dBμV/m)	Limit (dBμV/m)	Margin (dB)		Total (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1.9927	48.10	74	25.9	V	31.40	54	22.6

※ NOTE:

1. Measurement above 1 GHz was performed from 1 GHz to the 5th harmonic of highest fundamental frequency. Test was measured by 12 GHz.

5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB μ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB μ V/m value is mathematically converted to its corresponding level in μ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$

[Radiated Emission Limits]

Frequency of Emission (MHz)	Field Strength	
	μ V/m	dB μ V/m
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

6. TEST EQUIPMENT

Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	Next CAL Date
------	--------------	------------	---------------	-------------------	---------------

Conducted Emission

☒	EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	2014.04.25
☒	LISN	EMCO	3816/2SH	9706-1070	1 year	2014.04.26
☒	LISN	Rohde & Schwarz	ENV216	100073	1 year	2014.02.06
☐	Attenuator	Rohde & Schwarz	ESH3-Z2	357.8810.352	1 year	2013.07.31

Radiated Emission

-For measurement below 1 GHz

☒	EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
☒	Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	2014.12.17
☒	Antenna master	HD GmbH	MA240	240/520	N/A	-
☒	Turn Table	HD GmbH	2090	9702/1224	N/A	-

-For measurement above 1 GHz

☒	EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
☒	Antenna master	HD GmbH	MA240	240/520	N/A	-
☒	Turn Table	HD GmbH	2090	9702/1224	N/A	-
☒	Power Amplifier	Rohde & Schwarz	SCU-18	10094	1 year	2013.09.11
☒	Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	2014.12.13

7. CONCLUSION

The data collected shows that the **EUT type: CDMA Phone with Bluetooth3.0, WIFI802.11 b/g/n(2.4GHz only) supported, BC0/BC1 EVDO Rev.0/Rev.A supported, FCC ID: ZNFL39C, Model: L39C** complies with §15.107 and §15.109 of the FCC rules.