

EMI CERTIFICATION REPORT

Applicant:**LG Electronics MobileComm U.S.A., Inc.****1000 Sylvan Avenue, Englewood Cliffs NJ 07632****Date of Issue: March 20, 2014****Test Report No.: HCT-E-1403-F022****Test Site: HCT CO., LTD.****HCT FRN: 0005-8664-21****FCC ID:****ZNFLG305C**

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B Class B
Equipment Type : Cellular/PCS CDMA Phone with BT & WLAN
Model Name : LG305C
Additional Model Name : LG-305C, 305C, LG-LN280, LGLN280, LN280
Port / Connector(s) : USB / Earphone Port
Date of Test : March 18, 2014 – March 19, 2014

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4/2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Dong-Hyun Park
Test Engineer
EMC Team
Certification Division

Reviewed By

Sang-Jun Lee
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1403-F022	March 20, 2014	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Product Description.....	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Tested System Details.....	5
1.4 Cable Description	6
1.5 Noise Suppression Parts on Cable. (I/O Cable)	6
1.6 Test Methodology	7
1.7 Test Facility	7
1.8 Frequency Range of Radiated Measurements	7
2. DESCRIPTION OF TEST	8
3. PRELIMINARY TEST	10
3.1 Conducted Emission Test	10
3.2 Radiated Emission Test	10
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	11
4.1 Conducted Emission Test	11
4.2 Radiated Emission Test	16
5. FIELD STRENGTH CALCULATION	18
6. TEST EQUIPMENT	19
7. CONCLUSION.....	20

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Product Description

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model Name	LG305C
FCC ID	ZNFLG305C
Additional Model	LG-305C, 305C, LG-LN280, LGLN280, LN280
EUT Type	Cellular/PCS CDMA Phone with BT & WLAN
TX Frequency	824.70 MHz to 848.31 MHz (CDMA 850) 1 851.25 MHz to 1 908.75 MHz (CDMA 1 900)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA 850) 1 931.25 MHz to 1 988.75 MHz (CDMA 1 900)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.



1.3 Tested System Details

All

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG305C	LG	ZNFLG305C	Notebook PC Ear-phone
USB cable	EAD62377902	Ningbo Broad	-	E.U.T Notebook PC
USB cable	EAD62377903	KSD	-	E.U.T Notebook PC
Ear-phone	SGEY003219	CRESYN	-	E.U.T
Notebook PC	ProBook6560b	H.P	DoC	EUT Notebook PC adaptor
Notebook PC adaptor	PPP009D	DELTA Electronics (JIANGSU)LTD	-	Notebook PC
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
Mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	8 GB	SanDisk	-	EUT



1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Ear-phone	N/A	N	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	N	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.5 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Ear-phone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to EUT distance of 3 m.

1.7 Test Facility

Chamber used to collect the test data is located at the 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4/2003.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3m)	90661 (June 21, 2011)
Radiated Field strength measurement facility (10m)	90661 (June 21, 2011)

1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



2. DESCRIPTION OF TEST

2.1 Conducted Emission Test

EUT was connected to LISN via Notebook PC adaptor and Base Station. Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

[Conducted Emission Limits]

Frequency (MHz)	Quasi-Peak(dB μ V)	Average(dB μ V)
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

*Decreases with the logarithm of the frequency.

2.2 Radiated Emission Test

Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 m semi-anechoic chamber.

[Radiated Emission Limits]


Frequency (MHz)	Field Strength(μ V/m)	Quasi-Peak (dB μ V/m)
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

Frequency (MHz)	Peak (dB μ V/m)	Average (dB μ V/m)
1 000 to 12 000*	74	54

* 5th harmonic of highest fundamental frequency or 40 GHz, whichever is lower.



2.3 Configuration of Tested System



Power Line: 120 VAC



3. PRELIMINARY TEST

3.1 Conducted Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

3. 2 Radiated Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode



4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit Apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Operation Mode	: Data Communication mode
USB Cable Manufacturer	: KSD
Temperature	: 21.8°C
Humidity Level	: 41.5 %
Test Date	: March 19, 2014

Frequency (MHz)	Transd (dB)	Conductor	Quasi-Peak			Average		
			Limit (dBuV)	Measurement Level (dBuV)	Result Level (dBuV)	Limit (dBuV)	Measurement Level (dBuV)	Result Level (dBuV)
0.1500	9.7	N	66.0	50.3	60.0	56.0	-	-
0.1500	9.7	L1	66.0	51.2	60.9	56.0	31.4	41.1
0.1680	9.7	L1	65.1	47.1	56.8	55.1	22.9	32.6
0.1680	9.7	N	65.1	45.7	55.4	55.1	23.8	33.5

※ **NOTE:** Refer to page 11 to page 14 for details.

1. The worst-case emissions are reported.
 2. Conductor L1 = Hot, Conductor N = Neutral
 3. Transducer = LISN Factor + Cable Loss Factor
 4. Result Level = Measurement Level + Transducer Factor
- * 'Result Level' in above table is same as the 'Quasi-Peak' and 'CAverage' of the test data



EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG305C
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: DATA COMMUNICATION MODE (KSD)
 Operator Name:

FCC CLASS B



— FCCCLASS B_OP — FCCCLASS B_AV — Preview Result 1-PK
 — Preview Result 2-AVG X Final Result 1-CPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	60.9	9.000	Off	L1	9.7	5.1	66.0
0.168000	56.8	9.000	Off	L1	9.7	8.3	65.1
0.190500	54.0	9.000	Off	L1	9.7	10.0	64.0
0.217500	50.1	9.000	Off	L1	9.7	12.8	62.9
0.231000	46.4	9.000	Off	L1	9.7	16.0	62.4
0.240000	44.8	9.000	Off	L1	9.7	17.3	62.1
3.866000	28.3	9.000	Off	L1	10.0	27.7	56.0
3.888500	29.5	9.000	Off	L1	10.0	26.5	56.0
3.960500	30.1	9.000	Off	L1	10.1	25.9	56.0
3.983000	28.0	9.000	Off	L1	10.1	28.0	56.0
4.122500	27.5	9.000	Off	L1	10.1	28.5	56.0
4.518500	30.7	9.000	Off	L1	10.1	25.3	56.0
20.318000	30.8	9.000	Off	L1	10.9	29.2	60.0
20.682500	29.2	9.000	Off	L1	10.9	30.8	60.0
21.236000	28.6	9.000	Off	L1	11.0	31.4	60.0
21.281000	28.4	9.000	Off	L1	11.0	31.6	60.0

3/19/2014

4:31:14



EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
23.616500	28.5	9.000	Off	L1	11.1	31.5	60.0
23.661500	28.9	9.000	Off	L1	11.1	31.1	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	41.1	9.000	Off	L1	9.7	14.9	56.0
0.168000	32.6	9.000	Off	L1	9.7	22.5	55.1
0.177000	36.3	9.000	Off	L1	9.7	18.3	54.6
0.190500	32.6	9.000	Off	L1	9.7	21.4	54.0
0.204000	30.9	9.000	Off	L1	9.7	22.5	53.4
0.217500	30.6	9.000	Off	L1	9.7	22.3	52.9
3.866000	20.8	9.000	Off	L1	10.0	25.2	46.0
3.888500	20.7	9.000	Off	L1	10.0	25.3	46.0
3.960500	19.3	9.000	Off	L1	10.1	26.7	46.0
3.983000	20.4	9.000	Off	L1	10.1	25.6	46.0
4.122500	20.6	9.000	Off	L1	10.1	25.4	46.0
4.518500	22.9	9.000	Off	L1	10.1	23.1	46.0
20.318000	25.8	9.000	Off	L1	10.9	24.2	50.0
20.687000	24.3	9.000	Off	L1	10.9	25.7	50.0
21.231500	22.8	9.000	Off	L1	11.0	27.2	50.0
23.616500	23.2	9.000	Off	L1	11.1	26.8	50.0
23.661500	22.9	9.000	Off	L1	11.1	27.1	50.0
24.044000	24.6	9.000	Off	L1	11.1	25.4	50.0

3/19/2014

4:31:14



EMI Auto Test(2)


1 / 2

HCT TEST Report

Common Information

EUT: LG305C
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: DATA COMMUNICATION MODE (KSD)
 Operator Name:

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG X Final Result 1-QPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	60.0	9.000	Off	N	9.7	6.0	66.0
0.168000	55.4	9.000	Off	N	9.7	9.7	65.1
0.181500	54.0	9.000	Off	N	9.7	10.4	64.4
0.204000	49.8	9.000	Off	N	9.7	13.6	63.4
0.222000	47.2	9.000	Off	N	9.7	15.5	62.7
0.249000	42.9	9.000	Off	N	9.7	18.9	61.8
3.636500	29.2	9.000	Off	N	10.0	26.8	56.0
4.208000	30.1	9.000	Off	N	10.1	25.9	56.0
4.226000	30.1	9.000	Off	N	10.1	25.9	56.0
4.280000	30.3	9.000	Off	N	10.1	25.7	56.0
4.658000	29.8	9.000	Off	N	10.1	26.2	56.0
4.680500	28.1	9.000	Off	N	10.1	27.9	56.0
17.168000	25.5	9.000	Off	N	10.7	34.5	60.0
17.546000	25.5	9.000	Off	N	10.7	34.5	60.0
19.539500	28.3	9.000	Off	N	10.8	31.7	60.0
19.553000	27.9	9.000	Off	N	10.8	32.1	60.0

3/19/2014

4:36:17



EMI Auto Test(2)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
19.958000	28.8	9.000	Off	N	10.8	31.2	60.0
21.929000	27.8	9.000	Off	N	10.9	32.2	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.154500	35.5	9.000	Off	N	9.7	20.3	55.8
0.168000	33.5	9.000	Off	N	9.7	21.6	55.1
0.186000	34.9	9.000	Off	N	9.7	19.3	54.2
0.199500	30.0	9.000	Off	N	9.7	23.6	53.6
0.217500	30.6	9.000	Off	N	9.7	22.3	52.9
0.240000	28.1	9.000	Off	N	9.7	24.0	52.1
3.708500	20.6	9.000	Off	N	10.0	25.4	46.0
4.203500	21.7	9.000	Off	N	10.1	24.3	46.0
4.230500	21.8	9.000	Off	N	10.1	24.2	46.0
4.280000	22.2	9.000	Off	N	10.1	23.8	46.0
4.469000	23.0	9.000	Off	N	10.1	23.0	46.0
4.680500	21.5	9.000	Off	N	10.1	24.5	46.0
17.168000	20.3	9.000	Off	N	10.7	29.7	50.0
17.546000	20.2	9.000	Off	N	10.7	29.8	50.0
19.539500	21.4	9.000	Off	N	10.8	28.6	50.0
21.357500	23.4	9.000	Off	N	10.8	26.6	50.0
21.929000	22.4	9.000	Off	N	10.9	27.6	50.0
22.383500	22.2	9.000	Off	N	10.9	27.8	50.0

3/19/2014

4:36:17



4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

-For measurement below 1 GHz

Limit Apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak (6 dB Bandwidth: 120 kHz)
Operation Mode	: Data Communication mode
USB Cable Manufacturer	: Ningbo Broad
Temperature	: 22.6°C
Humidity Level	: 35.0 %
Test Date	: March 18, 2014

Frequency (MHz)	Reading (dBuV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBuV/m)	Level (dBuV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
62.10	21.10	V	1.0	11.55	3.55	40.0	36.2	3.8
125.00	18.09	V	1.0	12.01	3.90	43.5	34.0	9.5
625.00	11.94	V	1.0	19.97	5.39	46.0	37.3	8.7

※ NOTE:

1. The worst-case emissions are reported.



-For measurement above 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Peak mode: Peak (RBW: 1 MHz, VBW: 1 MHz)
: Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)

Operation Mode : Data Communication mode

USB Cable Manufacturer : Ningbo Broad

Temperature : 22.6°C

Humidity Level : 35.0 %

Test Date : March 18, 2014

Frequency (GHz)	Peak			POL	Average		
	Total (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)		Total (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1.33200	49.4	74	24.6	V	27.0	54	27.0
1.99900	52.4	74	21.6	V	28.7	54	25.3
2.66390	52.3	74	21.7	V	31.5	54	22.5

※ NOTE:

1. The worst-case emissions are reported.
2. Measurement above 1 GHz was performed from 1 GHz to the 5th harmonic of highest fundamental frequency. Test was measured by 12 GHz.



5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB μ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB μ V/m value is mathematically converted to its corresponding level in μ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$



6. TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>Next CAL Date</u>
<u>Conducted Emission</u>					
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	2015.01.24
☒ LISN	EMCO	3816/2SH	9706-1070	1 year	2014.04.26
☒ LISN	Rohde & Schwarz	ENV216	100073	1 year	2015.01.29
☐ EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	2014.06.23
☐ LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	2014.07.03
☐ Attenuator	Rohde & Schwarz	ESH3-Z2	357.8810.352	1 year	2014.07.03
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
☒ Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	2014.12.17
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Turn Table	HD GmbH	2090	9702/1224	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	2014.07.01
☐ Trilog Antenna	Schwarzbeck	VULB9168	185	2 year	2015.04.16
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
-For measurement above 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Turn Table	HD GmbH	2090	9702/1224	N/A	-
☐ Power Amplifier	CERNEX	CBLU1183540	21690	1 year	2014.07.12
☒ Power Amplifier	CERNEX	CBLU1183540	22964	1 year	2014.07.24
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	2014.12.13
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	2014.07.01
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-



7. CONCLUSION

The data collected shows that the **EUT type: Cellular/PCS CDMA Phone with BT & WLAN, FCC ID: ZNFLG305C, Model: LG305C** complies with §15.107 and §15.109 of the FCC rules.