

EMI CERTIFICATION REPORT

Applicant:**LG Electronics MobileComm U.S.A., Inc.****1000 Sylvan Avenue, Englewood Cliffs NJ 07632****Date of Issue: February 07, 2014****Test Report No.: HCTE1402F009****Test Site: HCT CO., LTD.****HCT FRN: 0005-8664-21****FCC ID:****ZNFLS740**

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B Class B
Equipment Type : Cellular/PCS CDMA/EVDO and AWS/PCS LTE Phone with Bluetooth and WLAN
Model Name : LGLS740
Additional Model Name : LGLS740 , LS740
Port / Connector(s) : USB / Earphone Port
Date of Test : February 05, 2014 - February 07, 2014

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4/2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Seul-Ki Lee
Test Engineer
EMC Team
Certification Division

Reviewed By

Sang-Jun Lee
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCTE1402F009	February 07, 2014	Initial Release



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Product Description.....	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Tested System Details.....	5
1.4 Cable Description	6
1.5 Noise Suppression Parts on Cable. (I/O cable)	6
1.6 Test Methodology	7
1.7 Test Facility	7
1.8 Frequency Range of Radiated Measurements	7
2. SYSTEM TEST CONFIGURATION.....	8
2.1 Configuration of Test System	8
3. PRELIMINARY TEST	9
3.1 Conducted Emission Test	9
3. 2 Radiated Emission Test	9
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	10
4.1 Conducted Emission Test	10
4.2 Radiated Emission Test	10
5. FIELD STRENGTH CALCULATION	17
6. TEST EQUIPMENT	18
7. CONCLUSION	19

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Product Description

Equipment Under Test is manufactured by **LG Electronics MobileComm U.S.A., Inc.**
Its basic purpose is used for communications.

Model Name	LGLS740
Additional Model Name	LGLS740 , LS740
FCC ID	ZNFLS740
EUT Type	Cellular/PCS CDMA/EVDO and AWS/PCS LTE Phone with Bluetooth and WLAN
TX Frequency	824.70 MHz to 848.31 MHz (CDMA BC0) 1 851.25 MHz to 1 908.75 MHz (CDMA BC1) 817.90 MHz to 823.10 MHz (CDMA BC10) 1 850 MHz to 1 915 MHz (LTE B25) 814 MHz to 849 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41)
RX Frequency	869.70 MHz to 893.31 MHz (CDMA BC0) 1 931.25 MHz to 1 988.75 MHz (CDMA BC1) 862 MHz to 894 MHz (CDMA BC10) 1 925 MHz to 1 990 MHz (LTE B25) 859 MHz to 894 MHz (LTE B26) 2 496 MHz to 2 690 MHz (LTE B41)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.



1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LGLS740	LG	ZNFLS740	Notebook PC Ear-phone
USB cable	EAD62185903	Ningbo Broad	-	E.U.T Notebook PC
USB cable [*]	EAD62150404	CRESYN		E.U.T Notebook PC
Ear-phone	SGEY0007612	CRESYN	-	E.U.T
Notebook PC	ProBook6560b	H.P	DoC	EUT Notebook PC adaptor
Notebook PC adaptor	PPP009D	DELTA Electronics (JIANGSU)LTD	-	Notebook PC
Gateway	MV440	Axesstel	PH7MV440	Notebook PC, Adaptor
Serial Mouse	Serial 2 Button mouse	Radio shack	FSUGMZE3	Notebook PC
Adaptor	DA-60M12	Yang Ming Industrial	-	Gateway
RJ45 cable	-	-	-	Notebook PC, Gateway
Micro SD card	8GB	SanDisk	-	E.U.T

※**Note:**

1^{*}. The worst-case emissions are reported.



1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Ear-phone	N/A	N	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.5
	Serial (Mouse)	N/A	N	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.5 Noise Suppression Parts on Cable. (I/O cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Ear-phone	N	N/A	Y	EUT End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to EUT distance of 3 m.

1.7 Test Facility

Chamber used to collect the test data is located at the 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4/2003.

Measurement Facilities	Reg. No.
Radiated Field strength measurement facility (3m)	90661 (June 21, 2011)
Radiated Field strength measurement facility (10m)	90661 (June 21, 2011)

1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower



2. SYSTEM TEST CONFIGURATION

2.1 Configuration of Test System


2.1.1 Conducted Emission Test

EUT was connected to LISN via Notebook PC adaptor and Base Station. Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

2.1.2 Radiated Emission Test

Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 m semi-anechoic chamber.

[Configuration of Tested System]



Power Line: 120 VAC



3. PRELIMINARY TEST

3.1 Conducted Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

3. 2 Radiated Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode



4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit Apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Operation Mode	: Data Communication mode
USB Manufacturer	: CRESYN
Temperature	: 19.3°C
Humidity Level	: 28.4 %
Test Date	: February 07, 2014

Frequency (MHz)	Transd (dB)	Conductor	Quasi-Peak			Average		
			Limit (dBuV)	Measurement Level (dBuV)	Result Level (dBuV)	Limit (dBuV)	Measurement Level (dBuV)	Result Level (dBuV)
0.1950	9.7	H	63.8	45.9	55.6	53.8	-	-
0.1995	9.7	N	63.6	43.1	52.8	53.6	26.9	36.6
0.2130	9.7	H	63.1	42.4	52.1	53.1	-	-
0.2625	9.7	N	61.4	36.4	46.1	51.4	-	-

※ **NOTE:** Refer to page 11 to page 14 for details.

1. Conductor H = Hot, Conductor N = Neutral
2. Transducer = LISN Factor + Cable Loss Factor
3. Result Level = Measurement Level + Transducer Factor

* 'Result Level' in above table is same as the 'Quasi-Peak' and 'Average' of the test data



EMI Auto Test(1)


1 / 2

HCT TEST Report

Common Information

EUT: LG-LS740
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: DATA MODE(CRESYN)
 Operator Name:

FCC CLASS B



— FCC CLASS B_QP — FCC CLASS B_AV — Preview Result 1-PK+
 — Preview Result 2-AVG X Final Result 1-QPK X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	46.8	9.000	Off	N	9.7	19.2	66.0
0.163500	41.6	9.000	Off	N	9.7	23.7	65.3
0.199500	52.8	9.000	Off	N	9.7	10.8	63.6
0.244500	36.8	9.000	Off	N	9.7	25.1	61.9
0.262500	46.1	9.000	Off	N	9.7	15.3	61.4
0.276000	45.0	9.000	Off	N	9.7	15.9	60.9
4.046000	38.5	9.000	Off	N	10.1	17.5	56.0
4.181000	38.4	9.000	Off	N	10.1	17.6	56.0
4.320500	38.4	9.000	Off	N	10.1	17.6	56.0
4.464500	38.9	9.000	Off	N	10.1	17.1	56.0
4.676000	38.5	9.000	Off	N	10.1	17.5	56.0
4.748000	38.1	9.000	Off	N	10.1	17.9	56.0
19.670000	33.5	9.000	Off	N	10.8	26.5	60.0
19.935500	33.3	9.000	Off	N	10.8	26.7	60.0
20.156000	30.9	9.000	Off	N	10.8	29.1	60.0
21.263000	35.3	9.000	Off	N	10.8	24.7	60.0

2/7/2014

9:51:41



EMI Auto Test(1)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
21.474500	34.7	9.000	Off	N	10.9	25.3	60.0
21.663500	35.4	9.000	Off	N	10.9	24.6	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	28.3	9.000	Off	N	9.7	27.7	56.0
0.159000	26.3	9.000	Off	N	9.7	29.2	55.5
0.168000	25.9	9.000	Off	N	9.7	29.2	55.1
0.199500	36.6	9.000	Off	N	9.7	17.0	53.6
0.208500	35.2	9.000	Off	N	9.7	18.1	53.3
0.276000	30.4	9.000	Off	N	9.7	20.5	50.9
4.109000	29.8	9.000	Off	N	10.1	16.2	46.0
4.176500	30.2	9.000	Off	N	10.1	15.8	46.0
4.320500	30.0	9.000	Off	N	10.1	16.0	46.0
4.347500	29.1	9.000	Off	N	10.1	16.9	46.0
4.464500	30.4	9.000	Off	N	10.1	15.6	46.0
4.748000	30.3	9.000	Off	N	10.1	15.7	46.0
19.670000	25.8	9.000	Off	N	10.8	24.2	50.0
19.935500	25.3	9.000	Off	N	10.8	24.7	50.0
20.156000	23.4	9.000	Off	N	10.8	26.6	50.0
21.263000	29.3	9.000	Off	N	10.8	20.7	50.0
21.402500	28.1	9.000	Off	N	10.8	21.9	50.0
21.663500	29.4	9.000	Off	N	10.9	20.6	50.0

2/7/2014

9:51:41



EMI Auto Test(1)


1 / 2

HCT TEST Report

Common Information

EUT: LG-LS740
 Manufacturer: LG
 Test Site: SHIELD ROOM
 Operating Conditions: DATA MODE(CRESYN)
 Operator Name:

FCC CLASS B



— FCC CLASS B_OP
 — Preview Result 2-AVG
 — FCC CLASS B_AV
 X Final Result 1-CPK
 X Preview Result 1-PK
 X Final Result 2-CAV

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154500	45.0	9.000	Off	L1	9.7	20.8	65.8
0.163500	41.8	9.000	Off	L1	9.7	23.5	65.3
0.195000	55.6	9.000	Off	L1	9.7	8.2	63.8
0.213000	52.1	9.000	Off	L1	9.7	11.0	63.1
0.267000	47.5	9.000	Off	L1	9.7	13.7	61.2
0.276000	46.8	9.000	Off	L1	9.7	14.1	60.9
3.969500	38.3	9.000	Off	L1	10.1	17.7	56.0
4.325000	38.0	9.000	Off	L1	10.1	18.0	56.0
4.370000	37.9	9.000	Off	L1	10.1	18.1	56.0
4.446500	37.5	9.000	Off	L1	10.1	18.5	56.0
4.536500	38.6	9.000	Off	L1	10.1	17.4	56.0
4.752500	38.2	9.000	Off	L1	10.1	17.8	56.0
17.582000	33.2	9.000	Off	L1	10.8	26.8	60.0
18.149000	32.0	9.000	Off	L1	10.8	28.0	60.0
18.216500	31.7	9.000	Off	L1	10.8	28.3	60.0
19.710500	34.6	9.000	Off	L1	10.9	25.4	60.0

2/7/2014

9:45:26



EMI Auto Test(1)

2 / 2

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
20.273000	32.3	9.000	Off	L1	10.9	27.7	60.0
22.334000	30.4	9.000	Off	L1	11.0	29.6	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	29.1	9.000	Off	L1	9.7	26.9	56.0
0.163500	25.9	9.000	Off	L1	9.7	29.4	55.3
0.177000	25.6	9.000	Off	L1	9.7	29.0	54.6
0.199500	37.6	9.000	Off	L1	9.7	16.0	53.6
0.253500	29.0	9.000	Off	L1	9.7	22.6	51.6
0.267000	31.6	9.000	Off	L1	9.7	19.6	51.2
3.969500	28.5	9.000	Off	L1	10.1	17.5	46.0
4.325000	30.1	9.000	Off	L1	10.1	15.9	46.0
4.370000	30.0	9.000	Off	L1	10.1	16.0	46.0
4.446500	30.7	9.000	Off	L1	10.1	15.3	46.0
4.536500	30.3	9.000	Off	L1	10.1	15.7	46.0
4.748000	30.3	9.000	Off	L1	10.1	15.7	46.0
18.149000	23.6	9.000	Off	L1	10.8	26.4	50.0
18.216500	23.2	9.000	Off	L1	10.8	26.8	50.0
19.710500	27.7	9.000	Off	L1	10.9	22.4	50.0
20.273000	23.4	9.000	Off	L1	10.9	26.6	50.0
22.046000	24.1	9.000	Off	L1	11.0	25.9	50.0
22.334000	23.2	9.000	Off	L1	11.0	26.8	50.0

2/7/2014

9:45:26



4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

-For measurement below 1 GHz

Limit Apply to	: FCC PART 15 Subpart B Class B
Detector	: Quasi-Peak (6 dB Bandwidth: 120 kHz)
Operation Mode	: Data Communication mode
USB Manufacturer	: CRESYN
Temperature	: 18.9°C
Humidity Level	: 27.4 %
Test Date	: February 05, 2014

Frequency (MHz)	Reading (dBuV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBuV/m)	Level (dBuV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
110.8	21.88	H	2.8	10.60	3.82	43.5	36.3	7.20
625.0	13.74	V	1.0	19.97	5.39	46.0	39.1	6.90



-For measurement above 1 GHz

Limit Apply to : FCC PART 15 Subpart B Class B

Detector : Peak mode: Peak (RBW: 1 MHz, VBW: 1 MHz)
: Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)

USB Manufacturer : CRESYN

Temperature : 18.9°C

Humidity Level : 27.4 %

Test Date : February 05, 2014

Frequency (GHz)	Peak			POL	Average		
	Total (dBμV/m)	Limit (dBμV/m)	Margin (dB)		Total (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1.3293	51.7	74	22.3	V	27.9	54	26.1
1.9807	52.9	74	21.1	V	29.6	54	24.4
2.0993	49.4	74	24.6	V	28.2	54	25.8
2.6592	50.3	74	23.7	V	30.4	54	23.6

※ NOTE:

1. Measurement above 1 GHz was performed from 1 GHz to the 5th harmonic of highest fundamental frequency. Test was measured by 12 GHz.



5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB μ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB μ V/m value is mathematically converted to its corresponding level in μ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$

[Radiated Emission Limits]

Frequency of Emission (MHz)	Field Strength	
	$\mu\text{V/m}$	dB $\mu\text{V/m}$
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0



6. TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>Next CAL Date</u>
<u>Conducted Emission</u>					
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	2014.04.25
☒ LISN	EMCO	3816/2SH	9706-1070	1 year	2014.04.26
☒ LISN	Rohde & Schwarz	ENV216	100073	1 year	2015.01.29
☐ EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	2014.06.23
☐ LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	2014.07.03
☐ Attenuator	Rohde & Schwarz	ESH3-Z2	357.8810.352	1 year	2014.07.03

Radiated Emission

-For measurement below 1 GHz

☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
☒ Trilog Antenna	Schwarzbeck	VULB9160	3301	2 year	2014.12.17
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Turn Table	HD GmbH	2090	9702/1224	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	2014.07.01
☐ Trilog Antenna	Schwarzbeck	VULB9168	185	2 year	2015.04.16
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-

-For measurement above 1 GHz

☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	2014.04.16
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Turn Table	HD GmbH	2090	9702/1224	N/A	-
☒ Power Amplifier	CERNEX	CBLU1183540	21690	1 year	2014.07.12
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	2014.12.13
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	2014.07.01
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-



7. CONCLUSION

The data collected shows that the **EUT type: Cellular/PCS CDMA/EVDO and AWS/PCS LTE Phone with Bluetooth and WLAN, FCC ID: ZNFLS740, Model: LGLS740** complies with §15.107 and §15.109 of the FCC rules.