



FCC 47 CFR PART 15 SUBPART C

C2PC CERTIFICATION TEST REPORT

FOR

CDMA/LTE PHONE + BLUETOOTH, DTS/b/g/n

MODEL NUMBER: LGLS751, LG-LS751, LS751

FCC ID: ZNFLS751

REPORT NUMBER: 15I20527-E2

ISSUE DATE: MAY 6, 2015

Prepared for

**LG ELECTRONICS MOBILECOMM U.S.A., INC
1000 SYLVAN AVENUE
ENGLEWOOD CLIFFS,
NEW JERSEY, 07632, U.S.A**

Prepared by

**UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Issue			
Rev.	Date	Revisions	Revised By
---	05/6/15	Initial Issue	D. Corona

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	5
4.1. MEASURING INSTRUMENT CALIBRATION	5
4.2. SAMPLE CALCULATION	5
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM OUTPUT POWER.....	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. WORST-CASE CONFIGURATION AND MODE	7
5.5. DESCRIPTION OF TEST SETUP.....	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. SUMMARY TABLE	11
9. RADIATED TEST RESULTS.....	12
9.1. LIMITS AND PROCEDURE	12
9.2. TRANSMITTER ABOVE 1 GHz	13
9.2.1. BASIC DATA RATE GFSK MODULATION	13
9.2.2. ENHANCED DATA RATE 8PSK MODULATION	26
9.3. TRANSMITTER BELOW 1 GHz.....	39
10. SETUP PHOTOS	41

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: LG ELECTRONICS MOBILECOMM U.S.A., INC
EUT DESCRIPTION: CDMA/LTE PHONE + BLUETOOTH, DTS b/g/n
MODEL: LGLS751, LG-LS751, LS751
SERIAL NUMBER: 1WEAD (Radiated), 1WEAC (Conducted)
DATE TESTED: APRIL 18-20, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:



DAN CORONIA
CONSUMER TECHNOLOGY DIVISION
WISE PROJECT LEAD
UL VERIFICATION SERVICES INC

Tested By:



ANGEL ESCAMILLA
CONSUMER TECHNOLOGY DIVISION
WISE LAB ENGINEER
UL VERIFICATION SERVICES INC

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, and FCC CFR 47 Part 15C.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☒ Chamber A(IC: 2324B-1)	☐ Chamber D(IC: 2324B-4)
☐ Chamber B(IC: 2324B-2)	☐ Chamber E(IC: 2324B-5)
☒ Chamber C(IC: 2324B-3)	☐ Chamber F(IC: 2324B-6)
	☐ Chamber F(IC: 2324B-7)
	☐ Chamber H(IC: 2324B-8)

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned}\text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \text{Cable} \\ &\text{Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m}\end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a CDMA/LTE PHONE + BLUETOOTH, DTS/b/g/n

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:
See original report for details.

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PIFA antenna, with a maximum gain of -2.9dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	LG	MCS-02WR	RA4Y1031433	N/A
Earphone	LG	N/A	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.
EUT was set in the Hidden menu mode to enable BT communications.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/15
Spectrum Analyzer, 9KHz-40GHz	HP	8564E	106	08/06/15
EMI Test Receiver, 9 kHz-7 GHz	R & S	ESCI 7	100773	08/15/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/15
Antenna, Horn, 18- 26 GHz	ARA	MWH-1826/B	C00946	11/12/15
Antenna, Horn, 26-40 GHz	ARA	MWH-2640	C00891	06/28/15
Antenna, Bilog, 30MHz-1 GHz	Sunol Sciences	JB1	T243	12/08/15
RF Preamplifier, 100KHz -> 1300MHz	HP	TBD	C00825	06/01/15
RF Preamplifier, 26GHz - 40GHz	Miteq	NSP4000-SP2	86	04/07/16
RF Preamplifier, 1GHz - 26.5GHz	HP	8449B	F00351	06/27/15
AC Power Supply, 2,500VA 45-500Hz	Elgar-Ametek	CW2501M	F00013	CNR
RF Preamplifier, 1GHz - 18GHz	Miteq	AFS42-00101800-25-S-42	1818466	05/09/15
Attenuator / Switch driver	HP	11713A	F00204	CNR
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	F00219	05/23/15
High Pass Filter 5GHz	Micro-Tronics	HPS17542	F00222	05/22/15
High Pass Filter 6GHz	Micro-Tronics	HPM17543	F00224	05/22/15

Test Software List			
Description	Manufacturer	Model	Version
Radiated Software	UL	UL EMC	Version 9.5, 07/22/14
Conducted Software	UL	UL EMC	Version 9.5, 05/17/14
CLT Software	UL	UL RF	Version 1.0, 02/02/15
Antenna Port Software	UL	UL RF	Version 2.1.1.1, 1/20/15

7. SUMMARY TABLE

C2PC reason: Please see LG FCC Class II cover letter for details.

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
2.1049	RSS-GEN 4.6	Occupied Band width (99%)	N/A	Conducted	Pass	See original
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	See original
15.247 (b)(1)	RSS-210 A8.4	TX conducted output power	<21dBm		Pass	See original
15.247 (a)(1)	RSS-210 A8.1(b)	Hopping frequency separation	> 25KHz		Pass	See original
15.247 (a)(1)(iii)	RSS-210 A8.1(d)	Number of Hopping channels	More than 15 non-overlapping channels		Pass	See original
15.247 (a)(1)(iii)	RSS-210 A8.1(d)	Avg Time of Occupancy	< 0.4sec		Pass	See original
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	See original
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	40.73 dBuV/m

9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit ($\mu\text{V/m}$) at 3 m	Field Strength Limit (dB $\mu\text{V/m}$) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For band edge measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 1/T (on time) for average measurement.
 $\text{GFSK} = 1/T = 1 / 0.00288\text{S} = 347\text{Hz}$.

The spectrum from 1GHzHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

9.2. TRANSMITTER ABOVE 1 GHz

9.2.1. BASIC DATA RATE GFSK MODULATION

RESTRICTED BANDEDGE (LOW CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	2.331	43.34	PK	31.7	-23.1	51.94	-	-	74	-22.06	208	380	H
4	2.389	29.9	VB1T	32	-23.1	38.8	54	-15.2	-	-	208	380	H
1	2.39	40.77	PK	32	-23.1	49.67	-	-	74	-24.33	208	380	H
3	2.39	29.75	VB1T	32	-23.1	38.65	54	-15.35	-	-	208	380	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	2.379	42.93	PK	31.9	-23.1	0	51.73	-	-	74	-22.27	90	198	V
4	2.389	30.97	VB1T	32	-23.1	0	39.87	54	-14.13	-	-	90	198	V
1	2.39	39.27	PK	32	-23.1	0	48.17	-	-	74	-25.83	90	198	V
3	2.39	30.86	VB1T	32	-23.1	0	39.76	54	-14.24	-	-	90	198	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/ Ftr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.484	40.32	PK	32.3	-22.8	49.82	-	-	74	-24.18	11	373	H
3	2.484	30.33	VB1T	32.3	-22.8	39.83	54	-14.17	-	-	11	373	H
4	2.484	30.35	VB1T	32.3	-22.8	39.85	54	-14.15	-	-	11	373	H
2	2.556	42.83	PK	32.4	-22.7	52.53	-	-	74	-21.47	11	373	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AFT119 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.484	41.76	PK	32.3	-22.8	0	51.26	-	-	74	-22.74	70	314	V
2	2.484	42.99	PK	32.3	-22.8	0	52.49	-	-	74	-21.51	70	314	V
3	2.484	31.45	VB1T	32.3	-22.8	0	40.95	54	-13.05	-	-	70	314	V
4	2.484	31.52	VB1T	32.3	-22.8	0	41.02	54	-12.98	-	-	70	314	V


HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


LOW CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.926	36.9	PK	30.9	-25.4	42.4	-	-	-	-	0-360	201	H
4	2.022	36.48	PK	31.2	-25.3	42.38	-	-	-	-	0-360	201	V
2	3.135	35.2	PK	32.8	-32	36	-	-	-	-	0-360	201	H
5	3.218	35.14	PK	32.7	-33.4	34.44	-	-	-	-	0-360	201	V
3	6.361	31.88	PK	35.5	-28.5	38.88	-	-	-	-	0-360	201	H
6	6.86	30.7	PK	35.6	-28	38.3	-	-	-	-	0-360	201	V


PK - Peak detector

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


MID CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.939	36.35	PK	30.9	-25.4	41.85	-	-	-	-	0-360	201	H
4	2.025	36.47	PK	31.2	-25.3	42.37	-	-	-	-	0-360	201	V
2	3.121	33.79	PK	32.9	-31.9	34.79	-	-	-	-	0-360	201	H
5	3.209	34.93	PK	32.7	-33.3	34.33	-	-	-	-	0-360	201	V
6	6	31.86	PK	35.4	-28.9	38.36	-	-	-	-	0-360	100	V
3	6.266	30.78	PK	35.5	-28.2	38.08	-	-	-	-	0-360	201	H

PK - Peak detector

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA


TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.967	37.81	PK	31	-25.3	43.51	-	-	-	-	0-360	201	H
4	2.035	37.01	PK	31.2	-25.3	42.91	-	-	-	-	0-360	201	V
2	3.124	34.15	PK	32.9	-31.9	35.15	-	-	-	-	0-360	201	H
5	3.218	35.28	PK	32.7	-33.4	34.58	-	-	-	-	0-360	201	V
3	6.209	31.78	PK	35.4	-28.8	38.38	-	-	-	-	0-360	100	H
6	6.458	32.07	PK	35.5	-28.8	38.77	-	-	-	-	0-360	201	V

PK - Peak detector

9.2.2. ENHANCED DATA RATE 8PSK MODULATION RESTRICTED BANDEDGE (LOW CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.88	PK	32	-24.9	47.98	-	-	74	-26.02	99	103	H
2	* 2.341	43.47	PK	31.9	-25	50.37	-	-	74	-23.63	99	103	H
3	* 2.39	29.61	VB1T	32	-24.9	36.71	54	-17.29	-	-	99	103	H
4	* 2.387	29.71	VB1T	32	-24.9	36.81	54	-17.19	-	-	99	103	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/ Filt/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.78	PK	32	-24.9	47.88	-	-	74	-26.12	234	111	V
2	* 2.353	43.52	PK	31.9	-25	50.42	-	-	74	-23.58	234	111	V
3	* 2.39	29.78	VB1T	32	-24.9	36.88	54	-17.12	-	-	234	111	V
4	* 2.387	29.87	VB1T	32	-24.9	36.97	54	-17.03	-	-	234	111	V

AUTHORIZED BANDEDGE (HIGH CHANNEL)


HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.484	44.33	PK	32.3	-22.8	0	53.83	-	-	74	-20.17	150	300	H
2	2.484	46.26	PK	32.3	-22.8	0	55.76	-	-	74	-18.24	150	300	H
3	2.484	32.47	VB1T	32.3	-22.8	0	41.97	54	-12.03	-	-	150	300	H
4	2.484	32.47	VB1T	32.3	-22.8	0	41.97	54	-12.03	-	-	150	300	H

VERTICAL PEAK AND AVERAGE PLOT




VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/ Fitr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.2	PK	32.1	-24.8	48.5	-	-	74	-25.5	29	109	V
3	* 2.484	30.04	VB1T	32.1	-24.8	37.34	54	-16.66	-	-	29	109	V
4	* 2.484	30.05	VB1T	32.1	-24.8	37.35	54	-16.65	-	-	29	109	V
2	2.53	43.69	PK	32.1	-24.7	51.09	-	-	74	-22.91	29	109	V


HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


LOW CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.931	36.85	PK	30.9	-25.4	42.35	-	-	-	-	0-360	100	H
4	2.02	36.53	PK	31.2	-25.3	42.43	-	-	-	-	0-360	201	V
2	3.126	34.51	PK	32.9	-31.9	35.51	-	-	-	-	0-360	100	H
5	3.176	34.42	PK	32.8	-32.8	34.42	-	-	-	-	0-360	100	V
3	6.621	30.61	PK	35.6	-27.4	38.81	-	-	-	-	0-360	100	H
6	6.823	30.96	PK	35.6	-27.9	38.66	-	-	-	-	0-360	201	V


PK - Peak detector

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.


MID CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.103	36.86	PK	31.4	-25.3	42.96	-	-	-	-	0-360	201	H
4	2.154	36.38	PK	31.4	-25.2	42.58	-	-	-	-	0-360	100	V
2	3.13	34.15	PK	32.9	-32	35.05	-	-	-	-	0-360	100	H
5	3.469	34.43	PK	33	-32.4	35.03	-	-	-	-	0-360	100	V
3	6.07	31.32	PK	35.4	-29.2	37.52	-	-	-	-	0-360	100	H
6	6.934	30.74	PK	35.6	-27.3	39.04	-	-	-	-	0-360	100	V

PK - Peak detector

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

TRACE MARKERS


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	2.036	36.4	PK	31.2	-25.3	42.3	-	-	-	-	0-360	100	H
4	2.093	36.93	PK	31.4	-25.3	43.03	-	-	-	-	0-360	100	V
2	3.151	34.34	PK	32.8	-32.3	34.84	-	-	-	-	0-360	201	H
5	3.251	34.86	PK	32.8	-33.5	34.16	-	-	-	-	0-360	201	V
3	6.764	31.07	PK	35.6	-27.5	39.17	-	-	-	-	0-360	201	H
6	7.003	30.56	PK	35.6	-26.7	39.46	-	-	-	-	0-360	100	V

PK - Peak detector

9.3. TRANSMITTER BELOW 1 GHz


GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)

HORIZONTAL PLOT



GFSK SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)

VERTICAL PLOT



BELOW 1 GHz TABLE

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T185 (dB/m)	Amp/Cbl (dB/m)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	30.0425	41.97	PK	21.8	-27.5	36.27	40	-3.73	0-360	100	V
2	32.465	42.29	PK	20	-27.5	34.79	40	-5.21	0-360	400	H
3	39.1375	51.21	PK	14.9	-27.4	38.71	40	-1.29	0-360	100	V
4	60.005	50.47	PK	7.3	-27.1	30.67	40	-9.33	0-360	100	V
5	66.5925	46.33	PK	8.1	-27.1	27.33	40	-12.67	0-360	100	V
6	94.43	45.82	PK	8.5	-26.9	27.42	43.52	-16.1	0-360	100	V
7	463.8	37.95	PK	16.6	-25.8	28.75	46.02	-17.27	0-360	200	H

PK - Peak detector