HCT CO.,LTD.
74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea
TEL: +82-31-645-6300 FAX: +82-31-645-6401

EMI TEST REPORT
FCC CERTIFICATION

Applicant: **LG Electronics MobileComm U.S.A., Inc.** **1000 Sylvan Avenue, Englewood Cliffs NJ 07632**	**Date of Receipt: April 24, 2017** **Date of Issue: June 15, 2017** **Test Report No. HCT-E-1706-F011** **HCT FRN: 0005866421**

FCC ID : **ZNFM700TV**

Rule Part(s) / Standard(s):	FCC CFR 47 PART 15 Subpart B Class B
FCC Classification:	JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type:	GSM/WCDMA/LTE Phone with Bluetooth4.2LE, WIFI802.11 b/g/n
Model Name:	LG-M700TV
Additional Model Name(s):	LGM700TV, M700TV
Date of Test:	May 04, 2017 – May 23, 2017

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)
I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.
HCT certifies that no party to application has been denial the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Yeong-Moo Kim
Test Engineer
EMC Team
Certification Division

Reviewed By

Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1706-F011	June 15, 2017	Initial Release

TABLE OF CONTENTS

PAGE

1. GENERAL INFORMATION 4
1.1 Description of EUT 4
1.2 Related Submittal(s) / Grant(s) 5
1.3 Test Facility 5
1.4 Calibration of Measuring Instrument 5
1.5 Tested System Details 6
1.6 Cable Description 7
1.7 Noise Suppression Parts on Cable. (I/O Cable) 7
2. MEASUREMENT UNCERTAINTY 8
3. DESCRIPTION OF TEST 9
3.1 Measurement of Conducted Emission 9
3.2 Measurement of Radiated Measurements 10
4. PRELIMINARY TEST 12
4.1 Conducted Emission Test 12
4. 2 Radiated Emission Test 12
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY 13
5.1 Conducted Emission Test 13
5.2 Radiated Emission Test 20
6. LIST OF TEST EQUIPMENT 22
7. CONCLUSION 23

ATTACHMENT: TEST SETUP PHOTOGRAPHS

1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFM700TV
Model	LG-M700TV
Additional Model(s)	LGM700TV, M700TV
EUT Type	GSM/WCDMA/LTE Phone with Bluetooth4.2LE, WIFI802.11 b/g/n
TX Frequency	824.20 MHz to 848.80 MHz (GSM 850) 1 850.20 MHz to 1 909.80 MHz (GSM 1 900) 826.40 MHz to 846.60 MHz (WCDMA 850) 1 852.4 MHz to 1 907.6 MHz (WCDMA 1 900) 1 850 MHz to 1 910 MHz (LTE B2) 2 496 MHz to 2 570 MHz (LTE B7) 704 MHz to 716 MHz (LTE B17) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)
RX Frequency	869.20 MHz to 893.80 MHz (GSM 850) 1 930.20 MHz to 1 989.80 MHz (GSM 1 900) 871.40 MHz to 891.60 MHz (WCDMA 850) 1 932.4 MHz to 1 987.6 MHz (WCDMA 1 900) 1 930 MHz to 1 990 MHz (LTE B2) 2 516 MHz to 2 690 MHz (LTE B7) 734 MHz to 746 MHz (LTE B17) 2 402 MHz to 2 480 MHz (Bluetooth) 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014.

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	90661 (July 07, 2015)
Radiated Field strength measurement facility 10 m Semi Anechoic chamber	

1.4 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipments, which is traceable to recognized national standards.
Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).

1.5 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-M700TV	LG	ZNFM700TV	Notebook PC, Earphone
USB Cable	EAD62377922	KSD	-	EUT, Notebook PC
Earphone	EAB64468401	CRESYN	-	EUT
Notebook PC	ProBook6560b	HP	DoC	Gateway , Notebook PC adaptor, RJ45 cable, Serial mouse
Notebook PC adaptor	Series PPP009L-E	LITE-On Technology	-	Notebook PC
Gateway	TL-WR747N	TP-LINK	-	RJ45 cable, Gateway adaptor
Gateway adaptor	T120150-2H1	TP-LINK	-	Gateway
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
RJ45 cable	-	-	-	Notebook PC, Gateway
SD card	256 GB EVO+UHS-I Micro SDXC U1	SAMSUNG	-	EUT

1.6 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.6
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.7 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	Both End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End

2. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.
All measurement uncertainty values are shown with a coverage factor of k = 2 to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	±1.82 dB (k = 2)
Radiated Emissions (30 MHz to 1 GHz)	±5.06 dB (k = 2)
Radiated Emissions (1 GHz to 6 GHz)	±5.0 dB (k = 2)
Radiated Emissions (6 GHz to 18 GHz)	±5.4 dB (k = 2)

3. DESCRIPTION OF TEST

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.

c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*

3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

a. The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
f. The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
g. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength (μV/m)	Quasi-Peak (dB(μV)/m)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	**Antenna Distance (m)**	**Peak (dB(μV)/m)**	**Average (dB(μV)/m)**
Above 1 000	3	74	54

3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5^{th} harmonic of the highest frequency or 40 ㎓, whichever is lower

3.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz

4. PRELIMINARY TEST

4.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

4. 2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
Kind of Test Site	Shielded Room
Temperature	24.8 °C
Relative Humidity	37.4 %
Test Date	May 04, 2017

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)



QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.152000	46.6	9.000	L1	9.6	19.3	65.9
0.156000	46.2	9.000	L1	9.6	19.4	65.7
0.186000	47.9	9.000	L1	9.6	16.3	64.2
0.192000	46.7	9.000	L1	9.6	17.3	63.9
0.196000	46.8	9.000	L1	9.6	17.0	63.8
0.206000	45.7	9.000	L1	9.6	17.7	63.4
3.502000	38.1	9.000	L1	9.8	17.9	56.0
3.558000	37.9	9.000	L1	9.8	18.1	56.0
3.630000	36.6	9.000	L1	9.8	19.4	56.0
3.642000	37.6	9.000	L1	9.8	18.4	56.0
3.710000	35.9	9.000	L1	9.8	20.1	56.0
3.782000	35.6	9.000	L1	9.8	20.4	56.0
8.658000	27.1	9.000	L1	10.1	32.9	60.0
8.700000	30.3	9.000	L1	10.1	29.7	60.0
12.018000	31.2	9.000	L1	10.2	28.8	60.0
12.196000	33.0	9.000	L1	10.2	27.0	60.0
12.410000	30.2	9.000	L1	10.2	29.8	60.0
18.078000	23.6	9.000	L1	10.3	36.4	60.0

CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	24.8	9.000	L1	9.6	31.2	56.0
0.158000	25.4	9.000	L1	9.6	30.2	55.6
0.166000	27.9	9.000	L1	9.6	27.3	55.2
0.186000	36.1	9.000	L1	9.6	18.1	54.2
0.192000	37.0	9.000	L1	9.6	16.9	53.9
0.196000	36.8	9.000	L1	9.6	17.0	53.8
3.502000	28.4	9.000	L1	9.8	17.6	46.0
3.558000	29.1	9.000	L1	9.8	16.9	46.0
3.630000	27.3	9.000	L1	9.8	18.7	46.0
3.642000	28.1	9.000	L1	9.8	17.9	46.0
3.710000	26.6	9.000	L1	9.8	19.4	46.0
3.782000	27.6	9.000	L1	9.8	18.4	46.0
8.658000	15.0	9.000	L1	10.1	35.0	50.0
8.700000	15.3	9.000	L1	10.1	34.7	50.0
12.018000	23.5	9.000	L1	10.2	26.5	50.0
12.196000	24.0	9.000	L1	10.2	26.0	50.0
12.362000	23.5	9.000	L1	10.2	26.5	50.0
18.078000	16.2	9.000	L1	10.3	33.8	50.0

Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	46.1	9.000	N	9.6	19.9	66.0
0.158000	44.9	9.000	N	9.6	20.7	65.6
0.190000	48.5	9.000	N	9.6	15.5	64.0
0.194000	50.1	9.000	N	9.6	13.7	63.9
0.200000	48.4	9.000	N	9.6	15.2	63.6
0.208000	45.2	9.000	N	9.6	18.1	63.3
4.068000	34.4	9.000	N	9.8	21.6	56.0
4.134000	38.2	9.000	N	9.8	17.8	56.0
4.144000	38.3	9.000	N	9.8	17.7	56.0
4.212000	37.5	9.000	N	9.9	18.5	56.0
4.280000	36.7	9.000	N	9.9	19.3	56.0
4.348000	36.2	9.000	N	9.9	19.8	56.0
5.210000	35.0	9.000	N	9.9	25.0	60.0
5.232000	36.5	9.000	N	9.9	23.5	60.0
5.246000	34.4	9.000	N	9.9	25.6	60.0
5.318000	34.7	9.000	N	9.9	25.3	60.0
5.326000	34.0	9.000	N	9.9	26.0	60.0
9.736000	30.8	9.000	N	10.1	29.2	60.0

CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	24.8	9.000	N	9.6	31.0	55.8
0.162000	26.4	9.000	N	9.6	29.0	55.4
0.182000	34.4	9.000	N	9.6	20.0	54.4
0.190000	36.8	9.000	N	9.6	17.3	54.0
0.194000	36.4	9.000	N	9.6	17.5	53.9
0.200000	36.2	9.000	N	9.6	17.4	53.6
4.070000	28.1	9.000	N	9.8	17.9	46.0
4.134000	29.4	9.000	N	9.8	16.6	46.0
4.142000	31.3	9.000	N	9.8	14.7	46.0
4.146000	30.7	9.000	N	9.8	15.3	46.0
4.212000	28.5	9.000	N	9.9	17.5	46.0
4.348000	25.9	9.000	N	9.9	20.1	46.0
5.178000	25.6	9.000	N	9.9	24.4	50.0
5.210000	25.8	9.000	N	9.9	24.2	50.0
5.234000	26.2	9.000	N	9.9	23.8	50.0
5.246000	25.6	9.000	N	9.9	24.4	50.0
5.390000	22.8	9.000	N	9.9	27.2	50.0
9.860000	22.6	9.000	N	10.1	27.4	50.0

5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.4 °C
Relative Humidity	39.3 %
Test Date	May 22, 2017

Frequency (MHz)	Quasi Peak (dBµV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
81.336673	24.7	229.0	H	155.0	18.6	15.3	40.0
85.372745	26.1	350.0	H	89.0	18.1	13.9	40.0
125.260521	26.8	365.0	V	279.0	21.5	16.7	43.5
199.981963	27.4	100.0	H	131.0	20.1	16.1	43.5
265.573146	34.8	150.0	H	290.0	22.8	11.2	46.0
275.977955	31.3	100.0	H	1.0	23.2	14.7	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak

-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	2 690 MHz
Upper Frequency of Measurement Range	1 GHz to 13.45 GHz
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	23.6 °C
Relative Humidity	39.6 %
Test Date	May 23, 2017

Frequency (MHz)	Peak (dBµV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
1399.749499	46.8	199.9	V	352.0	-12.8	27.2	74.0
1499.448898	46.2	299.8	V	150.0	-12.5	27.8	74.0
1799.849699	44.4	367.5	V	21.0	-12.3	29.6	74.0
1992.835671	49.5	100.0	V	206.0	-12.2	24.5	74.0
2658.366733	50.9	367.7	V	163.0	-9.1	23.1	74.0
2758.567134	35.1	299.8	V	187.0	-8.8	38.9	74.0

Frequency (MHz)	CAverage (dBµV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
1399.749499	44.0	199.9	V	352.0	-12.8	10.0	54.0
1499.448898	39.3	299.8	V	150.0	-12.5	14.7	54.0
1799.849699	38.7	367.5	V	21.0	-12.3	15.3	54.0
1992.835671	24.9	100.0	V	206.0	-12.2	29.1	54.0
2658.366733	24.5	367.7	V	163.0	-9.1	29.5	54.0
2758.567134	22.4	299.8	V	187.0	-8.8	31.6	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage

6. LIST OF TEST EQUIPMENT

	Type	Manufacturer	Model Name	Serial Number	Calibration Cycle	CAL Date
Conducted Emission						
☒	EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	06.29.2016
☐	EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	12.23.2016
☒	LISN	Rohde & Schwarz	ENV216	100073	1 year	12.23.2016
☒	LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	05.22.2017
☒	Software	Rohde & Schwarz	EMC32	-	-	-
Radiated Emission						
-For measurement below 1 GHz						
☒	EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	11.04.2016
☐	EMI Test Receiver	Rohde & Schwarz	ESU40	100514	1 year	10.10.2016
☒	Trilog Antenna	Schwarzbeck	VULB9168	760	2 year	04.06.2017
☒	Antenna master	HD GmbH	MA240	240/520	N/A	-
☒	Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒	Turn Table	EMCO	1060-2M	-	N/A	-
☐	Turn Table controller	EMCO	2090	9702-1224	N/A	-
☐	EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.16.2017
☐	Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐	Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒	Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz						
☒	EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	11.04.2016
☐	EMI Test Receiver	Rohde & Schwarz	ESU40	100514	1 year	10.10.2016
☐	Antenna master	HD GmbH	MA240	240/520	N/A	-
☐	Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒	Antenna master	INNCO Systems	MA4000-XP-ET	48709515	N/A	-
☒	Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515/L	N/A	-
☒	Turn Table	EMCO	1060-2M	-	N/A	-
☒	Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.07.2016
☐	Turn Table controller	EMCO	2090	9702-1224	N/A	-
☐	Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.04.2016
☒	Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
☐	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170541	2 year	09.03.2015
☐	Power Amplifier	CERNEX	CBL18265035	21873	1 year	01.19.2017
☐	Power Amplifier	CERNEX	CBL26405040	19660	1 year	07.15.2016
☐	Horn Antenna	Schwarzbeck	BBHA 9120D	1300	2 year	08.25.2016
☐	EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.16.2017
☐	Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒	Software	Rohde & Schwarz	EMC32	-	-	-

7. CONCLUSION

The data collected shows that the **EUT Type: GSM/WCDMA/LTE Phone with Bluetooth4.2LE, WIFI802.11 b/g/n**, **Model: LG-M700TV, FCC ID: ZNFM700TV** complies with §15.107 and §15.109 of the FCC rules.