

EMI TEST REPORT

FCC CERTIFICATION

Applicant:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs NJ 07632


Date of Receipt: May 29, 2017**Date of Issue: June 21, 2017****Test Report No. HCT-E-1706-F005-1****HCT FRN: 0005866421****FCC ID :****ZNFM700V**

Rule Part(s) / Standard(s): FCC CFR 47 PART 15 Subpart B Class B
FCC Classification: JBP (Part 15 B – Class B Computing Device Peripheral)
EUT Type: Portable device with Bluetooth and WLAN
Model Name: LG-M700V
Additional Model Name(s): LGM700V, M700V
Date of Test: June 09, 2017

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Tested By

Ju-Han You
Test Engineer
EMC Team
Certification Division

Reviewed By

Jin-Pyo Hong
Technical Manager
EMC Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.



DOCUMENT HISTORY

The revision history for this document is shown in table.

Version	Date	Description
HCT-E-1706-F005	June 12, 2017	Initial Release
HCT-E-1706-F005-1	June 21, 2017	Revision of EUT Type Name



TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	4
1.1 Description of EUT	4
1.2 Related Submittal(s) / Grant(s).....	4
1.3 Test Facility	4
1.4 Calibration of Measuring Instrument	4
1.5 Tested System Details.....	5
1.6 Cable Description.....	6
1.7 Noise Suppression Parts on Cable. (I/O Cable)	6
2. MEASUREMENT UNCERTAINTY	7
3. DESCRIPTION OF TEST	8
3.1 Measurement of Conducted Emission.....	8
3.2 Measurement of Radiated Measurements	10
4. PRELIMINARY TEST	11
4.1 Conducted Emission Test	11
4. 2 Radiated Emission Test	11
5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	12
5.1 Conducted Emission Test	12
5.2 Radiated Emission Test	19
6. LIST OF TEST EQUIPMENT	21
7. CONCLUSION	22

ATTACHMENT: TEST SETUP PHOTOGRAPHS



1. GENERAL INFORMATION

1.1 Description of EUT

Its basic purpose is used for communications.

FCC ID	ZNFM700V
Model	LG-M700V
Additional Model(s)	LGM700V, M700V
EUT Type	Portable device with Bluetooth and WLAN
Frequency Ranges	TX/RX 2 402 MHz to 2 480 MHz (Bluetooth) TX/RX 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Test Facility

Test site is located at 74, SEOICHEON-RO, 578BEON-GIL, MAJANG-MYEON, ICHEON-SI, GYEONGGI-DO, SOUTH KOREA. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014.

Measurement Facilities	Registration Number
Radiated Field strength measurement facility 3 m Semi Anechoic chamber	90661 (July 07, 2015)
Radiated Field strength measurement facility 10 m Semi Anechoic chamber	

1.4 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).



1.5 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Model Name	Manufacturer	FCC ID / DoC	Connected To
EUT	LG-M700V	LG	ZNFM700V	Notebook PC, Earphone
USB Cable	EAD62377922	KSD	-	EUT, Notebook PC
Earphone	EAB64468401	CRESYN	-	EUT
Notebook PC	ProBook6560b	HP	DoC	Gateway , Notebook PC adaptor, RJ45 cable, Serial mouse
Notebook PC adaptor	Series PPP009L-E	LITE-On Technology	-	Notebook PC
Gateway	TL-WR747N	TP-LINK	-	RJ45 cable, Gateway adaptor
Gateway adaptor	T120150-2H1	TP-LINK	-	Gateway
Serial mouse	Serial 2 button mouse	Radio shack	FSUGMZE3	Notebook PC
RJ45 cable	-	-	-	Notebook PC, Gateway



1.6 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
EUT	Micro USB	Y	Y	(P,D)1.0
	Earphone	N/A	Y	(D)1.2
Notebook PC	RJ 45	N/A	N	(D)1.6
	Serial (Mouse)	N/A	Y	(D)1.8
	DC in	N	N/A	(P)1.8
Gateway	DC in	N	N/A	(P)1.8

* The marked “(D)” means the data cable and “(P)” means the power cable.

1.7 Noise Suppression Parts on Cable. (I/O Cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
EUT	Micro USB	N	N/A	Y	Both End
	Earphone	N	N/A	Y	Both End
Notebook PC	RJ 45	N	N/A	N	N/A
	Serial (Mouse)	N	N/A	Y	Notebook PC End



2. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty (dB)
Conducted Emission (0.15 MHz to 30 MHz)	$\pm 1.82 \text{ dB } (k = 2)$
Radiated Emissions (30 MHz to 1 GHz)	$\pm 5.06 \text{ dB } (k = 2)$
Radiated Emissions (1 GHz to 6 GHz)	$\pm 5.0 \text{ dB } (k = 2)$
Radiated Emissions (6 GHz to 18 GHz)	$\pm 5.4 \text{ dB } (k = 2)$



3. DESCRIPTION OF TEST

3.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

[Conducted Emission Limits]

Frequency (MHz)	Resolution Bandwidth (kHz)	Quasi-Peak (dB(μV))	Average (dB(μV))
0.15 to 0.5	9	66 to 56*	56 to 46*
0.5 to 5	9	56	46
5 to 30	9	60	50

**Decreases with the logarithm of the frequency.*



3.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.(1 GHz to 40 GHz)

[Radiated Emission Limits]

Frequency (MHz)	Antenna Distance (m)	Field Strength ($\mu\text{V/m}$)	Quasi-Peak (dB(μV)/m)
30 to 88	3	100	40.0
88 to 216	3	150	43.5
216 to 960	3	200	46.0
Above 960	3	500	54.0
Frequency (MHz)	Antenna Distance (m)	Peak (dB(μV)/m)	Average (dB(μV)/m)
Above 1 000	3	74	54




3.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

3.3 Configuration of Tested System



Power Line: 120 VAC, 60 Hz



4. PRELIMINARY TEST

4.1 Conducted Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

4. 2 Radiated Emission Test

It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode



5. CONDUCTED AND RADIATED EMISSION TEST SUMMARY


5.1 Conducted Emission Test

The test results of conducted emission at mains ports provide the following information:

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak, CISPR-Average
Bandwidth	9 kHz (6 dB)
Operation Mode	Data Communication mode
Kind of Test Site	Shielded Room
Temperature	22.7 °C
Relative Humidity	38.4 %
Test Date	June 09, 2017

- Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage

**Figure 1: Spectral Diagrams, Conducted Emission, AC Main Port, Line (L1)**




QuasiPeak Final Result, Line (L1)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	46.9	9.000	L1	9.6	19.1	66.0
0.154000	46.1	9.000	L1	9.6	19.7	65.8
0.162000	44.9	9.000	L1	9.6	20.5	65.4
0.186000	46.1	9.000	L1	9.6	18.1	64.2
0.200000	45.6	9.000	L1	9.6	18.0	63.6
0.208000	42.6	9.000	L1	9.6	20.7	63.3
1.066000	38.3	9.000	L1	9.7	17.7	56.0
1.082000	37.4	9.000	L1	9.7	18.6	56.0
1.138000	36.8	9.000	L1	9.7	19.2	56.0
4.250000	32.4	9.000	L1	9.9	23.6	56.0
4.318000	31.3	9.000	L1	9.9	24.7	56.0
4.408000	31.3	9.000	L1	9.9	24.7	56.0
5.316000	30.1	9.000	L1	9.9	29.9	60.0
9.694000	31.6	9.000	L1	10.1	28.4	60.0
9.698000	31.8	9.000	L1	10.1	28.2	60.0
9.702000	31.1	9.000	L1	10.1	28.9	60.0
9.756000	31.4	9.000	L1	10.1	28.6	60.0
9.788000	31.3	9.000	L1	10.1	28.7	60.0



CAverage Final Result, Line (L1)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.154000	29.1	9.000	L1	9.6	26.7	55.8
0.162000	27.6	9.000	L1	9.6	27.8	55.4
0.192000	34.7	9.000	L1	9.6	19.3	53.9
0.196000	33.8	9.000	L1	9.6	20.0	53.8
0.202000	32.9	9.000	L1	9.6	20.7	53.5
0.208000	28.2	9.000	L1	9.6	25.1	53.3
1.066000	31.0	9.000	L1	9.7	15.0	46.0
4.168000	25.3	9.000	L1	9.9	20.7	46.0
4.250000	23.1	9.000	L1	9.9	22.9	46.0
4.318000	22.0	9.000	L1	9.9	24.0	46.0
4.388000	21.3	9.000	L1	9.9	24.7	46.0
4.408000	22.4	9.000	L1	9.9	23.6	46.0
5.316000	21.5	9.000	L1	9.9	28.5	50.0
5.462000	19.3	9.000	L1	9.9	30.7	50.0
9.648000	22.4	9.000	L1	10.1	27.6	50.0
9.694000	22.6	9.000	L1	10.1	27.4	50.0
9.702000	22.3	9.000	L1	10.1	27.7	50.0
9.990000	21.1	9.000	L1	10.1	28.9	50.0

**Figure 2: Spectral Diagrams, Conducted Emission, AC Main Port, Line (N)**



QuasiPeak Final Result, Line (N)

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	46.6	9.000	N	9.6	19.4	66.0
0.154000	46.0	9.000	N	9.6	19.8	65.8
0.160000	45.1	9.000	N	9.6	20.3	65.5
0.164000	44.8	9.000	N	9.6	20.4	65.3
0.170000	43.6	9.000	N	9.6	21.3	65.0
0.196000	43.2	9.000	N	9.6	20.6	63.8
1.056000	37.3	9.000	N	9.7	18.7	56.0
1.086000	37.7	9.000	N	9.7	18.3	56.0
1.108000	36.9	9.000	N	9.7	19.1	56.0
1.118000	36.6	9.000	N	9.7	19.4	56.0
1.126000	36.7	9.000	N	9.7	19.3	56.0
1.156000	34.7	9.000	N	9.7	21.3	56.0
9.228000	34.4	9.000	N	10.1	25.6	60.0
9.236000	34.2	9.000	N	10.1	25.8	60.0
9.322000	35.0	9.000	N	10.1	25.0	60.0
9.336000	34.9	9.000	N	10.1	25.1	60.0
9.406000	35.0	9.000	N	10.1	25.0	60.0
9.536000	34.7	9.000	N	10.1	25.3	60.0



CAverage Final Result, Line (N)

Frequency (MHz)	CAverage (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.150000	30.4	9.000	N	9.6	25.6	56.0
0.154000	24.4	9.000	N	9.6	31.4	55.8
0.164000	27.2	9.000	N	9.6	28.0	55.3
0.168000	28.4	9.000	N	9.6	26.6	55.1
0.188000	33.2	9.000	N	9.6	20.9	54.1
0.194000	31.7	9.000	N	9.6	22.1	53.9
1.070000	31.2	9.000	N	9.7	14.8	46.0
1.078000	31.2	9.000	N	9.7	14.8	46.0
1.086000	31.4	9.000	N	9.7	14.6	46.0
1.094000	31.8	9.000	N	9.7	14.2	46.0
1.126000	30.6	9.000	N	9.7	15.4	46.0
1.156000	28.6	9.000	N	9.7	17.4	46.0
9.228000	25.2	9.000	N	10.1	24.8	50.0
9.238000	25.8	9.000	N	10.1	24.2	50.0
9.262000	25.4	9.000	N	10.1	24.6	50.0
9.344000	25.8	9.000	N	10.1	24.2	50.0
9.406000	26.2	9.000	N	10.1	23.8	50.0
9.536000	25.7	9.000	N	10.1	24.3	50.0



5.2 Radiated Emission Test

The test results of radiated emission provide the following information:

-For Measurement Below 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Quasi-Peak
Bandwidth	120 kHz (6 dB)
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	22.9 °C
Relative Humidity	38.1 %
Test Date	June 09, 2017

Frequency (MHz)	Quasi Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
50.334670	29.6	100.0	V	318.0	23.4	10.4	40.0
56.006012	32.0	100.0	V	290.0	23.1	8.0	40.0
82.038076	28.8	250.0	H	63.0	18.5	11.2	40.0
265.561122	34.9	115.0	H	289.0	22.8	11.1	46.0
375.012024	36.3	100.0	H	204.0	26.0	9.7	46.0
500.014028	38.6	100.0	H	39.0	28.9	7.4	46.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak



-For Measurement Above 1 GHz

Rule Part / Standard	FCC PART 15 Subpart B Class B
Detector	Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz) CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz)
Highest Operating Frequency	2 480 MHz
Upper Frequency of Measurement Range	1 GHz to 12.4 GHz
Operation Mode	Data Communication mode
Kind of Test Site	3 m semi anechoic chamber
Temperature	22.9 °C
Relative Humidity	38.1 %
Test Date	June 09, 2017

Frequency (MHz)	Peak (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1157.164329	31.7	250.0	V	164.0	-13.5	42.3	74.0
1399.749499	47.5	220.6	V	25.0	-12.8	26.5	74.0
1499.048096	45.7	308.6	V	146.0	-12.5	28.3	74.0
1997.945892	46.8	100.0	V	223.0	-12.2	27.2	74.0
2659.368737	44.1	150.1	V	332.0	-9.1	29.9	74.0
4480.911824	41.9	299.6	V	251.0	-5.7	32.1	74.0

Frequency (MHz)	CAverage (dBμV/m)	Antenna Height (cm)	POL. (H/V)	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1157.164329	18.7	250.0	V	164.0	-13.5	35.3	54.0
1399.749499	44.9	220.6	V	25.0	-12.8	9.1	54.0
1499.048096	39.8	308.6	V	146.0	-12.5	14.2	54.0
1997.945892	20.7	100.0	V	223.0	-12.2	33.3	54.0
2659.368737	22.8	150.1	V	332.0	-9.1	31.2	54.0
4480.911824	26.6	299.6	V	251.0	-5.7	27.4	54.0

- Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage



6. LIST OF TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Name</u>	<u>Serial Number</u>	<u>Calibration Cycle</u>	<u>CAL Date</u>
<u>Conducted Emission</u>					
☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100033	1 year	06.29.2016
☐ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	1 year	12.23.2016
☒ LISN	Rohde & Schwarz	ENV216	100073	1 year	12.23.2016
☒ LISN	Rohde & Schwarz	ESH3-Z5	100282	1 year	05.22.2017
☒ Software	Rohde & Schwarz	EMC32	-	-	-
<u>Radiated Emission</u>					
-For measurement below 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	11.04.2016
☐ EMI Test Receiver	Rohde & Schwarz	ESU40	100514	1 year	10.10.2016
☒ Trilog Antenna	Schwarzbeck	VULB9168	760	2 year	04.06.2017
☒ Antenna master	HD GmbH	MA240	240/520	N/A	-
☒ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒ Turn Table	EMCO	1060-2M	-	N/A	-
☐ Turn Table controller	EMCO	2090	9702-1224	N/A	-
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.16.2017
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	N/A	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32	-	-	-
-For measurement above 1 GHz					
☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	1 year	11.04.2016
☐ EMI Test Receiver	Rohde & Schwarz	ESU40	100514	1 year	10.10.2016
☐ Antenna master	HD GmbH	MA240	240/520	N/A	-
☐ Antenna master controller	HD GmbH	HD 100	100/637	N/A	-
☒ Antenna master	INNCO Systems	MA4000-XP-ET	48709515	N/A	-
☒ Antenna master controller	INNCO Systems	CO 3000	CO 3000/870/ 35990515/L	N/A	-
☒ Turn Table	EMCO	1060-2M	-	N/A	-
☒ Power Amplifier	CERNEX	CBLU5183530	24348	1 year	06.01.2017
☐ Turn Table controller	EMCO	2090	9702-1224	N/A	-
☐ Power Amplifier	CERNEX	CBLU1183540	21691	1 year	07.04.2016
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	296	2 year	10.12.2016
☐ Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170541	2 year	09.03.2015
☐ Power Amplifier	CERNEX	CBL18265035	21873	1 year	01.19.2017
☐ Power Amplifier	CERNEX	CBL26405040	19660	1 year	07.15.2016
☐ Horn Antenna	Schwarzbeck	BBHA 9120D	1300	2 year	08.25.2016
☐ EMI Test Receiver	Rohde & Schwarz	ESU 26	100241	1 year	05.16.2017
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	N/A	-
☒ Software	Rohde & Schwarz	EMC32	-	-	-



7. CONCLUSION

The data collected shows that the **EUT Type: Portable device with Bluetooth and WLAN,**
Model: LG-M700V, FCC ID: ZNFM700V complies with §15.107 and §15.109 of the FCC rules.