Test Report
Part 15 Subpart C 15.247

Equipment under test Bluetooth Earbud

Model name TONE-T60Q

HVINs TONE-T60Q, TONE-UF60Q, TONE-DF60Q

FVIN 1.0

FCC ID ZNFTONET60Q

Applicant LG Electronics USA, Inc.

Manufacturer LG Electronics Inc.

Date of test(s) 2022.06.09 ~ 2022.06.13

Date of issue 2022.06.14

Issued to

LG Electronics USA, Inc.

111 Sylvan Avem North Building, Englewood Cliffs, New Jersey, United States
Tel: +82-10-9193-9881

Issued by

KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450

Test and report completed by :	**Report approval by :**
Bong-Seok, Kim Test engineer	Yeong-Jun, Cho Technical manager

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Revision history

Revision	Date of issue	Test report No.	Description
-	2022.06.14	KES-RF1-22T0059	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

TABLE OF CONTENTS

1. General information 4
1.1. EUT description 4
1.2. Test configuration 4
1.3. Information about derivative model 5
1.4. Accessory information 5
1.5. Sample calculation 5
1.6. Measurement Uncertainty 5
1.7. Frequency/channel operations 6
2. Summary of tests 7
3. Test results 8
3.1. 99% Occupied Bandwidth 8
3.2. 6 dB bandwidth 13
3.3. Output power 18
3.4. Power spectral density 20
3.5. Radiated restricted band and emissions 25
3.6. Conducted spurious emissions & band edge 60
Appendix A. Measurement equipment 70
Appendix B. Test setup photos 71

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1. General information

Applicant:	LG Electronics USA, Inc.
Applicant address:	111 Sylvan Avem North Building, Englewood Cliffs, New Jersey, United States
Test site:	KES Co., Ltd.
Test site address:	☐3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea ☒473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Test Facility	FCC Accreditation Designation No.: KR0100, Registration No.: 444148 ISED Registration No.: 23298
FCC,IC rule part(s):	FCC : 15.247 / IC : RSS-247
FCC ID:	ZNFTONET60Q
IC ID:	2703C-TONET60Q
Test device serial No.:	☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test	Bluetooth Earbud
Frequency range	2 402 ㎒ ~ 2 480 ㎒ (BDR/EDR) **2 402 ㎒ ~ 2 480 ㎒ (LE 1,2Mbps)**
Model	TONE-T60Q
Modulation technique	GFSK, π/4DQPSK, 8DPSK
Number of channels	2 402 ㎒ ~ 2 480 ㎒ (BDR / EDR) : 79ch **2 402 ㎒ ~ 2 480 ㎒ (LE 1,2Mbps) : 40ch**
Antenna specification	Left unit : PCB Antenna // Peak gain: 0.63 ㏈i Right unit : PCB Antenna // Peak gain: 0.95 ㏈i
Power source	DC 3.85 V (Battery)
H/W version	1.0
S/W version	1.0

1.2. Test configuration

The **LG Electronics USA, Inc //Bluetooth Earbud // TONE-T60Q // FCC ID: ZNFTONET60Q // IC ID: 2703C-TONET60Q** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
KDB 558074 D01 v05 r02
ANSI C63.10-2013

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.3. Information about derivative model

N/A

1.4. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
-	-	-	-	-

1.5. Sample calculation

Where relevant, the following sample calculation is provided
For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Offset(㎤) = RF cable loss(㎤) + attenuator factor(㎤).
= 0.72 + 10 = 10.72 (㎤)

For Radiation test :
Field strength level (㎤㎶/m) = Measured level (㎤㎶) + Antenna factor (㎤) + Cable loss (㎤) – Amplifier gain (㎤)

1.6. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.46 ㎤
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1㎓	4.40 ㎤
	Above 1㎓	5.94 ㎤
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

1.7. Frequency/channel operations

Ch.	Frequency (㎒)	Rate(Mbps)
00	2402	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps
⋮	⋮	⋮
40	2442	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps
⋮	⋮	⋮
78	2480	BDR 1 Mbps, EDR 2 Mbps, EDR 3 Mbps

Ch.	Frequency (㎒)	Rate(Mbps)
00	**2402**	**LE 1,2 Mbps**
⋮	⋮	⋮
20	**2442**	**LE 1,2 Mbps**
⋮	⋮	⋮
39	**2480**	**LE 1,2 Mbps**

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

2. Summary of tests

Section in FCC Part 15	Section in RSS-247 & Gen	Parameter	Test results
-	RSS-Gen 6.7	99% Occupied bandwidth	Pass
15.247(a)(2)	RSS-247 5.2(a)	6 dB bandwidth	
15.247(b)(3)	RSS-247 5.4(d)	Output power	Pass
15.247(e)	RSS-247 5.2(b)	Power spectral density	Pass
15.205 15.209	RSS-247 5.5 RSS-Gen 8.9,8,10	Radiated restricted band and emission	Pass
15.247(d)	RSS-247 5.5	Conducted spurious emission and band edge	Pass
15.207(a)	RSS-Gen 8.8	AC Conducted emissions	N/A(1)

Note.
1. This product is powered by battery.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3. Test results

3.1. 99% Occupied Bandwidth

Test procedure

ANSI C63.10-2013 clause 6.9.2 and 6.9.3

Test setup



Test setting

1. Span = The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
2. RBW = The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW 3. VBW = shall be approximately three times the RBW
4. Sweep = auto
5. Detector function = Peak
6. Trace = Max hold

Limit

None; for reporting purpose only.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Mode : LE 1Mbps(Left unit)

Frequency(㎒)	99% occupied bandwidth(㎒)	Limit(㎒)
2 402	1.05	-
2 442	1.05	
2 480	1.05	

Test plots

LE 1Mbps(Left Unit)

N/A

Mode : LE 2Mbps(Left unit)

Frequency(㎒)	99% occupied bandwidth(㎒)	Limit(㎒)
2 402	2.07	-
2 442	2.07	
2 480	2.07	

Test plots

LE 2Mbps(Left Unit)





N/A

Mode : LE 1Mbps(Right unit)

Frequency(㎒)	99% occupied bandwidth(㎒)	Limit(㎒)
2 402	1.05	-
2 442	1.05	
2 480	1.05	

Test plots

LE 1Mbps(Right Unit)





N/A

Mode : LE 2Mbps(Right unit)

Frequency(㎒)	99% occupied bandwidth(㎒)	Limit(㎒)
2 402	2.07	-
2 442	2.07	
2 480	2.07	

Test plots

LE 2Mbps(Right Unit)





N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.2. 6 dB bandwidth

Test procedure

ANSI C63.10-2013 - Section 11.8.2

Test setup



ANSI C63.10-2013 - Section 11.8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Limit

According to RSS-247 5.2(a), The minimum 6 dB bandwidth shall be 500 kHz.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

Frequency(㎒)	6 ㏈ bandwidth(㎒)	Limit(㎒)
2 402	0.76	≥ 0.500
2 442	0.76	
2 480	0.76	

LE 1 Mbps (Left Unit)







N/A

Frequency(㎒)	6 ㏈ bandwidth(㎒)	Limit(㎒)
2 402	1.26	≥ 0.500
2 442	1.25	
2 480	1.25	

LE 2 Mbps (Left Unit)

N/A

Frequency(㎒)	6 ㏈ bandwidth(㎒)	Limit(㎒)
2 402	0.72	≥ 0.500
2 442	0.72	
2 480	0.73	

LE 1 Mbps (Right Unit)



N/A

Frequency(㎒)	6 ㏈ bandwidth(㎒)	Limit(㎒)
2 402	1.25	≥ 0.500
2 442	1.26	
2 480	1.25	

LE 2 Mbps (Right Unit)	
	N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.3. Output power

Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

Test setup



ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS ba ndwidth and shall use a fast-responding diode detector.

ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 ㎒, 2 400~2 483.5 ㎒, and 5 725~5 850 ㎒ bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Limit

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results

[Left Unit]

Mode	2 402 ㎒		2 442 ㎒		2 480 ㎒	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 1 Mbps	8.27	8.36	8.14	8.23	8.03	8.13

Mode	2 402 ㎒		2 442 ㎒		2 480 ㎒	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 2 Mbps	8.28	8.39	8.16	8.26	8.04	8.15

[Right Unit]

Mode	2 402 ㎒		2 442 ㎒		2 480 ㎒	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 1 Mbps	7.92	8.02	7.83	7.93	7.78	7.89

Mode	2 402 ㎒		2 442 ㎒		2 480 ㎒	
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)
LE 2 Mbps	7.91	8.05	7.83	7.93	7.79	7.89

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

3.4. Power spectral density

Test procedure

ANSI C63.10-2013 - Section 11.10.2

Test setup



Section 10.2 & ANSI C63.10-2013 - Section 11.10.2

a. Set analyzer center frequency to DTS channel center frequency.
b. Set the span to 1.5 times the DTS bandwidth.
c. Set the RBW to 3 ㎑ ≤ RBW ≤ 100 ㎑
d. Set the VBW ≥ [3 × RBW].
e. Detector = peak.
f. Sweep time = auto couple.
g. Trace mode = max hold.
h. Allow trace to fully stabilize.
i. Use the peak marker function to determine the maximum amplitude level within the RBW.
j. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Limit

According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 ㏈m in any 3 ㎑ band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Limit

According to RSS-247 5.2(b), The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Results

Frequency(㎒)	PSD (dBm)	Limit(dBm)
2 402	-7.62	8
2 442	-7.80	
2 480	-7.84	

LE 1 Mbps(Left Unit)







Blank

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Frequency(㎒)	PSD (dBm)	Limit(dBm)
2 402	-9.99	8
2 442	-10.26	
2 480	-10.25	

LE 2 Mbps(Left Unit)







Blank

Frequency(㎒)	PSD (dBm)	Limit(dBm)
2 402	-7.42	8
2 442	-7.74	
2 480	-7.84	

LE 1 Mbps(Right Unit)







Blank

Frequency(㎒)	PSD (dBm)	Limit(dBm)
2 402	-9.95	8
2 442	-10.16	
2 480	-10.48	

LE 2 Mbps(Right Unit)







Blank

3.5. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 ㎑ to 30 ㎒ Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 ㎒ to 1 ㎓ emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 ㎓ to the tenth harmonic of the highest fundamental frequency or to 40 ㎓ emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

Test procedure below 30 ㎒

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that **parallel** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **parallel.**
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 ㎒

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

5. Spectrum analyzer settings for f < 1 ㎓:
   ① Span = wide enough to fully capture the emission being measured
   ② RBW = 100 ㎑
   ③ VBW ≥ RBW
   ④ Detector = quasi peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
6. Spectrum analyzer settings for f ≥1 ㎓: Peak
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 ㎒
   ④ Detector = peak
   ⑤ Sweep time = auto
   ⑥ Trace = max hold
   ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for f ≥1 ㎓: Average
   ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
   ② RBW = 1 ㎒
   ③ VBW ≥ 3 × RBW
   ④ Detector = RMS, if span/(# of points in sweep) ≤ (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
   ⑤ Averaging type = power(i.e., RMS)
      1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
      2) Some instruments require linear display mode in order to use linear voltage averaging. Log or ㏈ averaging shall not be used.
   ⑥ Sweep = auto
   ⑦ Trace = max hold
   ⑧ Perform a trace average of at least 100 traces.
   ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
      1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is 10 log(1/x), where x is the duty cycle.
      2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is 20 log(1/x), where x is the duty cycle.
      3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Note.

1. f <30 ㎒, extrapolation factor of 40 ㏈/decade of distance. $F_d = 40\log(D_m/Ds)$
   f ≥30 ㎒, extrapolation factor of 20 ㏈/decade of distance. $F_d = 20\log(D_m/Ds)$
   Where:
   F_d = Distance factor in ㏈
   D_m = Measurement distance in meters
   D_s = Specification distance in meters
2. Field strength(㏈㎶/m) = Level(㏈㎶) + CF (㏈) + or DCF(㏈)
3. Margin(㏈) = Limit(㏈㎶/m) - Field strength(㏈㎶/m)
4. Emissions below 18 ㎓ were measured at a 3 meter test distance while emissions above 18 ㎓ were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation.**
6. The worst-case emissions are reported however emissions whose levels were not within 20 ㏈ of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 ㎑ to 30 ㎒. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values：

Frequency (㎒)	Distance (Meters)	Radiated (㎶/m)
0.009 ~ 0.490	300	2400/F(㎑)
0.490 ~ 1.705	30	24000/F(㎑)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 ㎒, 76 ~ 88 ㎒, 174 ~ 216 ㎒ or 470 ~ 806 ㎒. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Limit

According to RSS-Gen, Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits：

Frequency (㎒)	Distance (Meters)	Radiated (㎶/m)
0.009 ~ 0.490	300	2 400 / F(㎑)
0.490 ~ 1.705	30	24 000 / F(㎑)
1.705 ~ 30.0	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960*	3	500

* Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.

Note: Transmitting devices are not permitted in restricted frequency bands unless stated otherwise in the specific RSS.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Duty cycle

Regarding to KDB 558074 D01_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

a) A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.

b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

Mode : Left unit(LE 1,2 Mbps)

T_{on} time (㎳)	Period (㎳)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (㏈)
2.16	2.50	0.86	86.40	0.63
1.10	1.87	0.59	58.69	2.31

Mode : Right unit(LE 1,2 Mbps)

T_{on} time (㎳)	Period (㎳)	Duty cycle (Linear)	Duty cycle (%)	Duty cycle correction factor (㏈)
2.16	2.50	0.86	86.35	0.64
1.10	1.87	0.59	58.76	2.31

Duty cycle (Linear) = T_{on} time/Period

DCF(Duty cycle correction factor (㏈)) = 10log(1/duty cycle)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Mode : Left Unit (LE 1,2 Mbps)

Middle channel	Middle channel

Mode : Right Unit (LE 1,2 Mbps)

Middle channel	Middle channel
	

Test results (Below 30 ㎒)

Mode:	LE 2 Mbps (Left Unit)
Distance of measurement:	3 meter
Channel:	00 (Worst case)

Parallel



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	0.601	H	24.0	19.9	43.9	72.0	28.1	99.7	28.7	
2	2.480	H	20.6	20.1	40.7	69.5	28.8	99.7	132.3	
3	3.548	H	23.2	19.9	43.1	69.5	26.4	99.7	228.4	

Note.
1. No spurious emission were detected under 30 ㎒, the above test result is the peak result.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Below 1 000 ㎒)

Mode:	LE 2 Mbps (Left Unit)
Distance of measurement:	3 meter
Channel:	00 (Worst case)

Horizontal // Vertical



Final Result

No.	Range	Frequency [MHz]	Pol	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	Range1	33.007	V	40.0	-14.0	26.0	40.0	14.0	99.8	6.4	
2	Range1	156.003	H	50.8	-13.1	37.7	43.5	5.8	200.1	153.3	
3	Range1	163.375	H	52.8	-13.6	39.2	43.5	4.3	200.1	1.6	
4	Range1	164.733	V	44.0	-13.6	30.4	43.5	13.1	149.9	294.3	
5	Range1	167.934	H	53.4	-13.9	39.5	43.5	4.0	200.1	158.1	
6	Range1	167.934	V	46.4	-13.9	32.5	43.5	11.0	99.8	143.5	
7	Range1	179.962	H	52.1	-14.6	37.5	43.5	6.0	200.1	2.6	
8	Range1	179.962	V	43.7	-14.6	29.1	43.5	14.4	149.9	300.5	
9	Range1	263.964	H	47.6	-13.5	34.1	46.0	11.9	99.8	122.5	
10	Range1	359.994	V	40.0	-11.0	29.0	46.0	17.0	149.9	65.6	
11	Range1	443.996	H	43.2	-8.6	34.6	46.0	11.4	99.8	58.3	
12	Range1	456.024	V	37.6	-8.3	29.3	46.0	16.7	99.8	195.4	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Below 30 ㎒)

Mode:	LE 1 Mbps (Right Unit)
Distance of measurement:	3 meter
Channel:	00 (Worst case)

Parallel



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	0.526	H	22.5	19.8	42.3	73.2	30.9	99.7	353.0	
2	2.483	H	19.4	20.1	39.5	69.5	30.0	99.7	131.6	
3	3.544	H	23.5	19.9	43.4	69.5	26.1	99.7	172.6	

Note.

1. No spurious emission were detected under 30 ㎒, the above test result is the peak result.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test results (Below 1 000 ㎒)

Mode:	LE 1 Mbps (Right Unit)
Distance of measurement:	3 meter
Channel:	00 (Worst case)

Horizontal // Vertical



Final Result

No.	Range	Frequency [MHz]	Pol	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	Range1	158.913	V	41.4	-13.3	28.1	43.5	15.4	99.8	122.6	
2	Range1	163.375	H	52.0	-13.6	38.4	43.5	5.1	199.8	356.0	
3	Range1	167.934	H	53.2	-13.9	39.3	43.5	4.2	199.8	0.9	
4	Range1	168.031	V	45.9	-13.9	32.0	43.5	11.5	99.8	131.9	
5	Range1	179.865	V	43.7	-14.6	29.1	43.5	14.4	150.3	297.0	
6	Range1	180.059	H	52.9	-14.6	38.3	43.5	5.2	199.8	3.6	
7	Range1	192.087	V	42.3	-15.5	26.8	43.5	16.7	99.8	134.9	
8	Range1	204.115	H	51.3	-15.9	35.4	43.5	8.1	99.8	141.0	
9	Range1	359.994	H	44.3	-11.0	33.3	46.0	12.7	99.8	234.7	
10	Range1	359.994	V	40.2	-11.0	29.2	46.0	16.8	150.3	77.8	
11	Range1	455.927	V	37.2	-8.3	28.9	46.0	17.1	99.8	208.8	
12	Range1	456.024	H	42.8	-8.3	34.5	46.0	11.5	99.8	64.3	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr