



HCT CO., LTD.

CERTIFICATION DIVISION
105-1, JANGAM-RI, MAJANG-MYEON, ICHEON-SI, KYOUNGKI-DO, REPUBLIC OF KOREA
TEL: +82 31 645 6300 FAX: +82 31 645 6401

EMI CERTIFICATION REPORT

Applicant:

LG Electronics MobileComm U.S.A., Inc.
10101 Old Grove Road, San Diego, CA 92131

Date of Issue: February 01, 2012

Test Report No.: HCTE1201FE17-1

Test Site: HCT CO., LTD.

HCT FRN: 0005-8664-21

FCC ID:

ZNFUD711

Rule Part(s) / Standard(s) : FCC PART 15 Subpart B Class B

Equipment Type : PCS WCDMA Modem

Model(s) Name : UD711, LG-UD711, LGUD711

Port / Connector(s) : USB Port

Date of Test : January 14, 2012

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

Report prepared by
: Jeong-Hyeon Choi
Test Engineer of EMC Team

Approved by
: Sang-Jun Lee
Manager of EMC Team

TABLE OF CONTENTS

	PAGE
1. GENERAL INFORMATION	3
1.1 Product Description.....	3
1.2 Related Submittal(s) / Grant(s).....	3
1.3 Tested System Details.....	4
1.4 Cable Description.....	5
1.5 Noise Suppression Parts on Cable. (I/O cable)	5
1.6 Test Methodology.....	6
1.7 Test Facility	6
1.8 Frequency Range of Radiated Measurements.....	6
2. SYSTEM TEST CONFIGURATION.....	7
2.1 Configuration of Test System.....	7
3. PRELIMINARY TEST	8
3.1 Conducted Emission Test	8
3. 2 Radiated Emission Test	8
4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY	9
4.1 Conducted Emission Test	9
4.2 Radiated Emission Test	10
5. FIELD STRENGTH CALCULATION	15
6. TEST EQUIPMENT	16
7. CONCLUSION	17

ATTACHMENT: TEST SETUP PHOTOGRAPHS

1. GENERAL INFORMATION

1.1 Product Description

Equipment Under Test is **PCS WCDMA Modem, Model: UD711** manufactured by **LG Electronics Mobilecomm U.S.A., Inc.** Its basic purpose is used for communications.

Model	UD711
Additional Model	LG-UD711, LGUD711
FCC ID	ZNFUD711
E.U.T Type	PCS WCDMA Modem
TX Frequency	1 852.4 MHz to 1 907.6 MHz (WCDMA 1 900)
RX Frequency	1 932.4 MHz to 1 987.6 MHz (WCDMA 1 900)

1.2 Related Submittal(s) / Grant(s)

Original submittal only.

1.3 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

Device Type	Manufacturer	Model Name	FCC ID / DoC	Connected To
PCS WCDMA Modem	LG	UD711	ZNFUD711	Notebook PC
Notebook PC	LG	X140-02	DoC	E.U.T Notebook PC adaptor
Notebook PC adaptor	DELTA (JIANG SU)	ADP-40PH AD	-	Notebook PC
Mouse	PRIMAX ELECTRONICS	MOARUO	DoC	Notebook PC
Micro SD card (2 GB)	SanDisk	-	-	E.U.T
RJ45 cable	-	-	-	Router Notebook PC
Router	-	HIGATE PLUS K12L012.00	-	Notebook PC
Router adaptor	FAIRONE ELECTRONICS	FLDE0501000K	-	Router

1.4 Cable Description

Product Name	Port	Power Cord Shielded (Y/N)	I/O Cable Shielded (Y/N)	Length (m)
PCS WCDMA Modem	USB	-	-	-
Notebook PC	RJ 45	-	N	(D)1.5
	USB (Mouse)	-	Y	(D)1.8

* The marked "(D)" means the data cable and "(P)" means the power cable.

1.5 Noise Suppression Parts on Cable. (I/O cable)

Product Name	Port	Ferrite Bead (Y/N)	Location	Metal Hood (Y/N)	Location
PCS WCDMA Modem	USB	N	N/A	Y	Notebook PC End
Notebook PC	RJ 45	N	N/A	N	Both End
	USB (Mouse)	-	-	Y	Notebook PC End

1.6 Test Methodology

Both Conducted and Radiated testing was performed according to the procedures in ANSI C63.4/2003. Radiated testing was performed at an antenna to E.U.T distance of 3 m

1.7 Test Facility

The 3 m semi anechoic chamber used to collect the test data is located at the 105-1, Jangam-Ri, Majang-Myeon, Icheon-Si, Kyongki-Do, Republic of Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4.

Detailed description of test facilities was submitted to the Commission and accepted dated Mar 02, 2011 (Registration Number: 90661)

1.8 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705 to 108	1 000
108 to 500	2 000
500 to 1 000	5 000
Above 1 000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower


2. SYSTEM TEST CONFIGURATION

2.1 Configuration of Test System

Power Line Conducted test : E.U.T was connected to LISN via Notebook PC adaptor and Base Station. Preliminary Power Line Conducted Emission tests were performed by using the procedure in ANSI C63.4/2003 7.2.3 to determine the worst operating conditions.

Radiated Emission test : Preliminary Radiated Emission tests were performed by using the procedure in ANSI C63.4/2003 8.3.1.1 to determine the worst operating condition. Final Radiated Emission tests were performed at 3 m semi-anechoic chamber.

[Configuration of Tested System]



3. PRELIMINARY TEST

3.1 Conducted Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

3. 2 Radiated Emission Test

- It was tested Data Communication mode, after connecting all peripheral devices.

Operation Mode: ☒ Data Communication mode

4. CONDUCTED AND RADIATED EMISSION TEST SUMMARY

4.1 Conducted Emission Test

The following table shows the highest levels of conducted emissions on both polarization of hot and neutral line.

Limit Apply to	: FCC PART 15 Subpart B Class B
Frequency Range (Test Limit)	: 0.15 MHz to 0.5 MHz Quasi-Peak(66dB μ V) Average (56 dB μ V) : 0.5 MHz to 5 MHz Quasi-Peak(56dB μ V) Average (46 dB μ V) : 5 MHz to 30 MHz Quasi-Peak(60dB μ V) Average (50 dB μ V)
Detector	: Quasi-Peak, Average (6 dB Bandwidth: 9 kHz)
Operation Mode	: Data Communication mode
Temperature	: 22.1 °C
Humidity Level	: 48.5 %
Test Date	: January 14, 2012

※ **NOTE:** Refer to page 10 to page 13 for details.


HCT

EMC

EUT: UD711
Manufacturer: LG
Operating Condition: DATA MODE
Test Site: SHIELD ROOM
Operator: JH CHOI
Test Specification: FCC PART15 CLASS B
Comment: H

SCAN TABLE: "FCC PART 15 B(H)"

Short Description:			FCC PART 15 CLASS B			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	500.0 kHz	1.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin QP"

1/14/2012 11:09AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.154010	50.40	10.1	66	15.4	---	---
0.229010	41.70	10.1	63	20.8	---	---
0.324010	34.70	10.1	60	24.9	---	---
3.416000	35.60	10.3	56	20.4	---	---
3.512000	33.70	10.3	56	22.3	---	---
3.540000	35.60	10.3	56	20.4	---	---
20.432000	50.20	11.9	60	9.8	---	---
20.612000	47.90	11.9	60	12.1	---	---
20.776000	46.90	11.9	60	13.1	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

01/14/2012 11:09AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.195010	27.00	10.1	54	26.8	---	---
0.201010	25.40	10.1	54	28.2	---	---
0.208010	22.20	10.1	53	31.1	---	---
1.948000	27.70	10.2	46	18.3	---	---
2.012000	28.40	10.2	46	17.6	---	---
3.764000	25.40	10.4	46	20.6	---	---
18.488000	37.00	11.7	50	13.0	---	---
20.160000	43.70	11.9	50	6.3	---	---
21.476000	37.90	11.9	50	12.1	---	---


HCT

EMC

EUT: UD711
Manufacturer: LG
Operating Condition: DATA MODE
Test Site: SHIELD ROOM
Operator: JH CHOI
Test Specification: FCC PART15 CLASS B
Comment: N

SCAN TABLE: "FCC PART 15 B(N)"

Short Description:			FCC PART 15 CLASS B			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency	Width				
150.0 kHz	500.0 kHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
500.0 kHz	5.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			
5.0 MHz	30.0 MHz	4.0 kHz	MaxPeak	10.0 ms	9 kHz	None
			Average			



MEASUREMENT RESULT: "PHONE_fin QP"

01/14/2012 11:12AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.158010	50.50	10.3	66	15.1	---	---
0.234010	42.20	10.3	62	20.1	---	---
0.366010	33.60	10.3	59	25.0	---	---
2.892000	30.10	10.5	56	25.9	---	---
2.976000	30.80	10.5	56	25.2	---	---
3.432000	35.40	10.6	56	20.6	---	---
20.068000	51.10	11.7	60	8.9	---	---
20.612000	48.30	11.7	60	11.7	---	---
21.512000	46.60	11.7	60	13.4	---	---

MEASUREMENT RESULT: "PHONE_fin AV"

01/14/2012 11:12AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Line	PE
0.182010	26.00	10.3	54	28.4	---	---
0.270010	20.20	10.3	51	30.9	---	---
0.314010	20.80	10.3	50	29.1	---	---
1.944000	26.80	10.4	46	19.2	---	---
2.008000	26.60	10.4	46	19.4	---	---
2.072000	26.70	10.4	46	19.3	---	---
20.116000	44.10	11.7	50	5.9	---	---
21.792000	40.10	11.7	50	9.9	---	---
22.624000	31.80	11.8	50	18.2	---	---

4.2 Radiated Emission Test

The following table shows the highest levels of Radiated Emissions on both polarization of horizontal and vertical.

Limit Apply to : FCC PART 15 Subpart B Class B

-For measurement below 1 GHz

Detector : Quasi-Peak (6 dB Bandwidth: 120 kHz)

Operation Mode : Data Communication mode

-For measurement above 1 GHz

Detector : Peak mode: Peak (RBW: 1 MHz / VBW: 1 MHz)

: Average mode: Peak (RBW: 1 MHz / VBW: 10 Hz)

Operation Mode : Data Communication mode

Temperature : 24.3 °C

Humidity Level : 50.0 %

Test Date : January 14, 2012

Frequency (MHz)	Reading (dBuV)	Polarity (H/V)	Antenna Height (m)	Correction Factor		Limit (dBuV/m)	Level (dBuV/m)	Margin (dB)
				Antenna (dB/m)	Cable (dB)			
300.010	23.01	H	1.2	13.39	4.60	46.0	41.0	5.0
499.900	16.91	H	1.0	17.69	5.30	46.0	39.9	6.1
529.900	17.83	H	1.8	18.31	5.36	46.0	41.5	4.5
706.500	14.56	H	1.0	20.94	5.70	46.0	41.2	4.8
847.800	13.60	H	1.0	22.95	5.84	46.0	42.4	3.6
919.500	12.79	H	1.0	23.49	6.02	46.0	42.3	3.7

※ NOTE:

1. Measurement above 1 GHz was performed from 1 GHz to the 5th harmonic of highest fundamental frequency. The highest fundamental frequency is WCDMA 1 900 center frequency.
2. For measurement above 1 GHz, Emission noise was not founded over the ambient noise.

5. FIELD STRENGTH CALCULATION

The field strength is calculated by adding the antenna factor and cable factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

Assume a receiver reading of 21.5 dB μ V is obtained. The antenna factor of 7.4 dB/m and a cable factor of 1.1 dB are added. The 30 dB μ V/m value is mathematically converted to its corresponding level in μ V/m.

$$FS = 21.5 + 7.4 + 1.1 = 30 \text{ dB}\mu\text{V/m}$$

[Radiated Emission Limits]

Frequency of Emission (MHz)	Field Strength	
	μ V/m	dB μ V/m
30 to 88	100	40.0
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

6. TEST EQUIPMENT

<u>Type</u>	<u>Manufacturer</u>	<u>Model Number</u>	<u>Serial Number</u>	<u>Next CAL Date</u>
-------------	---------------------	---------------------	----------------------	----------------------

Conducted Emission

☒ EMI Test Receiver	Rohde & Schwarz	ESCI	100584	2012.05.03
☒ LISN	Rohde & Schwarz	ESH3-Z5	100282	2012.02.01
☒ LISN	Rohde & Schwarz	ENV216	100073	2012.04.01
☒ Attenuator	Rohde & Schwarz	ESH3-Z2	357.8810.352	2012.08.01

Radiated Emission

☒ EMI Test Receiver	Rohde & Schwarz	ESI40	831564103	2012.05.26
☐ EMI Test Receiver	Rohde & Schwarz	ESU26	100241	2012.08.02
☐ Trilog Antenna	Schwarzbeck	VULB9160	3125	2013.05.03
☒ Trilog Antenna	Schwarzbeck	VULB9160	3301	2012.09.13
☐ Antenna master	INNCO Systems	MA4000-EP	MA4000/283	-
☐ Turn Table	INNCO Systems	DT3000-3T	DT3000/69	-
☒ Antenna master	HD GmbH	MA240	240/520	-
☒ Antenna master controller	HD GmbH	HD100	100/637BJ:00	
☒ Turn Table	HD GmbH	2090	9702/1224	-
☒ Power Amplifier	Rohde & Schwarz	SCU-18	10094	2012.09.19
☐ Communication Antenna	Schwarzbeck	USLP9142	9142-248	-
☐ Horn Antenna	Schwarzbeck	BBHA 9120D	-	2012.04.13
☒ Horn Antenna	Schwarzbeck	BBHA 9120D	937	2013.10.17

7. CONCLUSION

The data collected shows that the **PCS WCDMA Modem, FCC ID: ZNFUD711, Model: UD711** complies with §15.107 and §15.109 of the FCC rules.