



MEASUREMENT REPORT

FCC Part 15.407 UNII 802.11a/n/ac

Applicant Name:

LG Electronics MobileComm U.S.A
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

11/03 - 11/14/2014

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1411042067.ZNF

FCC ID:

ZNFUS995

APPLICANT:

LG Electronics MobileComm U.S.A

Application Type:

Certification

Model(s):

LG-US995, US995, LGUS995, LG-AS995, LGAS995, AS995

EUT Type:

Portable Handset

FCC Classification:

Unlicensed National Information Infrastructure (UNII)

FCC Rule Part(s):

Part 15.407

Test Procedure(s):

KDB 789033 D02 v01, KDB 644545 D01 v01r02, KDB 905462 D06 v01

Mode	UNII Band	Channel Bandwidth (MHz)	Tx Frequency (MHz)	Conducted Power		Mode	UNII Band	Channel Bandwidth (MHz)	Tx Frequency (MHz)	Conducted Power	
				Max. Power (mW)	Max. Power (dBm)					Max. Power (mW)	Max. Power (dBm)
802.11a	1	20	5180 - 5240	24.210	13.84	802.11n	1	40	5190 - 5230	19.275	12.85
	2A	20	5260 - 5320	23.933	13.79		2A	40	5270 - 5310	18.664	12.71
	2C	20	5500 - 5720	24.831	13.95		2C	40	5510 - 5710	16.749	12.24
	3	20	5745 - 5825	22.491	13.52		3	40	5755 - 5795	14.859	11.72
802.11n	1	20	5180 - 5240	19.770	12.96	802.11ac	1	40	5190 - 5230	16.106	12.07
	2A	20	5260 - 5320	19.409	12.88		2A	40	5270 - 5310	16.144	12.08
	2C	20	5500 - 5720	19.364	12.87		2C	40	5510 - 5710	15.560	11.92
	3	20	5745 - 5825	16.943	12.29		3	40	5755 - 5795	13.964	11.45
802.11ac	1	20	5180 - 5240	14.125	11.50	802.11ac	1	80	5210	19.498	12.90
	2A	20	5260 - 5320	14.223	11.53		2A	80	5290	19.815	12.97
	2C	20	5500 - 5720	13.772	11.39		2C	80	5530 - 5690	18.664	12.71
	3	20	5745 - 5825	12.445	10.95		3	80	5775	17.378	12.40

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033 D02v01 and KDB 644545 v01r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President



FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 1 of 112

TABLE OF CONTENTS

FCC PART 15.407 MEASUREMENT REPORT	3
1.0 INTRODUCTION.....	4
1.1 SCOPE.....	4
1.2 PCTEST TEST LOCATION.....	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION.....	5
2.2 DEVICE CAPABILITIES	5
2.3 TEST CONFIGURATION	5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....	5
2.5 LABELING REQUIREMENTS	5
3.0 DESCRIPTION OF TEST	6
3.1 EVALUATION PROCEDURE.....	6
3.2 AC LINE CONDUCTED EMISSIONS.....	6
3.3 RADIATED EMISSIONS	7
4.0 ANTENNA REQUIREMENTS	8
5.0 TEST EQUIPMENT CALIBRATION DATA.....	9
6.0 TEST RESULTS	10
6.1 SUMMARY	10
6.2 26DB BANDWIDTH MEASUREMENT – 802.11A/N/AC	11
6.3 6DB BANDWIDTH MEASUREMENT – 802.11A/N/AC	31
6.4 UNII OUTPUT POWER MEASUREMENT – 802.11A/N/AC	37
6.5 MAXIMUM POWER SPECTRAL DENSITY – 802.11A/N/AC	40
6.6 FREQUENCY STABILITY	62
6.7 RADIATED SPURIOUS EMISSION MEASUREMENTS.....	66
6.8 RADIATED BAND EDGE MEASUREMENTS (20MHZ BW)	83
6.9 RADIATED BAND EDGE MEASUREMENTS (40MHZ BW)	90
6.10 RADIATED BAND EDGE MEASUREMENTS (80MHZ BW)	97
6.11 LINE-CONDUCTED TEST DATA.....	104
7.0 CONCLUSION	112

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 2 of 112



MEASUREMENT REPORT

FCC Part 15.407



§ 2.1033 General Information

APPLICANT: LG Electronics MobileComm U.S.A

APPLICANT ADDRESS: 1000 Sylvan Avenue
Englewood Cliffs, NJ 07632, United States

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA

FCC RULE PART(S): Part 15.407

BASE MODEL: LG-US995, US995, LGUS995, LG-AS995, LGAS995, AS995

FCC ID: ZNFUS995

FCC CLASSIFICATION: Unlicensed National Information Infrastructure (UNII)

Test Device Serial No.: 1GPYT, 1GPYN ☐ Production ☒ Pre-Production ☐ Engineering

DATE(S) OF TEST: 11/03 - 11/14/2014

TEST REPORT S/N: 0Y1411042067.ZNF

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 3 of 112

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on February 15, 2012.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 4 of 112

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LGE Portable Handset FCC ID: ZNFUS995**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO, Multi-band LTE, 802.11 b/g/n/ac WLAN, 802.11 a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC

Note: 5GHz WLAN (DTS/NII) operation is possible in 20MHz, and 40MHz, and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of KDB 789033 D02 v01. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Maximum Achievable Duty Cycles		
802.11 Mode/Band		Duty Cycle [%]
		ANT1
5GHz	a	96.50
	n (HT20)	96.00
	n (HT40)	92.00
	ac (HT80)	82.00

2.3 Test Configuration

The LGE Portable Handset FCC ID: ZNFUS995 was tested per the guidance of KDB 789033 D02 v01. ANSI C63.10-2009 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 6.2, 6.4, 6.5, and 0 for antenna port conducted emissions test setups.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.5 Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 5 of 112	

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009) and the guidance provided in KDB 789033 D02v01 were used in the measurement of **LGE Portable Handset FCC ID: ZNFUS995**.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 6.11. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 9.15.0.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 6 of 112

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. For the EUT positioning, "H" is defined with the EUT lying flat on the test surface, "H2" is defined with the EUT standing up on its side, and "V" is defined with the EUT standing upright.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 7 of 112	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Portable Handset are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The **LGE Portable Handset FCC ID: ZNFUS995** unit complies with the requirement of §15.203.

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
:	:	:	:	:	:	:	:
42	5210	56	5280	116	5580	157	5785
:	:	:	:	:	:	:	:
48	5240	64	5320	140	5700	165	5825

Table 4-1. 802.11a / 802.11n / 802.11ac (20MHz) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
:	:	:	:	:	:	:	:
46	5230	62	5310	110	5550		
				:	:		
				134	5670	159	5795

Table 4-2. 802.11n / 802.11ac (40MHz BW) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
				138	5690		

Table 4-3. 802.11ac (80MHz BW) Frequency / Channel Operations

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)				Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset				Page 8 of 112

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	5/29/2014	Annual	5/29/2015	N/A
-	WL40-1	Conducted Cable Set (40GHz)	1/29/2014	Annual	1/29/2015	N/A
Agilent	8447D	Broadband Amplifier	5/30/2014	Annual	5/30/2015	2443A01900
Agilent	E4448A	PSA (3Hz-50GHz) Spectrum Analyzer	4/16/2014	Annual	4/16/2015	US42510244
Agilent	N9020A	MXA Signal Analyzer	10/27/2014	Annual	10/27/2015	US46470561
Agilent	N9038A	MXE EMI Receiver	1/3/2014	Annual	1/3/2015	MY51210133
Agilent	N9030A	PXA Signal Analyzer (26.5GHz)	5/8/2014	Annual	5/8/2015	MY49432391
Agilent	N9030A	PXA Signal Analyzer (44GHz)	1/17/2014	Annual	1/17/2015	MY52350166
Anritsu	ML2495A	Power Meter	10/31/2013	Biennial	10/31/2015	941001
Anritsu	MA2411B	Pulse Sensor	4/8/2014	Biennial	4/8/2016	846215
Emco	3115	Horn Antenna (1-18GHz)	1/30/2014	Biennial	1/30/2016	9704-5182
Emco	6502	Active Loop Antenna (10k - 30 MHz)	6/24/2014	Biennial	6/24/2016	267
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	4/8/2014	Biennial	4/8/2016	125518
ETS Lindgren	3160-09	18-26.5 GHz Standard Gain Horn	6/17/2014	Biennial	6/17/2016	135427
ETS Lindgren	3160-10	26.5-40 GHz Standard Gain Horn	6/17/2014	Biennial	6/17/2016	130993
Huber+Suhner	Sucoflex 102A	40GHz Radiated Cable	1/30/2014	Annual	1/30/2015	251425001
K & L	11SH10-6000/T18000	High Pass Filter	2/7/2014	Annual	2/7/2015	1
K & L	11SH10-3075/U18000	High Pass Filter	5/2/2014	Annual	5/2/2015	2
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/5/2014	Annual	3/5/2015	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	3/12/2014	Annual	3/12/2015	100040
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	1/27/2014	Annual	1/27/2015	100342
Rohde & Schwarz	TS-PR40	26.5-40 GHz Pre-Amplifier	5/15/2014	Annual	5/15/2015	100037
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	5/21/2014	Annual	5/21/2015	100348
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
Solar Electronics	8012-50-R-24-BNC	Line Impedance Stabilization Network	6/20/2013	Biennial	6/20/2015	310233
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/28/2014	Biennial	1/28/2016	A051107

Table 5-1. Annual Test Equipment Calibration Schedule

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 9 of 112

6.0 TEST RESULTS

6.1 Summary

Company Name: LG Electronics MobileComm U.S.A
 FCC ID: ZNFUS995
 Method/System: Unlicensed National Information Infrastructure (UNII)
 Data Rate(s) Tested: 6, 9, 12, 18, 24, 36, 48, 54Mbps (802.11a)
6.5/7.2, 13/14.4, 19.5/21.7, 26/28.9, 39/43.3, 52/57.8, 58.5/65, 65/72.2 (n – 20MHz)
13.5/15, 27/30, 40.5/45, 54/60, 81/90, 108/120, 121.5/135, 135/150 (n – 40MHz BW)
29.3/32.5, 58.5/65, 87.8/97.5, 117/130, 175.5/195, 234/260, 263.3/292.5, 292.5/325,
351/390, 390/433.3 (ac – 80MHz BW)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)					
N/A	26dB Bandwidth	N/A	CONDUCTED	PASS	Section 6.2
N/A	26dB Bandwidth	N/A		PASS	Section 6.2
15.407 (a.1)	Maximum Conducted Output Power	< 50mW (16.99dBm) (5150-5250MHz) < 250mW (23.98dBm) (5250-5350MHz) < 250mW (23.98dBm) (5470-5725MHz) < 11 + 11log10(B) dBm (5825-5825MHz)		PASS	Section 6.4
15.407 (a.1), (5)	Peak Power Spectral Density	< 11 dBm/MHz		PASS	Section 6.5
15.407(g)	Frequency Stability	N/A		PASS	Section 6.6
15.407(h)	Dynamic Frequency Selection	See DFS Test Report		PASS	See DFS Test Report
15.407(b.1), (2),(3)	Undesirable Emissions	< -27 dBm/MHz EIRP (5150-5350MHz, 5470-5725MHz)	RADIATED	PASS	Section 6.7
15.205, 15.407(b.1), (5), (6)	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-210 table 3 limits)		PASS	Section 6.8, 6.9, 6.10
15.407	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits or < RSS-Gen table 2 limits	LINE CONDUCTED	PASS	Section 6.11

Table 6-1. Summary of Test Results

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "UNII Automation", Version 3.1.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 10 of 112	

6.2 26dB Bandwidth Measurement – 802.11a/n/ac

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle (>98%), at its maximum power control level, as defined in KDB 789033 D02v01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

The 26dB bandwidth is used to determine the conducted power limits.

Test Procedure Used

KDB 789033 D02v01 – Section C

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 26. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. VBW > RBW
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-1. Test Instrument & Measurement Setup

Test Notes


Per KDB 644545 v01r02 and 15.215(c), a 20dB bandwidth measurement can be performed to demonstrate that the entire emission of one channel lies solely within a particular band. 20dB bandwidth plots are included at the end of this section to show that the DFS requirements are not applicable in UNII Band 1 since the Band 1 channel does not cross over into Band 2A.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 11 of 112


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured 26dB Bandwidth [MHz]
Band 1	5180	36	a	6	21.32
	5200	40	a	6	21.66
	5240	48	a	6	21.73
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	21.73
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	21.68
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	21.75
	5190	38	n (40MHz)	13.5/15 (MCS0)	39.89
	5230	46	n (40MHz)	13.5/15 (MCS0)	39.99
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	81.54
Band 2A	5260	52	a	6	21.67
	5280	56	a	6	21.52
	5320	64	a	6	21.80
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	21.61
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	21.71
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	21.75
	5270	54	n (40MHz)	13.5/15 (MCS0)	39.75
	5310	62	n (40MHz)	13.5/15 (MCS0)	39.70
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	81.68
Band 2C	5500	100	a	6	21.55
	5580	116	a	6	21.60
	5720	144	a	6	21.09
	5500	100	n (20MHz)	6.5/7.2 (MCS0)	21.71
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	21.76
	5720	144	n (20MHz)	6.5/7.2 (MCS0)	20.95
	5510	102	n (40MHz)	13.5/15 (MCS0)	39.84
	5550	110	n (40MHz)	13.5/15 (MCS0)	39.73
	5710	142	n (40MHz)	13.5/15 (MCS0)	39.02
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	81.49
	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	82.06

Table 6-2. Conducted Bandwidth Measurements

FCC ID: ZNFUS995			FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset			Page 12 of 112




Plot 6-1. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 6-2. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 13 of 112




Plot 6-3. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 6-4. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 14 of 112




Plot 6-5. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 6-6. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 15 of 112




Plot 6-7. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 6-8. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 16 of 112




Plot 6-9. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 6-10. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 52)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 17 of 112




Plot 6-11. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 6-12. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 64)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 18 of 112




Plot 6-13. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 6-14. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 19 of 112




Plot 6-15. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 6-16. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 20 of 112




Plot 6-17. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 6-18. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 21 of 112




Plot 6-19. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 100)




Plot 6-20. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 116)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 22 of 112




Plot 6-21. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 144)




Plot 6-22. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 23 of 112




Plot 6-23. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 116)




Plot 6-24. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 24 of 112




Plot 6-25. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)




Plot 6-26. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 110)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 25 of 112




Plot 6-27. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)




Plot 6-28. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 26 of 112



Plot 6-29. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138


FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 27 of 112



Plot 6-30. 20dB Bandwidth Plot (20MHz BW 802.11a (UNII Band 1) – Ch. 48)


Note: The 20dB bandwidth plot of the UNII Band 1 high channel was found to be within 20MHz and is, therefore, operating solely within the UNII Band 1 frequencies.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 28 of 112



Plot 6-31. 20dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)


Note: The 20dB bandwidth plot of the UNII Band 1 high channel was found to be within 20MHz and is, therefore, operating solely within the UNII Band 1 frequencies.



Plot 6-32. 20dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

Note: The 20dB bandwidth plot of the UNII Band 1 high channel was found to be within 40MHz and is, therefore, operating solely within the UNII Band 1 frequencies.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 29 of 112



Plot 6-33. 20dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)

Note: The 20dB bandwidth plot of the UNII Band 1 high channel was found to be within 80MHz and is, therefore, operating solely within the UNII Band 1 frequencies.

FCC ID: ZNFUS995	 PCTEST ENGINEERING LABORATORY, INC.		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset			Page 30 of 112

6.3 6dB Bandwidth Measurement – 802.11a/n/ac §15.407 (e)

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum power control level, as defined in KDB 789033 D02v01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 6dB bandwidth.

In the 5.725 – 5.850GHz band, the 6dB bandwidth must be ≥ 500 kHz.

Test Procedure Used

KDB 789033 D02v01 – Section C)2)

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100 kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-2. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 31 of 112


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured 6dB Bandwidth [MHz]	Min Permissible 6dB Bandwidth [kHz]	Pass / Fail
Band 3	5745	149	a	6	16.38	500	Pass
	5785	157	a	6	16.37	500	Pass
	5825	165	a	6	16.37	500	Pass
	5745	149	n (20MHz)	6.5/7.2 (MCS0)	17.60	500	Pass
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	17.61	500	Pass
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	17.59	500	Pass
	5755	151	n (40MHz)	13.5/15 (MCS0)	36.32	500	Pass
	5795	159	n (40MHz)	13.5/15 (MCS0)	36.36	500	Pass
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	75.53	500	Pass

Table 6-3. Conducted Bandwidth Measurements




Plot 6-34. 26dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 149)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 32 of 112




Plot 6-35. 26dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 6-36. 26dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 165)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 33 of 112




Plot 6-37. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 6-38. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 157)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 34 of 112




Plot 6-39. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 165)




Plot 6-40. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 151)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 35 of 112



Plot 6-41. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 159)



Plot 6-42. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 36 of 112

6.4 UNII Output Power Measurement – 802.11a/n/ac §15.407 (a.1)

Test Overview and Limits

A transmitter antenna terminal of the EUT is connected to the input of an RF pulse power sensor. Measurement is made using a broadband average power meter while the EUT is operating at its maximum power control level, as defined in KDB 789033 D02v01, and at the appropriate frequencies.

In the 5.15 – 5.25GHz band, the maximum permissible conducted output power is 250mW (23.98dBm)

In the 5.25 – 5.35GHz band, the maximum permissible conducted output power is the lesser of 250mW (23.98dBm) and $11 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 11 \text{ dBm} + 10\log_{10}(21.52) = 24.33\text{dBm}$.

In the 5.47 – 5.725GHz band, the maximum permissible conducted output power is the lesser of 250mW (23.98dBm) and $11 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 11 \text{ dBm} + 10\log_{10}(20.95) = 24.21\text{dBm}$.

In the 5.725 – 5.850GHz band, the maximum permissible conducted output power is 1W (30dBm).

Test Procedure Used

KDB 789033 D02v01 – Section E)3)b) Method PM-G

Test Settings

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-3. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 37 of 112

Mode	Freq [MHz]	Channel	Detector	802.11a Conducted Power [dBm]							
				Data Rate [Mbps]							
				6	9	12	18	24	36	48	54
802.11a	5180	36	AVG	13.41	13.47	13.53	13.40	13.71	13.61	13.74	13.60
802.11a	5200	40	AVG	13.55	13.58	13.66	13.50	13.82	13.69	13.84	13.81
802.11a	5220	44	AVG	13.60	13.72	13.71	13.60	13.80	13.81	13.84	13.73
802.11a	5240	48	AVG	13.45	13.46	13.61	13.44	13.76	13.61	13.78	13.60
802.11a	5260	52	AVG	13.67	13.38	13.32	13.22	13.55	13.50	13.70	13.33
802.11a	5280	56	AVG	13.37	13.41	13.48	13.30	13.66	13.57	13.79	13.40
802.11a	5300	60	AVG	13.35	13.44	13.41	13.34	13.63	13.56	13.72	13.46
802.11a	5320	64	AVG	13.36	13.47	13.43	13.23	13.62	13.57	13.77	13.45
802.11a	5500	100	AVG	13.71	13.74	13.32	13.40	13.73	13.60	13.78	13.68
802.11a	5520	104	AVG	13.47	13.33	13.76	13.83	13.52	13.47	13.50	13.51
802.11a	5540	108	AVG	13.50	13.39	13.77	13.81	13.65	13.60	13.76	13.65
802.11a	5560	112	AVG	13.58	13.49	13.87	13.87	13.60	13.68	13.67	13.65
802.11a	5580	116	AVG	13.46	13.32	13.78	13.80	13.78	13.67	13.67	13.48
802.11a	5660	132	AVG	13.70	13.57	13.92	13.48	13.51	13.66	13.51	13.60
802.11a	5680	136	AVG	13.54	13.45	13.77	13.93	13.67	13.68	13.80	13.67
802.11a	5700	140	AVG	13.55	13.47	13.79	13.95	13.78	13.56	13.67	13.76
802.11a	5720	144	AVG	13.70	13.75	13.62	13.67	13.78	13.60	13.50	13.67
802.11a	5745	149	AVG	13.25	13.25	13.20	13.20	13.45	13.36	13.49	13.15
802.11a	5765	153	AVG	13.30	13.28	13.28	13.30	13.52	13.37	13.51	13.21
802.11a	5785	157	AVG	13.27	13.26	13.24	13.25	13.49	13.32	13.51	13.21
802.11a	5805	161	AVG	13.15	13.15	13.10	13.10	13.29	13.31	13.38	13.07
802.11a	5825	165	AVG	13.10	13.10	13.01	13.10	13.21	13.11	13.22	13.01

Table 6-4. 802.11a (UNII) Maximum Conducted Output Power

Mode	Freq [MHz]	Channel	Detector	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
				Data Rate [Mbps]							
				6.5	13	19.5	26	39	52	58.5	65
802.11n	5180	36	AVG	12.46	12.55	12.50	12.85	12.83	12.85	12.92	12.80
802.11n	5200	40	AVG	12.55	12.64	12.60	12.93	12.96	12.96	12.94	12.90
802.11n	5220	44	AVG	12.65	12.81	12.69	12.82	12.80	12.86	12.86	12.84
802.11n	5240	48	AVG	12.72	12.88	12.73	12.84	12.88	12.94	12.96	12.80
802.11n	5260	52	AVG	12.52	12.20	12.21	12.54	12.55	12.50	12.56	12.43
802.11n	5280	56	AVG	12.67	12.33	12.38	12.72	12.79	12.71	12.80	12.61
802.11n	5300	60	AVG	12.81	12.44	12.49	12.82	12.81	12.78	12.81	12.79
802.11n	5320	64	AVG	12.85	12.49	12.57	12.88	12.88	12.88	12.82	12.77
802.11n	5500	100	AVG	12.60	12.53	12.41	12.87	12.68	12.70	12.84	12.84
802.11n	5520	104	AVG	12.45	12.29	12.20	12.65	12.55	12.51	12.73	12.64
802.11n	5540	108	AVG	12.35	12.21	12.12	12.64	12.48	12.38	12.63	12.58
802.11n	5560	112	AVG	12.45	12.37	12.23	12.68	12.53	12.53	12.72	12.64
802.11n	5580	116	AVG	12.46	12.30	12.24	12.71	12.49	12.52	12.69	12.70
802.11n	5660	132	AVG	12.37	12.28	12.19	12.65	12.42	12.42	12.62	12.60
802.11n	5680	136	AVG	12.46	12.41	12.28	12.75	12.51	12.61	12.72	12.71
802.11n	5700	140	AVG	12.24	12.21	12.06	12.55	12.28	12.27	12.52	12.54
802.11n	5720	144	AVG	12.00	12.10	12.05	12.10	12.00	12.20	12.05	12.00
802.11n	5745	149	AVG	12.00	12.10	12.03	12.01	12.00	12.00	12.05	12.01
802.11n	5765	153	AVG	12.05	12.10	12.00	12.10	12.10	12.00	12.01	12.00
802.11n	5785	157	AVG	12.01	12.06	12.11	12.12	12.07	12.00	12.00	12.02
802.11n	5805	161	AVG	12.10	12.29	12.00	12.01	12.09	12.13	12.08	12.10
802.11n	5825	165	AVG	12.10	12.25	12.00	12.01	12.09	12.02	12.02	12.02

Table 6-5. 20MHz BW 802.11n (UNII) Maximum Conducted Output Power

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 38 of 112

Mode	Freq [MHz]	Channel	Detector	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
				Data Rate [Mbps]							
				13.5	27	40.5	54	81	108	121.5	135
802.11n	5190	38	AVG	12.85	12.24	12.23	12.65	12.70	12.48	12.56	12.50
802.11n	5230	46	AVG	12.43	11.85	11.80	12.24	12.23	12.05	12.17	12.14
802.11n	5270	54	AVG	12.23	12.32	12.31	12.44	12.52	12.44	12.46	12.39
802.11n	5310	62	AVG	12.39	12.52	12.43	12.60	12.71	12.64	12.63	12.56
802.11n	5510	102	AVG	11.82	11.88	11.89	11.17	11.98	11.85	12.00	12.08
802.11n	5550	110	AVG	12.00	12.02	12.08	11.35	12.18	11.97	12.21	12.24
802.11n	5670	134	AVG	11.72	11.75	11.86	11.08	11.81	11.69	11.95	12.04
802.11n	5710	142	AVG	11.60	11.62	11.65	11.70	11.62	11.67	11.68	11.70
802.11n	5755	151	AVG	11.18	11.24	11.25	11.45	11.40	11.51	11.30	11.40
802.11n	5795	159	AVG	11.40	11.40	11.49	11.70	11.70	11.72	11.49	11.64

Table 6-6. 40MHz BW 802.11n (UNII) Maximum Conducted Output Power

20MHz BW 802.11ac (5GHz) Conducted Power [dBm]				
Mode	Freq [MHz]	Channel	Detector	Data Rate
				6.5 Mbps
802.11ac	5180	36	AVG	11.42
802.11ac	5200	40	AVG	11.33
802.11ac	5240	48	AVG	11.50
802.11ac	5260	52	AVG	11.23
802.11ac	5280	56	AVG	11.44
802.11ac	5320	64	AVG	11.53
802.11ac	5500	100	AVG	11.39
802.11ac	5580	116	AVG	11.20
802.11ac	5700	140	AVG	11.38
802.11ac	5720	144	AVG	11.00
802.11ac	5745	149	AVG	10.90
802.11ac	5785	157	AVG	10.90
802.11ac	5825	165	AVG	10.95

Table 6-7. 20MHz BW 802.11ac (UNII) Maximum Conducted Output Power

40MHz BW 802.11ac (5GHz) Conducted Power [dBm]				
Mode	Freq [MHz]	Channel	Detector	Data Rate
				13.5 Mbps
802.11ac	5190	38	AVG	11.70
802.11ac	5230	46	AVG	12.07
802.11ac	5270	54	AVG	11.80
802.11ac	5310	62	AVG	12.08
802.11ac	5510	102	AVG	11.92
802.11ac	5550	110	AVG	11.65
802.11ac	5670	134	AVG	11.67
802.11ac	5710	142	AVG	11.50
802.11ac	5755	151	AVG	11.40
802.11ac	5795	159	AVG	11.45

Table 6-8. 40MHz BW 802.11ac (UNII) Maximum Conducted Output Power

Mode	Freq [MHz]	Channel	Detector	80MHz BW 802.11ac (5GHz) Conducted Power [dBm]									
				Data Rate [Mbps]									
				29.3	58.5	87.8	117	175.5	234	263.3	292.5	351	390
802.11ac	5210	42	AVG	12.71	12.50	12.46	12.90	12.84	12.80	12.87	12.81	12.83	12.89
802.11ac	5290	58	AVG	12.74	12.53	12.49	12.93	12.88	12.93	12.92	12.97	12.94	12.86
802.11ac	5530	106	AVG	12.20	12.25	12.08	12.68	12.57	12.64	12.57	12.57	12.55	12.50
802.11ac	5690	138	AVG	12.50	12.43	12.53	12.60	12.56	12.70	12.57	12.45	12.64	12.71
802.11ac	5775	155	AVG	12.19	11.85	11.75	12.26	12.36	12.35	12.36	12.40	12.40	12.30

Table 6-9. 80MHz BW 802.11ac (UNII) Maximum Conducted Output Power

FCC ID: ZNFUS995	 PCTEST ENGINEERING LABORATORY, INC.		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset			Page 39 of 112

6.5 Maximum Power Spectral Density – 802.11a/n/ac §15.407(a.1)(2.5)

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum power control level, as defined in KDB 789033 D02v01, and at the appropriate frequencies. Method SA-1, as defined in KDB 789033 D02v01, was used to measure the power spectral density.

In the 5.15 – 5.25GHz, 5.25 - 5.35GHz, and 5.47 - 5.725GHz bands, the maximum permissible power spectral density is 11dBm/MHz.

In the 5.725 – 5.850GHz band, the maximum permissible power spectral density is 30dBm/500kHz.

Test Procedure Used

KDB 789033 D02v01 – Section F

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times (\text{span/RBW})$
6. Sweep time = auto
7. Detector = power averaging (RMS)
8. Trigger was set to free run since the EUT was operating at a duty cycle $\geq 98\%$
9. Trace was averaged over 100 sweeps
10. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-4. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 40 of 112


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 1	5180	36	a	6	4.12	11.0	-6.88	Pass
	5200	40	a	6	4.16	11.0	-6.84	Pass
	5240	48	a	6	4.09	11.0	-6.91	Pass
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	2.83	11.0	-8.17	Pass
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	2.71	11.0	-8.29	Pass
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	2.91	11.0	-8.09	Pass
	5190	38	n (40MHz)	13.5/15 (MCS0)	-0.28	11.0	-11.28	Pass
	5230	46	n (40MHz)	13.5/15 (MCS0)	-0.75	11.0	-11.75	Pass
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-2.95	11.0	-13.95	Pass
Band 2A	5260	52	a	6	4.08	11.0	-6.92	Pass
	5280	56	a	6	4.05	11.0	-6.95	Pass
	5320	64	a	6	3.93	11.0	-7.07	Pass
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	2.72	11.0	-8.28	Pass
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	2.73	11.0	-8.27	Pass
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	2.56	11.0	-8.44	Pass
	5270	54	n (40MHz)	13.5/15 (MCS0)	-0.75	11.0	-11.75	Pass
	5310	62	n (40MHz)	13.5/15 (MCS0)	-0.89	11.0	-11.89	Pass
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	-3.11	11.0	-14.11	Pass
Band 2C	5500	100	a	6	4.16	11.0	-6.84	Pass
	5580	116	a	6	3.88	11.0	-7.12	Pass
	5720	144	a	6	3.13	11.0	-7.87	Pass
	5500	100	n (20MHz)	6.5/7.2 (MCS0)	2.70	11.0	-8.30	Pass
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	2.50	11.0	-8.50	Pass
	5720	144	n (20MHz)	6.5/7.2 (MCS0)	2.84	11.0	-8.16	Pass
	5510	102	n (40MHz)	13.5/15 (MCS0)	-0.62	11.0	-11.62	Pass
	5550	110	n (40MHz)	13.5/15 (MCS0)	-0.97	11.0	-11.97	Pass
	5710	142	n (40MHz)	13.5/15 (MCS0)	-0.80	11.0	-11.80	Pass
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-3.14	11.0	-14.14	Pass
	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	-4.73	11.0	-15.73	Pass

Table 6-10. Conducted Power Spectral Density Measurements

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 41 of 112	



Plot 6-43. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 6-44. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 42 of 112




Plot 6-45. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 6-46. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 43 of 112




Plot 6-47. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 6-48. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 44 of 112




Plot 6-49. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 6-50. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 45 of 112




Plot 6-51. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 6-52. Peak Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 52)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 46 of 112




Plot 6-53. Peak Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 6-54. Peak Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 64)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 47 of 112




Plot 6-55. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 6-56. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 48 of 112




Plot 6-57. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 6-58. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 49 of 112



Plot 6-59. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 6-60. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 50 of 112




Plot 6-61. Peak Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 100)




Plot 6-62. Peak Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 116)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 51 of 112




Plot 6-63. Peak Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 144)




Plot 6-64. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 52 of 112




Plot 6-65. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 116)




Plot 6-66. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 53 of 112




Plot 6-67. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)




Plot 6-68. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 110)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 54 of 112




Plot 6-69. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)



Plot 6-70. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

FCC ID: ZNFUS995	 FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 55 of 112




Plot 6-71. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 56 of 112


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]	Pass / Fail
Band 3	5745	149	a	6	1.09	30.0	-28.91	Pass
	5785	157	a	6	0.45	30.0	-29.55	Pass
	5825	165	a	6	0.61	30.0	-29.39	Pass
	5745	149	n (20MHz)	6.5/7.2 (MCS0)	-0.38	30.0	-30.38	Pass
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	-0.77	30.0	-30.77	Pass
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	-0.94	30.0	-30.94	Pass
	5755	151	n (40MHz)	13.5/15 (MCS0)	-3.88	30.0	-33.88	Pass
	5795	159	n (40MHz)	13.5/15 (MCS0)	-3.99	30.0	-33.99	Pass
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	-5.62	30.0	-35.62	Pass

Table 6-11. Conducted Power Spectral Density Measurements




Plot 6-72. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 149)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 57 of 112




Plot 6-73. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 6-74. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 165)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 58 of 112




Plot 6-75. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 6-76. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 157)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 59 of 112




Plot 6-77. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 165)




Plot 6-78. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 151)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 60 of 112



Plot 6-79. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 159)



Plot 6-80. Peak Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 61 of 112

6.6 Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,180,000,000 Hz
 CHANNEL: 36
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,179,999,984	-16	-0.00000031
100 %		- 30	5,179,999,994	-6	-0.00000011
100 %		- 20	5,179,999,996	-4	-0.00000008
100 %		- 10	5,179,999,999	-1	-0.00000002
100 %		0	5,179,999,988	-12	-0.00000022
100 %		+ 10	5,179,999,987	-13	-0.00000025
100 %		+ 20	5,179,999,991	-9	-0.00000017
100 %		+ 30	5,179,999,982	-18	-0.00000034
100 %		+ 40	5,179,999,990	-10	-0.00000019
100 %		+ 50	5,179,999,988	-12	-0.00000024
BATT. ENDPOINT	3.40	+ 20	5,179,999,992	-8	-0.00000015

Table 6-12. Frequency Stability Measurements for UNII Band 1 (Ch. 36)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 62 of 112	

Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,260,000,000 Hz
 CHANNEL: 52
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,259,999,990	-10	-0.00000020
100 %		- 30	5,259,999,986	-14	-0.00000026
100 %		- 20	5,259,999,985	-15	-0.00000029
100 %		- 10	5,259,999,989	-11	-0.00000020
100 %		0	5,259,999,983	-17	-0.00000033
100 %		+ 10	5,259,999,991	-9	-0.00000016
100 %		+ 20	5,259,999,985	-15	-0.00000028
100 %		+ 30	5,259,999,997	-3	-0.00000006
100 %		+ 40	5,259,999,988	-12	-0.00000022
100 %		+ 50	5,259,999,987	-13	-0.00000025
BATT. ENDPOINT	3.40	+ 20	5,259,999,996	-4	-0.00000007

Table 6-13. Frequency Stability Measurements for UNII Band 2A (Ch. 52)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 63 of 112	

Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,500,000,000 Hz
 CHANNEL: 100
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,499,999,982	-18	-0.00000032
100 %		- 30	5,499,999,998	-2	-0.00000004
100 %		- 20	5,499,999,999	-1	-0.00000001
100 %		- 10	5,499,999,980	-20	-0.00000036
100 %		0	5,499,999,983	-17	-0.00000030
100 %		+ 10	5,499,999,980	-20	-0.00000035
100 %		+ 20	5,499,999,991	-9	-0.00000017
100 %		+ 30	5,499,999,998	-2	-0.00000003
100 %		+ 40	5,499,999,982	-18	-0.00000033
100 %		+ 50	5,499,999,986	-14	-0.00000025
BATT. ENDPOINT	3.40	+ 20	5,499,999,987	-13	-0.00000023

Table 6-14. Frequency Stability Measurements for UNII Band 2C (Ch. 100)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 64 of 112

Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,745,000,000 Hz
 CHANNEL: 149
 REFERENCE VOLTAGE: 3.85 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	5,744,999,982	-18	-0.00000031
100 %		- 30	5,744,999,982	-18	-0.00000031
100 %		- 20	5,744,999,981	-19	-0.00000033
100 %		- 10	5,744,999,983	-17	-0.00000030
100 %		0	5,744,999,999	-1	-0.00000002
100 %		+ 10	5,744,999,998	-2	-0.00000004
100 %		+ 20	5,744,999,992	-8	-0.00000015
100 %		+ 30	5,744,999,986	-14	-0.00000025
100 %		+ 40	5,744,999,999	-1	-0.00000001
100 %		+ 50	5,744,999,999	-1	-0.00000002
BATT. ENDPOINT	3.40	+ 20	5,744,999,994	-6	-0.00000010

Table 6-15. Frequency Stability Measurements for UNII Band 3 (Ch. 149)

Note:

Based on the results of the frequency stability test shown above the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 65 of 112

6.7 Radiated Spurious Emission Measurements

§15.407(b.1)(b.6) §15.205 §15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum power control level, as defined in KDB 789033 D02v01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n (20MHz BW) and 802.11n (40MHz BW)), and 802.11ac (80MHz BW)), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-16 per Section 15.209.

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-16. Radiated Limits

Test Procedures Used

KDB 789033 D02v01 – Section G

Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 66 of 112

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-5. Test Instrument & Measurement Setup

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 67 of 112

Test Notes

1. All radiated spurious emissions levels were measured in a radiated test setup per the guidance of KDB 789033 D02v01 Section G.
2. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-16.
3. All spurious emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-11. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. or -17dBm/MHz. At a distance of 3meters, field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. This unit was tested with its standard battery.
6. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported.
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
8. Radiated Spurious Emissions Pre-Scan plots are also reported at the beginning of the next section. Automated test software was used to perform the Radiated Spurious Emissions Pre-Scan testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 9.15.00.

Sample Calculations

Determining Spurious Emissions Levels

- o Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- o $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]}$
- o $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$


Radiated Band Edge Measurement Offset

- o The amplitude offset shown in the radiated restricted band edge plots in Section 6.8 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + 10 dB Attenuator) – Preamplifier Gain


FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 68 of 112

Radiated Spurious Emission Measurements

§15.407(b.1)(b.6) §15.205 §15.209




Plot 6-81. Radiated Spurious Plot below 1GHz (802.11a – Band 1, Ch. 36 Ant. Pol. H)




Plot 6-82. Radiated Spurious Plot above 1GHz (802.11a – Band 1, Ch. 36 Ant. Pol. H)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 69 of 112




Plot 6-83. Radiated Spurious Plot below 1GHz (802.11a – Band 1, Ch. 36 Ant. Pol. V)




Plot 6-84. Radiated Spurious Plot above 1GHz (802.11a – Band 1, Ch. 36 Ant. Pol. V)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 70 of 112




Plot 6-85. Radiated Spurious Plot below 1GHz (802.11a – Band 2A, Ch. 52 Ant. Pol. H)




Plot 6-86. Radiated Spurious Plot above 1GHz (802.11a – Band 2A, Ch. 52 Ant. Pol. H)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 71 of 112




Plot 6-87. Radiated Spurious Plot below 1GHz (802.11a – Band 2A, Ch. 52 Ant. Pol. V)




Plot 6-88. Radiated Spurious Plot above 1GHz (802.11a – Band 2A, Ch. 52 Ant. Pol. V)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 72 of 112




Plot 6-89. Radiated Spurious Plot below 1GHz (802.11a – Band 2C, Ch. 100 Ant. Pol. H)




Plot 6-90. Radiated Spurious Plot above 1GHz (802.11a – Band 2C, Ch. 100 Ant. Pol. H)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 73 of 112




Plot 6-91. Radiated Spurious Plot below 1GHz (802.11a – Band 2C, Ch. 100 Ant. Pol. V)




Plot 6-92. Radiated Spurious Plot above 1GHz (802.11a – Band 2C, Ch. 100 Ant. Pol. V)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 74 of 112




Plot 6-93. Radiated Spurious Plot below 1GHz (802.11a – Band 3, Ch. 149 Ant. Pol. H)




Plot 6-94. Radiated Spurious Plot above 1GHz (802.11a – Band 3, Ch. 149 Ant. Pol. H)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 75 of 112



Plot 6-95. Radiated Spurious Plot below 1GHz (802.11a – Band 3, Ch. 149 Ant. Pol. V)



Plot 6-96. Radiated Spurious Plot above 1GHz (802.11a – Band 3, Ch. 149 Ant. Pol. V)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 76 of 112

Radiated Spurious Emission Measurements (Harmonics)

\$15.407(b.1)(b.6) \$15.205 \$15.209

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5180MHz
Channel: 36

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	-102.81	Peak	H	H	46.35	0.00	50.53	68.20	-17.67
* 15540.00	-115.03	Average	H	H	48.66	0.00	40.63	53.98	-13.35
* 15540.00	-103.45	Peak	H	H	48.66	0.00	52.21	73.98	-21.77
* 20720.00	-108.12	Average	H	H	44.20	-9.54	33.53	53.98	-20.45
* 20720.00	-97.27	Peak	H	H	44.20	-9.54	44.38	73.98	-29.60
25900.00	-96.78	Peak	H	H	45.08	-9.54	45.75	68.20	-22.45

Table 6-17. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5200MHz
Channel: 40

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	-103.97	Peak	H	H	46.30	0.00	49.33	68.20	-18.87
* 15600.00	-115.41	Average	H	H	48.66	0.00	40.25	53.98	-13.72
* 15600.00	-105.06	Peak	H	H	48.66	0.00	50.60	73.98	-23.37
* 20800.00	-107.18	Average	H	H	44.20	-9.54	34.48	53.98	-19.50
* 20800.00	-96.89	Peak	H	H	44.20	-9.54	44.77	73.98	-29.21
26000.00	-98.20	Peak	H	H	45.11	-9.54	44.37	68.20	-23.83

Table 6-18. Radiated Measurements

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 77 of 112

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5240MHz
 Channel: 48

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	-103.42	Peak	H	H	46.19	0.00	49.77	68.20	-18.43
* 15720.00	-115.26	Average	H	H	48.76	0.00	40.50	53.98	-13.48
* 15720.00	-104.46	Peak	H	H	48.76	0.00	51.30	73.98	-22.68
* 20960.00	-107.07	Average	H	H	44.19	-9.54	34.57	53.98	-19.41
* 20960.00	-97.98	Peak	H	H	44.19	-9.54	43.66	73.98	-30.32
26200.00	-96.35	Peak	H	H	44.95	-9.54	46.06	68.20	-22.14

Table 6-19. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5260MHz
 Channel: 52

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	-103.80	Peak	H	H	46.18	0.00	49.38	68.20	-18.82
* 15780.00	-115.41	Average	H	H	48.91	0.00	40.50	53.98	-13.48
* 15780.00	-104.89	Peak	H	H	48.91	0.00	51.02	73.98	-22.96
* 21040.00	-108.98	Average	H	H	44.18	-9.54	32.65	53.98	-21.32
* 21040.00	-100.00	Peak	H	H	44.18	-9.54	41.63	73.98	-32.34
26300.00	-97.15	Peak	H	H	44.95	-9.54	45.25	68.20	-22.95

Table 6-20. Radiated Measurements

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 78 of 112

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5280MHz
Channel: 56

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	-103.09	Peak	H	H	46.24	0.00	50.14	68.20	-18.06
* 15840.00	-115.40	Average	H	H	49.10	0.00	40.70	53.98	-13.28
* 15840.00	-103.43	Peak	H	H	49.10	0.00	52.67	73.98	-21.31
* 21120.00	-105.20	Average	H	H	44.17	-9.54	36.43	53.98	-17.55
* 21120.00	-101.76	Peak	H	H	44.17	-9.54	39.87	73.98	-34.11
26400.00	-95.16	Peak	H	H	45.01	-9.54	47.30	68.20	-20.90

Table 6-21. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5320MHz
Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	-103.84	Average	H	H	46.33	0.00	49.49	53.98	-4.49
* 10640.00	-114.66	Peak	H	H	46.33	0.00	38.67	73.98	-35.31
* 15960.00	-115.37	Average	H	H	49.44	0.00	41.07	53.98	-12.91
* 15960.00	-104.58	Peak	H	H	49.44	0.00	51.86	73.98	-22.12
* 21280.00	-108.07	Average	H	H	44.18	-9.54	33.56	53.98	-20.41
* 21280.00	-100.21	Peak	H	H	44.18	-9.54	41.42	73.98	-32.55
26600.00	-103.56	Peak	H	H	47.61	-9.54	41.51	68.20	-26.69

Table 6-22. Radiated Measurements

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 79 of 112

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5500MHz
 Channel: 100

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	-114.77	Average	H	H	46.89	0.00	39.12	53.98	-14.86
* 11000.00	-103.97	Peak	H	H	46.89	0.00	49.92	73.98	-24.06
16500.00	-105.00	Peak	H	H	50.86	0.00	52.86	68.20	-15.35
22000.00	-100.37	Peak	H	H	44.47	-9.54	41.56	68.20	-26.64
27500.00	-103.93	Peak	H	H	47.92	-9.54	41.45	68.20	-26.75

Table 6-23. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5580MHz
 Channel: 116

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11160.00	-114.63	Average	H	H	46.98	0.00	39.35	53.98	-14.63
* 11160.00	-104.02	Peak	H	H	46.98	0.00	49.96	73.98	-24.02
16740.00	-105.14	Peak	H	H	51.68	0.00	53.54	68.20	-14.66
* 22320.00	-110.16	Average	H	H	44.59	-9.54	31.89	53.98	-22.09
* 22320.00	-99.82	Peak	H	H	44.59	-9.54	42.23	73.98	-31.75
27900.00	-103.91	Peak	H	H	48.09	-9.54	41.64	68.20	-26.56

Table 6-24. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5700MHz
 Channel: 140

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11400.00	-114.88	Average	H	H	47.40	0.00	39.52	53.98	-14.46
* 11400.00	-104.06	Peak	H	H	47.40	0.00	50.34	73.98	-23.64
17100.00	-104.79	Peak	H	H	52.55	0.00	54.76	68.20	-13.44
* 22800.00	-109.39	Average	H	H	44.62	-9.54	32.69	53.98	-21.29
* 22800.00	-98.86	Peak	H	H	44.62	-9.54	43.22	73.98	-30.76
28500.00	-106.93	Peak	H	H	48.35	-9.54	38.88	68.20	-29.32

Table 6-25. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 & 3 Meters
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	-114.78	Average	H	H	47.67	0.00	39.90	53.98	-14.08
* 11490.00	-104.19	Peak	H	H	47.67	0.00	50.49	73.98	-23.49
17235.00	-105.57	Peak	H	H	53.17	0.00	54.61	68.20	-13.59
* 22980.00	-108.84	Average	H	H	44.64	-9.54	33.25	53.98	-20.73
* 22980.00	-98.08	Peak	H	H	44.64	-9.54	44.01	68.20	-24.19
28725.00	-103.91	Peak	H	H	48.26	-9.54	41.81	69.20	-27.39

Table 6-26. Radiated Measurements

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 81 of 112

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5785MHz
Channel: 157

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	-114.72	Average	H	H	47.88	0.00	40.16	53.98	-13.82
* 11570.00	-103.50	Peak	H	H	47.88	0.00	51.38	73.98	-22.60
17355.00	-105.96	Peak	H	H	53.56	0.00	54.60	68.20	-13.60
23140.00	-97.56	Peak	H	H	44.73	-9.54	44.63	73.98	-29.34
28925.00	-104.11	Peak	H	H	48.28	-9.54	41.62	68.20	-26.58

Table 6-27. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 & 3 Meters
Operating Frequency: 5825MHz
Channel: 165

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	-114.68	Average	H	H	48.04	0.00	40.36	53.98	-13.62
* 11650.00	-103.39	Peak	H	H	48.04	0.00	51.65	73.98	-22.33
17475.00	-105.10	Peak	H	H	54.11	0.00	56.02	68.20	-12.18
23300.00	-98.37	Peak	H	H	44.76	-9.54	43.85	73.98	-30.13
29125.00	-104.02	Peak	H	H	48.24	-9.54	41.68	68.20	-26.52

Table 6-28. Radiated Measurements

6.8 Radiated Band Edge Measurements (20MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5180MHz

Channel: 36




Date: 5.NOV.2014 18:16:55

Plot 6-97. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 83 of 112

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 5.NOV.2014 18:18:48

Plot 6-98. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 84 of 112

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64



Date: 5.NOV.2014 18:28:34

Plot 6-99. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 85 of 112

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100




Date: 5.NOV.2014 18:42:46

Plot 6-101. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 87 of 112

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 5.NOV.2014 18:41:50

Plot 6-102. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 88 of 112

Radiated Band Edge Measurements (20MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5825MHz

Channel: 165



Date: 5.NOV.2014 18:47:55

Plot 6-103. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 89 of 112

6.9 Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5190MHz

Channel: 38




Date: 6.NOV.2014 20:12:39

Plot 6-104. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 90 of 112

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 5.NOV.2014 19:11:36

Plot 6-105. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 91 of 112

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62




Date: 5.NOV.2014 19:23:00

Plot 6-106. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 92 of 112

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 5.NOV.2014 19:24:26

Plot 6-107. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 93 of 112

Radiated Band Edge Measurements (40MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5510MHz

Channel: 102




Date: 5.NOV.2014 19:30:39

Plot 6-108. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 94 of 112

Radiated Band Edge Measurements (40MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 5.NOV.2014 19:32:12

Plot 6-109. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 95 of 112

6.10 Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11n (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5210MHz

Channel: 42




Date: 6.NOV.2014 20:18:34

Plot 6-111. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 1)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 97 of 112

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 5.NOV.2014 19:57:44

Plot 6-112. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 1)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 98 of 112

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5290MHz

Channel: 58




Date: 5.NOV.2014 20:07:05

Plot 6-113. Radiated Restricted Upper Band Edge Plot (Average – UNII Band 2A)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 99 of 112

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 5.NOV.2014 20:08:10

Plot 6-114. Radiated Restricted Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 100 of 112

Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5530MHz

Channel: 106




Date: 6.NOV.2014 20:25:20

Plot 6-115. Radiated Restricted Lower Band Edge Plot (Average – UNII Band 2C)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 101 of 112

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209



Date: 5.NOV.2014 20:28:37

Plot 6-116. Radiated Restricted Lower Band Edge Plot (Peak – UNII Band 2C)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 102 of 112

Radiated Band Edge Measurements (80MHz BW) \$15.407(b.1)(b.2) \$15.205 \$15.209


Worst Case Mode: 802.11ac (80MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5775MHz

Channel: 155




Date: 5.NOV.2014 20:33:24

Plot 6-117. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 103 of 112

6.11 Line-Conducted Test Data

\$15.407



Plot 6-118. Line Conducted Plot with 802.11a UNII Band 1 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.197	L1	0.2	42.10	63.73	21.63	27.99	53.73	25.74
0.510	L1	0.1	39.77	56.00	16.23	24.56	46.00	21.44
0.614	L1	0.1	42.35	56.00	13.65	27.54	46.00	18.46
3.158	L1	0.2	27.52	56.00	28.48	19.61	46.00	26.39
4.929	L1	0.2	31.67	56.00	24.33	24.01	46.00	21.99
8.907	L1	0.3	43.53	60.00	16.47	29.14	50.00	20.86

Table 6-29. Line Conducted Data with 802.11a UNII Band 1 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 104 of 112

Line-Conducted Test Data

\$15.407



Plot 6-119. Line Conducted Plot with 802.11a UNII Band 1 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.607	N	0.1	44.36	56.00	11.64	34.89	46.00	11.11
2.240	N	0.2	41.36	56.00	14.64	34.13	46.00	11.87
2.663	N	0.2	41.01	56.00	14.99	33.10	46.00	12.90
3.073	N	0.2	40.93	56.00	15.07	33.84	46.00	12.16
4.882	N	0.2	40.20	56.00	15.80	33.36	46.00	12.64
8.970	N	0.3	42.24	60.00	17.76	33.31	50.00	16.69

Table 6-30. Line Conducted Data with 802.11a UNII Band 1 (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 105 of 112

Line-Conducted Test Data

\$15.407



Plot 6-120. Line Conducted Plot with 802.11a UNII Band 2A (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.197	L1	0.2	42.05	63.73	21.68	27.83	53.73	25.90
0.506	L1	0.1	39.74	56.00	16.26	25.29	46.00	20.71
0.605	L1	0.1	42.51	56.00	13.49	28.21	46.00	17.79
2.625	L1	0.1	27.56	56.00	28.44	21.09	46.00	24.91
4.763	L1	0.2	30.70	56.00	25.30	22.93	46.00	23.07
8.608	L1	0.3	42.72	60.00	17.28	29.12	50.00	20.88

Table 6-31. Line Conducted Data with 802.11a UNII Band 2A (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFUS995		FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 106 of 112

Line-Conducted Test Data

\$15.407



Plot 6-121. Line Conducted Plot with 802.11a UNII Band 2A (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.611	N	0.1	44.25	56.00	11.75	34.67	46.00	11.33
2.240	N	0.2	41.49	56.00	14.51	34.48	46.00	11.52
2.643	N	0.2	41.12	56.00	14.88	34.16	46.00	11.84
2.931	N	0.2	41.31	56.00	14.69	34.92	46.00	11.08
4.983	N	0.2	40.00	56.00	16.00	33.60	46.00	12.40
8.561	N	0.3	42.26	60.00	17.74	33.32	50.00	16.68

Table 6-32. Line Conducted Data with 802.11a UNII Band 2A (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 107 of 112

Line-Conducted Test Data

\$15.407



Plot 6-122. Line Conducted Plot with 802.11a UNII Band 2C (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.195	L1	0.2	41.84	63.82	21.98	25.67	53.82	28.15
0.499	L1	0.1	39.80	56.02	16.22	24.99	46.02	21.03
0.602	L1	0.1	42.36	56.00	13.64	27.99	46.00	18.01
3.109	L1	0.2	26.61	56.00	29.39	19.74	46.00	26.26
4.952	L1	0.2	30.95	56.00	25.05	23.91	46.00	22.09
8.882	L1	0.3	43.38	60.00	16.62	28.66	50.00	21.34

Table 6-33. Line Conducted Plot with 802.11a UNII Band 2C (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 108 of 112

Line-Conducted Test Data

\$15.407



Plot 6-123. Line Conducted Plot with 802.11a UNII Band 2C (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.611	N	0.1	44.23	56.00	11.77	34.77	46.00	11.23
2.238	N	0.2	41.39	56.00	14.61	34.48	46.00	11.52
2.546	N	0.2	41.09	56.00	14.91	34.11	46.00	11.89
2.967	N	0.2	41.19	56.00	14.81	34.56	46.00	11.44
8.376	N	0.3	43.33	60.00	16.67	33.58	50.00	16.42
9.137	N	0.3	41.28	60.00	18.72	32.79	50.00	17.21

Table 6-34. Line Conducted Data with 802.11a UNII Band 2C (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 109 of 112

Line-Conducted Test Data

\$15.407



Plot 6-124. Line Conducted Plot with 802.11a UNII Band 3 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.195	L1	0.2	41.88	63.82	21.94	25.63	53.82	28.19
0.503	L1	0.1	39.80	56.00	16.20	25.29	46.00	20.71
0.602	L1	0.1	42.41	56.00	13.59	28.00	46.00	18.00
4.814	L1	0.2	31.72	56.00	24.28	23.68	46.00	22.32
7.062	L1	0.3	34.57	60.00	25.43	22.60	50.00	27.40
8.408	L1	0.3	43.17	60.00	16.83	28.77	50.00	21.23

Table 6-35. Line Conducted Plot with 802.11a UNII Band 3 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 110 of 112

Line-Conducted Test Data

\$15.407



Plot 6-125. Line Conducted Plot with 802.11a UNII Band 3 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.605	N	0.1	44.15	56.00	11.85	34.68	46.00	11.32
2.252	N	0.2	40.89	56.00	15.11	33.60	46.00	12.40
2.544	N	0.2	41.05	56.00	14.95	33.95	46.00	12.05
3.055	N	0.2	41.09	56.00	14.91	33.78	46.00	12.22
4.880	N	0.2	40.28	56.00	15.72	33.33	46.00	12.67
8.385	N	0.3	43.18	60.00	16.82	33.42	50.00	16.58

Table 6-36. Line Conducted Data with 802.11a UNII Band 3 (N)

Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: ZNFUS995	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset		Page 111 of 112

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **LGE Portable Handset FCC ID: ZNFUS995** is in compliance with Part 15E of the FCC Rules.

FCC ID: ZNFUS995	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n/ac UNII MEASUREMENT REPORT (CERTIFICATION)	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1411042067.ZNF	Test Dates: 11/03 - 11/14/2014	EUT Type: Portable Handset	Page 112 of 112	