



SAR EVALUATION REPORT

Applicant Name:

LG Electronics MobileComm U.S.A., Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

06/07/17 - 07/17/17

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M1706070187-01-R54.ZNF

FCC ID:

ZNFV30A

APPLICANT:

LG ELECTRONICS MOBILECOMM U.S.A., INC.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model:

LG-H931

Additional Model(s):

LGH931, H931, LG-H933, LGH933, H933, LG-VS996, LGVS996, VS996, LG-US998, LGUS998, US998

Equipment Class	Band & Mode	Tx Frequency	SAR			
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)	10 gm Phablet (W/kg)
PCE	GSMGPRS/EDGE 850	824.20 - 848.80 MHz	0.10	0.49	0.50	N/A
PCE	GSMGPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.15	0.56	0.70	N/A
PCE	UMTS 850	826.40 - 846.60 MHz	0.11	0.50	0.50	N/A
PCE	UMTS 1750	1712.4 - 1752.6 MHz	0.17	0.78	0.78	N/A
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.23	0.65	0.71	N/A
PCE	Cell. CDMA/EVDO	824.70 - 848.31 MHz	0.11	0.50	0.51	N/A
PCE	PCS CDMA/EVDO	1851.25 - 1908.75 MHz	0.13	0.59	0.61	N/A
PCE	LTE Band 12	699.7 - 715.3 MHz	< 0.1	0.44	0.44	N/A
PCE	LTE Band 17	706.5 - 713.5 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 13	779.5 - 784.5 MHz	0.11	0.48	0.48	N/A
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	< 0.1	0.48	0.48	N/A
PCE	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	0.15	0.72	0.72	N/A
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.14	0.75	0.76	N/A
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A	N/A	N/A
PCE	LTE Band 30	2307.5 - 2312.5 MHz	< 0.1	0.84	0.84	N/A
PCE	LTE Band 7	2502.5 - 2567.5 MHz	< 0.1	0.31	0.31	N/A
PCE	LTE Band 41	2498.5 - 2567.5 MHz	< 0.1	0.44	0.44	N/A
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.64	0.28	0.26	N/A
NII	U-NII-1	5180 - 5240 MHz	N/A	N/A	0.30	N/A
NII	U-NII-2A	5260 - 5320 MHz	0.48	0.36	N/A	1.43
NII	U-NII-2C	5500 - 5720 MHz	0.41	0.55	N/A	1.60
NII	U-NII-3	5745 - 5825 MHz	0.54	0.64	0.64	N/A
DSS/DTS	Bluetooth	2402 - 2480 MHz	0.22	< 0.1	< 0.1	N/A
Simultaneous SAR per KDB 690783 D01v01r03:			1.29	1.57	1.59	2.80

Note: This revised Test Report (S/N: 1M1706070187-01-R4.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 1 of 99

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	11
3	INTRODUCTION	12
4	DOSIMETRIC ASSESSMENT	13
5	DEFINITION OF REFERENCE POINTS.....	14
6	TEST CONFIGURATION POSITIONS.....	15
7	RF EXPOSURE LIMITS	19
8	FCC MEASUREMENT PROCEDURES.....	20
9	RF CONDUCTED POWERS	27
10	SYSTEM VERIFICATION.....	60
11	SAR DATA SUMMARY	65
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	83
13	SAR MEASUREMENT VARIABILITY	94
14	EQUIPMENT LIST	95
15	MEASUREMENT UNCERTAINTIES.....	96
16	CONCLUSION.....	97
17	REFERENCES	98
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX G: WLAN POWER REDUCTION VERIFICATION		
APPENDIX H: CONDUCTED POWERS FOR 4x4 DL MIMO		
APPENDIX I: CONDUCTED POWERS FOR LAA		

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 2 of 99	

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
Cell. CDMA/EVDO	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 30	Voice/Data	2307.5 - 2312.5 MHz
LTE Band 7	Voice/Data	2502.5 - 2567.5 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz

1.2 Power Reduction for SAR

This device uses an independent fixed level power reduction mechanism for WLAN operations during voice or VoIP held to ear scenarios. Per FCC Guidance, the held-to-ear exposure conditions were evaluated at reduced power according to the head SAR positions described in IEEE 1528-2013. Detailed descriptions of the power reduction mechanism are included in the operational description.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 3 of 99

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Power

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	34.2	34.2	30.0	28.0	27.0	27.0	27.0	26.0	25.0
	Nominal	33.7	33.7	29.5	27.5	26.5	26.5	26.5	25.5	24.5
GSM/GPRS/EDGE 1900	Maximum	31.7	31.7	27.5	26.5	25.5	26.0	26.0	25.5	24.5
	Nominal	31.2	31.2	27.0	26.0	25.0	25.5	25.5	25.0	24.0

Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	3GPP DC-HSDPA
UMTS Band 5 (850 MHz)	Maximum	25.5	25.5	25.5	25.5
	Nominal	25.0	25.0	25.0	25.0
UMTS Band 4 (1750 MHz)	Maximum	24.7	24.7	24.7	24.7
	Nominal	24.2	24.2	24.2	24.2
UMTS Band 2 (1900 MHz)	Maximum	24.7	24.7	24.7	24.7
	Nominal	24.2	24.2	24.2	24.2

Mode / Band		Modulated Average (dBm)
Cell. CDMA/EVDO	Maximum	25.5
	Nominal	25.0
PCS CDMA/EVDO	Maximum	24.7
	Nominal	24.2

Mode / Band		Modulated Average (dBm)
LTE Band 12	Maximum	25.5
	Nominal	25.0
LTE Band 17	Maximum	25.5
	Nominal	25.0
LTE Band 13	Maximum	25.5
	Nominal	25.0
LTE Band 5 (Cell)	Maximum	25.5
	Nominal	25.0
LTE Band 66 (AWS)	Maximum	24.7
	Nominal	24.2
LTE Band 4 (AWS)	Maximum	24.7
	Nominal	24.2
LTE Band 25 (PCS)	Maximum	24.7
	Nominal	24.2
LTE Band 2 (PCS)	Maximum	24.7
	Nominal	24.2
LTE Band 30	Maximum	25.2
	Nominal	24.7
LTE Band 7	Maximum	23.7
	Nominal	23.2
LTE Band 41	Maximum	22.7
	Nominal	22.2

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 4 of 99

Mode / Band		Modulated Average - Single Tx Chain (dBm)						Modulated Average - MIMO (dBm)		
		Antenna 1			Antenna 2			MIMO		
		Ch 1-2	Ch 3-9	Ch 10-11	Ch 1-2	Ch 3-9	Ch 10-11	Ch 1-2	Ch 3-9	Ch 10-11
IEEE 802.11b (2.4 GHz)	Maximum	20.0			19.5			22.7		
	Nominal	19.0			18.5			21.7		
IEEE 802.11g (2.4 GHz)	Maximum	17.5	18.5	16.0	17.5	18.5	16.0	20.5	21.5	19.0
	Nominal	16.5	17.5	15.0	16.5	17.5	15.0	19.5	20.5	18.0
IEEE 802.11n (2.4 GHz)	Maximum	16.5	17.5	15.0	16.5	17.5	15.0	19.5	20.5	18.0
	Nominal	15.5	16.5	14.0	15.5	16.5	14.0	18.5	19.5	17.0
IEEE 802.11ac (2.4 GHz)	Maximum	16.5	17.5	15.0	16.5	17.5	15.0	19.5	20.5	18.0
	Nominal	15.5	16.5	14.0	15.5	16.5	14.0	18.5	19.5	17.0

Mode / Band		Modulated Average (dBm)
Bluetooth 1 Mbps	Maximum	12.5
	Nominal	11.5
Bluetooth 2 Mbps	Maximum	12.0
	Nominal	11.0
Bluetooth 3 Mbps	Maximum	12.0
	Nominal	11.0
Bluetooth LE	Maximum	2.5
	Nominal	1.5

Mode / Band		Modulated Average (dBm)		
		20 MHz Bandwidth		
		Antenna 1	Antenna 2	MIMO
IEEE 802.11a (5 GHz)	Maximum	17.0	16.5	19.7
	Nominal	16.0	15.5	18.7
IEEE 802.11n (5 GHz)	Maximum	17.0	16.5	19.7
	Nominal	16.0	15.5	18.7
IEEE 802.11ac (5 GHz)	Maximum	17.0	16.5	19.7
	Nominal	16.0	15.5	18.7

Mode / Band		Modulated Average (dBm)								Modulated Average - MIMO (dBm)			
		40 MHz Bandwidth											
		Antenna 1				Antenna 2				MIMO			
		Ch 38	Ch 46, 54	Ch 62, 102	Ch 110 - 159	Ch 38	Ch 46, 54	Ch 62, 102	Ch 110 - 159	Ch 38	Ch 46, 54	Ch 62, 102	Ch 110 - 159
IEEE 802.11n (5 GHz)	Maximum	14.0	16.0	14.0	16.0	13.5	15.5	13.5	15.5	16.7	18.7	16.7	18.7
	Nominal	13.0	15.0	13.0	15.0	12.5	14.5	12.5	14.5	15.7	17.7	15.7	17.7
IEEE 802.11ac (5 GHz)	Maximum	14.0	16.0	14.0	16.0	13.5	15.5	13.5	15.5	16.7	18.7	16.7	18.7
	Nominal	13.0	15.0	13.0	15.0	12.5	14.5	12.5	14.5	15.7	17.7	15.7	17.7

Mode / Band		Modulated Average (dBm)						Modulated Average - MIMO (dBm)		
		80 MHz Bandwidth								
		Antenna 1			Antenna 2			MIMO		
		Ch 42	Ch 58	Ch 106 - 155	Ch 42	Ch 58	Ch 106 - 155	Ch 42	Ch 58	Ch 106 - 155
IEEE 802.11ac (5 GHz)	Maximum	13.0	11.0	13.0	12.5	10.5	12.5	15.7	13.7	15.7
	Nominal	12.0	10.0	12.0	11.5	9.5	11.5	14.7	12.7	14.7

FCC ID: ZNFV30A		SAR EVALUATION REPORT					Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset				Page 5 of 99	

1.3.2 Reduced Power

Mode / Band		Modulated Average (dBm)						Modulated Average - MIMO (dBm)		
		Antenna 1			Antenna 2			MIMO		
		Ch 1-2	Ch 3-9	Ch 10-11	Ch 1-2	Ch 3-9	Ch 10-11	Ch 1-2	Ch 3-9	Ch 10-11
IEEE 802.11b (2.4 GHz)	Maximum	17.0			17.0			20.0		
	Nominal	16.0			16.0			19.0		
IEEE 802.11g (2.4 GHz)	Maximum	17.0	17.0	16.0	17.0	17.0	16.0	20.0	20.0	19.0
	Nominal	16.0	16.0	15.0	16.0	16.0	15.0	19.0	19.0	18.0
IEEE 802.11n (2.4 GHz)	Maximum	16.5	17.0	15.0	16.5	17.0	15.0	19.5	20.0	18.0
	Nominal	15.5	16.0	14.0	15.5	16.0	14.0	18.5	19.0	17.0
IEEE 802.11ac (2.4 GHz)	Maximum	16.5	17.0	15.0	16.5	17.0	15.0	19.5	20.0	18.0
	Nominal	15.5	16.0	14.0	15.5	16.0	14.0	18.5	19.0	17.0

1.4 DUT Antenna Locations

The overall dimensions of this device are > 9 x 5 cm. A diagram showing the location of the device antennas can be found in Appendix F. Since the diagonal dimension of this device is > 160 mm and <200 mm, it is considered a "phablet."

**Table 1-1
Device Edges/Sides for SAR Testing**

Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	Yes
GPRS 1900	Yes	Yes	No	Yes	No	Yes
UMTS 850	Yes	Yes	No	Yes	Yes	Yes
UMTS 1750	Yes	Yes	No	Yes	No	Yes
UMTS 1900	Yes	Yes	No	Yes	No	Yes
Cell. EVDO	Yes	Yes	No	Yes	Yes	Yes
PCS EVDO	Yes	Yes	No	Yes	No	Yes
LTE Band 12	Yes	Yes	No	Yes	Yes	Yes
LTE Band 13	Yes	Yes	No	Yes	Yes	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	Yes	Yes
LTE Band 66 (AWS)	Yes	Yes	No	Yes	No	Yes
LTE Band 25 (PCS)	Yes	Yes	No	Yes	No	Yes
LTE Band 30	Yes	Yes	No	Yes	Yes	Yes
LTE Band 7	Yes	Yes	No	Yes	No	Yes
LTE Band 41	Yes	Yes	No	Yes	No	Yes
2.4 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
2.4 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 1	Yes	Yes	Yes	No	No	Yes
5 GHz WLAN Ant 2	Yes	Yes	Yes	No	No	Yes
Bluetooth	Yes	Yes	Yes	No	No	Yes

Note: Particular DUT edges were not required to be evaluated for wireless router SAR or phablet SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v02r01 Section III and FCC KDB Publication 648474 D04v01r03. The distances between the transmit antennas and the edges of the device are included in the filing. When wireless router mode is enabled, U-NII-2A and U-NII-2C operations are disabled.

1.5 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix F.

FCC ID: ZNFV30A	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 6 of 99

1.6 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



Figure 1-1
Simultaneous Transmission Paths

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 7 of 99

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Phablet	Notes
1	1x CDMA voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	Yes	
2	1x CDMA voice + 5 GHz Wi-Fi	Yes	Yes	N/A	Yes	
3	1x CDMA voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	*Bluetooth Tethering is considered.
4	1x CDMA voice + 2.4 GHz Wi-Fi MIMO	Yes	Yes	N/A	Yes	
5	1x CDMA voice + 5 GHz Wi-Fi MIMO	Yes	Yes	N/A	Yes	
6	1x CDMA voice + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	Yes	Yes	N/A	Yes	
7	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	Yes	
8	GSM voice + 5 GHz Wi-Fi	Yes	Yes	N/A	Yes	
9	GSM voice + 2.4 GHz Bluetooth	Yes^	Yes	N/A	Yes	*Bluetooth Tethering is considered.
10	GSM voice + 2.4 GHz Wi-Fi MIMO	Yes	Yes	N/A	Yes	
11	GSM voice + 5 GHz Wi-Fi MIMO	Yes	Yes	N/A	Yes	
12	GSM voice + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	Yes	Yes	N/A	Yes	
13	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	Yes	
14	UMTS + 5 GHz Wi-Fi	Yes	Yes	Yes	Yes	
15	UMTS + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	*Bluetooth Tethering is considered.
16	UMTS + 2.4 GHz Wi-Fi MIMO	Yes	Yes	Yes	Yes	
17	UMTS + 5 GHz Wi-Fi MIMO	Yes	Yes	Yes	Yes	
18	UMTS + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	Yes	Yes	Yes	Yes	
19	LTE + 2.4 GHz Wi-Fi	Yes	Yes	Yes	Yes	
20	LTE + 5 GHz Wi-Fi	Yes	Yes	Yes	Yes	
21	LTE + 2.4 GHz Bluetooth	Yes^	Yes	Yes^	Yes	*Bluetooth Tethering is considered.
22	LTE + 2.4 GHz Wi-Fi MIMO	Yes	Yes	Yes	Yes	
23	LTE + 5 GHz Wi-Fi MIMO	Yes	Yes	Yes	Yes	
24	LTE + 2.4 GHz Wi-Fi + 5 GHz Wi-Fi	Yes	Yes	Yes	Yes	
25	CDMA/EVDO data + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
26	CDMA/EVDO data + 5 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
27	CDMA/EVDO data + 2.4 GHz Bluetooth	Yes^	Yes*	Yes^	Yes	*-Pre-installed VOIP applications are considered. *Bluetooth Tethering is considered.
28	CDMA/EVDO data + 2.4 GHz Wi-Fi MIMO	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
29	CDMA/EVDO data + 5 GHz Wi-Fi MIMO	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
30	CDMA/EVDO data + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
31	GPRS/EDGE + 2.4 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
32	GPRS/EDGE + 5 GHz Wi-Fi	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
33	GPRS/EDGE + 2.4 GHz Bluetooth	Yes^	Yes*	Yes^	Yes	*-Pre-installed VOIP applications are considered. *Bluetooth Tethering is considered.
34	GPRS/EDGE + 2.4 GHz Wi-Fi MIMO	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
35	GPRS/EDGE + 5 GHz Wi-Fi MIMO	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.
36	GPRS/EDGE + 2.4 GHz Wi-Fi Ant 1 + 5 GHz Wi-Fi Ant 2	Yes*	Yes*	Yes	Yes	*-Pre-installed VOIP applications are considered.

1. All licensed modes share the same antenna path and cannot transmit simultaneously.
2. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.
3. Per the manufacturer, WIFI Direct is expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
4. 5 GHz Wireless Router is only supported for the U-NII-1 and U-NII-3 by S/W, therefore U-NII2A, and U-NII2C were not evaluated for wireless router conditions.
5. This device supports 2x2 MIMO Tx for WLAN. 802.11a/g/n/ac modes support CDD and 802.11n/ac modes additionally support SDM. 802.11b mode supports TDD operations only.
6. This device supports VOLTE and VOWIFI.
7. Bluetooth tethering is supported.

1.7 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

Since Wireless Router operations are not allowed by the chipset firmware using U-NII-2A & U-NII-2C WIFI, only 2.4 GHz, U-NII-1, and U-NII-3 WIFI Hotspot SAR tests and combinations are considered for SAR with respect to Wireless Router configurations according to FCC KDB 941225 D06v02r01.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 8 of 99	

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) Band gap channels are supported

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Because wireless router operations are not supported for U-NII-2A & U-NII-2C WLAN, phablet SAR tests were performed. Phablet SAR was not evaluated for Bluetooth, 2.4 GHz, U-NII-1, and U-NII-3 WLAN operations since wireless router 1g SAR was < 1.2 W/kg.

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

CDMA 1X Advanced technology was not required for SAR since the maximum allowed output powers for 1x Advanced was not more than 0.25 dB higher than the maximum powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg per FCC KDB Publication 941225 D01v03r01.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is greater than 160mm and less than 200mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was not evaluated for licensed technologies since wireless router 1g SAR was < 1.2 W/kg for these modes.

This device supports 64QAM on the uplink for LTE Operations. Conducted powers for 64QAM uplink configurations were measured per Section 5.1 of FCC KDB Publication 941225 D05v02r05. SAR was not required for 64QAM since the highest maximum output power for 64QAM is $\leq \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg, per Section 5.2.4 of FCC KDB Publication 941225 D05v02r05.

This device supports both LTE B12 and LTE B17. Since the supported frequency span for LTE B17 falls completely within the supported frequency span for LTE B12, both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B12.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 9 of 99

This device supports both LTE B66 (AWS) and LTE B4 (AWS). Since the supported frequency span for LTE B4 (AWS) falls completely within the supported frequency span for LTE B66 (AWS), both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B66 (AWS).

This device supports both LTE B25 (PCS) and LTE B2 (PCS). Since the supported frequency span for LTE B2 (PCS) falls completely within the supported frequency span for LTE B25 (PCS), both LTE bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE B25 (PCS).

This device supports downlink 4x4 MIMO operations for LTE Bands 2, 4, and 66 only. Per May 2017 TCB Workshop Notes, SAR for downlink 4x4 MIMO was not required since the maximum average output power with 4x4 downlink MIMO active was not > 0.25 dB higher than the maximum output power with downlink 4x4 MIMO inactive.

1.8 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D01v03r01, D05v02r04, D05Av01r02, D06v02r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 648474 D04v01r03 (Phablet Procedures)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number	Phablet Serial Number
GSM/GPRS/EDGE 850	04981	05061	05061	-
GSM/GPRS/EDGE 1900	04981	05061	05061	-
UMTS 850	04999	04999	04999	-
UMTS 1750	04999	04981	04981	-
UMTS 1900	04999	04999	04999	-
Cell. CDMA/EVDO	04999	04999	04999	-
PCS CDMA/EVDO	04999	04999	04999	-
LTE Band 12	05012	05004	05004	-
LTE Band 13	05012	05004	05004	-
LTE Band 5 (Cell)	05038	05012	05012	-
LTE Band 66 (AWS)	05004	05012	05012	-
LTE Band 25 (PCS)	05004	05012	05012	-
LTE Band 30	05020	05020	05020	-
LTE Band 7	05004	05038	05038	-
LTE Band 41	05020	05012	05012	-
2.4 GHz WLAN	05145	05145	05145	-
5 GHz WLAN	05160	05160, 05145	05160, 05145	05160
Bluetooth	05145	05145	05145	-

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 10 of 99

2 LTE INFORMATION

LTE Information					
FCC ID	ZNFV30A				
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 17 (706.5 - 713.5 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 30 (2307.5 - 2312.5 MHz)				
	LTE Band 7 (2502.5 - 2567.5 MHz)				
Channel Bandwidths	LTE Band 41 (2498.5 - 2687.5 MHz)				
	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 17: 5 MHz, 10 MHz				
	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 30: 5 MHz, 10 MHz				
Channel Numbers and Frequencies (MHz)	LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	Low	Low-Mid	Mid	Mid-High	High
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)	715.3 (23173)	
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)	714.5 (23165)	
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)	713.5 (23155)	
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)	711 (23130)	
LTE Band 17: 5 MHz	706.5 (23755)		710 (23790)	713.5 (23825)	
LTE Band 17: 10 MHz	709 (23780)		710 (23790)	711 (23800)	
LTE Band 13: 5 MHz	779.5 (23205)		782 (23230)	784.5 (23255)	
LTE Band 13: 10 MHz	N/A		782 (23230)	N/A	
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)	848.3 (20643)	
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)	847.5 (20635)	
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)	846.5 (20625)	
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)	844 (20600)	
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)		1745 (132322)	1779.3 (132665)	
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)		1745 (132322)	1778.5 (132657)	
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)		1745 (132322)	1777.5 (132647)	
LTE Band 66 (AWS): 10 MHz	1715 (132022)		1745 (132322)	1775 (132622)	
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)		1745 (132322)	1772.5 (132597)	
LTE Band 66 (AWS): 20 MHz	1720 (132072)		1745 (132322)	1770 (132572)	
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)	1754.3 (20393)	
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)	1753.5 (20385)	
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)	1752.5 (20375)	
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)	1750 (20350)	
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)	1747.5 (20325)	
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)	1745 (20300)	
LTE Band 25 (PCS): 1.4 MHz	1850.7 (26047)		1882.5 (26365)	1914.3 (26683)	
LTE Band 25 (PCS): 3 MHz	1851.5 (26055)		1882.5 (26365)	1913.5 (26675)	
LTE Band 25 (PCS): 5 MHz	1852.5 (26065)		1882.5 (26365)	1912.5 (26665)	
LTE Band 25 (PCS): 10 MHz	1855 (26090)		1882.5 (26365)	1910 (26640)	
LTE Band 25 (PCS): 15 MHz	1857.5 (26115)		1882.5 (26365)	1907.5 (26615)	
LTE Band 25 (PCS): 20 MHz	1860 (26140)		1882.5 (26365)	1905 (26590)	
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)	1909.3 (19193)	
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)	1908.5 (19185)	
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)	1907.5 (19175)	
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)	1905 (19150)	
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)	1902.5 (19125)	
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)	1900 (19100)	
LTE Band 30: 5 MHz	2307.5 (27685)		2310 (27710)	2312.5 (27735)	
LTE Band 30: 10 MHz	N/A		2310 (27710)	N/A	
LTE Band 7: 5 MHz	2502.5 (20775)		2535 (21100)	2567.5 (21425)	
LTE Band 7: 10 MHz	2505 (20800)		2535 (21100)	2565 (21400)	
LTE Band 7: 15 MHz	2507.5 (20825)		2535 (21100)	2562.5 (21375)	
LTE Band 7: 20 MHz	2510 (20850)		2535 (21100)	2560 (21350)	
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	DL: 16, UL: 5				
Modulations Supported in UL	QPSK, 16QAM, 64QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations				
LTE Release 14 Additional Information	This device does not support full features on 3GPP Release 14. It supports downlink carrier aggregation, downlink MIMO, and LAA features as shown in Section 9, Appendix H, and Appendix I. All other uplink communications are identical to the Release 8 specifications. Uplink Communications are done on the PCC unless otherwise specified. The following LTE Release 14 features are not supported: Relay, HetNet, Enhanced eCIC, MDH, eMBMS, Cross-carrier scheduling, Enhanced SC-FDMA				

FCC ID: ZNFV30A			SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 11 of 99		

3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 12 of 99

4 DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area
Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 13 of 99

5 DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.




Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 14 of 99

6 TEST CONFIGURATION POSITIONS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 15 of 99




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04v01r03. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 16 of 99

dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v06 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v06, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 17 of 99

6.8 Phablet Configurations

For smart phones with a display diagonal dimension > 150 mm or an overall diagonal dimension > 160 mm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the phablets procedures outlined in KDB Publication 648474 D04v01r03 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna ≤ 25 mm from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 18 of 99

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 19 of 99

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

8.4 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

8.4.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.” Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 20 of 99

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.

Table 8-1
Parameters for Max. Power for RC1

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 8-2
Parameters for Max. Power for RC3

Parameter	Units	Value
I_{or}	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode; otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

Head SAR is additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.4.5 for EVDO Rev. A configuration parameters.

8.4.3 Body-worn SAR Measurements

SAR for body-worn exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH+SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. When multiple code channels are enabled, the transmitter output can shift by more than 0.5 dB and may lead to higher SAR drifts and SCH dropouts.

The 3G SAR test reduction procedure is applied to body-worn accessory SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

8.4.4 Body-worn SAR Measurements for EVDO Devices

For handsets with Ev-Do capabilities, the 3G SAR test reduction procedure is applied to Ev-Do Rev. 0 with 1x RTT RC3 as the primary mode to determine body-worn accessory test requirements. Otherwise, body-worn accessory SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn accessory exposure in RC3.

The 3G SAR test reduction procedure is applied to Rev. A, with Rev. 0 as the primary mode to determine body-worn accessory SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1x RTT RC3 as the primary mode.

When SAR is required for EVDO Rev. A, SAR is measured with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations, using

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 21 of 99

the highest reported SAR configuration for body-worn accessory exposure in Rev. 0 or 1x RTT RC3, as appropriate.

8.4.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode; otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn accessory exposure in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

For Ev-Do data devices that also support 1x RTT voice and/or data operations, the 3G SAR test reduction procedure is applied to 1x RTT RC3 and RC1 with Ev-Do Rev. 0 and Rev. A as the respective primary modes. Otherwise, the 'Body-Worn Accessory SAR' procedures in the '3GPP2 CDMA 2000 1x Handsets' section are applied.

8.4.6 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers are measured using SO75 with RC8 on the uplink and RC11 on the downlink per FCC KDB Publication 941225 D01v03r01. Smart blanking is disabled for all measurements. The EUT is configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers are measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

The 3G SAR test reduction procedure is applied to the 1x-Advanced transmission mode with 1x RTT RC3 as the primary mode. When SAR measurement is required, the 1x-Advanced power measurement configurations are used. The 1x Advanced SAR procedures are applied separately to head, body-worn accessory and other exposure conditions.

8.5 SAR Measurement Conditions for UMTS

8.5.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCH_n and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.5.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.5.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH_n, for the highest reported SAR configuration in 12.2 kbps RMC.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 22 of 99

8.5.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

8.5.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.5.6 SAR Measurement Conditions for DC-HSDPA

SAR is required for Rel. 8 DC-HSDPA when SAR is required for Rel. 5 HSDPA; otherwise, the 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

8.6 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.6.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.6.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.6.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.6.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 23 of 99

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.6.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

8.6.6 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. For every supported combination of downlink only carrier aggregation, additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

8.7 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.7.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 24 of 99

programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.7.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

8.7.4 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.5 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 25 of 99

required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.6 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.7.7 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 8.7.6). When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.8 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

8.7.9 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 26 of 99

9 RF CONDUCTED POWERS

9.1 CDMA Conducted Powers

Band	Channel	Frequency	SO55 [dBm]	SO55 [dBm]	SO75 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	RC1	RC3	RC11	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	1013	824.7	25.40	25.30	25.33	25.34	25.44	25.50	25.50
	384	836.52	25.47	25.47	25.36	25.29	25.29	25.38	25.46
	777	848.31	25.37	25.34	25.40	25.39	25.35	25.38	25.31
PCS	25	1851.25	24.47	24.61	24.59	24.63	24.49	24.46	24.58
	600	1880	24.59	24.62	24.68	24.58	24.45	24.67	24.46
	1175	1908.75	24.70	24.62	24.61	24.50	24.62	24.50	24.70

Note: RC1 is only applicable for IS-95 compatibility.



Figure 9-1
Power Measurement Setup

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 27 of 99

9.2 GSM Conducted Powers

Maximum Burst-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	34.20	34.16	29.81	27.95	26.85	26.93	26.90	25.82	24.80
	190	34.20	34.16	29.92	28.00	26.99	26.93	26.88	25.94	24.81
	251	34.19	34.15	29.94	27.97	26.91	26.90	26.91	25.92	24.83
GSM 1900	512	31.60	31.56	27.38	26.41	25.31	25.85	25.80	25.31	24.39
	661	31.67	31.61	27.49	26.45	25.50	25.89	25.89	25.46	24.46
	810	31.61	31.56	27.35	26.39	25.36	26.00	25.93	25.41	24.50
Calculated Maximum Frame-Averaged Output Power										
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	25.17	25.13	23.79	23.69	23.84	17.90	20.88	21.56	21.79
	190	25.17	25.13	23.90	23.74	23.98	17.90	20.86	21.68	21.80
	251	25.16	25.12	23.92	23.71	23.90	17.87	20.89	21.66	21.82
GSM 1900	512	22.57	22.53	21.36	22.15	22.30	16.82	19.78	21.05	21.38
	661	22.64	22.58	21.47	22.19	22.49	16.86	19.87	21.20	21.45
	810	22.58	22.53	21.33	22.13	22.35	16.97	19.91	21.15	21.49
GSM 850	Frame	24.67	24.67	23.48	23.24	23.49	17.47	20.48	21.24	21.49
GSM 1900	Avg.Targets:	22.17	22.17	20.98	21.74	21.99	16.47	19.48	20.74	20.99

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B

GPRS Multislot class: 12 (Max 4 Tx uplink slots)

EDGE Multislot class: 12 (Max 4 Tx uplink slots)

DTM Multislot Class: N/A



Figure 9-2
Power Measurement Setup

FCC ID: ZNFV30A	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 28 of 99

9.3 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	1312	1412	1513	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	25.37	25.37	25.39	24.51	24.66	24.70	24.41	24.45	24.68	-
99		12.2 kbps AMR	25.35	25.34	25.40	24.48	24.62	24.65	24.40	24.41	24.63	-
6	HSDPA	Subtest 1	25.32	25.29	25.35	24.56	24.60	24.67	24.57	24.51	24.67	0
6		Subtest 2	25.35	25.31	25.37	24.55	24.56	24.64	24.59	24.48	24.68	0
6		Subtest 3	24.84	24.82	24.88	24.00	24.08	24.16	23.95	23.99	24.12	0.5
6		Subtest 4	24.81	24.89	24.90	24.09	24.10	24.16	23.97	24.02	24.15	0.5
6	HSUPA	Subtest 1	25.24	25.21	25.26	24.50	24.52	24.60	24.52	24.50	24.64	0
6		Subtest 2	23.29	23.31	23.32	22.48	22.55	22.57	22.55	22.58	22.62	2
6		Subtest 3	24.31	24.35	24.37	23.51	23.57	23.55	23.49	23.52	23.58	1
6		Subtest 4	23.37	23.39	23.41	22.45	22.51	22.60	22.51	22.53	22.57	2
6		Subtest 5	25.29	25.22	25.30	24.50	24.53	24.62	24.50	24.50	24.61	0
8	DC-HSDPA	Subtest 1	25.31	25.23	25.32	24.57	24.61	24.70	24.54	24.58	24.62	0
8		Subtest 2	25.27	25.27	25.39	24.47	24.62	24.67	24.54	24.38	24.70	0
8		Subtest 3	24.80	24.77	24.86	24.03	24.05	24.18	24.01	24.05	24.09	0.5
8		Subtest 4	24.80	24.88	24.95	24.09	24.06	24.19	24.04	23.96	24.12	0.5

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- The DUT supports UE category 24 for HSDPA




Figure 9-3
Power Measurement Setup

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 29 of 99

9.4 LTE Conducted Powers

9.4.1 LTE Band 12

Table 9-1
LTE Band 12 Conducted Powers - 10 MHz Bandwidth

LTE Band 12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23095 (707.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.35	0	0
	1	25	25.50		0
	1	49	25.27		0
	25	0	23.92	0-1	1
	25	12	23.98		1
	25	25	24.06		1
	50	0	23.98		1
16QAM	1	0	24.35	0-1	1
	1	25	24.34		1
	1	49	24.37		1
	25	0	22.98	0-2	2
	25	12	23.07		2
	25	25	23.07		2
	50	0	23.06		2
64QAM	1	0	23.34	0-2	2
	1	25	23.29		2
	1	49	23.33		2
	25	0	22.05	0-3	3
	25	12	21.97		3
	25	25	22.02		3
	50	0	21.99		3

Note: LTE Band 12 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-2
LTE Band 12 Conducted Powers - 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.94	24.88	25.10	0	0
	1	12	24.84	24.88	24.97		0
	1	24	24.88	24.84	24.62		0
	12	0	23.98	23.94	24.07	0-1	1
	12	6	23.98	23.92	24.07		1
	12	13	24.05	23.96	24.03		1
	25	0	24.09	23.94	24.05		1
16QAM	1	0	24.42	24.15	24.29	0-1	1
	1	12	24.26	24.18	24.22		1
	1	24	24.38	24.17	24.02		1
	12	0	23.21	23.00	23.11	0-2	2
	12	6	23.19	23.00	23.10		2
	12	13	23.28	22.96	23.07		2
	25	0	23.23	22.95	23.13		2
64QAM	1	0	23.33	23.19	23.25	0-2	2
	1	12	23.26	23.21	23.13		2
	1	24	23.47	23.21	22.92		2
	12	0	22.23	21.94	22.09	0-3	3
	12	6	22.18	22.08	22.20		3
	12	13	22.30	21.96	22.07		3
	25	0	22.21	21.92	22.13		3

FCC ID: ZNFV30A	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 30 of 99

Table 9-3
LTE Band 12 Conducted Powers - 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.99	24.70	24.99	0	0
	1	7	24.96	24.88	25.08		0
	1	14	24.89	24.75	24.55		0
	8	0	23.97	23.92	24.02	0-1	1
	8	4	23.95	23.92	24.02		1
	8	7	23.96	23.91	24.01		1
	15	0	23.95	23.91	24.03		1
16QAM	1	0	24.36	24.05	24.25	0-1	1
	1	7	24.38	24.21	24.31		1
	1	14	24.30	24.07	23.95		1
	8	0	23.04	22.98	23.02	0-2	2
	8	4	22.99	22.99	23.04		2
	8	7	22.97	22.96	22.99		2
	15	0	23.00	22.92	23.06		2
64QAM	1	0	23.42	23.15	23.32	0-2	2
	1	7	23.37	23.19	23.33		2
	1	14	23.27	23.11	22.96		2
	8	0	22.07	21.90	21.95	0-3	3
	8	4	21.96	22.01	22.04		3
	8	7	21.92	21.96	22.00		3
	15	0	21.97	21.85	22.14		3

Table 9-4
LTE Band 12 Conducted Powers -1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.91	24.81	24.82	0	0
	1	2	24.87	24.80	24.88		0
	1	5	24.83	24.80	24.48		0
	3	0	24.98	24.83	24.84		0
	3	2	24.95	24.84	24.64		0
	3	3	24.92	24.80	24.54		0
	6	0	23.84	23.85	23.95	0-1	1
16QAM	1	0	24.21	24.05	24.15	0-1	1
	1	2	24.21	24.13	24.18		1
	1	5	24.11	24.03	23.89		1
	3	0	23.91	23.98	24.01		1
	3	2	23.88	24.00	23.95		1
	3	3	23.84	23.91	23.79		1
	6	0	22.81	22.82	23.15	0-2	2
64QAM	1	0	23.16	22.97	23.22	0-2	2
	1	2	23.29	23.13	23.15		2
	1	5	23.13	22.99	22.82		2
	3	0	22.97	23.02	22.88		2
	3	2	22.94	22.95	22.84		2
	3	3	22.82	22.90	22.77		2
	6	0	21.81	21.70	22.16	0-3	3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 31 of 99

9.4.2

LTE Band 13

Table 9-5
LTE Band 13 Conducted Powers - 10 MHz Bandwidth

LTE Band 13 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.33	0	0
	1	25	25.50		0
	1	49	25.03		0
	25	0	24.32	0-1	1
	25	12	24.29		1
	25	25	23.87		1
	50	0	24.23		1
16QAM	1	0	23.87	0-1	1
	1	25	24.40		1
	1	49	23.65		1
	25	0	23.33	0-2	2
	25	12	23.33		2
	25	25	23.25		2
	50	0	23.41		2
64QAM	1	0	23.26	0-2	2
	1	25	23.44		2
	1	49	23.25		2
	25	0	22.16	0-3	3
	25	12	22.08		3
	25	25	22.33		3
	50	0	22.16		3

Table 9-6
LTE Band 13 Conducted Powers - 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.36	0	0
	1	12	25.14		0
	1	24	24.96		0
	12	0	24.44	0-1	1
	12	6	24.33		1
	12	13	24.23		1
	25	0	24.22		1
16QAM	1	0	24.49	0-1	1
	1	12	24.40		1
	1	24	24.25		1
	12	0	23.41	0-2	2
	12	6	23.43		2
	12	13	23.31		2
	25	0	23.33		2
64QAM	1	0	23.15	0-2	2
	1	12	23.06		2
	1	24	23.22		2
	12	0	22.25	0-3	3
	12	6	22.06		3
	12	13	22.16		3
	25	0	22.06		3

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFV30A			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset			Page 32 of 99

9.4.3

LTE Band 5 (Cell)

Table 9-7
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

LTE Band 5 (Cell) 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20525 (836.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.50	0	0
	1	25	25.50		0
	1	49	25.30		0
	25	0	24.36	0-1	1
	25	12	24.46		1
	25	25	24.39		1
	50	0	24.45		1
16QAM	1	0	24.42	0-1	1
	1	25	24.48		1
	1	49	24.31		1
	25	0	23.41	0-2	2
	25	12	23.48		2
	25	25	23.48		2
	50	0	23.45		2
64QAM	1	0	23.42	0-2	2
	1	25	23.40		2
	1	49	23.21		2
	25	0	22.33	0-3	3
	25	12	22.48		3
	25	25	22.44		3
	50	0	22.44		3

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-8
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.42	25.38	25.34	0	0
	1	12	25.37	25.42	25.07		0
	1	24	25.40	25.42	24.96		0
	12	0	24.40	24.32	24.46	0-1	1
	12	6	24.39	24.46	24.38		1
	12	13	24.33	24.41	24.34		1
	25	0	24.35	24.47	24.40		1
16QAM	1	0	24.32	24.22	24.31	0-1	1
	1	12	24.37	24.48	24.44		1
	1	24	24.42	24.47	24.44		1
	12	0	23.48	23.36	23.29	0-2	2
	12	6	23.42	23.46	23.47		2
	12	13	23.41	23.44	23.49		2
	25	0	23.41	23.46	23.45		2
64QAM	1	0	23.37	23.14	23.34	0-2	2
	1	12	23.30	23.46	23.37		2
	1	24	23.42	23.33	23.41		2
	12	0	22.50	22.37	22.30	0-3	3
	12	6	22.49	22.40	22.48		3
	12	13	22.41	22.38	22.49		3
	25	0	22.40	22.50	22.47		3

FCC ID: ZNFV30A			SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset			Page 33 of 99	

Table 9-9
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.37	25.24	25.24	0	0
	1	7	25.38	25.38	25.33		0
	1	14	25.28	25.29	25.05		0
	8	0	24.37	24.32	24.42	0-1	1
	8	4	24.41	24.45	24.41		1
	8	7	24.36	24.39	24.31		1
	15	0	24.37	24.41	24.32		1
16QAM	1	0	24.36	24.48	24.37	0-1	1
	1	7	24.44	24.37	24.39		1
	1	14	24.36	24.44	24.39		1
	8	0	23.37	23.40	23.40	0-2	2
	8	4	23.38	23.35	23.42		2
	8	7	23.35	23.49	23.34		2
	15	0	23.34	23.43	23.43		2
64QAM	1	0	23.23	23.44	23.32	0-2	2
	1	7	23.47	23.39	23.42		2
	1	14	23.29	23.37	23.37		2
	8	0	22.32	22.40	22.41	0-3	3
	8	4	22.41	22.30	22.47		3
	8	7	22.39	22.48	22.45		3
	15	0	22.33	22.35	22.45		3

Table 9-10
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	25.24	25.33	25.18	0	0
	1	2	25.29	25.37	25.12		0
	1	5	25.24	25.28	24.95		0
	3	0	25.28	25.34	25.11		0
	3	2	25.33	25.35	25.11		0
	3	3	25.28	25.30	25.04		0
	6	0	24.30	24.36	24.22	0-1	1
16QAM	1	0	24.44	24.41	24.40	0-1	1
	1	2	24.32	24.49	24.43		1
	1	5	24.50	24.31	24.47		1
	3	0	24.42	24.43	24.26		1
	3	2	24.46	24.46	24.24		1
	3	3	24.42	24.41	24.18		1
	6	0	23.28	23.49	23.24	0-2	2
64QAM	1	0	23.42	23.38	23.42	0-2	2
	1	2	23.32	23.44	23.50		2
	1	5	23.41	23.30	23.49		2
	3	0	23.46	23.42	23.24		2
	3	2	23.43	23.35	23.34		2
	3	3	23.43	23.35	23.13		2
	6	0	22.22	22.46	22.25	0-3	3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 34 of 99

9.4.4

LTE Band 66 (AWS)

Table 9-11
LTE Band 66 (AWS) Conducted Powers - 20 MHz Bandwidth

LTE Band 66 (AWS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132072 (1720.0 MHz)	132322 (1745.0 MHz)	132572 (1770.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.43	24.65	24.70	0	0
	1	50	24.32	24.54	24.52		0
	1	99	24.05	24.36	24.14		0
	50	0	23.54	23.57	23.58	0-1	1
	50	25	23.16	23.57	23.60		1
	50	50	23.23	23.41	23.59		1
	100	0	23.22	23.43	23.59		1
16QAM	1	0	23.11	23.55	23.69	0-1	1
	1	50	22.90	23.42	23.58		1
	1	99	23.30	23.63	23.62		1
	50	0	22.62	22.62	22.63	0-2	2
	50	25	22.12	22.63	22.65		2
	50	50	22.22	22.53	22.61		2
	100	0	22.19	22.56	22.63		2
64QAM	1	0	22.16	22.56	22.69	0-2	2
	1	50	21.99	22.46	22.58		2
	1	99	22.21	22.67	22.63		2
	50	0	21.64	21.66	21.51	0-3	3
	50	25	21.08	21.68	21.60		3
	50	50	21.29	21.49	21.56		3
	100	0	21.25	21.52	21.67		3

Table 9-12
LTE Band 66 (AWS) Conducted Powers - 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.81	24.46	24.64	0	0
	1	36	24.36	24.22	24.27		0
	1	74	24.09	24.62	24.58		0
	36	0	23.40	23.43	23.66	0-1	1
	36	18	23.63	23.41	23.56		1
	36	37	23.17	23.65	23.68		1
	75	0	22.81	23.65	23.61		1
16QAM	1	0	23.13	23.27	23.46	0-1	1
	1	36	22.74	23.02	23.36		1
	1	74	23.46	23.39	23.54		1
	36	0	22.38	22.45	22.53	0-2	2
	36	18	22.59	22.44	22.63		2
	36	37	22.13	22.65	22.57		2
	75	0	21.85	22.65	22.66		2
64QAM	1	0	22.16	22.25	22.54	0-2	2
	1	36	21.79	21.99	22.36		2
	1	74	22.52	22.46	22.61		2
	36	0	21.29	21.37	21.52	0-3	3
	36	18	21.50	21.49	21.57		3
	36	37	21.07	21.59	21.56		3
	75	0	20.81	21.60	21.66		3

FCC ID: ZNFV30A			SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset				Page 35 of 99

Table 9-13
LTE Band 66 (AWS) Conducted Powers - 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.86	24.23	24.20	0	0
	1	25	24.14	24.28	24.61		0
	1	49	23.86	24.59	24.70		0
	25	0	23.18	23.30	23.70	0-1	1
	25	12	23.32	23.36	23.58		1
	25	25	23.62	23.49	23.48		1
	50	0	23.36	23.40	23.58		1
16QAM	1	0	23.12	22.99	23.53	0-1	1
	1	25	23.36	23.11	23.33		1
	1	49	23.08	23.34	23.53		1
	25	0	22.19	22.41	22.55	0-2	2
	25	12	22.33	22.44	22.52		2
	25	25	22.63	22.53	22.47		2
	50	0	22.46	22.45	22.41		2
64QAM	1	0	22.15	22.01	22.51	0-2	2
	1	25	22.34	22.10	22.27		2
	1	49	22.04	22.39	22.60		2
	25	0	21.11	21.27	21.58	0-3	3
	25	12	21.24	21.50	21.62		3
	25	25	21.57	21.48	21.43		3
	50	0	21.49	21.44	21.39		3

Table 9-14
LTE Band 66 (AWS) Conducted Powers - 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.98	24.15	24.67	0	0
	1	12	24.16	24.14	24.67		0
	1	24	23.87	24.22	24.60		0
	12	0	22.77	23.34	23.62	0-1	1
	12	6	22.82	23.33	23.55		1
	12	13	22.88	23.35	23.53		1
	25	0	22.80	23.32	23.66		1
16QAM	1	0	22.71	23.62	23.65	0-1	1
	1	12	22.80	23.67	23.67		1
	1	24	22.93	23.64	23.31		1
	12	0	21.83	22.49	22.53	0-2	2
	12	6	21.87	22.48	22.52		2
	12	13	21.91	22.49	22.60		2
	25	0	21.85	22.33	22.64		2
64QAM	1	0	21.76	22.62	22.69	0-2	2
	1	12	21.78	22.70	22.60		2
	1	24	21.94	22.57	22.25		2
	12	0	20.83	21.48	21.47	0-3	3
	12	6	20.95	21.50	21.45		3
	12	13	20.94	21.40	21.63		3
	25	0	20.73	21.44	21.52		3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 36 of 99

Table 9-15
LTE Band 66 (AWS) Conducted Powers - 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.13	24.26	24.22	0	0
	1	7	24.25	24.31	24.29		0
	1	14	24.12	24.14	24.22		0
	8	0	23.38	23.32	23.21	0-1	1
	8	4	23.23	23.29	23.23		1
	8	7	23.20	23.22	23.32		1
15	0	23.22	23.23	23.35	1		
16QAM	1	0	23.53	23.45	23.45	0-1	1
	1	7	23.56	23.53	23.23		1
	1	14	23.41	23.42	23.47		1
	8	0	22.33	22.21	22.35	0-2	2
	8	4	22.36	22.15	22.34		2
	8	7	22.33	22.26	22.29		2
15	0	22.22	22.24	22.23	2		
64QAM	1	0	22.40	22.43	22.49	0-2	2
	1	7	22.56	22.55	22.24		2
	1	14	22.33	22.39	22.35		2
	8	0	21.33	21.33	21.31	0-3	3
	8	4	21.42	21.19	21.41		3
	8	7	21.29	21.22	21.16		3
	15	0	21.13	21.29	21.25		3

Table 9-16
LTE Band 66 (AWS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.15	24.18	24.19	0	0
	1	2	24.21	24.17	24.23		0
	1	5	24.35	24.15	24.31		0
	3	0	24.19	24.13	24.21		0
	3	2	24.15	24.13	24.25		0
	3	3	24.13	24.19	24.15	0	
	6	0	23.26	23.11	23.23	0-1	1
16QAM	1	0	23.43	23.53	23.29	0-1	1
	1	2	23.48	23.53	23.51		1
	1	5	23.36	23.35	23.35		1
	3	0	23.25	23.14	23.33		1
	3	2	23.28	23.26	23.38		1
	3	3	23.25	23.13	23.31	1	
	6	0	22.14	22.18	22.13	0-2	2
64QAM	1	0	22.16	22.26	22.33	0-2	2
	1	2	22.25	22.33	22.36		2
	1	5	22.40	22.31	22.40		2
	3	0	22.22	22.35	22.41		2
	3	2	22.46	22.30	22.35		2
	3	3	22.15	22.30	22.26	2	
	6	0	21.23	21.20	21.15	0-3	3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 37 of 99

9.4.5

LTE Band 25 (PCS)

Table 9-17
LTE Band 25 (PCS) Conducted Powers - 20 MHz Bandwidth

LTE Band 25 (PCS) 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26140 (1860.0 MHz)	26365 (1882.5 MHz)	26590 (1905.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.65	24.68	24.70	0	0
	1	50	24.37	24.37	24.65		0
	1	99	24.22	23.98	24.24		0
	50	0	23.28	23.54	23.56	0-1	1
	50	25	23.13	23.28	23.67		1
	50	50	23.29	23.17	23.66		1
16QAM	100	0	23.29	23.28	23.66	0-1	1
	1	0	23.63	23.68	23.51		1
	1	50	23.39	23.49	23.66		1
	1	99	23.53	23.67	23.66	0-2	1
	50	0	22.36	22.59	22.67		2
	50	25	22.14	22.29	22.55		2
64QAM	50	50	22.30	22.18	22.66	0-2	2
	100	0	22.29	22.32	22.53		2
	1	0	22.51	22.60	22.52		0-2
	1	50	22.39	22.44	22.67	2	
	1	99	22.58	22.68	22.61	0-3	
	50	0	21.34	21.58	21.62		3
50	25	21.25	21.28	21.50	3		
64QAM	50	50	21.36	21.14	21.65	0-3	3
	100	0	21.25	21.27	21.49		3

Table 9-18
LTE Band 25 (PCS) Conducted Powers - 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.47	24.43	24.66	0	0
	1	36	24.18	23.98	24.61		0
	1	74	24.26	24.16	24.22		0
	36	0	23.34	23.45	23.63	0-1	1
	36	18	23.19	23.24	23.69		1
	36	37	23.01	23.16	23.52		1
16QAM	75	0	23.16	23.22	23.64	1	
	1	0	23.56	23.64	23.54	0-1	1
	1	36	23.50	23.31	23.59		1
	1	74	23.64	23.44	23.54		1
	36	0	22.41	22.38	22.64	0-2	2
	36	18	22.37	22.18	22.51		2
36	37	22.23	22.05	22.52	2		
64QAM	75	0	22.36	22.24	22.41	2	
	1	0	22.47	22.55	22.54	0-2	2
	1	36	22.46	22.38	22.69		2
	1	74	22.59	22.47	22.60		2
	36	0	21.46	21.34	21.58	0-3	3
	36	18	21.46	21.25	21.54		3
36	37	21.32	21.01	21.46	3		
	75	0	21.35	21.23	21.36		3

FCC ID: ZNFV30A			SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset			Page 38 of 99	

Table 9-19
LTE Band 25 (PCS) Conducted Powers - 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.64	24.37	24.55	0	0
	1	25	24.34	24.01	24.67		0
	1	49	24.30	24.18	24.21		0
	25	0	23.45	23.33	23.62	0-1	1
	25	12	23.41	23.15	23.53		1
	25	25	23.42	23.06	23.66		1
	50	0	23.42	23.13	23.64		1
16QAM	1	0	23.57	23.57	23.53	0-1	1
	1	25	23.61	23.37	23.56		1
	1	49	23.54	23.53	23.58		1
	25	0	22.37	22.37	22.68	0-2	2
	25	12	22.35	22.36	22.65		2
	25	25	22.38	22.14	22.54		2
	50	0	22.43	22.30	22.68		2
64QAM	1	0	22.62	22.61	22.59	0-2	2
	1	25	22.61	22.41	22.47		2
	1	49	22.53	22.57	22.61		2
	25	0	21.34	21.38	21.62	0-3	3
	25	12	21.38	21.30	21.65		3
	25	25	21.33	21.21	21.67		3
	50	0	21.41	21.32	21.63		3

Table 9-20
LTE Band 25 (PCS) Conducted Powers - 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.32	24.21	24.65	0	0
	1	12	24.24	24.07	24.69		0
	1	24	24.23	24.06	24.22		0
	12	0	23.41	23.25	23.68	0-1	1
	12	6	23.37	23.19	23.70		1
	12	13	23.37	23.10	23.50		1
16QAM	25	0	23.37	23.16	23.68	1	
	1	0	23.64	23.54	23.57	0-1	1
	1	12	23.65	23.51	23.57		1
	1	24	23.70	23.42	23.49		1
	12	0	22.44	22.37	22.64	0-2	2
	12	6	22.52	22.24	22.63		2
	12	13	22.52	22.17	22.58		2
25	0	22.41	22.15	22.62	2		
64QAM	1	0	22.55	22.50	22.50	0-2	2
	1	12	22.60	22.60	22.48		2
	1	24	22.65	22.42	22.43		2
	12	0	21.46	21.27	21.55	0-3	3
	12	6	21.45	21.25	21.67		3
	12	13	21.49	21.22	21.69		3
	25	0	21.54	21.19	21.63		3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 39 of 99

Table 9-21
LTE Band 25 (PCS) Conducted Powers - 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.34	24.11	24.67	0	0
	1	7	24.44	24.11	24.37		0
	1	14	24.31	23.98	24.12		0
	8	0	23.37	23.18	23.52	0-1	1
	8	4	23.40	23.17	23.47		1
	8	7	23.36	23.13	23.38		1
	15	0	23.38	23.18	23.43		1
16QAM	1	0	23.55	23.42	23.53	0-1	1
	1	7	23.66	23.54	23.68		1
	1	14	23.65	23.34	23.46		1
	8	0	22.32	22.29	22.52	0-2	2
	8	4	22.32	22.25	22.51		2
	8	7	22.40	22.18	22.40		2
	15	0	22.37	22.17	22.51		2
64QAM	1	0	22.45	22.30	22.50	0-2	2
	1	7	22.66	22.51	22.70		2
	1	14	22.60	22.31	22.42		2
	8	0	21.19	21.16	21.48	0-3	3
	8	4	21.40	21.29	21.49		3
	8	7	21.40	21.28	21.31		3
	15	0	21.37	21.25	21.51		3

Table 9-22
LTE Band 25 (PCS) Conducted Powers -1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.26	24.18	24.20	0	0
	1	2	24.32	24.24	24.18		0
	1	5	24.28	24.16	24.09		0
	3	0	24.29	24.15	24.12		0
	3	2	24.36	24.19	24.13		0
	3	3	24.29	24.13	24.09		0
	6	0	23.28	23.16	23.26	0-1	1
16QAM	1	0	23.69	23.43	23.49	0-1	1
	1	2	23.59	23.55	23.52		1
	1	5	23.69	23.42	23.41		1
	3	0	23.32	23.31	23.27		1
	3	2	23.39	23.36	23.37		1
	3	3	23.35	23.21	23.30		1
	6	0	22.28	22.08	22.45	0-2	2
64QAM	1	0	22.61	22.44	22.45	0-2	2
	1	2	22.58	22.49	22.61		2
	1	5	22.65	22.42	22.29		2
	3	0	22.26	22.26	22.17		2
	3	2	22.38	22.32	22.33		2
	3	3	22.30	22.21	22.34		2
	6	0	21.35	21.10	21.39	0-3	3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 40 of 99	

9.4.6

LTE Band 30

Table 9-23
LTE Band 30 Conducted Powers - 10 MHz Bandwidth

LTE Band 30 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	25.20	0	0
	1	25	25.19		0
	1	49	24.93		0
	25	0	23.80	0-1	1
	25	12	23.79		1
	25	25	23.76		1
	50	0	23.77		1
16QAM	1	0	24.15	0-1	1
	1	25	24.16		1
	1	49	24.16		1
	25	0	22.85	0-2	2
	25	12	22.82		2
	25	25	22.82		2
	50	0	22.86		2
64QAM	1	0	22.80	0-2	2
	1	25	22.89		2
	1	49	22.90		2
	25	0	21.88	0-3	3
	25	12	21.89		3
	25	25	21.84		3
	50	0	21.76		3

Table 9-24
LTE Band 30 Conducted Powers - 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.68	0	0
	1	12	24.64		0
	1	24	24.66		0
	12	0	23.78	0-1	1
	12	6	23.77		1
	12	13	23.76		1
	25	0	23.75		1
16QAM	1	0	24.08	0-1	1
	1	12	24.02		1
	1	24	24.08		1
	12	0	22.92	0-2	2
	12	6	22.94		2
	12	13	22.88		2
	25	0	22.77		2
64QAM	1	0	22.76	0-2	2
	1	12	22.80		2
	1	24	22.65		2
	12	0	21.89	0-3	3
	12	6	21.90		3
	12	13	21.78		3
	25	0	21.80		3

Note: LTE Band 30 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 41 of 99

9.4.7

LTE Band 7

Table 9-25
LTE Band 7 Conducted Powers - 20 MHz Bandwidth

LTE Band 7 20 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20850 (2510.0 MHz)	21100 (2535.0 MHz)	21350 (2560.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.58	23.70	23.66	0	0
	1	50	23.43	23.42	23.62		0
	1	99	23.45	23.22	23.31		0
	50	0	22.54	22.47	22.29	0-1	1
	50	25	22.46	22.41	22.24		1
	50	50	22.39	22.28	22.23		1
	100	0	22.42	22.39	22.27		1
16QAM	1	0	22.61	22.64	22.69	0-1	1
	1	50	22.61	22.57	22.57		1
	1	99	22.70	22.51	22.59		1
	50	0	21.53	21.49	21.37	0-2	2
	50	25	21.43	21.41	21.32		2
	50	50	21.41	21.32	21.26		2
	100	0	21.48	21.40	21.28		2
64QAM	1	0	21.60	21.64	21.70	0-2	2
	1	50	21.48	21.55	21.47		2
	1	99	21.60	21.48	21.60		2
	50	0	20.52	20.43	20.44	0-3	3
	50	25	20.54	20.40	20.23		3
	50	50	20.38	20.39	20.37		3
	100	0	20.48	20.37	20.21		3

Table 9-26
LTE Band 7 Conducted Powers - 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.62	23.45	23.35	0	0
	1	36	23.52	23.25	23.24		0
	1	74	23.42	23.16	23.20		0
	36	0	22.52	22.33	22.25	0-1	1
	36	18	22.50	22.40	22.26		1
	36	37	22.40	22.30	22.20		1
	75	0	22.47	22.38	22.22		1
16QAM	1	0	22.69	22.61	22.65	0-1	1
	1	36	22.65	22.58	22.49		1
	1	74	22.54	22.55	22.45		1
	36	0	21.54	21.34	21.27	0-2	2
	36	18	21.54	21.40	21.25		2
	36	37	21.49	21.31	21.20		2
	75	0	21.47	21.39	21.27		2
64QAM	1	0	21.64	21.57	21.60	0-2	2
	1	36	21.68	21.62	21.48		2
	1	74	21.54	21.61	21.55		2
	36	0	20.61	20.35	20.24	0-3	3
	36	18	20.56	20.36	20.17		3
	36	37	20.38	20.34	20.22		3
	75	0	20.50	20.33	20.28		3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 42 of 99

Table 9-27
LTE Band 7 Conducted Powers - 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.45	23.39	23.27	0	0
	1	25	23.42	23.36	23.21		0
	1	49	23.35	23.28	23.16		0
	25	0	22.46	22.32	22.26	0-1	1
	25	12	22.51	22.42	22.28		1
	25	25	22.46	22.33	22.24		1
16QAM	50	0	22.47	22.37	22.24	0-1	1
	1	0	22.62	22.67	22.69		1
	1	25	22.55	22.68	22.58		1
	1	49	22.61	22.57	22.61	0-2	2
	25	0	21.55	21.37	21.31		2
	25	12	21.50	21.43	21.29		2
64QAM	25	25	21.49	21.36	21.28	0-2	2
	50	0	21.51	21.43	21.28		2
	1	0	21.65	21.67	21.60		0-2
	1	25	21.52	21.70	21.58	2	
	1	49	21.55	21.53	21.67	0-3	
	25	0	20.61	20.36	20.24		3
25	12	20.41	20.41	20.23	3		
25	25	20.45	20.42	20.17	3		
	50	0	20.55	20.55	20.24		3

Table 9-28
LTE Band 7 Conducted Powers - 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.50	23.34	23.12	0	0
	1	12	23.47	23.34	23.10		0
	1	24	23.45	23.30	23.10		0
	12	0	22.43	22.34	22.24	0-1	1
	12	6	22.48	22.38	22.23		1
	12	13	22.46	22.31	22.17		1
16QAM	25	0	22.44	22.33	22.19	0-1	1
	1	0	22.66	22.57	22.52		1
	1	12	22.63	22.60	22.50		1
	1	24	22.53	22.58	22.49	0-2	1
	12	0	21.51	21.40	21.33		2
	12	6	21.54	21.42	21.34		2
64QAM	12	13	21.51	21.35	21.32	0-2	2
	25	0	21.46	21.39	21.21		2
	1	0	21.70	21.62	21.56	0-2	2
	1	12	21.69	21.60	21.49		2
	1	24	21.52	21.60	21.39		2
	64QAM	12	0	20.47	20.44	20.35	0-3
12		6	20.44	20.31	20.34	3	
12		13	20.54	20.39	20.33	3	
25		0	20.38	20.42	20.11	3	

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 43 of 99	

9.4.8

LTE Band 41

Table 9-29
LTE Band 41 Conducted Powers - 20 MHz Bandwidth

LTE Band 41 20 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.69	22.62	22.56	22.54	22.58	0	0
	1	50	22.62	22.58	22.60	22.48	22.64		0
	1	99	22.50	22.57	22.56	22.48	22.68		0
	50	0	21.65	21.54	21.66	21.66	21.61	0-1	1
	50	25	21.67	21.62	21.53	21.61	21.53		1
	50	50	21.59	21.58	21.60	21.55	21.55		1
16QAM	100	0	21.56	21.51	21.56	21.57	21.55	0-1	1
	1	0	21.66	21.67	21.65	21.51	21.53		1
	1	50	21.60	21.61	21.59	21.55	21.65		1
	1	99	21.54	21.58	21.59	21.67	21.56	0-2	1
	50	0	20.52	20.56	20.64	20.57	20.51		2
	50	25	20.52	20.55	20.58	20.61	20.62		2
64QAM	50	50	20.58	20.55	20.63	20.60	20.55	0-2	2
	100	0	20.57	20.60	20.56	20.50	20.54		2
	1	0	20.64	20.56	20.62	20.60	20.58		2
	1	50	20.56	20.60	20.52	20.66	20.48	0-2	2
	1	99	20.59	20.57	20.67	20.56	20.52		2
	50	0	19.48	19.57	19.58	19.50	19.60		0-3
50	25	19.55	19.54	19.60	19.59	19.50	3		
50	50	19.65	19.54	19.68	19.64	19.55	3		
100	0	19.49	19.48	19.66	19.65	19.63	3		

Table 9-30
LTE Band 41 Conducted Powers - 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.57	22.59	22.53	22.58	22.61	0	0
	1	36	22.55	22.61	22.53	22.63	22.57		0
	1	74	22.69	22.53	22.50	22.60	22.48		0
	36	0	21.51	21.60	21.55	21.60	21.52	0-1	1
	36	18	21.50	21.54	21.57	21.59	21.50		1
	36	37	21.52	21.68	21.53	21.62	21.67		1
16QAM	75	0	21.61	21.67	21.63	21.63	21.51	0-1	1
	1	0	21.51	21.56	21.59	21.60	21.63		1
	1	36	21.60	21.57	21.63	21.56	21.63		1
	1	74	21.58	21.54	21.54	21.69	21.61	0-2	1
	36	0	20.62	20.60	20.50	20.54	20.61		2
	36	18	20.56	20.56	20.61	20.59	20.54		2
64QAM	36	37	20.49	20.64	20.50	20.57	20.55	0-2	2
	75	0	20.55	20.68	20.61	20.55	20.58		2
	1	0	20.58	20.59	20.69	20.61	20.55		0-2
	1	36	20.53	20.65	20.58	20.58	20.52	2	
	1	74	20.59	20.58	20.63	20.57	20.58	2	
	36	0	19.61	19.55	19.68	19.63	19.57	0-3	3
36	18	19.65	19.53	19.51	19.52	19.58	3		
36	37	19.69	19.53	19.64	19.46	19.57	3		
	75	0	19.66	19.57	19.49	19.55	19.58		3

FCC ID: ZNFV30A			SAR EVALUATION REPORT				Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17		DUT Type: Portable Handset				Page 44 of 99

Table 9-31
LTE Band 41 Conducted Powers - 10 MHz Bandwidth

LTE Band 41 10 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.66	22.63	22.59	22.60	22.52	0	0
	1	25	22.55	22.62	22.49	22.57	22.61		0
	1	49	22.54	22.58	22.68	22.51	22.51		0
	25	0	21.47	21.50	21.59	21.56	21.63	0-1	1
	25	12	21.59	21.62	21.59	21.58	21.55		1
	25	25	21.63	21.68	21.61	21.59	21.53		1
50	0	21.53	21.60	21.49	21.50	21.61	1		
16QAM	1	0	21.62	21.66	21.55	21.65	21.59	0-1	1
	1	25	21.65	21.60	21.68	21.55	21.61		1
	1	49	21.58	21.59	21.58	21.64	21.62		1
	25	0	20.60	20.57	20.60	20.67	20.50	0-2	2
	25	12	20.62	20.59	20.67	20.59	20.60		2
	25	25	20.56	20.68	20.54	20.55	20.51		2
50	0	20.58	20.60	20.58	20.51	20.57	2		
64QAM	1	0	20.65	20.63	20.65	20.56	20.59	0-2	2
	1	25	20.62	20.56	20.65	20.52	20.57		2
	1	49	20.55	20.67	20.55	20.65	20.63		2
	25	0	19.53	19.53	19.60	19.64	19.62	0-3	3
	25	12	19.54	19.66	19.57	19.50	19.48		3
	25	25	19.53	19.54	19.57	19.52	19.60		3
50	0	19.63	19.50	19.46	19.60	19.50	3		

Table 9-32
LTE Band 41 Conducted Powers - 5 MHz Bandwidth

LTE Band 41 5 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	22.67	22.56	22.59	22.56	22.54	0	0
	1	12	22.66	22.56	22.66	22.61	22.55		0
	1	24	22.52	22.66	22.53	22.67	22.55		0
	12	0	21.50	21.58	21.61	21.56	21.62	0-1	1
	12	6	21.60	21.59	21.47	21.68	21.53		1
	12	13	21.49	21.51	21.55	21.65	21.60		1
	25	0	21.61	21.62	21.48	21.56	21.60		1
16QAM	1	0	21.54	21.47	21.60	21.51	21.62	0-1	1
	1	12	21.47	21.64	21.60	21.64	21.58		1
	1	24	21.48	21.54	21.49	21.58	21.53		1
	12	0	20.54	20.62	20.52	20.50	20.63	0-2	2
	12	6	20.64	20.55	20.59	20.67	20.54		2
	12	13	20.62	20.54	20.52	20.53	20.61		2
	25	0	20.60	20.61	20.59	20.61	20.54		2
64QAM	1	0	20.58	20.47	20.57	20.61	20.64	0-2	2
	1	12	20.54	20.59	20.61	20.58	20.61		2
	1	24	20.61	20.61	20.61	20.59	20.52		2
	12	0	19.60	19.64	19.62	19.64	19.64	0-3	3
	12	6	19.63	19.51	19.59	19.55	19.53		3
	12	13	19.49	19.58	19.61	19.62	19.56		3
	25	0	19.68	19.62	19.66	19.63	19.55		3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 45 of 99	

9.4.9 LTE Carrier Aggregation Conducted Powers

Table 9-33
LTE Band 12 PCC Two Component Carrier Conducted Powers

Combination	PCC Band	PCC								SCC				Power	
		PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 12B	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B12	5	5020	730	25.30	25.50
CA 2A-12A (1)	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	25.50	25.50
CA 12A-30A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B30	10	9820	2355	25.40	25.50
CA 12A-66A (2)	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B66	20	66786	2145	25.46	25.50
CA 4A-12A (2)	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B4	20	2175	2132.5	25.44	25.50
CA 7A-12A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B7	20	3100	2655	25.49	25.50

Table 9-34
LTE Band 12 PCC Three Component Carrier Conducted Powers

Combination	PCC Band	PCC								SCC 1				SCC 2				Power	
		PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 2A-2A-12A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	5	900	1960	LTE B2	5	625	1932.5	25.39	25.50
CA 2A-12B	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B2	20	900	1960	LTE B12	5	5107	738.7	25.35	25.10
CA 4A-12B	LTE B12	5	23155	713.5	QPSK	1	0	5155	743.5	LTE B4	20	2175	2132.5	LTE B12	5	5107	738.7	25.26	25.10
CA 2A-4A-12A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	25.48	25.50
CA 4A-4A-12A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B4	20	2175	2132.5	LTE B4	5	2375	2152.5	25.50	25.50
CA 2A-12A-66A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B66	20	66786	2145	25.48	25.50
CA 2A-12A-30A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B30	10	9820	2355	25.36	25.50
CA 4A-12A-30A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	25.42	25.50
CA 4A-7A-12A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	25.50	25.50
CA 12A-66A-66A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B66	5	66786	2145	LTE B66	5	66461	2112.5	25.47	25.50
CA 2A-7A-12A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B7	20	3100	2655	25.46	25.50
CA 12A-30A-66A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B30	10	68886	2355	LTE B66	20	66786	2145	25.41	25.50

Table 9-35
LTE Band 12 PCC Four Component Carrier Conducted Powers

Combination	PCC Band	PCC								SCC 1				SCC 2				SCC 3				Power	
		PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 12A-30A-66A-66A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B30	10	9820	2355	LTE B66	5	66786	2145	LTE B66	5	66461	2112.5	25.44	25.50
CA 2A-2A-12A-30A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	5	900	1960	LTE B2	5	625	1932.5	LTE B30	10	9820	2355	25.50	25.50
CA 2A-12A-30A-66A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B30	10	9820	2355	LTE B66	20	66786	2145	25.38	25.50
CA 2A-12A-66A-66A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B66	5	66786	2145	LTE B66	5	66461	2112.5	25.49	25.50
CA 2A-4A-7A-12A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	25.44	25.50
CA 2A-4A-4A-12A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B4	5	1975	2112.5	25.50	25.50
CA 2A-4A-12A-30A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	25.47	25.50
CA 4A-4A-12A-30A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B30	10	4850	2355	LTE B4	20	2175	2132.5	LTE B4	5	1975	2112.5	25.45	25.50
CA 2A-2A-12A-66A	LTE B12	10	23095	707.5	QPSK	1	25	5095	737.5	LTE B2	20	900	1960	LTE B2	5	625	1932.5	LTE B66	20	66786	2145	25.47	25.50

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 46 of 99

Table 9-36
LTE Band 17 PCC Two Component Carrier Conducted Powers

Combination	PCC									SCC				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-17A	LTE B17	10	23780	709	QPSK	1	25	5780	739	LTE B2	10	900	1960	25.40	25.50
CA_4A-17A	LTE B17	10	23780	709	QPSK	1	25	5780	739	LTE B4	10	2175	2132.5	25.46	25.50

Table 9-37
LTE Band 13 PCC Two Component Carrier Conducted Powers

Combination	PCC									SCC				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-13A	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B2	20	900	1960	25.26	25.50
CA_13A-66A	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B66	20	66786	2145	25.36	25.50
CA_4A-13A	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B4	20	2175	2132.5	25.40	25.50

Table 9-38
LTE Band 13 Three Component Carrier Conducted Powers

Combination	PCC									SCC 1				SCC 2				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-2A-13A	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B2	5	900	1960	LTE B2	5	625	1932.5	25.49	25.50
CA_2A-13A-66A	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B2	20	900	1960	LTE B66	20	66786	2145	25.40	25.50
CA_2A-4A-13A	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	25.36	25.50
CA_4A-4A-13A	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B4	20	2175	2132.5	LTE B4	5	2375	2152.5	25.50	25.50
CA_13A-66A-66A	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B66	5	66786	2145	LTE B66	5	67311	2197.5	25.49	25.50
CA_13A-66B	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B66	15	66786	2145	LTE B66	5	66885	2154.9	25.49	25.50
CA_13A-66C	LTE B13	10	23230	782	QPSK	1	25	5230	751	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	25.45	25.50

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 47 of 99

Table 9-39
LTE Band 5 Two Component Carrier Conducted Powers

	PCC									SCC				Power	
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-5A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	20	900	1960	25.46	25.50
CA_5B	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B5	5	2453	874.3	25.48	25.50
CA_5A-66A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B66	20	66786	2145	25.43	25.50
CA_4A-5A (1)	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B4	20	2175	2132.5	25.45	25.50
CA_5A-30A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B30	10	9820	2355	25.29	25.50

Table 9-40
LTE Band 5 Three Component Carrier Conducted Powers

	PCC								SCC 1				SCC 2				Power		
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-2A-5A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	5	900	1960	LTE B2	5	625	1932.5	25.46	25.50
CA_2A-5A-66A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	20	900	1960	LTE B66	20	66786	2145	25.43	25.50
CA_2A-4A-5A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	25.48	25.50
CA_4A-4A-5A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B4	5	2175	2132.5	LTE B4	5	1975	2112.5	25.50	25.50
CA_5A-66A-66A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B66	5	66786	2145	LTE B66	5	67311	2197.5	25.48	25.50
CA_5A-66B	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B66	15	66786	2145	LTE B66	5	66885	2154.9	25.49	25.50
CA_5A-66C	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	25.42	25.50
CA_5A-30A-66A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B30	10	9820	2355	LTE B66	20	66786	2145	25.49	25.50
CA_2A-5A-30A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	20	900	1960	LTE B30	10	9820	2355	25.48	25.50
CA_4A-5A-30A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	25.41	25.50

Table 9-41
LTE Band 5 Four Component Carrier Conducted Powers

Combination	PCC Band	PCC								SCC 1				SCC 2				SCC 3				Power	
		PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-5A-66A-66A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	20	900	1960	LTE B66	5	66786	2145	LTE B66	5	67311	2197.5	25.46	25.50
CA_5A-30A-66A-66A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B30	10	4850	2355	LTE B66	5	66786	2145	LTE B66	5	67311	2197.5	25.49	25.50
CA_2A-2A-5A-30A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	5	900	1960	LTE B2	5	625	1932.5	LTE B30	10	9820	2355	25.49	25.50
CA_2A-5A-30A-66A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	20	900	1960	LTE B30	10	9820	2355	LTE B66	20	66786	2145	25.48	25.50
CA_2A-4A-5A-30A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	25.46	25.50
CA_2A-2A-5A-66A	LTE B5	10	20525	836.5	QPSK	1	0	2525	881.5	LTE B2	5	900	1960	LTE B2	5	625	1932.5	LTE B66	20	66786	2145	25.46	25.50

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 48 of 99

Table 9-42
LTE Band 66 Two Component Carrier Conducted Powers

Combination	PCC									SCC				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-66A (2)	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	24.63	24.70
CA_5A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B5	10	2525	881.5	24.70	24.70
CA_13A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B13	10	5230	751	24.70	24.70
CA_66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	5	66461	2112.5	24.66	24.70
CA_66B	LTE B66	10	132622	1775	QPSK	1	49	67086	2175	LTE B66	10	66987	2165.1	24.60	24.70
CA_66C	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	20	66838	2150.2	24.59	24.70
CA_30A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B30	10	9820	2355	24.61	24.70
CA_29A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B29	10	9715	722.5	24.68	24.70
CA_12A-66A (2)	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B12	10	5095	737.5	24.68	24.70

Table 9-43
LTE Band 66 Three Component Carrier Conducted Powers

Combination	PCC									SCC 1				SCC 2				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-12A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B12	10	5095	737.5	24.70	24.70
CA_5A-30A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.64	24.70
CA_2A-5A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B5	10	2525	881.5	24.61	24.70
CA_2A-13A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B13	10	5230	751	24.61	24.70
CA_2A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B66	5	66461	2112.5	24.70	24.70
CA_2A-66B	LTE B66	10	132622	1775	QPSK	1	49	67086	2175	LTE B2	20	900	1960	LTE B66	10	66987	2165.1	24.60	24.70
CA_2A-66C	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B66	20	66838	2150.2	24.68	24.70
CA_2A-2A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B2	5	625	1932.5	24.57	24.70
CA_5A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B5	10	2525	881.5	LTE B66	5	66461	2112.5	24.68	24.70
CA_5A-66B	LTE B66	10	132622	1775	QPSK	1	49	67086	2175	LTE B5	10	2525	881.5	LTE B66	10	66987	2165.1	24.69	24.70
CA_5A-66C	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B5	10	2525	881.5	LTE B66	20	66838	2150.2	24.68	24.70
CA_13A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B13	10	5230	751	LTE B66	5	66461	2112.5	24.62	24.70
CA_13A-66B	LTE B66	10	132622	1775	QPSK	1	49	67086	2175	LTE B13	10	5230	751	LTE B66	10	66987	2165.1	24.70	24.70
CA_13A-66C	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B13	10	5230	751	LTE B66	20	66838	2150.2	24.70	24.70
CA_66A-66C	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	20	66578	2124.2	LTE B66	5	66461	2112.5	24.63	24.70
CA_29A-30A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	24.66	24.70
CA_66A-66B	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	10	66486	2115	LTE B66	10	66585	2124.9	24.70	24.70
CA_66C-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	5	66461	2112.5	LTE B66	20	66838	2150.2	24.60	24.70
CA_66A-66B	LTE B66	10	132622	1775	QPSK	1	49	67086	2175	LTE B66	5	66461	2112.5	LTE B66	10	66987	2165.1	24.55	24.70
CA_12A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B12	10	5095	737.5	LTE B66	5	66461	2112.5	24.59	24.70
CA_12A-30A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.69	24.70
CA_30A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B30	10	5230	2355	LTE B66	5	66461	2112.5	24.60	24.70
CA_2A-30A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B30	10	9820	2355	24.65	24.70

Table 9-44
LTE Band 66 Four Component Carrier Conducted Powers

Combination	PCC									SCC1				SCC2				SCC3				Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dbm)
CA_2A-5A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	5	66461	2112.5	LTE B2	20	900	1960	LTE B5	10	2525	881.5	24.70	24.70
CA_5A-30A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	5	66461	2112.5	LTE B5	10	6535	881.5	LTE B30	10	9820	2355	24.68	24.70
CA_12A-30A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	5	66461	2112.5	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.67	24.70
CA_2A-12A-66A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B66	5	66461	2112.5	LTE B2	20	900	1960	LTE B12	10	5095	737.5	24.66	24.70
CA_2A-5A-30A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.58	24.70
CA_2A-12A-30A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.55	24.70
CA_2A-2A-5A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B2	20	702	1940.2	LTE B5	10	4108	881.5	24.70	24.70
CA_2A-2A-12A-66A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	LTE B2	20	900	1960	LTE B2	5	625	1932.5	LTE B12	20	2668	737.5	24.64	24.70

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 49 of 99	

Table 9-45
LTE Band 4 Two Component Carrier Conducted Powers

Combination	PCC									SCC				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_4A-4A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	5	1975	2112.5	24.68	24.70
CA_2A-4A (2)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	24.70	24.70
CA_4A-5A (1)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B5	10	2525	881.5	24.61	24.70
CA_4A-13A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B13	10	5230	751	24.69	24.70
CA_4A-29A (2)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B29	10	9715	722.5	24.68	24.70
CA_4A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B30	10	9820	2355	24.59	24.70
CA_4A-7A (1)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B7	20	3100	2655	24.68	24.70
CA_4A-12A (2)	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B12	10	5095	737.5	24.65	24.70
CA_4A-17A	LTE B4	10	20350	1750	QPSK	1	49	2350	2150	LTE B17	10	5790	740	24.70	24.70

Table 9-46
LTE Band 4 Three Component Carrier Conducted Powers

Combination	PCC									SCC1				SCC 2				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 4A-4A-7A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	5	1975	2112.5	LTE B7	20	3100	2655	24.59	24.70
CA 2A-4A-7A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B7	20	3100	2655	24.70	24.70
CA 2A-4A-29A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B29	10	9715	722.5	24.69	24.70
CA 4A-4A-29A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	5	1975	2112.5	LTE B29	10	9715	722.5	24.66	24.70
CA 2A-4A-5A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B5	10	2525	881.5	24.62	24.70
CA 2A-4A-13A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B13	10	5230	751	24.70	24.70
CA 4A-4A-5A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	5	1975	2112.5	LTE B5	10	2525	881.5	24.62	24.70
CA 4A-4A-13A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	5	1975	2112.5	LTE B13	10	5230	751	24.65	24.70
CA 4A-12B	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B12	5	5095	737.5	LTE B12	5	5047	732.7	24.20	24.70
CA 2A-4A-12A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B12	10	5095	737.5	24.60	24.70
CA 4A-4A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	5	1975	2112.5	LTE B30	10	9820	2355	24.65	24.70
CA 4A-4A-12A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	5	1975	2112.5	LTE B12	10	5095	737.5	24.68	24.70
CA 2A-4A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B30	10	9820	2355	24.62	24.70
CA 4A-29A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	24.66	24.70
CA 4A-5A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.66	24.70
CA 4A-12A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.66	24.70
CA 4A-7A-7A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B7	20	3100	2655	LTE B7	5	2775	2622.5	24.62	24.70
CA 4A-7A-12A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	24.60	24.70

Table 9-47
LTE Band 4 Four Component Carrier Conducted Powers

Combination	PCC Band	PCC							SCC 1				SCC 2				SCC 3				Power		
		PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_4A-4A-12A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B4	5	1975	2112.5	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.60	24.70
CA_2A-4A-12A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.66	24.70
CA_2A-4A-4A-12A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B4	5	1975	2112.5	LTE B12	10	5095	737.5	24.67	24.70
CA_2A-4A-7A-7A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B7	20	3100	2655	LTE B7	20	2850	2630	24.70	24.70
CA_2A-4A-5A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.61	24.70
CA_2A-4A-7A-12A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	24.66	24.70
CA_2A-4A-29A-30A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	LTE B2	20	900	1960	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	24.57	24.70

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 50 of 99	

Table 9-48
LTE Band 2 Two Component Carrier Conducted Powers

Combination	PCC									SCC				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-2A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	24.59	24.70
CA_2A-4A (2)	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	24.66	24.70
CA_2A-5A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B5	10	2525	881.5	24.70	24.70
CA_2A-13A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B13	10	5230	751	24.62	24.70
CA_2A-66A (2)	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B66	20	66786	2145	24.68	24.70
CA_2A-12A (1)	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B12	10	5095	737.5	24.63	24.70
CA_2A-29A (2)	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B29	10	9715	722.5	24.69	24.70
CA_2A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B30	10	9820	2355	24.70	24.70
CA_2A-7A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B7	20	3100	2655	24.67	24.70
CA_2A-17A	LTE B2	5	19175	1907.5	QPSK	1	12	1175	1987.5	LTE B17	10	5790	740	24.66	24.69

Table 9-49
LTE Band 2 Three Component Carrier Conducted Powers

Combination	PCC									SCC 1				SCC 2				Power	
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-2A-5A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B5	10	2525	881.5	24.59	24.70
CA_2A-2A-13A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B13	10	5230	751	24.68	24.70
CA_2A-4A-5A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B5	10	2525	881.5	24.67	24.70
CA_2A-4A-13A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B13	10	5230	751	24.60	24.70
CA_2A-5A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B5	10	2525	881.5	LTE B66	20	66786	2145	24.65	24.70
CA_2A-13A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B13	10	5230	751	LTE B66	20	66786	2145	24.66	24.70
CA_2A-66A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B66	5	66786	2145	LTE B66	5	67311	2197.5	24.69	24.70
CA_2A-66B	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B66	10	66786	2145	LTE B66	10	66885	2154.9	24.68	24.70
CA_2A-66C	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B66	20	66786	2145	LTE B66	20	66984	2164.8	24.69	24.70
CA_2A-2A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B66	20	66786	2145	24.51	24.70
CA_2A-2A-12A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B12	10	5095	737.5	24.68	24.70
CA_2A-4A-12A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	24.66	24.70
CA_2A-12B	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B12	5	5155	743.5	LTE B12	5	5107	738.7	24.70	24.70
CA_2A-12A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B12	10	5095	737.5	LTE B66	20	66786	2145	24.68	24.70
CA_2A-2A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B30	10	9820	2355	24.59	24.70
CA_2A-4A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B30	10	9820	2355	24.62	24.70
CA_2A-5A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.65	24.70
CA_2A-12A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.68	24.70
CA_2A-29A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	24.70	24.70
CA_2A-30A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B30	10	9820	2355	LTE B66	20	66786	2145	24.62	24.70
CA_2A-4A-29A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B29	10	9715	722.5	24.68	24.70
CA_2A-4A-7A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	24.56	24.70
CA_2A-7A-7A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B7	20	3100	2655	LTE B7	5	2775	2622.5	24.55	24.70
CA_2A-7A-12A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	24.70	24.70

Table 9-50
LTE Band 2 Four Component Carrier Conducted Powers

Combination	PCC									SCC 1				SCC 2				SCC 3				Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-2A-5A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.60	24.70
CA_2A-2A-12A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.66	24.70
CA_2A-5A-30A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	LTE B66	20	66786	2145	24.58	24.70
CA_2A-12A-30A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	LTE B66	20	66786	2145	24.69	24.70
CA_2A-12A-66A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B12	10	5095	737.5	LTE B66	5	66786	2145	LTE B66	5	67311	2197.5	24.50	24.70
CA_2A-5A-66A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B5	10	6535	881.5	LTE B66	5	66786	2145	LTE B66	5	67311	2197.5	24.63	24.70
CA_2A-2A-5A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B5	10	9716	881.5	LTE B66	20	66786	2145	24.65	24.70
CA_2A-4A-12A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	LTE B30	10	9820	2355	24.60	24.70
CA_2A-4A-4A-12A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B4	10	2025	2117.5	LTE B12	10	5095	737.5	24.67	24.70
CA_2A-4A-29A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B29	10	9715	722.5	LTE B30	10	9820	2355	24.66	24.70
CA_2A-4A-7A-12A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	LTE B12	10	5095	737.5	24.64	24.70
CA_2A-4A-5A-30A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B5	10	2525	881.5	LTE B30	10	9820	2355	24.68	24.70
CA_2A-4A-7A-7A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B4	20	2175	2132.5	LTE B7	20	3100	2655	LTE B7	20	2850	2630	24.70	24.70
CA_2A-2A-12A-66A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	LTE B2	5	625	1932.5	LTE B12	10	5095	737.5	LTE B66	20	66786	2145	24.62	24.70

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 51 of 99	

Table 9-51
LTE Band 30 Two Component Carrier Conducted Powers

	PCC									SCC				Power	
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	25.10	25.20
CA_4A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B4	20	2175	2132.5	25.13	25.20
CA_29A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B29	10	9715	722.5	25.16	25.20
CA_5A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B5	10	2525	881.5	25.20	25.20
CA_12A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B12	10	5095	737.5	25.14	25.20
CA_30A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B66	20	66786	2145	25.13	25.20

Table 9-52
LTE Band 30 Three Component Carrier Conducted Powers

Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	PCC					SCC 1				SCC 2				Power	
					Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 29A-30A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B29	10	9715	722.5	LTE B66	20	66786	2145	25.19	25.20
CA 4A-4A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B4	5	2175	2132.5	LTE B4	5	2375	2152.5	25.13	25.20
CA 5A-30A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B5	10	2525	881.5	LTE B66	20	66786	2145	25.16	25.20
CA 2A-2A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	5	900	1960	LTE B2	5	625	1932.5	25.16	25.20
CA 2A-29A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B29	10	9715	722.5	25.16	25.20
CA 2A-30A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B66	20	66786	2145	25.18	25.20
CA 2A-4A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	25.16	25.20
CA 2A-5A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B5	10	2525	881.5	25.13	25.20
CA 2A-12A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B12	10	5095	737.5	25.18	25.20
CA 30A-66A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B66	5	66786	2145	LTE B66	5	67311	2197.5	25.20	25.20
CA 4A-29A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B4	20	2175	2132.5	LTE B29	10	9715	722.5	25.18	25.20
CA 12A-30A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B12	10	5095	737.5	LTE B66	20	66786	2145	25.20	25.20
CA 4A-5A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B4	20	2175	2132.5	LTE B5	10	2525	881.5	25.11	25.20
CA 4A-12A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	25.20	25.20

Table 9-53
LTE Band 30 Four Component Carrier Conducted Powers

Combination	PCC Band	PCC								SCC 1				SCC 2				SCC 3				Power	
		PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL#	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 4A-4A-12A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B4	5	2175	2132.5	LTE B4	5	2025	2117.5	LTE B12	10	5095	737.5	25.18	25.20
CA 2A-5A-30A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B5	10	2525	881.5	LTE B66	20	66786	2145	25.18	25.20
CA 12A-30A-66A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B12	10	5095	737.5	LTE B66	5	66786	2145	LTE B66	5	66461	2112.5	25.13	25.20
CA 2A-2A-5A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	5	900	1960	LTE B2	5	625	1932.5	LTE B5	10	2525	881.5	25.17	25.20
CA 2A-2A-12A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	5	900	1960	LTE B2	5	625	1932.5	LTE B12	10	5095	737.5	25.06	25.20
CA 2A-12A-30A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	5	900	1960	LTE B12	10	5095	737.5	LTE B66	20	66786	2145	25.09	25.20
CA 2A-4A-5A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B5	10	2525	881.5	25.20	25.20
CA 2A-4A-29A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B29	10	9715	722.5	25.19	25.20
CA 2A-4A-12A-30A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	25.11	25.20
CA 5A-30A-66A-66A	LTE B30	10	27710	2310	QPSK	1	0	9820	2355	LTE B5	10	6535	881.5	LTE B66	5	66786	2145	LTE B66	5	66461	2112.5	25.14	25.20

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 52 of 99

Table 9-54
LTE Band 7 Two Component Carrier Conducted Powers

	PCC									SCC				Power	
Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_4A-7A (1)	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B4	20	2175	2132.5	23.70	23.70
CA_2A-7A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B2	20	900	1960	23.66	23.70
CA_7A-7A (1)	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B7	5	2775	2622.5	23.65	23.70
CA_7B	LTE B7	15	20825	2507.5	QPSK	1	0	2825	2627.5	LTE B7	5	2924	2637.4	23.68	23.62
CA_7C (1)	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B7	20	2902	2635.2	23.70	23.70
CA_7A-12A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B12	10	5095	737.5	23.65	23.70

Table 9-55
LTE Band 7 Three Component Carrier Maximum Conducted Powers

Combination	PCC								SCC 1				SCC 2				Power		
	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_4A-4A-7A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B4	20	2175	2132.5	LTE B4	10	2025	2117.5	23.70	23.70
CA_2A-7A-12A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B2	20	900	1960	LTE B12	10	5095	737.5	23.70	23.70
CA_2A-7A-7A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B2	20	900	1960	LTE B7	5	2775	2622.5	23.70	23.70
CA_2A-4A-7A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	23.60	23.70
CA_4A-7A-12A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	23.61	23.70
CA_4A-7A-7A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B4	20	2175	2132.5	LTE B7	5	2775	2622.5	23.64	23.70

Table 9-56
LTE Band 7 Four Component Carrier Conducted Powers

Combination	PCC									SCC1				SCC 2				SCC 3				Power	
	PCC Band	PCC BW [MHz]	PCC (UL) Channel	PCC (UL) Freq. [MHz]	Modulation	PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	SCC Band	SCC BW [MHz]	SCC (DL) Channel	SCC (DL) Freq. [MHz]	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA 2A-4A-7A-12A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B12	10	5095	737.5	23.59	23.70
CA 2A-4A-7A-7A	LTE B7	20	21100	2535	QPSK	1	0	3100	2655	LTE B2	20	900	1960	LTE B4	20	2175	2132.5	LTE B7	5	2775	2622.5	23.70	23.70

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 53 of 99

Table 9-57
Three Component Carrier 2x2 MIMO Conducted Powers

Combination	PCC Band	PCC Bandwidth [MHz]	PCC (UL) Channel	PCC (UL) Frequency [MHz]	Modulation	PCC					SCC 1					SCC 2					Power	
						PCC UL# RB	PCC UL RB Offset	PCC (DL) Channel	PCC (DL) Frequency [MHz]	DL Antenna Configuration	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	DL Antenna Configuration	SCC Band	SCC Bandwidth [MHz]	SCC (DL) Channel	SCC (DL) Frequency [MHz]	DL Antenna Configuration	LTE Tx.Power with DL CA Enabled (dBm)	LTE Single Carrier Tx Power (dBm)
CA_2A-4A-4A	LTE B2	20	19100	1900	QPSK	1	0	1100	1980	2x2 MIMO	LTE B4	20	2175	2132.5	2x2 MIMO	LTE B4	5	2375	2152.5	2x2 MIMO	24.65	24.70
CA_2A-4A-4A	LTE B4	20	20300	1745	QPSK	1	0	2300	2145	2x2 MIMO	LTE B2	20	900	1960	2x2 MIMO	LTE B4	5	1975	2112.5	2x2 MIMO	24.49	24.70

Notes:

1. The device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.
2. All control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
3. For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.
4. All control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
5. Per FCC guidance, LTE Band 66 standalone powers were used to select measurement configurations for LTE Band 4, LTE Band 25 standalone powers were used to select measurement configurations for LTE Band 2, and LTE Band 12 standalone powers were used to select measurement configurations for LTE Band 17.
6. For downlink carrier aggregation combinations, PCC uplink channel was selected based on section C)3)b)ii) of KBD 941225 D05 V01r02. The downlink PCC channel was paired with the selected PCC uplink channel according to normal configurations without carrier aggregation. For inter-band CA, the SCC downlink channels were selected near the middle of their transmission bands. For contiguous intra-band CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing defined in section 5.4.1A of 3GPP TS 36.521. For non-contiguous intra-band CA, the downlink channel spacing between the component carriers was set to be larger than the nominal channel spacing and provided maximum separation between the component carriers. All selected downlink channels remained fully within the downlink transmission band of the respective component carrier.




Figure 9-4
Power Measurement Setup

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 54 of 99	

9.5 WLAN Conducted Powers

Table 9-58
2.4 GHz WLAN Ant 1 Maximum Average RF Power
2.4GHz Conducted Power [dBm]

Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11b	802.11g
2412	1	19.70	N/A
2422	3	N/A	18.20
2437	6	19.93	18.27
2452	9	N/A	18.34
2462	11	19.67	N/A

Table 9-59
2.4 GHz WLAN Ant 2 Maximum Average RF Power
2.4GHz Conducted Power [dBm]

Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11b	802.11g
2412	1	19.26	N/A
2422	3	N/A	17.70
2437	6	19.10	17.58
2452	9	N/A	17.58
2462	11	18.32	N/A

Table 9-60
2.4 GHz WLAN Ant 1 Reduced Average RF Power
2.4GHz Conducted Power [dBm]

Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11b	802.11g
2412	1	16.98	16.89
2437	6	16.90	16.91
2452	9	N/A	16.95
2462	11	16.98	N/A

Table 9-61
2.4 GHz WLAN Ant 2 Reduced Average RF Power
2.4GHz Conducted Power [dBm]

Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11b	802.11g
2412	1	16.22	16.27
2437	6	16.28	16.15
2452	9	N/A	16.07
2462	11	15.34	N/A

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 55 of 99

Table 9-62
5 GHz WLAN Ant 1 Maximum Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	16.76	16.54	16.55
5200	40	16.72	16.51	16.51
5220	44	16.68	16.50	16.54
5240	48	16.61	16.40	16.38
5260	52	16.57	16.39	16.38
5280	56	16.52	16.50	16.58
5300	60	16.54	16.35	16.39
5320	64	16.66	16.45	16.42
5500	100	16.66	16.50	16.49
5580	116	16.81	16.61	16.60
5660	132	16.68	16.47	16.49
5720	144	16.73	16.51	16.55
5745	149	16.76	16.57	16.51
5785	157	16.75	16.56	16.58
5825	165	16.80	16.60	16.60

Table 9-63
5 GHz WLAN Ant 2 Maximum Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11a	802.11n	802.11ac
5180	36	16.40	16.18	16.18
5200	40	16.46	16.23	16.19
5220	44	16.48	16.31	16.24
5240	48	16.49	16.26	16.29
5260	52	16.48	16.31	16.27
5280	56	16.48	16.24	16.25
5300	60	16.45	16.24	16.25
5320	64	16.49	16.30	16.27
5500	100	16.38	16.20	16.17
5580	116	16.49	16.28	16.23
5660	132	16.44	16.31	16.25
5720	144	16.47	16.23	16.24
5745	149	16.45	16.30	16.28
5785	157	16.47	16.30	16.28
5825	165	16.34	16.39	16.41

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 56 of 99

Table 9-64
5 GHz WLAN MIMO 802.11n Maximum Average RF Power

5GHz (20MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	ANT1	ANT2	MIMO
5180	36	16.54	16.18	19.37
5200	40	16.51	16.23	19.38
5220	44	16.50	16.31	19.42
5240	48	16.40	16.26	19.34
5260	52	16.39	16.31	19.36
5280	56	16.50	16.24	19.38
5300	60	16.35	16.24	19.31
5320	64	16.45	16.30	19.39
5500	100	16.50	16.20	19.36
5580	116	16.61	16.28	19.46
5660	132	16.47	16.31	19.40
5720	144	16.51	16.23	19.38
5745	149	16.57	16.30	19.45
5785	157	16.56	16.30	19.44
5825	165	16.89	16.39	19.66

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The bolded data rate and channel above were tested for SAR.




Figure 9-5
Power Measurement Setup for Bandwidths < 50 MHz

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 57 of 99	

9.6 Bluetooth Conducted Powers

Table 9-65
Bluetooth Average RF Power

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
			[dBm]	[mW]
2402	1.0	0	10.41	10.986
2441	1.0	39	11.59	14.426
2480	1.0	78	10.68	11.686
2402	2.0	0	9.68	9.283
2441	2.0	39	10.91	12.320
2480	2.0	78	9.98	9.950
2402	3.0	0	9.73	9.388
2441	3.0	39	10.95	12.440
2480	3.0	78	10.03	10.059

Note: The bolded data rates and channel above were tested for SAR.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 58 of 99




Figure 9-6
Bluetooth Transmission Plot

Equation 2
Bluetooth Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.895\text{ms}}{3.750\text{ms}} * 100\% = 77.2\%$$




Figure 9-7
Power Measurement Setup

FCC ID: ZNFV30A	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	
			Page 59 of 99

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Head Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
06/08/2017	750H	22.1	700	0.852	42.391	0.889	42.201	-4.16%	0.45%
			710	0.861	42.163	0.890	42.149	-3.26%	0.03%
			740	0.891	41.665	0.893	41.994	-0.22%	-0.78%
			755	0.899	41.478	0.894	41.916	0.56%	-1.04%
			770	0.916	41.391	0.895	41.838	2.35%	-1.07%
06/17/2017	835H	20.0	785	0.929	41.191	0.896	41.760	3.68%	-1.36%
			820	0.887	40.827	0.899	41.578	-1.33%	-1.81%
			835	0.902	40.636	0.900	41.500	0.22%	-2.08%
06/23/2017	1750H	24.0	850	0.916	40.430	0.916	41.500	0.00%	-2.58%
			1710	1.295	39.994	1.348	40.142	-3.93%	-0.37%
			1750	1.333	39.844	1.371	40.079	-2.77%	-0.59%
06/12/2017	1900H	22.0	1790	1.374	39.648	1.394	40.016	-1.43%	-0.92%
			1850	1.398	39.162	1.400	40.000	-0.14%	-2.10%
			1880	1.431	39.060	1.400	40.000	2.21%	-2.35%
06/26/2017	1900H	21.5	1910	1.462	38.950	1.400	40.000	4.43%	-2.62%
			1850	1.379	40.337	1.400	40.000	-1.50%	0.84%
			1880	1.412	40.196	1.400	40.000	0.86%	0.49%
06/07/2017	2300H	21.2	1910	1.444	40.082	1.400	40.000	3.14%	0.21%
			2300	1.706	38.519	1.670	39.500	2.16%	-2.48%
			2310	1.720	38.527	1.679	39.480	2.44%	-2.41%
06/12/2017	2450H-2600H	24.3	2320	1.725	38.417	1.687	39.460	2.25%	-2.64%
			2400	1.806	38.465	1.756	39.289	2.85%	-2.10%
			2450	1.867	38.251	1.800	39.200	3.72%	-2.42%
			2500	1.921	38.063	1.855	39.136	3.56%	-2.74%
			2550	1.985	37.838	1.909	39.073	3.98%	-3.16%
06/19/2017	2450H	24.0	2600	2.040	37.640	1.964	39.009	3.87%	-3.51%
			2400	1.750	38.524	1.756	39.289	-0.34%	-1.95%
			2450	1.803	38.360	1.800	39.200	0.17%	-2.14%
07/07/2017	2450H	22.3	2500	1.858	38.152	1.855	39.136	0.16%	-2.51%
			2400	1.794	38.361	1.756	39.289	2.16%	-2.36%
			2450	1.845	38.165	1.800	39.200	2.50%	-2.64%
			2500	1.903	37.948	1.855	39.136	2.59%	-3.04%
06/17/2017	5200H-5800H	20.2	2550	1.958	37.775	1.909	39.073	2.57%	-3.32%
			5240	4.554	35.313	4.696	35.940	-3.02%	-1.74%
			5260	4.586	35.255	4.717	35.917	-2.78%	-1.84%
			5320	4.625	35.103	4.778	35.849	-3.20%	-2.08%
			5580	4.877	34.764	5.045	35.551	-3.33%	-2.21%
			5600	4.920	34.774	5.065	35.529	-2.86%	-2.13%
			5745	5.095	34.605	5.214	35.363	-2.28%	-2.14%
			5765	5.112	34.529	5.234	35.340	-2.33%	-2.29%
			5785	5.137	34.568	5.255	35.317	-2.25%	-2.12%
			5825	5.139	34.449	5.296	35.271	-2.96%	-2.33%

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 60 of 99

Table 10-2
Measured Body Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
06/14/2017	750B	22.8	700	0.914	56.901	0.959	55.726	-4.69%	2.11%
			710	0.924	56.757	0.960	55.687	-3.75%	1.92%
			740	0.954	56.473	0.963	55.570	-0.93%	1.62%
			755	0.968	56.371	0.964	55.512	0.41%	1.55%
			770	0.982	56.269	0.965	55.453	1.76%	1.47%
			785	0.997	56.054	0.966	55.395	3.21%	1.19%
06/12/2017	835B	22.7	820	0.949	52.847	0.969	55.258	-2.06%	-4.36%
			835	0.964	52.729	0.970	55.200	-0.62%	-4.48%
			850	0.980	52.597	0.988	55.154	-0.81%	-4.64%
06/14/2017	835B	22.2	820	0.947	52.831	0.969	55.258	-2.27%	-4.39%
			835	0.962	52.689	0.970	55.200	-0.82%	-4.55%
			850	0.977	52.510	0.988	55.154	-1.11%	-4.79%
06/22/2017	835B	24.5	820	0.987	52.978	0.969	55.258	1.86%	-4.13%
			835	1.001	52.828	0.970	55.200	3.20%	-4.30%
			850	1.013	52.734	0.988	55.154	2.53%	-4.39%
06/11/2017	1750B	22.4	1710	1.421	53.115	1.463	53.537	-2.87%	-0.79%
			1750	1.461	52.944	1.488	53.432	-1.81%	-0.91%
			1790	1.500	52.802	1.514	53.326	-0.92%	-0.98%
06/19/2017	1750B	22.0	1710	1.399	52.672	1.463	53.537	-4.37%	-1.62%
			1750	1.440	52.565	1.488	53.432	-3.23%	-1.62%
			1790	1.481	52.384	1.514	53.326	-2.18%	-1.77%
06/15/2017	1900B	21.3	1850	1.495	52.403	1.520	53.300	-1.64%	-1.68%
			1880	1.526	52.252	1.520	53.300	0.39%	-1.97%
			1910	1.565	52.179	1.520	53.300	2.96%	-2.10%
06/20/2017	1900B	21.3	1850	1.513	51.297	1.520	53.300	-0.46%	-3.76%
			1880	1.545	51.183	1.520	53.300	1.64%	-3.97%
			1910	1.582	51.123	1.520	53.300	4.08%	-4.08%
06/24/2017	1900B	23.7	1850	1.452	52.539	1.520	53.300	-4.47%	-1.43%
			1880	1.486	52.433	1.520	53.300	-2.24%	-1.63%
			1910	1.521	52.318	1.520	53.300	0.07%	-1.84%
06/21/2017	2300B-2600B	22.9	2300	1.749	52.222	1.809	52.900	-3.32%	-1.28%
			2310	1.770	52.153	1.816	52.887	-2.53%	-1.39%
			2320	1.773	52.111	1.826	52.873	-2.90%	-1.44%
			2400	1.890	51.858	1.902	52.767	-0.63%	-1.72%
			2450	1.954	51.639	1.950	52.700	0.21%	-2.01%
			2500	2.022	51.454	2.021	52.636	0.05%	-2.25%
			2550	2.089	51.265	2.092	52.573	-0.14%	-2.49%
			2600	2.150	51.054	2.163	52.509	-0.60%	-2.77%
06/27/2017	2450B	22.6	2400	1.921	52.129	1.902	52.767	1.00%	-1.21%
			2450	1.985	51.927	1.950	52.700	1.79%	-1.47%
			2500	2.056	51.724	2.021	52.636	1.73%	-1.73%
07/05/2017	2450B	23.6	2400	1.953	51.492	1.902	52.767	2.68%	-2.42%
			2450	2.016	51.287	1.950	52.700	3.38%	-2.68%
			2500	2.088	51.087	2.021	52.636	3.32%	-2.94%
			2550	2.160	50.920	2.092	52.573	3.25%	-3.14%

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 61 of 99

**Table 10-3
Measured Body Tissue Properties (Cont.)**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
06/12/2017	5200B-5800B	21.5	5180	5.403	48.060	5.276	49.041	2.41%	-2.00%
			5220	5.466	47.940	5.323	48.987	2.69%	-2.14%
			5240	5.487	47.929	5.346	48.960	2.64%	-2.11%
			5260	5.518	47.906	5.369	48.933	2.78%	-2.10%
			5320	5.587	47.818	5.439	48.851	2.72%	-2.11%
			5500	5.829	47.500	5.650	48.607	3.17%	-2.28%
			5580	5.937	47.378	5.743	48.499	3.38%	-2.31%
			5600	5.965	47.313	5.766	48.471	3.45%	-2.39%
			5660	6.045	47.266	5.837	48.390	3.56%	-2.32%
			5700	6.088	47.203	5.883	48.336	3.48%	-2.34%
			5745	6.179	47.093	5.936	48.275	4.09%	-2.45%
			5765	6.190	47.049	5.959	48.248	3.88%	-2.49%
			5785	6.224	47.062	5.982	48.220	4.05%	-2.40%
06/26/2017	5200B-5800B	21.2	5825	6.285	46.990	6.029	48.166	4.25%	-2.44%
			5240	5.383	47.508	5.346	48.960	0.69%	-2.97%
			5260	5.417	47.461	5.369	48.933	0.89%	-3.01%
			5320	5.475	47.378	5.439	48.851	0.66%	-3.02%
			5500	5.726	47.078	5.650	48.607	1.35%	-3.15%
			5580	5.823	46.904	5.743	48.499	1.39%	-3.29%
			5600	5.870	46.869	5.766	48.471	1.80%	-3.31%
			5660	5.945	46.814	5.837	48.390	1.85%	-3.26%
			5700	5.996	46.715	5.883	48.336	1.92%	-3.35%
			5745	6.065	46.647	5.936	48.275	2.17%	-3.37%
			5765	6.085	46.626	5.959	48.248	2.11%	-3.36%
			5785	6.111	46.596	5.982	48.220	2.16%	-3.37%
			5825	6.184	46.498	6.029	48.166	2.57%	-3.46%
07/17/2017	5200B-5800B	21.0	5180	5.361	47.846	5.276	49.041	1.61%	-2.44%
			5200	5.393	47.833	5.299	49.014	1.77%	-2.41%
			5220	5.432	47.797	5.323	48.987	2.05%	-2.43%
			5240	5.457	47.730	5.346	48.960	2.08%	-2.51%
			5260	5.477	47.704	5.369	48.933	2.01%	-2.51%
			5280	5.509	47.663	5.393	48.906	2.15%	-2.54%
			5300	5.520	47.603	5.416	48.879	1.92%	-2.61%
			5320	5.553	47.604	5.439	48.851	2.10%	-2.55%
			5500	5.803	47.304	5.650	48.607	2.71%	-2.68%
			5580	5.915	47.137	5.743	48.499	2.99%	-2.81%
			5600	5.955	47.069	5.766	48.471	3.28%	-2.89%
			5660	6.026	47.017	5.837	48.390	3.24%	-2.84%
			5700	6.088	46.880	5.883	48.336	3.48%	-3.01%
			5745	6.154	46.831	5.936	48.275	3.67%	-2.99%
			5765	6.161	46.860	5.959	48.248	3.39%	-2.88%
			5785	6.215	46.803	5.982	48.220	3.90%	-2.94%
			5825	6.266	46.692	6.029	48.166	3.93%	-3.06%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 62 of 99	

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-4
System Verification Results – 1g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
K	750	HEAD	06/08/2017	22.7	21.7	0.200	1003	7406	1.790	8.390	8.950	6.67%
I	835	HEAD	06/17/2017	19.9	20.0	0.200	4d133	3213	2.000	9.320	10.000	7.30%
J	1750	HEAD	06/23/2017	25.0	24.7	0.100	1092	3209	3.600	36.400	36.000	-1.10%
J	1900	HEAD	06/12/2017	19.2	22.0	0.100	5d080	3209	3.860	39.300	38.600	-1.78%
J	1900	HEAD	06/26/2017	21.3	21.2	0.100	5d080	3209	3.820	39.300	38.200	-2.80%
I	2300	HEAD	06/07/2017	19.3	21.2	0.100	1038	3213	4.730	47.500	47.300	-0.42%
K	2450	HEAD	06/12/2017	22.7	23.5	0.100	981	7406	5.350	52.800	53.500	1.33%
I	2450	HEAD	06/19/2017	23.0	23.0	0.100	797	3213	5.330	52.100	53.300	2.30%
I	2450	HEAD	07/07/2017	22.0	21.0	0.100	797	3213	5.400	52.100	54.000	3.65%
K	2600	HEAD	06/12/2017	22.7	23.5	0.100	1004	7406	5.790	57.600	57.900	0.52%
H	5250	HEAD	06/17/2017	20.1	20.2	0.050	1191	3914	3.720	78.900	74.400	-5.70%
H	5600	HEAD	06/17/2017	20.1	20.2	0.050	1191	3914	3.860	83.600	77.200	-7.66%
H	5750	HEAD	06/17/2017	20.1	20.2	0.050	1191	3914	3.660	79.100	73.200	-7.46%
J	750	BODY	06/14/2017	21.1	21.4	0.200	1003	3209	1.730	8.790	8.650	-1.59%
E	835	BODY	06/12/2017	23.9	22.5	0.200	4d133	3319	2.050	9.500	10.250	7.89%
E	835	BODY	06/14/2017	23.7	22.2	0.200	4d133	3319	1.960	9.500	9.800	3.16%
H	835	BODY	06/22/2017	24.8	24.5	0.200	4d133	3318	2.000	9.500	10.000	5.26%
E	1750	BODY	06/11/2017	23.0	22.5	0.100	1148	3319	3.730	37.000	37.300	0.81%
H	1750	BODY	06/19/2017	24.6	22.4	0.100	1148	3318	3.660	37.000	36.600	-1.08%
J	1900	BODY	06/15/2017	21.0	21.3	0.100	5d026	3209	4.000	40.300	40.000	-0.74%
E	1900	BODY	06/20/2017	23.3	21.3	0.100	5d149	3319	4.060	39.900	40.600	1.75%
H	1900	BODY	06/24/2017	21.7	23.7	0.100	5d080	3318	4.010	39.100	40.100	2.56%
G	2300	BODY	06/21/2017	24.6	23.5	0.100	1038	3287	5.040	47.500	50.400	6.11%
G	2450	BODY	06/21/2017	24.6	23.5	0.100	797	3287	5.250	50.700	52.500	3.55%
G	2450	BODY	06/27/2017	21.1	22.6	0.100	981	3287	5.430	50.800	54.300	6.89%
K	2450	BODY	07/05/2017	22.4	23.6	0.100	797	7406	5.410	50.700	54.100	6.71%
G	2600	BODY	06/21/2017	24.6	23.5	0.100	1126	3287	5.710	54.500	57.100	4.77%
D	5250	BODY	06/26/2017	22.1	20.4	0.050	1123	3589	3.720	75.900	74.400	-1.98%
D	5600	BODY	06/26/2017	22.1	20.4	0.050	1123	3589	4.050	78.900	81.000	2.66%
D	5750	BODY	06/26/2017	22.1	20.4	0.050	1123	3589	3.490	76.300	69.800	-8.52%
D	5250	BODY	07/17/2017	22.1	21.0	0.050	1123	3589	3.790	75.900	75.800	-0.13%
D	5600	BODY	07/17/2017	22.1	21.0	0.050	1123	3589	4.000	78.900	80.000	1.39%
D	5750	BODY	07/17/2017	22.1	21.0	0.050	1123	3589	3.640	76.300	72.800	-4.59%

FCC ID: ZNFV30A	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 63 of 99

Table 10-5
System Verification Results – 10g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR10g (W/kg)	1 W Target SAR10g (W/kg)	1 W Normalized SAR10g (W/kg)	Deviation10g (%)
D	5250	BODY	06/12/2017	22.1	21.3	0.050	1237	3589	1.060	21.000	21.200	0.95%
D	5600	BODY	06/12/2017	22.1	21.3	0.050	1237	3589	1.050	21.500	21.000	-2.33%
D	5750	BODY	06/12/2017	22.1	21.3	0.050	1237	3589	1.000	20.900	20.000	-4.31%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: ZNFV30A	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 64 of 99	

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	34.2	34.20	0.03	Right	Cheek	04981	1	1:8.3	0.066	1.000	0.066	
836.60	190	GSM 850	GSM	34.2	34.20	0.07	Right	Tilt	04981	1	1:8.3	0.045	1.000	0.045	
836.60	190	GSM 850	GSM	34.2	34.20	0.01	Left	Cheek	04981	1	1:8.3	0.103	1.000	0.103	A1
836.60	190	GSM 850	GSM	34.2	34.20	0.02	Left	Tilt	04981	1	1:8.3	0.042	1.000	0.042	
836.60	190	GSM 850	GPRS	34.2	34.16	0.01	Right	Cheek	04981	1	1:8.3	0.060	1.009	0.061	
836.60	190	GSM 850	GPRS	34.2	34.16	-0.04	Right	Tilt	04981	1	1:8.3	0.045	1.009	0.045	
836.60	190	GSM 850	GPRS	34.2	34.16	0.16	Left	Cheek	04981	1	1:8.3	0.102	1.009	0.103	
836.60	190	GSM 850	GPRS	34.2	34.16	0.08	Left	Tilt	04981	1	1:8.3	0.037	1.009	0.037	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-2
GSM 1900 Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	# of Time Slots	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	31.7	31.67	-0.06	Right	Cheek	04981	1	1:8.3	0.083	1.007	0.084	
1880.00	661	GSM 1900	GSM	31.7	31.67	-0.03	Right	Tilt	04981	1	1:8.3	0.028	1.007	0.028	
1880.00	661	GSM 1900	GSM	31.7	31.67	0.05	Left	Cheek	04981	1	1:8.3	0.107	1.007	0.108	
1880.00	661	GSM 1900	GSM	31.7	31.67	0.15	Left	Tilt	04981	1	1:8.3	0.041	1.007	0.041	
1880.00	661	GSM 1900	GPRS	25.5	25.50	-0.11	Right	Cheek	04981	4	1:2.076	0.106	1.000	0.106	
1880.00	661	GSM 1900	GPRS	25.5	25.50	0.07	Right	Tilt	04981	4	1:2.076	0.043	1.000	0.043	
1880.00	661	GSM 1900	GPRS	25.5	25.50	-0.12	Left	Cheek	04981	4	1:2.076	0.149	1.000	0.149	A2
1880.00	661	GSM 1900	GPRS	25.5	25.50	0.06	Left	Tilt	04981	4	1:2.076	0.060	1.000	0.060	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 65 of 99

Table 11-3
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	25.5	25.37	0.14	Right	Cheek	04999	1:1	0.072	1.030	0.074	
836.60	4183	UMTS 850	RMC	25.5	25.37	0.09	Right	Tilt	04999	1:1	0.045	1.030	0.046	
836.60	4183	UMTS 850	RMC	25.5	25.37	0.01	Left	Cheek	04999	1:1	0.110	1.030	0.113	A3
836.60	4183	UMTS 850	RMC	25.5	25.37	0.05	Left	Tilt	04999	1:1	0.046	1.030	0.047	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-4
UMTS 1750 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1732.40	1412	UMTS 1750	RMC	24.7	24.66	0.03	Right	Cheek	04999	1:1	0.128	1.009	0.129	
1732.40	1412	UMTS 1750	RMC	24.7	24.66	0.08	Right	Tilt	04999	1:1	0.106	1.009	0.107	
1732.40	1412	UMTS 1750	RMC	24.7	24.66	0.04	Left	Cheek	04999	1:1	0.168	1.009	0.170	A4
1732.40	1412	UMTS 1750	RMC	24.7	24.66	0.00	Left	Tilt	04999	1:1	0.111	1.009	0.112	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-5
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	24.7	24.45	0.14	Right	Cheek	04999	1:1	0.152	1.059	0.161	
1880.00	9400	UMTS 1900	RMC	24.7	24.45	-0.02	Right	Tilt	04999	1:1	0.093	1.059	0.098	
1880.00	9400	UMTS 1900	RMC	24.7	24.45	0.07	Left	Cheek	04999	1:1	0.218	1.059	0.231	A5
1880.00	9400	UMTS 1900	RMC	24.7	24.45	-0.04	Left	Tilt	04999	1:1	0.098	1.059	0.104	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 66 of 99

**Table 11-6
Cell. CDMA Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.52	384	Cell. CDMA	RC3 / SO55	25.5	25.47	-0.08	Right	Cheek	04999	1:1	0.070	1.007	0.070	
836.52	384	Cell. CDMA	RC3 / SO55	25.5	25.47	0.14	Right	Tilt	04999	1:1	0.047	1.007	0.047	
836.52	384	Cell. CDMA	RC3 / SO55	25.5	25.47	-0.01	Left	Cheek	04999	1:1	0.111	1.007	0.112	A6
836.52	384	Cell. CDMA	RC3 / SO55	25.5	25.47	0.06	Left	Tilt	04999	1:1	0.046	1.007	0.046	
836.52	384	Cell. CDMA	EVDO Rev. A	25.5	25.46	0.06	Right	Cheek	04999	1:1	0.071	1.009	0.072	
836.52	384	Cell. CDMA	EVDO Rev. A	25.5	25.46	0.06	Right	Tilt	04999	1:1	0.047	1.009	0.047	
836.52	384	Cell. CDMA	EVDO Rev. A	25.5	25.46	0.03	Left	Cheek	04999	1:1	0.110	1.009	0.111	
836.52	384	Cell. CDMA	EVDO Rev. A	25.5	25.46	0.01	Left	Tilt	04999	1:1	0.047	1.009	0.047	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-7
PCS CDMA Head SAR**

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.62	0.14	Right	Cheek	04999	1:1	0.092	1.019	0.094	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.62	0.18	Right	Tilt	04999	1:1	0.044	1.019	0.045	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.62	0.07	Left	Cheek	04999	1:1	0.116	1.019	0.118	
1880.00	600	PCS CDMA	RC3 / SO55	24.7	24.62	0.13	Left	Tilt	04999	1:1	0.056	1.019	0.057	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.46	0.02	Right	Cheek	04999	1:1	0.104	1.057	0.110	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.46	0.06	Right	Tilt	04999	1:1	0.046	1.057	0.049	
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.46	0.07	Left	Cheek	04999	1:1	0.125	1.057	0.132	A7
1880.00	600	PCS CDMA	EVDO Rev. A	24.7	24.46	0.14	Left	Tilt	04999	1:1	0.055	1.057	0.058	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

**Table 11-8
LTE Band 12 Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.14	0	Right	Cheek	QPSK	1	25	05012	1:1	0.076	1.000	0.076	
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	0.01	1	Right	Cheek	QPSK	25	25	05012	1:1	0.061	1.107	0.068	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.21	0	Right	Tilt	QPSK	1	25	05012	1:1	0.043	1.000	0.043	
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	0.01	1	Right	Tilt	QPSK	25	25	05012	1:1	0.032	1.107	0.035	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	-0.03	0	Left	Cheek	QPSK	1	25	05012	1:1	0.091	1.000	0.091	A8
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	0.07	1	Left	Cheek	QPSK	25	25	05012	1:1	0.075	1.107	0.083	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.13	0	Left	Tilt	QPSK	1	25	05012	1:1	0.041	1.000	0.041	
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	0.10	1	Left	Tilt	QPSK	25	25	05012	1:1	0.034	1.107	0.038	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 67 of 99

Table 11-9
LTE Band 13 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY			Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.	(W/kg)														(W/kg)			
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	0.02	0	Right	Cheek	QPSK	1	25	05012	1:1	0.078	1.000	0.078	
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	0.07	1	Right	Cheek	QPSK	25	0	05012	1:1	0.064	1.042	0.067	
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	0.14	0	Right	Tilt	QPSK	1	25	05012	1:1	0.049	1.000	0.049	
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	0.14	1	Right	Tilt	QPSK	25	0	05012	1:1	0.042	1.042	0.044	
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	-0.01	0	Left	Cheek	QPSK	1	25	05012	1:1	0.109	1.000	0.109	A9
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	0.01	1	Left	Cheek	QPSK	25	0	05012	1:1	0.087	1.042	0.091	
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	-0.07	0	Left	Tilt	QPSK	1	25	05012	1:1	0.053	1.000	0.053	
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	0.18	1	Left	Tilt	QPSK	25	0	05012	1:1	0.041	1.042	0.043	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-10
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	0.05	0	Right	Cheek	QPSK	1	0	05038	1:1	0.060	1.000	0.060	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	0.09	1	Right	Cheek	QPSK	25	12	05038	1:1	0.056	1.009	0.057	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	0.13	0	Right	Tilt	QPSK	1	0	05038	1:1	0.045	1.000	0.045	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	0.05	1	Right	Tilt	QPSK	25	12	05038	1:1	0.038	1.009	0.038	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	-0.18	0	Left	Cheek	QPSK	1	0	05038	1:1	0.093	1.000	0.093	A10
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	0.03	1	Left	Cheek	QPSK	25	12	05038	1:1	0.084	1.009	0.085	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	0.07	0	Left	Tilt	QPSK	1	0	05038	1:1	0.040	1.000	0.040	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	0.03	1	Left	Tilt	QPSK	25	12	05038	1:1	0.033	1.009	0.033	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-11
LTE Band 66 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	0.09	0	Right	Cheek	QPSK	1	0	05004	1:1	0.120	1.000	0.120	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	0.07	1	Right	Cheek	QPSK	50	25	05004	1:1	0.098	1.023	0.100	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	-0.13	0	Right	Tilt	QPSK	1	0	05004	1:1	0.137	1.000	0.137	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	0.03	1	Right	Tilt	QPSK	50	25	05004	1:1	0.096	1.023	0.098	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	0.03	0	Left	Cheek	QPSK	1	0	05004	1:1	0.154	1.000	0.154	A11
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	0.05	1	Left	Cheek	QPSK	50	25	05004	1:1	0.111	1.023	0.114	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	0.00	0	Left	Tilt	QPSK	1	0	05004	1:1	0.120	1.000	0.120	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	0.05	1	Left	Tilt	QPSK	50	25	05004	1:1	0.089	1.023	0.091	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 68 of 99

Table 11-12
LTE Band 25 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	0.18	0	Right	Cheek	QPSK	1	0	05004	1:1	0.113	1.000	0.113	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	0.02	1	Right	Cheek	QPSK	50	25	05004	1:1	0.100	1.007	0.101	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	0.17	0	Right	Tilt	QPSK	1	0	05004	1:1	0.056	1.000	0.056	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	0.00	1	Right	Tilt	QPSK	50	25	05004	1:1	0.039	1.007	0.039	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	-0.04	0	Left	Cheek	QPSK	1	0	05004	1:1	0.136	1.000	0.136	A12
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	0.07	1	Left	Cheek	QPSK	50	25	05004	1:1	0.105	1.007	0.106	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	0.07	0	Left	Tilt	QPSK	1	0	05004	1:1	0.072	1.000	0.072	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	0.10	1	Left	Tilt	QPSK	50	25	05004	1:1	0.057	1.007	0.057	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-13
LTE Band 30 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.10	0	Right	Cheek	QPSK	1	0	05020	1:1	0.017	1.000	0.017	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.19	1	Right	Cheek	QPSK	25	0	05020	1:1	0.013	1.096	0.014	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.18	0	Right	Tilt	QPSK	1	0	05020	1:1	0.010	1.000	0.010	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.12	1	Right	Tilt	QPSK	25	0	05020	1:1	0.009	1.096	0.010	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.11	0	Left	Cheek	QPSK	1	0	05020	1:1	0.021	1.000	0.021	A13
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.15	1	Left	Cheek	QPSK	25	0	05020	1:1	0.015	1.096	0.016	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.14	0	Left	Tilt	QPSK	1	0	05020	1:1	0.014	1.000	0.014	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.19	1	Left	Tilt	QPSK	25	0	05020	1:1	0.011	1.096	0.012	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-14
LTE Band 7 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	0.21	0	Right	Cheek	QPSK	1	0	05004	1:1	0.013	1.000	0.013	A14
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	0.11	1	Right	Cheek	QPSK	50	0	05004	1:1	0.011	1.038	0.011	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	0.17	0	Right	Tilt	QPSK	1	0	05004	1:1	0.005	1.000	0.005	
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	0.06	1	Right	Tilt	QPSK	50	0	05004	1:1	0.004	1.038	0.004	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	0.17	0	Left	Cheek	QPSK	1	0	05004	1:1	0.011	1.000	0.011	
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	0.11	1	Left	Cheek	QPSK	50	0	05004	1:1	0.009	1.038	0.009	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	0.14	0	Left	Mouth-Jaw	QPSK	1	0	05004	1:1	0.004	1.000	0.004	
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	0.11	1	Left	Mouth-Jaw	QPSK	50	0	05004	1:1	0.002	1.038	0.002	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 69 of 99

Table 11-15
LTE Band 41 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	0.10	0	Right	Cheek	QPSK	1	0	05020	1:1.58	0.020	1.002	0.020	A15
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	0.16	1	Right	Cheek	QPSK	50	25	05020	1:1.58	0.017	1.007	0.017	
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	0.15	0	Right	Tilt	QPSK	1	0	05020	1:1.58	0.011	1.002	0.011	
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	0.10	1	Right	Tilt	QPSK	50	25	05020	1:1.58	0.010	1.007	0.010	
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	0.17	0	Left	Cheek	QPSK	1	0	05020	1:1.58	0.016	1.002	0.016	
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	0.17	1	Left	Cheek	QPSK	50	25	05020	1:1.58	0.015	1.007	0.015	
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	-0.14	0	Left	Tilt	QPSK	1	0	05020	1:1.58	0.006	1.002	0.006	
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	0.13	1	Left	Tilt	QPSK	50	25	05020	1:1.58	0.004	1.007	0.004	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-16
DTS Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2462	11	802.11b	DSSS	22	17.0	16.98	0.17	Right	Cheek	1	05145	1	99.0	0.760	0.417	1.005	1.010	0.423	
2462	11	802.11b	DSSS	22	17.0	16.98	0.17	Right	Tilt	1	05145	1	99.0	0.282	0.231	1.005	1.010	0.234	
2462	11	802.11b	DSSS	22	17.0	16.98	0.10	Left	Cheek	1	05145	1	99.0	0.119	-	1.005	1.010	-	
2462	11	802.11b	DSSS	22	17.0	16.98	0.14	Left	Tilt	1	05145	1	99.0	0.133	-	1.005	1.010	-	
2437	6	802.11b	DSSS	22	17.0	16.28	-0.01	Right	Cheek	2	05145	1	99.0	0.807	0.534	1.180	1.010	0.636	A16
2437	6	802.11b	DSSS	22	17.0	16.28	-0.06	Right	Tilt	2	05145	1	99.0	0.731	0.506	1.180	1.010	0.603	
2437	6	802.11b	DSSS	22	17.0	16.28	-0.17	Left	Cheek	2	05145	1	99.0	0.493	-	1.180	1.010	-	
2437	6	802.11b	DSSS	22	17.0	16.28	0.06	Left	Tilt	2	05145	1	99.0	0.536	-	1.180	1.010	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Head 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 70 of 99

**Table 11-17
NII Head SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5320	64	802.11a	OFDM	20	17.0	16.66	0.16	Right	Cheek	1	05160	6	94.3	0.383	-	1.081	1.060	-	
5320	64	802.11a	OFDM	20	17.0	16.66	0.11	Right	Tilt	1	05160	6	94.3	0.445	0.207	1.081	1.060	0.237	
5320	64	802.11a	OFDM	20	17.0	16.66	-0.13	Left	Cheek	1	05160	6	94.3	0.134	-	1.081	1.060	-	
5320	64	802.11a	OFDM	20	17.0	16.66	0.13	Left	Tilt	1	05160	6	94.3	0.165	-	1.081	1.060	-	
5320	64	802.11a	OFDM	20	16.5	16.49	0.18	Right	Cheek	2	05160	6	94.3	0.582	0.415	1.002	1.060	0.441	
5320	64	802.11a	OFDM	20	16.5	16.49	0.10	Right	Tilt	2	05160	6	94.3	0.574	0.448	1.002	1.060	0.476	
5320	64	802.11a	OFDM	20	16.5	16.49	0.17	Left	Cheek	2	05160	6	94.3	0.327	-	1.002	1.060	-	
5320	64	802.11a	OFDM	20	16.5	16.49	0.17	Left	Tilt	2	05160	6	94.3	0.368	-	1.002	1.060	-	
5580	116	802.11a	OFDM	20	17.0	16.81	0.19	Right	Cheek	1	05160	6	94.3	0.553	-	1.045	1.060	-	
5580	116	802.11a	OFDM	20	17.0	16.81	0.19	Right	Tilt	1	05160	6	94.3	0.602	0.270	1.045	1.060	0.299	
5580	116	802.11a	OFDM	20	17.0	16.81	0.19	Left	Cheek	1	05160	6	94.3	0.162	-	1.045	1.060	-	
5580	116	802.11a	OFDM	20	17.0	16.81	0.13	Left	Tilt	1	05160	6	94.3	0.198	-	1.045	1.060	-	
5580	116	802.11a	OFDM	20	16.5	16.49	0.13	Right	Cheek	2	05160	6	94.3	0.660	0.388	1.002	1.060	0.412	
5580	116	802.11a	OFDM	20	16.5	16.49	0.17	Right	Tilt	2	05160	6	94.3	0.571	0.384	1.002	1.060	0.408	
5580	116	802.11a	OFDM	20	16.5	16.49	0.16	Left	Cheek	2	05160	6	94.3	0.361	-	1.002	1.060	-	
5580	116	802.11a	OFDM	20	16.5	16.49	0.15	Left	Tilt	2	05160	6	94.3	0.343	-	1.002	1.060	-	
5825	165	802.11a	OFDM	20	17.0	16.80	0.16	Right	Cheek	1	05160	6	94.3	0.919	0.482	1.047	1.060	0.535	A17
5825	165	802.11a	OFDM	20	17.0	16.80	0.16	Right	Tilt	1	05160	6	94.3	0.623	0.275	1.047	1.060	0.305	
5825	165	802.11a	OFDM	20	17.0	16.80	0.15	Left	Cheek	1	05160	6	94.3	0.215	-	1.047	1.060	-	
5825	165	802.11a	OFDM	20	17.0	16.80	0.16	Left	Tilt	1	05160	6	94.3	0.223	-	1.047	1.060	-	
5785	157	802.11a	OFDM	20	16.5	16.47	0.21	Right	Cheek	2	05160	6	94.3	0.536	0.260	1.007	1.060	0.278	
5785	157	802.11a	OFDM	20	16.5	16.47	-0.16	Right	Tilt	2	05160	6	94.3	0.420	-	1.007	1.060	-	
5785	157	802.11a	OFDM	20	16.5	16.47	0.12	Left	Cheek	2	05160	6	94.3	0.216	-	1.007	1.060	-	
5785	157	802.11a	OFDM	20	16.5	16.47	-0.21	Left	Tilt	2	05160	6	94.3	0.244	-	1.007	1.060	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Head											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

**Table 11-18
Bluetooth Head SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441.00	39	Bluetooth	FHSS	12.5	11.59	-0.05	Right	Cheek	05145	1	77.2	0.137	1.233	1.295	0.219	A18
2441.00	39	Bluetooth	FHSS	12.5	11.59	0.05	Right	Tilt	05145	1	77.2	0.074	1.233	1.295	0.118	
2441.00	39	Bluetooth	FHSS	12.5	11.59	0.01	Left	Cheek	05145	1	77.2	0.038	1.233	1.295	0.061	
2441.00	39	Bluetooth	FHSS	12.5	11.59	0.02	Left	Tilt	05145	1	77.2	0.052	1.233	1.295	0.083	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 71 of 99

11.2 Standalone Body-Worn SAR Data

Table 11-19
GSM/UMTS/CDMA Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	34.2	34.20	-0.01	10 mm	05061	1	1:8.3	back	0.464	1.000	0.464	
836.60	190	GSM 850	GPRS	34.2	34.16	-0.05	10 mm	05061	1	1:8.3	back	0.481	1.009	0.485	A19
1880.00	661	GSM 1900	GSM	31.7	31.67	-0.07	10 mm	05061	1	1:8.3	back	0.502	1.007	0.506	
1880.00	661	GSM 1900	GPRS	25.5	25.50	0.15	10 mm	05061	4	1:2.076	back	0.558	1.000	0.558	A21
836.60	4183	UMTS 850	RMC	25.5	25.37	0.00	10 mm	04999	N/A	1:1	back	0.486	1.030	0.501	A23
1732.40	1412	UMTS 1750	RMC	24.7	24.66	0.07	10 mm	04981	N/A	1:1	back	0.772	1.009	0.779	A24
1880.00	9400	UMTS 1900	RMC	24.7	24.45	-0.04	10 mm	04999	N/A	1:1	back	0.610	1.059	0.646	A25
836.52	384	Cell. CDMA	TDSO / SO32	25.5	25.29	0.02	10 mm	04999	N/A	1:1	back	0.476	1.050	0.500	A27
1880.00	600	PCS CDMA	TDSO / SO32	24.7	24.45	0.00	10 mm	04999	N/A	1:1	back	0.558	1.059	0.591	A29
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-20
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.00	0	05004	QPSK	1	25	10 mm	back	1:1	0.441	1.000	0.441	A31
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	0.00	1	05004	QPSK	25	25	10 mm	back	1:1	0.353	1.107	0.391	
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	-0.09	0	05004	QPSK	1	25	10 mm	back	1:1	0.475	1.000	0.475	A32
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	-0.02	1	05004	QPSK	25	0	10 mm	back	1:1	0.375	1.042	0.391	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	0.03	0	05012	QPSK	1	0	10 mm	back	1:1	0.479	1.000	0.479	A34
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	0.06	1	05012	QPSK	25	12	10 mm	back	1:1	0.380	1.009	0.383	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	0.03	0	05012	QPSK	1	0	10 mm	back	1:1	0.720	1.000	0.720	A35
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	-0.09	1	05012	QPSK	50	25	10 mm	back	1:1	0.579	1.023	0.592	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	-0.04	0	05012	QPSK	1	0	10 mm	back	1:1	0.754	1.000	0.754	A36
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	0.01	1	05012	QPSK	50	25	10 mm	back	1:1	0.567	1.007	0.571	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.06	0	05020	QPSK	1	0	10 mm	back	1:1	0.842	1.000	0.842	A38
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.00	1	05020	QPSK	25	0	10 mm	back	1:1	0.687	1.096	0.753	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.77	0.00	1	05020	QPSK	50	0	10 mm	back	1:1	0.695	1.104	0.767	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.04	0	05020	QPSK	1	0	10 mm	back	1:1	0.798	1.000	0.798	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	-0.11	0	05038	QPSK	1	0	10 mm	back	1:1	0.314	1.000	0.314	A39
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	-0.10	1	05038	QPSK	50	0	10 mm	back	1:1	0.226	1.038	0.235	
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	-0.18	0	05012	QPSK	1	0	10 mm	back	1:1.58	0.441	1.002	0.442	A40
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	-0.09	1	05012	QPSK	50	25	10 mm	back	1:1.58	0.336	1.007	0.338	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

Note: Blue entry represents variability measurement.

FCC ID: ZNFV30A			SAR EVALUATION REPORT			Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 72 of 99		

**Table 11-21
DTS Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	20.0	19.93	-0.02	10 mm	1	05145	1	back	99.0	0.306	0.255	1.016	1.010	0.262	
2412	1	802.11b	DSSS	22	19.5	19.26	0.17	10 mm	2	05145	1	back	99.0	0.264	0.264	1.057	1.010	0.282	A41
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-22
NII Body-Worn SAR**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5320	64	802.11a	OFDM	20	17.0	16.66	0.08	10 mm	1	05160	6	back	94.3	0.764	0.306	1.081	1.060	0.351	
5320	64	802.11a	OFDM	20	16.5	16.49	0.07	10 mm	2	05160	6	back	94.3	0.685	0.336	1.002	1.060	0.357	
5580	116	802.11a	OFDM	20	17.0	16.81	0.08	10 mm	1	05160	6	back	94.3	1.061	0.500	1.045	1.060	0.554	
5580	116	802.11a	OFDM	20	16.5	16.49	0.08	10 mm	2	05160	6	back	94.3	0.827	0.386	1.002	1.060	0.410	
5825	165	802.11a	OFDM	20	17.0	16.80	0.07	10 mm	1	05160	6	back	94.3	1.532	0.579	1.047	1.060	0.643	
5785	157	802.11a	OFDM	20	16.5	16.47	-0.01	10 mm	2	05160	6	back	94.3	0.570	0.262	1.007	1.060	0.280	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

**Table 11-23
NII MIMO Body-Worn SAR**

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.				(Ant 1)	(Ant 1)	(Ant 2)	(Ant 2)								W/kg	(W/kg)			(W/kg)	
5320	64	802.11n	OFDM	20	17.0	16.45	16.5	16.30	0.09	10 mm	MIMO	05145	13	back	94.5	1.356	0.611	1.135	1.058	0.734	
5580	116	802.11n	OFDM	20	17.0	16.51	16.5	16.28	0.09	10 mm	MIMO	05145	13	back	94.5	1.631	0.729	1.094	1.058	0.844	A43
5660	132	802.11n	OFDM	20	17.0	16.47	16.5	16.31	0.13	10 mm	MIMO	05145	13	back	94.5	1.740	0.712	1.130	1.058	0.851	
5825	165	802.11n	OFDM	20	17.0	16.89	16.5	16.39	0.06	10 mm	MIMO	05145	13	back	94.5	1.673	0.693	1.026	1.058	0.752	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Body											
Spatial Peak										1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population										averaged over 1 gram											

**Table 11-24
Bluetooth Body-Worn SAR**

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441	39	Bluetooth	FHSS	12.5	11.59	0.03	10 mm	05145	1	back	77.2	0.034	1.233	1.295	0.054	A45
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 73 of 99

11.3 Standalone Hotspot SAR Data

Table 11-25
GPRS/UMTS/CDMA Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	34.2	34.16	-0.05	10 mm	05061	1	1:8.3	back	0.481	1.009	0.485	A20
836.60	190	GSM 850	GPRS	34.2	34.16	-0.06	10 mm	05061	1	1:8.3	front	0.499	1.009	0.503	
836.60	190	GSM 850	GPRS	34.2	34.16	-0.06	10 mm	05061	1	1:8.3	bottom	0.289	1.009	0.292	
836.60	190	GSM 850	GPRS	34.2	34.16	0.04	10 mm	05061	1	1:8.3	right	0.083	1.009	0.084	
836.60	190	GSM 850	GPRS	34.2	34.16	0.08	10 mm	05061	1	1:8.3	left	0.183	1.009	0.185	
1880.00	661	GSM 1900	GPRS	25.5	25.50	0.15	10 mm	05061	4	1:2.076	back	0.558	1.000	0.558	
1880.00	661	GSM 1900	GPRS	25.5	25.50	-0.02	10 mm	05061	4	1:2.076	front	0.437	1.000	0.437	
1880.00	661	GSM 1900	GPRS	25.5	25.50	0.03	10 mm	05061	4	1:2.076	bottom	0.701	1.000	0.701	A22
1880.00	661	GSM 1900	GPRS	25.5	25.50	0.19	10 mm	05061	4	1:2.076	left	0.240	1.000	0.240	
836.60	4183	UMTS 850	RMC	25.5	25.37	0.00	10 mm	04999	N/A	1:1	back	0.486	1.030	0.501	
836.60	4183	UMTS 850	RMC	25.5	25.37	0.00	10 mm	04999	N/A	1:1	front	0.456	1.030	0.470	
836.60	4183	UMTS 850	RMC	25.5	25.37	-0.05	10 mm	04999	N/A	1:1	bottom	0.248	1.030	0.255	
836.60	4183	UMTS 850	RMC	25.5	25.37	0.00	10 mm	04999	N/A	1:1	right	0.080	1.030	0.082	
836.60	4183	UMTS 850	RMC	25.5	25.37	-0.01	10 mm	04999	N/A	1:1	left	0.168	1.030	0.173	
1732.40	1412	UMTS 1750	RMC	24.7	24.66	0.07	10 mm	04981	N/A	1:1	back	0.772	1.009	0.779	
1732.40	1412	UMTS 1750	RMC	24.7	24.66	-0.01	10 mm	04981	N/A	1:1	front	0.628	1.009	0.634	A24
1732.40	1412	UMTS 1750	RMC	24.7	24.66	-0.01	10 mm	04981	N/A	1:1	bottom	0.650	1.009	0.656	
1732.40	1412	UMTS 1750	RMC	24.7	24.66	0.00	10 mm	04981	N/A	1:1	left	0.284	1.009	0.287	
1880.00	9400	UMTS 1900	RMC	24.7	24.45	-0.04	10 mm	04999	N/A	1:1	back	0.610	1.059	0.646	
1880.00	9400	UMTS 1900	RMC	24.7	24.45	0.04	10 mm	04999	N/A	1:1	front	0.617	1.059	0.653	
1880.00	9400	UMTS 1900	RMC	24.7	24.45	-0.03	10 mm	04999	N/A	1:1	bottom	0.674	1.059	0.714	A26
1880.00	9400	UMTS 1900	RMC	24.7	24.45	-0.06	10 mm	04999	N/A	1:1	left	0.195	1.059	0.207	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	25.38	0.15	10 mm	04999	N/A	1:1	back	0.496	1.028	0.510	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	25.38	-0.04	10 mm	04999	N/A	1:1	front	0.477	1.028	0.490	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	25.38	-0.06	10 mm	04999	N/A	1:1	bottom	0.240	1.028	0.247	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	25.38	-0.06	10 mm	04999	N/A	1:1	right	0.084	1.028	0.086	
836.52	384	Cell. CDMA	EVDO Rev. 0	25.5	25.38	0.01	10 mm	04999	N/A	1:1	left	0.170	1.028	0.175	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.67	-0.01	10 mm	04999	N/A	1:1	back	0.592	1.007	0.596	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.67	0.03	10 mm	04999	N/A	1:1	front	0.514	1.007	0.518	
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.67	-0.01	10 mm	04999	N/A	1:1	bottom	0.610	1.007	0.614	A30
1880.00	600	PCS CDMA	EVDO Rev. 0	24.7	24.67	-0.02	10 mm	04999	N/A	1:1	left	0.179	1.007	0.180	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body								
Spatial Peak							1.6 W/kg (mW/g)								
Uncontrolled Exposure/General Population							averaged over 1 gram								

FCC ID: ZNFV30A			SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset			Page 74 of 99

Table 11-26
LTE Band 12 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.00	0	05004	QPSK	1	25	10 mm	back	1:1	0.441	1.000	0.441	A31
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	0.00	1	05004	QPSK	25	25	10 mm	back	1:1	0.353	1.107	0.391	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	-0.04	0	05004	QPSK	1	25	10 mm	front	1:1	0.428	1.000	0.428	
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	-0.04	1	05004	QPSK	25	25	10 mm	front	1:1	0.333	1.107	0.369	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	-0.03	0	05004	QPSK	1	25	10 mm	bottom	1:1	0.250	1.000	0.250	
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	0.01	1	05004	QPSK	25	25	10 mm	bottom	1:1	0.204	1.107	0.226	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	-0.11	0	05004	QPSK	1	25	10 mm	right	1:1	0.121	1.000	0.121	
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	-0.06	1	05004	QPSK	25	25	10 mm	right	1:1	0.096	1.107	0.106	
707.50	23095	Mid	LTE Band 12	10	25.5	25.50	0.18	0	05004	QPSK	1	25	10 mm	left	1:1	0.120	1.000	0.120	
707.50	23095	Mid	LTE Band 12	10	24.5	24.06	-0.01	1	05004	QPSK	25	25	10 mm	left	1:1	0.095	1.107	0.105	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

Table 11-27
LTE Band 13 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	-0.09	0	05004	QPSK	1	25	10 mm	back	1:1	0.475	1.000	0.475	
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	-0.02	1	05004	QPSK	25	0	10 mm	back	1:1	0.375	1.042	0.391	
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	-0.03	0	05004	QPSK	1	25	10 mm	front	1:1	0.481	1.000	0.481	A33
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	-0.01	1	05004	QPSK	25	0	10 mm	front	1:1	0.382	1.042	0.398	
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	-0.06	0	05004	QPSK	1	25	10 mm	bottom	1:1	0.235	1.000	0.235	
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	-0.04	1	05004	QPSK	25	0	10 mm	bottom	1:1	0.189	1.042	0.197	
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	-0.07	0	05004	QPSK	1	25	10 mm	right	1:1	0.083	1.000	0.083	
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	-0.03	1	05004	QPSK	25	0	10 mm	right	1:1	0.063	1.042	0.066	
782.00	23230	Mid	LTE Band 13	10	25.5	25.50	0.19	0	05004	QPSK	1	25	10 mm	left	1:1	0.167	1.000	0.167	
782.00	23230	Mid	LTE Band 13	10	24.5	24.32	-0.09	1	05004	QPSK	25	0	10 mm	left	1:1	0.145	1.042	0.151	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																			
Spatial Peak								Body											
Uncontrolled Exposure/General Population								1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-28
LTE Band 5 (Cell) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	0.03	0	05012	QPSK	1	0	10 mm	back	1:1	0.479	1.000	0.479	A34
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	0.06	1	05012	QPSK	25	12	10 mm	back	1:1	0.380	1.009	0.383	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	-0.01	0	05012	QPSK	1	0	10 mm	front	1:1	0.458	1.000	0.458	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	0.05	1	05012	QPSK	25	12	10 mm	front	1:1	0.362	1.009	0.365	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	-0.10	0	05012	QPSK	1	0	10 mm	bottom	1:1	0.221	1.000	0.221	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	-0.14	1	05012	QPSK	25	12	10 mm	bottom	1:1	0.178	1.009	0.180	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	-0.13	0	05012	QPSK	1	0	10 mm	right	1:1	0.077	1.000	0.077	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	0.13	1	05012	QPSK	25	12	10 mm	right	1:1	0.065	1.009	0.066	
836.50	20525	Mid	LTE Band 5 (Cell)	10	25.5	25.50	0.11	0	05012	QPSK	1	0	10 mm	left	1:1	0.149	1.000	0.149	
836.50	20525	Mid	LTE Band 5 (Cell)	10	24.5	24.46	-0.15	1	05012	QPSK	25	12	10 mm	left	1:1	0.118	1.009	0.119	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram										

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 75 of 99	

Table 11-29
LTE Band 66 (AWS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	0.03	0	05012	QPSK	1	0	10 mm	back	1:1	0.720	1.000	0.720	A35
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	-0.09	1	05012	QPSK	50	25	10 mm	back	1:1	0.579	1.023	0.592	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	0.00	0	05012	QPSK	1	0	10 mm	front	1:1	0.674	1.000	0.674	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	0.06	1	05012	QPSK	50	25	10 mm	front	1:1	0.534	1.023	0.546	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	-0.04	0	05012	QPSK	1	0	10 mm	bottom	1:1	0.632	1.000	0.632	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	-0.08	1	05012	QPSK	50	25	10 mm	bottom	1:1	0.552	1.023	0.565	
1770.00	132572	High	LTE Band 66 (AWS)	20	24.7	24.70	-0.06	0	05012	QPSK	1	0	10 mm	left	1:1	0.289	1.000	0.289	
1770.00	132572	High	LTE Band 66 (AWS)	20	23.7	23.60	0.00	1	05012	QPSK	50	25	10 mm	left	1:1	0.237	1.023	0.242	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-30
LTE Band 25 (PCS) Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	-0.04	0	05012	QPSK	1	0	10 mm	back	1:1	0.754	1.000	0.754	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	0.01	1	05012	QPSK	50	25	10 mm	back	1:1	0.567	1.007	0.571	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	0.14	0	05012	QPSK	1	0	10 mm	front	1:1	0.650	1.000	0.650	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	-0.05	1	05012	QPSK	50	25	10 mm	front	1:1	0.499	1.007	0.502	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	-0.01	0	05012	QPSK	1	0	10 mm	bottom	1:1	0.759	1.000	0.759	A37
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	-0.01	1	05012	QPSK	50	25	10 mm	bottom	1:1	0.582	1.007	0.586	
1905.00	26590	High	LTE Band 25 (PCS)	20	24.7	24.70	0.02	0	05012	QPSK	1	0	10 mm	left	1:1	0.265	1.000	0.265	
1905.00	26590	High	LTE Band 25 (PCS)	20	23.7	23.67	0.10	1	05012	QPSK	50	25	10 mm	left	1:1	0.236	1.007	0.238	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-31
LTE Band 30 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.06	0	05020	QPSK	1	0	10 mm	back	1:1	0.842	1.000	0.842	A38
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.00	1	05020	QPSK	25	0	10 mm	back	1:1	0.687	1.096	0.753	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.77	0.00	1	05020	QPSK	50	0	10 mm	back	1:1	0.695	1.104	0.767	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	-0.21	0	05020	QPSK	1	0	10 mm	front	1:1	0.012	1.000	0.012	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.12	1	05020	QPSK	25	0	10 mm	front	1:1	0.009	1.096	0.010	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	-0.01	0	05020	QPSK	1	0	10 mm	bottom	1:1	0.178	1.000	0.178	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.07	1	05020	QPSK	25	0	10 mm	bottom	1:1	0.143	1.096	0.157	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.00	0	05020	QPSK	1	0	10 mm	right	1:1	0.042	1.000	0.042	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	0.08	1	05020	QPSK	25	0	10 mm	right	1:1	0.034	1.096	0.037	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.13	0	05020	QPSK	1	0	10 mm	left	1:1	0.008	1.000	0.008	
2310.00	27710	Mid	LTE Band 30	10	24.2	23.80	-0.15	1	05020	QPSK	25	0	10 mm	left	1:1	0.006	1.096	0.007	
2310.00	27710	Mid	LTE Band 30	10	25.2	25.20	0.04	0	05020	QPSK	1	0	10 mm	back	1:1	0.798	1.000	0.798	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Note: Blue entry represents variability measurement.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 76 of 99

Table 11-32
LTE Band 7 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	-0.11	0	05038	QPSK	1	0	10 mm	back	1:1	0.314	1.000	0.314	A39
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	-0.10	1	05038	QPSK	50	0	10 mm	back	1:1	0.226	1.038	0.235	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	0.03	0	05038	QPSK	1	0	10 mm	front	1:1	0.135	1.000	0.135	
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	0.07	1	05038	QPSK	50	0	10 mm	front	1:1	0.097	1.038	0.101	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	-0.02	0	05038	QPSK	1	0	10 mm	bottom	1:1	0.184	1.000	0.184	
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	0.00	1	05038	QPSK	50	0	10 mm	bottom	1:1	0.134	1.038	0.139	
2535.00	21100	Mid	LTE Band 7	20	23.7	23.70	0.00	0	05038	QPSK	1	0	10 mm	left	1:1	0.043	1.000	0.043	
2510.00	20850	Low	LTE Band 7	20	22.7	22.54	0.09	1	05038	QPSK	50	0	10 mm	left	1:1	0.030	1.038	0.031	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

Table 11-33
LTE Band 41 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Reported SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	-0.18	0	05012	QPSK	1	0	10 mm	back	1:1.58	0.441	1.002	0.442	A40
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	-0.09	1	05012	QPSK	50	25	10 mm	back	1:1.58	0.336	1.007	0.338	
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	0.00	0	05012	QPSK	1	0	10 mm	front	1:1.58	0.188	1.002	0.188	
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	0.05	1	05012	QPSK	50	25	10 mm	front	1:1.58	0.142	1.007	0.143	
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	-0.04	0	05012	QPSK	1	0	10 mm	bottom	1:1.58	0.290	1.002	0.291	
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	-0.15	1	05012	QPSK	50	25	10 mm	bottom	1:1.58	0.241	1.007	0.243	
2506.00	39750	Low	LTE Band 41	20	22.7	22.69	0.00	0	05012	QPSK	1	0	10 mm	left	1:1.58	0.064	1.002	0.064	
2506.00	39750	Low	LTE Band 41	20	21.7	21.67	-0.01	1	05012	QPSK	50	25	10 mm	left	1:1.58	0.047	1.007	0.047	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 77 of 99

Table 11-34
WLAN SISO Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
2437	6	802.11b	DSSS	22	20.0	19.93	-0.02	10 mm	1	05145	1	back	99.0	0.306	0.255	1.016	1.010	0.262	A42
2437	6	802.11b	DSSS	22	20.0	19.93	0.06	10 mm	1	05145	1	front	99.0	0.190	-	1.016	1.010	-	
2437	6	802.11b	DSSS	22	20.0	19.93	0.19	10 mm	1	05145	1	top	99.0	0.220	-	1.016	1.010	-	
2437	6	802.11b	DSSS	22	20.0	19.93	0.11	10 mm	1	05145	1	left	99.0	0.288	-	1.016	1.010	-	
2412	1	802.11b	DSSS	22	19.5	19.26	0.17	10 mm	2	05145	1	back	99.0	0.264	-	1.057	1.010	-	
2412	1	802.11b	DSSS	22	19.5	19.26	0.08	10 mm	2	05145	1	front	99.0	0.276	-	1.057	1.010	-	
2412	1	802.11b	DSSS	22	19.5	19.26	0.13	10 mm	2	05145	1	top	99.0	0.297	0.239	1.057	1.010	0.255	
2412	1	802.11b	DSSS	22	19.5	19.26	-0.10	10 mm	2	05145	1	left	99.0	0.013	-	1.057	1.010	-	
5180	36	802.11a	OFDM	20	17.0	16.76	0.06	10 mm	1	05160	6	back	94.3	0.661	0.271	1.057	1.060	0.304	
5180	36	802.11a	OFDM	20	17.0	16.76	0.00	10 mm	1	05160	6	front	94.3	0.027	-	1.057	1.060	-	
5180	36	802.11a	OFDM	20	17.0	16.76	0.11	10 mm	1	05160	6	top	94.3	0.133	-	1.057	1.060	-	
5180	36	802.11a	OFDM	20	17.0	16.76	0.16	10 mm	1	05160	6	left	94.3	0.287	-	1.057	1.060	-	
5240	48	802.11a	OFDM	20	16.5	16.49	-0.02	10 mm	2	05160	6	back	94.3	0.579	0.256	1.002	1.060	0.272	
5240	48	802.11a	OFDM	20	16.5	16.49	0.00	10 mm	2	05160	6	front	94.3	0.052	-	1.002	1.060	-	
5240	48	802.11a	OFDM	20	16.5	16.49	0.10	10 mm	2	05160	6	top	94.3	0.039	-	1.002	1.060	-	
5240	48	802.11a	OFDM	20	16.5	16.49	0.00	10 mm	2	05160	6	left	94.3	0.154	-	1.002	1.060	-	
5825	165	802.11a	OFDM	20	17.0	16.80	0.07	10 mm	1	05160	6	back	94.3	1.532	0.579	1.047	1.060	0.643	
5825	165	802.11a	OFDM	20	17.0	16.80	0.09	10 mm	1	05160	6	front	94.3	0.154	-	1.047	1.060	-	
5825	165	802.11a	OFDM	20	17.0	16.80	0.11	10 mm	1	05160	6	top	94.3	0.156	-	1.047	1.060	-	
5825	165	802.11a	OFDM	20	17.0	16.80	0.18	10 mm	1	05160	6	left	94.3	0.705	0.311	1.047	1.060	0.345	
5785	157	802.11a	OFDM	20	16.5	16.47	-0.01	10 mm	2	05160	6	back	94.3	0.570	0.262	1.007	1.060	0.280	
5785	157	802.11a	OFDM	20	16.5	16.47	0.00	10 mm	2	05160	6	front	94.3	0.075	-	1.007	1.060	-	
5785	157	802.11a	OFDM	20	16.5	16.47	0.01	10 mm	2	05160	6	top	94.3	0.242	-	1.007	1.060	-	
5785	157	802.11a	OFDM	20	16.5	16.47	0.00	10 mm	2	05160	6	left	94.3	0.111	-	1.007	1.060	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

Table 11-35
WLAN MIMO Hotspot SAR

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm] (Ant 1)	Conducted Power [dBm] (Ant 1)	Maximum Allowed Power [dBm] (Ant 2)	Conducted Power [dBm] (Ant 2)	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.															W/kg	(W/kg)			(W/kg)	
5220	44	802.11n	OFDM	20	17.0	16.50	16.5	16.31	0.07	10 mm	MIMO	05145	13	back	94.5	1.163	0.543	1.122	1.058	0.645	
5220	44	802.11n	OFDM	20	17.0	16.50	16.5	16.31	0.19	10 mm	MIMO	05145	13	front	94.5	0.085	-	1.122	1.058	-	
5220	44	802.11n	OFDM	20	17.0	16.50	16.5	16.31	-0.12	10 mm	MIMO	05145	13	top	94.5	0.300	-	1.122	1.058	-	
5220	44	802.11n	OFDM	20	17.0	16.50	16.5	16.31	0.17	10 mm	MIMO	05145	13	left	94.5	0.414	0.178	1.122	1.058	0.211	
5825	165	802.11n	OFDM	20	17.0	16.89	16.5	16.39	0.06	10 mm	MIMO	05145	13	back	94.5	1.673	0.693	1.026	1.058	0.752	A44
5825	165	802.11n	OFDM	20	17.0	16.89	16.5	16.39	0.15	10 mm	MIMO	05145	13	front	94.5	0.145	-	1.026	1.058	-	
5825	165	802.11n	OFDM	20	17.0	16.89	16.5	16.39	0.14	10 mm	MIMO	05145	13	top	94.5	0.364	-	1.026	1.058	-	
5825	165	802.11n	OFDM	20	17.0	16.89	16.5	16.39	0.16	10 mm	MIMO	05145	13	left	94.5	0.748	0.304	1.026	1.058	0.330	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT											Body										
Spatial Peak											1.6 W/kg (mW/g)										
Uncontrolled Exposure/General Population											averaged over 1 gram										

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 78 of 99

Table 11-36
Bluetooth Hotspot SAR

MEASUREMENT RESULTS																
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Plot #
MHz	Ch.											(W/kg)			(W/kg)	
2441	39	Bluetooth	FHSS	12.5	11.59	0.03	10 mm	05145	1	back	77.2	0.034	1.233	1.295	0.054	
2441	39	Bluetooth	FHSS	12.5	11.59	0.07	10 mm	05145	1	front	77.2	0.027	1.233	1.295	0.043	
2441	39	Bluetooth	FHSS	12.5	11.59	0.00	10 mm	05145	1	top	77.2	0.020	1.233	1.295	0.032	
2441	39	Bluetooth	FHSS	12.5	11.59	-0.02	10 mm	05145	1	left	77.2	0.038	1.233	1.295	0.061	A46
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram									

11.4 Standalone Phablet SAR Data

Table 11-37
WLAN Phablet SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	Peak SAR of Area Scan	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Plot #
MHz	Ch.													W/kg	(W/kg)			(W/kg)	
5320	64	802.11a	OFDM	20	17.0	16.66	0.06	0 mm	1	05160	6	back	94.3	29.851	1.250	1.081	1.060	1.432	
5320	64	802.11a	OFDM	20	17.0	16.66	0.00	0 mm	1	05160	6	front	94.3	2.101	-	1.081	1.060	-	
5320	64	802.11a	OFDM	20	17.0	16.66	0.16	0 mm	1	05160	6	top	94.3	2.096	-	1.081	1.060	-	
5320	64	802.11a	OFDM	20	17.0	16.66	0.14	0 mm	1	05160	6	left	94.3	5.212	0.532	1.081	1.060	0.610	
5320	64	802.11a	OFDM	20	16.5	16.49	0.17	0 mm	2	05160	6	back	94.3	6.242	1.130	1.002	1.060	1.200	
5320	64	802.11a	OFDM	20	16.5	16.49	0.00	0 mm	2	05160	6	front	94.3	2.118	-	1.002	1.060	-	
5320	64	802.11a	OFDM	20	16.5	16.49	0.12	0 mm	2	05160	6	top	94.3	4.275	0.466	1.002	1.060	0.495	
5320	64	802.11a	OFDM	20	16.5	16.49	0.10	0 mm	2	05160	6	left	94.3	0.888	-	1.002	1.060	-	
5500	100	802.11a	OFDM	20	17.0	16.66	-0.09	0 mm	1	05160	6	back	94.3	19.801	0.931	1.081	1.060	1.067	
5580	116	802.11a	OFDM	20	17.0	16.81	-0.01	0mm	1	05160	6	back	94.3	28.303	1.440	1.045	1.060	1.595	A47
5660	132	802.11a	OFDM	20	17.0	16.68	0.04	0mm	1	05160	6	back	94.3	28.237	1.250	1.076	1.060	1.426	
5720	144	802.11a	OFDM	20	17.0	16.73	0.02	0mm	1	05160	6	back	94.3	17.542	1.180	1.064	1.060	1.331	
5580	116	802.11a	OFDM	20	17.0	16.81	0.00	0 mm	1	05160	6	front	94.3	1.803	-	1.045	1.060	-	
5580	116	802.11a	OFDM	20	17.0	16.81	0.13	0 mm	1	05160	6	top	94.3	2.721	-	1.045	1.060	-	
5580	116	802.11a	OFDM	20	17.0	16.81	0.14	0 mm	1	05160	6	left	94.3	10.070	0.807	1.045	1.060	0.894	
5580	116	802.11a	OFDM	20	16.5	16.49	0.05	0 mm	2	05160	6	back	94.3	5.563	1.110	1.002	1.060	1.179	
5580	116	802.11a	OFDM	20	16.5	16.49	0.00	0 mm	2	05160	6	front	94.3	1.206	-	1.002	1.060	-	
5580	116	802.11a	OFDM	20	16.5	16.49	0.15	0 mm	2	05160	6	top	94.3	4.785	0.436	1.002	1.060	0.463	
5580	116	802.11a	OFDM	20	16.5	16.49	0.14	0 mm	2	05160	6	left	94.3	0.897	-	1.002	1.060	-	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Phablet											
Spatial Peak								4.0 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 10 grams											

11.5 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, and FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 79 of 99

6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01r03, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
8. Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v02r01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).
10. Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet" since the diagonal dimension is > 160 mm and < 200 mm. Therefore, phablet SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg.

GSM Test Notes:

1. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
2. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
3. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.
4. GPRS was additionally evaluated for head and body-worn exposure conditions to address possible VoIP scenarios.

CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03r01.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO Rev0 and RevA and TDSO / SO32 FCH+SCH SAR tests were not required per the 3G SAR Test Reduction Procedure in FCC KDB Publication 941225 D01v03r01.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01v03r01 procedures for data devices. Wireless Router SAR tests for Subtype 2 of Rev.A and 1x RTT configurations were not required per the 3G SAR Test Reduction Policy in KDB Publication 941225 D01v03r01.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 80 of 99

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 8.6.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per KDB Publication 941225 D05Av01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.
5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 8.7.5 for more information.
3. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg. See Section 8.7.6 for more information.
4. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06 by either evaluating the sum of the 1g SAR values of each antenna transmitting independently or making a SAR measurement with both antennas transmitting simultaneously. Please see Section 12 for complete analysis.
5. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
6. When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 81 of 99

7. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.

Bluetooth Notes:

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests test mode type. Per October 2016 TCB Workshop Notes, the reported SAR was scaled to the 100% transmission duty factor to determine compliance. See section 9.6 for the time-domain plot and calculation for the duty factor of the device.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 82 of 99

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1-g or 10-g SAR.

Main antenna SAR testing was not required for phablet exposure conditions per FCC KDB 648474 D04v01r03. Therefore, no further analysis was required to determine that possible simultaneous scenarios would not exceed the SAR limit.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 83 of 99

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM/GPRS 850	0.103	0.423	0.636	0.526	0.739	1.162
	GSM/GPRS 1900	0.149	0.423	0.636	0.572	0.785	1.208
	UMTS 850	0.113	0.423	0.636	0.536	0.749	1.172
	UMTS 1750	0.170	0.423	0.636	0.593	0.806	1.229
	UMTS 1900	0.231	0.423	0.636	0.654	0.867	1.290
	Cell. CDMA/EVDO	0.112	0.423	0.636	0.535	0.748	1.171
	PCS CDMA/EVDO	0.132	0.423	0.636	0.555	0.768	1.191
	LTE Band 12	0.091	0.423	0.636	0.514	0.727	1.150
	LTE Band 13	0.109	0.423	0.636	0.532	0.745	1.168
	LTE Band 5 (Cell)	0.093	0.423	0.636	0.516	0.729	1.152
	LTE Band 66 (AWS)	0.154	0.423	0.636	0.577	0.790	1.213
	LTE Band 25 (PCS)	0.136	0.423	0.636	0.559	0.772	1.195
	LTE Band 30	0.021	0.423	0.636	0.444	0.657	1.080
	LTE Band 7	0.013	0.423	0.636	0.436	0.649	1.072
	LTE Band 41	0.020	0.423	0.636	0.443	0.656	1.079

Table 12-2
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM/GPRS 850	0.103	0.535	0.476	0.638	0.579	1.114
	GSM/GPRS 1900	0.149	0.535	0.476	0.684	0.625	1.160
	UMTS 850	0.113	0.535	0.476	0.648	0.589	1.124
	UMTS 1750	0.170	0.535	0.476	0.705	0.646	1.181
	UMTS 1900	0.231	0.535	0.476	0.766	0.707	1.242
	Cell. CDMA/EVDO	0.112	0.535	0.476	0.647	0.588	1.123
	PCS CDMA/EVDO	0.132	0.535	0.476	0.667	0.608	1.143
	LTE Band 12	0.091	0.535	0.476	0.626	0.567	1.102
	LTE Band 13	0.109	0.535	0.476	0.644	0.585	1.120
	LTE Band 5 (Cell)	0.093	0.535	0.476	0.628	0.569	1.104
	LTE Band 66 (AWS)	0.154	0.535	0.476	0.689	0.630	1.165
	LTE Band 25 (PCS)	0.136	0.535	0.476	0.671	0.612	1.147
	LTE Band 30	0.021	0.535	0.476	0.556	0.497	1.032
	LTE Band 7	0.013	0.535	0.476	0.548	0.489	1.024
	LTE Band 41	0.020	0.535	0.476	0.555	0.496	1.031

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 84 of 99

Table 12-3
Simultaneous Transmission Scenario with 2.4 GHz Ant1 & 5GHz Ant2 WLAN (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Head SAR	GSM/GPRS 850	0.103	0.423	0.476	0.526	0.579	1.002
	GSM/GPRS 1900	0.149	0.423	0.476	0.572	0.625	1.048
	UMTS 850	0.113	0.423	0.476	0.536	0.589	1.012
	UMTS 1750	0.170	0.423	0.476	0.593	0.646	1.069
	UMTS 1900	0.231	0.423	0.476	0.654	0.707	1.130
	Cell. CDMA/EVDO	0.112	0.423	0.476	0.535	0.588	1.011
	PCS CDMA/EVDO	0.132	0.423	0.476	0.555	0.608	1.031
	LTE Band 12	0.091	0.423	0.476	0.514	0.567	0.990
	LTE Band 13	0.109	0.423	0.476	0.532	0.585	1.008
	LTE Band 5 (Cell)	0.093	0.423	0.476	0.516	0.569	0.992
	LTE Band 66 (AWS)	0.154	0.423	0.476	0.577	0.630	1.053
	LTE Band 25 (PCS)	0.136	0.423	0.476	0.559	0.612	1.035
	LTE Band 30	0.021	0.423	0.476	0.444	0.497	0.920
	LTE Band 7	0.013	0.423	0.476	0.436	0.489	0.912
	LTE Band 41	0.020	0.423	0.476	0.443	0.496	0.919

Table 12-4
Simultaneous Transmission Scenario with Bluetooth (Held to Ear)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Head SAR	GSM/GPRS 850	0.103	0.219	0.322
	GSM/GPRS 1900	0.149	0.219	0.368
	UMTS 850	0.113	0.219	0.332
	UMTS 1750	0.170	0.219	0.389
	UMTS 1900	0.231	0.219	0.450
	Cell. CDMA/EVDO	0.112	0.219	0.331
	PCS CDMA/EVDO	0.132	0.219	0.351
	LTE Band 12	0.091	0.219	0.310
	LTE Band 13	0.109	0.219	0.328
	LTE Band 5 (Cell)	0.093	0.219	0.312
	LTE Band 66 (AWS)	0.154	0.219	0.373
	LTE Band 25 (PCS)	0.136	0.219	0.355
	LTE Band 30	0.021	0.219	0.240
	LTE Band 7	0.013	0.219	0.232
	LTE Band 41	0.020	0.219	0.239

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 85 of 99

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-5
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM/GPRS 850	0.485	0.262	0.282	0.747	0.767	1.029
	GSM/GPRS 1900	0.558	0.262	0.282	0.820	0.840	1.102
	UMTS 850	0.501	0.262	0.282	0.763	0.783	1.045
	UMTS 1750	0.779	0.262	0.282	1.041	1.061	1.323
	UMTS 1900	0.646	0.262	0.282	0.908	0.928	1.190
	Cell. CDMA	0.500	0.262	0.282	0.762	0.782	1.044
	PCS CDMA	0.591	0.262	0.282	0.853	0.873	1.135
	LTE Band 12	0.441	0.262	0.282	0.703	0.723	0.985
	LTE Band 13	0.475	0.262	0.282	0.737	0.757	1.019
	LTE Band 5 (Cell)	0.479	0.262	0.282	0.741	0.761	1.023
	LTE Band 66 (AWS)	0.720	0.262	0.282	0.982	1.002	1.264
	LTE Band 25 (PCS)	0.754	0.262	0.282	1.016	1.036	1.298
	LTE Band 30	0.842	0.262	0.282	1.104	1.124	1.386
	LTE Band 7	0.314	0.262	0.282	0.576	0.596	0.858
	LTE Band 41	0.442	0.262	0.282	0.704	0.724	0.986

Table 12-6
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	
		1	2	3	1+2	1+3
Body-Worn	GSM/GPRS 850	0.485	0.643	0.410	1.128	0.895
	GSM/GPRS 1900	0.558	0.643	0.410	1.201	0.968
	UMTS 850	0.501	0.643	0.410	1.144	0.911
	UMTS 1750	0.779	0.643	0.410	1.422	1.189
	UMTS 1900	0.646	0.643	0.410	1.289	1.056
	Cell. CDMA	0.500	0.643	0.410	1.143	0.910
	PCS CDMA	0.591	0.643	0.410	1.234	1.001
	LTE Band 12	0.441	0.643	0.410	1.084	0.851
	LTE Band 13	0.475	0.643	0.410	1.118	0.885
	LTE Band 5 (Cell)	0.479	0.643	0.410	1.122	0.889
	LTE Band 66 (AWS)	0.720	0.643	0.410	1.363	1.130
	LTE Band 25 (PCS)	0.754	0.643	0.410	1.397	1.164
	LTE Band 30	0.842	0.643	0.410	1.485	1.252
	LTE Band 7	0.314	0.643	0.410	0.957	0.724
	LTE Band 41	0.442	0.643	0.410	1.085	0.852

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 86 of 99	

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)	SPLSR
		1	2	1+2	1+2
Body-Worn	GSM/GPRS 850	0.485	0.851	1.336	N/A
	GSM/GPRS 1900	0.558	0.851	1.409	N/A
	UMTS 850	0.501	0.851	1.352	N/A
	UMTS 1750	0.779	0.851	See Note 1	0.02
	UMTS 1900	0.646	0.851	1.497	N/A
	Cell. CDMA	0.500	0.851	1.351	N/A
	PCS CDMA	0.591	0.851	1.442	N/A
	LTE Band 12	0.441	0.851	1.292	N/A
	LTE Band 13	0.475	0.851	1.326	N/A
	LTE Band 5 (Cell)	0.479	0.851	1.330	N/A
	LTE Band 66 (AWS)	0.720	0.851	1.571	N/A
	LTE Band 25 (PCS)	0.754	0.851	See Note 1	0.01
	LTE Band 30	0.842	0.851	See Note 1	0.02
	LTE Band 7	0.314	0.851	1.165	N/A
	LTE Band 41	0.442	0.851	1.293	N/A

Table 12-7

Simultaneous Transmission Scenario with 2.4 GHz Ant1 and 5 GHz Ant2 WLAN (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Body-Worn	GSM/GPRS 850	0.485	0.262	0.410	0.747	0.895	1.157
	GSM/GPRS 1900	0.558	0.262	0.410	0.820	0.968	1.230
	UMTS 850	0.501	0.262	0.410	0.763	0.911	1.173
	UMTS 1750	0.779	0.262	0.410	1.041	1.189	1.451
	UMTS 1900	0.646	0.262	0.410	0.908	1.056	1.318
	Cell. CDMA	0.500	0.262	0.410	0.762	0.910	1.172
	PCS CDMA	0.591	0.262	0.410	0.853	1.001	1.263
	LTE Band 12	0.441	0.262	0.410	0.703	0.851	1.113
	LTE Band 13	0.475	0.262	0.410	0.737	0.885	1.147
	LTE Band 5 (Cell)	0.479	0.262	0.410	0.741	0.889	1.151
	LTE Band 66 (AWS)	0.720	0.262	0.410	0.982	1.130	1.392
	LTE Band 25 (PCS)	0.754	0.262	0.410	1.016	1.164	1.426
	LTE Band 30	0.842	0.262	0.410	1.104	1.252	1.514
	LTE Band 7	0.314	0.262	0.410	0.576	0.724	0.986
	LTE Band 41	0.442	0.262	0.410	0.704	0.852	1.114

FCC ID: ZNFV30A	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 87 of 99

Table 12-8
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body-Worn	GSM/GPRS 850	0.485	0.054	0.539
	GSM/GPRS 1900	0.558	0.054	0.612
	UMTS 850	0.501	0.054	0.555
	UMTS 1750	0.779	0.054	0.833
	UMTS 1900	0.646	0.054	0.700
	Cell. CDMA	0.500	0.054	0.554
	PCS CDMA	0.591	0.054	0.645
	LTE Band 12	0.441	0.054	0.495
	LTE Band 13	0.475	0.054	0.529
	LTE Band 5 (Cell)	0.479	0.054	0.533
	LTE Band 66 (AWS)	0.720	0.054	0.774
	LTE Band 25 (PCS)	0.754	0.054	0.808
	LTE Band 30	0.842	0.054	0.896
	LTE Band 7	0.314	0.054	0.368
	LTE Band 41	0.442	0.054	0.496

Notes:

1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.04 per FCC KDB 447498 D01v06. See Section 12.7 for detailed SPLS ratio analysis.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 88 of 99

12.5 Hotspot SAR Simultaneous Transmission Analysis

Table 12-9
Simultaneous Transmission Scenario (2.4 GHz Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	2.4 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.503	0.262	0.255	0.765	0.758	1.020
	GPRS 1900	0.701	0.262	0.255	0.963	0.956	1.218
	UMTS 850	0.501	0.262	0.255	0.763	0.756	1.018
	UMTS 1750	0.779	0.262	0.255	1.041	1.034	1.296
	UMTS 1900	0.714	0.262	0.255	0.976	0.969	1.231
	Cell. EVDO	0.510	0.262	0.255	0.772	0.765	1.027
	PCS EVDO	0.614	0.262	0.255	0.876	0.869	1.131
	LTE Band 12	0.441	0.262	0.255	0.703	0.696	0.958
	LTE Band 13	0.481	0.262	0.255	0.743	0.736	0.998
	LTE Band 5 (Cell)	0.479	0.262	0.255	0.741	0.734	0.996
	LTE Band 66 (AWS)	0.720	0.262	0.255	0.982	0.975	1.237
	LTE Band 25 (PCS)	0.759	0.262	0.255	1.021	1.014	1.276
	LTE Band 30	0.842	0.262	0.255	1.104	1.097	1.359
	LTE Band 7	0.314	0.262	0.255	0.576	0.569	0.831
	LTE Band 41	0.442	0.262	0.255	0.704	0.697	0.959

Table 12-10
Simultaneous Transmission Scenario (5 GHz Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)	
		1	2	3	1+2	1+3
Hotspot SAR	GPRS 850	0.503	0.643	0.280	1.146	0.783
	GPRS 1900	0.701	0.643	0.280	1.344	0.981
	UMTS 850	0.501	0.643	0.280	1.144	0.781
	UMTS 1750	0.779	0.643	0.280	1.422	1.059
	UMTS 1900	0.714	0.643	0.280	1.357	0.994
	Cell. EVDO	0.510	0.643	0.280	1.153	0.790
	PCS EVDO	0.614	0.643	0.280	1.257	0.894
	LTE Band 12	0.441	0.643	0.280	1.084	0.721
	LTE Band 13	0.481	0.643	0.280	1.124	0.761
	LTE Band 5 (Cell)	0.479	0.643	0.280	1.122	0.759
	LTE Band 66 (AWS)	0.720	0.643	0.280	1.363	1.000
	LTE Band 25 (PCS)	0.759	0.643	0.280	1.402	1.039
	LTE Band 30	0.842	0.643	0.280	1.485	1.122
	LTE Band 7	0.314	0.643	0.280	0.957	0.594
	LTE Band 41	0.442	0.643	0.280	1.085	0.722

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 89 of 99

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.503	0.752	1.255
	GPRS 1900	0.701	0.752	1.453
	UMTS 850	0.501	0.752	1.253
	UMTS 1750	0.779	0.752	1.531
	UMTS 1900	0.714	0.752	1.466
	Cell. EVDO	0.510	0.752	1.262
	PCS EVDO	0.614	0.752	1.366
	LTE Band 12	0.441	0.752	1.193
	LTE Band 13	0.481	0.752	1.233
	LTE Band 5 (Cell)	0.479	0.752	1.231
	LTE Band 66 (AWS)	0.720	0.752	1.472
	LTE Band 25 (PCS)	0.759	0.752	1.511
	LTE Band 30	0.842	0.752	1.594
	LTE Band 7	0.314	0.752	1.066
	LTE Band 41	0.442	0.752	1.194

Table 12-11
Simultaneous Transmission Scenario (2.4 GHz Ant1 and 5 GHz Ant2 Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)		
		1	2	3	1+2	1+3	1+2+3
Hotspot SAR	GPRS 850	0.503	0.262	0.280	0.765	0.783	1.045
	GPRS 1900	0.701	0.262	0.280	0.963	0.981	1.243
	UMTS 850	0.501	0.262	0.280	0.763	0.781	1.043
	UMTS 1750	0.779	0.262	0.280	1.041	1.059	1.321
	UMTS 1900	0.714	0.262	0.280	0.976	0.994	1.256
	Cell. EVDO	0.510	0.262	0.280	0.772	0.790	1.052
	PCS EVDO	0.614	0.262	0.280	0.876	0.894	1.156
	LTE Band 12	0.441	0.262	0.280	0.703	0.721	0.983
	LTE Band 13	0.481	0.262	0.280	0.743	0.761	1.023
	LTE Band 5 (Cell)	0.479	0.262	0.280	0.741	0.759	1.021
	LTE Band 66 (AWS)	0.720	0.262	0.280	0.982	1.000	1.262
	LTE Band 25 (PCS)	0.759	0.262	0.280	1.021	1.039	1.301
	LTE Band 30	0.842	0.262	0.280	1.104	1.122	1.384
	LTE Band 7	0.314	0.262	0.280	0.576	0.594	0.856
	LTE Band 41	0.442	0.262	0.280	0.704	0.722	0.984

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 90 of 99

Table 12-12
Simultaneous Transmission Scenario (Bluetooth Hotspot at 1.0 cm)

Exposure Condition	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Hotspot SAR	GPRS 850	0.503	0.061	0.564
	GPRS 1900	0.701	0.061	0.762
	UMTS 850	0.501	0.061	0.562
	UMTS 1750	0.779	0.061	0.840
	UMTS 1900	0.714	0.061	0.775
	Cell. EVDO	0.510	0.061	0.571
	PCS EVDO	0.614	0.061	0.675
	LTE Band 12	0.441	0.061	0.502
	LTE Band 13	0.481	0.061	0.542
	LTE Band 5 (Cell)	0.479	0.061	0.540
	LTE Band 66 (AWS)	0.720	0.061	0.781
	LTE Band 25 (PCS)	0.759	0.061	0.820
	LTE Band 30	0.842	0.061	0.903
	LTE Band 7	0.314	0.061	0.375
	LTE Band 41	0.442	0.061	0.503

12.6 Phablet Simultaneous Transmission Analysis

Table 12-13
Simultaneous Transmission Scenario with 5 GHz WLAN (Phablet at 0.0 cm)

Exposure Condition	5 GHz WLAN Ant 1 SAR (W/kg)	5 GHz WLAN Ant 2 SAR (W/kg)	Σ SAR (W/kg)
	1	2	1+2
Phablet SAR	1.595	1.200	2.795

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 91 of 99

12.7 SPLSR Evaluation and Analysis

Per FCC KDB Publication 447498 D01v06, when the sum of the standalone transmitters is more than 1.6 W/kg for 1g, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. When the SAR peak to location ratio (shown below) for each pair of antennas is

≤ 0.04 for 1g, simultaneous SAR evaluation is not required. The distance between the transmitters was calculated using the following formula.

$$\text{Distance}_{\text{Tx1} - \text{Tx2}} = R_i = \sqrt{(x_1 - x_2)^2 + (y_1 - y_2)^2}$$

$$\text{SPLS Ratio} = \frac{(SAR_1 + SAR_2)^{1.5}}{R_i}$$

12.7.1 Back Side SPLSR Evaluation and Analysis

Table 12-14
Peak SAR Locations for Back Side


Mode/Band	x (mm)	y (mm)	Reported SAR (W/kg)
5 GHz WLAN MIMO	12.00	62.00	0.851
UMTS 1750	-18.00	-64.00	0.779
LTE Band 25 (PCS)	0.50	-85.00	0.754
LTE Band 30	-35.00	-69.60	0.842

Table 12-15
Back Side SAR to Peak Location Separation Ratio Calculations

Antenna Pair		Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (mm)	SPLS Ratio	Plot Number
Ant "a"	Ant "b"	a	b	a+b	D _{a-b}	(a+b) ^{1.5} /D _{a-b}	
UMTS 1750	5 GHz WLAN MIMO	0.779	0.851	1.630	129.52	0.02	1
LTE Band 25 (PCS)	5 GHz WLAN MIMO	0.754	0.851	1.605	147.45	0.01	2
LTE Band 30	5 GHz WLAN MIMO	0.842	0.851	1.693	139.74	0.02	3

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 92 of 99

Table 12-16
Back Side SAR to Peak Location Separation Ratio Plots



12.8 Simultaneous Transmission Conclusion

The above numerical summed SAR results and SPLSR analysis are sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 93 of 99

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10-g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
2300	2310.00	27710	LTE Band 30, 10 MHz Bandwidth	QPSK, 1 RB, 0 RB Offset	back	10 mm	0.842	0.798	1.06	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 94 of 99

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Agilent	8753ES	S-Parameter Vector Network Analyzer	8/19/2016	Annual	8/19/2017	MY40003841
Agilent	8753ES	S-Parameter Network Analyzer	10/26/2016	Annual	10/26/2017	US39170118
Agilent	E4432B	ESG-D Series Signal Generator	3/24/2017	Annual	3/24/2018	US40053896
Agilent	E4438C	ESG Vector Signal Generator	3/24/2017	Biennial	3/24/2019	MY42082385
Agilent	E4438C	ESG Vector Signal Generator	3/23/2017	Biennial	3/23/2019	MY42082659
Agilent	E5515C	Wireless Communications Test Set	1/8/2015	Triennial	1/8/2018	GB43163447
Agilent	E5515C	Wireless Communications Test Set	10/23/2015	Biennial	10/23/2017	GB43193563
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/22/2017	Annual	3/22/2018	MY45470194
Agilent	N4010A	Wireless Connectivity Test Set	CBT	N/A	CBT	GB44450273
Agilent	N5182A	MXG Vector Signal Generator	10/27/2016	Annual	10/27/2017	MY47420603
Agilent	N9020A	MXA Signal Analyzer	10/28/2016	Annual	10/28/2017	US46470561
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433971
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433972
Anritsu	MA24106A	USB Power Sensor	6/7/2017	Annual	6/7/2018	1231535
Anritsu	MA24106A	USB Power Sensor	6/7/2017	Annual	6/7/2018	1231538
Anritsu	MA2411B	Pulse Power Sensor	8/18/2016	Annual	8/18/2017	1126066
Anritsu	MA2411B	Pulse Power Sensor	2/10/2017	Annual	2/10/2018	1207364
Anritsu	ML2495A	Power Meter	10/16/2015	Biennial	10/16/2017	941001
Anritsu	ML2496A	Power Meter	4/20/2017	Annual	4/20/2018	1306009
Anritsu	MT8820C	Radio Communication Analyzer	9/15/2016	Annual	9/15/2017	620901190
Anritsu	MT8820C	Radio Communication Analyzer	11/4/2016	Annual	11/4/2017	6201144418
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	4352	Ultra Long Stem Thermometer	3/8/2016	Biennial	3/8/2018	160261694
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mitutoyo	CD-6 CSX	Digital Caliper	3/2/2016	Biennial	3/2/2018	13264162
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	NC-100	Torque Wrench	3/8/2017	Annual	3/8/2018	N/A
Pasternack	PE208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	12/12/2016	Annual	12/12/2017	833855/0010
Rohde & Schwarz	CMW500	Radio Communication Tester	10/20/2016	Annual	10/20/2017	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	5/4/2017	Annual	5/4/2018	101699
Rohde & Schwarz	CMW500	Radio Communication Tester	10/13/2016	Annual	10/13/2017	102060
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/20/2016	Annual	7/20/2017	132885
Seekonk	NC-100	Torque Wrench	11/6/2015	Biennial	11/6/2017	N/A
SPEAG	D750V3	750 MHz SAR Dipole	1/11/2017	Annual	1/11/2018	1003
SPEAG	D835V2	835 MHz SAR Dipole	7/14/2016	Annual	7/14/2017	4d133
SPEAG	D1750V2	1750 MHz SAR Dipole	5/9/2017	Annual	5/9/2018	1092
SPEAG	D1750V2	1750 MHz SAR Dipole	5/9/2017	Annual	5/9/2018	1148
SPEAG	D1900V2	1900 MHz SAR Dipole	5/10/2017	Annual	5/10/2018	5d026
SPEAG	D1900V2	1900 MHz SAR Dipole	7/8/2016	Annual	7/8/2017	5d080
SPEAG	D1900V2	1900 MHz SAR Dipole	7/15/2016	Annual	7/15/2017	5d149
SPEAG	D2300V2	2300 MHz SAR Dipole	3/7/2017	Annual	3/7/2018	1038
SPEAG	D2450V2	2450 MHz SAR Dipole	9/13/2016	Annual	9/13/2017	797
SPEAG	D2450V2	2450 MHz SAR Dipole	7/25/2016	Annual	7/25/2017	981
SPEAG	D2600V2	2600 MHz SAR Dipole	4/13/2017	Annual	4/13/2018	1004
SPEAG	D2600V2	2600 MHz SAR Dipole	7/25/2016	Annual	7/25/2017	1126
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/21/2016	Annual	9/21/2017	1191
SPEAG	D5GHzV2	5 GHz SAR Dipole	3/9/2017	Annual	3/9/2018	1123
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/2/2016	Annual	8/2/2017	1237
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2017	Annual	2/9/2018	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2017	Annual	2/9/2018	1272
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/8/2017	Annual	3/8/2018	1368
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2017	Annual	4/11/2018	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	9/14/2016	Annual	9/14/2017	1408
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/13/2017	Annual	3/13/2018	1415
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/16/2017	Annual	1/16/2018	1466
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/10/2017	Annual	5/10/2018	1070
SPEAG	ES3DV3	SAR Probe	3/14/2017	Annual	3/14/2018	3209
SPEAG	ES3DV3	SAR Probe	2/10/2017	Annual	2/10/2018	3213
SPEAG	ES3DV3	SAR Probe	9/19/2016	Annual	9/19/2017	3287
SPEAG	ES3DV3	SAR Probe	2/10/2017	Annual	2/10/2018	3318
SPEAG	ES3DV3	SAR Probe	3/14/2017	Annual	3/14/2018	3319
SPEAG	EX3DV4	SAR Probe	1/13/2017	Annual	1/13/2018	3589
SPEAG	EX3DV4	SAR Probe	2/13/2017	Annual	2/13/2018	3914
SPEAG	EX3DV4	SAR Probe	4/18/2017	Annual	4/18/2018	7406

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 95 of 99

15 MEASUREMENT UNCERTAINTIES

a	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)						RSS	11.5	11.3
Expanded Uncertainty (95% CONFIDENCE LEVEL)						k=2	23.0	22.6

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 96 of 99

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: ZNFV30A		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset		Page 97 of 99

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: ZNFV30A	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 98 of 99

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: ZNFV30A	 SAR EVALUATION REPORT 		Approved by: Quality Manager
Document S/N: 1M1706070187-01-R4.ZNF	Test Dates: 06/07/17 - 07/17/17	DUT Type: Portable Handset	Page 99 of 99

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04981

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.614$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-17-2017; Ambient Temp: 19.9°C; Tissue Temp: 20.0°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GSM 850, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.06 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.126 W/kg

SAR(1 g) = 0.103 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04981

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.076

Medium: 1900 Head; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.412 \text{ S/m}$; $\epsilon_r = 40.196$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-26-2017; Ambient Temp: 21.3°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3209; ConvF(5.31, 5.31, 5.31); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 1900, Left Head, Cheek, Mid.ch, 4 Tx slot


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.09 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.230 W/kg

SAR(1 g) = 0.149 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.614$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-17-2017; Ambient Temp: 19.9°C; Tissue Temp: 20.0°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.46 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.136 W/kg

SAR(1 g) = 0.110 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.316 \text{ S/m}$; $\epsilon_r = 39.91$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-23-2017; Ambient Temp: 25.0°C; Tissue Temp: 24.7°C

Probe: ES3DV3 - SN3209; ConvF(5.50, 5.50, 5.50); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.83 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.248 W/kg

SAR(1 g) = 0.168 W/kg



0 dB = 0.193 W/kg = -7.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.431 \text{ S/m}$; $\epsilon_r = 39.060$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-12-2017; Ambient Temp: 19.2°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3209; ConvF(5.31, 5.31, 5.31); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.69 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.229 W/kg

SAR(1 g) = 0.218 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, Cellular CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.615$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-17-2017; Ambient Temp: 19.9°C; Tissue Temp: 20.0°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: CDMA, Rule Part 22H, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.46 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.137 W/kg

SAR(1 g) = 0.111 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, PCS CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.431 \text{ S/m}$; $\epsilon_r = 39.06$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-12-2017; Ambient Temp: 19.2°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3209; ConvF(5.31, 5.31, 5.31); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: PCS EVDO Rev A, Left Head, Cheek, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.838 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.193 W/kg

SAR(1 g) = 0.125 W/kg



0 dB = 0.146 W/kg = -8.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05012

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Head; Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.859 \text{ S/m}$; $\epsilon_r = 42.22$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-08-2017; Ambient Temp: 22.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7406; ConvF(10.26, 10.26, 10.26); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Left Head, Cheek, Mid.ch, QPSK,
10 MHz Bandwidth, 1 RB, 25 RB Offset**


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.81 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.110 W/kg

SAR(1 g) = 0.091 W/kg



0 dB = 0.108 W/kg = -9.67 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05012

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Head; Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.231$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-08-2017; Ambient Temp: 22.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7406; ConvF(10.26, 10.26, 10.26); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 13, Left Head, Cheek, Mid.ch, QPSK,
10 MHz Bandwidth, 1 RB, 25 RB Offset**


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.37 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.138 W/kg

SAR(1 g) = 0.109 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05038

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.903 \text{ S/m}$; $\epsilon_r = 40.615$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-17-2017; Ambient Temp: 19.9°C; Tissue Temp: 20.0°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: LTE Band 5 (Cell.), Left Head, Cheek, Mid.ch

10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.17 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.114 W/kg

SAR(1 g) = 0.093 W/kg



0 dB = 0.101 W/kg = -9.96 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05004

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used (interpolated):

$f = 1770 \text{ MHz}$; $\sigma = 1.353 \text{ S/m}$; $\epsilon_r = 39.746$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-23-2017; Ambient Temp: 25.0°C; Tissue Temp: 24.7°C

Probe: ES3DV3 - SN3209; ConvF(5.50, 5.50, 5.50); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: LTE Band 66 (AWS), Left Head, Cheek, High.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.76 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.229 W/kg

SAR(1 g) = 0.154 W/kg



0 dB = 0.177 W/kg = -7.53 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05004

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.457 \text{ S/m}$; $\epsilon_r = 38.968$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-12-2017; Ambient Temp: 19.2°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3209; ConvF(5.31, 5.31, 5.31); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: LTE Band 25 (PCS), Left Head, Cheek, High.ch
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.74 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.213 W/kg

SAR(1 g) = 0.136 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05020

Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1

Medium: 2300 Head; Medium parameters used:

$f = 2310 \text{ MHz}$; $\sigma = 1.720 \text{ S/m}$; $\epsilon_r = 38.527$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 06-07-2017; Ambient Temp: 19.3°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3213; ConvF(4.95, 4.95, 4.95); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 30, Left Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.836 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.0360 W/kg

SAR(1 g) = 0.021 W/kg



0 dB = 0.0250 W/kg = -16.02 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05004

Communication System: UID 0, LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: 2600 Head; Medium parameters used (interpolated):

$f = 2535 \text{ MHz}$; $\sigma = 1.966 \text{ S/m}$; $\epsilon_r = 37.906$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-12-2017; Ambient Temp: 22.7°C; Tissue Temp: 23.5°C

Probe: EX3DV4 - SN7406; ConvF(7.44, 7.44, 7.44); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: LTE Band 7, Right Head, Cheek, Mid.ch

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x9x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.877 V/m; Power Drift = 0.21 dB

Peak SAR (extrapolated) = 0.0250 W/kg

SAR(1 g) = 0.013 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05020

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2600 Head; Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 1.91 \text{ S/m}$; $\epsilon_r = 37.927$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-07-2017; Ambient Temp: 22.0°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(4.7, 4.7, 4.7); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 41, Right Head, Cheek, Low.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 3.696 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.0370 W/kg

SAR(1 g) = 0.020 W/kg



0 dB = 0.0248 W/kg = -16.06 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05145

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.851 \text{ S/m}$; $\epsilon_r = 38.307$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-12-2017; Ambient Temp: 22.7°C; Tissue Temp: 23.5°C

Probe: EX3DV4 - SN7406; ConvF(7.68, 7.68, 7.68); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Right Head, Cheek,
Ch 06, 1 Mbps, Antenna 2**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 17.19 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.534 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05160

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used:

$f = 5825 \text{ MHz}$; $\sigma = 5.139 \text{ S/m}$; $\epsilon_r = 34.449$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-17-2017; Ambient Temp: 20.1°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN3914; ConvF(4.91, 4.91, 4.91); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11a, U-NII-3, 20 MHz Bandwidth, Right Head, Cheek,
Ch 165, 6 Mbps, Antenna 1**


Area Scan (13x20x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 2.583 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 2.47 W/kg

SAR(1 g) = 0.482 W/kg



0 dB = 1.36 W/kg = 1.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05145

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.295

Medium: 2450 Head; Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.793 \text{ S/m}$; $\epsilon_r = 38.39$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 06-19-2017; Ambient Temp: 23.0°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3213; ConvF(4.7, 4.7, 4.7); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Right Head, Cheek, Ch 39, 1Mbps


Area Scan (11x19x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.487 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.383 W/kg

SAR(1 g) = 0.137 W/kg



0 dB = 0.191 W/kg = -7.19 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05061

Communication System: UID 0, GSM GPRS; 1 Tx slot; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.002 \text{ S/m}$; $\epsilon_r = 52.818$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-22-2017; Ambient Temp: 24.8°C; Tissue Temp: 24.5°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 850, Body SAR, Back Side, Mid.ch, 1 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.31 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.779 W/kg

SAR(1 g) = 0.481 W/kg



0 dB = 0.581 W/kg = -2.36 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05061

Communication System: UID 0, GSM GPRS; 1 Tx slot; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.002 \text{ S/m}$; $\epsilon_r = 52.818$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-22-2017; Ambient Temp: 24.8°C; Tissue Temp: 24.5°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 850, Body SAR, Front Side, Mid.ch, 1 Tx Slots


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.23 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.747 W/kg

SAR(1 g) = 0.499 W/kg



0 dB = 0.543 W/kg = -2.65 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05061

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.486 \text{ S/m}$; $\epsilon_r = 52.433$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-24-2017; Ambient Temp: 21.7°C; Tissue Temp: 23.7°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 4 Tx Slots


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.83 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.974 W/kg

SAR(1 g) = 0.558 W/kg



0 dB = 0.689 W/kg = -1.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05061

Communication System: UID 0, GSM GPRS; 4 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:2.076

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.486 \text{ S/m}$; $\epsilon_r = 52.433$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-24-2017; Ambient Temp: 21.7°C; Tissue Temp: 23.7°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 4 Tx Slots


Area Scan (10x7x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.24 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.701 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.966 \text{ S/m}$; $\epsilon_r = 52.715$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2017; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 850, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.45 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.727 W/kg

SAR(1 g) = 0.486 W/kg



0 dB = 0.553 W/kg = -2.57 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04981

Communication System: UID 0, UMTS; Frequency: 1732.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1732.4 \text{ MHz}$; $\sigma = 1.422 \text{ S/m}$; $\epsilon_r = 52.612$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-19-2017; Ambient Temp: 24.6°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3318; ConvF(5.12, 5.12, 5.12); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1750, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.47 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.772 W/kg



0 dB = 0.884 W/kg = -0.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.526 \text{ S/m}$; $\epsilon_r = 52.252$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-15-2017; Ambient Temp: 21.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (9x7x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.32 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.610 W/kg



0 dB = 0.745 W/kg = -1.28 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.526 \text{ S/m}$; $\epsilon_r = 52.252$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-15-2017; Ambient Temp: 21.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: UMTS 1900, Body SAR, Bottom Edge, Mid.ch


Area Scan (11x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.41 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.674 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.52$ MHz; $\sigma = 0.964$ S/m; $\epsilon_r = 52.671$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-14-2017; Ambient Temp: 23.7°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. CDMA, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.03 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.789 W/kg

SAR(1 g) = 0.476 W/kg



0 dB = 0.557 W/kg = -2.54 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.52 \text{ MHz}$; $\sigma = 0.964 \text{ S/m}$; $\epsilon_r = 52.671$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-14-2017; Ambient Temp: 23.7°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Cell. EVDO, Body SAR, Back side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.37 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.746 W/kg

SAR(1 g) = 0.496 W/kg



0 dB = 0.564 W/kg = -2.49 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.486 \text{ S/m}$; $\epsilon_r = 52.433$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-24-2017; Ambient Temp: 21.7°C; Tissue Temp: 23.7°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: PCS CDMA, Body SAR, Back Side, Mid.ch


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.95 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.982 W/kg

SAR(1 g) = 0.558 W/kg



0 dB = 0.705 W/kg = -1.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 04999

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.486 \text{ S/m}$; $\epsilon_r = 52.433$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-24-2017; Ambient Temp: 21.7°C; Tissue Temp: 23.7°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: PCS EVDO, Body SAR, Bottom Edge, Mid.ch


Area Scan (10x7x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.70 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.610 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05004

Communication System: UID 0, LTE Band 12; Frequency: 707.5 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 707.5 \text{ MHz}$; $\sigma = 0.921 \text{ S/m}$; $\epsilon_r = 56.793$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-14-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(6.44, 6.44, 6.44); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 12, Body SAR, Back Side, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 25 RB Offset**


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.96 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.733 W/kg

SAR(1 g) = 0.441 W/kg



0 dB = 0.526 W/kg = -2.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05004

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.994 \text{ S/m}$; $\epsilon_r = 56.097$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-14-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(6.44, 6.44, 6.44); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 13, Body SAR, Back Side, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 25 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.12 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.687 W/kg

SAR(1 g) = 0.475 W/kg



0 dB = 0.548 W/kg = -2.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05004

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 782 \text{ MHz}$; $\sigma = 0.994 \text{ S/m}$; $\epsilon_r = 56.097$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-14-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(6.44, 6.44, 6.44); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 13, Body SAR, Front side, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 25 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.93 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.726 W/kg

SAR(1 g) = 0.481 W/kg



0 dB = 0.545 W/kg = -2.64 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05012

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.5$ MHz; $\sigma = 0.966$ S/m; $\epsilon_r = 52.716$; $\rho = 1000$ kg/m³

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2017; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 5 (Cell.), Body SAR, Back Side, Mid.ch, 10 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.84 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.788 W/kg

SAR(1 g) = 0.479 W/kg



0 dB = 0.548 W/kg = -2.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05012

Communication System: UID 0, LTE Band 66 (AWS); Frequency: 1770 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1770 \text{ MHz}$; $\sigma = 1.48 \text{ S/m}$; $\epsilon_r = 52.873$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-11-2017; Ambient Temp: 23.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(5.07, 5.07, 5.07); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 66 (AWS), Body SAR, Back Side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.43 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.10 W/kg

SAR(1 g) = 0.720 W/kg



0 dB = 0.797 W/kg = -0.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05012

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.576 \text{ S/m}$; $\epsilon_r = 51.133$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-20-2017; Ambient Temp: 23.3°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3319; ConvF(4.88, 4.88, 4.88); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Body SAR, Back Side, High.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.69 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.754 W/kg



0 dB = 0.895 W/kg = -0.48 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05012

Communication System: UID 0, LTE Band 25 (PCS); Frequency: 1905 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1905 \text{ MHz}$; $\sigma = 1.576 \text{ S/m}$; $\epsilon_r = 51.133$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-20-2017; Ambient Temp: 23.3°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3319; ConvF(4.88, 4.88, 4.88); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 25 (PCS), Body SAR, Bottom Edge, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x9x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.42 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.759 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05020

Communication System: UID 0, LTE Band 30; Frequency: 2310 MHz; Duty Cycle: 1:1

Medium: 2300 Body; Medium parameters used:

$f = 2310 \text{ MHz}$; $\sigma = 1.77 \text{ S/m}$; $\epsilon_r = 52.153$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-21-2017; Ambient Temp: 24.6°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3287; ConvF(4.55, 4.55, 4.55); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 30, Body SAR, Back Side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x18x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.31 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.75 W/kg

SAR(1 g) = 0.842 W/kg



0 dB = 0.792 W/kg = -1.01 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05038

Communication System: UID 0, LTE Band 7; Frequency: 2535 MHz; Duty Cycle: 1:1

Medium: 2600 Body; Medium parameters used (interpolated):

$f = 2535 \text{ MHz}$; $\sigma = 2.069 \text{ S/m}$; $\epsilon_r = 51.322$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-21-2017; Ambient Temp: 24.6°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3287; ConvF(4.12, 4.12, 4.12); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 7, Body SAR, Back Side, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x18x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.32 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.712 W/kg

SAR(1 g) = 0.314 W/kg



0 dB = 0.407 W/kg = -3.90 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05012

Communication System: UID 0, LTE Band 41; Frequency: 2506 MHz; Duty Cycle: 1:1.58

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2506 \text{ MHz}$; $\sigma = 2.097 \text{ S/m}$; $\epsilon_r = 51.067$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2017; Ambient Temp: 22.4°C; Tissue Temp: 23.6°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: LTE Band 41, Body SAR, Back side, Low.ch, 20 MHz Bandwidth,
QPSK, 1 RB, 0 RB Offset**


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.60 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.441 W/kg



0 dB = 0.768 W/kg = -1.15 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05145

Communication System: UID 0, IEEE 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2412 \text{ MHz}$; $\sigma = 1.905 \text{ S/m}$; $\epsilon_r = 51.805$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-21-2017; Ambient Temp: 24.6°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3287; ConvF(4.35, 4.35, 4.35); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 1, 1 Mbps,
Back Side, Antenna 2**


Area Scan (10x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 2.016 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.470 W/kg

SAR(1 g) = 0.264 W/kg



0 dB = 0.325 W/kg = -4.88 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05145

Communication System: UID 0, IEEE 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2437 \text{ MHz}$; $\sigma = 1.937 \text{ S/m}$; $\epsilon_r = 51.696$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-21-2017; Ambient Temp: 24.6°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3287; ConvF(4.35, 4.35, 4.35); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11b, 22 MHz Bandwidth, Body SAR, Ch 6, 1 Mbps,
Back Side, Antenna 1**


Area Scan (10x17x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.609 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.495 W/kg

SAR(1 g) = 0.255 W/kg



0 dB = 0.323 W/kg = -4.91 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05145

Communication System: UID 0, 802.11n 5.2-5.8 GHz Band; Frequency: 5580 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5580 \text{ MHz}$; $\sigma = 5.823 \text{ S/m}$; $\epsilon_r = 46.904$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-26-2017; Ambient Temp: 22.1°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(3.82, 3.82, 3.82); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11n, UNII-2C, 20 MHz Bandwidth, Body SAR, Ch 116, 13 Mbps,
Back Side, MIMO**


Area Scan (13x19x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 11.52 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 3.08 W/kg

SAR(1 g) = 0.729 W/kg



0 dB = 1.78 W/kg = 2.50 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05145

Communication System: UID 0, 802.11n 5.2-5.8 GHz Band; Frequency: 5825 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5825 \text{ MHz}$; $\sigma = 6.184 \text{ S/m}$; $\epsilon_r = 46.498$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-26-2017; Ambient Temp: 22.1°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(3.83, 3.83, 3.83); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11n, UNII-3, 20 MHz Bandwidth, Body SAR, Ch 165, 13 Mbps,
Back Side, MIMO**


Area Scan (13x21x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 10.62 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 2.82 W/kg

SAR(1 g) = 0.629 W/kg



0 dB = 1.62 W/kg = 2.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05145

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.295

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.973 \text{ S/m}$; $\epsilon_r = 51.963$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-27-2017; Ambient Temp: 21.1°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3287; ConvF(4.35, 4.35, 4.35); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.369 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.0740 W/kg

SAR(1 g) = 0.034 W/kg



0 dB = 0.0434 W/kg = -13.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05145

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.295

Medium: 2450 Body; Medium parameters used (interpolated):

$f = 2441 \text{ MHz}$; $\sigma = 1.973 \text{ S/m}$; $\epsilon_r = 51.963$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-27-2017; Ambient Temp: 21.1°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3287; ConvF(4.35, 4.35, 4.35); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

Mode: Bluetooth, Body SAR, Ch 39, 1 Mbps, Left Side


Area Scan (10x17x1): Measurement grid: $dx=5\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.875 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.0840 W/kg

SAR(1 g) = 0.038 W/kg



0 dB = 0.0516 W/kg = -12.87 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: ZNFV30A; Type: Portable Handset; Serial: 05160

Communication System: UID 0, 802.11a 5.2-5.8 GHz Band; Frequency: 5580 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5580 \text{ MHz}$; $\sigma = 5.937 \text{ S/m}$; $\epsilon_r = 47.378$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 06-12-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.82, 3.82, 3.82); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

**Mode: IEEE 802.11a, UNII-2C, 20 MHz Bandwidth, Phablet SAR, Ch 116, 6 Mbps,
Back Side, Antenna 1**


Area Scan (11x19x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 42.00 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 89.0 W/kg

SAR(10 g) = 1.44 W/kg



0 dB = 36.9 W/kg = 15.67 dBW/kg

APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.896 \text{ S/m}$; $\epsilon_r = 41.54$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-08-2017; Ambient Temp: 22.7°C; Tissue Temp: 21.7°C

Probe: EX3DV4 - SN7406; ConvF(10.26, 10.26, 10.26); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Right; Type: QD000P40CD; Serial: TP:7535

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.79 W/kg

SAR(1 g) = 1.79 W/kg

Deviation(1 g) = 6.67%



0 dB = 2.43 W/kg = 3.86 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.902 \text{ S/m}$; $\epsilon_r = 40.636$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-17-2017; Ambient Temp: 19.9°C; Tissue Temp: 20.0°C

Probe: ES3DV3 - SN3213; ConvF(6.49, 6.49, 6.49); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Front; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.95 W/kg

SAR(1 g) = 2.00 W/kg

Deviation(1 g) = 7.30%



0 dB = 2.36 W/kg = 3.73 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1092

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.333 \text{ S/m}$; $\epsilon_r = 39.844$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-23-2017; Ambient Temp: 25.0°C; Tissue Temp: 24.7°C

Probe: ES3DV3 - SN3209; ConvF(5.5, 5.5, 5.5); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.42 W/kg

SAR(1 g) = 3.60 W/kg

Deviation(1 g) = -1.10%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.433 \text{ S/m}$; $\epsilon_r = 40.12$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-26-2017; Ambient Temp: 21.3°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3209; ConvF(5.31, 5.31, 5.31); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.06 W/kg

SAR(1 g) = 3.82 W/kg

Deviation(1 g) = -2.80%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2300 MHz; Type: D2300V2; Serial: 1038

Communication System: UID 0, CW; Frequency: 2300 MHz; Duty Cycle: 1:1

Medium: 2300 Head; Medium parameters used:

$f = 2300 \text{ MHz}$; $\sigma = 1.706 \text{ S/m}$; $\epsilon_r = 38.519$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-07-2017; Ambient Temp: 19.3°C; Tissue Temp: 21.2°C

Probe: ES3DV3 - SN3213; ConvF(4.95, 4.95, 4.95); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2300 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 9.57 W/kg

SAR(1 g) = 4.73 W/kg

Deviation(1 g) = -0.42%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.867 \text{ S/m}$; $\epsilon_r = 38.251$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2017; Ambient Temp: 22.7°C; Tissue Temp: 23.5°C

Probe: EX3DV4 - SN7406; ConvF(7.68, 7.68, 7.68); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.8 W/kg

SAR(1 g) = 5.35 W/kg

Deviation(1 g) = 1.33%



0 dB = 9.25 W/kg = 9.66 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.845 \text{ S/m}$; $\epsilon_r = 38.165$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-07-2017; Ambient Temp: 22.0°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3213; ConvF(4.7, 4.7, 4.7); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1272; Calibrated: 2/9/2017

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.1 W/kg

SAR(1 g) = 5.40 W/kg

Deviation(1 g) = 3.65%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1004

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Head; Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.04 \text{ S/m}$; $\epsilon_r = 37.64$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2017; Ambient Temp: 22.7°C; Tissue Temp: 23.5°C

Probe: EX3DV4 - SN7406; ConvF(7.44, 7.44, 7.44); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 13.3 W/kg

SAR(1 g) = 5.79 W/kg

Deviation(1 g) = 0.52%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 4.57 \text{ S/m}$; $\epsilon_r = 35.284$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-17-2017; Ambient Temp: 20.1°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN3914; ConvF(5.49, 5.49, 5.49); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.0 W/kg

SAR(1 g) = 3.72 W/kg

Deviation(1 g) = -5.70%



0 dB = 8.68 W/kg = 9.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.92 \text{ S/m}$; $\epsilon_r = 34.774$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-17-2017; Ambient Temp: 20.1°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN3914; ConvF(4.94, 4.94, 4.94); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.8 W/kg

SAR(1 g) = 3.86 W/kg

Deviation(1 g) = -7.66%



0 dB = 9.25 W/kg = 9.66 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1191

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5GHz Head; Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 5.099 \text{ S/m}$; $\epsilon_r = 34.586$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-17-2017; Ambient Temp: 20.1°C; Tissue Temp: 20.2°C

Probe: EX3DV4 - SN3914; ConvF(4.91, 4.91, 4.91); Calibrated: 2/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP (Left); Type: SAM; Serial: 1715

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.5 W/kg

SAR(1 g) = 3.66 W/kg

Deviation(1 g) = -7.46%



0 dB = 8.88 W/kg = 9.48 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body; Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.963 \text{ S/m}$; $\epsilon_r = 56.405$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-14-2017; Ambient Temp: 21.1°C; Tissue Temp: 21.4°C

Probe: ES3DV3 - SN3209; ConvF(6.44, 6.44, 6.44); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

750 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 2.51 W/kg

SAR(1 g) = 1.73 W/kg

Deviation(1 g) = -1.59%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.964 \text{ S/m}$; $\epsilon_r = 52.729$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-12-2017; Ambient Temp: 23.9°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(6.29, 6.29, 6.29); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 3.01 W/kg

SAR(1 g) = 2.05 W/kg

Deviation(1 g) = 7.89%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d133

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.001 \text{ S/m}$; $\epsilon_r = 52.828$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 06-22-2017; Ambient Temp: 24.8°C; Tissue Temp: 24.5°C

Probe: ES3DV3 - SN3318; ConvF(6.37, 6.37, 6.37); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

835 MHz System Verification at 23.0 dBm (200 mW)


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 2.92 W/kg

SAR(1 g) = 2.00 W/kg

Deviation(1 g) = 5.26%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.461 \text{ S/m}$; $\epsilon_r = 52.944$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-11-2017; Ambient Temp: 23.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(5.07, 5.07, 5.07); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.43 W/kg

SAR(1 g) = 3.73 W/kg

Deviation(1 g) = 0.81%



0 dB = 4.60 W/kg = 6.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1148

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.44 \text{ S/m}$; $\epsilon_r = 52.565$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-19-2017; Ambient Temp: 24.6°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3318; ConvF(5.12, 5.12, 5.12); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

1750 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 6.37 W/kg

SAR(1 g) = 3.66 W/kg

Deviation(1 g) = -1.08%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d026

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.552 \text{ S/m}$; $\epsilon_r = 52.203$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-15-2017; Ambient Temp: 21.0°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3209; ConvF(4.93, 4.93, 4.93); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1415; Calibrated: 3/13/2017

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.11 W/kg

SAR(1 g) = 4.00 W/kg

Deviation(1 g) = -0.74%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d149

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.57 \text{ S/m}$; $\epsilon_r = 51.143$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-20-2017; Ambient Temp: 23.3°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3319; ConvF(4.88, 4.88, 4.88); Calibrated: 3/14/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 3/8/2017

Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.32 W/kg

SAR(1 g) = 4.06 W/kg

Deviation(1 g) = 1.75%



0 dB = 5.15 W/kg = 7.12 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d080

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.509 \text{ S/m}$; $\epsilon_r = 52.356$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-24-2017; Ambient Temp: 21.7°C; Tissue Temp: 23.7°C

Probe: ES3DV3 - SN3318; ConvF(4.96, 4.96, 4.96); Calibrated: 2/10/2017;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/9/2017

Phantom: SAM with CRP v5.0 (Right); Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

1900 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 7.10 W/kg

SAR(1 g) = 4.01 W/kg

Deviation(1 g) = 2.56%



0 dB = 5.06 W/kg = 7.04 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2300 MHz; Type: D2300V2; Serial: 1038

Communication System: UID 0, CW; Frequency: 2300 MHz; Duty Cycle: 1:1

Medium: 2300 Body; Medium parameters used:

$f = 2300 \text{ MHz}$; $\sigma = 1.749 \text{ S/m}$; $\epsilon_r = 52.222$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-21-2017; Ambient Temp: 24.6°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3287; ConvF(4.55, 4.55, 4.55); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2300 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 9.53 W/kg

SAR(1 g) = 5.04 W/kg

Deviation(1 g) = 6.11%



0 dB = 6.50 W/kg = 8.13 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.954 \text{ S/m}$; $\epsilon_r = 51.639$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-21-2017; Ambient Temp: 24.6°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3287; ConvF(4.35, 4.35, 4.35); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 10.7 W/kg

SAR(1 g) = 5.25 W/kg

Deviation(1 g) = 3.55%



0 dB = 6.90 W/kg = 8.39 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 981

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.985 \text{ S/m}$; $\epsilon_r = 51.927$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-27-2017; Ambient Temp: 21.1°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3287; ConvF(4.35, 4.35, 4.35); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 11.1 W/kg

SAR(1 g) = 5.43 W/kg

Deviation(1 g) = 6.89%



0 dB = 7.03 W/kg = 8.47 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.016 \text{ S/m}$; $\epsilon_r = 51.287$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2017; Ambient Temp: 22.4°C; Tissue Temp: 23.6°C

Probe: EX3DV4 - SN7406; ConvF(7.6, 7.6, 7.6); Calibrated: 4/18/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1407; Calibrated: 4/11/2017

Phantom: SAM Left; Type: QD000P40CC; Serial: TP: 1375

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

2450 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 11.7 W/kg

SAR(1 g) = 5.41 W/kg

Deviation(1 g) = 6.71%



0 dB = 9.16 W/kg = 9.62 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: 1126

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: 2600 Body; Medium parameters used:

$f = 2600 \text{ MHz}$; $\sigma = 2.15 \text{ S/m}$; $\epsilon_r = 51.054$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-21-2017; Ambient Temp: 24.6°C; Tissue Temp: 23.5°C

Probe: ES3DV3 - SN3287; ConvF(4.12, 4.12, 4.12); Calibrated: 9/19/2016;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 9/14/2016

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

2600 MHz System Verification at 20.0 dBm (100 mW)


Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Peak SAR (extrapolated) = 12.3 W/kg

SAR(1 g) = 5.71 W/kg

Deviation(1 g) = 4.77%



0 dB = 7.57 W/kg = 8.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.502 \text{ S/m}$; $\epsilon_r = 47.918$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(4.19, 4.19, 4.19); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10;SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.1 W/kg

SAR(10 g) = 1.06 W/kg

Deviation(10 g) = 0.95%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1123

Communication System: UID 0, CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5250 \text{ MHz}$; $\sigma = 5.4 \text{ S/m}$; $\epsilon_r = 47.485$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-26-2017; Ambient Temp: 22.1°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(4.19, 4.19, 4.19); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5250 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.0 W/kg

SAR(1 g) = 3.72 W/kg

Deviation(1 g) = -1.98%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.965 \text{ S/m}$; $\epsilon_r = 47.313$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.82, 3.82, 3.82); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (9x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 17.7 W/kg

SAR(10 g) = 1.05 W/kg

Deviation(10 g) = -2.33%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1123

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.87 \text{ S/m}$; $\epsilon_r = 46.869$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-26-2017; Ambient Temp: 22.1°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(3.82, 3.82, 3.82); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5600 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 19.0 W/kg

SAR(1 g) = 4.05 W/kg

Deviation(1 g) = 2.66%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1237

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.182 \text{ S/m}$; $\epsilon_r = 47.082$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-12-2017; Ambient Temp: 22.1°C; Tissue Temp: 21.3°C

Probe: EX3DV4 - SN3589; ConvF(3.83, 3.83, 3.83); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)


Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.7 W/kg

SAR(10 g) = 1.00 W/kg

Deviation(10 g) = -4.31%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5 GHz; Type: D5GHzV2; Serial: 1123

Communication System: UID 0, CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5750 \text{ MHz}$; $\sigma = 6.07 \text{ S/m}$; $\epsilon_r = 46.642$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 06-26-2017; Ambient Temp: 22.1°C; Tissue Temp: 20.4°C

Probe: EX3DV4 - SN3589; ConvF(3.83, 3.83, 3.83); Calibrated: 1/13/2017;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1466; Calibrated: 1/16/2017

Phantom: SAM with CRP v5.0 Front; Type: QD000P40CD; Serial: 1646

Measurement SW: DASY52, Version 52.10; SEMCAD X Version 14.6.10 (7417)

5750 MHz System Verification at 17.0 dBm (50 mW)

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Peak SAR (extrapolated) = 16.1 W/kg

SAR(1 g) = 3.49 W/kg

Deviation(1 g) = -8.52%

