


# SAR TEST REPORT

HCT CO., LTD

|                                                  |                                                                                                                                                                                                                                                                                                                                        |
|--------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EUT Type:                                        | 2.4/5GHz BT/WiFi Tablet                                                                                                                                                                                                                                                                                                                |
| FCC ID:                                          | ZNFV400                                                                                                                                                                                                                                                                                                                                |
| IC ID:                                           | 2703C-V400                                                                                                                                                                                                                                                                                                                             |
| Model:                                           | LG-V400                                                                                                                                                                                                                                                                                                                                |
| Date of Issue:                                   | May. 08, 2014                                                                                                                                                                                                                                                                                                                          |
| Test report No.:                                 | HCT-A-1404-F005-2                                                                                                                                                                                                                                                                                                                      |
| Test Laboratory:                                 | <b>HCT CO., LTD.</b><br>74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Korea<br>TEL: +82 31 645 6300 FAX: +82 31 645 6401                                                                                                                                                                                         |
| Applicant :                                      | <b>LG Electronics, MobileComm U.S.A., Inc.</b><br>1000 Sylvan Avenue, Englewood Cliffs NJ 07632                                                                                                                                                                                                                                        |
| Testing has been carried out in accordance with: | RSS-102 Issue 4; Health Canada Safety Code 6<br>47CFR §2.1093<br>ANSI/ IEEE C95.1 – 1992<br>IEEE 1528-2003                                                                                                                                                                                                                             |
| Test result:                                     | The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.                                                                |
| Signature                                        | <div><br/>Report prepared by<br/>: Yun-jeang, Heo<br/>Test Engineer of SAR Part</div> <div><br/>Approved by<br/>: Dong-seob, Kim<br/>Manager of SAR Part</div> |

## Revision History

| Rev.              | Issue DATE    | DESCRIPTION                                                                                                                                                                                              |
|-------------------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HCT-A-1404-F005   | Apr. 29, 2014 | Initial Issue                                                                                                                                                                                            |
| HCT-A-1404-F005-1 | May. 07, 2014 | Sec. 4.7 was revised. (test equipment list updated)                                                                                                                                                      |
| HCT-A-1404-F005-2 | May. 08, 2014 | Sec. 4.7 was revised. (add describe the test equipment cal. note)<br>Sec. 10.2-1 was revised (Add 2450 MHz verification target for IC)<br>Sec. 10.2-2 was revised (revised 2450 MHz verification target) |

---

# Table of Contents

---

|                                                        |    |
|--------------------------------------------------------|----|
| 1. INTRODUCTION .....                                  | 4  |
| 2. TEST METHODOLOGY .....                              | 5  |
| 3. DESCRIPTION OF DEVICE.....                          | 6  |
| 4. DESCRIPTION OF TEST EQUIPMENT .....                 | 7  |
| 5. SAR MEASUREMENT PROCEDURE.....                      | 15 |
| 6. DESCRIPTION OF TEST POSITION.....                   | 17 |
| 7. MEASUREMENT UNCERTAINTY .....                       | 18 |
| 8. ANSI/ IEEE C95.1 - 1992 RF EXPOSURE LIMITS .....    | 20 |
| 9. SAR SYSTEM VALIDATION.....                          | 21 |
| 10. SYSTEM VERIFICATION.....                           | 22 |
| 11. RF CONDUCTED POWER MEASUREMENT .....               | 24 |
| 11.5 Test Exclusions Applied.....                      | 30 |
| 12. SAR Test configuration & Antenna Information ..... | 31 |
| 13. SAR TEST DATA SUMMARY .....                        | 32 |
| 13.1-1 Measurement Results (WLAN Hotspot SAR) .....    | 32 |
| 13.2 SAR Test Notes .....                              | 33 |
| 14. SAR Measurement Variability and Uncertainty .....  | 34 |
| 15. CONCLUSION.....                                    | 35 |
| 16. REFERENCES .....                                   | 36 |
| Attachment 1. – SAR Test Plots .....                   | 37 |
| Attachment 2. – Dipole Verification Plots.....         | 47 |
| Attachment 3. – Probe Calibration Data.....            | 53 |
| Attachment 4. – Dipole Calibration Data .....          | 70 |

# 1. INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017. The measurement procedure described in IEEE/ANSI C95.3-1992 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86 NCRP, 1986, Bethesda, MD 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

## SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative of the incremental electromagnetic energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body.

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dV} \right)$$

Figure 1. SAR Mathematical Equation

*SAR is expressed in units of Watts per Kilogram (W/kg)*

$$SAR = \sigma E^2 / \rho$$

Where:

$\sigma$  = conductivity of the tissue-simulant material (S/m)

$\rho$  = mass density of the tissue-simulant material (kg/m<sup>3</sup>)

$E$  = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

## 2. TEST METHODOLOGY

---

The tests documented in this report were performed in accordance with FCC KDB Procedure, IEEE Standard 1528-2003 & IEEE 1528a-2005 and the following published KDB procedures.

- FCC KDB Publication 248227 D01v01r02(SAR Considerationa for 802.11 Devices)
- FCC KDB Publication 447498 D01v05r02 (General SAR Guidance)
- FCC KDB Publication 616217 D04v01r01 (SAR for laptop and tablets)
- FCC KDB Publication 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz
- FCC KDB Publication 865664 D02v01r01 SAR Reporting

### 3. DESCRIPTION OF DEVICE

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

|                                        |                                                                 |                    |                 |                        |
|----------------------------------------|-----------------------------------------------------------------|--------------------|-----------------|------------------------|
| EUT Type                               | 2.4/5GHz BT/WiFi Tablet                                         |                    |                 |                        |
| FCC ID:                                | ZNFV400                                                         |                    |                 |                        |
| IC ID:                                 | 2703C-V400                                                      |                    |                 |                        |
| Model:                                 | LG-V400                                                         |                    |                 |                        |
| Trade Name                             | LG Electronics, MobileComm U.S.A., Inc.                         |                    |                 |                        |
| Application Type                       | Certification                                                   |                    |                 |                        |
| Mode(s) of Operation                   | 802.11a/b/g/n                                                   |                    |                 |                        |
| Tx Frequency                           | 2 412 - 2 462 MHz (802.11b/g/n) / 5 180 - 5 825 MHz (802.11a/n) |                    |                 |                        |
| Production Unit or Identical Prototype | Prototype                                                       |                    |                 |                        |
| Max SAR                                | Band                                                            | Tx Frequency (MHz) | Equipment Class | Reported 1g SAR (W/Kg) |
|                                        |                                                                 |                    |                 | Body                   |
|                                        | 802.11b                                                         | 2 412.0 - 2 462.0  | DTS             | 0.91                   |
|                                        | 802.11a                                                         | 5 745 - 5 825      | DTS             | 0.31                   |
|                                        | 802.11a                                                         | 5 180 - 5 240      | UNII            | 0.35                   |
|                                        | 802.11a                                                         | 5 260 - 5 320      | UNII            | 0.30                   |
|                                        | 802.11a                                                         | 5 500 - 5 700      | UNII            | 0.30                   |
|                                        | Bluetooth                                                       | 2 402 - 2 480      | DSS/DTS         | -                      |
| Date(s) of Tests                       | Apr. 14, 2014 ~ Apr. 28, 2014                                   |                    |                 |                        |
| Antenna Type                           | Integral Antenna                                                |                    |                 |                        |

## 4. DESCRIPTION OF TEST EQUIPMENT

### 4.1 SAR MEASUREMENT SETUP

These measurements are performed using the DASY4 automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Staubli), robot controller, Pentium III computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure.2).

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the HP Pentium IV 3.0 GHz computer with Windows XP system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 2. HCT SAR Lab. Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in.

## 4.2 DASY E-FIELD PROBE SYSTEM

### 4.1 ET3DV6 Probe Specification

|                   |                                                                                                                                                  |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction      | Symmetrical design with triangular core<br>Built-in optical fiber for surface detection System<br>Built-in shielding against static charges      |
| Calibration       | In air from 10 MHz to 2.5 GHz<br>In brain and muscle simulating tissue at<br>Frequencies of 450 MHz, 900 MHz and<br>1.8 GHz (accuracy: 8 %)      |
| Frequency         | 10 MHz to > 3 GHz; Linearity: $\pm 0.2$ dB<br>(30 MHz to 3 GHz)                                                                                  |
| Directivity       | $\pm 0.2$ dB in brain tissue (rotation around probe axis)<br>$\pm 0.4$ dB in brain tissue (rotation normal probe axis)                           |
| Dynamic           | 5 $\mu$ W/g to > 100 mW/g;                                                                                                                       |
| Range Linearity:  | $\pm 0.2$ dB                                                                                                                                     |
| Surface Detection | $\pm 0.2$ mm repeatability in air and clear liquids<br>over diffuse reflecting surfaces.                                                         |
| Dimensions        | Overall length: 330 mm<br>Tip length: 16 mm<br>Body diameter: 12 mm<br>Tip diameter: 6.8 mm<br>Distance from probe tip to dipole centers: 2.7 mm |
| Application       | General dissymmetry up to 3 GHz<br>Compliance tests of WCDMA/LTE Phones<br>Fast automatic scanning in arbitrary phantoms                         |



Figure 3. Photograph of the probe and the Phantom




Figure 4. ET3DV6 E-field Probe

The SAR measurements were conducted with the dosimetric probe ET3DV6, designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches a maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2<sup>nd</sup> order fitting. The approach is stopped at reaching the maximum.

## 4.2.1 EX3DV4 Probe Specification

|               |                                                                                                                                                                                 |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction  | Symmetrical design with triangular core Interleaved sensors<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| Calibration   | Basic Broad Band Calibration in air<br>Conversion Factors (CF) for HSL 900 and HSL 1810<br>Additional CF for other liquids and frequencies upon request                         |
| Frequency     | 10 MHz to 4 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 4 GHz)                                                                                                                      |
| Directivity   | $\pm 0.2$ dB in HSL (rotation around probe axis)<br>$\pm 0.3$ dB in tissue material (rotation normal to probe axis)                                                             |
| Dynamic Range | 5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB                                                                                                                              |
| Dimensions    | Overall length: 330 mm (Tip: 20 mm)<br>Tip diameter: 3.9 mm (Body: 12 mm)<br>Distance from probe tip to dipole centers: 2.0 mm                                                  |
| Application   | General dosimetry up to 4 GHz<br>Dosimetry in strong gradient fields<br>Compliance tests of mobile phones                                                                       |



Figure 5. Photograph of the probe and the Phantom



Figure 6. EX3DV4 E-field Probe

The SAR measurements were conducted with the dosimetric probe EX3DV4, designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches a maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2<sup>nd</sup> order fitting. The approach is stopped at reaching the maximum.

## 4.3 PROBE CALIBRATION PROCESS

### 4.3.1 E-Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with an accuracy better than  $\pm 10\%$ . The spherical isotropy was evaluated with the proper procedure and found to be better than  $\pm 0.25$  dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe is tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a waveguide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

$\Delta t$  = exposure time (30 seconds),

$C$  = heat capacity of tissue (brain or muscle),

$\Delta T$  = temperature increase due to RF exposure.

SAR is proportional to  $\Delta T/\Delta t$ , the initial rate of tissue heating, before thermal diffusion takes place.

Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E-field;

$$SAR = \frac{|E^2| \cdot \sigma}{\rho}$$

where:

$\sigma$  = simulated tissue conductivity,

$\rho$  = Tissue density ( $1.25 \text{ g/cm}^3$  for brain tissue)




Figure 7. E-Field and Temperature measurements at 900 MHz




Figure 8. E-Field and temperature measurements at 1.8 GHz

### 4.3.2 Data Extrapolation

The DASY4 software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given like below;

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i} \quad \text{with} \quad \begin{array}{ll} V_i & = \text{compensated signal of channel } i \quad (i=x,y,z) \\ U_i & = \text{input signal of channel } i \quad (i=x,y,z) \\ cf & = \text{crest factor of exciting field} \quad (\text{DASY parameter}) \\ dcp_i & = \text{diode compression poing} \quad (\text{DASY parameter}) \end{array}$$

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes: with

$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\begin{array}{ll} V_i & = \text{compensated signal of channel } i \quad (i=x,y,z) \\ Norm_i & = \text{sensor sensitivity of channel } i \quad (i=x,y,z) \\ & \quad \mu V/(V/m)^2 \text{ for E-field probes} \\ ConvF & = \text{sensitivity of enhancement in solution} \\ E_i & = \text{electric field strength of channel } i \text{ in V/m} \end{array}$$

The RSS value of the field components gives the total field strength (Hermetian magnitude):

$$E_{tot} = E_x^2 + E_y^2 + E_z^2$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000} \quad \text{with} \quad \begin{array}{ll} SAR & = \text{local specific absorption rate in W/g} \\ E_{tot} & = \text{total field strength in V/m} \\ \sigma & = \text{conductivity in [mho/m] or [Siemens/m]} \\ \rho & = \text{equivalent tissue density in g/cm}^3 \end{array}$$

The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{with} \quad \begin{array}{ll} P_{pwe} & = \text{equivalent power density of a plane wave in w/cm}^2 \\ E_{tot} & = \text{total electric field strength in V/m} \end{array}$$

## 4.4 SAM Phantom

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.



Figure 9. SAM Phantom

|                 |                                                   |
|-----------------|---------------------------------------------------|
| Shell Thickness | 2.0 mm $\pm$ 0.2 mm (6 $\pm$ 0.2 mm at ear point) |
| Filling Volume  | about 25 L                                        |
| Dimensions      | 810 mm x 1 000 mm x 500 mm (H x L x W)            |

Triple Modular Phantom consists of three identical modules which can be installed and removed separately without emptying the liquid. It includes three reference points for phantom installation. Covers prevent evaporation of the liquid. Phantom material is resistant to DGBE based tissue simulating liquids. The MFP V5.1 will be delivered including wooden support only (**non**-standard SPEAG support).

Applicable for system performance check from 700 MHz to 6 GHz (MFP V5.1C) or 800 MHz - 6 GHz (MFP V5.1A) as well as dosimetric evaluations for body-worn operation.

|                 |                         |
|-----------------|-------------------------|
| Shell Thickness | 2.0 mm $\pm$ 0.2 mm     |
| Filling Volume  | approx. 9.2 L           |
| Dimensions      | 830 mm x 500 mm (L x W) |



Figure 10. MFP V5.1 Triple Modular Phantom

## 4.5 Device Holder for Transmitters

In combination with the SAM Phantom V 4.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatably positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produced infinite number of configurations. To produce the Worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.



Figure 11. Device Holder

## 4.6 Tissue Simulating Mixture Characterization

The mixture is characterized to obtain proper dielectric constant (permittivity) and conductivity of the tissue of interest. The tissue dielectric parameters recommended in IEEE 1528 and IEC 62209 have been used as targets for the compositions, and are to match within 5%, per the FCC recommendations

| Ingredients<br>(% by weight)  | Frequency (MHz) |       |       |       |               |      |               |       |
|-------------------------------|-----------------|-------|-------|-------|---------------|------|---------------|-------|
|                               | 835             |       | 1 900 |       | 2 450 ~ 2 700 |      | 5 200 - 5 800 |       |
| Tissue Type                   | Head            | Body  | Head  | Body  | Head          | Body | Head          | Body  |
| Water                         | 40.45           | 53.06 | 54.9  | 70.17 | 71.88         | 73.2 | 65.52         | 78.66 |
| Salt (NaCl)                   | 1.45            | 0.94  | 0.18  | 0.39  | 0.16          | 0.1  | 0.0           | 0.0   |
| Sugar                         | 57.0            | 44.9  | 0.0   | 0     | 0.0           | 0.0  | 0.0           | 0.0   |
| HEC                           | 1.0             | 1.0   | 0.0   | 0     | 0.0           | 0.0  | 0.0           | 0.0   |
| Bactericide                   | 0.1             | 0.1   | 0.0   | 0     | 0.0           | 0.0  | 0.0           | 0.0   |
| Triton X-100                  | 0.0             | 0.0   | 0.0   | 0.0   | 19.97         | 0.0  | 17.24         | 10.67 |
| DGBE                          | 0.0             | 0.0   | 44.92 | 29.44 | 7.99          | 26.7 | 0.0           | 0.0   |
| Diethylene glycol hexyl ether | -               | -     | -     | -     | -             | -    | 17.24         | 10.67 |

|                           |                                                                    |        |                        |
|---------------------------|--------------------------------------------------------------------|--------|------------------------|
| Salt:                     | 99 % Pure Sodium Chloride                                          | Sugar: | 98 % Pure Sucrose      |
| Water:                    | De-ionized, 16M resistivity                                        | HEC:   | Hydroxyethyl Cellulose |
| DGBE:                     | 99 % Di(ethylene glycol) butyl ether,[2-(2-butoxyethoxy) ethanol]  |        |                        |
| Triton X-100(ultra pure): | Polyethylene glycol mono[4-(1,1,3,3-tetramethylbutyl)phenyl] ether |        |                        |

**Table 4.1 Composition of the Tissue Equivalent Matter**

## 4.7 SAR TEST EQUIPMENT

| Manufacturer    | Type / Model                | S/N             | Calib. Date   | Calib.Interval | Calib.Due     |
|-----------------|-----------------------------|-----------------|---------------|----------------|---------------|
| SPEAG           | SAM Phantom                 | -               | N/A           | N/A            | N/A           |
| SPEAG           | Triple Modular Phantom      | -               | N/A           | N/A            | N/A           |
| Staubli         | Robot RX90L                 | F01/5K09A1/A/01 | N/A           | N/A            | N/A           |
| Staubli         | Robot ControllerCS7MB       | F99/5A82A1/C/01 | N/A           | N/A            | N/A           |
| HP              | Pavilion t000_puffer        | KRJ51201TV      | N/A           | N/A            | N/A           |
| SPEAG           | Light Alignment Sensor      | 265             | N/A           | N/A            | N/A           |
| Staubli         | Teach Pendant (Joystick)    | D221340.01      | N/A           | N/A            | N/A           |
| SPEAG           | DAE4                        | 652             | Mar.26, 2014  | Annual         | Mar.26, 2015  |
| SPEAG           | E-Field Probe EX3DV4        | 3797            | Nov.29, 2013  | Annual         | Nov.29, 2014  |
| SPEAG           | Dipole D2450V2              | 743             | Aug. 23, 2013 | Annual         | Aug. 23, 2014 |
| SPEAG           | Dipole D5GHzV2              | 1107            | Jan. 27, 2014 | Annual         | Jan. 27, 2015 |
| Agilent         | Power Meter(F) E4419B       | MY41291386      | Nov. 01, 2013 | Annual         | Nov. 01, 2014 |
| Agilent         | Power Sensor(G) 8481        | MY41090680      | Oct. 30, 2013 | Annual         | Oct. 30, 2014 |
| HP              | Dielectric Probe Kit 85070C | 00721521        | CBT           |                |               |
| HP              | Dual Directional Coupler    | 16072           | Oct. 31, 2013 | Annual         | Oct. 31, 2014 |
| Agilent         | Base Station E5515C         | GB44400269      | Feb. 10, 2014 | Annual         | Feb. 10, 2015 |
| HP              | Signal Generator 8664A      | 3744A02069      | Nov. 04, 2013 | Annual         | Nov. 04, 2014 |
| Hewlett Packard | 11636B/Power Divider        | 11377           | Nov. 10, 2013 | Annual         | Nov. 11, 2014 |
| Agilent         | N9020A/ SIGNAL ANALYZER     | MY50510407      | Mar. 25, 2014 | Annual         | Mar. 25, 2015 |
| TESCOM          | TC-3000C / BT Tester        | 3000C000276     | Apr. 11, 2014 | Annual         | Apr. 11, 2015 |
| Rohde&Schwarz   | CBT                         | 100422          | Apr. 25, 2013 | Annual         | Apr. 25, 2014 |
| HP              | Network Analyzer 8753ES     | JP39240221      | Mar. 21, 2014 | Annual         | Mar. 21, 2015 |

### NOTE:

1. The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Verification measurement is performed by HCT Lab. before each test. The brain/body simulating material is calibrated by HCT using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain/body-equivalent material.
2. CBT(Calibrating Before Testing). Prior to testing, the dielectric probe kit was calibrated via the network analyzer, with the specified procedure(calibrated in pure water) and calibration kit(standard) short circuit, before the dielectric measurement. The specific procedure and calibration kit are provided by Agilent
3. TC-3000C(BLUETOOTH TESTER) is used after Apr. 11, .2014 and CBT(Rohde & Schwarz BT tester device) is used before Apr. 24, 2014.

## 5. SAR MEASUREMENT PROCEDURE

The evaluation was performed with the following procedure:

1. The SAR value at a fixed location above the ear point was measured and was used as a reference value for assessing the power drop.
2. The SAR distribution at the exposed side of the head was measured at a distance of 3.9 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15 mm x 15 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.
3. Around this point, a volume of 32 mm x 32 mm x 30 mm was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:
  - a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
  - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR value, at the same location as procedure #1, was re-measured. If the value changed by more than 5 %, the evaluation is repeated.




Figure 12. SAR Measurement Point in Area Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extend, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SASR-distribution over 10g. Area scan and zoom scan resolution setting follow KDB 865664 D01v01r03 quoted below

|                                                                                                                                                                                                                                                                                                             |                                    |                                                                                      |                                                                                                                                                                                                                                                                        |                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
|                                                                                                                                                                                                                                                                                                             |                                    |                                                                                      | $\leq 3$ GHz                                                                                                                                                                                                                                                           | $> 3$ GHz                                                                     |
| Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface                                                                                                                                                                                                      |                                    |                                                                                      | $5 \pm 1$ mm                                                                                                                                                                                                                                                           | $\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm                            |
| Maximum probe angle from probe axis to phantom surface normal at the measurement location                                                                                                                                                                                                                   |                                    |                                                                                      | $30^\circ \pm 1^\circ$                                                                                                                                                                                                                                                 | $20^\circ \pm 1^\circ$                                                        |
| Maximum area scan spatial resolution: $\Delta x_{Area}$ , $\Delta y_{Area}$                                                                                                                                                                                                                                 |                                    |                                                                                      | $\leq 2$ GHz: $\leq 15$ mm<br>2 – 3 GHz: $\leq 12$ mm                                                                                                                                                                                                                  | 3 – 4 GHz: $\leq 12$ mm<br>4 – 6 GHz: $\leq 10$ mm                            |
|                                                                                                                                                                                                                                                                                                             |                                    |                                                                                      | When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device. |                                                                               |
| Maximum zoom scan spatial resolution: $\Delta x_{Zoom}$ , $\Delta y_{Zoom}$                                                                                                                                                                                                                                 |                                    |                                                                                      | $\leq 2$ GHz: $\leq 8$ mm<br>2 – 3 GHz: $\leq 5$ mm*                                                                                                                                                                                                                   | 3 – 4 GHz: $\leq 5$ mm*<br>4 – 6 GHz: $\leq 4$ mm*                            |
| Maximum zoom scan spatial resolution, normal to phantom surface                                                                                                                                                                                                                                             | uniform grid: $\Delta z_{Zoom}(n)$ |                                                                                      | $\leq 5$ mm                                                                                                                                                                                                                                                            | 3 – 4 GHz: $\leq 4$ mm<br>4 – 5 GHz: $\leq 3$ mm<br>5 – 6 GHz: $\leq 2$ mm    |
|                                                                                                                                                                                                                                                                                                             | graded grid                        | $\Delta z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface | $\leq 4$ mm                                                                                                                                                                                                                                                            | 3 – 4 GHz: $\leq 3$ mm<br>4 – 5 GHz: $\leq 2.5$ mm<br>5 – 6 GHz: $\leq 2$ mm  |
|                                                                                                                                                                                                                                                                                                             |                                    | $\Delta z_{Zoom}(n>1)$ : between subsequent points                                   | $\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$                                                                                                                                                                                                                                  |                                                                               |
| Minimum zoom scan volume                                                                                                                                                                                                                                                                                    | x, y, z                            |                                                                                      | $\geq 30$ mm                                                                                                                                                                                                                                                           | 3 – 4 GHz: $\geq 28$ mm<br>4 – 5 GHz: $\geq 25$ mm<br>5 – 6 GHz: $\geq 22$ mm |
| Note: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.                                                                                                                                                           |                                    |                                                                                      |                                                                                                                                                                                                                                                                        |                                                                               |
| * When zoom scan is required and the <u>reported</u> SAR from the area scan based <i>1-g SAR estimation</i> procedures of KDB 447498 is $\leq 1.4$ W/kg, $\leq 8$ mm, $\leq 7$ mm and $\leq 5$ mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz. |                                    |                                                                                      |                                                                                                                                                                                                                                                                        |                                                                               |

## **6. DESCRIPTION OF TEST POSITION**

### **6.2 Body Holster/Belt Clip Configurations**

Body operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body operation configurations are divided into two categories: those that do not contain metallic components and those that contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with each accessory. If multiple accessory share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body accessories may not always be supplied or available as options for some Devices intended to be authorized for body use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used.

Since this EUT does not supply any body worn accessory to the end user a distance of 0 cm from the EUT back surface to the liquid interface is configured for the generic test.

"See the Test SET-UP Photo"

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), Including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worstcase positioning is then documented and used to perform Body SAR testing.

## 7. MEASUREMENT UNCERTAINTY

| Error Description                   | Tol<br>(± %) | Prob.<br>dist. | Div. | $c_i$ | Standard<br>Uncertainty<br>(± %) | $v_{eff}$ |
|-------------------------------------|--------------|----------------|------|-------|----------------------------------|-----------|
| <b>1. Measurement System</b>        |              |                |      |       |                                  |           |
| Probe Calibration                   | 6.00         | N              | 1    | 1     | 6.00                             | $\infty$  |
| Axial Isotropy                      | 4.70         | R              | 1.73 | 0.7   | 1.90                             | $\infty$  |
| Hemispherical Isotropy              | 9.60         | R              | 1.73 | 0.7   | 3.88                             | $\infty$  |
| Boundary Effects                    | 1.00         | R              | 1.73 | 1     | 0.58                             | $\infty$  |
| Linearity                           | 4.70         | R              | 1.73 | 1     | 2.71                             | $\infty$  |
| System Detection Limits             | 1.00         | R              | 1.73 | 1     | 0.58                             | $\infty$  |
| Readout Electronics                 | 0.30         | N              | 1.00 | 1     | 0.30                             | $\infty$  |
| Response Time                       | 0.8          | R              | 1.73 | 1     | 0.46                             | $\infty$  |
| Integration Time                    | 2.6          | R              | 1.73 | 1     | 1.50                             | $\infty$  |
| RF Ambient Conditions               | 3.00         | R              | 1.73 | 1     | 1.73                             | $\infty$  |
| Probe Positioner                    | 0.40         | R              | 1.73 | 1     | 0.23                             | $\infty$  |
| Probe Positioning                   | 2.90         | R              | 1.73 | 1     | 1.67                             | $\infty$  |
| Max SAR Eval                        | 1.00         | R              | 1.73 | 1     | 0.58                             | $\infty$  |
| <b>2. Test Sample Related</b>       |              |                |      |       |                                  |           |
| Device Positioning                  | 2.90         | N              | 1.00 | 1     | 2.90                             | 145       |
| Device Holder                       | 3.60         | N              | 1.00 | 1     | 3.60                             | 5         |
| Power Drift                         | 5.00         | R              | 1.73 | 1     | 2.89                             | $\infty$  |
| <b>3. Phantom and Setup</b>         |              |                |      |       |                                  |           |
| Phantom Uncertainty                 | 4.00         | R              | 1.73 | 1     | 2.31                             | $\infty$  |
| Liquid Conductivity(target)         | 5.00         | R              | 1.73 | 0.64  | 1.85                             | $\infty$  |
| Liquid Conductivity(meas.)          | 2.07         | N              | 1    | 0.64  | 1.32                             | 9         |
| Liquid Permittivity(target)         | 5.00         | R              | 1.73 | 0.6   | 1.73                             | $\infty$  |
| Liquid Permittivity(meas.)          | 5.02         | N              | 1    | 0.6   | 3.01                             | 9         |
| <b>Combine Standard Uncertainty</b> |              |                |      |       | 11.13                            |           |
| <b>Coverage Factor for 95 %</b>     |              |                |      |       | $k=2$                            |           |
| <b>Expanded STD Uncertainty</b>     |              |                |      |       | 22.25                            |           |

Table 7.1 Uncertainty (800 MHz - 2 450 MHz)

| Error<br>Description                | Tol<br>(± %) | Prob.<br>dist. | Div. | C <sub>i</sub> | Standard<br>Uncertainty<br>(± %) | V <sub>eff</sub> |
|-------------------------------------|--------------|----------------|------|----------------|----------------------------------|------------------|
| <b>1. Measurement System</b>        |              |                |      |                |                                  |                  |
| Probe Calibration                   | 6.55         | N              | 1    | 1              | 6.00                             | ∞                |
| Axial Isotropy                      | 4.70         | R              | 1.73 | 0.7            | 1.90                             | ∞                |
| Hemispherical Isotropy              | 9.60         | R              | 1.73 | 0.7            | 3.88                             | ∞                |
| Boundary Effects                    | 1.00         | R              | 1.73 | 1              | 0.58                             | ∞                |
| Linearity                           | 4.70         | R              | 1.73 | 1              | 2.71                             | ∞                |
| System Detection Limits             | 1.00         | R              | 1.73 | 1              | 0.58                             | ∞                |
| Readout Electronics                 | 0.30         | N              | 1.00 | 1              | 0.30                             | ∞                |
| Response Time                       | 0.8          | R              | 1.73 | 1              | 0.46                             | ∞                |
| Integration Time                    | 2.6          | R              | 1.73 | 1              | 1.50                             | ∞                |
| RF Ambient Conditions               | 3.00         | R              | 1.73 | 1              | 1.73                             | ∞                |
| Probe Positioner                    | 0.40         | R              | 1.73 | 1              | 0.23                             | ∞                |
| Probe Positioning                   | 2.90         | R              | 1.73 | 1              | 1.67                             | ∞                |
| Max SAR Eval                        | 1.00         | R              | 1.73 | 1              | 0.58                             | ∞                |
| <b>2. Test Sample Related</b>       |              |                |      |                |                                  |                  |
| Device Positioning                  | 2.90         | N              | 1.00 | 1              | 2.90                             | 145              |
| Device Holder                       | 3.60         | N              | 1.00 | 1              | 3.60                             | 5                |
| Power Drift                         | 5.00         | R              | 1.73 | 1              | 2.89                             | ∞                |
| <b>3. Phantom and Setup</b>         |              |                |      |                |                                  |                  |
| Phantom Uncertainty                 | 4.00         | R              | 1.73 | 1              | 2.31                             | ∞                |
| Liquid Conductivity(target)         | 5.00         | R              | 1.73 | 0.64           | 1.85                             | ∞                |
| Liquid Conductivity(meas.)          | 2.07         | N              | 1    | 0.64           | 1.32                             | 9                |
| Liquid Permittivity(target)         | 5.00         | R              | 1.73 | 0.6            | 1.73                             | ∞                |
| Liquid Permittivity(meas.)          | 5.02         | N              | 1    | 0.6            | 3.01                             | 9                |
| <b>Combine Standard Uncertainty</b> |              |                |      |                | 11.43                            |                  |
| <b>Coverage Factor for 95 %</b>     |              |                |      |                | k=2                              |                  |
| <b>Expanded STD Uncertainty</b>     |              |                |      |                | 22.86                            |                  |

Table 7.2 Uncertainty (5000-5900 MHz)

## 8. ANSI/ IEEE C95.1 - 1992 RF EXPOSURE LIMITS

| HUMAN EXPOSURE                                         | UNCONTROLLED ENVIRONMENT<br>General Population<br>(W/kg) or (mW/g) | CONTROLLED ENVIRONMENT<br>Occupational<br>(W/kg) or (mW/g) |
|--------------------------------------------------------|--------------------------------------------------------------------|------------------------------------------------------------|
| SPATIAL PEAK SAR *<br>(Brain)                          | 1.60                                                               | 8.00                                                       |
| SPATIAL AVERAGE SAR **<br>(Whole Body)                 | 0.08                                                               | 0.40                                                       |
| SPATIAL PEAK SAR ***<br>(Hands / Feet / Ankle / Wrist) | 4.00                                                               | 20.00                                                      |

**Table 8.1 Safety Limits for Partial Body Exposure**

### NOTES:

\* The Spatial Peak value of the SAR averaged over any 1 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

\*\* The Spatial Average value of the SAR averaged over the whole-body.

\*\*\* The Spatial Peak value of the SAR averaged over any 10 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

**Uncontrolled Environments** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Controlled Environments** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e.as a result of employment or occupation).

## 9. SAR SYSTEM VALIDATION

Per FCC KCB 865664 D02v01r01, SAR system validation status should be document to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in IEEE 1528-2003 and FCC KDB 865664 D01v01r03. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

| SAR System # | Probe | probe Type | Probe Calibration Point |      | Dipole | Date        | Dielectric Parameters |                       | CW Validation |                 |                | Modulation Validation |             |      |
|--------------|-------|------------|-------------------------|------|--------|-------------|-----------------------|-----------------------|---------------|-----------------|----------------|-----------------------|-------------|------|
|              |       |            |                         |      |        |             | Measured Permittivity | Measured Conductivity | Sensitivity   | Probe Linearity | Probe Isortopy | MOD. Type             | Duty Factor | PAR  |
| 3            | 3797  | EX3DV4     | Body                    | 2450 | 743    | Dec.11,2013 | 52.5                  | 1.97                  | PASS          | PASS            | PASS           | OFDM                  | N/A         | PASS |
| 3            | 3797  | EX3DV4     | Body                    | 5200 | 1107   | Feb.11,2014 | 49.6                  | 5.38                  | PASS          | PASS            | PASS           | OFDM                  | N/A         | PASS |
| 3            | 3797  | EX3DV4     | Body                    | 5300 | 1107   | Feb.11,2014 | 49.1                  | 5.44                  | PASS          | PASS            | PASS           | OFDM                  | N/A         | PASS |
| 3            | 3797  | EX3DV4     | Body                    | 5600 | 1107   | Feb.11,2014 | 48.7                  | 5.88                  | PASS          | PASS            | PASS           | OFDM                  | N/A         | PASS |
| 3            | 3797  | EX3DV4     | Body                    | 5800 | 1107   | Feb.11,2014 | 48.5                  | 6.11                  | PASS          | PASS            | PASS           | OFDM                  | N/A         | PASS |

**SAR System Validation Summary**

**Note;**

All measurement were performed using probes calibrated for CW signal only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r03. SAR system were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to KDB 865664 D01v01r03.

## 10. SYSTEM VERIFICATION

### 10.1-1 Tissue Verification

| Freq. [MHz] | Date          | Probe | Dipole | Liquid | Liquid Temp. [°C] | Parameters   | Target Value | Measured Value | Deviation [%] | Limit [%] |
|-------------|---------------|-------|--------|--------|-------------------|--------------|--------------|----------------|---------------|-----------|
| 2 450       | Apr. 14, 2014 | 3797  | 743    | Body   | 21.1              | $\epsilon_r$ | 52.7         | 52.6           | - 0.19        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 1.95         | 1.97           | + 1.03        | $\pm 5$   |
| 5 200       | Apr. 15, 2014 |       | 1107   | Body   | 21.3              | $\epsilon_r$ | 49.01        | 47.8           | - 2.47        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 5.3          | 5.22           | - 1.51        | $\pm 5$   |
| 5 300       | Apr. 15, 2014 |       |        | Body   | 21.3              | $\epsilon_r$ | 48.85        | 47.3           | - 3.17        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 5.42         | 5.31           | - 2.03        | $\pm 5$   |
| 5 600       | Apr. 15, 2014 |       |        | Body   | 21.3              | $\epsilon_r$ | 48.61        | 47.3           | - 2.69        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 5.65         | 5.79           | + 2.48        | $\pm 5$   |
| 5 800       | Apr. 15, 2014 |       |        | Body   | 21.3              | $\epsilon_r$ | 48.2         | 46.6           | - 3.32        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 6.00         | 6.09           | + 1.50        | $\pm 5$   |

### 10.1-2 Tissue Verification for IC(802.11 n)

| Freq. [MHz] | Date          | Probe | Dipole | Liquid | Liquid Temp. [°C] | Parameters   | Target Value | Measured Value | Deviation [%] | Limit [%] |
|-------------|---------------|-------|--------|--------|-------------------|--------------|--------------|----------------|---------------|-----------|
| 2 450       | Apr. 28, 2014 | 3797  | 743    | Body   | 19.5              | $\epsilon_r$ | 52.7         | 52.0           | - 1.33        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 1.95         | 1.95           | + 0.00        | $\pm 5$   |
| 5 200       | Apr. 28, 2014 |       | 1107   | Body   | 19.5              | $\epsilon_r$ | 49.01        | 48.7           | - 0.63        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 5.3          | 5.2            | - 1.89        | $\pm 5$   |
| 5 300       | Apr. 28, 2014 |       |        | Body   | 19.5              | $\epsilon_r$ | 48.85        | 48.4           | - 0.92        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 5.42         | 5.37           | - 0.92        | $\pm 5$   |
| 5 600       | Apr. 28, 2014 |       |        | Body   | 19.5              | $\epsilon_r$ | 48.61        | 47.6           | - 2.08        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 5.65         | 5.87           | + 3.89        | $\pm 5$   |
| 5 800       | Apr. 28, 2014 |       |        | Body   | 19.5              | $\epsilon_r$ | 48.2         | 47.1           | - 2.28        | $\pm 5$   |
|             |               |       |        |        |                   | $\sigma$     | 6.00         | 6.2            | + 3.33        | $\pm 5$   |

The Tissue dielectronic parameters were measured prior to the SAR evaluation using an Agilent 85070C Dielectronic Probe Kit and Agilent Network Analyzer.

\*Note : Sec. 10.1-2 is only valid for 802.11 n test case.

## 10.2-1 System Verification

Prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at 2 450MHz / 5 200 MHz/ 5 300 MHz/ 5 600 MHz/ 5 800 MHz by using the system Verification kit. (Graphic Plots Attached)

### System Verification Results

| Freq. [MHz] | Date          | Probe (SN) | Dipole (SN) | Liquid | Amb. Temp. [°C] | Liquid Temp. [°C] | 1 W Target SAR <sub>1q</sub> (SPEAG) (mW/g) | Measured SAR <sub>1q</sub> (mW/g) | 1 W Normalized SAR <sub>1q</sub> (mW/g) | Deviation [%] | Limit [%] |
|-------------|---------------|------------|-------------|--------|-----------------|-------------------|---------------------------------------------|-----------------------------------|-----------------------------------------|---------------|-----------|
| 2 450       | Apr. 14, 2014 | 3797       | 743         | Body   | 21.3            | 21.1              | 50.5                                        | 5.02                              | 50.2                                    | - 0.59        | $\pm 10$  |
| 2 450       | Apr. 14, 2014 | 3797       | 743         | Body   | 21.3            | 21.1              | 52.4 <sup>*1)</sup>                         | 5.02                              | 50.2                                    | - 4.20        | $\pm 10$  |
| 5 200       | Apr. 15, 2014 | 3797       | 1107        | Body   | 21.5            | 21.3              | 74.7                                        | 7.54                              | 75.4                                    | + 0.94        | $\pm 10$  |
| 5 300       | Apr. 15, 2014 | 3797       |             | Body   | 21.5            | 21.3              | 75.8                                        | 7.58                              | 75.8                                    | + 0.00        | $\pm 10$  |
| 5 600       | Apr. 15, 2014 | 3797       |             | Body   | 21.5            | 21.3              | 80.2                                        | 8.29                              | 82.9                                    | + 3.37        | $\pm 10$  |
| 5 800       | Apr. 15, 2014 | 3797       |             | Body   | 21.5            | 21.3              | 74.4                                        | 7.3                               | 73                                      | - 1.88        | $\pm 10$  |

\*Note 1 : Per RSS-102, 2450MHz body 1W target value(52.4 mW/g) is added for IC.

## 10.2-2 System Verification for IC (802.11 n)

Prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at 2 450MHz / 5 200 MHz/ 5 300 MHz/ 5 600 MHz/ 5 800 MHz by using the system Verification kit. (Graphic Plots Attached)

### System Verification Results

| Freq. [MHz] | Date          | Probe (SN) | Dipole (SN) | Liquid | Amb. Temp. [°C] | Liquid Temp. [°C] | 1 W Target SAR <sub>1q</sub> (SPEAG) (mW/g) | Measured SAR <sub>1q</sub> (mW/g) | 1 W Normalized SAR <sub>1q</sub> (mW/g) | Deviation [%] | Limit [%] |
|-------------|---------------|------------|-------------|--------|-----------------|-------------------|---------------------------------------------|-----------------------------------|-----------------------------------------|---------------|-----------|
| 2 450       | Apr. 28, 2014 | 3797       | 743         | Body   | 21.3            | 21.1              | 52.4                                        | 5.01                              | 50.1                                    | - 4.39        | $\pm 10$  |
| 5 200       | Apr. 28, 2014 | 3797       | 1107        | Body   | 21.5            | 21.3              | 74.7                                        | 7.50                              | 75.0                                    | + 0.40        | $\pm 10$  |
| 5 300       | Apr. 28, 2014 | 3797       |             | Body   | 21.5            | 21.3              | 75.8                                        | 8.18                              | 81.8                                    | +7.92         | $\pm 10$  |
| 5 600       | Apr. 28, 2014 | 3797       |             | Body   | 21.5            | 21.3              | 80.2                                        | 8.38                              | 83.8                                    | + 4.49        | $\pm 10$  |
| 5 800       | Apr. 28, 2014 | 3797       |             | Body   | 21.5            | 21.3              | 74.4                                        | 7.76                              | 77.6                                    | + 4.30        | $\pm 10$  |

\*Note : Sec. 10.2-2 is only valid for 802.11 n test case.

### **10.3 System Verification Procedure**

SAR measurement was prior to assessment, the system is verified to the  $\pm 10\%$  of the specifications at each frequency band by using the system Verification kit. (Graphic Plots Attached)

- Cabling the system, using the Verification kit equipments.
- Generate about 100 mW Input Level from the Signal generator to the Dipole Antenna.
- Dipole Antenna was placed below the Flat phantom.
- The measured one-gram SAR at the surface of the phantom above the dipole feed-point should be within 10 % of the target reference value.
- The results are normalized to 1 W input power.

Note; SAR Verification was performed according to the FCC KDB 865664 D01v01r03.

## **11. RF CONDUCTED POWER MEASUREMENT**

Power measurements were performed using a base station simulator under digital average power. The handset was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluation SAR. SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, this was configured with the base station simulator. The SAR measurement Software calculates a reference point at the start and end of the test to check for power drifts. If conducted Power deviations of more than 5 % occurred, the tests were repeated.

## 11.1 Output Power Specifications.

This device operates using the following maximum output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB publication 447498 D01v05r02.

### Wifi

| Wifi<br>(Average Power) | Mode / Band |          |          |          |                  |                  |
|-------------------------|-------------|----------|----------|----------|------------------|------------------|
|                         | 2.4 GHz     |          |          | 5 GHz    |                  |                  |
|                         | 802.11 b    | 802.11 g | 802.11 n | 802.11 a | 802.11 n (20MHz) | 802.11 n (40MHz) |
| Maximum                 | 14 dBm      | 12 dBm   | 11 dBm   | 9 dBm    | 8 dBm            | 8 dBm            |
| Nominal                 | 13 dBm      | 11 dBm   | 10 dBm   | 8 dBm    | 7 dBm            | 7 dBm            |

### BT.

| Bluetooth<br>(Average Power) | Mode / Band |       |
|------------------------------|-------------|-------|
|                              | Bluetooth   | LE    |
| Maximum                      | 8.5 dBm     | 2 dBm |
| Nominal                      | 7.5 dBm     | -     |

## 11.4 WiFi

### 11.4.1 SAR Testing for 802.11b/g/n modes

#### General Device Setup

Normal Network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

#### Frequency Channel Configurations

802.11 a/b/g and 4.9 GHz operating modes are tested independently according to the service requirements in each frequency band. 802.11 b/g modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; Channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz § 15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. 4.9 GHz is tested on channels 1, 10 and 5 or 6, whichever has the higher output power, for 5 MHz channels; channels 11, 15 and 19 for 10 MHz channels; and channels 21 and 25 for 20 MHz channels. These are referred to as the “default test channels”. 802.11g mode was evaluated only if the output power was 0.25 dB higher than the 802.11b mode.

| Mode            | GHz   | Channel | Turbo Channel  | “Default Test Channels” |         |      |   |
|-----------------|-------|---------|----------------|-------------------------|---------|------|---|
|                 |       |         |                | §15.247                 |         | UNII |   |
|                 |       |         |                | 802.11b                 | 802.11g |      |   |
| 802.11b/g       | 2.412 | 1#      |                | √                       | √       |      |   |
|                 | 2.437 | 6       | 6              | √                       | √       |      |   |
|                 | 2.462 | 11#     |                | √                       | √       |      |   |
| 802.11a         | 5.18  | 36      |                |                         |         | √    |   |
|                 | 5.20  | 40      | 42 (5.21 GHz)  |                         |         |      | * |
|                 | 5.22  | 44      |                |                         |         |      | * |
|                 | 5.24  | 48      | 50 (5.25 GHz)  |                         |         | √    |   |
|                 | 5.26  | 52      |                |                         |         | √    |   |
|                 | 5.28  | 56      | 58 (5.29 GHz)  |                         |         |      | * |
|                 | 5.30  | 60      |                |                         |         |      | * |
|                 | 5.32  | 64      |                |                         |         | √    |   |
|                 | 5.500 | 100     | Unknown        |                         |         |      | * |
|                 | 5.520 | 104     |                |                         |         | √    |   |
|                 | 5.540 | 108     |                |                         |         |      | * |
|                 | 5.560 | 112     |                |                         |         |      | * |
|                 | 5.580 | 116     |                |                         |         | √    |   |
|                 | 5.600 | 120     |                |                         |         |      | * |
|                 | 5.620 | 124     |                |                         |         | √    |   |
|                 | 5.640 | 128     |                |                         |         |      | * |
|                 | 5.660 | 132     |                |                         |         |      | * |
|                 | 5.680 | 136     |                |                         |         | √    |   |
|                 | 5.700 | 140     |                |                         |         |      | * |
|                 | 5.745 | 149     |                | √                       |         | √    |   |
|                 | 5.765 | 153     | 152 (5.76 GHz) |                         | *       |      | * |
|                 | 5.785 | 157     |                | √                       |         |      | * |
|                 | 5.805 | 161     | 160 (5.80 GHz) |                         | *       | √    |   |
|                 | 5.825 | 165     |                | √                       |         |      |   |
| UNII or §15.247 |       |         |                |                         |         |      |   |
|                 |       |         |                |                         |         |      |   |

802.11 Test Channels per FCC Requirements

### IEEE 802.11b Average RF Power

| Mode    | Freq.<br>[MHz] | Channel | 802.11b (2.4 GHz) Conducted Power [dBm] |       |       |       |
|---------|----------------|---------|-----------------------------------------|-------|-------|-------|
|         |                |         | Data Rate (Mbps)                        |       |       |       |
|         |                |         | 1                                       | 2     | 5.5   | 11    |
| 802.11b | 2412           | 1       | 13.58                                   | 13.54 | 13.66 | 13.51 |
|         | 2437           | 6       | 13.77                                   | 13.75 | 13.78 | 13.87 |
|         | 2462           | 11      | 13.72                                   | 13.70 | 13.84 | 13.69 |

### IEEE 802.11g Average RF Power

| Mode    | Freq.<br>[MHz] | Channel | 802.11g (2.4 GHz) Conducted Power [dBm] |       |       |       |       |       |       |       |
|---------|----------------|---------|-----------------------------------------|-------|-------|-------|-------|-------|-------|-------|
|         |                |         | Data Rate (Mbps)                        |       |       |       |       |       |       |       |
|         |                |         | 6                                       | 9     | 12    | 18    | 24    | 36    | 48    | 54    |
| 802.11g | 2412           | 1       | 11.12                                   | 11.14 | 11.10 | 11.24 | 11.36 | 11.25 | 11.22 | 11.28 |
|         | 2437           | 6       | 11.46                                   | 11.51 | 11.54 | 11.57 | 11.60 | 11.50 | 11.61 | 11.50 |
|         | 2462           | 11      | 11.75                                   | 11.77 | 11.78 | 11.99 | 11.86 | 11.65 | 11.82 | 11.79 |

### IEEE 802.11n Average RF Power

| Mode    | Freq.<br>[MHz] | Channel | 802.11n (2.4 GHz) Conducted Power [dBm] |       |       |       |       |       |       |       |
|---------|----------------|---------|-----------------------------------------|-------|-------|-------|-------|-------|-------|-------|
|         |                |         | Data Rate (Mbps)                        |       |       |       |       |       |       |       |
|         |                |         | 6.5                                     | 13    | 19.5  | 26    | 39    | 52    | 58.5  | 65    |
| 802.11n | 2412           | 1       | 10.26                                   | 10.55 | 10.54 | 10.48 | 10.54 | 10.51 | 10.59 | 10.53 |
|         | 2437           | 6       | 10.72                                   | 10.74 | 10.80 | 10.68 | 10.74 | 10.72 | 10.73 | 10.63 |
|         | 2462           | 11      | 10.64                                   | 10.79 | 10.82 | 10.68 | 10.76 | 10.77 | 10.84 | 10.75 |

### IEEE 802.11a Average RF Power– 20 MHz Bandwidth

| Mode    | Freq.<br>[MHz] | Channel | 802.11a (5 GHz) Conducted Power [dBm] |      |      |      |      |      |      |      |
|---------|----------------|---------|---------------------------------------|------|------|------|------|------|------|------|
|         |                |         | Data Rate (Mbps)                      |      |      |      |      |      |      |      |
|         |                |         | 6                                     | 9    | 12   | 18   | 24   | 36   | 48   | 54   |
| 802.11a | 5180           | 36      | 7.86                                  | 7.64 | 7.77 | 7.80 | 7.84 | 7.82 | 7.83 | 7.58 |
|         | 5200           | 40      | 8.34                                  | 8.08 | 8.19 | 8.08 | 8.29 | 8.18 | 7.94 | 7.90 |
|         | 5220           | 44      | 8.05                                  | 7.80 | 7.68 | 7.41 | 7.33 | 7.10 | 6.58 | 6.51 |
|         | 5240           | 48      | 8.03                                  | 8.17 | 8.02 | 8.06 | 8.16 | 7.99 | 7.88 | 7.96 |
|         | 5260           | 52      | 7.88                                  | 7.92 | 7.99 | 7.86 | 7.89 | 7.74 | 7.62 | 7.79 |
|         | 5280           | 56      | 7.71                                  | 7.63 | 7.51 | 7.38 | 7.11 | 6.68 | 6.31 | 6.34 |
|         | 5300           | 60      | 8.04                                  | 8.01 | 7.97 | 8.04 | 7.98 | 7.82 | 7.85 | 7.87 |
|         | 5320           | 64      | 7.70                                  | 7.74 | 7.65 | 7.74 | 7.76 | 7.63 | 7.54 | 7.52 |
|         | 5500           | 100     | 7.60                                  | 7.63 | 7.66 | 7.69 | 7.79 | 7.71 | 7.53 | 7.58 |
|         | 5520           | 104     | 7.46                                  | 7.38 | 7.29 | 7.11 | 6.92 | 6.74 | 6.23 | 6.18 |
|         | 5540           | 108     | 7.51                                  | 7.45 | 7.31 | 7.20 | 6.96 | 6.71 | 6.29 | 6.22 |
|         | 5560           | 112     | 7.43                                  | 7.26 | 7.17 | 7.05 | 6.84 | 6.69 | 6.31 | 6.10 |
|         | 5580           | 116     | 7.69                                  | 7.60 | 7.65 | 7.64 | 7.79 | 7.50 | 7.59 | 7.40 |
|         | 5660           | 132     | 7.55                                  | 7.31 | 7.28 | 7.08 | 6.95 | 6.51 | 6.28 | 6.07 |
|         | 5680           | 136     | 7.92                                  | 7.87 | 7.91 | 7.82 | 7.82 | 7.85 | 7.55 | 7.45 |
|         | 5700           | 140     | 7.85                                  | 7.86 | 7.89 | 7.88 | 7.86 | 7.83 | 7.68 | 7.78 |
|         | 5745           | 149     | 7.56                                  | 7.51 | 7.59 | 7.66 | 7.64 | 7.55 | 7.50 | 7.47 |
|         | 5765           | 153     | 7.51                                  | 7.46 | 7.43 | 7.21 | 7.08 | 6.88 | 6.54 | 6.31 |
|         | 5785           | 157     | 7.90                                  | 7.95 | 8.01 | 8.03 | 7.78 | 7.83 | 7.71 | 7.93 |
|         | 5805           | 161     | 7.42                                  | 7.31 | 7.29 | 7.21 | 7.04 | 6.74 | 6.33 | 6.15 |
|         | 5825           | 165     | 7.62                                  | 7.60 | 7.79 | 7.78 | 7.88 | 7.76 | 7.46 | 7.61 |

### IEEE 802.11n Average RF Power – 20 MHz Bandwidth

| Mode    | Freq.<br>[MHz] | Channel | 20 MHz BW 802.11n (5 GHz) Conducted Power [dBm] |      |      |      |      |      |      |      |
|---------|----------------|---------|-------------------------------------------------|------|------|------|------|------|------|------|
|         |                |         | Data Rate (Mbps)                                |      |      |      |      |      |      |      |
|         |                |         | 6.5                                             | 13   | 19.5 | 26   | 39   | 52   | 58.5 | 65   |
| 802.11n | 5180           | 36      | 6.89                                            | 7.09 | 6.95 | 7.04 | 6.90 | 6.97 | 6.91 | 6.91 |
|         | 5200           | 40      | 7.48                                            | 7.22 | 7.56 | 7.26 | 7.32 | 7.26 | 7.28 | 7.17 |
|         | 5220           | 44      | 7.34                                            | 7.17 | 7.34 | 7.04 | 7.02 | 6.98 | 7.02 | 6.96 |
|         | 5240           | 48      | 7.07                                            | 6.96 | 7.05 | 6.79 | 6.82 | 6.86 | 6.97 | 6.95 |
|         | 5260           | 52      | 7.06                                            | 6.99 | 7.03 | 7.07 | 6.97 | 6.94 | 6.93 | 6.88 |
|         | 5280           | 56      | 7.13                                            | 7.05 | 7.09 | 7.04 | 6.99 | 6.97 | 6.94 | 6.90 |
|         | 5300           | 60      | 7.24                                            | 7.18 | 7.19 | 7.17 | 7.16 | 7.15 | 7.00 | 7.16 |
|         | 5320           | 64      | 6.83                                            | 6.84 | 6.89 | 6.79 | 6.82 | 6.76 | 6.72 | 6.69 |
|         | 5500           | 100     | 6.56                                            | 6.82 | 6.71 | 6.52 | 6.65 | 6.59 | 6.55 | 6.46 |
|         | 5520           | 104     | 6.89                                            | 6.67 | 6.71 | 6.69 | 6.62 | 6.58 | 6.53 | 6.55 |
|         | 5540           | 108     | 7.05                                            | 6.81 | 6.79 | 6.82 | 6.63 | 6.68 | 6.56 | 6.51 |
|         | 5560           | 112     | 7.23                                            | 6.94 | 6.98 | 6.98 | 6.75 | 6.81 | 6.74 | 6.72 |
|         | 5580           | 116     | 7.35                                            | 7.01 | 7.05 | 7.06 | 6.88 | 6.99 | 6.88 | 6.89 |
|         | 5660           | 132     | 7.01                                            | 6.79 | 6.75 | 6.78 | 6.59 | 6.62 | 6.51 | 6.49 |
|         | 5680           | 136     | 6.94                                            | 6.73 | 6.76 | 6.72 | 6.60 | 6.53 | 6.48 | 6.50 |
|         | 5700           | 140     | 7.00                                            | 6.74 | 6.84 | 6.82 | 6.85 | 6.68 | 6.66 | 6.79 |
|         | 5745           | 149     | 6.34                                            | 6.80 | 6.64 | 6.57 | 6.45 | 6.47 | 6.74 | 6.47 |
|         | 5765           | 153     | 6.81                                            | 6.82 | 6.87 | 6.76 | 6.81 | 6.74 | 6.70 | 6.67 |
|         | 5785           | 157     | 7.49                                            | 7.17 | 7.18 | 7.24 | 7.22 | 7.06 | 7.04 | 7.10 |
|         | 5805           | 161     | 6.88                                            | 7.07 | 6.93 | 7.00 | 6.89 | 6.95 | 6.89 | 6.89 |
|         | 5825           | 165     | 7.13                                            | 6.96 | 7.01 | 6.93 | 6.80 | 6.70 | 6.93 | 6.63 |

### IEEE 802.11n Average RF Power – 40 MHz Bandwidth

| Mode    | Freq.<br>[MHz] | Channel | 40 MHz BW 802.11n (5 GHz) Conducted Power [dBm] |      |      |      |      |      |       |      |
|---------|----------------|---------|-------------------------------------------------|------|------|------|------|------|-------|------|
|         |                |         | Data Rate (Mbps)                                |      |      |      |      |      |       |      |
|         |                |         | 13.5                                            | 27   | 40.5 | 54   | 81   | 108  | 121.5 | 135  |
| 802.11n | 5190           | 38      | 7.81                                            | 7.94 | 7.92 | 7.82 | 7.87 | 7.90 | 7.94  | 7.91 |
|         | 5230           | 46      | 7.53                                            | 7.49 | 7.54 | 7.61 | 7.42 | 7.68 | 7.61  | 7.43 |
|         | 5270           | 54      | 7.68                                            | 7.59 | 7.67 | 7.65 | 7.51 | 7.75 | 7.54  | 7.59 |
|         | 5310           | 62      | 7.59                                            | 7.68 | 7.81 | 7.63 | 7.70 | 7.67 | 7.61  | 7.70 |
|         | 5510           | 102     | 7.58                                            | 7.86 | 7.56 | 7.50 | 7.61 | 7.74 | 7.50  | 7.60 |
|         | 5550           | 110     | 7.84                                            | 7.95 | 7.98 | 7.72 | 7.86 | 7.83 | 7.79  | 7.84 |
|         | 5670           | 134     | 7.24                                            | 7.35 | 7.49 | 7.38 | 7.40 | 7.50 | 7.31  | 7.30 |
|         | 5755           | 151     | 7.16                                            | 6.62 | 6.29 | 5.98 | 5.41 | 5.03 | 4.66  | 4.51 |
|         | 5795           | 159     | 7.03                                            | 6.53 | 6.17 | 5.86 | 5.29 | 4.84 | 4.59  | 4.42 |

## 11.5 Test Exclusions Applied

### 11.5.1 BT

#### BT

Per FCC KDB 447498 D01v05r02, The SAR exclusion threshold for distance < 50 mm is defined by the following equation:

$$\frac{\text{Max Power of Channel(mW)}}{\text{Test Separation Distance (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

| Mode      | Frequency | Maximum Allowed Power | Separatuin Distance | $\leq 3.0$ |
|-----------|-----------|-----------------------|---------------------|------------|
|           | [MHz]     | [mW]                  | [mm]                |            |
| Bluetooth | 2441      | 7                     | 10                  | 1.09       |

Based on the maximum conducted power of Bluetooth and antenna to use separation distance, Bluetooth SAR was not required  $[(7/10) * \sqrt{2.441}] = 1.09 < 3.0$ .

Note :


1) Per RSS-102 issue 4 Sec. 2.5.1, The BT SAR evaluation is not reired for IC. BT Max target Power is less than 20mW.

## 12. SAR Test configuration & Antenna Information

### 12.1 SAR Testing configurations

| Mode         | Rear | Front | Left | Right | Bottom | Top |
|--------------|------|-------|------|-------|--------|-----|
| 2.4 GHz WLAN | Yes  | No    | No   | Yes   | No     | Yes |
| 5 GHz WLAN   | Yes  | No    | No   | Yes   | No     | Yes |

### 12.2 Antenna and Device Information



**Note;**

1. Particular DUT edges were not required to be evaluated for SAR based on the SAR exclusion threshold in KDB 447498 D01v05r01

\*Please see the LG-V400\_Antenna distance for further information.

## 13. SAR TEST DATA SUMMARY

### 13. 1-1 Measurement Results (WLAN SAR)

| Frequency                                                                                          |     | Mode             | Power (dBm)   |                 | Power Drift (dB) | Con figuration | Data Rate                                       | Separation Distance | Measured SAR (mW/g) | Corrected SAR (mW/g) | Scaling Facor | Scaled SAR (mW/g) | Plot No. |
|----------------------------------------------------------------------------------------------------|-----|------------------|---------------|-----------------|------------------|----------------|-------------------------------------------------|---------------------|---------------------|----------------------|---------------|-------------------|----------|
| MHz                                                                                                | Ch. |                  | Tune-Up Limit | Conducted Power |                  |                |                                                 |                     |                     |                      |               |                   |          |
| 2 412                                                                                              | 1   | 802.11b          | 14            | 13.58           | 0.059            | Rear           | 1Mbps                                           | 0 cm                | 0.679               | N/A                  | 1.102         | 0.748             | -        |
| 2 437                                                                                              | 6   |                  | 14            | 13.77           | -0.163           | Rear           | 1Mbps                                           | 0 cm                | 0.722               | N/A                  | 1.054         | 0.761             | -        |
| 2 462                                                                                              | 11  |                  | 14            | 13.72           | -0.012           | Rear           | 1Mbps                                           | 0 cm                | 0.851               | N/A                  | 1.067         | 0.908             | 1        |
| 2 437                                                                                              | 6   |                  | 14            | 13.77           | -0.160           | Right          | 1Mbps                                           | 0 cm                | 0.247               | N/A                  | 1.054         | 0.260             | -        |
|                                                                                                    |     |                  | 14            | 13.77           | 0.014            | Top            | 1Mbps                                           | 0 cm                | 0.241               | N/A                  | 1.054         | 0.254             | -        |
| 2437                                                                                               | 6   | 802.11n          | 11            | 10.72           | -0.108           | Rear           | 6.5Mbps                                         | 0 cm                | 0.349               | N/A                  | 1.067         | 0.372             | 2        |
| 5 785                                                                                              | 157 | 802.11a          | 9             | 7.90            | 0.141            | Rear           | 6Mbps                                           | 0 cm                | 0.238               | 0.240                | 1.288         | 0.307             | 3        |
|                                                                                                    |     |                  | 9             | 7.90            | -0190            | Right          | 6Mbps                                           | 0 cm                | 0.234               | 0.236                | 1.288         | 0.301             | -        |
|                                                                                                    |     |                  | 9             | 7.90            | -0.186           | Top            | 6Mbps                                           | 0 cm                | 0.058               | 0.058                | 1.288         | 0.075             | -        |
| 5 785                                                                                              | 157 | 802.11n<br>20MHz | 8             | 7.49            | -0.179           | Rear           | 6.5Mbps                                         | 0 cm                | 0.152               | 0.154                | 1.125         | 0.171             | 4        |
| 5755                                                                                               | 151 | 802.11n<br>40MHz | 8             | 7.16            | 0.171            | Rear           | 13.5Mbps                                        | 0 cm                | 0.145               | 0.147                | 1.213         | 0.176             | 5        |
| 5 200                                                                                              | 40  | 802.11a          | 9             | 8.34            | -0.026           | Rear           | 6Mbps                                           | 0 cm                | 0.296               | 0.298                | 1.164         | 0.345             | 6        |
|                                                                                                    |     |                  | 9             | 8.34            | -0.169           | Right          | 6Mbps                                           | 0 cm                | 0.209               | 0.210                | 1.164         | 0.243             | -        |
|                                                                                                    |     |                  | 9             | 8.34            | -0.141           | Top            | 6Mbps                                           | 0 cm                | 0.082               | 0.082                | 1.164         | 0.095             | -        |
| 5 300                                                                                              | 60  | 802.11a          | 9             | 8.04            | 0.118            | Rear           | 6Mbps                                           | 0 cm                | 0.239               | 0.241                | 1.247         | 0.298             | -        |
|                                                                                                    |     |                  | 9             | 8.04            | -0.168           | Right          | 6Mbps                                           | 0 cm                | 0.208               | 0.209                | 1.247         | 0.259             | -        |
|                                                                                                    |     |                  | 9             | 8.04            | 0.128            | Top            | 6Mbps                                           | 0 cm                | 0.089               | 0.090                | 1.247         | 0.111             | -        |
| 5 680                                                                                              | 136 | 802.11a          | 9             | 7.92            | 0.146            | Rear           | 6Mbps                                           | 0 cm                | 0.219               | 0.220                | 1.282         | 0.281             | -        |
|                                                                                                    |     |                  | 9             | 7.92            | -0.143           | Right          | 6Mbps                                           | 0 cm                | 0.235               | 0.236                | 1.282         | 0.301             | -        |
|                                                                                                    |     |                  | 9             | 7.92            | 0.162            | Top            | 6Mbps                                           | 0 cm                | 0.086               | 0.086                | 1.282         | 0.110             | -        |
| 5200                                                                                               | 40  | 802.11n<br>20MHz | 8             | 7.48            | -0.156           | Rear           | 6.5Mbps                                         | 0 cm                | 0.261               | 0.261                | 1.127         | 0.294             | 7        |
| 5300                                                                                               | 60  |                  | 8             | 7.24            | -0.051           | Rear           | 6.5Mbps                                         | 0 cm                | 0.168               | 0.168                | 1.191         | 0.200             | -        |
| 5580                                                                                               | 116 |                  | 8             | 7.35            | -0.164           | Rear           | 6.5Mbps                                         | 0 cm                | 0.160               | 0.161                | 1.161         | 0.186             | -        |
| 5190                                                                                               | 38  | 802.11n<br>40MHz | 8             | 7.81            | 0.176            | Rear           | 13.5Mbps                                        | 0 cm                | 0.217               | 0.217                | 1.045         | 0.227             | 8        |
| 5270                                                                                               | 54  |                  | 8             | 7.68            | -0.127           | Rear           | 13.5Mbps                                        | 0 cm                | 0.176               | 0.176                | 1.076         | 0.189             | -        |
| 5500                                                                                               | 110 |                  | 8             | 7.84            | 0.159            | Rear           | 13.5Mbps                                        | 0 cm                | 0.191               | 0.192                | 1.038         | 0.198             | -        |
| ANSI/ IEEE C95.1 - 1992– Safety Limit<br>Spatial Peak<br>Uncontrolled Exposure/ General Population |     |                  |               |                 |                  |                | Body<br>1.6 W/kg (mW/g)<br>Averaged over 1 gram |                     |                     |                      |               |                   |          |

## **13.2 SAR Test Notes**

### **General Notes:**

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, FCC KDB Procedure.
2. Batteries are fully charged at the beginning of the SAR measurements. A standard battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB 447498 D01v05r02.

### **WLAN Notes:**

1. Justification for reduced test configurations for WIFI channels per KDB 248227 D01v01r02 and Oct. 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other IEEE 802.11 modes (including 802.11 g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
2. Justification for reduced test configurations for WIFI channels per KDB 248227 D01v01r02 and Oct. 2012 FCC/TCB Meeting Notes for 5 GHz WIFI: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11a. Other IEEE 802.11 modes (including 802.11 n 20MHz and 40 MHz bandwidths) were not investigated since the average output power over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data of IEEE 802.11a mode.
3. Since the maximum extrapolated peak SAR of the zoom scan for the maximum output channel was  $\leq 1.6$  W/kg and the reported 1g averaged SAR was  $< 0.8$  W/kg, SAR testing on other default channels was not required.
4. According to IC Notice 2012-DRS0529, corrected SAR is added. For 2.4 GHz,  $\Delta$ SAR is positive, so it doesn't need to be calculated corrected SAR.
5. 802.11 n SAR measurement per Apr. 2014 TCBC workshop: SAR testing be conducted on channel with the highest output power and highest channel BW configuration with highest output power.

## 14. SAR Measurement Variability and Uncertainty

In accordance with published RF Exposure KDB procedure 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

| Frequency |     | Modulation | Battery  | Configuration | Conducted Power | Original SAR (mW/g) | Repeated SAR (mW/g) | Largest to Smallest SAR Ratio | Plot No. |
|-----------|-----|------------|----------|---------------|-----------------|---------------------|---------------------|-------------------------------|----------|
| MHz       | Ch. |            |          |               |                 |                     |                     |                               |          |
| 2 462     | 11  | WIFI 2450  | Standard | Rear          | 13.77           | 0.851               | 0.848               | 1.00                          | 9        |

## 15. CONCLUSION

---

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the ANSI/IEEE C95.1 1992.

These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests.

## 16. REFERENCES

---

- [1] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields, July 2001.
- [2] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body from Wireless Communications Devices.
- [3] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio frequency Radiation, Aug. 1996.
- [4] ANSI/IEEE C95.1 - 1991, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 kHz to 100 GHz, New York: IEEE, Aug. 1992
- [5] ANSI/IEEE C95.3 - 1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, 1992.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Poković, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300 MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computer mathematic, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [18] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10 kHz-300 GHz, Jan. 1995.
- [20] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [21] SAR Evaluation of Handsets with Multiple Transmitters and Antennas #648474.
- [22] SAR Measurement Procedure for 802.11 a/b/g Transmitters #KDB 248227.

## Attachment 1. – SAR Test Plots

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Apr. 14, 2014  
Plot No. 1

**DUT: LG-V400; Type: Bar; Serial: #A**

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3797; ConvF(6.75, 6.75, 6.75); Calibrated: 2013-11-29
- Sensor - Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11b Body Rear 11ch 1Mbps/Area Scan (111x181x1):** Measurement grid:  
dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 1.34 mW/g


**802.11b Body Rear 11ch 1Mbps/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  
dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.23 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 2.35 W/kg

**SAR(1 g) = 0.851 mW/g; SAR(10 g) = 0.338 mW/g**

Maximum value of SAR (measured) = 1.43 mW/g



0 dB = 1.43mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 19.5 °C  
Ambient Temperature: 19.7 °C  
Test Date: Apr. 28, 2014  
Plot No. 2

**DUT: LG-V400; Type: Bar; Serial: #A**

Communication System: 2450MHz FCC; Frequency: 2437 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.93$  mho/m;  $\epsilon_r = 52$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3797; ConvF(6.75, 6.75, 6.75); Calibrated: 2013-11-29
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11n Body Rear 6ch 1Mbps/Area Scan (61x81x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 0.555 mW/g


**802.11n Body Rear 6ch 1Mbps/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.41 V/m; Power Drift = -0.108 dB

Peak SAR (extrapolated) = 0.948 W/kg

**SAR(1 g) = 0.349 mW/g; SAR(10 g) = 0.144 mW/g**

Maximum value of SAR (measured) = 0.572 mW/g



0 dB = 0.572mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 21.3 °C  
Ambient Temperature: 21.5 °C  
Test Date: Apr.15, 2014  
Plot No. 3

**DUT: LG-V400; Type: TabletPC; Serial: #1**

Communication System: WIFI 5GHz; Frequency: 5785 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 5785$  MHz;  $\sigma = 6.06$  mho/m;  $\epsilon_r = 46.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(4.23, 4.23, 4.23); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11a body rear 157ch 6Mbps/Area Scan (131x211x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.727 mW/g


**802.11a body rear 157ch 6Mbps/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 1.53 V/m; Power Drift = 0.141 dB

Peak SAR (extrapolated) = 1.27 W/kg

**SAR(1 g) = 0.238 mW/g; SAR(10 g) = 0.074 mW/g**

Maximum value of SAR (measured) = 0.627 mW/g



0 dB = 0.627mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 19.5 °C  
Ambient Temperature: 19.7 °C  
Test Date: Apr. 28, 2014  
Plot No. 4

**DUT: LG-V400; Type: TabletPC; Serial: #1**

Communication System: WIFI 5GHz; Frequency: 5785 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 5785$  MHz;  $\sigma = 6.18$  mho/m;  $\epsilon_r = 47.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3797; ConvF(4.23, 4.23, 4.23); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11n body rear 157ch 6.5Mbps 20MHz Bw/Area Scan (71x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.422 mW/g


**802.11n body rear 157ch 6.5Mbps 20MHz Bw/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 1.65 V/m; Power Drift = -0.179 dB

Peak SAR (extrapolated) = 1.11 W/kg

**SAR(1 g) = 0.152 mW/g; SAR(10 g) = 0.047 mW/g**

Maximum value of SAR (measured) = 0.425 mW/g



0 dB = 0.425mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 19.5 °C  
Ambient Temperature: 19.7 °C  
Test Date: Apr. 28, 2014  
Plot No. 5

**DUT: LG-V400; Type: TabletPC; Serial: #1**

Communication System: WIFI 5GHz; Frequency: 5755 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 5755$  MHz;  $\sigma = 6.14$  mho/m;  $\epsilon_r = 47.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**DASY4 Configuration:**


- Probe: EX3DV4 - SN3797; ConvF(4.23, 4.23, 4.23); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11n body rear 151ch 6.5Mbps 40MHz Bw/Area Scan (71x91x1):**

Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.424 mW/g

**802.11n body rear 151ch 6.5Mbps 40MHz Bw/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 1.47 V/m; Power Drift = 0.171 dB  
Peak SAR (extrapolated) = 0.767 W/kg  
**SAR(1 g) = 0.145 mW/g; SAR(10 g) = 0.045 mW/g**  
Maximum value of SAR (measured) = 0.393 mW/g



0 dB = 0.393mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 21.3 °C  
Ambient Temperature: 21.5 °C  
Test Date: Apr.15, 2014  
Plot No. 6

**DUT: LG-V400; Type: TabletPC; Serial: #1**

Communication System: WIFI 5GHz; Frequency: 5200 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5200 \text{ MHz}$ ;  $\sigma = 5.22 \text{ mho/m}$ ;  $\epsilon_r = 47.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(4.42, 4.42, 4.42); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11a body rear 40ch 6Mbps/Area Scan (131x211x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
Maximum value of SAR (interpolated) = 0.752 mW/g


**802.11a body rear 40ch 6Mbps/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$

Reference Value = 2.16 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 1.45 W/kg

**SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.090 mW/g**

Maximum value of SAR (measured) = 0.765 mW/g



0 dB = 0.765mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 19.5 °C  
Ambient Temperature: 19.7 °C  
Test Date: Apr. 28, 2014  
Plot No. 7

**DUT: LG-V400; Type: TabletPC; Serial: #1**

Communication System: WIFI 5GHz; Frequency: 5200 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5200 \text{ MHz}$ ;  $\sigma = 5.2 \text{ mho/m}$ ;  $\epsilon_r = 48.7$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**DASY4 Configuration:**


- Probe: EX3DV4 - SN3797; ConvF(4.42, 4.42, 4.42); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11n body rear 40ch 6.5Mbps 20MHz BW/Area Scan (71x91x1):**

Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
Maximum value of SAR (interpolated) = 0.714 mW/g

**802.11n body rear 40ch 6.5Mbps 20MHz BW/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$   
Reference Value = 2.74 V/m; Power Drift = -0.156 dB  
Peak SAR (extrapolated) = 1.28 W/kg  
**SAR(1 g) = 0.261 mW/g; SAR(10 g) = 0.075 mW/g**  
Maximum value of SAR (measured) = 0.652 mW/g



0 dB = 0.652mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 19.5 °C  
Ambient Temperature: 19.7 °C  
Test Date: Apr. 28, 2014  
Plot No. 8

**DUT: LG-V400; Type: TabletPC; Serial: #1**


Communication System: WIFI 5GHz; Frequency: 5190 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 5190$  MHz;  $\sigma = 5.19$  mho/m;  $\epsilon_r = 48.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3797; ConvF(4.42, 4.42, 4.42); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11n body rear 38ch 6.5Mbps 40MHz/Area Scan (71x91x1):** Measurement  
grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.542 mW/g

**802.11n body rear 38ch 6.5Mbps 40MHz/Zoom Scan (7x7x7)/Cube 0:**  
Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 2.25 V/m; Power Drift = 0.176 dB  
Peak SAR (extrapolated) = 1.01 W/kg  
**SAR(1 g) = 0.217 mW/g; SAR(10 g) = 0.065 mW/g**  
Maximum value of SAR (measured) = 0.552 mW/g



0 dB = 0.552mW/g

Test Laboratory: HCT CO., LTD  
EUT Type: 2.4/5GHz BT/WiFi Tablet  
Liquid Temperature: 21.1 °C  
Ambient Temperature: 21.3 °C  
Test Date: Apr. 14, 2014  
Plot No. 9

**DUT: LG-V400; Type: Bar; Serial: #A**

Communication System: 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1  
Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 1.99$  mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(6.75, 6.75, 6.75); Calibrated: 2013-11-29
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**802.11b Body Rear 11ch 1Mbps/Area Scan (111x181x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 1.33 mW/g


**802.11b Body Rear 11ch 1Mbps/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.23 V/m; Power Drift = 0.108 dB

Peak SAR (extrapolated) = 2.34 W/kg

**SAR(1 g) = 0.848 mW/g; SAR(10 g) = 0.338 mW/g**

Maximum value of SAR (measured) = 1.42 mW/g



0 dB = 1.42mW/g

## Attachment 2. – Dipole Verification Plots

## ■ Verification Data (2 450 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 21.1 °C  
Test Date: Apr. 14, 2014

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:743**


Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.97$  mho/m;  $\epsilon_r = 52.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(6.75, 6.75, 6.75); Calibrated: 2013-11-29
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**2.45GHz Verification body/Area Scan (81x71x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 7.84 mW/g

**2.45GHz Verification body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
Reference Value = 63.2 V/m; Power Drift = 0.037 dB  
Peak SAR (extrapolated) = 10.6 W/kg  
**SAR(1 g) = 5.02 mW/g; SAR(10 g) = 2.3 mW/g**  
Maximum value of SAR (measured) = 7.74 mW/g



0 dB = 7.74mW/g

## ■ Verification Data (5 200 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 21.3 °C  
Test Date: Apr .15, 2014

**DUT: Dipole 5GHz; Type: D5000V2; Serial: D5000V2 - SN:1107**

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.22$  mho/m;  $\epsilon_r = 47.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(4.42, 4.42, 4.42); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**5..2GHz Verification body 5200MHz/Area Scan (61x71x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 19.3 mW/g


**5..2GHz Verification body 5200MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 60.8 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 32.3 W/kg

**SAR(1 g) = 7.54 mW/g; SAR(10 g) = 2.14 mW/g**

Maximum value of SAR (measured) = 19.4 mW/g



0 dB = 19.4mW/g

## ■ Verification Data (5 300 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 21.3 °C  
Test Date: Apr .15, 2014

**DUT: Dipole 5GHz; Type: D5000V2; Serial: D5000V2 - SN:1107**

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.31$  mho/m;  $\epsilon_r = 47.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(4.17, 4.17, 4.17); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**5.3GHz Verification body 5300MHz/Area Scan (61x71x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 20.0 mW/g



**5.3GHz Verification body 5300MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.1 V/m; Power Drift = 0.023 dB

Peak SAR (extrapolated) = 32.4 W/kg

**SAR(1 g) = 7.58 mW/g; SAR(10 g) = 2.13 mW/g**

Maximum value of SAR (measured) = 19.5 mW/g



0 dB = 19.5mW/g

## ■ Verification Data (5 600 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 21.3 °C  
Test Date: Apr .15, 2014

**DUT: Dipole 5GHz; Type: D5000V2; Serial: D5000V2 - SN:1107**

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.79$  mho/m;  $\epsilon_r = 47.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(3.67, 3.67, 3.67); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**5.6GHz Verification body 5600MHz/Area Scan (61x71x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 21.6 mW/g


**5.6GHz Verification body 5600MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.2 V/m; Power Drift = 0.072 dB

Peak SAR (extrapolated) = 38.7 W/kg

**SAR(1 g) = 8.29 mW/g; SAR(10 g) = 2.34 mW/g**

Maximum value of SAR (measured) = 22.6 mW/g



0 dB = 22.6mW/g

## ■ Verification Data (5 800 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 21.3 °C  
Test Date: Apr .15, 2014

**DUT: Dipole 5GHz; Type: D5000V2; Serial: D5000V2 - SN:1107**


Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.09$  mho/m;  $\epsilon_r = 46.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(4.23, 4.23, 4.23); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**5.8GHz Verification body 5800MHz/Area Scan (61x71x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 19.5 mW/g

**5.8GHz Verification body 5800MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 59.1 V/m; Power Drift = 0.016 dB  
Peak SAR (extrapolated) = 36.5 W/kg  
**SAR(1 g) = 7.3 mW/g; SAR(10 g) = 2.05 mW/g**  
Maximum value of SAR (measured) = 19.9 mW/g



0 dB = 19.9mW/g

## ■ Verification Data for IC (2 450 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 19.5 °C  
Test Date: Apr. 28, 2014

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:743**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 2450 \text{ MHz}$ ;  $\sigma = 1.95 \text{ mho/m}$ ;  $\epsilon_r = 52$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(6.75, 6.75, 6.75); Calibrated: 2013-11-29
- Sensor - Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**2.45GHz Verification body/Area Scan (81x71x1):** Measurement grid:  $dx=12\text{mm}$ ,  $dy=12\text{mm}$   
Maximum value of SAR (interpolated) = 7.92 mW/g



**2.45GHz Verification body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 63.4 V/m; Power Drift = 0.029 dB

Peak SAR (extrapolated) = 10.5 W/kg

**SAR(1 g) = 5.01 mW/g; SAR(10 g) = 2.31 mW/g**

Maximum value of SAR (measured) = 7.74 mW/g



0 dB = 7.74mW/g

## ■ Verification Data for IC (5 200 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 19.5 °C  
Test Date: Apr. 28, 2014

**DUT: Dipole 5GHz; Type: D5000V2; Serial: D5000V2 - SN:1107**

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.2$  mho/m;  $\epsilon_r = 48.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(4.42, 4.42, 4.42); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**5.2GHz Verification body 5200MHz/Area Scan (61x71x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 19.2 mW/g


**5.2GHz Verification body 5200MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 60.8 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 32.1 W/kg

**SAR(1 g) = 7.5 mW/g; SAR(10 g) = 2.13 mW/g**

Maximum value of SAR (measured) = 19.3 mW/g



0 dB = 19.3mW/g

## ■ Verification Data for IC (5 300 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 19.5 °C  
Test Date: Apr. 28, 2014

**DUT: Dipole 5GHz; Type: D5000V2; Serial: D5000V2 - SN:1107**

Communication System: CW; Frequency: 5300 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5300 \text{ MHz}$ ;  $\sigma = 5.37 \text{ mho/m}$ ;  $\epsilon_r = 48.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section  
Measurement Standard: DAS4 (High Precision Assessment)

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(4.17, 4.17, 4.17); Calibrated: 2013-11-29
- Sensor - Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA;

**5.3GHz Verification body 5300MHz/Area Scan (61x71x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
Maximum value of SAR (interpolated) = 21.2 mW/g



**5.3GHz Verification body 5300MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$

Reference Value = 64.2 V/m; Power Drift = 0.039 dB

Peak SAR (extrapolated) = 35.0 W/kg

**SAR(1 g) = 8.18 mW/g; SAR(10 g) = 2.3 mW/g**

Maximum value of SAR (measured) = 21.1 mW/g



0 dB = 21.1mW/g

## ■ Verification Data for IC (5 600 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 19.5 °C  
Test Date: Apr. 28, 2014

**DUT: Dipole 5GHz; Type: D5000V2; Serial: D5000V2 - SN:1107**

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.87$  mho/m;  $\epsilon_r = 47.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(3.67, 3.67, 3.67); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**5.6GHz Verification body 5600MHz/Area Scan (61x71x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 21.8 mW/g



**5.6GHz Verification body 5600MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.5 V/m; Power Drift = -0.010 dB

Peak SAR (extrapolated) = 37.0 W/kg

**SAR(1 g) = 8.38 mW/g; SAR(10 g) = 2.34 mW/g**

Maximum value of SAR (measured) = 22.4 mW/g



0 dB = 22.4mW/g

## ■ Verification Data for IC (5 800 MHz Body)

Test Laboratory: HCT CO., LTD  
Input Power: 100 mW (20 dBm)  
Liquid Temp: 19.5 °C  
Test Date: Apr. 28, 2014

**DUT: Dipole 5GHz; Type: D5000V2; Serial: D5000V2 - SN:1107**


Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1  
Medium parameters used:  $f = 5800 \text{ MHz}$ ;  $\sigma = 6.2 \text{ mho/m}$ ;  $\epsilon_r = 47.1$ ;  $\rho = 1000 \text{ kg/m}^3$   
Phantom section: Flat Section ; Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

DASY4 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(4.23, 4.23, 4.23); Calibrated: 2013-11-29
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2014-03-26
- Phantom: Flat Phantom ELI4.0; Type: QDOVA001BA

**5.8GHz Verification body 5800MHz/Area Scan (61x71x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
Maximum value of SAR (interpolated) = 21.1 mW/g

**5.8GHz Verification body 5800MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=1.4\text{mm}$   
Reference Value = 59.9 V/m; Power Drift = 0.036 dB  
Peak SAR (extrapolated) = 38.1 W/kg  
**SAR(1 g) = 7.76 mW/g; SAR(10 g) = 2.18 mW/g**  
Maximum value of SAR (measured) = 21.0 mW/g



0 dB = 21.0mW/g

## Attachment 3. – Probe Calibration Data

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
S Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client HCT (Dymstec)

Certificate No: EX3-3797\_Nov13

## CALIBRATION CERTIFICATE

Object EX3DV4 - SN:3797

Calibration procedure(s) QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6  
Calibration procedure for dosimetric E-field probes

Calibration date: November 29, 2013

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^{\circ}\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID              | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|-----------------|-----------------------------------|------------------------|
| Power meter E4419B         | GB41293874      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Power sensor E4412A        | MY41498087      | 04-Apr-13 (No. 217-01733)         | Apr-14                 |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 04-Apr-13 (No. 217-01737)         | Apr-14                 |
| Reference 20 dB Attenuator | SN: S5277 (20x) | 04-Apr-13 (No. 217-01735)         | Apr-14                 |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 04-Apr-13 (No. 217-01738)         | Apr-14                 |
| Reference Probe ES3DV2     | SN: 3013        | 28-Dec-12 (No. ES3-3013_Dec12)    | Dec-13                 |
| DAE4                       | SN: 660         | 4-Sep-13 (No. DAE4-660_Sep13)     | Sep-14                 |
| Secondary Standards        | ID              | Check Date (in house)             | Scheduled Check        |
| RF generator HP 8648C      | US3642U01700    | 4-Aug-99 (in house check Apr-13)  | In house check: Apr-15 |
| Network Analyzer HP 8753E  | US37390585      | 18-Oct-01 (in house check Oct-13) | In house check: Oct-14 |

|                                                                                                                 | Name           | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|----------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Jeton Kastrati | Laboratory Technician |           |
| Approved by:                                                                                                    | Katja Pokovic  | Technical Manager     |           |
| Issued: November 30, 2013                                                                                       |                |                       |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |                |                       |           |

Certificate No: EX3-3797\_Nov13

Page 1 of 11

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

**Glossary:**

|                       |                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                   | tissue simulating liquid                                                                                                                          |
| NORM <sub>x,y,z</sub> | sensitivity in free space                                                                                                                         |
| ConvF                 | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                        |
| DCP                   | diode compression point                                                                                                                           |
| CF                    | crest factor (1/duty_cycle) of the RF signal                                                                                                      |
| A, B, C, D            | modulation dependent linearization parameters                                                                                                     |
| Polarization $\phi$   | $\phi$ rotation around probe axis                                                                                                                 |
| Polarization $\theta$ | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle       | information used in DASY system to align probe sensor X to the robot coordinate system                                                            |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

**Methods Applied and Interpretation of Parameters:**

- NORM<sub>x,y,z</sub>:** Assessed for E-field polarization  $\theta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>:** A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle:** The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

Certificate No: EX3-3797\_Nov13

Page 2 of 11

EX3DV4 – SN:3797

November 29, 2013

# Probe EX3DV4

## SN:3797

Manufactured: April 5, 2011  
Calibrated: November 29, 2013

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)

EX3DV4- SN:3797

November 29, 2013

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3797

### Basic Calibration Parameters

|                                                    | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|----------------------------------------------------|----------|----------|----------|-----------|
| Norm ( $\mu\text{V}/(\text{V/m})^2$ ) <sup>A</sup> | 0.63     | 0.58     | 0.57     | ± 10.1 %  |
| DCP (mV) <sup>B</sup>                              | 98.7     | 97.9     | 96.5     |           |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>C</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 135.5    | ±2.7 %                    |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 175.4    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 176.6    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>C</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:3797

November 29, 2013

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3797

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750                  | 41.9                               | 0.89                            | 9.33    | 9.33    | 9.33    | 0.59               | 0.73                    | ± 12.0 %    |
| 835                  | 41.5                               | 0.90                            | 9.04    | 9.04    | 9.04    | 0.71               | 0.66                    | ± 12.0 %    |
| 900                  | 41.5                               | 0.97                            | 8.89    | 8.89    | 8.89    | 0.35               | 0.98                    | ± 12.0 %    |
| 1450                 | 40.5                               | 1.20                            | 8.27    | 8.27    | 8.27    | 0.80               | 0.68                    | ± 12.0 %    |
| 1750                 | 40.1                               | 1.37                            | 8.02    | 8.02    | 8.02    | 0.69               | 0.62                    | ± 12.0 %    |
| 1900                 | 40.0                               | 1.40                            | 7.73    | 7.73    | 7.73    | 0.64               | 0.65                    | ± 12.0 %    |
| 1950                 | 40.0                               | 1.40                            | 7.48    | 7.48    | 7.48    | 0.60               | 0.66                    | ± 12.0 %    |
| 2300                 | 39.5                               | 1.67                            | 7.27    | 7.27    | 7.27    | 0.31               | 0.92                    | ± 12.0 %    |
| 2450                 | 39.2                               | 1.80                            | 6.94    | 6.94    | 6.94    | 0.51               | 0.71                    | ± 12.0 %    |
| 2600                 | 39.0                               | 1.96                            | 6.76    | 6.76    | 6.76    | 0.34               | 0.89                    | ± 12.0 %    |
| 5200                 | 36.0                               | 4.66                            | 5.00    | 5.00    | 5.00    | 0.33               | 1.80                    | ± 13.1 %    |
| 5300                 | 35.9                               | 4.76                            | 4.77    | 4.77    | 4.77    | 0.35               | 1.80                    | ± 13.1 %    |
| 5500                 | 35.6                               | 4.96                            | 4.70    | 4.70    | 4.70    | 0.37               | 1.80                    | ± 13.1 %    |
| 5600                 | 35.5                               | 5.07                            | 4.43    | 4.43    | 4.43    | 0.40               | 1.80                    | ± 13.1 %    |
| 5800                 | 35.3                               | 5.27                            | 4.64    | 4.64    | 4.64    | 0.35               | 1.80                    | ± 13.1 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3797

November 29, 2013

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3797

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 750                  | 55.5                               | 0.96                            | 9.03    | 9.03    | 9.03    | 0.53               | 0.76                    | ± 12.0 %    |
| 835                  | 55.2                               | 0.97                            | 9.03    | 9.03    | 9.03    | 0.43               | 0.87                    | ± 12.0 %    |
| 900                  | 55.0                               | 1.05                            | 8.73    | 8.73    | 8.73    | 0.33               | 1.01                    | ± 12.0 %    |
| 1750                 | 53.4                               | 1.49                            | 7.61    | 7.61    | 7.61    | 0.31               | 1.20                    | ± 12.0 %    |
| 1900                 | 53.3                               | 1.52                            | 7.14    | 7.14    | 7.14    | 0.28               | 1.17                    | ± 12.0 %    |
| 1950                 | 53.3                               | 1.52                            | 7.33    | 7.33    | 7.33    | 0.27               | 1.11                    | ± 12.0 %    |
| 2450                 | 52.7                               | 1.95                            | 6.75    | 6.75    | 6.75    | 0.80               | 0.59                    | ± 12.0 %    |
| 2600                 | 52.5                               | 2.16                            | 6.45    | 6.45    | 6.45    | 0.80               | 0.60                    | ± 12.0 %    |
| 5200                 | 49.0                               | 5.30                            | 4.42    | 4.42    | 4.42    | 0.42               | 1.90                    | ± 13.1 %    |
| 5300                 | 48.9                               | 5.42                            | 4.17    | 4.17    | 4.17    | 0.45               | 1.90                    | ± 13.1 %    |
| 5500                 | 48.6                               | 5.65                            | 4.01    | 4.01    | 4.01    | 0.45               | 1.90                    | ± 13.1 %    |
| 5600                 | 48.5                               | 5.77                            | 3.67    | 3.67    | 3.67    | 0.55               | 1.90                    | ± 13.1 %    |
| 5800                 | 48.2                               | 6.00                            | 4.23    | 4.23    | 4.23    | 0.45               | 1.90                    | ± 13.1 %    |

<sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.


<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3797

November 29, 2013

### Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

EX3DV4- SN:3797

November 29, 2013

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$





Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  (k=2)

EX3DV4- SN:3797

November 29, 2013

### Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell, $f = 900 \text{ MHz}$ )




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )


EX3DV4-- SN:3797

November 29, 2013

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid Error ( $\phi$ , $\theta$ ), f = 900 MHz



EX3DV4- SN:3797

November 29, 2013

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3797****Other Probe Parameters**

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -111.7     |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 2 mm       |

## Attachment 4. – Dipole Calibration Data

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **HCT (Dymstec)**

Certificate No: **D2450V2-743\_Aug13**

## CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 743**

Calibration procedure(s) **QA CAL-05.v9**  
Calibration procedure for dipole validation kits above 700 MHz

Calibration date: **August 23, 2013**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility; environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|-----------------------------|--------------------|-----------------------------------|------------------------|
| Power meter EPM-442A        | GB37480704         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Power sensor HP 8481A       | US37292783         | 01-Nov-12 (No. 217-01640)         | Oct-13                 |
| Reference 20 dB Attenuator  | SN: 5058 (20K)     | 04-Apr-13 (No. 217-01736)         | Apr-14                 |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)         | Apr-14                 |
| Reference Probe ES3DV3      | SN: 3205           | 28-Dec-12 (No. ES3-3205_Dec12)    | Dec-13                 |
| DAE4                        | SN: 601            | 25-Apr-13 (No. DAE4-601_Apr13)    | Apr-14                 |
| Secondary Standards         | ID #               | Check Date (in house)             | Scheduled Check        |
| Power sensor HP 8481A       | MY41092317         | 18-Oct-02 (in house check Oct-11) | In house check: Oct-13 |
| RF generator R&S SMT-06     | 109005             | 04-Aug-99 (in house check Oct-11) | In house check: Oct-13 |
| Network Analyzer HP 8753E   | US37390585 S4206   | 18-Oct-01 (in house check Oct-12) | In house check: Oct-13 |

|                |                        |                                   |               |
|----------------|------------------------|-----------------------------------|---------------|
| Calibrated by: | Name<br>Jeton Kastrati | Function<br>Laboratory Technician | Signature<br> |
| Approved by:   | Katja Pokovic          | Technical Manager                 |               |

Issued: August 23, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D2450V2-743\_Aug13

Page 1 of 8

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                        |             |
|------------------------------|------------------------|-------------|
| DASY Version                 | DASY5                  | V52.8.7     |
| Extrapolation                | Advanced Extrapolation |             |
| Phantom                      | Modular Flat Phantom   |             |
| Distance Dipole Center - TSL | 10 mm                  | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm      |             |
| Frequency                    | 2450 MHz $\pm$ 1 MHz   |             |

### Head TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 39.2           | 1.80 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 37.8 $\pm$ 6 % | 1.80 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Head TSL

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL   | Condition          |                              |
| SAR measured                                            | 250 mW input power | 13.3 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 52.8 W/kg $\pm$ 17.0 % (k=2) |
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 6.18 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 24.6 W/kg $\pm$ 16.5 % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Body TSL parameters             | 22.0 °C             | 52.7           | 1.95 mho/m           |
| Measured Body TSL parameters            | (22.0 $\pm$ 0.2) °C | 50.6 $\pm$ 6 % | 2.03 mho/m $\pm$ 6 % |
| Body TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Body TSL

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL   | Condition          |                              |
| SAR measured                                            | 250 mW input power | 13.0 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 50.5 W/kg $\pm$ 17.0 % (k=2) |
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                              |
| SAR measured                                            | 250 mW input power | 6.01 W/kg                    |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 23.6 W/kg $\pm$ 16.5 % (k=2) |

## Appendix

### Antenna Parameters with Head TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 53.9 $\Omega$ + 4.2 j $\Omega$ |
| Return Loss                          | - 25.1 dB                      |

### Antenna Parameters with Body TSL

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 50.0 $\Omega$ + 5.5 j $\Omega$ |
| Return Loss                          | - 25.2 dB                      |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.159 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                   |
|-----------------|-------------------|
| Manufactured by | SPEAG             |
| Manufactured on | December 01, 2003 |

## DASY5 Validation Report for Head TSL

Date: 22.08.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 743**

Communication System: UID 0 - CW ; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.8$  S/m;  $\epsilon_r = 37.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.52, 4.52, 4.52); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 100.4 V/m; Power Drift = 0.06 dB


Peak SAR (extrapolated) = 27.8 W/kg

**SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.18 W/kg**

Maximum value of SAR (measured) = 16.9 W/kg



Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 23.08.2013

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 743**

Communication System: UID 0 - CW ; Frequency: 2450 MHz

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.03$  S/m;  $\epsilon_r = 50.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.42, 4.42, 4.42); Calibrated: 28.12.2012;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93,835 V/m; Power Drift = 0,06 dB


Peak SAR (extrapolated) = 27.3 W/kg

SAR(1 g) = 13 W/kg; SAR(10 g) = 6.01 W/kg

Maximum value of SAR (measured) = 16.8 W/kg



# Impedance Measurement Plot for Body TSL



Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: SCS 108

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Client HCT (Dymstec)

Certificate No: D5GHzV2-1107\_Jan14

## CALIBRATION CERTIFICATE

Object D5GHzV2 - SN: 1107

Calibration procedure(s) QA CAL-22.v2  
Calibration procedure for dipole validation kits between 3-6 GHz

Calibration date: January 27, 2014

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Certificate No.)     | Scheduled Calibration |
|-----------------------------|--------------------|--------------------------------|-----------------------|
| Power meter EPM-442A        | GB37480704         | 09-Oct-13 (No. 217-01827)      | Oct-14                |
| Power sensor HP 8481A       | US37292783         | 09-Oct-13 (No. 217-01827)      | Oct-14                |
| Power sensor HP 8481A       | MY41092317         | 09-Oct-13 (No. 217-01828)      | Oct-14                |
| Reference 20 dB Attenuator  | SN: 5058 (20k)     | 04-Apr-13 (No. 217-01736)      | Apr-14                |
| Type-N mismatch combination | SN: 5047.3 / 06327 | 04-Apr-13 (No. 217-01739)      | Apr-14                |
| Reference Probe EX3DV4      | SN: 3503           | 30-Dec-13 (No. EX3-3503_Dec13) | Dec-14                |
| DAE4                        | SN: 601            | 25-Apr-13 (No. DAE4-601_Apr13) | Apr-14                |

| Secondary Standards       | ID #             | Check Date (in house)             | Scheduled Check        |
|---------------------------|------------------|-----------------------------------|------------------------|
| RF generator R&S SMT-06   | 100005           | 04-Aug-99 (in house check Oct-13) | In house check: Oct-16 |
| Network Analyzer HP 8753E | US37390585 S4206 | 18-Oct-01 (in house check Oct-13) | In house check: Oct-14 |

|                |                        |                                   |               |
|----------------|------------------------|-----------------------------------|---------------|
| Calibrated by: | Name<br>Israe El-Naouq | Function<br>Laboratory Technician | Signature<br> |
| Approved by:   | Katja Pokovic          | Technical Manager                 |               |

Issued: January 27, 2014

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D5GHzV2-1107\_Jan14

Page 1 of 16

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accreditation No.: **SCS 108**

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

**Glossary:**

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

**Calibration is Performed According to the Following Standards:**

- IEC 62209-2, "Evaluation of Human Exposure to Radio Frequency Fields from Handheld and Body-Mounted Wireless Communication Devices in the Frequency Range of 30 MHz to 6 GHz: Human models, Instrumentation, and Procedures"; Part 2: "Procedure to determine the Specific Absorption Rate (SAR) for including accessories and multiple transmitters", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"
- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013

**Additional Documentation:**

- DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                                                                                                                      |                                  |
|------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------|
| DASY Version                 | DASY5                                                                                                                | V52.8.7                          |
| Extrapolation                | Advanced Extrapolation                                                                                               |                                  |
| Phantom                      | Modular Flat Phantom V5.0                                                                                            |                                  |
| Distance Dipole Center - TSL | 10 mm                                                                                                                | with Spacer                      |
| Zoom Scan Resolution         | dx, dy = 4.0 mm, dz = 1.4 mm                                                                                         | Graded Ratio = 1.4 (Z direction) |
| Frequency                    | 5200 MHz $\pm$ 1 MHz<br>5300 MHz $\pm$ 1 MHz<br>5500 MHz $\pm$ 1 MHz<br>5600 MHz $\pm$ 1 MHz<br>5800 MHz $\pm$ 1 MHz |                                  |

### Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

|                                         | Temperature         | Permittivity   | Conductivity         |
|-----------------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters             | 22.0 °C             | 36.0           | 4.66 mho/m           |
| Measured Head TSL parameters            | (22.0 $\pm$ 0.2) °C | 35.0 $\pm$ 6 % | 4.45 mho/m $\pm$ 6 % |
| Head TSL temperature change during test | < 0.5 °C            | ----           | ----                 |

### SAR result with Head TSL at 5200 MHz

|                                                       |                    |                              |
|-------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                              |
| SAR measured                                          | 100 mW input power | 7.83 W/kg                    |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 77.8 W/kg $\pm$ 19.9 % (k=2) |

|                                                         |                    |                              |
|---------------------------------------------------------|--------------------|------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                              |
| SAR measured                                            | 100 mW input power | 2.25 W/kg                    |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 22.3 W/kg $\pm$ 19.5 % (k=2) |

#### Head TSL parameters at 5300 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.9         | 4.76 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.9 ± 6 %   | 4.54 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

#### SAR result with Head TSL at 5300 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                            |
|-------------------------------------------------------|--------------------|----------------------------|
| SAR measured                                          | 100 mW input power | 8.35 W/kg                  |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 82.9 W / kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.41 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.9 W/kg ± 19.5 % (k=2) |

#### Head TSL parameters at 5500 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.6         | 4.96 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.6 ± 6 %   | 4.74 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

#### SAR result with Head TSL at 5500 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.47 W/kg                |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 84.0 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.42 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 24.0 W/kg ± 19.5 % (k=2) |

#### Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.5         | 5.07 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.5 ± 6 %   | 4.86 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

#### SAR result with Head TSL at 5600 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.37 W/kg                |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 83.0 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.39 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 23.7 W/kg ± 19.5 % (k=2) |

#### Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 35.3         | 5.27 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 34.2 ± 6 %   | 5.07 mho/m ± 6 % |
| Head TSL temperature change during test | < 0.5 °C        | ----         | ----             |

#### SAR result with Head TSL at 5800 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.01 W/kg                |
| SAR for nominal Head TSL parameters                   | normalized to 1W   | 79.4 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.28 W/kg                |
| SAR for nominal Head TSL parameters                     | normalized to 1W   | 22.6 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5200 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 49.0         | 5.30 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.3 ± 6 %   | 5.44 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5200 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 7.52 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 74.7 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.10 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 20.8 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5300 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.9         | 5.42 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 47.2 ± 6 %   | 5.57 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ---          | ---              |

### SAR result with Body TSL at 5300 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 7.63 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 75.8 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.14 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.2 W/kg ± 19.5 % (k=2) |

#### Body TSL parameters at 5500 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.6         | 5.65 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.8 ± 6 %   | 5.84 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

#### SAR result with Body TSL at 5500 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 7.96 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 79.1 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.21 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 21.9 W/kg ± 19.5 % (k=2) |

#### Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.5         | 5.77 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.6 ± 6 %   | 5.98 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

#### SAR result with Body TSL at 5600 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 8.07 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 80.2 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.24 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 22.2 W/kg ± 19.5 % (k=2) |

### Body TSL parameters at 5800 MHz

The following parameters and calculations were applied.

|                                         | Temperature     | Permittivity | Conductivity     |
|-----------------------------------------|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 48.2         | 6.00 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 46.3 ± 6 %   | 6.23 mho/m ± 6 % |
| Body TSL temperature change during test | < 0.5 °C        | ----         | ----             |

### SAR result with Body TSL at 5800 MHz

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                          |
|-------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                          | 100 mW input power | 7.49 W/kg                |
| SAR for nominal Body TSL parameters                   | normalized to 1W   | 74.4 W/kg ± 19.9 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                          |
|---------------------------------------------------------|--------------------|--------------------------|
| SAR measured                                            | 100 mW input power | 2.07 W/kg                |
| SAR for nominal Body TSL parameters                     | normalized to 1W   | 20.5 W/kg ± 19.5 % (k=2) |

## Appendix

### Antenna Parameters with Head TSL at 5200 MHz

|                                      |                                 |
|--------------------------------------|---------------------------------|
| Impedance, transformed to feed point | 48.9 $\Omega$ - 10.5 j $\Omega$ |
| Return Loss                          | - 19.5 dB                       |

### Antenna Parameters with Head TSL at 5300 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.2 $\Omega$ - 7.4 j $\Omega$ |
| Return Loss                          | - 22.6 dB                      |

### Antenna Parameters with Head TSL at 5500 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.0 $\Omega$ - 5.4 j $\Omega$ |
| Return Loss                          | - 25.3 dB                      |

### Antenna Parameters with Head TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 53.7 $\Omega$ - 5.7 j $\Omega$ |
| Return Loss                          | - 23.7 dB                      |

### Antenna Parameters with Head TSL at 5800 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 55.0 $\Omega$ - 5.8 j $\Omega$ |
| Return Loss                          | - 22.8 dB                      |

### Antenna Parameters with Body TSL at 5200 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.2 $\Omega$ - 9.7 j $\Omega$ |
| Return Loss                          | - 20.2 dB                      |

### Antenna Parameters with Body TSL at 5300 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 49.6 $\Omega$ - 6.7 j $\Omega$ |
| Return Loss                          | - 23.5 dB                      |

### Antenna Parameters with Body TSL at 5500 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 51.0 $\Omega$ - 4.7 j $\Omega$ |
| Return Loss                          | - 26.5 dB                      |

#### Antenna Parameters with Body TSL at 5600 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 54.6 $\Omega$ - 4.6 j $\Omega$ |
| Return Loss                          | - 24.1 dB                      |

#### Antenna Parameters with Body TSL at 5800 MHz

|                                      |                                |
|--------------------------------------|--------------------------------|
| Impedance, transformed to feed point | 56.1 $\Omega$ - 4.2 j $\Omega$ |
| Return Loss                          | - 23.1 dB                      |

#### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.196 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

#### Additional EUT Data

|                 |                |
|-----------------|----------------|
| Manufactured by | SPEAG          |
| Manufactured on | March 11, 2011 |

## DASY5 Validation Report for Head TSL

Date: 27.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1107**

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz  
Medium parameters used:  $f = 5200$  MHz;  $\sigma = 4.45$  S/m;  $\epsilon_r = 35$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5300$  MHz;  $\sigma = 4.54$  S/m;  $\epsilon_r = 34.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5500$  MHz;  $\sigma = 4.74$  S/m;  $\epsilon_r = 34.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.86$  S/m;  $\epsilon_r = 34.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5800$  MHz;  $\sigma = 5.07$  S/m;  $\epsilon_r = 34.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
Phantom section: Flat Section  
Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.52, 5.52, 5.52); Calibrated: 30.12.2013, ConvF(5.2, 5.2, 5.2); Calibrated: 30.12.2013, ConvF(5.01, 5.01, 5.01); Calibrated: 30.12.2013, ConvF(4.86, 4.86, 4.86); Calibrated: 30.12.2013, ConvF(4.91, 4.91, 4.91); Calibrated: 30.12.2013;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan,

**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.171 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 28.2 W/kg

**SAR(1 g) = 7.83 W/kg; SAR(10 g) = 2.25 W/kg**

Maximum value of SAR (measured) = 17.8 W/kg

### Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan,

**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 64.166 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 31.1 W/kg

**SAR(1 g) = 8.35 W/kg; SAR(10 g) = 2.41 W/kg**

Maximum value of SAR (measured) = 19.3 W/kg

### Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan,

**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.499 V/m; Power Drift = 0.08 dB


Peak SAR (extrapolated) = 32.9 W/kg

**SAR(1 g) = 8.47 W/kg; SAR(10 g) = 2.42 W/kg**


Maximum value of SAR (measured) = 19.7 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 62.691 V/m; Power Drift = 0.05 dB  
Peak SAR (extrapolated) = 32.8 W/kg  
SAR(1 g) = 8.37 W/kg; SAR(10 g) = 2.39 W/kg

**Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 60.600 V/m; Power Drift = 0.07 dB  
Peak SAR (extrapolated) = 33.0 W/kg  
SAR(1 g) = 8.01 W/kg; SAR(10 g) = 2.28 W/kg



# Impedance Measurement Plot for Head TSL



## DASY5 Validation Report for Body TSL

Date: 24.01.2014

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 5GHz; Type: D5GHzV2; Serial: D5GHzV2 - SN: 1107**

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 5.44$  S/m;  $\epsilon_r = 47.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.57$  S/m;  $\epsilon_r = 47.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5500$  MHz;  $\sigma = 5.84$  S/m;  $\epsilon_r = 46.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.98$  S/m;  $\epsilon_r = 46.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>, Medium parameters used:  $f = 5800$  MHz;  $\sigma = 6.23$  S/m;  $\epsilon_r = 46.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.01, 5.01, 5.01); Calibrated: 30.12.2013, ConvF(4.76, 4.76, 4.76); Calibrated: 30.12.2013, ConvF(4.52, 4.52, 4.52); Calibrated: 30.12.2013, ConvF(4.3, 4.3, 4.3); Calibrated: 30.12.2013, ConvF(4.47, 4.47, 4.47); Calibrated: 30.12.2013;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 25.04.2013
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- DASY52 52.8.7(1137); SEMCAD X 14.6.10(7164)

### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan,

**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.992 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 29.6 W/kg

**SAR(1 g) = 7.52 W/kg; SAR(10 g) = 2.1 W/kg**

Maximum value of SAR (measured) = 17.3 W/kg

### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan,

**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.567 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 31.0 W/kg

**SAR(1 g) = 7.63 W/kg; SAR(10 g) = 2.14 W/kg**

Maximum value of SAR (measured) = 17.8 W/kg

### Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan,

**dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 58.552 V/m; Power Drift = -0.01 dB


Peak SAR (extrapolated) = 34.3 W/kg

**SAR(1 g) = 7.96 W/kg; SAR(10 g) = 2.21 W/kg**

Maximum value of SAR (measured) = 18.9 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 58.338 V/m; Power Drift = -0.01 dB  
Peak SAR (extrapolated) = 35.7 W/kg  
**SAR(1 g) = 8.07 W/kg; SAR(10 g) = 2.24 W/kg**  
Maximum value of SAR (measured) = 19.4 W/kg

**Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm  
Reference Value = 55.156 V/m; Power Drift = -0.02 dB  
Peak SAR (extrapolated) = 34.8 W/kg  
**SAR(1 g) = 7.49 W/kg; SAR(10 g) = 2.07 W/kg**  
Maximum value of SAR (measured) = 18.2 W/kg



### Impedance Measurement Plot for Body TSL

