



SAR EVALUATION REPORT

Applicant Name:
LG Electronics U.S.A., Inc.
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:
09/18/2020
Test Site/Location:
PCTEST, Columbia, MD, USA
Document Serial No.:
1M2009170147-02.ZNF

FCC ID: ZNFV600VM

APPLICANT: LG ELECTRONICS U.S.A., INC.

DUT Type: Portable Handset
Application Type: Class II Permissive Change
FCC Rule Part(s): CFR §2.1093
Model: LM-V600VM
Additional Model(s): LMV600VM, V600VM, LM-V600QM5, LMV600QM5, V600QM5, LM-V600QM6, LMV600QM6, V600QM6
Permissive Change(s): Adding ENDC and LTE-CA Downlink Only Operations
Date of Original Certification 02/28/2020

Note: The following test data was evaluated for the current test report. Please refer to RF Exposure Technical Report (S/N: 1M1912300227-01-R2.ZNF& 1M1911250199-01-R2.ZNF) for original compliance evaluation.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.4 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Orlanez
President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: ZNFV600VM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset	Page 1 of 11	

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	5
3	FCC MEASUREMENT PROCEDURES.....	6
4	RF CONDUCTED POWERS	8
5	EQUIPMENT LIST	9
6	REFERENCES	10

FCC ID: ZNFV600VM	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset		Page 2 of 11

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
Cell. CDMA/EVDO	Voice/Data	824.70 - 848.31 MHz
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 12	Voice/Data	699.7 - 715.3 MHz
LTE Band 13	Voice/Data	779.5 - 784.5 MHz
LTE Band 14	Voice/Data	790.5 - 795.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 30	Voice/Data	2307.5 - 2312.5 MHz
LTE Band 48	Voice/Data	3552.5 - 3697.5 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
NR Band n5	Data	826.5 - 846.5 MHz
NR Band n66	Data	1712.5 - 1777.5 MHz
NR Band n2	Data	1852.5 - 1907.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2462 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
NR Band n260	Data	37000 - 40000 MHz
NR Band n261	Data	27500 - 28350 MHz
WMC	Data	500 Hz - 4 kHz

1.2 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. See RF Exposure Technical Report S/N: 1M1912300227-01-R2.ZNF & 1M1911250199-01-R2.ZNF for complete maximum and nominal output power specifications.

FCC ID: ZNFV600VM	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset		Page 3 of 11

1.2.1 Maximum Output Power

Mode / Band		Modulated Average Output Power (in dBm)	
		DSI = 1, 6, 7 (Head, Body-worn, or Phablet Max)	DSI = 5 (Hotspot); DSI = 8 (Phablet Reduced)
LTE FDD Band 13	Max allowed power	25.5	25.5
	Nominal	25.0	25.0
LTE FDD Band 66	Max allowed power	25.2	22.7
	Nominal	24.7	22.2

1.3 Miscellaneous SAR Test Considerations

This device supports LTE Carrier Aggregation (CA) in the downlink. All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for downlink only LTE CA operations was not needed since the maximum average output power in downlink only LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive. See RF Exposure Technical Report S/N: 1M1912300227-01-R2.ZNF & 1M1911250199-01-R2.ZNF for SAR compliance evaluation and complete RF conducted output power measurements.

1.4 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 941225 D05v02r04, D05Av01r02 (4G)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- April 2018 TCB Workshop Notes (LTE Carrier Aggregation)

FCC ID: ZNFV600VM	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset	Page 4 of 11	

LTE Information					
Form Factor	Portable Handset				
Frequency Range of each LTE transmission band	LTE Band 12 (699.7 - 715.3 MHz)				
	LTE Band 13 (779.5 - 784.5 MHz)				
	LTE Band 14 (790.5 - 795.5 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 30 (2307.5 - 2312.5 MHz)				
	LTE Band 48 (3552.5 - 3697.5 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
Channel Bandwidths	LTE Band 12: 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 13: 5 MHz, 10 MHz				
	LTE Band 14: 5 MHz, 10 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 30: 5 MHz, 10 MHz				
	LTE Band 48: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 12: 1.4 MHz	699.7 (23017)		707.5 (23095)	715.3 (23173)	
LTE Band 12: 3 MHz	700.5 (23025)		707.5 (23095)	714.5 (23165)	
LTE Band 12: 5 MHz	701.5 (23035)		707.5 (23095)	713.5 (23155)	
LTE Band 12: 10 MHz	704 (23060)		707.5 (23095)	711 (23130)	
LTE Band 13: 5 MHz	779.5 (23205)		782 (23230)	784.5 (23255)	
LTE Band 13: 10 MHz	N/A		782 (23230)	N/A	
LTE Band 14: 5 MHz	790.5 (23305)		793 (23330)	795.5 (23355)	
LTE Band 14: 10 MHz	N/A		793 (23330)	N/A	
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)		836.5 (20525)	848.3 (20643)	
LTE Band 5 (Cell): 3 MHz	825.5 (20415)		836.5 (20525)	847.5 (20635)	
LTE Band 5 (Cell): 5 MHz	826.5 (20425)		836.5 (20525)	846.5 (20625)	
LTE Band 5 (Cell): 10 MHz	829 (20450)		836.5 (20525)	844 (20600)	
LTE Band 66 (AWS): 1.4 MHz	1710.7 (131979)		1745 (132322)	1779.3 (132665)	
LTE Band 66 (AWS): 3 MHz	1711.5 (131987)		1745 (132322)	1778.5 (132657)	
LTE Band 66 (AWS): 5 MHz	1712.5 (131997)		1745 (132322)	1777.5 (132647)	
LTE Band 66 (AWS): 10 MHz	1715 (132022)		1745 (132322)	1775 (132622)	
LTE Band 66 (AWS): 15 MHz	1717.5 (132047)		1745 (132322)	1772.5 (132597)	
LTE Band 66 (AWS): 20 MHz	1720 (132072)		1745 (132322)	1770 (132572)	
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)		1732.5 (20175)	1754.3 (20393)	
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)		1732.5 (20175)	1753.5 (20385)	
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)		1732.5 (20175)	1752.5 (20375)	
LTE Band 4 (AWS): 10 MHz	1715 (20000)		1732.5 (20175)	1750 (20350)	
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)		1732.5 (20175)	1747.5 (20325)	
LTE Band 4 (AWS): 20 MHz	1720 (20050)		1732.5 (20175)	1745 (20300)	
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)		1880 (18900)	1909.3 (19193)	
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)		1880 (18900)	1908.5 (19185)	
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)		1880 (18900)	1907.5 (19175)	
LTE Band 2 (PCS): 10 MHz	1855 (18650)		1880 (18900)	1905 (19150)	
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)		1880 (18900)	1902.5 (19125)	
LTE Band 2 (PCS): 20 MHz	1860 (18700)		1880 (18900)	1900 (19100)	
LTE Band 30: 5 MHz	2307.5 (27685)		2310 (27710)	2312.5 (27735)	
LTE Band 30: 10 MHz	N/A		2310 (27710)	N/A	
LTE Band 48: 5 MHz	3552.5 (55265)	3600.8 (55748)	N/A	3649.2 (56232)	3697.5 (56715)
LTE Band 48: 10 MHz	3555 (55290)	3601.7 (55757)	N/A	3648.3 (56223)	3695 (56690)
LTE Band 48: 15 MHz	3557.5 (55315)	3602.5 (55765)	N/A	3647.5 (56215)	3692.5 (56665)
LTE Band 48: 20 MHz	3560 (55340)	3603.3 (55773)	N/A	3646.7 (56207)	3690 (56640)
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	DL UE Cat 20, UL UE Cat 18				
Modulations Supported in UL	QPSK, 16QAM, 64QAM, 256QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
EN-DC Carrier Aggregation Possible Combinations	The technical description includes all the possible carrier aggregation combinations				
LTE Additional Information	This device does not support full CA features on 3GPP Release 15. It supports carrier aggregation, downlink MIMO, LAA features as shown in Section 4. All uplink communications are identical to the Release 8 Specifications. Uplink communications are done on the PCC. The following LTE Release 15 Features are not supported: Relay, HetNet, Enhanced MIMO, eICIC, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: ZNFV600VM		SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset	Page 5 of 11	

3

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

3.1 Downlink Only Carrier Aggregation

Conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band. Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for downlink only carrier aggregation configurations when the average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive.

3.2 LTE Downlink Only Carrier Aggregation Test Reduction

SAR test exclusion for LTE downlink Carrier Aggregation is determined by power measurements according to the number of component carriers (CCs) supported by the product implementation. Per April 2018 TCBC Workshop Notes, the following test reduction methodology was applied to determine the combinations required for conducted power measurements.

LTE DLCA Test Reduction Methodology:

- The supported combinations were arranged by the number of component carriers in columns.
- Any limitations on the PCC or SCC for each combination were identified alongside the combination (e.g. CA_2A-2A-4A-12A, but B12 can only be configured as a SCC).
- Power measurements were performed for "supersets" (LTE CA combinations with multiple components carriers) and any "subsets" (LTE CA combinations with fewer component carriers) that were not completely covered by the supersets.
- Only subsets that have the exact same components as a superset were excluded for measurement.
- When there were certain restrictions on component carriers that existed in the superset that were not applied for the subset, the subset configuration was additionally evaluated.
- Both inter-band and intra-band downlink carrier aggregation scenarios were considered.
-

Table 3-1 – Example of Exclusion Table for SISO Configurations

Supplemental Clinical Study (SCS)						Revision	Compliance Corrected By Measurement Support	Supplemental Clinical Study (SCS)						Revision	Compliance Corrected By Measurement Support		
Index	SCC	CC1	CC2	CC3	CC4			Index	SCC	CC1	CC2	CC3	CC4			Index	SCC
CC1-41	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-44	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-47	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-42	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-45	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-48	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-43	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-46	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-49	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-44	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-47	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-50	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-45	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-48	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-51	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-46	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-49	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-52	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-47	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-50	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-53	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-48	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-51	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-54	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-49	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-52	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-55	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-50	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-53	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-56	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-51	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-54	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-57	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-52	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-55	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-58	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-53	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-56	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-59	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-54	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-57	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-60	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-55	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-58	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-61	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-56	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-59	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-62	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-57	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-60	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-63	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-58	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-61	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-64	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-59	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-62	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-65	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-60	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-63	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-66	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-61	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-64	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-67	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-62	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-65	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-68	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-63	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-66	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-69	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-64	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-67	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-70	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-65	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-68	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-71	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-66	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-69	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-72	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-67	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-70	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-73	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-68	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-71	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-74	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-69	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-72	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-75	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-70	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-73	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-76	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-71	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-74	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-77	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-72	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-75	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-78	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-73	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-76	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-79	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-74	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-77	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-80	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-75	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-78	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-81	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-76	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-79	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-82	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-77	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-80	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-83	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-78	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-81	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-84	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-79	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-82	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-85	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-80	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-83	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-86	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-81	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-84	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-87	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-82	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-85	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-88	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-83	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-86	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-89	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-84	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-87	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-90	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-85	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-88	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-91	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-86	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-89	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-92	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-87	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-90	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-93	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-88	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-91	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-94	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-89	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-92	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-95	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-90	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-93	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-96	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-91	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-94	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-97	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-92	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-95	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-98	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-93	CC-1A-20-004	5/15/15/20	5/15/15/20			CC1-96	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20		CC1-99	CC-1A-20-004	5/15/15/20	5/15/15/20	5/15/15/20	5/15/15/20
CC1-94	CC-1A-20-004																

FCC ID: ZNFB600VM	 PCTEST Proud to be part of the element		 LG	Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset	Page 6 of 11	

3.3 LTE Downlink Only Carrier Aggregation Test Selection and Setup

SAR test exclusion for LTE downlink Carrier Aggregation is determined by power measurements according to the number component carriers (CCs) supported by the product implementation. For those configurations required by April 2018 TCBC Workshop Notes, conducted power measurements with LTE Carrier Aggregation (CA) (downlink only) active are made in accordance to KDB Publication 941225 D05Av01r02. The RRC connection is only handled by one cell, the primary component carrier (PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds secondary component carrier(s) (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to specifications when downlink carrier aggregation is inactive on the PCC. Additional conducted output powers are measured with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation, and RB combinations in each frequency band.

Per FCC KDB Publication 941225 D05Av01r02, no SAR measurements are required for carrier aggregation configurations when the maximum average output power with downlink only carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink only carrier aggregation inactive. All bands required for SAR testing per FCC KDB procedures were considered. Based on the measured maximum powers below, no additional SAR tests were required for DLCA SAR configurations.

General PCC and SCC configuration selection procedure

- PCC uplink channel, channel bandwidth, modulation and RB configurations were selected based on section C)3)b)ii) of KDB 941225 D05 V01r02. The downlink PCC channel was paired with the selected PCC uplink channel according to normal configurations without carrier aggregation.
- To maximize aggregated bandwidth, highest channel bandwidth available for that CA combination was selected for SCC. For inter-band CA, the SCC downlink channels were selected near the middle of their transmission bands. For contiguous intra-band CA, the downlink channel spacing between the component carriers was set to multiple of 300 kHz less than the nominal channel spacing defined in section 5.4.1A of 3GPP TS 36.521. For non-contiguous intra-band CA, the downlink channel spacing between the component carriers was set to be larger than the nominal channel spacing and provided maximum separation between the component carriers.
- All selected PCC and SCC(s) remained fully within the uplink/downlink transmission band of the respective component carrier.




Figure 3-1
DL CA with DL 4x4 MIMO Power Measurement Setup

FCC ID: ZNFV600VM	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset	Page 7 of 11	

4 RF CONDUCTED POWERS

4.1 LTE Downlink Carrier Aggregation RF Conducted Powers

See RF Exposure Technical Report S/N: 1M1912300227-01-R2.ZNF & 1M1911250199-01-R2.ZNF for complete RF conducted output power measurements.

Table 4-1
Maximum Output Powers – LTE B13 as PCC

		PCC										SCC 1				SCC 2				SCC 3				Power			
Combination	PCC Band	PCC BW [MHz]	PCC [UL] Ch.	PCC [UL] Freq. [MHz]	Mod.	PCC UL RB	PCC UL RB Offset	PCC [DL] Ch.	PCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch.	SCC [DL] Freq. [MHz]	DL Ant. Config.	LTE Tx Power with DL CA Enabled	LTE Single Carrier Tx Power (dBm)
CA_13A{48A}	LTE B13	10	23230	782	QPSK	1	0	5230	751	2x2	LTE B48	20	55990	3625	4x4	-	-	-	-	-	-	-	-	-	-	25.35	25.27
CA_13A{66A}{66A}	LTE B13	10	23230	782	QPSK	1	0	5230	751	2x2	LTE B66	20	66786	2145	4x4	LTE B66	20	67236	2190	4x4	-	-	-	-	-	25.25	25.27
CA_13A{48C}	LTE B13	10	23230	782	QPSK	1	0	5230	751	2x2	LTE B48	20	55990	3625	4x4	LTE B48	20	56188	3644.8	4x4	-	-	-	-	-	25.26	25.27
CA_13A{48D}	LTE B13	10	23230	782	QPSK	1	0	5230	751	2x2	LTE B48	20	55990	3625	4x4	LTE B48	20	56188	3644.8	4x4	LTE B48	20	56386	3664.6	4x4	25.33	25.27

Table 4-1
Maximum Output Powers – LTE B66 as PCC

Combination	PCC										SCC 1				SCC 2				SCC 3				SCC 4		Power		
	PCC Band	PCC BW [MHz]	PCC [UL] Ch. Freq. [MHz]	Mod.	PCC UL RB Offset	PCC [DL] Freq. [MHz]	PCC [DL] Ch. Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch. Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch. Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch. Freq. [MHz]	DL Ant. Config.	SCC Band	SCC BW [MHz]	SCC [DL] Ch. Freq. [MHz]	DL Ant. Config.	LTE Tx Power with DL CA Enabled	LTE Single Carrier Tx Power (dBm)	
CA_160A{66A}	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	4x4	LTE B48	20	55990	3625	4x4	-	-	-	-	-	-	-	-	-	25.19	25.30	
CA_13A{66A}-166A	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	4x4	LTE B66	20	66536	2120	4x4	LTE B13	10	5230	751	2x2	-	-	-	-	-	25.20	25.20
CA_140C{66A}	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	4x4	LTE B48	20	55990	3625	4x4	LTE B48	20	56288	3644.8	4x4	-	-	-	-	-	25.19	25.26
CA_140D{66A}	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	4x4	LTE B48	20	55990	3625	4x4	LTE B48	20	56288	3644.8	4x4	LTE B48	20	56386	3664.6	4x4	25.19	25.20
CA_48E{66A}	LTE B66	20	132572	1770	QPSK	1	0	67036	2170	4x4	LTE B48	20	55990	3625	2x2	LTE B48	20	56288	3644.8	2x2	LTE B48	20	56386	3664.6	2x2	25.18	25.20

FCC ID: ZNFV600VM	 PCTEST Proud to be part of 	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset		Page 8 of 11

5 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Anritsu	MT8821C	Radio Communication Analyzer	3/10/2020	Annual	3/10/2021	6200301190
Anritsu	MT8821C	Radio Communication Analyzer	6/15/2020	Annual	6/15/2021	6201381794
Anritsu	MT8821C	Radio Communication Analyzer	2/22/2020	Annual	2/22/2021	6261895213
Anritsu	MT8821C	Radio Communication Analyzer	7/3/2020	Annual	7/3/2021	6262150047
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	NC-100	Torque Wrench	8/4/2020	Biennial	8/4/2022	N/A

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: ZNFV600VM	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset		Page 9 of 11

6 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: ZNFV600VM	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset	Page 10 of 11	

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: ZNFV600VM	 PCTEST Proud to be part of 	SAR EVALUATION REPORT	 LG	Approved by: Quality Manager
Document S/N: 1M2009170147-02.ZNF	Test Dates: 09/18/2020	DUT Type: Portable Handset	Page 11 of 11	