

Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transceiver (Master Unit) for a RC Toy. The sample supplied operated on 3 channels, normally at 2450 - 2470MHz. The channels are 2450MHz, 2460MHz and 2470MHz.

The EUT is powered by 2 x 1.5V AA batteries. After switching on the EUT, the Slave unit will be flashed light and generated sound effect.

Antenna Type: Internal, Integral antenna

Antenna Gain: 0dBi

Nominal rated field strength is 84.0dBμV/m at 3m (Peak), 66.8dBμV/m at 3m (Average) Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the maximum average field strength of production tolerance was 69.8dBμV/m at 3m in frequency 2.460GHz.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

The worst case of SAR Exclusion Threshold Level:

$$\begin{aligned} &= 3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz}) \\ &= 3.0 * 5 / \text{sqrt}(2.483.5) \text{ mW} \\ &= 9.52 \text{ mW} \end{aligned}$$

According to the KDB 412172 D01:

$$\text{EIRP} = [(\text{FS} * \text{D})^2 * 1000 / 30]$$

Calculated Field Strength for 9.52mW is 105dBuV/m @3m

Since maximum average field strength plus production tolerance $\leq$ 105dBuV/m @3m and antenna gain is $\geq$ 0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.