

RF Exposure Report

Report No.: SA180305C20

FCC ID: ZOQVT-410

Test Model: VT-410

Received Date: Mar. 05, 2018

Date of Evaluation: Apr. 24, 2018

Issued Date: May 04, 2018

Applicant: Verizon Connect.

Address: 2002 Summit Blvd, Suite 1800

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City 33383, Taiwan (R.O.C)

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result Of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA180305C20	Original Release	May 04, 2018

1 Certificate of Conformity

Product: OBD2 LTE/3G/GPS/WIFI/BT tracker

Brand: Verizon Telematics Inc.

Test Model: VT-410

Sample Status: Production Unit

Applicant: Verizon Connect.

Date of Evaluation: Apr. 24, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date: May 04, 2018

Gina Liu / Specialist

Approved by :



Date: May 04, 2018

Dylan Chiou / Project Engineer

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.
So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna Type	Frequency Band (MHz)	Antenna Gain (dBi)
Metal	WCDMA II 1852.4-1907.6	2.49
	WCDMA V 826.4-846.6	1.1
	LTE 2 1850.7-1909.3	2.49
	LTE 4 1710.7-1754.3	1.1
	LTE 5 824.7-846.5	1.1
	LTE 12 699.7-715.3	1.3
	LTE 13 779.5-784.5	2.2
	LTE 17 706.5-713.5	1.3
	2412-2462	0.15
	5180-5240	4.26
	5745-5825	4.26
	Bluetooth 2402-2480	0.15

2.5 Calculation Result Of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II 1852.4-1907.6	25.7	2.49	20	0.131	1
WCDMA V 826.4-846.6	25.7	1.1	20	0.095	1
LTE 2 1850.7-1909.3	25.7	2.49	20	0.131	1
LTE 4 1710.7-1754.3	25.7	1.1	20	0.095	1
LTE 5 824.7-846.5	25.7	1.1	20	0.095	1
LTE 12 699.7-715.3	25.7	1.3	20	0.100	1
LTE 13 779.5-784.5	25.7	2.2	20	0.123	1
LTE 17 706.5-713.5	25.7	1.3	20	0.100	1
2412-2462	17.0	0.15	20	0.010	1
5180-5240	14.0	4.26	20	0.013	1
5745-5825	14.0	4.26	20	0.013	1
Bluetooth 2402-2480	4.0	0.15	20	0.001	1

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WWAN + WLAN = $0.131 / 1 + 0.013 / 1 = 0.144$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---