
FCC Part 90 Rules Test Report

Report No.: AGC01303141001FE10

FCC ID : ZP5BF-F9V2
PRODUCT DESIGNATION : WALKIE TALKIE
BRAND NAME : BAOFENG
MODEL NAME : BF-F9V2+
CLIENT : FUJIAN NAN'AN BAOFENG ELECTRONICS CO.,LTD.
DATE OF ISSUE : Nov.07, 2014
STANDARD(S) : FCC Part 90 Rules
REPORT VERSION : V 1.0

Attestation of *Global Compliance (Shenzhen) Co., Ltd*

CAUTION: This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov.07, 2014	Valid	Original Report

VERIFICATION OF COMPLIANCE

Applicant:	FUJIAN NAN'AN BAOFENG ELECTRONICS CO.,LTD.
	CHANGFU INDUSTRIAL ZONE,XIAMEI,NAN'AN,QUANZHOU,FUJIAN,CHINA
Manufacturer:	FUJIAN NAN'AN BAOFENG ELECTRONICS CO.,LTD.
	CHANGFU INDUSTRIAL ZONE,XIAMEI,NAN'AN,QUANZHOU,FUJIAN,CHINA
Product Designation:	WALKIE TALKIE
Brand Name:	BAOFENG
Test Model	BF-F9V2+
Date of Test:	Oct.30, 2014 to Nov.06, 2014

WE HEREBY CERTIFY THAT:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2009. The sample tested as described in this report is in compliance with the FCC Rules Part 90 requirements

The test results of this report relate only to the tested sample identified in this report.



Tested by	
	Freddie Duan Nov.07, 2014
Checked By	
	Kidd Yang Nov.07, 2014
Authorized By	
	Solger Zhang Nov.07, 2014

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	6
1.1 PRODUCT DESCRIPTION.....	6
1.2 RELATED SUBMITTAL(S) / GRANT (S).....	7
1.3 TEST METHODOLOGY	7
1.4 TEST FACILITY	7
1.5 SPECIAL ACCESSORIES.....	7
1.6 EQUIPMENT MODIFICATIONS	7
2. SYSTEM TEST CONFIGURATION	8
2.1 EUT CONFIGURATION	8
2.2 EUT EXERCISE	8
2.3 GENERAL TECHNICAL REQUIREMENTS.....	8
2.4 CONFIGURATION OF TESTED SYSTEM.....	9
3. SUMMARY OF TEST RESULTS	10
4. DESCRIPTION OF TEST MODES	11
5. CONDUCTED LIMITS	12
5.1 PROVISIONS APPLICABLE	12
5.2 MEASUREMENT PROCEDURE.....	12
5.3 TEST SETUP BLOCK DIAGRAM.....	13
5.4 TEST EQUIPMENT USED	13
5.5 TEST RESULT.....	14
6. FREQUENCY TOLERANCE	16
6.1 PROVISIONS APPLICABLE	16
6.2 MEASUREMENT PROCEDURE.....	16
6.3 TEST SETUP BLOCK DIAGRAM	17
6.4 TEST EQUIPMENT USED:.....	17
7. EMISSION BANDWIDTH	24
7.1 PROVISIONS APPLICABLE	24
7.2 MEASUREMENT PROCEDURE.....	24
7.3 TEST SETUP BLOCK DIAGRAM.....	24
7.4 MEASUREMENT EQUIPMENT USED:.....	24
7.5 MEASUREMENT RESULT	25
8. UNWANTED RADIATION.....	31
8.1 PROVISIONS APPLICABLE	31
8.2 MEASUREMENT PROCEDURE.....	31

8.3 TEST SETUP BLOCK DIAGRAM.....	32
8.4 MEASUREMENT EQUIPMENT USED:.....	34
8.5 MEASUREMENT RESULTS:	34
9. MODULATION CHARACTERISTICS.....	41
9.1 PROVISIONS APPLICABLE	41
9.2 MEASUREMENT METHOD	41
9.3 MEASUREMENT INSTRUMENTS.....	41
9.4 MEASUREMENT RESULT	42
10. MAXIMUM TRANSMITTER POWER.....	48
10.1 PROVISIONS APPLICABLE	48
10.2 TEST PROCEDURE.....	48
10.3 TEST INSTRUMENTS.....	48
10.4 TEST CONFIGURATION.....	49
10.5 TEST RESULT.....	51
10.6 CONDUCT SPURIOUS PLOT.....	54
11. TRANSMITTER FREQUENCY BEHAVIOR.....	56
11.1 PROVISIONS APPLICABLE	56
11.2 TEST METHOD	56
11.3 TEST INSTRUMENTS.....	56
11.4 DESCRIBE LIMIT LINE OF TRANSMITTER FREQUENCY BEHAVIOR.....	57
11.5 MEASURE RESULT	58
12. RADIATED EMISSION ON RECEIVING MODE.....	59
12.1 PROVISIONS APPLICABLE	59
12.2 TEST METHOD.....	59
12.3 TEST INSTRUMENTS	59
12.4 MEASURE RESULT (MEASURED AT 3M USING FCC PART15 B LIMITS).....	60
13. AUDIO LOW PASS FILTER RESPONSE.....	64
13.1 LIMITS.....	64
13.2. METHOD OF MEASUREMENTS.....	64
13.3 TEST DATA	65
APPENDIX I: PHOTOGRAPHS OF SETUP.....	67
APPENDIX II: EXTERNAL VIEW OF EUT	69

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

The EUT is a **WALKIE TALKIE** designed for voice communication. It is designed by way of utilizing the FM modulation achieves the system operating.

A major technical description of EUT is described as following:

Communication Type	Voice / Tone only	
Modulation	FM	
Emission Type	11K4F3E	
Emission Bandwidth	HIGH POWER:10.32KHz(UHF), 10.36KHz(VHF) MIDDLE POWER:10.33KHz(UHF), 10.35KHz(VHF) LOW POWER: 10.31KHz(UHF), 10.38KHz(VHF)	
Peak Frequency Deviation	1.86KHz	
Audio Frequency Response	10.88dB	
Maximum Transmitter Power	38.93dBm(8W), 38.38dBm(7W) 35.93dBm(4W), 29.92dBm(1W)	
Output power Modification	H: 8W M: 4W L:1W(VHF) H: 7W M:4W L:1W(UHF) (It was fixed by the manufacturer, any individual can't arbitrarily change it.)	
Antenna Designation	Detachable	
Power Supply	DC 7.4V, 1800mAh (by battery)	
Adapter Parameter	Input: AC100V-240V, 50/60HZ Output: DC10V, 0.5A	
Limiting Voltage	DC 6.29V-8.51V	
Operation Frequency Range and Channel	Frequency Range: 400MHz to 520MHz (UHF) & 136MHz~174MHz (VHF) Channel Separation: 12.5KHz	
	Bottom Channel: 400.025MHz Centre Channel: 460.000MHz Top Channel: 519.975MHz	Bottom Channel: 136.025MHz Centre Channel: 155.000MHz Top Channel: 173.975MHz
Frequency Tolerance	0.750ppm	

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: ZP5BF-F9V2**, filing to comply with the FCC Part 90 requirements.

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2009; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

1.4 TEST FACILITY

The test site used to collect the radiated data is located on the address of Attestation of Global Compliance (Shenzhen) Co., Ltd. 2/F., Building 2, No.1-No.4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003 and IC requirements in documents RS212.

FCC register No.: 259865

1.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

1.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

For FCC Part 90 requirements:

- (1). Section 15.207: Conducted Limits
- (2). Section 90.205: Maximum ERP is dependent upon the station's antenna HAAT and required service area
- (3). Section 90.207: Modulation Characteristic
- (4). Section 90.209: Occupied Bandwidth
- (5). Section 90.210: Emission Mask
- (6). Section 90.213: Frequency Tolerance
- (7). Section 90.214: Transient Frequency Behavior
- (8). Section 15.109: Radiated Emission

2.4 CONFIGURATION OF TESTED SYSTEM

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Model No.	Identifier	Note
1	WALKIE TALKIE	BF-F9V2+	FCC ID: ZP5BF-F9V2	EUT

Table 2-2 Cable used in test

Name of Equipment	Manufacturer	Model	Number	Cal. Due
RF Cable	SUIRONG	30MHz-18GHz	2	07/15/2015
Headphone Line	AGC	N/A	1	07/15/2015

3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207	Conducted Emission	Compliant
§90.205	Maximum Transmitter Power	Compliant
§90.207	Modulation Characteristic	Compliant
§90.209	Occupied Bandwidth	Compliant
§90.210	Emission Mask	Compliant
§90.213	Frequency Tolerance	Compliant
§90.214	Transient Frequency Behavior	Compliant
§15.109	Radiated Emission	Compliant

4. DESCRIPTION OF TEST MODES

RF TEST MODES

The EUT (WALKIE TALKIE) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

No.	TEST MODES	CHANNEL SEPARATION
1	Low Channel	12.5 KHz
2	Middle Channel	12.5 KHz
3	High Channel	12.5 KHz

EMC TEST MODES

No.	TEST MODES
1	Standby Mode

Note: Only the result of the worst case was recorded in the report.

5. CONDUCTED LIMITS

5.1 PROVISIONS APPLICABLE

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the, the radio frequency voltage that is conducted back onto the AC power line on any frequencies within the band 150 KHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50uH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.


Frequency of Emission (MHz)	Conducted Limit(dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency.

5.2 MEASUREMENT PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. The EUT received power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes. During the above scans, the emissions were maximized by cable manipulation.

5.3 TEST SETUP BLOCK DIAGRAM



5.4 TEST EQUIPMENT USED


Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	N/A	07/16/2014	07/15/2015
LISN	R&S	ESH3-Z5	N/A	07/16/2014	07/15/2015
RF Cable	SUIRONG	9KHz-30MHz	N/A	07/16/2014	07/15/2015

5.5 TEST RESULT

CONDUCTED EMISSION TEST – LINE L1

SCAN TABLE: "Voltage (150K-30M) FIN"

Short Description: 9k-30M Voltage



MEASUREMENT RESULT

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
1.790000	27.00	0.3	56	29.0	QP	L1	GND	ON
2.974000	42.70	0.3	56	13.3	QP	L1	GND	ON
3.022000	41.20	0.3	56	14.8	QP	L1	GND	ON
3.138000	41.30	0.3	56	14.7	QP	L1	GND	ON
5.410000	45.10	0.4	60	14.9	QP	L1	GND	ON
5.846000	45.20	0.4	60	14.8	QP	L1	GND	ON


MEASUREMENT RESULT:

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
0.206000	33.30	0.2	53	20.1	AV	L1	GND	ON
0.514000	26.90	0.2	46	19.1	AV	L1	GND	ON
0.842000	26.40	0.2	46	19.6	AV	L1	GND	ON
2.430000	27.10	0.3	46	18.9	AV	L1	GND	ON
5.806000	32.50	0.4	50	17.5	AV	L1	GND	ON
18.094000	25.50	0.7	50	24.5	AV	L1	GND	ON

CONDUCTED EMISSION TEST – LINE N

SCAN TABLE: "Voltage (150K-30M) FIN"

Short Description: 9k-30M Voltage

**MEASUREMENT RESULT:**

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
3.206000	23.10	0.3	56	32.9	QP	N	GND	ON
3.246000	42.20	0.3	56	13.8	QP	N	GND	ON
3.354000	42.10	0.3	56	13.9	QP	N	GND	ON
3.578000	41.80	0.3	56	14.2	QP	N	GND	ON
3.746000	40.30	0.3	56	15.7	QP	N	GND	ON
3.826000	40.80	0.3	56	15.2	QP	N	GND	ON

MEASUREMENT RESULT:

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
0.210000	29.00	0.2	53	24.2	AV	N	GND	ON
0.422000	19.60	0.2	47	27.8	AV	N	GND	ON
1.170000	21.90	0.2	46	24.1	AV	N	GND	ON
2.342000	25.70	0.3	46	20.3	AV	N	GND	ON
3.194000	27.70	0.3	46	18.3	AV	N	GND	ON
18.934000	27.00	0.8	50	23.0	AV	N	GND	ON

6. FREQUENCY TOLERANCE

6.1 PROVISIONS APPLICABLE

- a). According to FCC Part 2 Section 2.1055(a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade.
- b). According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- c). According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5 KHz channel separation.
- d). According to RSS-119 Section 119.5.3, the frequency tolerance must be maintained within 0.00025% for 12.5 KHz channel separation and 0.0005% for 25KHz channel separation.

6.2 MEASUREMENT PROCEDURE


6.2.1 Frequency stability versus environmental temperature

1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz and Frequency Span to 50KHz. Record this frequency as reference frequency.
3. Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

1. Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C . Otherwise, an environment chamber set for a temperature of 20°C shall be used. The EUT shall be powered by DC 7.4V.
2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 KHz and Video Resolution Bandwidth to 1KHz. Record this frequency as reference frequency.
3. Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 TEST SETUP BLOCK DIAGRAM



6.4 TEST EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
RECEIVER	R&S	ESCI	N/A	07/16/2014	07/15/2015
CLIMATE CHAMBER	EXPERY	TN-400	N/A	07/16/2014	07/15/2015
ATTENUATOR	WEINSCHTEL CORP	58-30-33	ML030	07/16/2014	07/15/2015
DC POWER SUPPLY	ZHAOXIN	RXN-605D	N/A	05/16/2014	05/15/2015
RF CABLE	SUIRONG	30MHZ-18GHZ	N/A	07/16/2014	07/15/2015

TEST RESULT**Frequency bands: UHF**

(1) Frequency stability versus input voltage (Supply nominal voltage is 7.40V)

Bottom Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	400.025 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 7.40 V	400.025073	0.182
40	DC 7.40 V	400.025064	0.160
30	DC 7.40 V	400.025051	0.127
20	DC 7.40 V	400.025036	0.090
10	DC 7.40 V	400.025055	0.137
0	DC 7.40 V	400.025063	0.157
-10	DC 7.40 V	400.025075	0.187
-20	DC 7.40 V	400.025087	0.217
-30	DC 7.40 V	400.025092	0.230

Middle Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	460.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 7.40 V	460.000074	0.161
40	DC 7.40 V	460.000061	0.133
30	DC 7.40 V	460.000053	0.115
20	DC 7.40 V	460.000034	0.074
10	DC 7.40 V	460.000042	0.091
0	DC 7.40 V	460.000056	0.122
-10	DC 7.40 V	460.000062	0.135
-20	DC 7.40 V	460.000071	0.154
-30	DC 7.40 V	460.000097	0.211

Top Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	519.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 7.40 V	519.975083	0.160
40	DC 7.40 V	519.975064	0.123
30	DC 7.40 V	519.975054	0.104
20	DC 7.40 V	519.975035	0.067
10	DC 7.40 V	519.975046	0.088
0	DC 7.40 V	519.975053	0.102
-10	DC 7.40 V	519.975076	0.146
-20	DC 7.40 V	519.975087	0.167
-30	DC 7.40 V	519.975095	0.183

Frequency bands: VHF

Bottom Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	136.025 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 7.40 V	136.025072	0.529
40	DC 7.40 V	136.025069	0.507
30	DC 7.40 V	136.025052	0.382
20	DC 7.40 V	136.025034	0.250
10	DC 7.40 V	136.025057	0.419
0	DC 7.40 V	136.025065	0.478
-10	DC 7.40 V	136.025077	0.566
-20	DC 7.40 V	136.025086	0.632
-30	DC 7.40 V	136.025094	0.691

Middle Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	155.000 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 7.40 V	155.000073	0.471
40	DC 7.40 V	155.000067	0.432
30	DC 7.40 V	155.000054	0.348
20	DC 7.40 V	155.000033	0.213
10	DC 7.40 V	155.000045	0.290
0	DC 7.40 V	155.000056	0.361
-10	DC 7.40 V	155.000062	0.400
-20	DC 7.40 V	155.000078	0.503
-30	DC 7.40 V	155.000093	0.600

Top Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	173.975 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 7.40 V	173.975087	0.500
40	DC 7.40 V	173.975061	0.351
30	DC 7.40 V	173.975059	0.339
20	DC 7.40 V	173.975035	0.201
10	DC 7.40 V	173.975047	0.270
0	DC 7.40 V	173.975051	0.293
-10	DC 7.40 V	173.975072	0.414
-20	DC 7.40 V	173.975083	0.477
-30	DC 7.40 V	173.975091	0.523

Frequency bands: UHF

(2) Frequency stability versus input voltage (Battery limiting voltage is 6.29V)

Bottom Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	400.025 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 6.29 V	400.025081	0.202
40	DC 6.29 V	400.025074	0.185
30	DC 6.29 V	400.025052	0.130
20	DC 6.29 V	400.025046	0.115
10	DC 6.29 V	400.025065	0.162
0	DC 6.29 V	400.025072	0.180
-10	DC 6.29 V	400.025086	0.215
-20	DC 6.29 V	400.025094	0.235
-30	DC 6.29 V	400.025102	0.255

Middle Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	460.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 6.29 V	460.000083	0.180
40	DC 6.29 V	460.000071	0.154
30	DC 6.29 V	460.000061	0.133
20	DC 6.29 V	460.000042	0.091
10	DC 6.29 V	460.000067	0.146
0	DC 6.29 V	460.000079	0.172
-10	DC 6.29 V	460.000085	0.185
-20	DC 6.29 V	460.000091	0.198
-30	DC 6.29 V	460.000104	0.226

Top Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	519.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 6.29 V	519.975083	0.160
40	DC 6.29 V	519.975072	0.138
30	DC 6.29 V	519.975065	0.125
20	DC 6.29 V	519.975047	0.090
10	DC 6.29 V	519.975064	0.123
0	DC 6.29 V	519.975074	0.142
-10	DC 6.29 V	519.975082	0.158
-20	DC 6.29 V	519.975097	0.187
-30	DC 6.29 V	519.975109	0.210

Frequency bands: VHF

Bottom Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	136.025 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 6.29 V	136.025089	0.654
40	DC 6.29 V	136.025077	0.566
30	DC 6.29 V	136.025058	0.426
20	DC 6.29 V	136.025044	0.323
10	DC 6.29 V	136.025063	0.463
0	DC 6.29 V	136.025076	0.559
-10	DC 6.29 V	136.025083	0.610
-20	DC 6.29 V	136.025095	0.698
-30	DC 6.29 V	136.025102	0.750

Middle Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	155.000 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 6.29 V	155.000083	0.535
40	DC 6.29 V	155.000072	0.465
30	DC 6.29 V	155.000062	0.400
20	DC 6.29 V	155.000045	0.290
10	DC 6.29 V	155.000066	0.426
0	DC 6.29 V	155.000077	0.497
-10	DC 6.29 V	155.000081	0.523
-20	DC 6.29 V	155.000096	0.619
-30	DC 6.29 V	155.000104	0.671

Top Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	173.975 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 6.29 V	173.97506	0.345
40	DC 6.29 V	173.975073	0.420
30	DC 6.29 V	173.975062	0.356
20	DC 6.29 V	173.975041	0.236
10	DC 6.29 V	173.975064	0.368
0	DC 6.29 V	173.975072	0.414
-10	DC 6.29 V	173.975084	0.483
-20	DC 6.29 V	173.975097	0.558
-30	DC 6.29 V	173.975105	0.604

Frequency bands: UHF

(3) Frequency stability versus input voltage (Battery Fully Charged voltage is 8.51V)

Bottom Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	400.025 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 8.51 V	400.025085	0.212
40	DC 8.51 V	400.025073	0.182
30	DC 8.51 V	400.025056	0.140
20	DC 8.51 V	400.025044	0.110
10	DC 8.51 V	400.025063	0.157
0	DC 8.51 V	400.025072	0.180
-10	DC 8.51 V	400.025084	0.210
-20	DC 8.51 V	400.025091	0.227
-30	DC 8.51 V	400.025102	0.255

Middle Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	460.000 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 8.51 V	460.000081	0.176
40	DC 8.51 V	460.000073	0.159
30	DC 8.51 V	460.000064	0.139
20	DC 8.51 V	460.000041	0.089
10	DC 8.51 V	460.000066	0.143
0	DC 8.51 V	460.000072	0.157
-10	DC 8.51 V	460.000087	0.189
-20	DC 8.51 V	460.000095	0.207
-30	DC 8.51 V	460.000103	0.224

Top Channel @ 12.5 KHz Channel Separation-7W

Reference Frequency:	519.975 MHz	Limit:	2.5ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 8.51 V	519.975082	0.158
40	DC 8.51 V	519.975077	0.148
30	DC 8.51 V	519.975061	0.117
20	DC 8.51 V	519.975042	0.081
10	DC 8.51 V	519.975061	0.117
0	DC 8.51 V	519.975073	0.140
-10	DC 8.51 V	519.975087	0.167
-20	DC 8.51 V	519.975093	0.179
-30	DC 8.51 V	519.975106	0.204

Frequency bands: VHF

Bottom Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	136.025 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 8.51 V	136.025082	0.603
40	DC 8.51 V	136.025075	0.551
30	DC 8.51 V	136.025054	0.397
20	DC 8.51 V	136.025044	0.323
10	DC 8.51 V	136.025065	0.478
0	DC 8.51 V	136.025073	0.537
-10	DC 8.51 V	136.025081	0.595
-20	DC 8.51 V	136.025095	0.698
-30	DC 8.51 V	136.025102	0.750

Middle Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	155.000 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 8.51 V	155.000086	0.555
40	DC 8.51 V	155.000073	0.471
30	DC 8.51 V	155.000067	0.432
20	DC 8.51 V	155.000043	0.277
10	DC 8.51 V	155.000065	0.419
0	DC 8.51 V	155.000074	0.477
-10	DC 8.51 V	155.000087	0.561
-20	DC 8.51 V	155.000094	0.606
-30	DC 8.51 V	155.000102	0.658

Top Channel @ 12.5 KHz Channel Separation-8W

Reference Frequency:	173.975 MHz	Limit:	5.0ppm
Environment Temperature	Power Supply	Frequency Deviation	
(°C)	(V)	(MHz)	ppm
50	DC 8.51 V	173.975088	0.506
40	DC 8.51 V	173.975073	0.420
30	DC 8.51 V	173.975064	0.368
20	DC 8.51 V	173.975045	0.259
10	DC 8.51 V	173.975062	0.356
0	DC 8.51 V	173.975077	0.443
-10	DC 8.51 V	173.975082	0.471
-20	DC 8.51 V	173.975095	0.546
-30	DC 8.51 V	173.975108	0.621

7. EMISSION BANDWIDTH

7.1 PROVISIONS APPLICABLE


According to FCC Part 90 Section 90.209: The authorized bandwidth shall be 11.25 KHz for 12.5 KHz channel separation.

According to RSS-119 Section 119.5.5: The authorized bandwidth shall be 11.25 KHz for 12.5 KHz

7.2 MEASUREMENT PROCEDURE

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). The EUT was modulated by 2.5 KHz Sine wave audio signal, The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz (12.5 kHz channel spacing).
- 3). Set SPA Center Frequency = fundamental frequency, RBW=100 Hz , VBW= 300 Hz, Span =50 KHz.
- 4). Set SPA Max hold. Mark peak, -26 dB.

7.3 TEST SETUP BLOCK DIAGRAM



7.4 MEASUREMENT EQUIPMENT USED:


NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	07/16/2014	07/15/2015
MODULATION ANALYZER	HP	8920B	3104A03367	07/16/2014	07/15/2015
BROADBAND ANT	A.H.	SAS-521-4	A0304224	07/16/2014	07/15/2015
ATTENUATOR	WEINSCHEL CORP	58-30-33	ML030	07/16/2014	07/15/2015
HEADPHONE LINE	AGC	N/A	N/A	N/A	N/A
RF CABLE	SUIRONG	30MHZ-18GHZ	N/A	07/16/2014	07/15/2015

7.5 MEASUREMENT RESULT

TEST RESULT TS FOR HIGH POWER LEVEL


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	10.30KHz	11.25 KHz	Pass
155.000MHz	10.34KHz	11.25 KHz	Pass
173.975MHz	10.36KHz	11.25 KHz	Pass

Occupied bandwidth of High Channel (Maximum)-VHF



26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	10.32KHz	11.25 KHz	Pass
460.000MHz	10.27KHz	11.25 KHz	Pass
519.975MHz	10.29KHz	11.25 KHz	Pass


Occupied bandwidth of Low Channel (Maximum)-UHF



TEST RESULT TS FOR MIDDLE POWER LEVEL


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	10.31KHz	11.25 KHz	Pass
155.000MHz	10.32KHz	11.25 KHz	Pass
173.975MHz	10.35KHz	11.25 KHz	Pass

Occupied bandwidth of High Channel (Maximum)-VHF



26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	10.33KHz	11.25 KHz	Pass
460.000MHz	10.29KHz	11.25 KHz	Pass
519.975MHz	10.31KHz	11.25 KHz	Pass


Occupied bandwidth of Low Channel (Maximum)-UHF



TEST RESULT TS FOR LOW POWER LEVEL


26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
136.025MHz	10.35KHz	11.25 KHz	Pass
155.000MHz	10.36KHz	11.25 KHz	Pass
173.975MHz	10.38KHz	11.25 KHz	Pass

Occupied bandwidth of High Channel (Maximum)-VHF



26 DB BANDWIDTH MEASUREMENT RESULT			
Operating Frequency	12.5 KHz Channel Separation		
	Test Data	Limits	Result
400.025MHz	10.31KHz	11.25 KHz	Pass
460.000MHz	10.29KHz	11.25 KHz	Pass
519.975MHz	10.28KHz	11.25 KHz	Pass

Occupied bandwidth of Low Channel (Maximum)-UHF



8. UNWANTED RADIATION

8.1 PROVISIONS APPLICABLE

8.1.1 According to Section 90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation.

According to RSS-119 Section 119.5.8, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters with each channel separation.

For 12.5 KHz Channel Separation:

- (1). On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 KHz removed from f_0 : Zero dB.
- (2). On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_0 of more than 5.625 KHz but no more than 12.5 KHz: At least $7.27(f_d - 2.88 \text{ KHz})$ dB
- (3). On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in KHz) f_0 of more than 12.5 KHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.

8.2 MEASUREMENT PROCEDURE

- (1) On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- (2) The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- (3) The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- (4) The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- (5) The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- (6) The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- (7) The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- (8) The maximum signal level detected by the measuring receiver shall be noted.
- (9) The measurement shall be repeated with the test antenna set to horizontal polarization.
- (10) Replace the antenna with a proper Antenna (substitution antenna).
- (11) The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- (12) The substitution antenna shall be connected to a calibrated signal generator.
- (13) If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.


(14) The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.

(15) The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.

(16) The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.


(17) The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

8.3 TEST SETUP BLOCK DIAGRAM




SUBSTITUTION METHOD: (Radiated Emissions)

Radiated Below 1GHz



Radiated Above 1 GHz



8.4 MEASUREMENT EQUIPMENT USED:

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	07/16/2014	07/15/2015
HORN ANT.	EM	EM-AH-10180	100150	04/20/2014	04/19/2015
BROADBAND ANT.	A.H.	SAS-521-4	A0304224	06/06/2014	06/05/2015
AMPLIFIER	EM	EM30180	0607030	07/16/2014	07/15/2015
Multi-Device Controller	EMCO	2090	N/A	07/30/2014	07/29/2015
HORN ANTENNA	A.H. SYSTEMS INC.	SAS-574	N/A	07/16/2014	07/15/2015
SIGNAL GENERATOR	AGILENT	E4421B	122501288	07/16/2014	07/15/2015
ATTENUATOR	WEINSCHEL CORP	58-30-33	ML030	07/16/2014	07/15/2015
RF CABLE	SUIRONG	30MHZ-18GHZ	N/A	07/16/2014	07/15/2015

8.5 MEASUREMENT RESULTS:**Measurement Result for 12.5 KHz Channel Separation**

On any frequency removed from the center of the authorized bandwidth by a displacement

Frequency (f_d in KHz) for of more than 12.5 KHz: at least $50+10 \log(P)$ dB or 70 dB, which ever is lesser attenuation.

High Power Limit: At least $50+10 \log(P) = 50+10 \log(7) = 58$ (dB)

At least $50+10 \log(P) = 50+10 \log(8) = 59$ (dB)

Middle Power Limit: At least $50+10 \log(P) = 50+10 \log(4) = 56$ (dB)

Low Power Limit: At least $50+10 \log(P) = 50+10 \log(1) = 50$ (dB)

TEST RESULT TS FOR H POWER LEVEL**Measurement Result for 12.5 KHz Channel Separation @ 400.025MHz**

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
400.025	V	0		pass
800.050	V	69.26	58	pass
1200.075	V	70.16	58	pass
1600.100	V	70.34	58	pass
2000.125	V	72.53	58	pass
2400.150	V	74.11	58	pass
2800.175	V	75.14	58	pass
3200.200	V	77.55	58	pass
3600.225	V	79.83	58	pass
4000.250	V	81.37	58	pass

Measurement Result for 12.5 KHz Channel Separation @ 460.000MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
460.000	V	0		pass
920.000	V	68.33	58	pass
1380.000	V	69.65	58	pass
1840.000	V	72.64	58	pass
2300.000	V	75.56	58	pass
2760.000	V	76.42	58	pass
3220.000	V	78.25	58	pass
3680.000	V	70.61	58	pass
4140.000	V	80.45	58	pass
4600.000	V	81.23	58	pass

Measurement Result for 12.5 KHz Channel Separation @ 519.975MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
519.975	V	0		pass
1039.950	V	69.56	58	pass
1559.925	V	71.34	58	pass
2079.900	V	73.25	58	pass
2599.875	V	74.47	58	pass
3119.850	V	75.46	58	pass
3639.825	V	77.53	58	pass
4159.800	V	79.54	58	pass
4679.775	V	70.48	58	pass
5199.750	V	71.71	58	pass

Measurement Result for 12.5 KHz Channel Separation @ 136.025MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
136.025	V	0		pass
272.050	V	69.28	59	pass
408.08	V	70.17	59	pass
544.100	V	70.32	59	pass
680.125	V	72.52	59	pass
816.150	V	74.12	59	pass
952.175	V	75.15	59	pass
1088.200	V	77.57	59	pass
1224.225	V	79.85	59	pass
1360.250	V	81.36	59	pass

Measurement Result for 12.5 KHz Channel Separation @ 155.000MHz

Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
155.000	V	0		pass
310.000	V	68.34	59	pass
465.000	V	69.65	59	pass
620.000	V	72.67	59	pass
775.000	V	75.56	59	pass
930.000	V	76.43	59	pass
1085.000	V	78.29	59	pass
1240.000	V	70.64	59	pass
1395.000	V	80.46	59	pass
1550.000	V	81.23	59	pass

Measurement Result for 12.5 KHz Channel Separation @ 173.975MHz


Emission Frequency (MHz)	Ant. Polarity(H/V)	Measurement Result Below carrier(dBc)	Limit below carrier(dBc)	Result(P/F)
173.975	V	0		pass
347.950	V	69.54	59	pass
521.925	V	71.32	59	pass
695.900	V	73.28	59	pass
869.875	V	74.47	59	pass
1043.850	V	75.46	59	pass
1217.825	V	77.57	59	pass
1391.800	V	79.53	59	pass
1565.775	V	70.48	59	pass
1739.750	V	71.72	59	pass

8.6 EMISSION MASK PLOT


The detailed procedure employed for Emission Mask measurements are specified as following:

- The transmitter shall be modulated by a 2.5 kHz audio signal,
- The level of the audio signal employed is 16 dB greater than that necessary to produce 50% of rated system deviation. Rated system deviation is 2.5 kHz.


The Worst Emission Mask D for 12.5 KHz channel Separation (8W)-(VHF)




The Worst Emission Mask D for 12.5 KHz channel Separation (4W)-(VHF)




The Worst Emission Mask D for 12.5 KHz channel Separation (1W)-(VHF)




The Worst Emission Mask D for 12.5 KHz channel Separation (7W)-(UHF)



The Worst Emission Mask E for 12.5 KHz channel Separation (4W)-(UHF)





9. MODULATION CHARACTERISTICS

9.1 PROVISIONS APPLICABLE

According to CFR 47 section 2.1047(a), for Voice Modulation Communication Equipment, the frequency response of the audio modulation circuit over a range of 100 to 5000Hz shall be measured.

9.2 MEASUREMENT METHOD

9.2.1 Modulation Limit

- (1). Configure the EUT as shown in figure 1, adjust the audio input for 60% of rated system deviation at 1KHz using this level as a reference (0dB) and vary the input level from -20 to +20dB. Record the frequency deviation obtained as a function of the input level.
- (2). Repeat step 1 with input frequency changing to 300, 1000, 1500 and 3000Hz in sequence.

9.2.2 Audio Frequency Response

- (1). Configure the EUT as shown in figure 1.
- (2). Adjust the audio input for 20% of rated system deviation at 1 KHz using this level as a reference (0 dB).
- (3). Vary the Audio frequency from 100 Hz to 10 KHz and record the frequency deviation.
- (4). Audio Frequency Response = $20\log_{10} (\text{Deviation of test frequency} / \text{Deviation of 1 KHz reference})$.




Figure 1: Modulation characteristic measurement configuration

9.3 MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
Modulation Analyzer	HP	8920B	3104A03367	07/16/2014	07/15/2015
Signal Generator	R&S	SMT02	A0304261	05/26/2014	05/25/2015
Attenuator	Weinschel Corp	58-30-33	ML030	07/16/2014	07/15/2015
RF CABLE	SUIRONG	30MHZ-18GHZ	N/A	07/16/2014	07/15/2015

NOTE: 8920B can generate audio modulation frequency.


9.4 MEASUREMENT RESULT

TEST RESULT TS FOR H POWER LEVEL

(A). MODULATION LIMIT:

Middle Channel @ 12.5 KHz Channel Separations

Modulation Level (dB)	Peak Freq. Deviation At 300 Hz	Peak Freq. Deviation At 1000 Hz	Peak Freq. Deviation At 1500 Hz	Peak Freq. Deviation At 3000 Hz
-20	0.21	0.83	0.87	0.91
-15	0.33	0.94	0.96	1.06
-10	0.46	1.27	1.28	1.38
-5	0.54	1.34	1.43	1.49
0	0.67	1.5	1.52	1.59
5	0.73	1.63	1.74	1.86
10	0.87	1.76	1.78	1.84
15	0.97	1.65	1.74	1.78
20	0.88	1.59	1.68	1.76




Note: All the modes had been tested, but only the worst data recorded in the report.

(B). AUDIO FREQUENCY RESPONSE:**Middle Channel @ 12.5 KHz Channel Separations**

Frequency (Hz)	Deviation (KHz)	Audio Frequency Response(dB)
100	--	--
200	--	--
300	0.14	-11.70
400	0.17	-8.87
500	0.23	-7.13
600	0.27	-5.35
700	0.29	-4.73
800	0.36	-2.85
900	0.42	-1.72
1000	0.50	0.00
1200	0.55	0.83
1400	0.65	2.28
1600	0.75	3.52
1800	0.86	4.71
2000	0.94	5.48
2400	1.22	7.75
2500	1.44	9.19
2800	1.66	10.42
3000	1.75	10.88
3200	1.71	10.68
3600	1.56	9.88
4000	1.05	6.44
4500	0.84	4.51
5000	0.75	3.41
5500	0.46	-0.72
6000	0.14	-11.06
6500	0.06	-18.42
7000	0.04	-21.94
7500	0.02	-27.96
9000	--	--
10000	--	--
14000	--	--
18000	--	--
20000	--	--
30000	--	--

Frequency Response of Middle Channel (VHF)




Note: All the modes had been tested, but only the worst data recorded in the report.

TEST RESULT TS FOR H POWER LEVEL

(A). MODULATION LIMIT:

High Channel @ 12.5 KHz Channel Separations

Modulation Level (dB)	Peak Freq. Deviation At 300 Hz	Peak Freq. Deviation At 1000 Hz	Peak Freq. Deviation At 1500 Hz	Peak Freq. Deviation At 3000 Hz
-20	0.27	0.86	0.88	0.9
-15	0.33	0.96	0.98	1.06
-10	0.45	1.25	1.29	1.38
-5	0.53	1.36	1.45	1.49
0	0.65	1.5	1.56	1.59
5	0.72	1.63	1.74	1.86
10	0.87	1.71	1.77	1.84
15	0.95	1.63	1.74	1.78
20	0.86	1.54	1.65	1.75




Note: All the modes had been tested, but only the worst data recorded in the report.

(B). AUDIO FREQUENCY RESPONSE:**High Channel @ 12.5 KHz Channel Separations**

Frequency (Hz)	Deviation (KHz)	Audio Frequency Response(dB)
100	--	--
200	--	--
300	0.14	-11.06
400	0.18	-8.87
500	0.23	-6.74
600	0.27	-5.35
700	0.29	-4.73
800	0.36	-2.85
900	0.41	-1.72
1000	0.5	0.00
1200	0.55	0.83
1400	0.65	2.28
1600	0.75	3.52
1800	0.86	4.71
2000	0.94	5.48
2400	1.22	7.75
2500	1.44	9.19
2800	1.66	10.42
3000	1.75	10.88
3200	1.71	10.68
3600	1.56	9.88
4000	1.05	6.44
4500	0.84	4.51
5000	0.74	3.41
5500	0.56	0.98
6000	0.14	-11.06
6500	0.05	-20.00
7000	0.04	-21.94
7500	0.01	-33.98
9000	--	--
10000	--	--
14000	--	--
18000	--	--
20000	--	--
30000	--	--

Frequency Response of Middle Channel (UHF)



Note: All the modes had been tested, but only the worst data recorded in the report.

10. MAXIMUM TRANSMITTER POWER**10.1 PROVISIONS APPLICABLE**

Per FCC §2.1046 and §90.205 AND RSS 119 Part 4.1: Maximum ERP is dependent upon the station's antenna HAAT and required service area.

10.2 TEST PROCEDURE


The RF output of Two-way Radio was conducted to a spectrum analyzer through an appropriate attenuator.

10.3 TEST INSTRUMENTS


NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	07/16/2014	07/15/2015
SIGNAL GENERATOR	R&S	SMT02	A0304261	05/26/2014	05/25/2015
HORN ANT.	EM	EM-AH-10180	100150	04/20/2014	04/19/2015
BROADBAND ANT.	A.H.	SAS-521-4	A0304224	06/06/2014	06/05/2015
AMPLIFIER	EM	EM30180	0607030	07/16/2014	07/15/2015
Multi-Device Controller	EMCO	2090	N/A	07/30/2014	07/29/2015
HORN ANTENNA	A.H. SYSTEMS INC.	SAS-574	N/A	07/16/2014	07/15/2015
SIGNAL GENERATOR	AGILENT	E4421B	122501288	07/16/2014	07/15/2015
ATTENUATOR	WEINSCHEL CORP	58-30-33	ML030	07/16/2014	07/15/2015
RF CABLE	SUIRONG	30MHZ-18GHZ	N/A	07/16/2014	07/15/2015


10.4 TEST CONFIGURATION

Conducted Output Power:





Effective Radiated Power measurement Below 1GHz





Above 1GHz



10.5 TEST RESULT

The maximum Conducted Power (CP) is

8W/7W/4W/1 W for 12.5 KHz Channel Separation

Calculation Formula: $CP = R + A + L$

* Note:

CP: The final Conducted Power

R : The reading value from spectrum analyzer

A : The attenuation value of the used attenuator


L : The loss of all connection cables

Conducted Power Measurement Results		
Channel Separation	Channel	Measurement Result (dBm)
		For 39.03dBm(8W)
12.5 KHz	Bottom(136.025MHz)	38.91
	Middle(155.000MHz)	38.93
	Top (173.975MHz)	38.90
	Channel	Measurement Result (dBm)
		For 38.45dBm(7W)
	Bottom(400.025MHz)	38.35
	Middle(460.000MHz)	38.38
	Top (519.975MHz)	38.36
	Channel	Measurement Result (dBm)
		For 36.02dBm(4W)
	Bottom(400.025MHz)	35.88
	Middle(460.000MHz)	35.92
	Top (519.975MHz)	35.87
	Bottom(136.025MHz)	35.91
	Middle(155.000MHz)	35.93
	Top (173.975MHz)	35.89
	Channel	Measurement Result (dBm)
		For 30dBm(1W)
	Bottom(400.025MHz)	29.87
	Middle(460.000MHz)	29.91
	Top (519.975MHz)	29.89
	Bottom(136.025MHz)	29.88
	Middle(155.000MHz)	29.92
	Top (173.975MHz)	29.90


Radiated Power Measurement Results		
Channel Separation	Channel	Measurement Result (dBm)
		For 39.03dBm(8W)
12.5 KHz	Bottom(400.025MHz)	38.90
	Middle(460.000MHz)	38.92
	Top (519.975MHz)	38.89
	Channel	Measurement Result (dBm)
		For 38.45dBm(7W)
	Bottom(136.025MHz)	38.34
	Middle(155.000MHz)	38.37
	Top (173.975MHz)	38.35
	Channel	Measurement Result (dBm)
		For 36.02dBm(4W)
	Bottom(400.025MHz)	35.87
	Middle(460.000MHz)	35.91
	Top (519.975MHz)	35.88
	Bottom(136.025MHz)	35.90
	Middle(155.000MHz)	35.92
	Top (173.975MHz)	35.88
	Channel	Measurement Result (dBm)
		For 30dBm(1W)
	Bottom(400.025MHz)	29.86
	Middle(460.000MHz)	29.90
	Top (519.975MHz)	29.87
	Bottom(136.025MHz)	29.89
	Middle(155.000MHz)	29.91
	Top (173.975MHz)	29.88

10.6 CONDUCT SPURIOUS PLOT

Conducted Spurious Emission (worst) @ 173.975MHz With 12.5 KHz Channel Separation-8W 30MHz-1GHz




Conduct Spurious Emission (worst) @ 173.975MHz With 12.5 KHz Channel Separation-8W 1GHz-12.75GHz




Conducted Spurious Emission (worst) @ 400.025MHz With 12.5 KHz Channel Separation-7W

30MHz-1GHz



Conducted Spurious Emission (worst) @ 400.025MHz With 12.5 KHz Channel Separation-7W

1GHz-12.75GHz



11. TRANSMITTER FREQUENCY BEHAVIOR**11.1 PROVISIONS APPLICABLE**

Section 90.214

Time intervals ^{1, 2}	Maximum frequency difference ³	All equipment	
		150 to 174 MHz	421 to 512 MHz
Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels			
t ₁ ⁴	± 25.0 kHz	5.0 ms	10.0 ms
t ₂	± 12.5 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 25.0 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels			
t ₁ ⁴	± 12.5 kHz	5.0 ms	10.0 ms
t ₂	± 6.25 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 12.5 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels			
t ₁ ⁴	± 6.25 kHz	5.0 ms	10.0 ms
t ₂	± 3.125 kHz	20.0 ms	25.0 ms
t ₃ ⁴	± 6.25 kHz	5.0 ms	10.0 ms

¹ t_{on} is the instant when a 1 kHz test signal is completely suppressed, including any capture time due to phasing. t_1 is the time period immediately following t_{on} . t_2 is the time period immediately following t_1 . t_3 is the time period from the instant when the transmitter is turned off until t_{off} . t_{off} is the instant when the 1 kHz test signal starts to rise.² During the time from the end of t_2 to the beginning of t_3 , the frequency difference must not exceed the limits specified in § 90.213.³ Difference between the actual transmitter frequency and the assigned transmitter frequency.⁴ If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency difference for this time period.**11.2 TEST METHOD**

TIA/EIA-603 2.2.19

11.3 TEST INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SIGNAL GENERATOR	AGILENT	E4412B	LR114196	05/28/2014	05/27/2015
STORAGE OSCILLOSCOPE	TEKTRONIX	TDS3052	B017447	07/16/2014	07/15/2015
VOLTAGE PROBE	SCHWARZBECK	TK 9420	N/A	07/16/2014	07/15/2015

11.4 DESCRIBE LIMIT LINE OF TRANSMITTER FREQUENCY BEHAVIOR


ton: The switch-on instant t_{on} of a transmitter is defined by the condition when the output power, measured at the antenna terminal, exceeds 0,1 % of the full output power (-30 dBc).

t1: period of time starting at t_{on} and finishing according to above 11.1

t2: period of time starting at the end of t_1 and finishing according to above 11.1


toff: switch-off instant defined by the condition when the output power falls below 0,1 % of the full output power (-30 dBc).

t3: period of time that finishing at t_{off} and starting according to above 11.1




11.5 MEASURE RESULT

Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation--Off to On



Transmitter Frequency Behaviour @ 12.5 KHz Channel Separation--On to Off



12. RADIATED EMISSION ON RECEIVING MODE

12.1 PROVISIONS APPLICABLE

FCC Part 15 Subpart B Section 15.109

RSS-Gen Subpart B Section RSS-Gen.6.1

12.2 TEST METHOD


ANSI C 63.4: 2003

12.3 TEST INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Cal. Date	Cal. Due
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	07/16/2014	07/15/2015
HORN ANT.	EM	EM-AH-10180	100150	04/20/2014	04/19/2015
BROADBAND ANT.	A.H.	SAS-521-4	A0304224	06/06/2014	06/05/2015
AMPLIFIER	EM	EM30180	0607030	07/16/2014	07/15/2015
Multi-Device Controller	EMCO	2090	N/A	07/30/2014	07/29/2015
RF CABLE	SUIRONG	30MHZ-18GHZ	N/A	07/16/2014	07/15/2015


12.4 MEASURE RESULT (MEASURED AT 3M USING FCC PART15 B LIMITS)

RADIATED EMISSION TEST RESULTS – HORIZONTAL (BELOW 1G)




Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m)	Limit dB(uV/m) PK	Margin dB PK	Pass/Fail	Height cm	Angle deg
37.760	H	5.8	21.2	27.0	40.0	13.0	Pass	100.0	211.6
146.400	H	9.2	14.9	24.1	43.5	19.4	Pass	200.0	267.8
990.300	H	7.6	28.4	36.0	54.0	18.0	Pass	200.0	61.8
293.840	H	9.6	15.5	25.1	46.0	20.9	Pass	100.0	136.6
367.560	H	6.8	17.7	24.5	46.0	21.5	Pass	200.0	2.6
641.100	H	6.7	23.0	29.7	46.0	16.3	Pass	150.0	65.8

RADIATED EMISSION TEST RESULTS – VERTICAL (BELOW 1G)




Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m)	Limit dB(uV/m) PK	Margin dB PK	Pass/Fail	Height cm	Angle deg
37.760	V	7.3	21.2	28.5	40.0	11.5	Pass	100.0	184.2
947.620	V	6.4	28.7	35.1	46.0	10.9	Pass	150.0	171.1
377.260	V	6.3	18.2	24.5	46.0	21.5	Pass	200.0	68.8
173.560	V	5.4	14.6	20.0	43.5	23.5	Pass	100.0	25.1
530.520	V	5.9	21.5	27.4	46.0	18.6	Pass	100.0	240.7
648.860	V	7.3	23.1	30.4	46.0	15.6	Pass	200.0	29.2

RADIATED EMISSION TEST RESULTS – HORIZONTAL (ABOVE 1G)



Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m)	Limit dB(uV/m) PK	Margin dB PK	Pass/Fail	Height cm	Angle deg
2897.500	H	41.1	3.3	44.4	74.0	29.6	Pass	200.0	154.8
2102.500	H	41.4	-2.4	39.0	74.0	35.0	Pass	200.0	298.3
1307.500	H	39.1	-5.4	33.7	74.0	40.3	Pass	200.0	154.8
1810.000	H	39.1	-3.3	35.8	74.0	38.2	Pass	100.0	73.0
2327.500	H	40.1	-1.1	39.0	74.0	35.0	Pass	200.0	154.8
3385.000	H	38.3	4.0	42.3	74.0	31.7	Pass	200.0	154.8

RADIATED EMISSION TEST RESULTS – VERTICAL (ABOVE 1G)



Frequency MHz	Polarization	Reading dB(μV)	Factor dB (1/m)	Level dB(μV/m)	Limit dB(μV/m) PK	Margin dB PK	Pass/Fail	Height cm	Angle deg
2147.500	V	39.8	-2.1	37.7	74.0	36.3	Pass	200.0	249.3
1442.500	V	38.7	-4.4	34.3	74.0	39.7	Pass	200.0	71.6
2822.500	V	41.3	2.6	43.9	74.0	30.1	Pass	200.0	142.1
3265.000	V	39.0	3.9	42.9	74.0	31.1	Pass	100.0	294.2
1720.000	V	39.1	-3.4	35.7	74.0	38.3	Pass	100.0	185.6
2290.000	V	39.6	-1.3	38.3	74.0	35.7	Pass	100.0	185.6

13. AUDIO LOW PASS FILTER RESPONSE

13.1 LIMITS

2.1047(a): Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.

90.242(b)(8): Recommended audio filter attenuation characteristics are given below:

Audio band	Minimum Attenuation Rel. to 1 KHz Attenuation
3 – 20 KHz	$60 \log_{10}(f/3)$ dB where f is in KHz
20 – 30 KHz	50dB

13.2. METHOD OF MEASUREMENTS


The rated audio input signal was applied to the input of the audio low-pass filter (or of all modulation stages) using an audio oscillator, this input signal level and its corresponding output signal were then measured and recorded using the FFT Digital Spectrum Analyzer. Tests were repeated at different audio signal frequencies from 0 to 50 KHz.

13.3 TEST DATA


12.5 KHZ CHANNEL SPACING, F3E, FREQUENCY OF ALL MODULATION STATES (TEST RESULT FOR VHF)-8W

Frequency	Audio In	Audio out	Attenuation	Attenuation	Recommended Attenuation
(KHz)	(dBV)	(dBV)	(Out_In)	Rel.to 3 KHz	(dB)
			dB	(dB)	
0.1	-76.17	-31.21	46.38	-36.53	
0.2	-76.17	-17.38	58.25	-25.63	
0.4	-76.17	-6.29	71.65	-12.83	
0.6	-76.17	0.41	74.25	-6.43	
0.8	-76.17	4.17	78.95	-2.93	
1.0	-76.17	7.18	83.65	-0.03	
1.5	-76.17	8.27	84.85	2.16	
2.0	-76.17	8.99	85.35	1.57	
2.5	-76.17	7.52	83.85	0.67	
3.0	-76.17	6.27	82.55	-1.82	0
3.5	-76.17	2.63	78.45	-4.93	-4
4.0	-76.17	-2.3	74.65	-9.43	-7
4.5	-76.17	-9.21	68.25	-16.53	-12
5.0	-76.17	-15.17	60.65	-21.73	-15
6.0	-76.17	-21.23	54.15	-28.63	-18
7.0	-76.17	-31.61	46.25	-36.43	-22
8.0	-76.17	-39.22	37.95	-47.63	-26
9.0	-76.17	-61.95	15.15	-66.93	-28
10.0	-76.17	-61.95	15.15	-66.43	-31
12.0	-76.17	-61.95	15.15	-66.43	-37
14.0	-76.17	-61.95	15.15	-66.43	-40
16.0	-76.17	-61.95	15.15	-66.43	-44
18.0	-76.17	-61.95	15.15	-66.43	-47
20.0	-76.17	-61.95	15.15	-66.43	-49
25.0	-76.17	-61.95	15.15	-66.43	-49
30.0	-76.17	-61.95	15.15	-66.43	-49
35.0	-76.17	-61.95	15.15	-66.43	-49
40.0	-76.17	-61.95	15.15	-66.43	-49
45.0	-76.17	-61.95	15.15	-66.43	-49
50.0	-76.17	-61.95	15.15	-66.43	-49

Note: Due to the difficulty of measuring the Frequency Response of the internal low-pass filter, the Frequency Response of All Modulation States is performed to show the roll-off at 3 KHz in comparison with the recommended audio filter attenuation.



APPENDIX I: PHOTOGRAPHS OF SETUP
RADIATED EMISSION TEST SETUP



CONDUCTED EMISSION TEST SETUP



APPENDIX II: EXTERNAL VIEW OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



OPEN VIEW-1 OF EUT




OPEN VIEW-2 OF EUT




OPEN VIEW-3 OF EUT




INTERNAL VIEW-1 OF EUT



INTERNAL VIEW-1 OF EUT



INTERNAL VIEW-3 OF EUT



-----END OF REPORT-----