



BY
Tanc Peng
tanc@aziocorp.com

QUICK START GUIDE

USING HOT-SWAPPABLE SWITCHES

Scan QR code to view the full user guide of **CASCADE**. Visit www.azbiocorp.com/support for any additional questions or support needs.



STEP 1. REMOVE KEYCAP

Use the rectangular side of the puller to pull and wiggle the keycaps off gently. Please make sure not to yank the keycaps out as you may damage the switch.

A circular inset diagram showing a close-up of the keyboard being lifted out of the base unit. An arrow points upwards from the keyboard, indicating the direction of removal.

STEP 2. REMOVE SWITCHES

With the keycap off, you should see the switch underneath. Use the tong side of the puller to hook underneath the switch, pushing down onto the two plastic tabs on the top and bottom of the switches.

Now you may gently pull and wiggle the switches out. Please avoid yanking on the switch when extracting.

STEP 3. INSTALL SWITCHES

When you are ready to install new switches, please make sure the pins on your new switches are straight.

on the keyboard and gently pressing down until the switch glides into place. The switch should settle in and feel secure in place if properly lined up.

STEP 4. TEST KEYS

If any of the keys are not working, you may have a bent pin on your switch. Take out the problematic switch, straighten out the pin with the switch puller, then re-install the switch.

FCC STATEMENT

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, it may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

www.aziocorp.com

This document contains confidential, copyrighted, and privileged information. If you are not the intended recipient or believe that you have received this document in error, please inform AZIO Corporation immediately and delete this document from your possession. Please do not print, copy, retransmit or otherwise use of this document without permission and consent of AZIO Corporation.

Copyrighted © 2021