



Prüfbericht-Nr.: <i>Test report no.:</i>	CN25VKMH 001	Auftrags-Nr.: <i>Order no.:</i>	48282485	Seite 1 von 48 Page 1 of 48
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2025-09-26	
Auftraggeber: <i>Client:</i>	AMPAK Technology Inc. 6F-2, No.23, Huanke 1st Rd., Zhubei City 302047, Taiwan			
Prüfgegenstand: <i>Test item:</i>	AP6684PL			
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	AP6684PL			
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C Test report (WLAN 5GHz)			
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart E Section 15.407			
Wareneingangsdatum: <i>Date of sample receipt:</i>	2025-10-22			
Prüfmuster-Nr.: <i>Test sample no:</i>	A004120268-001, 002 A004120268-024			
Prüfzeitraum: <i>Testing period:</i>	2025-11-03 - 2025-12-03			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland Taiwan Ltd. New Taipei Branch			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories			
Prüfergebnis*: <i>Test result*:</i>	Pass			
zusammengestellt von: <i>compiled by:</i>	genehmigt von: <i>authorized by:</i>			
Datum: <i>Date:</i> 2025-12-05	 Anderson Chiu	Ausstellungsdatum: <i>Issue date:</i> 2025-12-05	 Brenda Chen	
Stellung / Position:	Senior Project Manager	Stellung / Position:	Senior Project Manager	
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
5 = mangelhaft N/T = nicht getestet				
5 = poor N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.:
Test report no.:

CN25VKMH 001

Seite 2 von 48
Page 2 of 48

Anmerkungen
Remarks

- | | |
|----------|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</p> <p>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p> |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature</p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.</p> <p>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i></p> <p><i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p> |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p> |

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.407(a) & 15.203	Antenna Requirement	Pass
5.1.2	15.407(a)	Maximum Conducted Output Power	Pass
5.1.3	15.407(h)(1)	Transmit Power Control (TPC)	Not Required
5.1.4	15.407(a)	26 dB Bandwidth	Pass
5.1.4	2.1049	99% Occupied Bandwidth	Pass
5.1.5	15.407(e)	6 dB Bandwidth (U-NII-3 Band only)	Pass
5.1.6	15.407(g)	Frequency Stability	Pass
5.1.7	15.407(a)	Power Spectral Density	Pass
5.1.8	15.407(b) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.1.9	15.407(h) & KDB 905462 D02	Dynamic Frequency Selection	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT	6
1. GENERAL REMARKS	7
1.1 COMPLEMENTARY MATERIALS	7
1.2 DECISION RULE OF CONFORMITY	7
2. TEST SITES	8
2.1 TEST LABORATORY	8
2.2 TEST FACILITY	8
2.3 TRACEABILITY	9
2.4 CALIBRATION	9
2.5 MEASUREMENT UNCERTAINTY	9
3. GENERAL PRODUCT INFORMATION	10
3.1 PRODUCT FUNCTION AND INTENDED USE	10
3.2 SYSTEM DETAILS AND RATINGS	10
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS	12
3.4 SUBMITTED DOCUMENTS	12
4. TEST SET-UP AND OPERATION MODES	13
4.1 PRINCIPLE OF CONFIGURATION SELECTION	13
4.2 CARRIER FREQUENCY AND CHANNEL	14
4.3 TEST OPERATION AND TEST SOFTWARE	15
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	18
4.5 TEST SETUP DIAGRAM	18
4.6 DUTY CYCLE OF TEST SIGNAL	20
5. TEST RESULTS	21
5.1 TRANSMITTER REQUIREMENT & TEST SUITES	21
5.1.1 Antenna Requirement	21
5.1.2 Maximum Conducted Output Power	22
5.1.3 Transmit Power Control (TPC)	29
5.1.4 26 dB Bandwidth and 99% Occupied Bandwidth	30
5.1.5 6 dB Bandwidth (5725-5850MHz)	31
5.1.6 Frequency Stability Measurement	32
5.1.7 Power Spectral Density	34
5.1.8 Radiated Spurious Emissions	36
5.1.9 Dynamic Frequency Selection	41
5.2 MAINS EMISSION	47
5.2.1 Mains Conducted Emission	47

Prüfbericht - Nr.: **CN25VKMH 001**
Test Report No.

Seite 5 von 48
Page 5 of 48

APPENDIX A - TEST RESULT OF CONDUCTED

APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: **CN25VKMH 001**
Test Report No.

Seite 6 von 48
Page 6 of 48

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2025-12-05

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Conducted

Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart E Section 15.407
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10-2020
KDB 789033 D02 General UNII Test Procedures New Rules v02r01
KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02
KDB 662911 D01 Multiple Transmitter Output v02r01

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2. Test Sites

2.1 Test Laboratory

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

TÜV Rheinland Taiwan Ltd. Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 180491 (TW3567)
ISED Registration No.: 25563 (TW3567)

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.30 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.30 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.54 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.52 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a AP6684PL. It contains a WLAN compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	AP6684PL
Type Identification	AP6684PL
FCC ID	ZQ6-AP6684PL

Technical Specification of EUT

Item	EUT information
Operating Frequency	Band 1: 5180 MHz ~ 5240 MHz Band 2: 5260 MHz ~ 5320 MHz Band 3: 5500 MHz ~ 5720 MHz Band 4: 5745 MHz ~ 5825 MHz
Channel Number	Band 1: 4 for 802.11a/802.11n HT20/802.11ac VHT20/802.11ax HE20/802.11be EHT20 2 for 802.11n HT40/802.11ac VHT40/802.11ax HE40/802.11be EHT40 1 for 802.11ac VHT80/802.11ax HE80/802.11be EHT80 Band 2: 4 for 802.11a/802.11n HT20/802.11ac VHT20/802.11ax HE20/802.11be EHT20 2 for 802.11n HT40/802.11ac VHT40/802.11ax HE40/802.11be EHT40 1 for 802.11ac VHT80/802.11ax HE80/802.11be EHT80 Band 3: 11 for 802.11a/802.11n HT20/802.11ac VHT20/802.11ax HE20/802.11be EHT20 5 for 802.11n HT40/802.11ac VHT40/802.11ax HE40/802.11be EHT40 2 for 802.11ac VHT80/802.11ax HE80/802.11be EHT80 Band 4: 5 for 802.11a/802.11n HT20/802.11ac VHT20/802.11ax HE20/802.11be EHT20 2 for 802.11n HT40/802.11ac VHT40/802.11ax HE40/802.11be EHT40 1 for 802.11ac VHT80/802.11ax HE80/802.11be EHT80
Data Rate	802.11a: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7 802.11ac: up to MCS9 802.11ax/be: up to MCS11
Operation Voltage	VBAT: 3.85 Vdc VDDIO: 1.8 Vdc
Modulation	OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) OFDMA (1024QAM)
Maximum Output Power (mW)	5180 ~ 5240 MHz: 111.44 5260 ~ 5320 MHz: 106.55 5500 ~ 5720 MHz: 127.19 5745 ~ 5825 MHz: 104.12
Maximum EIRP (mW)	5260 ~ 5320 MHz: 242.97 5500 ~ 5720 MHz: 305.10
DFS Mode	Slave without radar detection
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

802.11a		802.11n HT20 802.11ac VHT20 802.11ax HE20 802.11be EHT20		802.11n HT40 802.11ac VHT40 802.11ax HE40 802.11be EHT40		802.11ac VHT80 802.11ax HE80 802.11be EHT80	
Channel	Power Setting	Channel	Power Setting	Channel	Power Setting	Channel	Power Setting
36	64	36	60	38	58	42	56
40	72	40	72	46	68	58	54
48	66	48	72	54	70	106	56
52	72	52	72	62	58	122	68
60	72	60	72	102	62	138 (U-NII-2C)	72
64	70	64	64	110	72	138 (U-NII-3)	72
100	70	100	64	134	66	155	64
116	72	116	72	142 (U-NII-2C)	72		
140	62	140	62	142 (U-NII-3)	72		
144 (U-NII-2C)	72	144 (U-NII-2C)	72	151	72		
144 (U-NII-3)	72	144 (U-NII-3)	72	159	72		
149	72	149	72				
157	72	157	72				
165	72	165	72				

4.2 Carrier Frequency and Channel

Band	Channel	Frequency (MHz)	802.11a 802.11n HT20 802.11ac VHT20 802.11ax HE20 802.11be EHT20	802.11n HT40 802.11ac VHT40 802.11ax HE40 802.11be EHT40	802.11ac VHT80 802.11ax HE80 802.11be EHT80
U-NII-1 (Band 1)	36	5180	V		
	38	5190		V	
	40	5200	V		
	42	5210			V
	44	5220	V		
	46	5230		V	
	48	5240	V		
U-NII-2A (Band 2)	52	5260	V		
	54	5270		V	
	56	5280	V		
	58	5290			V
	60	5300	V		
	62	5310		V	
	64	5320	V		
U-NII-2C (Band 3)	100	5500	V		
	102	5510		V	
	104	5520	V		
	106	5530			V
	108	5540	V		
	110	5550		V	
	112	5560	V		
	116	5580	V		
	118	5590		V	
	120	5600	V		
	122	5610			V
	124	5620	V		
	126	5630		V	
	128	5640	V		
	132	5660	V		
	134	5670		V	
	136	5680	V		
	140	5700	V		
Straddle Channel	138	5690			V
	142	5710		V	
	144	5720	V		
U-NII-3 (Band 4)	149	5745	V		
	151	5755		V	
	153	5765	V		
	155	5775			V
	157	5785	V		
	159	5795		V	
	161	5805	V		
	165	5825	V		

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	command
---------------	---------

The samples were used as follows:

A004120268-001, 002

A004120268-024

Full test was applied on all test modes, but only worst case was shown.

The EUT incorporates a MIMO function. Physically, the EUT provides two complete transmitters and receivers.

Modulation Mode	Tx Function
802.11a	2TX (MIMO)
802.11n HT20	2TX (MIMO)
802.11n HT40	2TX (MIMO)
802.11ac VHT20	2TX (MIMO)
802.11ac VHT40	2TX (MIMO)
802.11ac VHT80	2TX (MIMO)
802.11ax HE20	2TX (MIMO)
802.11ax HE40	2TX (MIMO)
802.11ax HE80	2TX (MIMO)
802.11be EHT20	2TX (MIMO)
802.11be EHT40	2TX (MIMO)
802.11be EHT80	2TX (MIMO)

* The modulation and bandwidth are similar for 802.11n mode HT20/40 and 802.11ac mode VHT20/40/80 and 802.11ax mode HE20/40/80 and 802.11be mode EHT20/40/80, therefore, only investigated worse case as representative mode in test report.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	√	-

Note:

- The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **Z-plane**.
- "-" means no effect.

Prüfbericht - Nr.: CN25VKMH 001
Test Report No.

Seite 16 von 48
Page 16 of 48

Antenna Port Conducted Measurement
☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36, 40, 48	6.0
-		5260-5320	52 to 64	52, 60, 64	
-		5500-5720	100 to 144	100, 116, 140, 144	
-		5745-5825	149 to 165	149, 157, 165	
Power Only	802.11n HT20	5180-5240	36 to 48	36, 40, 48	MCS0
		5260-5320	52 to 64	52, 60, 64	
		5500-5720	100 to 144	100, 116, 140, 144	
		5745-5825	149 to 165	149, 157, 165	
	802.11n HT40	5190-5230	38 to 46	38, 46	MCS0
		5270-5310	54 to 62	54, 62	
		5510-5670	102 to 142	102, 110, 134, 142	
		5755-5795	151 to 159	151, 159	
	802.11ac VHT20	5180-5240	36 to 48	36, 40, 48	NSS1 MCS0
		5260-5320	52 to 64	52, 60, 64	
		5500-5720	100 to 144	100, 116, 140, 144	
		5745-5825	149 to 165	149, 157, 165	
	802.11ac VHT40	5190-5230	38 to 46	38, 46	NSS1 MCS0
		5270-5310	54 to 62	54, 62	
		5510-5670	102 to 142	102, 110, 134, 142	
		5755-5795	151 to 159	151, 159	
	802.11ac VHT80	5210	42	42	NSS1 MCS0
		5290	58	58	
		5530-5610	106 to 138	106, 122, 138	
		5775	155	155	
	802.11ax HE20	5180-5240	36 to 48	36, 40, 48	NSS1 MCS0
		5260-5320	52 to 64	52, 60, 64	
		5500-5720	100 to 144	100, 116, 140, 144	
		5745-5825	149 to 165	149, 157, 165	
	802.11ax HE40	5190-5230	38 to 46	38, 46	NSS1 MCS0
		5270-5310	54 to 62	54, 62	
		5510-5670	102 to 142	102, 110, 134, 142	
		5755-5795	151 to 159	151, 159	
	802.11ax HE80	5210	42	42	NSS1 MCS0
		5290	58	58	
		5530-5610	106 to 138	106, 122, 138	
		5775	155	155	
-	802.11be EHT20	5180-5240	36 to 48	36, 40, 48	NSS1 MCS0
-		5260-5320	52 to 64	52, 60, 64	
-		5500-5720	100 to 144	100, 116, 140, 144	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11be EHT40	5190-5230	38 to 46	38, 46	NSS1 MCS0
-		5270-5310	54 to 62	54, 62	
-		5510-5670	102 to 142	102, 110, 134, 142	
-		5755-5795	151 to 159	151, 159	
-	802.11be EHT80	5210	42	42	NSS1 MCS0
-		5290	58	58	
-		5530-5610	106 to 138	106, 122, 138	
-		5775	155	155	

Prüfbericht - Nr.: CN25VKMH 001
Test Report No.

Seite 17 von 48
Page 17 of 48

Radiated Spurious Emissions (Above 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36, 40, 48	6.0
-		5260-5320	52 to 64	52, 60, 64	
-		5500-5720	100 to 144	100, 116, 140, 144	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11be EHT20	5180-5240	36 to 48	36, 40, 48	NSS1 MCS0
-		5260-5320	52 to 64	52, 60, 64	
-		5500-5720	100 to 144	100, 116, 140, 144	
-		5745-5825	149 to 165	149, 157, 165	
-	802.11be EHT40	5190-5230	38 to 46	38, 46	NSS1 MCS0
-		5270-5310	54 to 62	54, 62	
-		5510-5670	102 to 142	102, 110, 134, 142	
-		5755-5795	151 to 159	151, 159	
-	802.11be EHT80	5210	42	42	NSS1 MCS0
-		5290	58	58	
-		5530-5610	106 to 138	106, 122, 138	
-		5775	155	155	

Radiated Spurious Emissions (Below 1 GHz)

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11be EHT80	5530-5610	106 to 138	138	NSS1 MCS0

Mains Conducted Emission Test

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency (MHz)	Available Channel	Tested Channel	Date Rate (Mbps)
-	802.11be EHT80	5530-5610	106 to 138	138	NSS1 MCS0

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	22-26 °C	50-65 %	Nick Hsu
Radiated Spurious Emissions above 1 GHz	22.5-24.7 °C	46-50 %	Roger Liao
Radiated Spurious Emissions below 1 GHz	22.5-24.7 °C	46-50 %	Roger Liao
Mains Conducted Emission	22.8 °C	55 %	Roger Liao

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT


None.

Support Unit


Support Unit								
No	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
Radiated and Mains Conducted Test								
A	Type C Cable	Ampak	Ampak-01	-	-	-	100	--
1	Adapter	OPPO	VC56JACH	J119492AC1009 359	-	-	-	--
Conducted Test								
-	USB Type-C To USB Type-A	TUV	TUV-06	1	-	-	150	--
-	Adapter	HANG	C6	C2A-C6-BK	-	-	-	-
-	Setup NB Linux	acer	ZQW	NXV7BTA01640 303DC37600	-	-	-	-
DFS Test								
-	Notebook	Acer	N20C4	NXA1UTA00114 210D5C3400	-	-	-	-
-	Signaling unit	TP-Link	Archer BE800	Y2360M9000808	-	-	-	-

4.5 Test Setup Diagram

<Radiated Spurious Emissions Mode>




<Mains Conducted Emission Mode>



4.6 Duty Cycle of Test Signal

Mode	On + Off Time (ms)	On Time (ms)	Duty Cycle (%)	Duty Factor (dB)
802.11a	2.095	2.055	98.09	0.08
802.11be EHT20	1.53	1.49	97.39	0.12
802.11be EHT40	0.815	0.78	95.71	0.19
802.11be EHT80	0.445	0.405	91.01	0.41



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the EUT's antenna specifications are described as below.
 The antenna is used with no possibility of replacement with a non-approved antenna by the end-user.
 Therefore, the EUT is considered to comply with this provision.

ANT	Antenna Type	Gain (dBi)			
		5180~5240 MHz	5260~5320 MHz	5500~5720 MHz	5745~5825 MHz
1	Loop	2.81	3.58	3.80	3.68
2	Loop	2.37	3.26	3.65	3.35
CDD Mode	Power Directional Gain =	2.81	3.58	3.80	3.68
	PSD Directional Gain = $10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$	5.60	6.43	6.74	6.53

Refer to EUT photo for details.

5.1.2 Maximum Conducted Output Power

Limit

Operation Band	EUT Category	Limit
U-NII-1	Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125 mW (21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
	Fixed point-to-point Access Point	1 Watt (30 dBm)
	Indoor Access Point	1 Watt (30 dBm)
	Mobile and Portable client device	250 mW (24 dBm)
U-NII-2A	---	250 mW (24 dBm) or 11 dBm + 10 log B*
U-NII-2C	---	250 mW (24 dBm) or 11 dBm + 10 log B*
U-NII-3	---	1 Watt (30 dBm)

Note: B* is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20 MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

Kind of Test Site Shielded room

Test Setup



Test Instruments


Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2025/2/26	2026/2/25	2025/11/11	2025/11/12
Power Sensor	Anritsu	MA2411B	1725269	2025/2/26	2026/2/25	2025/11/11	2025/11/12

Test Procedures

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to AVERAGE. Duty factor is not added to measured value.

Gate Setup:

1. Select the [Gates] tab in the software.
2. Check the box (e.g., Gate 1) to display it on the trace.
3. Set Gate Position
 - Drag the gate line with the mouse to the desired point on the waveform, or
 - Enter Values using the [Set] button and input start/stop times.
4. Switch to the next measurement channel and repeat the same gate setup procedure.
5. The instrument calculates average/peak power only within the defined gate interval.



Test Result
<802.11a>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
36	5180	16.66	17.50	20.11	102.58	24.00
40	5200	17.50	17.42	20.47	111.44	24.00
48	5240	16.32	17.55	19.99	99.74	24.00
52	5260	16.79	17.46	20.15	103.47	24.00
60	5300	16.89	16.83	19.87	97.06	24.00
64	5320	16.70	16.67	19.70	93.23	24.00
100	5500	16.87	16.41	19.66	92.39	24.00
116	5580	17.05	16.93	20.00	100.02	24.00
140	5700	15.08	15.07	18.09	64.35	24.00
144	5720 (U-NII-2C)	16.90	16.85	19.89	97.40	24.00
144	5720 (U-NII-3)	16.90	16.85	19.89	97.40	30.00
149	5745	16.66	17.06	19.87	97.16	30.00
157	5785	16.52	16.97	19.76	94.65	30.00
165	5825	16.62	16.68	19.66	92.48	30.00

Note:
For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(39.20) = 26.93 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(40.68) = 27.09 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(36.56) = 26.63 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(29.22) = 25.66 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(37.56) = 26.75 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(21.53) = 24.33 \text{ dBm} > 24 \text{ dBm}$.
7. $11 \text{ dBm} + 10\log(23.73) = 24.75 \text{ dBm} > 24 \text{ dBm}$.

<802.11n HT20>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
36	5180	15.04	14.29	17.69	58.77	24.00
40	5200	17.02	16.06	19.58	90.71	24.00
48	5240	17.11	16.26	19.72	93.67	24.00
52	5260	16.66	16.86	19.77	94.87	24.00
60	5300	16.78	16.71	19.76	94.52	24.00
64	5320	15.26	15.71	18.50	70.81	24.00
100	5500	14.91	15.62	18.29	67.45	24.00
116	5580	16.58	16.90	19.75	94.48	24.00
140	5700	14.89	15.14	18.03	63.49	24.00
144	5720 (U-NII-2C)	16.61	16.98	19.81	95.70	23.05
144	5720 (U-NII-3)	16.61	16.98	19.81	95.70	30.00
149	5745	16.52	16.81	19.68	92.85	30.00
157	5785	16.39	16.73	19.57	90.65	30.00
165	5825	16.31	16.56	19.45	88.05	30.00

<802.11n HT40>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
38	5190	15.14	13.81	17.54	56.70	24.00
46	5230	17.23	15.67	19.53	89.74	24.00
54	5270	16.91	16.97	19.95	98.86	24.00
62	5310	14.51	14.40	17.47	55.79	24.00
102	5510	15.08	14.87	17.99	62.90	24.00
110	5550	16.95	16.98	19.98	99.43	24.00
134	5670	15.83	16.02	18.94	78.28	24.00
142	5710 (U-NII-2C)	17.20	17.12	20.17	104.00	24.00
142	5710 (U-NII-3)	17.20	17.12	20.17	104.00	30.00
151	5755	16.91	17.08	20.01	100.14	30.00
159	5795	16.81	16.95	19.89	97.52	30.00

<802.11ac VHT20>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
36	5180	15.12	14.35	17.76	59.74	24.00
40	5200	17.09	16.13	19.65	92.19	24.00
48	5240	17.17	16.31	19.77	94.88	24.00
52	5260	16.72	16.91	19.83	96.08	24.00
60	5300	16.84	16.78	19.82	95.95	24.00
64	5320	15.31	15.75	18.55	71.55	24.00
100	5500	14.96	15.65	18.33	68.06	24.00
116	5580	16.64	16.97	19.82	95.91	24.00
140	5700	14.96	15.21	18.10	64.52	24.00
144	5720 (U-NII-2C)	16.68	17.02	19.86	96.91	23.05
144	5720 (U-NII-3)	16.68	17.02	19.86	96.91	30.00
149	5745	16.57	16.86	19.73	93.92	30.00
157	5785	16.44	16.79	19.63	91.81	30.00
165	5825	16.38	16.63	19.52	89.48	30.00

<802.11ac VHT40>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
38	5190	15.23	13.87	17.61	57.72	24.00
46	5230	17.27	15.72	19.57	90.66	24.00
54	5270	16.96	17.02	20.00	100.01	24.00
62	5310	14.55	14.45	17.51	56.37	24.00
102	5510	15.14	14.93	18.05	63.78	24.00
110	5550	16.98	17.05	20.03	100.59	24.00
134	5670	15.91	16.07	19.00	79.45	24.00
142	5710 (U-NII-2C)	17.29	17.17	20.24	105.70	24.00
142	5710 (U-NII-3)	17.29	17.17	20.24	105.70	30.00
151	5755	16.95	17.10	20.04	100.83	30.00
159	5795	16.85	17.01	19.94	98.65	30.00

<802.11ac VHT80>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
42	5210	15.16	14.69	17.94	62.25	24.00
58	5290	14.15	15.02	17.62	57.77	24.00
106	5530	14.43	14.77	17.61	57.72	24.00
122	5610	16.91	17.46	20.20	104.81	24.00
138	5690 (U-NII-2C)	17.61	18.11	20.88	122.39	24.00
138	5690 (U-NII-3)	17.61	18.11	20.88	122.39	30.00
155	5775	15.63	16.64	19.17	82.69	30.00

<802.11ax HE20>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
36	5180	15.16	14.55	17.88	61.32	24.00
40	5200	17.17	16.27	19.75	94.48	24.00
48	5240	17.27	16.38	19.86	96.78	24.00
52	5260	16.77	16.97	19.88	97.31	24.00
60	5300	16.91	17.01	19.97	99.33	24.00
64	5320	15.36	15.81	18.60	72.46	24.00
100	5500	15.01	15.72	18.39	69.02	24.00
116	5580	16.72	17.04	19.89	97.57	24.00
140	5700	15.01	15.29	18.16	65.50	24.00
144	5720 (U-NII-2C)	16.75	17.06	19.92	98.13	23.05
144	5720 (U-NII-3)	16.75	17.06	19.92	98.13	30.00
149	5745	16.64	17.12	19.90	97.65	30.00
157	5785	16.51	16.86	19.70	93.30	30.00
165	5825	16.43	16.72	19.59	90.94	30.00

<802.11ax HE40>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
38	5190	15.27	13.93	17.66	58.37	24.00
46	5230	17.35	15.84	19.67	92.70	24.00
54	5270	17.01	17.07	20.05	101.17	24.00
62	5310	14.63	14.75	17.70	58.89	24.00
102	5510	15.24	15.05	18.16	65.41	24.00
110	5550	17.12	17.41	20.28	106.60	24.00
134	5670	16.26	16.11	19.20	83.10	24.00
142	5710 (U-NII-2C)	17.40	17.45	20.44	110.54	24.00
142	5710 (U-NII-3)	17.40	17.45	20.44	110.54	30.00
151	5755	17.13	17.16	20.16	103.64	30.00
159	5795	16.91	17.10	20.02	100.38	30.00

<802.11ax HE80>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
42	5210	15.47	14.81	18.16	65.51	24.00
58	5290	14.32	15.26	17.83	60.61	24.00
106	5530	14.50	14.83	17.68	58.59	24.00
122	5610	17.13	17.72	20.45	110.80	24.00
138	5690 (U-NII-2C)	17.81	18.17	21.00	126.01	24.00
138	5690 (U-NII-3)	17.81	18.17	21.00	126.01	30.00
155	5775	15.78	16.82	19.34	85.93	30.00

<802.11be EHT20>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
36	5180	15.21	14.62	17.94	62.16	24.00
40	5200	17.20	16.34	19.80	95.53	24.00
48	5240	17.32	16.69	20.03	100.62	24.00
52	5260	16.86	17.03	19.96	98.99	24.00
60	5300	16.99	17.05	20.03	100.70	24.00
64	5320	15.43	15.87	18.67	73.55	24.00
100	5500	15.07	15.77	18.44	69.89	24.00
116	5580	16.83	17.12	19.99	99.72	24.00
140	5700	15.08	15.34	18.22	66.41	24.00
144	5720 (U-NII-2C)	16.86	17.19	20.04	100.89	23.05
144	5720 (U-NII-3)	16.86	17.19	20.04	100.89	30.00
149	5745	16.61	17.21	19.93	98.42	30.00
157	5785	16.64	16.91	19.79	95.22	30.00
165	5825	16.51	16.98	19.76	94.66	30.00

Note:
For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(40.64) = 27.09 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(24.27) = 24.85 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(21.50) = 24.32 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(21.50) = 24.32 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(27.17) = 25.34 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(21.62) = 24.35 \text{ dBm} > 24 \text{ dBm}$.
7. $11 \text{ dBm} + 10\log(16.04) = 23.05 \text{ dBm} < 24 \text{ dBm}$.

Prüfbericht - Nr.: CN25VKMH 001
Test Report No.

Seite 28 von 48
Page 28 of 48

<802.11be EHT40>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
38	5190	15.31	14.21	17.81	60.33	24.00
46	5230	17.39	15.93	19.73	94.00	24.00
54	5270	17.30	17.23	20.28	106.55	24.00
62	5310	14.96	14.99	17.99	62.88	24.00
102	5510	15.40	15.19	18.31	67.71	24.00
110	5550	17.33	17.66	20.51	112.42	24.00
134	5670	16.39	16.20	19.31	85.24	24.00
142	5710 (U-NII-2C)	17.57	17.49	20.54	113.25	24.00
142	5710 (U-NII-3)	17.57	17.49	20.54	113.25	30.00
151	5755	17.15	17.18	20.18	104.12	30.00
159	5795	17.02	17.13	20.09	101.99	30.00

Note:

For U-NII-2A, U-NII-2C Band:

1. $11 \text{ dBm} + 10\log(77.00) = 29.86 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(40.44) = 27.07 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(40.36) = 27.06 \text{ dBm} > 24 \text{ dBm}$.
4. $11 \text{ dBm} + 10\log(73.97) = 29.69 \text{ dBm} > 24 \text{ dBm}$.
5. $11 \text{ dBm} + 10\log(40.68) = 27.09 \text{ dBm} > 24 \text{ dBm}$.
6. $11 \text{ dBm} + 10\log(50.72) = 28.05 \text{ dBm} > 24 \text{ dBm}$.

<802.11be EHT80>

Channel	Channel Frequency (MHz)	Average Output Power (dBm)		Total Power		Limit (dBm)
		Ant 1	Ant 2	(dBm)	(mW)	
42	5210	15.56	15.03	18.31	67.82	24.00
58	5290	14.46	15.33	17.93	62.04	24.00
106	5530	14.54	14.95	17.76	59.71	24.00
122	5610	17.27	17.76	20.53	113.04	24.00
138	5690 (U-NII-2C)	17.84	18.22	21.04	127.19	24.00
138	5690 (U-NII-3)	17.84	18.22	21.04	127.19	30.00
155	5775	15.83	16.91	19.41	87.37	30.00

Note:

For U-NII-2A, U-NII-2C Band:

Ant 1

1. $11 \text{ dBm} + 10\log(82.32) = 30.15 \text{ dBm} > 24 \text{ dBm}$.
2. $11 \text{ dBm} + 10\log(82.48) = 30.16 \text{ dBm} > 24 \text{ dBm}$.
3. $11 \text{ dBm} + 10\log(87.27) = 30.41 \text{ dBm} > 24 \text{ dBm}$.

5.1.3 Transmit Power Control (TPC)

Requirement U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p of less than 500 mW.

Maximum EIRP of this device is 305.10mW which is less than 500mW, therefore it's not required TPC function.


TPC	E.I.R.P	15.407(h)(1)
	> 500mW	The TPC mechanism is required for system with an E.I.R.P. of above 500mW
V	< 500mW	-

Note: The product supports the TPC function.

5.1.4 26 dB Bandwidth and 99% Occupied Bandwidth

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2025/11/11	2025/11/24
Thermal Chamber	GIANT FORCE	GCT-099-40-S	MAF0103-007	2025/02/24	2026/02/23	2025/11/11	2025/11/24

Test Procedure

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
- For 99% Bandwidth Measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

Test Results

Please refer to Appendix A


Prüfbericht - Nr.: CN25VKMH 001
Test Report No.

Seite 31 von 48
Page 31 of 48

5.1.5 6 dB Bandwidth (5725-5850MHz)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2025/11/11	2025/11/24
Thermal Chamber	GIANT FORCE	GCT-099-40-S	MAF0103-007	2025/02/24	2026/02/23	2025/11/11	2025/11/24

Test Procedure

MEASUREMENT PROCEDURE REF

- Set resolution bandwidth (RBW) = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


Test Results

Please refer to Appendix A

5.1.6 Frequency Stability Measurement

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2025/11/11	2025/11/24
Thermal Chamber	GIANT FORCE	GCT-099-40-S	MAF0103-007	2025/02/24	2026/02/23	2025/11/11	2025/11/24

Test Procedure

- To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
- The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10 dB lower than the measured peak value.
- The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

Prüfbericht - Nr.: CN25VKMH 001
Test Report No.

 Seite 33 von 48
 Page 33 of 48

Test Results

Frequency (MHz)	5180			
Voltage (V)	Measurement Frequency (MHz)			Max. Deviation (ppm)
5.5	5180.00868			1.676
5	5180.00868			1.676
4.5	5180.00868			1.676
Temperature (°C)	Measurement Frequency (MHz)			
	0 Minute	2 Minute	5 Minute	10 Minute
85	5180.0912	5180.0912	5180.0916	5180.0912
80	5180.0968	5180.0964	5180.0972	5180.0976
70	5180.03329	5180.04124	5180.05065	5180.05499
60	5180.01375	5180.01809	5180.02243	5180.02315
50	5180.00651	5180.00724	5180.00796	5180.00796
40	5180.00507	5180.00507	5180.00507	5180.00507
30	5180.00651	5180.00868	5180.00868	5180.00868
20	5180.00868	5180.00897	5180.00897	5180.00868
10	5180.03068	5180.03068	5180.03068	5180.03068
0	5180.04139	5180.04139	5180.04139	5180.04139
-10	5180.04863	5180.04863	5180.04863	5180.04863
-20	5180.04949	5180.0492	5180.0492	5180.04978
-30	5180.04168	5180.0411	5180.04081	5180.0411
Max. Deviation (ppm)	18.687	18.610	18.764	18.842

5.1.7 Power Spectral Density

Limit

For the 5.15~5.25GHz Bands:

For mobile and portable client devices in the 5.15~5.25GHz band, the Maximum Power spectral density shall not exceed 11dBm/MHz. For an indoor access point operating in the band 5.15~5.25GHz, the maximum power spectral density shall not exceed 17dBm/MHz.

For the 5.25~5.35GHz and 5.47~5.725GHz Bands:


The maximum power spectral density shall not exceed 11dBm/MHz.

For the 5.745~5.85GHz Bands:

The maximum power spectral density shall not exceed 30dBm/500kHz.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2025/05/14	2026/05/13	2025/11/11	2025/11/24
Thermal Chamber	GIANT FORCE	GCT-099-40-S	MAF0103-007	2025/02/24	2026/02/23	2025/11/11	2025/11/24

Test Procedure

For U-NII-1, U-NII-2A, U-NII-2C band:

Using method SA-1 Duty cycle >98%

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW ≥ 3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value

Using method SA-2 Duty cycle <98%

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 1 MHz, Set VBW ≥ 3 MHz, Detector = RMS
3. Sweep time = auto, trigger set to "free run".
4. Trace average at least 100 traces in power averaging mode.
5. Record the max value and add 10 log (1/duty cycle)

※For U-NII-3: Duty cycle >98 %

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 500 kHz, Set VBW $\geq$ 3 RBW, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
4. Sweep time = auto, trigger set to "free run".
5. Trace average at least 100 traces in power averaging mode.
6. Record the max value

※For U-NII-3: Duty cycle <98 %

1. Set span to encompass the entire emission bandwidth (EBW) of the signal.
2. Set RBW = 500 kHz, Set VBW $\geq$ 3 RBW, Detector = RMS
3. Use the peak marker function to determine the maximum power level in any 500 kHz band segment within the fundamental EBW.
4. Sweep time = auto, trigger set to "free run".
5. Trace average at least 100 traces in power averaging mode.
6. Record the max value and add 10 log (1/duty cycle)

For MIMO mode, calculation method follows FCC KDB 662911 Method 2) a) of power density measurement using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.

Test Results

Please refer to Appendix A

5.1.8 Radiated Spurious Emissions

Limit


Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).

Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.407(b).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup


<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Prüfbericht - Nr.: CN25VKMH 001
Test Report No.

 Seite 38 von 48
 Page 38 of 48

Test Instruments

Test Date: 2025/11/3 ~ 2025/11/9

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1 GHz					
Signal Analyzer	R&S	FSV40	101509	2025/5/7	2026/5/6
Horn Antenna	ETS-Lindgren	3117	00218930	2024/12/10	2025/12/9
Horn Antenna	SCHWARZBECK	BBHA 9170	00887	2025/3/28	2026/3/27
Amplifier	EM	EM01G18GA	060967	2025/4/2	2026/4/1
HF-AMP + AC source	EMCI	EMC184045SE	980657	2025/2/4	2026/2/3
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
30MHz – 1GHz					
Receiver	R&S	ESR7	102108	2025/7/2	2026/7/1
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2025/4/8	2026/4/7
LF-AMP	Agilent	8447D	2944A107722	2025/3/19	2026/3/18
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
Below 30MHz					
Receiver	R&S	ESR7	102108	2025/7/2	2026/7/1
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2024/12/11	2025/12/10
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht - Nr.: **CN25VKMH 001**
Test Report No.

Seite 40 von 48
Page 40 of 48

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Amplifier (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

5.1.9 Dynamic Frequency Selection

Limit

<DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection>

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

<DFS Response Requirement Values>


Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time and the Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Kind of Test Site


Shielded room

Test Setup


<Setup for Master with injection at the Master>



<Setup for Client with injection at the Master>



<Setup for Client with injection at the Client>



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	Keysight	N9000B	MY62361339	2025/02/13	2026/02/12	2025/11/3	2025/11/3
EXG Vector Signal Generator	Keysight	N5172B	MY61253270	2024/12/24	2025/12/23	2025/11/3	2025/11/3
Frequency Extender	Keysight	N5182BX07	MY61500182	2024/12/24	2025/12/23	2025/11/3	2025/11/3

Requirement

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required



Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

Prüfbericht - Nr.: **CN25VKMH 001**
Test Report No.

Seite 44 von 48
Page 44 of 48

Test Results





<802.11be EHT80 >

Channel Moving Time (CMT):

Radar Type	Channel (MHz)	Channel Move Time (s)	Limit (s)	Result
R0	5290	0.538	10	Pass
R0	5530	0.510	10	Pass

Channel Closing Transmission Time (CCTT):

Radar Type	Channel (MHz)	Channel Closing Transmission Time (s)	Limit (ms)	Result
R0	5290	0.012	< 60	Pass
R0	5530	0.012	< 60	Pass




Prüfbericht - Nr.: CN25VKMH 001
Test Report No.

Seite 46 von 48
 Page 46 of 48

Non-occupancy period

Channel (MHz)	Limit (minute)	Result
5290	≥ 30	Pass
5530	≥ 30	Pass



5.2 Mains Emission


5.2.1 Mains Conducted Emission

Limit

Mains Conducted emissions as defined in §15.207 must comply with the mains conducted emission limits.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Test Date: 2025/12/3

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Two-Line V-Network	Rohde & Schwarz	ENV216	101243	2025/8/6	2026/8/5
EMI Test Receiver	R&S	ESCI	101094	2025/11/19	2026/11/18

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

Test Results

Please refer to Appendix B.