

RF Exposure Evaluation declaration

Product Name	Network Media Module
Model No.	CY920-24C
FCC ID	ZQO-CY92024C

Applicant	MICROCHIP TECHNOLOGY INC.
Address	2355 West Chandler Blvd.Chandler, Arizona, USA 85224-6199

Date of Receipt	Jun. 04, 2014
Date of Declaration	Jun. 26, 2014
Report No.	1460175R-RFUSP26V00

The test results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.
This report must not be used to claim product endorsement by TAF or any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : Network Media Module
Test Item : RF Exposure Evaluation
Test Site : No.3 OATS

WLAN:

Operation Frequency	2412-2462MHz, 2422-2452MHz
Maximum Conducted output power	21.98dBm
Antenna gain	1.84dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
157.7611	0.047944

Power density in column 4 is much lower than the limit (1 mW/cm²).

BT:

Operation Frequency	2402-2480MHz
Maximum Conducted output power	2.46dBm
Antenna gain	1.84dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1.7620	0.000535

Power density in column 4 is much lower than the limit (1 mW/cm²).