

# TEST REPORT

**Applicant:** Signcomplex Limited

**Address of Applicant:** 401,Mingfeng Bulding, No.2 Xikeng Road, Xinhe Community, Fucheng Street, Longhua, Shenzhen, Guangdong 518110, China

**Manufacturer:** Signcomplex Limited

**Address of Manufacturer:** No.70 Hexiang West Road, Heshan Industrial Park, Heshan, Guangdong, China

**Equipment Under Test (EUT)**

**Product Name:** LED Camera Motion Security Lights

**Model No.:** SEC102P-36W-CCT-R80-0001, SEC103P-020-CCT-R80-0001, SEC102P-036-CCT-RXX-YY, SEC103P-020-CCT-RXX-YY  
YY---The "YY": can be 70, 80, 90, represent LED Color Rendering Index 70、80、90;  
ZZ-- from 01 to 99, represents the Light body color or sequential number  
Including: 01 indicates the light body color white, 02 indicates the light color black, 03 represents the light body color bronze

**FCC ID:** ZR3-SECABCAM5G

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** January 25, 2024

**Date of Test:** January 26, 2024-March 28, 2024

**Date of report issued:** March 28, 2024

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



**Robinson Luo**


**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

| Version No. | Date           | Description |
|-------------|----------------|-------------|
| 00          | March 28, 2024 | Original    |
|             |                |             |
|             |                |             |
|             |                |             |
|             |                |             |

Prepared By:




Project Engineer

Date:

March 28, 2024

Check By:



Reviewer

Date:

March 28, 2024

## 3 Contents

|                                                                  | Page |
|------------------------------------------------------------------|------|
| 1 COVER PAGE .....                                               | 1    |
| 2 VERSION .....                                                  | 2    |
| 3 CONTENTS .....                                                 | 3    |
| 4 TEST SUMMARY .....                                             | 4    |
| 5 GENERAL INFORMATION .....                                      | 5    |
| 5.1 GENERAL DESCRIPTION OF EUT .....                             | 5    |
| 5.2 TEST MODE .....                                              | 7    |
| 5.3 DESCRIPTION OF SUPPORT UNITS .....                           | 7    |
| 5.4 DEVIATION FROM STANDARDS .....                               | 7    |
| 5.5 ABNORMALITIES FROM STANDARD CONDITIONS .....                 | 7    |
| 5.6 TEST FACILITY .....                                          | 7    |
| 5.7 TEST LOCATION .....                                          | 7    |
| 5.8 ADDITIONAL INSTRUCTIONS .....                                | 7    |
| 6 TEST INSTRUMENTS LIST .....                                    | 8    |
| 7 TEST RESULTS AND MEASUREMENT DATA .....                        | 10   |
| 7.1 ANTENNA REQUIREMENT .....                                    | 10   |
| 7.2 CONDUCTED EMISSIONS .....                                    | 11   |
| 7.3 CONDUCTED OUTPUT POWER .....                                 | 16   |
| 7.4 CHANNEL BANDWIDTH .....                                      | 17   |
| 7.5 POWER SPECTRAL DENSITY .....                                 | 18   |
| 7.6 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS ..... | 19   |
| 7.6.1 Conducted Emission Method .....                            | 19   |
| 7.6.2 Radiated Emission Method .....                             | 20   |
| 8 TEST SETUP PHOTO .....                                         | 37   |
| 9 EUT CONSTRUCTIONAL DETAILS .....                               | 37   |

## 4 Test Summary

| Test Item                        | Section                    | Result |
|----------------------------------|----------------------------|--------|
| Antenna requirement              | FCC part 15.203/15.247 (c) | Pass   |
| AC Power Line Conducted Emission | FCC part 15.207            | Pass   |
| Conducted Peak Output Power      | FCC part 15.247 (b)(3)     | Pass   |
| Channel Bandwidth & 99% OCB      | FCC part 15.247 (a)(2)     | Pass   |
| Power Spectral Density           | FCC part 15.247 (e)        | Pass   |
| Band Edge                        | FCC part 15.247(d)         | Pass   |
| Spurious Emission                | FCC part 15.205/15.209     | Pass   |

*Remark: Test according to ANSI C63.10:2013 and RSS-Gen*

*Pass: The EUT complies with the essential requirements in the standard.*

### Measurement Uncertainty

| Test Item                        | Frequency Range | Measurement Uncertainty | Notes |
|----------------------------------|-----------------|-------------------------|-------|
| Radiated Emission                | 9kHz-30MHz      | 3.1dB                   | (1)   |
| Radiated Emission                | 30MHz-200MHz    | 3.8039dB                | (1)   |
| Radiated Emission                | 200MHz-1GHz     | 3.9679dB                | (1)   |
| Radiated Emission                | 1GHz-18GHz      | 4.29dB                  | (1)   |
| Radiated Emission                | 18GHz-40GHz     | 3.30dB                  | (1)   |
| AC Power Line Conducted Emission | 0.15MHz ~ 30MHz | 3.44dB                  | (1)   |

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

|                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:                                                                                                                                                                          | LED Camera Motion Security Lights                                                                                                                                                                                                                                                                                                                                                                      |
| Model No.:                                                                                                                                                                             | SEC102P-36W-CCT-R80-0001, SEC103P-020-CCT-R80-0001, SEC102P-036-CCT-RXX-YY, SEC103P-020-CCT-RXX-YY<br>YY---The "YY": can be 70, 80, 90, represent LED Color Rendering Index 70、80、90;<br>ZZ-- from 01 to 99, represents the Light body color or sequential number<br>Including: 01 indicates the light body color white, 02 indicates the light color black, 03 represents the light body color bronze |
| Test Model No:                                                                                                                                                                         | SEC102P-36W-CCT-R80-0001, SEC103P-020-CCT-R80-0001                                                                                                                                                                                                                                                                                                                                                     |
| Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are light body color and model name for commercial purpose. |                                                                                                                                                                                                                                                                                                                                                                                                        |
| Test sample(s) ID:                                                                                                                                                                     | GTS2024010316-1                                                                                                                                                                                                                                                                                                                                                                                        |
| Sample(s) Status                                                                                                                                                                       | Engineer sample                                                                                                                                                                                                                                                                                                                                                                                        |
| S/N:                                                                                                                                                                                   | 2401220001                                                                                                                                                                                                                                                                                                                                                                                             |
| Operation Frequency:                                                                                                                                                                   | 802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz<br>802.11n(HT40): 2422MHz~2452MHz                                                                                                                                                                                                                                                                                                                       |
| Channel numbers:                                                                                                                                                                       | 802.11b/802.11g /802.11n(HT20): 11<br>802.11n(HT40):7                                                                                                                                                                                                                                                                                                                                                  |
| Channel separation:                                                                                                                                                                    | 5MHz                                                                                                                                                                                                                                                                                                                                                                                                   |
| Modulation technology:                                                                                                                                                                 | 802.11b: Direct Sequence Spread Spectrum (DSSS)<br>802.11g/802.11n(HT20) /802.11n(HT40):<br>Orthogonal Frequency Division Multiplexing (OFDM)                                                                                                                                                                                                                                                          |
| Antenna Type:                                                                                                                                                                          | FPC Antenna                                                                                                                                                                                                                                                                                                                                                                                            |
| Antenna gain:                                                                                                                                                                          | 2.16dBi(Declared by applicant)                                                                                                                                                                                                                                                                                                                                                                         |
| Power supply:                                                                                                                                                                          | AC 120~277V 50/60Hz 0.40A 36W                                                                                                                                                                                                                                                                                                                                                                          |

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1                                   | 2412MHz   | 4       | 2427MHz   | 7       | 2442MHz   | 10      | 2457MHz   |
| 2                                   | 2417MHz   | 5       | 2432MHz   | 8       | 2447MHz   | 11      | 2462MHz   |
| 3                                   | 2422MHz   | 6       | 2437MHz   | 9       | 2452MHz   |         |           |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Test channel    | Frequency (MHz)               |               |
|-----------------|-------------------------------|---------------|
|                 | 802.11b/802.11g/802.11n(HT20) | 802.11n(HT40) |
| Lowest channel  | 2412MHz                       | 2422MHz       |
| Middle channel  | 2437MHz                       | 2437MHz       |
| Highest channel | 2462MHz                       | 2452MHz       |

## 5.2 Test mode

|                   |                                                |
|-------------------|------------------------------------------------|
| Transmitting mode | Keep the EUT in continuously transmitting mode |
|-------------------|------------------------------------------------|

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

| Mode      | 802.11b | 802.11g | 802.11n(HT20) | 802.11n(HT40) |
|-----------|---------|---------|---------------|---------------|
| Data rate | 1Mbps   | 6Mbps   | 6.5Mbps       | 13Mbps        |

## 5.3 Description of Support Units

None

## 5.4 Deviation from Standards

None.

## 5.5 Abnormalities from Standard Conditions

None.

## 5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

## 5.7 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

## 5.8 Additional Instructions

|                   |                                               |
|-------------------|-----------------------------------------------|
| Test Software     | Special test command provided by manufacturer |
| Power level setup | Default                                       |

## 6 Test Instruments list

| Radiated Emission: |                                     |                                |                       |               |                     |                         |
|--------------------|-------------------------------------|--------------------------------|-----------------------|---------------|---------------------|-------------------------|
| Item               | Test Equipment                      | Manufacturer                   | Model No.             | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | 3m Semi- Anechoic Chamber           | ZhongYu Electron               | 9.2(L)*6.2(W)* 6.4(H) | GTS250        | June 23, 2021       | June 22, 2024           |
| 2                  | Control Room                        | ZhongYu Electron               | 6.2(L)*2.5(W)* 2.4(H) | GTS251        | N/A                 | N/A                     |
| 3                  | EMI Test Receiver                   | Rohde & Schwarz                | ESU26                 | GTS203        | April 14, 2023      | April 13, 2024          |
| 4                  | BiConiLog Antenna                   | SCHWARZBECK<br>MESS-ELEKTRONIK | VULB9168              | GTS640        | March 19, 2023      | March 18, 2025          |
| 5                  | Double -ridged waveguide horn       | SCHWARZBECK<br>MESS-ELEKTRONIK | BBHA 9120 D           | GTS208        | April 17, 2023      | April 16, 2025          |
| 6                  | EMI Test Software                   | AUDIX                          | E3                    | N/A           | N/A                 | N/A                     |
| 7                  | Wideband Radio Communication Tester | Rohde & Schwarz                | CMW500                | GTS575        | April 14, 2023      | April 13, 2024          |
| 8                  | Loop Antenna                        | ZHINAN                         | ZN30900A              | GTS534        | Nov. 13, 2023       | Nov.12, 2024            |
| 9                  | Broadband Preamplifier              | SCHWARZBECK                    | BBV9718               | GTS535        | April 14, 2023      | April 13, 2024          |
| 10                 | Amplifier(1GHz-26.5GHz)             | HP                             | 8449B                 | GTS601        | April 14, 2023      | April 13, 2024          |
| 11                 | Horn Antenna (18-26.5GHz)           | /                              | UG-598A/U             | GTS664        | Oct. 29, 2023       | Oct. 28, 2024           |
| 12                 | Horn Antenna (26.5-40GHz)           | A.H Systems                    | SAS-573               | GTS665        | Oct. 29, 2023       | Oct. 28, 2024           |
| 13                 | FSV·Signal Analyzer (10Hz-40GHz)    | Keysight                       | FSV-40-N              | GTS666        | March 12, 2024      | March 11, 2025          |
| 14                 | Amplifier                           | /                              | LNA-1000-30S          | GTS650        | April 14, 2023      | April 13, 2024          |
| 15                 | CDNE M2+M3-16A                      | HCT                            | 30MHz-300MHz          | GTS692        | Nov. 08, 2023       | Nov.07, 2024            |
| 16                 | Wideband Amplifier                  | /                              | WDA-01004000-15P35    | GTS602        | April 14, 2023      | April 13, 2024          |
| 17                 | Thermo meter                        | JINCHUANG                      | GSP-8A                | GTS643        | April 19, 2023      | April 18, 2024          |
| 18                 | RE cable 1                          | GTS                            | N/A                   | GTS675        | July 31. 2023       | July 30. 2024           |
| 19                 | RE cable 2                          | GTS                            | N/A                   | GTS676        | July 31. 2023       | July 30. 2024           |
| 20                 | RE cable 3                          | GTS                            | N/A                   | GTS677        | July 31. 2023       | July 30. 2024           |
| 21                 | RE cable 4                          | GTS                            | N/A                   | GTS678        | July 31. 2023       | July 30. 2024           |
| 22                 | RE cable 5                          | GTS                            | N/A                   | GTS679        | July 31. 2023       | July 30. 2024           |
| 23                 | RE cable 6                          | GTS                            | N/A                   | GTS680        | July 31. 2023       | July 30. 2024           |
| 24                 | RE cable 7                          | GTS                            | N/A                   | GTS681        | July 31. 2023       | July 30. 2024           |
| 25                 | RE cable 8                          | GTS                            | N/A                   | GTS682        | July 31. 2023       | July 30. 2024           |

| Conducted Emission |                      |                         |                      |               |                     |                         |
|--------------------|----------------------|-------------------------|----------------------|---------------|---------------------|-------------------------|
| Item               | Test Equipment       | Manufacturer            | Model No.            | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | Shielding Room       | ZhongYu Electron        | 7.3(L)x3.1(W)x2.9(H) | GTS252        | July 12, 2022       | July 11, 2027           |
| 2                  | EMI Test Receiver    | R&S                     | ESCI 7               | GTS552        | April 14, 2023      | April 13, 2024          |
| 3                  | LISN                 | ROHDE & SCHWARZ         | ENV216               | GTS226        | April 14, 2023      | April 13, 2024          |
| 4                  | Coaxial Cable        | GTS                     | N/A                  | GTS227        | N/A                 | N/A                     |
| 5                  | EMI Test Software    | AUDIX                   | E3                   | N/A           | N/A                 | N/A                     |
| 6                  | Thermo meter         | JINCHUANG               | GSP-8A               | GTS642        | April 19, 2023      | April 18, 2024          |
| 7                  | Absorbing clamp      | Elektronik-Feinmechanik | MDS21                | GTS229        | April 14, 2023      | April 13, 2024          |
| 8                  | ISN                  | SCHWARZBECK             | NTFM 8158            | GTS565        | April 14, 2023      | April 13, 2024          |
| 9                  | High voltage probe   | SCHWARZBECK             | TK9420               | GTS537        | April 14, 2023      | April 13, 2024          |
| 10                 | Antenna end assembly | Weinschel               | 1870A                | GTS560        | April 14, 2023      | April 13, 2024          |

| RF Conducted Test: |                                                |              |                  |            |                     |                         |
|--------------------|------------------------------------------------|--------------|------------------|------------|---------------------|-------------------------|
| Item               | Test Equipment                                 | Manufacturer | Model No.        | Serial No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | MXA Signal Analyzer                            | Agilent      | N9020A           | GTS566     | April 14, 2023      | April 13, 2024          |
| 2                  | EMI Test Receiver                              | R&S          | ESCI 7           | GTS552     | April 14, 2023      | April 13, 2024          |
| 3                  | PSA Series Spectrum Analyzer                   | Agilent      | E4440A           | GTS536     | April 14, 2023      | April 13, 2024          |
| 4                  | MXG vector Signal Generator                    | Agilent      | N5182A           | GTS567     | April 14, 2023      | April 13, 2024          |
| 5                  | ESG Analog Signal Generator                    | Agilent      | E4428C           | GTS568     | April 14, 2023      | April 13, 2024          |
| 6                  | USB RF Power Sensor                            | DARE         | RPR3006W         | GTS569     | April 14, 2023      | April 13, 2024          |
| 7                  | RF Switch Box                                  | Shongyi      | RFSW3003328      | GTS571     | April 14, 2023      | April 13, 2024          |
| 8                  | Programmable Constant Temp & Humi Test Chamber | WEWON        | WHTH-150L-40-880 | GTS572     | April 14, 2023      | April 13, 2024          |
| 9                  | Thermo meter                                   | JINCHUANG    | GSP-8A           | GTS641     | April 19, 2023      | April 18, 2024          |
| 10                 | EXA Signal Analyzer                            | Keysight     | N9010B           | MY60241168 | Nov. 03, 2023       | Nov. 02, 2024           |

| General used equipment: |                |              |           |               |                     |                         |
|-------------------------|----------------|--------------|-----------|---------------|---------------------|-------------------------|
| Item                    | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                       | Barometer      | KUMAO        | SF132     | GTS647        | April 19, 2023      | April 18, 2024          |

## 7 Test results and Measurement Data

### 7.1 Antenna requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                     | FCC Part15 C Section 15.203 /247(c) |
| <b>15.203 requirement:</b><br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |                                     |
| <b>15.247(c) (1)(i) requirement:</b><br>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.                                                                                |                                     |
| <b>EUT Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                     |
| The antenna is FPC antenna, reference to the appendix II for details                                                                                                                                                                                                                                                                                                                                                                                                             |                                     |

## 7.2 Conducted Emissions


|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       |              |     |           |          |  |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--------------|-----|-----------|----------|--|
| Test Requirement:                                | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |              |     |           |          |  |
| Test Method:                                     | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       |              |     |           |          |  |
| Test Frequency Range:                            | 150KHz to 30MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       |              |     |           |          |  |
| Receiver setup:                                  | RBW=9KHz, VBW=30KHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       |              |     |           |          |  |
| Limit:                                           | Frequency range (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |       | Limit (dBuV) |     |           |          |  |
|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       | Quasi-peak   |     | Average   |          |  |
|                                                  | 0.15-0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |       | 66 to 56*    |     | 56 to 46* |          |  |
|                                                  | 0.5-5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |       | 56           |     | 46        |          |  |
|                                                  | 5-30                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       | 60           |     | 50        |          |  |
| * Decreases with the logarithm of the frequency. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       |              |     |           |          |  |
| Test setup:                                      | <div><div><div>Reference Plane</div><div><div><div>40cm</div><div>LISN</div></div><div><div>40cm</div><div>AUX Equipment</div><div>E.U.T</div></div></div><div>80cm</div><div><div><div>40cm</div><div>LISN</div></div><div><div>Filter</div><div>AC power</div></div><div>EMI Receiver</div></div></div><div>Test table/Insulation plane</div><div><div>Remark:</div><div>E.U.T: Equipment Under Test</div><div>LISN: Line Impedance Stabilization Network</div><div>Test table height=0.8m</div></div></div>                                                                                                                                                                                                                       |       |              |     |           |          |  |
| Test procedure:                                  | <div><div>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</div></div> |       |              |     |           |          |  |
| Test Instruments:                                | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       |              |     |           |          |  |
| Test mode:                                       | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       |              |     |           |          |  |
| Test environment:                                | Temp.:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 25 °C | Humid.:      | 52% | Press.:   | 1012mbar |  |
| Test voltage:                                    | AC 120V, 60Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |              |     |           |          |  |
| Test results:                                    | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       |              |     |           |          |  |

## Measurement data

Pre-scan all test modes, found worst case at 802.11g 2462MHz, and so only show the test result of it.


Model No.: SEC102P-36W-CCT-R80-0001

Line:



| Freq  | Reading | LISN/ISN | Cable | Level | Limit | Over   | Remark  |
|-------|---------|----------|-------|-------|-------|--------|---------|
| MHz   | dBuV    | factor   | loss  | dBuV  | dBuV  | limit  |         |
| 0.15  | 38.62   | 9.56     | 0.01  | 48.19 | 65.82 | -17.63 | QP      |
| 0.15  | 31.34   | 9.56     | 0.01  | 40.91 | 55.82 | -14.91 | Average |
| 0.23  | 36.68   | 9.51     | 0.01  | 46.20 | 62.44 | -16.24 | QP      |
| 0.23  | 28.86   | 9.51     | 0.01  | 38.38 | 52.44 | -14.06 | Average |
| 0.97  | 27.12   | 9.49     | 0.03  | 36.64 | 56.00 | -19.36 | QP      |
| 0.97  | 23.32   | 9.49     | 0.03  | 32.84 | 46.00 | -13.16 | Average |
| 1.46  | 28.70   | 9.56     | 0.04  | 38.30 | 56.00 | -17.70 | QP      |
| 1.46  | 17.86   | 9.56     | 0.04  | 27.46 | 46.00 | -18.54 | Average |
| 2.71  | 27.95   | 9.55     | 0.05  | 37.55 | 56.00 | -18.45 | QP      |
| 2.71  | 15.83   | 9.55     | 0.05  | 25.43 | 46.00 | -20.57 | Average |
| 16.23 | 31.73   | 9.69     | 0.17  | 41.59 | 60.00 | -18.41 | QP      |
| 16.23 | 23.76   | 9.69     | 0.17  | 33.62 | 50.00 | -16.38 | Average |


Neutral:



| Freq  | Reading level | LISN/ISN factor | Cable loss | Level | Limit level | Over limit | Remark  |
|-------|---------------|-----------------|------------|-------|-------------|------------|---------|
| MHz   | dBuV          | dB              | dB         | dBuV  | dBuV        | dB         |         |
| 0.15  | 38.46         | 9.55            | 0.01       | 48.02 | 65.74       | -17.72     | QP      |
| 0.15  | 30.95         | 9.55            | 0.01       | 40.51 | 55.74       | -15.23     | Average |
| 0.32  | 30.64         | 9.56            | 0.01       | 40.21 | 59.71       | -19.50     | QP      |
| 0.32  | 19.89         | 9.56            | 0.01       | 29.46 | 49.71       | -20.25     | Average |
| 0.54  | 28.32         | 9.57            | 0.01       | 37.90 | 56.00       | -18.10     | QP      |
| 0.54  | 18.37         | 9.57            | 0.01       | 27.95 | 46.00       | -18.05     | Average |
| 0.97  | 27.28         | 9.55            | 0.03       | 36.86 | 56.00       | -19.14     | QP      |
| 0.97  | 23.89         | 9.55            | 0.03       | 33.47 | 46.00       | -12.53     | Average |
| 1.46  | 28.27         | 9.55            | 0.04       | 37.86 | 56.00       | -18.14     | QP      |
| 1.46  | 17.03         | 9.55            | 0.04       | 26.62 | 46.00       | -19.38     | Average |
| 14.99 | 29.45         | 9.67            | 0.16       | 39.28 | 60.00       | -20.72     | QP      |
| 14.99 | 22.21         | 9.67            | 0.16       | 32.04 | 50.00       | -17.96     | Average |


Model No.: SEC103P-020-CCT-R80-0001

Line:



| Freq | Reading | LISN/ISN | Cable |       | Limit | Over   |         |
|------|---------|----------|-------|-------|-------|--------|---------|
|      | level   | factor   | loss  | Level | level | limit  | Remark  |
| MHz  | dBuV    | dB       | dB    | dBuV  | dBuV  | dB     |         |
| 0.15 | 52.49   | 9.56     | 0.01  | 62.06 | 65.87 | -3.81  | QP      |
| 0.15 | 33.39   | 9.56     | 0.01  | 42.96 | 55.87 | -12.91 | Average |
| 0.20 | 50.76   | 9.52     | 0.01  | 60.29 | 63.76 | -3.47  | QP      |
| 0.20 | 40.79   | 9.52     | 0.01  | 50.32 | 53.76 | -3.44  | Average |
| 0.41 | 31.05   | 9.49     | 0.01  | 40.55 | 57.68 | -17.13 | QP      |
| 0.41 | 18.33   | 9.49     | 0.01  | 27.83 | 47.68 | -19.85 | Average |
| 0.90 | 15.95   | 9.49     | 0.03  | 25.47 | 56.00 | -30.53 | QP      |
| 0.90 | 7.12    | 9.49     | 0.03  | 16.64 | 46.00 | -29.36 | Average |
| 2.58 | 9.52    | 9.56     | 0.05  | 19.13 | 56.00 | -36.87 | QP      |
| 2.58 | 1.05    | 9.56     | 0.05  | 10.66 | 46.00 | -35.34 | Average |
| 9.86 | 13.89   | 9.31     | 0.11  | 23.31 | 60.00 | -36.69 | QP      |
| 9.86 | 4.42    | 9.31     | 0.11  | 13.84 | 50.00 | -36.16 | Average |


Neutral:



Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

## 7.3 Conducted Output Power

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement : | FCC Part15 C Section 15.247 (b)(3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Test Method :      | KDB558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Limit:             | <p>30dBm</p> <p>The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p> |
| Test setup:        |  <p>The diagram illustrates the test setup. A 'Power Meter' is connected to an 'E.U.T.' (Equipment Under Test) via a red cable. Both components are placed on a 'Non-Conducted Table'. This table is supported by two vertical legs and sits on a 'Ground Reference Plane'.</p>                                                                                                                                                                                                   |
| Test Instruments:  | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Test mode:         | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Test results:      | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |


**Measurement Data:** The detailed test data see Appendix for WIFI 2.4G.

## 7.4 Channel Bandwidth

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement : | FCC Part15 C Section 15.247 (a)(2)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Method :      | KDB558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Limit:             | >500KHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Test setup:        |  <p>The diagram illustrates the test setup. A Spectrum Analyzer, showing a frequency spectrum on its screen, is connected to an E.U.T (Equipment Under Test) by a red cable. Both the Spectrum Analyzer and the E.U.T are positioned on a Non-Conducted Table. This table is supported by a Ground Reference Plane, which is represented by a thick grey bar at the bottom of the setup.</p> |
| Test Instruments:  | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test mode:         | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test results:      | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

**Measurement Data:** The detailed test data see Appendix for WIFI 2.4G.


## 7.5 Power Spectral Density

|                   |                                                                                                                                                                                                                                                                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (e)                                                                                                                                                                                                                                                                                                                            |
| Test Method:      | KDB558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                  |
| Limit:            | 8dBm/3kHz                                                                                                                                                                                                                                                                                                                                                  |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                           |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                           |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                       |

**Measurement Data:** The detailed test data see Appendix for WIFI 2.4G.


## 7.6 Spurious Emission in Non-restricted & restricted Bands



### 7.6.1 Conducted Emission Method

|                   |                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                           |
| Test Method:      | KDB558074 D01 15.247 Meas Guidance v05r02                                                                                                                                                                                                                                                                                                                                                 |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.   |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                          |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                          |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                      |

**Measurement Data:** The detailed test data see Appendix for WIFI 2.4G.

## 7.6.2 Radiated Emission Method

|                                          |                                                                                                                            |              |              |                      |            |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|--------------|--------------|----------------------|------------|
| Test Requirement:                        | FCC Part15 C Section 15.209                                                                                                |              |              |                      |            |
| Test Method:                             | ANSI C63.10:2013                                                                                                           |              |              |                      |            |
| Test Frequency Range:                    | 9kHz to 25GHz                                                                                                              |              |              |                      |            |
| Test site:                               | Measurement Distance: 3m                                                                                                   |              |              |                      |            |
| Receiver setup:                          | Frequency                                                                                                                  | Detector     | RBW          | VBW                  | Value      |
|                                          | 9KHz-150KHz                                                                                                                | Quasi-peak   | 200Hz        | 600Hz                | Quasi-peak |
|                                          | 150KHz-30MHz                                                                                                               | Quasi-peak   | 9KHz         | 30KHz                | Quasi-peak |
|                                          | 30MHz-1GHz                                                                                                                 | Quasi-peak   | 120KHz       | 300KHz               | Quasi-peak |
|                                          | Above 1GHz                                                                                                                 | Peak         | 1MHz         | 3MHz                 | Peak       |
|                                          |                                                                                                                            | Peak         | 1MHz         | 10Hz                 | Average    |
|                                          | Note: For Duty cycle ≥ 98%, average detector set as above For Duty cycle < 98%, average detector set as below: VBW ≥ 1 / T |              |              |                      |            |
| Limit:                                   | Frequency                                                                                                                  | Limit (uV/m) | Value        | Measurement Distance |            |
|                                          | 0.009MHz-0.490MHz                                                                                                          | 2400/F(KHz)  | PK/QP/A<br>V | 300m                 |            |
|                                          | 0.490MHz-1.705MHz                                                                                                          | 24000/F(KHz) | QP           | 30m                  |            |
|                                          | 1.705MHz-30MHz                                                                                                             | 30           | QP           | 30m                  |            |
|                                          | 30MHz-88MHz                                                                                                                | 100          | QP           | 3m                   |            |
|                                          | 88MHz-216MHz                                                                                                               | 150          | QP           |                      |            |
|                                          | 216MHz-960MHz                                                                                                              | 200          | QP           |                      |            |
|                                          | 960MHz-1GHz                                                                                                                | 500          | QP           |                      |            |
|                                          | Above 1GHz                                                                                                                 | 500          | Average      |                      |            |
|                                          |                                                                                                                            | 5000         | Peak         |                      |            |
| Test setup:                              | For radiated emissions from 9kHz to 30MHz                                                                                  |              |              |                      |            |
|                                          | <div></div>                            |              |              |                      |            |
| For radiated emissions from 30MHz to1GHz |                                                                                                                            |              |              |                      |            |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          |  <p>For radiated emissions above 1GHz</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <p>Test Procedure:</p>   | <ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol> |
| <p>Test Instruments:</p> | <p>Refer to section 6.0 for details</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

|                   |                                  |       |         |     |         |          |
|-------------------|----------------------------------|-------|---------|-----|---------|----------|
| Test mode:        | Refer to section 5.2 for details |       |         |     |         |          |
| Test environment: | Temp.:                           | 25 °C | Humid.: | 52% | Press.: | 1012mbar |
| Test voltage:     | AC 120V, 60Hz                    |       |         |     |         |          |
| Test results:     | Pass                             |       |         |     |         |          |

*Remarks:*

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

**Measurement data:**

■ **9kHz~30MHz**


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

## ■ Below 1GHz

Pre-scan all test modes, found worst case at 802.11g 2462MHz, and so only show the test result of it.


Model No.: SEC102P-36W-CCT-R80-0001

Horizontal:



| Freq<br>MHz | Reading<br>level<br>dBuV | Antenna<br>factor<br>dB/m | Cable<br>loss<br>dB | Preamp<br>factor<br>dB | level<br>dBuV/m | Limit<br>level<br>dBuV/m | Over<br>limit<br>dB | Remark |
|-------------|--------------------------|---------------------------|---------------------|------------------------|-----------------|--------------------------|---------------------|--------|
| 151.067     | 54.00                    | 12.51                     | 1.58                | 33.12                  | 34.97           | 43.50                    | -8.53               | QP     |
| 186.441     | 56.91                    | 9.93                      | 1.77                | 32.88                  | 35.73           | 43.50                    | -7.77               | QP     |
| 199.986     | 63.36                    | 9.20                      | 1.84                | 32.80                  | 41.60           | 43.50                    | -1.90               | QP     |
| 214.514     | 60.88                    | 10.01                     | 1.93                | 32.78                  | 40.04           | 43.50                    | -3.46               | QP     |
| 221.392     | 61.98                    | 10.39                     | 1.97                | 32.77                  | 41.57           | 46.00                    | -4.43               | QP     |
| 280.024     | 54.07                    | 12.90                     | 2.27                | 32.72                  | 36.52           | 46.00                    | -9.48               | QP     |


Vertical:




| Freq<br>MHz | Reading<br>level<br>dBuV | Antenna<br>factor<br>dB/m | Cable<br>loss<br>dB | Preamp<br>factor<br>dB | level<br>dBuV/m | Limit<br>level<br>dBuV/m | Over<br>limit<br>dB | Remark |
|-------------|--------------------------|---------------------------|---------------------|------------------------|-----------------|--------------------------|---------------------|--------|
| 34.639      | 52.52                    | 12.66                     | 0.61                | 33.77                  | 32.02           | 40.00                    | -7.98               | QP     |
| 45.535      | 54.66                    | 13.33                     | 0.72                | 33.70                  | 35.01           | 40.00                    | -4.99               | QP     |
| 52.025      | 55.28                    | 13.07                     | 0.79                | 33.67                  | 35.47           | 40.00                    | -4.53               | QP     |
| 128.563     | 58.71                    | 11.74                     | 1.43                | 33.31                  | 38.57           | 43.50                    | -4.93               | QP     |
| 271.325     | 51.62                    | 12.22                     | 2.23                | 32.72                  | 33.35           | 46.00                    | -12.65              | QP     |
| 400.432     | 43.93                    | 15.71                     | 2.85                | 32.30                  | 30.19           | 46.00                    | -15.81              | QP     |

Model No.: SEC103P-020-CCT-R80-0001

Horizontal:



Vertical:



| Freq<br>MHz | Reading<br>level<br>dBuV | Antenna<br>factor<br>dB/m | Cable<br>loss<br>dB | Preamp<br>factor<br>dB | level<br>dBuV/m | Limit<br>level<br>dBuV/m | Over<br>limit<br>dB | Remark |
|-------------|--------------------------|---------------------------|---------------------|------------------------|-----------------|--------------------------|---------------------|--------|
| 130.379     | 52.73                    | 11.85                     | 1.44                | 33.29                  | 32.73           | 43.50                    | -10.77              | QP     |
| 199.986     | 56.04                    | 9.20                      | 1.84                | 32.80                  | 34.28           | 43.50                    | -9.22               | QP     |
| 300.367     | 42.47                    | 12.41                     | 2.36                | 32.70                  | 24.54           | 46.00                    | -21.46              | QP     |
| 400.432     | 47.19                    | 15.71                     | 2.85                | 32.30                  | 33.45           | 46.00                    | -12.55              | QP     |
| 601.427     | 40.05                    | 19.32                     | 3.73                | 31.78                  | 31.32           | 46.00                    | -14.68              | QP     |
| 709.182     | 42.10                    | 20.99                     | 4.12                | 31.57                  | 35.64           | 46.00                    | -10.36              | QP     |

## ■ Above 1GHz

■ Only show the worst case(Model No.: SEC102P-36W-CCT-R80-0001)

## ■ Unwanted Emissions in non-restricted Frequency Bands

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11b | Test channel: | Lowest |
|------------|---------|---------------|--------|

### Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 37.91             | 31.22                 | 4.63            | 37.68              | 36.08          | 74.00               | -37.92          | Vertical     |
| 7236.00         | 32.71             | 36.25                 | 6.52            | 37.81              | 37.67          | 74.00               | -36.33          | Vertical     |
| 9648.00         | 31.64             | 37.97                 | 7.99            | 37.93              | 39.67          | 74.00               | -34.33          | Vertical     |
| 4824.00         | 36.95             | 31.22                 | 4.63            | 37.68              | 35.12          | 74.00               | -38.88          | Horizontal   |
| 7236.00         | 32.65             | 36.25                 | 6.52            | 37.81              | 37.61          | 74.00               | -36.39          | Horizontal   |
| 9648.00         | 31.30             | 37.97                 | 7.99            | 37.93              | 39.33          | 74.00               | -34.67          | Horizontal   |

### Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 27.18             | 31.22                 | 4.63            | 37.68              | 25.35          | 54.00               | -28.65          | Vertical     |
| 7236.00         | 21.63             | 36.25                 | 6.52            | 37.81              | 26.59          | 54.00               | -27.41          | Vertical     |
| 9648.00         | 22.03             | 37.97                 | 7.99            | 37.93              | 30.06          | 54.00               | -23.94          | Vertical     |
| 4824.00         | 26.61             | 31.22                 | 4.63            | 37.68              | 24.78          | 54.00               | -29.22          | Horizontal   |
| 7236.00         | 21.27             | 36.25                 | 6.52            | 37.81              | 26.23          | 54.00               | -27.77          | Horizontal   |
| 9648.00         | 21.08             | 37.97                 | 7.99            | 37.93              | 29.11          | 54.00               | -24.89          | Horizontal   |

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11b | Test channel: | Middle |
|------------|---------|---------------|--------|

### Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 37.38             | 31.31                 | 4.69            | 37.63              | 35.75          | 74.00               | -38.25          | Vertical     |
| 7311.00         | 33.04             | 36.39                 | 6.61            | 37.78              | 38.26          | 74.00               | -35.74          | Vertical     |
| 9748.00         | 32.84             | 38.10                 | 8.03            | 37.95              | 41.02          | 74.00               | -32.98          | Vertical     |
| 4874.00         | 38.16             | 31.31                 | 4.69            | 37.63              | 36.53          | 74.00               | -37.47          | Horizontal   |
| 7311.00         | 31.84             | 36.39                 | 6.61            | 37.78              | 37.06          | 74.00               | -36.94          | Horizontal   |
| 9748.00         | 32.80             | 38.10                 | 8.03            | 37.95              | 40.98          | 74.00               | -33.02          | Horizontal   |

### Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 28.38             | 31.31                 | 4.69            | 37.63              | 26.75          | 54.00               | -27.25          | Vertical     |
| 7311.00         | 21.40             | 36.39                 | 6.61            | 37.78              | 26.62          | 54.00               | -27.38          | Vertical     |
| 9748.00         | 22.13             | 38.10                 | 8.03            | 37.95              | 30.31          | 54.00               | -23.69          | Vertical     |
| 4874.00         | 28.38             | 31.31                 | 4.69            | 37.63              | 26.75          | 54.00               | -27.25          | Horizontal   |
| 7311.00         | 20.96             | 36.39                 | 6.61            | 37.78              | 26.18          | 54.00               | -27.82          | Horizontal   |
| 9748.00         | 22.54             | 38.10                 | 8.03            | 37.95              | 30.72          | 54.00               | -23.28          | Horizontal   |

|            |         |               |         |
|------------|---------|---------------|---------|
| Test mode: | 802.11b | Test channel: | Highest |
|------------|---------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 41.48             | 31.37                 | 4.75            | 37.58                    | 40.02          | 74.00               | -33.98          | Vertical     |
| 7386.00         | 32.82             | 36.57                 | 6.71            | 37.74                    | 38.36          | 74.00               | -35.64          | Vertical     |
| 9848.00         | 35.49             | 38.20                 | 8.07            | 37.58                    | 44.18          | 74.00               | -29.82          | Vertical     |
| 4924.00         | 41.31             | 31.37                 | 4.75            | 37.58                    | 39.85          | 74.00               | -34.15          | Horizontal   |
| 7386.00         | 31.99             | 36.57                 | 6.71            | 37.74                    | 37.53          | 74.00               | -36.47          | Horizontal   |
| 9848.00         | 31.78             | 38.20                 | 8.07            | 37.58                    | 40.47          | 74.00               | -33.53          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 32.66             | 31.37                 | 4.75            | 37.58                    | 31.20          | 54.00               | -22.80          | Vertical     |
| 7386.00         | 22.81             | 36.57                 | 6.71            | 37.74                    | 28.35          | 54.00               | -25.65          | Vertical     |
| 9848.00         | 24.06             | 38.20                 | 8.07            | 37.58                    | 32.75          | 54.00               | -21.25          | Vertical     |
| 4924.00         | 31.86             | 31.37                 | 4.75            | 37.58                    | 30.40          | 54.00               | -23.60          | Horizontal   |
| 7386.00         | 21.43             | 36.57                 | 6.71            | 37.74                    | 26.97          | 54.00               | -27.03          | Horizontal   |
| 9848.00         | 21.09             | 38.20                 | 8.07            | 37.58                    | 29.78          | 54.00               | -24.22          | Horizontal   |

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11g | Test channel: | lowest |
|------------|---------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 37.63             | 31.24                 | 4.63            | 37.68                    | 35.82          | 74.00               | -38.18          | Vertical     |
| 7236.00         | 32.53             | 36.25                 | 6.52            | 37.80                    | 37.50          | 74.00               | -36.50          | Vertical     |
| 9648.00         | 31.51             | 37.97                 | 7.98            | 37.93                    | 39.53          | 74.00               | -34.47          | Vertical     |
| 4824.00         | 36.71             | 31.24                 | 4.63            | 37.68                    | 34.90          | 74.00               | -39.10          | Horizontal   |
| 7236.00         | 32.49             | 36.25                 | 6.52            | 37.80                    | 37.46          | 74.00               | -36.54          | Horizontal   |
| 9648.00         | 31.18             | 37.97                 | 7.98            | 37.93                    | 39.20          | 74.00               | -34.80          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 26.92             | 31.24                 | 4.63            | 37.68                    | 25.11          | 54.00               | -28.89          | Vertical     |
| 7236.00         | 21.46             | 36.25                 | 6.52            | 37.80                    | 26.43          | 54.00               | -27.57          | Vertical     |
| 9648.00         | 21.90             | 37.97                 | 7.98            | 37.93                    | 29.92          | 54.00               | -24.08          | Vertical     |
| 4824.00         | 26.39             | 31.24                 | 4.63            | 37.68                    | 24.58          | 54.00               | -29.42          | Horizontal   |
| 7236.00         | 21.12             | 36.25                 | 6.52            | 37.80                    | 26.09          | 54.00               | -27.91          | Horizontal   |
| 9648.00         | 20.97             | 37.97                 | 7.98            | 37.93                    | 28.99          | 54.00               | -25.01          | Horizontal   |

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11g | Test channel: | Middle |
|------------|---------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 37.14             | 31.31                 | 4.69            | 37.62                    | 35.52          | 74.00               | -38.48          | Vertical     |
| 7311.00         | 32.90             | 36.39                 | 6.61            | 37.78                    | 38.12          | 74.00               | -35.88          | Vertical     |
| 9748.00         | 32.74             | 38.10                 | 8.02            | 37.95                    | 40.91          | 74.00               | -33.09          | Vertical     |
| 4874.00         | 37.97             | 31.31                 | 4.69            | 37.62                    | 36.35          | 74.00               | -37.65          | Horizontal   |
| 7311.00         | 31.71             | 36.39                 | 6.61            | 37.78                    | 36.93          | 74.00               | -37.07          | Horizontal   |
| 9748.00         | 32.70             | 38.10                 | 8.02            | 37.95                    | 40.87          | 74.00               | -33.13          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 28.17             | 31.31                 | 4.69            | 37.62                    | 26.55          | 54.00               | -27.45          | Vertical     |
| 7311.00         | 21.26             | 36.39                 | 6.61            | 37.78                    | 26.48          | 54.00               | -27.52          | Vertical     |
| 9748.00         | 22.03             | 38.10                 | 8.02            | 37.95                    | 30.20          | 54.00               | -23.80          | Vertical     |
| 4874.00         | 28.19             | 31.31                 | 4.69            | 37.62                    | 26.57          | 54.00               | -27.43          | Horizontal   |
| 7311.00         | 20.84             | 36.39                 | 6.61            | 37.78                    | 26.06          | 54.00               | -27.94          | Horizontal   |
| 9748.00         | 22.45             | 38.10                 | 8.02            | 37.95                    | 30.62          | 54.00               | -23.38          | Horizontal   |

|            |         |               |         |
|------------|---------|---------------|---------|
| Test mode: | 802.11g | Test channel: | Highest |
|------------|---------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 41.08             | 31.37                 | 4.75            | 37.58                    | 39.62          | 74.00               | -34.38          | Vertical     |
| 7386.00         | 32.56             | 36.57                 | 6.71            | 37.74                    | 38.10          | 74.00               | -35.90          | Vertical     |
| 9848.00         | 35.31             | 38.20                 | 8.07            | 37.58                    | 44.00          | 74.00               | -30.00          | Vertical     |
| 4924.00         | 40.98             | 31.37                 | 4.75            | 37.58                    | 39.52          | 74.00               | -34.48          | Horizontal   |
| 7386.00         | 31.76             | 36.57                 | 6.71            | 37.74                    | 37.30          | 74.00               | -36.70          | Horizontal   |
| 9848.00         | 31.61             | 38.20                 | 8.07            | 37.58                    | 40.30          | 74.00               | -33.70          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 32.29             | 31.37                 | 4.75            | 37.58                    | 30.83          | 54.00               | -23.17          | Vertical     |
| 7386.00         | 22.56             | 36.57                 | 6.71            | 37.74                    | 28.10          | 54.00               | -25.90          | Vertical     |
| 9848.00         | 23.88             | 38.20                 | 8.07            | 37.58                    | 32.57          | 54.00               | -21.43          | Vertical     |
| 4924.00         | 31.54             | 31.37                 | 4.75            | 37.58                    | 30.08          | 54.00               | -23.92          | Horizontal   |
| 7386.00         | 21.22             | 36.57                 | 6.71            | 37.74                    | 26.76          | 54.00               | -27.24          | Horizontal   |
| 9848.00         | 20.93             | 38.20                 | 8.07            | 37.58                    | 29.62          | 54.00               | -24.38          | Horizontal   |

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT20) | Test channel: | Lowest |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 37.79             | 31.24                 | 4.63            | 37.68              | 35.98          | 74.00               | -38.02          | Vertical     |
| 7236.00         | 32.63             | 36.25                 | 6.52            | 37.80              | 37.60          | 74.00               | -36.40          | Vertical     |
| 9648.00         | 31.58             | 37.97                 | 7.98            | 37.93              | 39.60          | 74.00               | -34.40          | Vertical     |
| 4824.00         | 36.85             | 31.24                 | 4.63            | 37.68              | 35.04          | 74.00               | -38.96          | Horizontal   |
| 7236.00         | 32.58             | 36.25                 | 6.52            | 37.80              | 37.55          | 74.00               | -36.45          | Horizontal   |
| 9648.00         | 31.25             | 37.97                 | 7.98            | 37.93              | 39.27          | 74.00               | -34.73          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 27.07             | 31.24                 | 4.63            | 37.68              | 25.26          | 54.00               | -28.74          | Vertical     |
| 7236.00         | 21.56             | 36.25                 | 6.52            | 37.80              | 26.53          | 54.00               | -27.47          | Vertical     |
| 9648.00         | 21.97             | 37.97                 | 7.98            | 37.93              | 29.99          | 54.00               | -24.01          | Vertical     |
| 4824.00         | 26.51             | 31.24                 | 4.63            | 37.68              | 24.70          | 54.00               | -29.30          | Horizontal   |
| 7236.00         | 21.21             | 36.25                 | 6.52            | 37.80              | 26.18          | 54.00               | -27.82          | Horizontal   |
| 9648.00         | 21.03             | 37.97                 | 7.98            | 37.93              | 29.05          | 54.00               | -24.95          | Horizontal   |

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT20) | Test channel: | Middle |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 37.28             | 31.31                 | 4.69            | 37.62              | 35.66          | 74.00               | -38.34          | Vertical     |
| 7311.00         | 32.98             | 36.39                 | 6.61            | 37.78              | 38.20          | 74.00               | -35.80          | Vertical     |
| 9748.00         | 32.80             | 38.10                 | 8.02            | 37.95              | 40.97          | 74.00               | -33.03          | Vertical     |
| 4874.00         | 38.08             | 31.31                 | 4.69            | 37.62              | 36.46          | 74.00               | -37.54          | Horizontal   |
| 7311.00         | 31.78             | 36.39                 | 6.61            | 37.78              | 37.00          | 74.00               | -37.00          | Horizontal   |
| 9748.00         | 32.76             | 38.10                 | 8.02            | 37.95              | 40.93          | 74.00               | -33.07          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 28.29             | 31.31                 | 4.69            | 37.62              | 26.67          | 54.00               | -27.33          | Vertical     |
| 7311.00         | 21.34             | 36.39                 | 6.61            | 37.78              | 26.56          | 54.00               | -27.44          | Vertical     |
| 9748.00         | 22.09             | 38.10                 | 8.02            | 37.95              | 30.26          | 54.00               | -23.74          | Vertical     |
| 4874.00         | 28.30             | 31.31                 | 4.69            | 37.62              | 26.68          | 54.00               | -27.32          | Horizontal   |
| 7311.00         | 20.91             | 36.39                 | 6.61            | 37.78              | 26.13          | 54.00               | -27.87          | Horizontal   |
| 9748.00         | 22.50             | 38.10                 | 8.02            | 37.95              | 30.67          | 54.00               | -23.33          | Horizontal   |

|            |               |               |         |
|------------|---------------|---------------|---------|
| Test mode: | 802.11n(HT20) | Test channel: | Highest |
|------------|---------------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 41.31             | 31.37                 | 4.75            | 37.58              | 39.85          | 74.00               | -34.15          | Vertical     |
| 7386.00         | 32.71             | 36.57                 | 6.71            | 37.74              | 38.25          | 74.00               | -35.75          | Vertical     |
| 9848.00         | 35.41             | 38.20                 | 8.07            | 37.58              | 44.10          | 74.00               | -29.90          | Vertical     |
| 4924.00         | 41.17             | 31.37                 | 4.75            | 37.58              | 39.71          | 74.00               | -34.29          | Horizontal   |
| 7386.00         | 31.89             | 36.57                 | 6.71            | 37.74              | 37.43          | 74.00               | -36.57          | Horizontal   |
| 9848.00         | 31.71             | 38.20                 | 8.07            | 37.58              | 40.40          | 74.00               | -33.60          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 32.50             | 31.37                 | 4.75            | 37.58              | 31.04          | 54.00               | -22.96          | Vertical     |
| 7386.00         | 22.70             | 36.57                 | 6.71            | 37.74              | 28.24          | 54.00               | -25.76          | Vertical     |
| 9848.00         | 23.98             | 38.20                 | 8.07            | 37.58              | 32.67          | 54.00               | -21.33          | Vertical     |
| 4924.00         | 31.72             | 31.37                 | 4.75            | 37.58              | 30.26          | 54.00               | -23.74          | Horizontal   |
| 7386.00         | 21.34             | 36.57                 | 6.71            | 37.74              | 26.88          | 54.00               | -27.12          | Horizontal   |
| 9848.00         | 21.02             | 38.20                 | 8.07            | 37.58              | 29.71          | 54.00               | -24.29          | Horizontal   |

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT40) | Test channel: | Lowest |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4844.00         | 37.82             | 31.26                 | 4.65            | 37.66              | 36.07          | 74.00               | -37.93          | Vertical     |
| 7266.00         | 32.65             | 36.30                 | 6.57            | 37.79              | 37.73          | 74.00               | -36.27          | Vertical     |
| 9688.00         | 31.60             | 38.03                 | 8.00            | 37.94              | 39.69          | 74.00               | -34.31          | Vertical     |
| 4844.00         | 36.87             | 31.26                 | 4.65            | 37.66              | 35.12          | 74.00               | -38.88          | Horizontal   |
| 7266.00         | 32.60             | 36.30                 | 6.57            | 37.79              | 37.68          | 74.00               | -36.32          | Horizontal   |
| 9688.00         | 31.26             | 38.03                 | 8.00            | 37.94              | 39.35          | 74.00               | -34.65          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4844.00         | 27.10             | 31.26                 | 4.65            | 37.66              | 25.35          | 54.00               | -28.65          | Vertical     |
| 7266.00         | 21.58             | 36.30                 | 6.57            | 37.79              | 26.66          | 54.00               | -27.34          | Vertical     |
| 9688.00         | 21.99             | 38.03                 | 8.00            | 37.94              | 30.08          | 54.00               | -23.92          | Vertical     |
| 4844.00         | 26.54             | 31.26                 | 4.65            | 37.66              | 24.79          | 54.00               | -29.21          | Horizontal   |
| 7266.00         | 21.22             | 36.30                 | 6.57            | 37.79              | 26.30          | 54.00               | -27.70          | Horizontal   |
| 9688.00         | 21.05             | 38.03                 | 8.00            | 37.94              | 29.14          | 54.00               | -24.86          | Horizontal   |

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT40) | Test channel: | Middle |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 37.30             | 31.31                 | 4.69            | 37.62              | 35.68          | 74.00               | -38.32          | Vertical     |
| 7311.00         | 33.00             | 36.39                 | 6.61            | 37.78              | 38.22          | 74.00               | -35.78          | Vertical     |
| 9748.00         | 32.81             | 38.10                 | 8.03            | 37.95              | 40.99          | 74.00               | -33.01          | Vertical     |
| 4874.00         | 38.10             | 31.31                 | 4.69            | 37.62              | 36.48          | 74.00               | -37.52          | Horizontal   |
| 7311.00         | 31.80             | 36.39                 | 6.61            | 37.78              | 37.02          | 74.00               | -36.98          | Horizontal   |
| 9748.00         | 32.77             | 38.10                 | 8.03            | 37.95              | 40.95          | 74.00               | -33.05          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 28.32             | 31.31                 | 4.69            | 37.62              | 26.70          | 54.00               | -27.30          | Vertical     |
| 7311.00         | 21.36             | 36.39                 | 6.61            | 37.78              | 26.58          | 54.00               | -27.42          | Vertical     |
| 9748.00         | 22.10             | 38.10                 | 8.03            | 37.95              | 30.28          | 54.00               | -23.72          | Vertical     |
| 4874.00         | 28.32             | 31.31                 | 4.69            | 37.62              | 26.70          | 54.00               | -27.30          | Horizontal   |
| 7311.00         | 20.92             | 36.39                 | 6.61            | 37.78              | 26.14          | 54.00               | -27.86          | Horizontal   |
| 9748.00         | 22.51             | 38.10                 | 8.03            | 37.95              | 30.69          | 54.00               | -23.31          | Horizontal   |

|            |               |               |         |
|------------|---------------|---------------|---------|
| Test mode: | 802.11n(HT40) | Test channel: | Highest |
|------------|---------------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4904.00         | 41.35             | 31.35                 | 4.71            | 37.60              | 39.81          | 74.00               | -34.19          | Vertical     |
| 7356.00         | 32.74             | 36.53                 | 6.67            | 37.76              | 38.18          | 74.00               | -35.82          | Vertical     |
| 9808.00         | 35.44             | 38.17                 | 8.05            | 37.96              | 43.70          | 74.00               | -30.30          | Vertical     |
| 4904.00         | 41.21             | 31.35                 | 4.71            | 37.60              | 39.67          | 74.00               | -34.33          | Horizontal   |
| 7356.00         | 31.92             | 36.53                 | 6.67            | 37.76              | 37.36          | 74.00               | -36.64          | Horizontal   |
| 9808.00         | 31.73             | 38.17                 | 8.05            | 37.96              | 39.99          | 74.00               | -34.01          | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4904.00         | 32.55             | 31.35                 | 4.71            | 37.60              | 31.01          | 54.00               | -22.99          | Vertical     |
| 7356.00         | 22.73             | 36.53                 | 6.67            | 37.76              | 28.17          | 54.00               | -25.83          | Vertical     |
| 9808.00         | 24.00             | 38.17                 | 8.05            | 37.96              | 32.26          | 54.00               | -21.74          | Vertical     |
| 4904.00         | 31.76             | 31.35                 | 4.71            | 37.60              | 30.22          | 54.00               | -23.78          | Horizontal   |
| 7356.00         | 21.37             | 36.53                 | 6.67            | 37.76              | 26.81          | 54.00               | -27.19          | Horizontal   |
| 9808.00         | 21.04             | 38.17                 | 8.05            | 37.96              | 29.30          | 54.00               | -24.70          | Horizontal   |

**Notes:**

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## ■ Unwanted Emissions in restricted Frequency Bands

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11b | Test channel: | Lowest |
|------------|---------|---------------|--------|

### Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2310.00         | 39.72             | 27.14                 | 2.81            | 38.64                    | 31.03          | 74.00               | -42.97          | Horizontal   |
| 2390.00         | 48.09             | 27.37                 | 2.91            | 38.84                    | 39.53          | 74.00               | -34.47          | Horizontal   |
| 2310.00         | 38.27             | 27.14                 | 2.81            | 38.64                    | 29.58          | 74.00               | -44.42          | Vertical     |
| 2390.00         | 49.37             | 27.37                 | 2.91            | 38.84                    | 40.81          | 74.00               | -33.19          | Vertical     |

### Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2310.00         | 30.04             | 27.14                 | 2.81            | 38.64                    | 21.35          | 54.00               | -32.65          | Horizontal   |
| 2390.00         | 37.12             | 27.37                 | 2.91            | 38.84                    | 28.56          | 54.00               | -25.44          | Horizontal   |
| 2310.00         | 28.70             | 27.14                 | 2.81            | 38.64                    | 20.01          | 54.00               | -33.99          | Vertical     |
| 2390.00         | 39.10             | 27.37                 | 2.91            | 38.84                    | 30.54          | 54.00               | -23.46          | Vertical     |

|            |         |               |         |
|------------|---------|---------------|---------|
| Test mode: | 802.11b | Test channel: | Highest |
|------------|---------|---------------|---------|

### Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 48.55             | 27.82                 | 2.99            | 39.05                    | 40.31          | 74.00               | -33.69          | Horizontal   |
| 2500.00         | 41.00             | 27.70                 | 3.01            | 39.10                    | 32.61          | 74.00               | -41.39          | Horizontal   |
| 2483.50         | 48.42             | 27.82                 | 2.99            | 39.05                    | 40.18          | 74.00               | -33.82          | Vertical     |
| 2500.00         | 42.17             | 27.70                 | 3.01            | 39.10                    | 33.78          | 74.00               | -40.22          | Vertical     |

### Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 37.11             | 27.82                 | 2.99            | 39.05                    | 28.87          | 54.00               | -25.13          | Horizontal   |
| 2500.00         | 33.58             | 27.70                 | 3.01            | 39.10                    | 25.19          | 54.00               | -28.81          | Horizontal   |
| 2483.50         | 37.89             | 27.82                 | 2.99            | 39.05                    | 29.65          | 54.00               | -24.35          | Vertical     |
| 2500.00         | 32.39             | 27.70                 | 3.01            | 39.10                    | 24.00          | 54.00               | -30.00          | Vertical     |

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11g | Test channel: | Lowest |
|------------|---------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2310.00         | 39.56             | 27.14                 | 2.81            | 38.64                    | 30.87          | 74.00               | -43.13          | Horizontal   |
| 2390.00         | 47.87             | 27.37                 | 2.91            | 38.84                    | 39.31          | 74.00               | -34.69          | Horizontal   |
| 2310.00         | 38.09             | 27.14                 | 2.81            | 38.64                    | 29.40          | 74.00               | -44.60          | Vertical     |
| 2390.00         | 49.10             | 27.37                 | 2.91            | 38.84                    | 40.54          | 74.00               | -33.46          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2310.00         | 29.92             | 27.14                 | 2.81            | 38.64                    | 21.23          | 54.00               | -32.77          | Horizontal   |
| 2390.00         | 36.99             | 27.37                 | 2.91            | 38.84                    | 28.43          | 54.00               | -25.57          | Horizontal   |
| 2310.00         | 28.57             | 27.14                 | 2.81            | 38.64                    | 19.88          | 54.00               | -34.12          | Vertical     |
| 2390.00         | 38.95             | 27.37                 | 2.91            | 38.84                    | 30.39          | 54.00               | -23.61          | Vertical     |

|            |         |               |         |
|------------|---------|---------------|---------|
| Test mode: | 802.11g | Test channel: | Highest |
|------------|---------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 48.32             | 27.82                 | 2.99            | 39.05                    | 40.08          | 74.00               | -33.92          | Horizontal   |
| 2500.00         | 40.82             | 27.70                 | 3.01            | 39.10                    | 32.43          | 74.00               | -41.57          | Horizontal   |
| 2483.50         | 48.15             | 27.82                 | 2.99            | 39.05                    | 39.91          | 74.00               | -34.09          | Vertical     |
| 2500.00         | 41.96             | 27.70                 | 3.01            | 39.10                    | 33.57          | 74.00               | -40.43          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 36.97             | 27.82                 | 2.99            | 39.05                    | 28.73          | 54.00               | -25.27          | Horizontal   |
| 2500.00         | 33.47             | 27.70                 | 3.01            | 39.10                    | 25.08          | 54.00               | -28.92          | Horizontal   |
| 2483.50         | 37.73             | 27.82                 | 2.99            | 39.05                    | 29.49          | 54.00               | -24.51          | Vertical     |
| 2500.00         | 32.27             | 27.70                 | 3.01            | 39.10                    | 23.88          | 54.00               | -30.12          | Vertical     |

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT20) | Test channel: | Lowest |
|------------|---------------|---------------|--------|

## Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2310.00         | 39.67             | 27.14                 | 2.81            | 38.64                    | 30.98          | 74.00               | -43.02          | Horizontal   |
| 2390.00         | 48.02             | 27.37                 | 2.91            | 38.84                    | 39.46          | 74.00               | -34.54          | Horizontal   |
| 2310.00         | 38.22             | 27.14                 | 2.81            | 38.64                    | 29.53          | 74.00               | -44.47          | Vertical     |
| 2390.00         | 49.29             | 27.37                 | 2.91            | 38.84                    | 40.73          | 74.00               | -33.27          | Vertical     |

## Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2310.00         | 30.00             | 27.14                 | 2.81            | 38.64                    | 21.31          | 54.00               | -32.69          | Horizontal   |
| 2390.00         | 37.08             | 27.37                 | 2.91            | 38.84                    | 28.52          | 54.00               | -25.48          | Horizontal   |
| 2310.00         | 28.67             | 27.14                 | 2.81            | 38.64                    | 19.98          | 54.00               | -34.02          | Vertical     |
| 2390.00         | 39.06             | 27.37                 | 2.91            | 38.84                    | 30.50          | 54.00               | -23.50          | Vertical     |

|            |               |               |         |
|------------|---------------|---------------|---------|
| Test mode: | 802.11n(HT20) | Test channel: | Highest |
|------------|---------------|---------------|---------|

## Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 48.48             | 27.82                 | 2.99            | 39.05                    | 40.24          | 74.00               | -33.76          | Horizontal   |
| 2500.00         | 40.94             | 27.70                 | 3.01            | 39.10                    | 32.55          | 74.00               | -41.45          | Horizontal   |
| 2483.50         | 48.34             | 27.82                 | 2.99            | 39.05                    | 40.10          | 74.00               | -33.90          | Vertical     |
| 2500.00         | 42.11             | 27.70                 | 3.01            | 39.10                    | 33.72          | 74.00               | -40.28          | Vertical     |

## Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 37.07             | 27.82                 | 2.99            | 39.05                    | 28.83          | 54.00               | -25.17          | Horizontal   |
| 2500.00         | 33.55             | 27.70                 | 3.01            | 39.10                    | 25.16          | 54.00               | -28.84          | Horizontal   |
| 2483.50         | 37.84             | 27.82                 | 2.99            | 39.05                    | 29.60          | 54.00               | -24.40          | Vertical     |
| 2500.00         | 32.35             | 27.70                 | 3.01            | 39.10                    | 23.96          | 54.00               | -30.04          | Vertical     |

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT40) | Test channel: | Lowest |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2310.00         | 39.47             | 27.14                 | 2.81            | 38.64                    | 30.78          | 74.00               | -43.22          | Horizontal   |
| 2390.00         | 47.75             | 27.37                 | 2.91            | 38.84                    | 39.19          | 74.00               | -34.81          | Horizontal   |
| 2310.00         | 38.00             | 27.14                 | 2.81            | 38.64                    | 29.31          | 74.00               | -44.69          | Vertical     |
| 2390.00         | 48.96             | 27.37                 | 2.91            | 38.84                    | 40.40          | 74.00               | -33.60          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2310.00         | 29.86             | 27.14                 | 2.81            | 38.64                    | 21.17          | 54.00               | -32.83          | Horizontal   |
| 2390.00         | 36.92             | 27.37                 | 2.91            | 38.84                    | 28.36          | 54.00               | -25.64          | Horizontal   |
| 2310.00         | 28.50             | 27.14                 | 2.81            | 38.64                    | 19.81          | 54.00               | -34.19          | Vertical     |
| 2390.00         | 38.87             | 27.37                 | 2.91            | 38.84                    | 30.31          | 54.00               | -23.69          | Vertical     |

|            |               |               |         |
|------------|---------------|---------------|---------|
| Test mode: | 802.11n(HT40) | Test channel: | Highest |
|------------|---------------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 48.19             | 27.82                 | 2.99            | 39.05                    | 39.95          | 74.00               | -34.05          | Horizontal   |
| 2500.00         | 40.72             | 27.70                 | 3.01            | 39.10                    | 32.33          | 74.00               | -41.67          | Horizontal   |
| 2483.50         | 48.00             | 27.82                 | 2.99            | 39.05                    | 39.76          | 74.00               | -34.24          | Vertical     |
| 2500.00         | 41.84             | 27.70                 | 3.01            | 39.10                    | 33.45          | 74.00               | -40.55          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 36.89             | 27.82                 | 2.99            | 39.05                    | 28.65          | 54.00               | -25.35          | Horizontal   |
| 2500.00         | 33.41             | 27.70                 | 3.01            | 39.10                    | 25.02          | 54.00               | -28.98          | Horizontal   |
| 2483.50         | 37.64             | 27.82                 | 2.99            | 39.05                    | 29.40          | 54.00               | -24.60          | Vertical     |
| 2500.00         | 32.21             | 27.70                 | 3.01            | 39.10                    | 23.82          | 54.00               | -30.18          | Vertical     |

**Remarks:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 8 Test Setup Photo

Reference to the **appendix I** for details.

## 9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----