TEST REPORT

Report No. ..... :	**CHTEW20110096**	**Report verificaiton:**
Project No. ..... :	**SHT2011030002EW**	
FCC ID ..... :	**ZSW-30-103**	
Applicant's name ..... :	**b mobile HK Limited**	
Address.....:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.	
Test item description ..... :	**Mobile Phone**	
Trade Mark .....:	Bmobile	
Model/Type reference.....:	50 PRO	
Listed Model(s) .....:	B50,B50 Lite	
Standard ..... :	**FCC 47 CFR Part2.1093** **IEEE Std C95.1, 1999 Edition** **IEEE 1528: 2013**	
Date of receipt of test sample……..:	Nov.09, 2020	
Date of testing……...:	Nov.10, 2020- Nov.15, 2020	
Date of issue……..:	Nov.16, 2020	
Result..... ……...:	**PASS**	

Compiled by (position+printedname+signature)...:	File administrators: Fanghui Zhu	Fanghui Zhu
Supervised by (position+printedname+signature)...:	Test Engineer: Patrick Qiu	Patrick. Qiu
Approved by (position+printedname+signature)...:	Manager: Hans Hu	Hans Hu

Testing Laboratory Name ..... :	**Shenzhen Huatongwei International Inspection Co., Ltd**
Address.....:	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

1. Statement of Compliance 4
2. Test Standards and Report version 5
   2.1. Test Standards 5
   2.2. Report version 5
3. Summary 6
   3.1. Client Information 6
   3.2. Product Description 6
   3.3. RF Specification Description 6
   3.4. Testing Laboratory Information 8
   3.5. Environmental conditions 8
4. Equipments Used during the Test 9
5. Measurement Uncertainty 10
6. SAR Measurements System Configuration 11
   6.1. SAR Measurement Set-up 11
   6.2. DASY5 E-field Probe System 12
   6.3. Phantoms 13
   6.4. Device Holder 13
7. SAR Test Procedure 14
   7.1. Scanning Procedure 14
   7.2. Data Storage and Evaluation 16
8. Position of the wireless device in relation to the phantom 18
   8.1. Head Position 18
   8.2. Body Position 19
   8.3. Hotspot Mode Exposure conditions 19
9. Dielectric Property Measurements & System Check 20
   9.1. Tissue Dielectric Parameters 20
   9.2. System Check 22
10. SAR Exposure Limits 28
11. Conducted Power Measurement Results 29
   11.1. GSM 29
   11.2. WCDMA 30
   11.3. Wi-Fi 33
   11.4. Bluetooth 33
12. Maximum Tune-up Limit 34
13. Antenna Location 36
14. Measured and Reported SAR Results 37
   14.1. Head SAR 39
   14.2. Body SAR 42
   14.3. Hotspot SAR 44
15. SAR Measurement Variability 46
16. Simultaneous Transmission analysis 47
   16.1. Head 48
   16.2. Body-worn 50

16.3. Hotspot 51
17. TestSetup Photos 52
18. External and Internal Photos of the EUT 54

1 . Statement of Compliance

Maximum Reported SAR (W/kg @1g)			
RF Exposure Conditions	PCE	DTS	Simultaneous TX
Head	0.710	0.190	0.900
Body-worn(Dist.= 10mm)	0.877	0.051	0.927
Hotspot(Dist.= 10mm)	0.877	0.051	0.927

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

2 . Test Standards and Report version

2.1. Test Standards

The tests were performed according to following standards:

FCC 47 Part 2.1093: Radiofrequency radiation exposure evaluation: portable devices.
IEEE Std C95.1, 1999 Edition: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
IEEE Std 1528™-2013: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.

FCC published RF exposure KDB procedures:
865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz
865664 D02 RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations
447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
248227 D01 802 11 Wi-Fi SAR v02r02: SAR Measurement Proceduresfor802.11 a/b/g Transmitters
648474 D04 Handset SAR v01r03: SAR Evaluation Considerations for Wireless Handsets
941225 D01 3G SAR Procedures v03r01: SAR Measurement Procedures for 3G Devices
941225 D06 Hotspot Mode v02r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

TCB workshop April, 2019; Page 19, Tissue Simulating Liquids (TSL)

2.2. Report version

Revision No.	Date of issue	Description
N/A	2020-11-16	Original

3. Summary

3.1. Client Information

Applicant:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.
Manufacturer:	b mobile HK Limited
Address:	Flat 18; 14/F Block 1; Golden Industrial Building;16-26 Kwai Tak Street; Kwai Chung; New Territories; Hong Kong.

3.2. Product Description

Main unit	
Name of EUT:	Mobile Phone
Trade Mark:	Bmobile
Model No.:	50 PRO
Listed Model(s):	B50,B50 Lite
Power supply:	DC 3.8V
Device Category:	Portable
Product stage:	Production unit
RF Exposure Environment:	General Population/Uncontrolled
HTW test sample No.:	YPHT20110300001
Hardware version:	Bmobile_B50 Pro_OM_LATAM_V001
Software version:	Bmobile_B50 Pro_OM_LATAM_V002
Device Dimension:	Overall (Length x Width x Thickness): 145x70x10mm

3.3. RF Specification Description

GSM	
Operation Band:	GSM850 PCS1900
Support Network:	GSM GPRS
Operating Mode:	GSM:GMSK GPRS:GMSK
Device Class:	B
GPRS Multi-Slot Class:	12
Antenna Type:	PIFA
Does this device support DTM (Dual Transfer Mode)? ☐ Yes ☒ No	

WCDMA	
Operation Band:	FDD Band II FDD Band IV FDD Band V
Power Class:	Class 3
Operating Mode:	UMTS Rel. 99 (Voice & Data) HSDPA HSUPA
Antenna Type:	PIFA
Wi-Fi 2.4G	
Operating Mode:	802.11b 802.11g 802.11n(HT20)
Antenna Type:	PIFA
Does this device 2.4GHz Wi-Fi support hotspot operation? ☒ Yes ☐ No	
Bluetooth	
Bluetooth version:	V4.2
Support function:	EDR
Operating Mode:	GFSK π/4DQPSK 8DPSK
Antenna Type:	PIFA
Does this device support Bluetooth Tethering? ☒ Yes ☐ No	
Bluetooth	
Bluetooth version:	V4.2
Support function:	BLE
Operating Mode:	GFSK
Antenna Type:	PIFA
Does this device support Bluetooth Tethering? ☒ Yes ☐ No	
Remark: *1. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power.* *2. The Test EUT support two SIM card(SIM1,SIM2),so all the tests are performed at each SIM card (SIM1,SIM2) mode, the datum recorded is the worst case for all the mode at SIM1 Card mode.*	

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Qualifications	Type	Accreditation Number
	CNAS	L1225
	A2LA	3902.01
	FCC	762235
	Canada	5377A

3.5. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Ambient temperature	18 °C to 25 °C
Ambient humidity	30%RH to 70%RH
Air Pressure	950-1050mbar

4. Equipments Used during the Test

Used	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date (YY-MM-DD)	Due date (YY-MM-DD)
●	Data Acquisition Electronics DAEx	SPEAG	DAE4	1549	2020/04/04	2021/04/03
●	E-field Probe	SPEAG	EX3DV4	7494	2020/04/01	2021/03/31
●	Universal Radio Communication Tester	R&S	CMW500	137681	2020/06/18	2021/06/17
● Tissue-equivalent liquids Validation						
●	Dielectric Assessment Kit	SPEAG	DAK-3.5	1267	N/A	N/A
○	Dielectric Assessment Kit	SPEAG	DAK-12	1130	N/A	N/A
●	Network analyzer	Keysight	E5071C	MY46733048	2020/10/15	2021/10/14
● System Validation						
○	System Validation Antenna	SPEAG	CLA-150	4024	2018/02/21	2021/02/20
○	System Validation Dipole	SPEAG	D450V3	1102	2018/02/23	2021/02/22
○	System Validation Dipole	SPEAG	D750V3	1180	2018/02/07	2021/02/06
●	System Validation Dipole	SPEAG	D835V2	4d238	2018/02/19	2021/02/18
●	System Validation Dipole	SPEAG	D1750V2	1164	2018/02/06	2021/02/05
●	System Validation Dipole	SPEAG	D1900V2	5d226	2018/02/22	2021/02/21
●	System Validation Dipole	SPEAG	D2450V2	1009	2018/02/05	2021/02/04
○	System Validation Dipole	SPEAG	D2600V2	1150	2018/02/05	2021/02/04
○	System Validation Dipole	SPEAG	D5GHzV2	1273	2018/02/21	2021/02/20
●	Signal Generator	R&S	SMB100A	114360	2020/08/11	2021/08/10
●	Power Viewer for Windows	R&S	N/A	N/A	N/A	N/A
●	Power sensor	R&S	NRP18A	101010	2020/08/11	2021/08/10
●	Power sensor	R&S	NRP18A	101386	2020/06/08	2021/06/07
●	Power Amplifier	BONN	BLWA 0160-2M	1811887	2020/11/12	2021/11/11
●	Dual Directional Coupler	Mini-Circuits	ZHDC-10-62-S+	F975001814	2020/11/12	2021/11/11
●	Attenuator	Mini-Circuits	VAT-3W2+	1819	2020/11/12	2021/11/11
●	Attenuator	Mini-Circuits	VAT-10W2+	1741	2020/11/12	2021/11/11

Note:

1. *The Probe,Dipole and DAE calibration reference to the Appendix B and C.*
2. *Referring to KDB865664 D01, the dipole calibration interval can be extended to 3 years with justifcatio. The dipole are also not physically damaged or repaired during the interval.*

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be ⩽ 30%, for a confidence interval of k = 2. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

Therefore, the measurement uncertainty is not required.

6. SAR Measurements System Configuration

6.1. SAR Measurement Set-up

The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).

A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

A unit to operate the optical surface detector which is connected to the EOC.

The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.

The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.

DASY5 software and SEMCAD data evaluation software.

Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.

The generic twin phantom enabling the testing of left-hand and right-hand usage.

The device holder for handheld Mobile Phones.

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles allowing to validate the proper functioning of the system.



6.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

- **Probe Specification**

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available.
Frequency	4 MHz to 10 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 µW/g to > 100 W/kg; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 6 GHz Dosimetry in strong gradient fields Compliance tests of Mobile Phones
Compatibility	DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI

- **Isotropic E-Field Probe**

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



6.3. Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness increases to 6mm).
System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

SAM-Twin Phantom

6.4. Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the DASY system.
The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

Device holder supplied by SPEAG

7. SAR Test Procedure

7.1. Scanning Procedure

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. Measure the local SAR at a test point within 8 mm of the phantom inner surface that is closest to the DUT. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Resolutions per FCC KDB Publication 865664 D01v04

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 mm ± 1 mm	½·δ·ln(2) mm ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area}, Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1g and 10g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Resolutions per FCC KDB Publication 865664 D01v04

Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$ mm	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details. * When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB Publication 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1. The SAR drift shall be kept within ± 5 %.

7.2. Data Storage and Evaluation

Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors),s together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [W/kg], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	Sensitivity:	Normi, ai0, ai1, ai2
	Conversion factor:	ConvFi
	Diode compression point:	Dcpi
Device parameters:	Frequency:	f
	Crest factor:	cf
Media parameters:	Conductivity:	σ
	Density:	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Vi: compensated signal of channel (i = x, y, z)
Ui: input signal of channel (i = x, y, z)
cf: crest factor of exciting field (DASY parameter)
dcpi: diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E} - \text{fieldprobes}: \qquad E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\text{H} - \text{fieldprobes}: \qquad H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1} f + a_{i2} f^2}{f}$$

Vi: compensated signal of channel (i = x, y, z)
Normi: sensor sensitivity of channel (i = x, y, z), [mV/(V/m)2] for E-field Probes
ConvF: sensitivity enhancement in solution
aij: sensor sensitivity factors for H-field probes
f: carrier frequency [GHz]
Ei: electric field strength of channel i in V/m
Hi: magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

SAR: local specific absorption rate in W/kg
Etot: total field strength in V/m
σ: conductivity in [mho/m] or [Siemens/m]
ρ: equivalent tissue density in g/cm3

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

8. Position of the wireless device in relation to the phantom

8.1. Head Position

The wireless device define two imaginary lines on the handset, the vertical centreline and the horizontal line, for the handset in vertical orientation as shown in Figures 5a and 5b.
The vertical centreline passes through two points on the front side of the handset: the midpoint of the width W_t of the handset at the level of the acoustic output (point A in Figures 5a and 5b), and the midpoint of the width W_b of the bottom of the handset (point B).
The horizontal line is perpendicular to the vertical centreline and passes through the centre of the acoustic output (see Figures 5a and 5b). The two lines intersect at point A.
Note that for many handsets, point A coincides with the centre of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centreline is not necessarily parallel to the front face of the handset (see Figure 5b), especially for clam-shell handsets, handsets with flip cover pieces, and other irregularly shaped handsets.



Figures 5a



Figures 5b

W_t	Width of the handset at the level of the acoustic
W_b	Width of the bottom of the handset
A	Midpoint of the widthwt of the handset at the level of the acoustic output
B	Midpoint of the width wb of the bottom of the handset

Cheek position



Picture 2 Cheek position of the wireless device on the left side of SAM

Tilt position



Picture 3 Tilt position of the wireless device on the left side of SAM

8.2. Body Position

Devices that support transmission while used with body-worn accessories must be tested for body-worn accessory SAR compliance, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics.
Devices that are designed to operate on the body of users using lanyards and straps or without requiring additional body-worn accessories must be tested for SAR compliance using a conservative minimum test separation distance ≤ 5mm to support compliance.



Picture 4 Test positions for body-worn devices

8.3. Hotspot Mode Exposure conditions

The hotspot mode and body-worn accessory SAR test configurations may overlap for handsets. When the same wireless mode transmission configurations for voice and data are required for SAR measurements, the more conservative configuration with a smaller separation distance should be tested for the overlapping SAR configurations. This typically applies to the back and front surfaces of a handset when SAR is required for both hotspot mode and body-worn accessory exposure conditions. Depending on the form factor and dimensions of a device, the test separation distance used for hotspot mode SAR measurement is either 10 mm or that used in the body-worn accessory configuration, whichever is less for devices with dimension > 9 cm x 5 cm. For smaller devices with dimensions ≤ 9 cm x 5 cm because of a greater potential for next to body use a test separation of ≤ 5 mm must be used.



Picture 5 Test positions for Hotspot Mode

9. Dielectric Property Measurements & System Check

9.1. Tissue Dielectric Parameters

The temperature of the tissue-equivalent medium used during measurement must also be within 18℃ to 25℃ and within ± 2℃ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3-4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

The dielectric constant (ε_r) and conductivity (σ) of typical tissue-equivalent media recipes are expected to be within ± 5% of the required target values; but for SAR measurement systems that have implemented the SAR error compensation algorithms documented in IEEE Std 1528-2013, to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters, the tolerance for ε_r and σ may be relaxed to ± 10%. This is limited to frequencies ≤ 3 GHz.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Tissue dielectric parameters for Head and Body				
Target Frequency (MHz)	Head		Body	
	ε_r	σ(S/m)	ε_r	σ(S/m)
835	41.5	0.90	55.2	0.97
1750	40.1	1.37	53.4	1.49
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95

IEEE Std 1528-2013

Refer to Table 3 within the IEEE Std 1528-2013

Dielectric Property Measurements Results:

Dielectric performance of Head tissue simulating liquid									
Frequency (MHz)	ε_r		σ(S/m)		Delta (ε_r)	Delta (σ)	Limit	Temp (℃)	Date
	Target	Measured	Target	Measured					
835	41.50	43.19	0.900	0.941	4.07%	4.56%	±5%	22.6	2020-11-10
1750	40.10	41.39	1.370	1.370	3.22%	0.00%	±5%	22.3	2020-11-12
1900	40.00	41.19	1.400	1.455	2.97%	3.93%	±5%	22.5	2020-11-11
2450	39.20	40.44	1.800	1.835	3.16%	1.94%	±5%	22.3	2020-11-12

9.2. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions:

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0±0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm for SAR measurements ≤ 3 GHz and ≥10.0 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
  For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- The results are normalized to 1 W input power.



System Performance Check Setup



Photo of Dipole Setup

System Check Result:
The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within ±10% of the manufacturer calibrated dipole SAR target.

Head											
Frequency (MHz)	1g SAR			10g SAR			Delta (1g)	Delta (10g)	Limit	Temp (℃)	Date
	Target 1W	Normalize to 1W	Measured 250mW	Target 1W	Normalize to 1W	Measured 250mW					
835	9.51	10.28	2.57	6.15	6.72	1.68	8.10%	9.27%	±10%	22.6	2020-11-10
1750	36.60	38.68	9.67	19.40	20.72	5.18	5.68%	6.80%	±10%	22.3	2020-11-12
1900	40.30	44.00	11.00	21.10	22.96	5.74	9.18%	8.82%	±10%	22.5	2020-11-11
2450	51.50	55.20	13.80	24.10	25.80	6.45	7.18%	7.05%	±10%	22.3	2020-11-12

Plots of System Performance Check

System Performance Check-Head 835MHz

DUT: D835V2; Type: D835V2; Serial: 4d238
Date: 2020-11-10
Communication System: UID 0, CW (0); Frequency: 835 MHz;Duty Cycle: 1:1
Medium parameters used: f = 835 MHz; σ = 0.946 S/m; ε_r = 43.19; ρ = 1000 kg/m^3
Phantom section: Flat Section
Ambient Temperature:22.7℃;Liquid Temperature:22.5℃;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(10.46, 10.46, 10.46) @ 835 MHz; Calibrated: 4/1/2020
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/4/2020
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=15mm, Pin=250mW/Area Scan (41x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 3.52W/kg

Head/d=15mm, Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 62.70 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 4.04W/kg
SAR(1 g) = 2.57 W/kg; SAR(10 g) = 1.68 W/kg
Maximum value of SAR (measured) = 3.51 W/kg



0 dB = 3.51 W/kg = 5.45 dBW/kg

System Performance Check-Head 1750MHz

DUT: D1750V2; Type: D1750V2; Serial: 1164
Date: 2020-11-12
Communication System: UID 0, CW (0); Frequency: 1750 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1750 MHz; σ = 1.37 S/m; ε_r = 41.39; ρ = 1000 kg/m^3
Phantom section: Flat Section
Ambient Temperature:22.6℃;Liquid Temperature:22.4℃;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.92, 8.92, 8.92) @ 1750 MHz; Calibrated: 4/1/2020
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/4/2020
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 14.9 W/kg

Head/d=10mm,Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 106.3 V/m; Power Drift = -0.00 dB
Peak SAR (extrapolated) = 17.8 W/kg
SAR(1 g) = 9.67 W/kg; SAR(10 g) = 5.18 W/kg
Maximum value of SAR (measured) = 14.9 W/kg



0 dB = 14.9 W/kg = 11.73 dBW/kg

System Performance Check-Head 1900MHz

DUT: D1900V2; Type: D1900V2; Serial: 5d226
Date: 2020-11-11
Communication System: UID 0, CW (0); Frequency: 1900 MHz;Duty Cycle: 1:1
Medium parameters used: f = 1900 MHz; σ = 1.455 S/m; ε_r = 41.189; ρ = 1000 kg/m^3
Phantom section: Flat Section
Ambient Temperature:22.5℃;Liquid Temperature:22.3℃;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(8.6, 8.6, 8.6) @ 1900 MHz; Calibrated: 4/1/2020
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/4/2020
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 17.5 W/kg

Head/d=10mm,Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 111.8 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 20.7 W/kg
SAR(1 g) = 11 W/kg; SAR(10 g) = 5.74 W/kg
Maximum value of SAR (measured) = 17.0W/kg



0 dB = 17.0 W/kg = 12.30 dBW/kg

SystemPerformanceCheck-Head 2450MHz

DUT: D2450V2; Type: D2450V2; Serial: 1009
Date: 2020-11-12
Communication System: UID 0, CW (0); Frequency: 2450 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 2450 MHz; σ = 1.835 S/m; ε_r = 40.444; ρ = 1000 kg/m^3
Phantom section: Flat Section
Ambient Temperature:22.4℃;Liquid Temperature:22.2℃;

DASY5 Configuration:

- Probe: EX3DV4 - SN7494; ConvF(7.91, 7.91, 7.91) @ 2450 MHz; Calibrated: 4/1/2020
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1549; Calibrated: 4/4/2020
- Phantom: Twin-SAM V8.0 ; Type: QD 000 P41 AA; Serial: 1974
- DASY52 52.10.2(1495); SEMCAD X 14.6.12(7450)

Head/d=10mm,Pin=250mW/Area Scan (41x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 23.4 W/kg

Head/d=10mm,Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 115.9 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 28.5 W/kg
SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.45 W/kg
Maximum value of SAR (measured) = 22.8 W/kg



0 dB = 22.8 W/kg = 13.58 dBW/kg

10. SAR Exposure Limits

SAR assessments have been made in line with the requirements of FCC 47 CFR § 2.1093.

Type Exposure	Limit (W/kg)	
	General Population/ Uncontrolled Exposure Environment	Occupational/ Controlled Exposure Environment
Spatial Average SAR (whole body)	0.08	0.4
Spatial Peak SAR (1g cube tissue for head and trunk)	1.6	8.0
Spatial Peak SAR (10g for limb)	4.0	20.0

Population/Uncontrolled Environments: are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

11. Conducted Power Measurement Results

11.1. GSM

1. *Per KDB 447498 D01, the maximum output power channel is used for SAR testing and further SAR test reduction.*
2. *Per KDB 941225 D01, considering the possibility of e.g. 3rd party VoIP operation for Head and Body-worn SAR test reduction for GSM and GPRS modes is determined by the source-base time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.*
3. *Per KDB941225 D01, for hotspot SAR test reduction for GPRS modes is determined by the source-based time-averaged output power including tune-up tolerance, For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.*

Mode: GSM850		**Burst Average Power (dBm)**			Division Factors	**Frame-Average Power (dBm)**		
		CH128	CH190	CH251		CH128	CH190	CH251
		824.2MHz	836.6MHz	848.8MHz		824.2MHz	836.6MHz	848.8MHz
GSM Voice		31.25	31.25	31.54	-9.03	22.22	22.22	22.51
GPRS (GMSK)	1TXslot	31.91	31.96	32.00	-9.03	22.88	22.93	22.97
	2TXslots	30.19	30.22	30.24	-6.02	24.17	24.20	24.22
	3TXslots	28.65	28.55	28.71	-4.26	24.39	24.29	24.45
	4TXslots	26.65	26.75	26.74	-3.01	23.64	23.74	23.73
Mode: PCS1900		**Burst Average Power (dBm)**			Division Factors	**Frame-Average Power (dBm)**		
		CH512	CH661	CH810		CH512	CH661	CH810
		1850.2MHz	1880MHz	1909.8MHz		1850.2MHz	1880MHz	1909.8MHz
GSM Voice		30.12	30.35	30.50	-9.03	21.09	21.32	21.47
GPRS (GMSK)	1TXslot	30.18	30.34	30.44	-9.03	21.15	21.31	21.41
	2TXslots	28.48	28.71	28.84	-6.02	22.46	22.69	22.82
	3TXslots	26.81	27.05	27.05	-4.26	22.55	22.79	22.79
	4TXslots	24.64	24.88	25.05	-3.01	21.63	21.87	22.04

Note:

1) Division Factors

To Frame-Average Power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> Burst Average Power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> Burst Average Power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> Burst Average Power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> Burst Average Power divided by (8/4) => -3.01dB

11.2. WCDMA

1. *The following tests were conducted according to the test requirements outlines in 3GPP TS34.121 specification.*
2. *The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode to determine SAR test exclusion*

A summary of thest setting are illustrated belowe:

HSDPA Setup Configureation:

a) The EUT was connected to base station RS CMU200 referred to the setup configuration
b) The RF path losses were compensated into the measurements
c) A call was established between EUT and base station with following setting:
   i. Set Gain Factors (βc and βd) and parameters were set according to each specific sub-test in the following table, C10.1.4, Quoted from the TS 34.121
   ii. Set RMC 12.2Kbps + HSDPA mode
   iii. Set Cell Power=-86dBm
   iv. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
   v. Select HSDPA uplink parameters
   vi. Set Delta ACK, Delta NACK and Delta CQI=8
   vii. Set Ack-Nack repetition Factor to 3
   viii. Set CQI Feedback Cycle (K) to 4ms
   ix. Set CQI repetition factor to 2
   x. Power ctrl mode= all up bits
d) The transmitter maximum output power waw recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 30/15 with β_{hs} = 30/15 * β_c.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and Δ_{NACK} = 30/15 with β_{hs} = 30/15 * β_c, and Δ_{CQI} = 24/15 with β_{hs} = 24/15 * β_c.

Note 3: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c=24/15. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to β_c = 11/15 and β_d = 15/15.

Setup Configuration

HSUPA Setup Configureation:

a) The EUT was connected to base station RS CMU200 referred to the setup configuration
b) The RF path losses were compensated into the measurements
c) A call was established between EUT and base station with following setting:
   i. Call configs = 5.2b, 5.9b, 5.10b, and 5.13.2B with QPSK
   ii. Set Gain Factors (βc and βd) and parameters (AG index) were set according to each specific sub-test in the following table, C11.1.3, Quoted from the TS 34.121
   iii. Set Cell Power=-86dBm
   iv. Set channel type= 12.2Kbps + HSPA mode
   v. Set UE Target power
   vi. Set Ctrl mode=Alternating bits
   vii. Set and observe the E-TFCI
   viii. Confirm that E-TFCI is equal the target E-TFCI of 75 for Sub-test 1, and other subtest's E-TFCI
d) The transmitter maximum output power waw recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/225	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed}1$: 47/15 $\beta_{ed}2$: 47/15	4 4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK}, Δ_{NACK} and Δ_{CQI} = 30/15 with β_{hs} = 30/15 * β_c .

Note 2: CM = 1 for β_c/β_d =12/15, β_{hs}/β_c=24/15. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to β_c = 10/15 and β_d = 15/15.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to β_c = 14/15 and β_d = 15/15.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

General Note:

1. Per KDB 941225 D01, SAR for Head / Hotsport / Body-worn Exposure is measured using a 12.2Kbps RMC with TPC bit ocnfigured to all 1s
2. Per KDB 941225 D01 RMC12.2Kbps setting is used to evaluate SAR. If the maximum output power and Tune-up tolerance specified for production units in HSDPA/HSUPA is ≦1/4dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio fo specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC 12.2Kbps and the adjusted SAR is ≦1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

Mode		WCDMA Band II			WCDMA Band IV		
		Conducted Power (dBm)			Conducted Power (dBm)		
		CH9262	CH9400	CH9538	CH1312	CH1413	CH1513
		1852.4MHz	1880MHz	1907.6MHz	1712.4MHz	1732.6MHz	1752.6MHz
AMR 12.2K		22.96	22.89	22.63	23.25	23.17	23.37
RMC 12.2K		22.99	22.92	22.66	23.28	23.20	23.41
HSDPA	Subtest-1	22.48	22.44	22.07	22.12	22.12	22.45
	Subtest-2	22.14	22.09	20.39	21.92	21.96	22.29
	Subtest-3	21.77	21.74	19.72	21.17	21.34	21.48
	Subtest-4	21.79	21.55	19.45	20.89	21.08	21.20
HSUPA	Subtest-1	19.77	19.69	19.69	20.36	20.34	20.54
	Subtest-2	19.96	19.99	19.93	20.26	20.44	20.64
	Subtest-3	19.65	19.59	19.66	20.25	20.42	20.47
	Subtest-4	19.99	19.96	19.99	20.34	20.48	20.72
	Subtest-5	22.97	23.02	22.93	22.63	22.72	22.90

Mode		WCDMA Band V		
		Conducted Power (dBm)		
		CH4132	CH4183	CH4233
		826.4MHz	836.6MHz	846.6MHz
AMR 12.2K		23.12	23.21	23.16
RMC 12.2K		23.15	23.24	23.19
HSDPA	Subtest-1	22.24	22.40	22.34
	Subtest-2	22.56	22.69	22.61
	Subtest-3	21.82	21.95	21.88
	Subtest-4	21.84	21.95	19.90
HSUPA	Subtest-1	18.92	19.04	19.05
	Subtest-2	19.04	19.15	19.14
	Subtest-3	19.28	19.26	19.28
	Subtest-4	19.17	19.22	19.13
	Subtest-5	22.74	22.90	22.82

11.3. Wi-Fi

For 2.4GHz Wi-Fi SAR testing, highest average RF output power channel for the lowest data rate for 802.11b were for SAR evaluation.

The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures.

SAR testing is not required for OFDM mode(s) when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Wi-Fi 2.4G				
Mode	Channel	Frequency (MHz)	Conducted Peak Power (dBm)	Conducted Average Power (dBm)
802.11b	1	2412	13.87	11.72
	6	2437	14.03	11.88
	11	2462	13.92	11.75
802.11g	1	2412	14.18	10.46
	6	2437	14.33	10.66
	11	2462	14.30	10.64
802.11n (HT20)	1	2412	14.57	11.40
	6	2437	14.71	11.51
	11	2462	14.48	11.25

11.4. Bluetooth

Bluetooth				
Mode	Channel	Frequency (MHz)	Conducted Peak Power (dBm)	Conducted Average Power (dBm)
GFSK	0	2402	5.26	5.24
	39	2441	4.84	4.82
	78	2480	4.01	4.00
π/4QPSK	0	2402	7.38	5.50
	39	2441	6.97	5.25
	78	2480	6.24	4.12
8DPSK	0	2402	**7.70**	**6.09**
	39	2441	7.29	5.26
	78	2480	6.56	4.71
BLE	0	2402	1.76	1.75
	19	2440	1.41	1.40
	39	2480	0.55	0.53

12. Maximum Tune-up Limit

GSM		
Mode	Maximum Tune-up (dBm)	
	GSM850	PCS1900
GSM (GMSK, 1Tx Slot)	32.00	31.00
GPRS (GMSK, 1Tx Slot)	32.00	30.50
GPRS (GMSK, 2Tx Slots)	30.50	29.00
GPRS (GMSK, 3Tx Slots)	29.00	27.50
GPRS (GMSK, 4Tx Slots)	27.00	25.50

WCDMA			
Mode	Maximum Tune-up (dBm)		
	FDD Band II	FDD Band IV	FDD Band V
AMR 12.2Kbps	23.00	23.50	23.50
RMC 12.2Kbps	23.00	23.50	23.50
HSDPA Subtest-1	22.50	22.50	22.50
HSDPA Subtest-2	22.50	22.50	23.00
HSDPA Subtest-3	22.00	21.50	22.00
HSDPA Subtest-4	22.00	21.50	22.00
HSUPA Subtest-1	20.00	21.00	19.50
HSUPA Subtest-2	20.00	21.00	19.50
HSUPA Subtest-3	20.00	20.50	19.50
HSUPA Subtest-4	20.00	21.00	19.50
HSUPA Subtest-5	23.50	23.00	23.00

Wi-Fi 2.4G		
Mode	Channel	Maximum Tune-up (dBm) Conducted Average Power
802.11b	1	12.00
	6	12.00
	11	12.00
802.11g	1	10.50
	6	11.00
	11	11.00
802.11n(HT20)	1	11.50
	6	12.00
	11	11.50

Bluetooth		
Mode	Channel	Maximum Tune-up (dBm) Conducted Average Power
GFSK	0	5.50
	39	5.00
	78	4.00
π/4 QPSK	0	5.50
	39	5.50
	78	4.50
8DPSK	0	6.50
	39	5.50
	78	5.00
BLE	0	2.00
	19	1.50
	39	1.00

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≦50mm are determined by:

[(max. Power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] * [√f(GHz)] ≦3.0 for 1-g SAR

Band/Mode	F(GHz)	Position	Separation Distance (mm)	Exclusion Thresholds	SAR test exclusion
Bluetooth	2.402	Head	0	1.4	Yes
		Body	10	0.7	Yes

Per KDB 447498 D01, when the minimum test separation distance is <5mm, a distance of 5mm is applied to determine SAR test exclusion.

The test exclusion thereshold is ≦3, SAR testing is not required.

13. Antenna Location



Distance of the Antenna to the EUT surface/edge(mm)						
Antenna	Rear	Front	Top side	Bottom side	Right side	Left side
WWAN	5mm	5mm	135mm	5mm	30mm	5mm
Wi-Fi/BT	5mm	5mm	5mm	125mm	5mm	60mm

Positions for SAR tests; Hotspot mode						
Antenna	Rear	Front	Top side	Bottom side	Right side	Left side
WWAN	Yes	Yes	No	Yes	Yes	Yes
Wi-Fi/BT	Yes	Yes	Yes	No	Yes	No

General note:
Referring to KDB941225 D06, when the overall device length and width are >9cm*5cm, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

14. Measured and Reported SAR Results

SAR Test Reduction criteria are as follows:

- Reported SAR(W/kg) for WWAN = Measured SAR *Tune-up Scaling Factor
- Reported SAR(W/kg) for Wi-Fi and Bluetooth = Measured SAR * Tune-up scaling factor * Duty Cycle scaling factor
- Duty Cycle scaling factor = 1 / Duty cycle (%)

KDB 447498 D01 General RF Exposure Guidance:

Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 648474 D04 Handset SAR:

With headset attached, when the reported SAR for body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset. Additional 1-g SAR testing at 5 mm is not required when hotspot mode 10-g extremity SAR is not required for the surfaces and edges; since all 1-g reported SAR < 1.2 W/kg.

KDB 941225 D01 SAR test for 3G SAR Test Reduction Procedure:

When the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤ ¼ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

GSM Guidance

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Please refer to section 9. for GSM power verification.

SAR is not required for EDGE (8PSK) mode because the maximum output power and tune-up limit is ≤ 1/4dB higher than GPRS/EDGE (GMSK) or the adjusted SAR of the highest reported SAR of GPRS/EDGE (GMSK) is ≤ 1.2W/kg.

W-CDMA Guidance

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1’s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC (Head) and other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC (Body-Worn Accessory) as the primary mode.

SAR measurement is not required for the HSDPA, HSUPA, DC-HSDPA and HSPA+. When primary mode and the adjusted SAR is ≤ 1.2 W/kg and secondary mode is ≤ ¼ dB higher than the primary mode

KDB 248227 D01 SAR meas for 802.11:

When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

SAR test reduction for 802.11 Wi-Fi transmission mode configurations are considered separately for DSSS and OFDM. An initial test position is determined to reduce the number of tests required for certain exposure configurations with multiple test positions. An initial test configuration is determined for each frequency band and aggregated band according to maximum output power, channel bandwidth, wireless mode configurations and other operating parameters to streamline the measurement requirements. For 2.4 GHz DSSS, either the initial test position or DSSS procedure is applied to reduce the number of SAR tests; these are mutually exclusive. For OFDM, an initial test position is only applicable to next to the ear, UMPC mini-tablet and hotspot mode configurations, which is tested using the initial test configuration to facilitate test reduction. For

other exposure conditions with a fixed test position, SAR test reduction is determined using only the initial test configuration.

The multiple test positions require SAR measurements in head, hotspot mode or UMPC mini-tablet configurations may be reduced according to the highest reported SAR determined using the initial test position(s) by applying the DSSS or OFDM SAR measurement procedures in the required wireless mode test configuration(s). The initial test position(s) is measured using the highest measured maximum output power channel in the required wireless mode test configuration(s). When the reported SAR for the initial test position is:

- ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and wireless mode combination within the frequency band or aggregated band. DSSS and OFDM configurations are considered separately according to the required SAR procedures.
- > 0.4 W/kg, SAR is repeated using the same wireless mode test configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions are tested.
  - For subsequent test positions with equivalent test separation distance or when exposure is dominated by coupling conditions, the position for maximum coupling condition should be tested.
  - When it is unclear, all equivalent conditions must be tested.
- For all positions/configurations tested using the initial test position and subsequent test positions,when the reported SAR is > 0.8 W/kg, measure the SAR for these positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required test channels are considered.
  - The additional power measurements required for this step should be limited to those necessary for identifying subsequent highest output power channels to apply the test reduction.
- When the specified maximum output power is the same for both UNII 1 and UNII 2A, begin SAR measurements in UNII 2A with the channel with the highest measured output power. If the reported SAR for UNII 2A is ≤ 1.2 W/kg, SAR is not required for UNII 1; otherwise treat the remaining bands separately and test them independently for SAR.
- When the specified maximum output power is different between UNII 1 and UNII 2A, begin SAR with the band that has the higher specified maximum output. If the highest reported SAR for the band with the highest specified power is ≤ 1.2 W/kg, testing for the band with the lower specified output power is not required; otherwise test the remaining bands independently for SAR.

To determine the initial test position, Area Scans were performed to determine the position with the Maximum Value of SAR (measured). The position that produced the highest Maximum Value of SAR is considered the worst case position; thus used as the initial test position.

14.1. Head SAR

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (3Tx slots)	Left Cheek	128	824.2	28.65	29.00	1.084	-	-	-	-
		190	836.6	28.55	29.00	1.109	-	-	-	-
		251	848.8	28.71	29.00	1.069	-0.02	0.632	0.676	-
	Left Tilt	128	824.2	28.65	29.00	1.084	-	-	-	-
		190	836.6	28.55	29.00	1.109	-	-	-	-
		251	848.8	28.71	29.00	1.069	-0.09	0.417	0.446	-
	Right Cheek	128	824.2	28.65	29.00	1.084	-	-	-	-
		190	836.6	28.55	29.00	1.109	-	-	-	-
		251	848.8	28.71	29.00	1.069	0.01	0.664	0.710	1
	Right Tilt	128	824.2	28.65	29.00	1.084	-	-	-	-
		190	836.6	28.55	29.00	1.109	-	-	-	-
		251	848.8	28.71	29.00	1.069	0.13	0.446	0.477	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (2Tx slots)	Left Cheek	512	1850.2	28.48	29.00	1.127	-	-	-	-
		661	1880	28.71	29.00	1.069	-	-	-	-
		810	1909.8	28.84	29.00	1.038	-0.13	0.346	0.359	2
	Left Tilt	512	1850.2	28.48	29.00	1.127	-	-	-	-
		661	1880	28.71	29.00	1.069	-	-	-	-
		810	1909.8	28.84	29.00	1.038	0.12	0.263	0.273	-
	Right Cheek	512	1850.2	28.48	29.00	1.127	-	-	-	-
		661	1880	28.71	29.00	1.069	-	-	-	-
		810	1909.8	28.84	29.00	1.038	-0.10	0.197	0.204	-
	Right Tilt	512	1850.2	28.48	29.00	1.127	-	-	-	-
		661	1880	28.71	29.00	1.069	-	-	-	-
		810	1909.8	28.84	29.00	1.038	-0.08	0.146	0.151	-

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Left Cheek	9262	1852.4	22.99	23.00	1.002	-0.19	0.401	0.402	3
		9400	1880	22.92	23.00	1.019	-	-	-	-
		9538	1907.6	22.66	23.00	1.081	-	-	-	-
	Left Tilt	9262	1852.4	22.99	23.00	1.002	-0.16	0.350	0.351	-
		9400	1880	22.92	23.00	1.019	-	-	-	-
		9538	1907.6	22.66	23.00	1.081	-	-	-	-
	Right Cheek	9262	1852.4	22.99	23.00	1.002	-0.17	0.191	0.191	-
		9400	1880	22.92	23.00	1.019	-	-	-	-
		9538	1907.6	22.66	23.00	1.081	-	-	-	-
	Right Tilt	9262	1852.4	22.99	23.00	1.002	0.08	0.156	0.156	-
		9400	1880	22.92	23.00	1.019	-	-	-	-
		9538	1907.6	22.66	23.00	1.081	-	-	-	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Left Cheek	1312	1712.4	23.28	23.50	1.052	-	-	-	-
		1413	1732.6	23.20	23.50	1.072	-	-	-	-
		1513	1752.6	23.41	23.50	1.021	-0.12	0.401	0.409	4
	Left Tilt	1312	1712.4	23.28	23.50	1.052	-	-	-	-
		1413	1732.6	23.20	23.50	1.072	-	-	-	-
		1513	1752.6	23.41	23.50	1.021	0.17	0.336	0.343	-
	Right Cheek	1312	1712.4	23.28	23.50	1.052	-	-	-	-
		1413	1732.6	23.20	23.50	1.072	-	-	-	-
		1513	1752.6	23.41	23.50	1.021	-0.04	0.183	0.187	-
	Right Tilt	1312	1712.4	23.28	23.50	1.052	-	-	-	-
		1413	1732.6	23.20	23.50	1.072	-	-	-	-
		1513	1752.6	23.41	23.50	1.021	-0.10	0.147	0.150	-

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Left Cheek	4132	826.4	23.15	23.50	1.084	-	-	-	-
		4183	836.6	23.24	23.50	1.062	0.17	0.260	0.276	-
		4233	846.6	23.19	23.50	1.074	-	-	-	-
	Left Tilt	4132	826.4	23.15	23.50	1.084	-	-	-	-
		4183	836.6	23.24	23.50	1.062	-0.03	0.237	0.252	-
		4233	846.6	23.19	23.50	1.074	-	-	-	-
	Right Cheek	4132	826.4	23.15	23.50	1.084	-	-	-	-
		4183	836.6	23.24	23.50	1.062	-0.12	0.271	0.288	5
		4233	846.6	23.19	23.50	1.074	-	-	-	-
	Right Tilt	4132	826.4	23.15	23.50	1.084	-	-	-	-
		4183	836.6	23.24	23.50	1.062	0.18	0.251	0.266	-
		4233	846.6	23.19	23.50	1.074	-	-	-	-

Wi-Fi 2.4G												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11b	Left Cheek	1	2412	11.72	12.00	1.067	99.40%	1.01	-	-	-	-
		6	2437	11.88	12.00	1.028	99.40%	1.01	-0.12	0.062	0.065	-
		11	2462	11.75	12.00	1.059	99.40%	1.01	-	-	-	-
	Left Tilt	1	2412	11.72	12.00	1.067	99.40%	1.01	-	-	-	-
		6	2437	11.88	12.00	1.028	99.40%	1.01	0.18	0.047	0.049	-
		11	2462	11.75	12.00	1.059	99.40%	1.01	-	-	-	-
	Right Cheek	1	2412	11.72	12.00	1.067	99.40%	1.01	-	-	-	-
		6	2437	11.88	12.00	1.028	99.40%	1.01	-0.13	0.184	0.190	6
		11	2462	11.75	12.00	1.059	99.40%	1.01	-	-	-	-
	Right Tilt	1	2412	11.72	12.00	1.067	99.40%	1.01	-	-	-	-
		6	2437	11.88	12.00	1.028	99.40%	1.01	0.07	0.163	0.169	-
		11	2462	11.75	12.00	1.059	99.40%	1.01	-	-	-	-

14.2. Body SAR

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (3Tx slots)	Front	128	824.2	28.65	29.00	1.084	-	-	-	-
		190	836.6	28.55	29.00	1.109	-	-	-	-
		251	848.8	28.71	29.00	1.069	-0.04	0.738	0.789	-
	Rear	128	824.2	28.65	29.00	1.084	-0.06	0.729	0.790	-
		190	836.6	28.55	29.00	1.109	0.17	0.774	0.859	-
		251	848.8	28.71	29.00	1.069	0.08	0.820	0.877	7

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (2Tx slots)	Front	512	1850.2	28.48	29.00	1.127	-	-	-	-
		661	1880	28.71	29.00	1.069	-	-	-	-
		810	1909.8	28.84	29.00	1.038	-0.11	0.319	0.331	-
	Rear	512	1850.2	28.48	29.00	1.127	-	-	-	-
		661	1880	28.71	29.00	1.069	-	-	-	-
		810	1909.8	28.84	29.00	1.038	-0.06	0.406	0.421	8

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2Kbps	Front	9262	1852.4	22.99	23.00	1.002	-0.10	0.383	0.384	-
		9400	1880	22.92	23.00	1.019	-	-	-	-
		9538	1907.6	22.66	23.00	1.081	-	-	-	-
	Rear	9262	1852.4	22.99	23.00	1.002	-0.19	0.435	0.436	9
		9400	1880	22.92	23.00	1.019	-	-	-	-
		9538	1907.6	22.66	23.00	1.081	-	-	-	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2Kbps	Front	1312	1712.4	23.28	23.50	1.052	-	-	-	-
		1413	1732.6	23.20	23.50	1.072	-	-	-	-
		1513	1752.6	23.41	23.50	1.021	0.16	0.575	0.587	-
	Rear	1312	1712.4	23.28	23.50	1.052	-	-	-	-
		1413	1732.6	23.20	23.50	1.072	-	-	-	-
		1513	1752.6	23.41	23.50	1.021	-0.13	0.613	0.626	10

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2Kbps	Front	4132	826.4	23.15	23.50	1.084	-	-	-	-
		4183	836.6	23.24	23.50	1.062	-0.05	0.301	0.320	-
		4233	846.6	23.19	23.50	1.074	-	-	-	-
	Rear	4132	826.4	23.15	23.50	1.084	-	-	-	-
		4183	836.6	23.24	23.50	1.062	0.01	0.335	0.356	11
		4233	846.6	23.19	23.50	1.074	-	-	-	-

Wi-Fi 2.4G												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11b	Front	1	2412	11.72	12.00	1.067	99.40%	1.01	-	-	-	-
		6	2437	11.88	12.00	1.028	99.40%	1.01	-0.13	0.021	0.022	-
		11	2462	11.75	12.00	1.059	99.40%	1.01	-	-	-	-
	Rear	1	2412	11.72	12.00	1.067	99.40%	1.01	-	-	-	-
		6	2437	11.88	12.00	1.028	99.40%	1.01	-0.19	0.049	0.051	12
		11	2462	11.75	12.00	1.059	99.40%	1.01	-	-	-	-

14.3. Hotspot SAR

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (3Tx slots)	Front	128	824.2	28.65	29.00	1.084	-	-	-	-
		190	836.6	28.55	29.00	1.109	-	-	-	-
		251	848.8	28.71	29.00	1.069	-0.04	0.738	0.789	-
	Rear	128	824.2	28.65	29.00	1.084	-0.06	0.729	0.790	-
		190	836.6	28.55	29.00	1.109	0.17	0.774	0.859	-
		251	848.8	28.71	29.00	1.069	0.08	0.820	0.877	7
	Left	251	848.8	28.71	29.00	1.069	-0.07	0.698	0.746	-
	Right	251	848.8	28.71	29.00	1.069	0.15	0.314	0.336	-
	Top	251	848.8	28.71	29.00	1.069	-	-	-	-
	Bottom	251	848.8	28.71	29.00	1.069	-0.01	0.624	0.667	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
GPRS (2Tx slots)	Front	512	1850.2	28.48	29.00	1.127	-	-	-	-
		661	1880	28.71	29.00	1.069	-	-	-	-
		810	1909.8	28.84	29.00	1.038	-0.11	0.319	0.331	-
	Rear	512	1850.2	28.48	29.00	1.127	-	-	-	-
		661	1880	28.71	29.00	1.069	-	-	-	-
		810	1909.8	28.84	29.00	1.038	-0.06	0.406	0.421	8
	Left	810	1909.8	28.84	29.00	1.038	0.07	0.296	0.307	-
	Right	810	1909.8	28.84	29.00	1.038	0.13	0.247	0.256	-
	Top	810	1909.8	28.84	29.00	1.038	-	-	-	-
	Bottom	810	1909.8	28.84	29.00	1.038	-0.04	0.382	0.396	-

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Front	9262	1852.4	22.99	23.00	1.002	-0.10	0.383	0.384	-
		9400	1880	22.92	23.00	1.019	-	-	-	-
		9538	1907.6	22.66	23.00	1.081	-	-	-	-
	Rear	9262	1852.4	22.99	23.00	1.002	-0.19	0.435	0.436	9
		9400	1880	22.92	23.00	1.019	-	-	-	-
		9538	1907.6	22.66	23.00	1.081	-	-	-	-
	Left	9262	1852.4	22.99	23.00	1.002	0.06	0.355	0.356	-
	Right	9262	1852.4	22.99	23.00	1.002	-0.04	0.307	0.308	-
	Top	9262	1852.4	22.99	23.00	1.002	-	-	-	-
	Bottom	9262	1852.4	22.99	23.00	1.002	-0.11	0.400	0.401	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Front	1312	1712.4	23.28	23.50	1.052	-	-	-	-
		1413	1732.6	23.20	23.50	1.072	-	-	-	-
		1513	1752.6	23.41	23.50	1.021	0.16	0.575	0.587	-
	Rear	1312	1712.4	23.28	23.50	1.052	-	-	-	-
		1413	1732.6	23.20	23.50	1.072	-	-	-	-
		1513	1752.6	23.41	23.50	1.021	-0.13	0.613	0.626	10
	Left	1513	1752.6	23.41	23.50	1.021	0.01	0.370	0.378	-
	Right	1513	1752.6	23.41	23.50	1.021	-0.12	0.288	0.294	-
	Top	1513	1752.6	23.41	23.50	1.021	-	-	-	-
	Bottom	1513	1752.6	23.41	23.50	1.021	-0.09	0.582	0.594	-

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune up limit (dBm)	Tune up scaling factor	Power Drift(dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz							
RMC 12.2K	Front	4132	826.4	23.15	23.50	1.084	-	-	-	-
		4183	836.6	23.24	23.50	1.062	-0.05	0.301	0.320	-
		4233	846.6	23.19	23.50	1.074	-	-	-	-
	Rear	4132	826.4	23.15	23.50	1.084	-	-	-	-
		4183	836.6	23.24	23.50	1.062	0.01	0.335	0.356	11
		4233	846.6	23.19	23.50	1.074	-	-	-	-
	Left	4183	836.6	23.24	23.50	1.062	-0.19	0.306	0.325	-
	Right	4183	836.6	23.24	23.50	1.062	0.11	0.183	0.194	-
	Top	4183	836.6	23.24	23.50	1.062	-	-	-	-
	Bottom	4183	836.6	23.24	23.50	1.062	0.06	0.247	0.262	-

Wi-Fi 2.4G												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift (dB)	Measured SAR(1g) (W/kg)	Report SAR(1g) (W/kg)	Plot No.
		CH	MHz									
802.11b	Front	1	2412	11.72	12.00	1.067	99.40%	1.01	-	-	-	-
		6	2437	11.88	12.00	1.028	99.40%	1.01	-0.13	0.021	0.022	-
		11	2462	11.75	12.00	1.059	99.40%	1.01	-	-	-	-
	Rear	1	2412	11.72	12.00	1.067	99.40%	1.01	-	-	-	-
		6	2437	11.88	12.00	1.028	99.40%	1.01	-0.19	0.049	0.051	12
		11	2462	11.75	12.00	1.059	99.40%	1.01	-	-	-	-
	Left	6	2437.0	11.88	12.00	1.028	99.40%	1.01	0.08	0.038	0.039	-
	Right	6	2437.0	11.88	12.00	1.028	99.40%	1.01	-	-	-	-
	Top	6	2437.0	11.88	12.00	1.028	99.40%	1.01	-0.11	0.044	0.046	-
	Bottom	6	2437.0	11.88	12.00	1.028	99.40%	1.01	-	-	-	-

SAR Test Data Plots to the Appendix A.

15. SAR Measurement Variability

In accordance with published RF Exposure KDB 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

1) Repeated measurement is not required when the original highest measured SAR is <0.8 or 2 W/kg (1-g or 10-g respectively); steps 2) through 4) do not apply.

2) When the original highest measured SAR is ≥ 0.8 or 2 W/kg (1-g or 10-g respectively), repeat that measurement once.

3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 or 3.6 W/kg (~ 10% from the 1-g or 10-g respective SAR limit).

4) Perform a third repeated measurement only if the original, first, or second repeated measurement is ≥ 1.5 or 3.75 W/kg (1-g or 10-g respectively) and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

Band	Test Position	Frequency		Highest Measured SAR (W/kg)	First Repeated		Second Repeated	
		CH	MHz		Measured SAR(W/kg)	Largest to Smallest SAR Ratio	Measured SAR(W/kg)	Largest to Smallest SAR Ratio
GSM850 GPRS (3Tx slots)	Rear	251	848.8	0.820	0.811	1.011	N/A	N/A

16. Simultaneous Transmission analysis

No.	Simultaneous Transmission Configurations	Head	Body-worn	Hotspot	Note
1	GSM(voice) + Bluetooth (data)	Yes	Yes		
2	GSM(voice) + WLAN (data)	Yes	Yes		
3	WCDMA(voice) + Bluetooth (data)	Yes	Yes		
4	WCDMA(voice) + WLAN (data)	Yes	Yes		
5	GPRS (data) + Bluetooth (data)	Yes	Yes	NA	
6	GPRS (data) + WLAN (data)	Yes	Yes	Yes	
7	WCDMA (data) + Bluetooth (data)	Yes	Yes	NA	
8	WCDMA (data) + WLAN (data)	Yes	Yes	Yes	

General note:

1. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
2. EUT will choose either GSM or WCDMA according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. The reported SAR summation is calculated based on the same configuration and test position
4. For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 based on the formula below
   a) [(max. Power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] * [√f(GHz)/x]W/kg for test separation distances ≦50mm; whetn x=7.5 for 1-g SAR, and x=18.75 for 10-g SAR.
   b) When the minimum separation distance is <5mm, the distance is used 5mm to determine SAR test exclusion
   c) 0.4 W/kg for 1-g SAR and 1.0W/kg for 10-g SAR, when the test separation distances is >50mm.

Bluetooth Max power	Exposure position	Head	Body-worn
	Test separation	0mm	10mm
6.50dBm	Estimated SAR (W/kg)	0.185	0.092

16.1. Head

PCE+ WLAN DTS					
WWAN Band		Exposure Position	Standalone SAR (W/kg)		Σ 1-g SAR
			PCE	WLAN DTS	(W/kg)
GSM	GSM850	Left Cheek	0.676	0.065	0.740
		Left Tilted	0.446	0.049	0.494
		Right Cheek	0.710	0.190	**0.900**
		Right Tilted	0.477	0.169	0.645
	PCS1900	Left Cheek	0.359	0.065	0.424
		Left Tilted	0.273	0.049	0.321
		Right Cheek	0.204	0.190	0.395
		Right Tilted	0.151	0.169	0.320
WCDMA	Band II	Left Cheek	0.402	0.065	0.466
		Left Tilted	0.351	0.049	0.399
		Right Cheek	0.191	0.190	0.382
		Right Tilted	0.156	0.169	0.325
	Band IV	Left Cheek	0.409	0.065	**0.474**
		Left Tilted	0.343	0.049	0.392
		Right Cheek	0.187	0.190	0.377
		Right Tilted	0.150	0.169	0.319
	Band V	Left Cheek	0.276	0.065	0.341
		Left Tilted	0.252	0.049	0.300
		Right Cheek	0.288	0.190	0.478
		Right Tilted	0.266	0.169	0.435

PCE+ BT					
WWAN Band		Exposure Position	Standalone SAR (W/kg)		Σ 1-g SAR
			WWAN	BT	(W/kg)
GSM	GSM850	Left Cheek	0.676	0.185	0.860
		Left Tilted	0.446	0.185	0.630
		Right Cheek	0.710	0.185	**0.894**
		Right Tilted	0.477	0.185	0.661
	PCS1900	Left Cheek	0.359	0.185	0.544
		Left Tilted	0.273	0.185	0.457
		Right Cheek	0.204	0.185	0.389
		Right Tilted	0.151	0.185	0.336
WCDMA	Band II	Left Cheek	0.402	0.185	0.587
		Left Tilted	0.351	0.185	0.535
		Right Cheek	0.191	0.185	0.376
		Right Tilted	0.156	0.185	0.341
	Band IV	Left Cheek	0.409	0.185	**0.594**
		Left Tilted	0.343	0.185	0.528
		Right Cheek	0.187	0.185	0.371
		Right Tilted	0.150	0.185	0.335
	Band V	Left Cheek	0.276	0.185	0.461
		Left Tilted	0.252	0.185	0.436
		Right Cheek	0.288	0.185	0.472
		Right Tilted	0.266	0.185	0.451

16.2. Body-worn

PCE + WLAN DTS					
WWAN Band		Exposure Position	Standalone SAR (W/kg)		Σ 1-g SAR
			PCE	WLAN DTS	(W/kg)
GSM	GSM850	Front	0.789	0.022	0.811
		Rear	0.877	0.051	**0.927**
	PCS1900	Front	0.331	0.022	0.353
		Rear	0.421	0.051	0.472
WCDMA	Band II	Front	0.384	0.022	0.406
		Rear	0.436	0.051	0.487
	Band IV	Front	0.587	0.022	0.609
		Rear	0.626	0.051	**0.677**
	Band V	Front	0.320	0.022	0.341
		Rear	0.356	0.051	0.406

PCE + Bluetooth					
WWAN Band		Exposure Position	Standalone SAR (W/kg)		Σ 1-g SAR
			PCE	Bluetooth	(W/kg)
GSM	GSM850	Front	0.789	0.092	0.881
		Rear	0.877	0.092	**0.969**
	PCS1900	Front	0.331	0.092	0.423
		Rear	0.421	0.092	0.514
WCDMA	Band II	Front	0.384	0.092	0.476
		Rear	0.436	0.092	0.528
	Band IV	Front	0.587	0.092	0.679
		Rear	0.626	0.092	**0.718**
	Band V	Front	0.320	0.092	0.412
		Rear	0.356	0.092	0.448

16.3. Hotspot

PCE + WLAN DTS					
WWAN Band		Exposure Position	Standalone SAR (W/kg)		Σ 1-g SAR
			PCE	WLAN DTS	(W/kg)
GSM	GSM850	Front	0.789	0.022	0.811
		Rear	0.877	0.051	**0.927**
		Left side	0.746	0.039	0.786
		Right side	0.336	0.000	0.336
		Top side	0.000	0.046	0.046
		Bottom side	0.667	0.000	0.667
	PCS1900	Front	0.331	0.022	0.353
		Rear	0.421	0.051	0.472
		Left side	0.307	0.039	0.346
		Right side	0.256	0.000	0.256
		Top side	0.000	0.046	0.046
		Bottom side	0.396	0.000	0.396
WCDMA	Band II	Front	0.384	0.022	0.406
		Rear	0.436	0.051	0.487
		Left side	0.356	0.039	0.395
		Right side	0.308	0.000	0.308
		Top side	0.000	0.046	0.046
		Bottom side	0.401	0.000	0.401
	Band IV	Front	0.587	0.022	0.609
		Rear	0.626	0.051	**0.677**
		Left side	0.378	0.039	0.417
		Right side	0.294	0.000	0.294
		Top side	0.000	0.046	0.046
		Bottom side	0.594	0.000	0.594
	Band V	Front	0.320	0.022	0.341
		Rear	0.356	0.051	0.406
		Left side	0.325	0.039	0.364
		Right side	0.194	0.000	0.194
		Top side	0.000	0.046	0.046
		Bottom side	0.262	0.000	0.262

17. TestSetup Photos

	
Liquid depth in the Head phantom	Liquid depth in the Body phantom
	
Left Head Touch	Right Head Touch
	
Left Head Tilt (15°)	Right Head Tilt (15°)

Body-worn Front (10mm)

Body-worn Rear(10mm)

Front (10mm)

Rear (10mm)

Left Side (10mm)

Right Side (10mm)

	
Top Side (10mm)	Bottom Side (10mm)

18. External and Internal Photos of the EUT

Please reference to the report No.: CHTEW20110158

---------End of Report----------