



FCC RADIO TEST REPORT

FCC ID:ZUBWIFI-601

Product : WiFi video door phone

Trade Name : N/A

Model Name : WiFi-601

Serial Model : N/A

Prepared for

Shenzhen Zhuohao Intelligent Electronic Development Co., Ltd.
5F, Building B2, Shangrong Industry Zone, Baolong 5th Road,
Longgang District, Shenzhen, China

Prepared by

Shenzhen Asia Test Technology Co.,Ltd.
1/6, Bldg.8, Zhonghua Industrial City, Chuangye Rd., Nanshan District,
Shenzhen, Guangdong, China



TEST RESULT CERTIFICATION

Applicant's name Shenzhen Zhuohao Intelligent Electronic Development Co., Ltd.

Address 5F, Building B2, Shangrong Industry Zone, Baolong 5th Road,
Longgang District, Shenzhen, China

Manufacture's Name... Shenzhen Zhuohao Intelligent Electronic Development Co., Ltd.

Address 5F, Building B2, Shangrong Industry Zone, Baolong 5th Road,
Longgang District, Shenzhen, China

Product description

Product name WiFi video door phone

Model and/or type WiFi-601
reference

Serial Model N/A

Standards FCC Part15.247

Test procedure ANSI C63.4-2003

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Oct 31, 2014 ~ Nov 12, 2014

Date of Issue..... Nov 12, 2014

Test Result..... **Pass**

Testing Engineer :

Eric Wang

(Eric Wang)

Technical Manager :

Jerry You

(Jerry You)

Authorized Signatory :

Jack Yu

(Jack Yu)

**Table of Contents**

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
3 . EMC EMISSION TEST	12
3.1 CONDUCTED EMISSION MEASUREMENT	12
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	12
3.1.2 TEST PROCEDURE	13
3.1.3 DEVIATION FROM TEST STANDARD	13
3.1.4 TEST SETUP	13
3.1.5 EUT OPERATING CONDITIONS	13
3.1.6 TEST RESULTS	14
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 RADIATED EMISSION LIMITS	16
3.2.2 TEST PROCEDURE	17
3.2.3 DEVIATION FROM TEST STANDARD	17
3.2.4 TEST SETUP	18
3.2.5 EUT OPERATING CONDITIONS	19
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	20
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	21
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	22
4 . POWER SPECTRAL DENSITY TEST	41
4.1 APPLIED PROCEDURES / LIMIT	41
4.1.1 TEST PROCEDURE	41
4.1.2 DEVIATION FROM STANDARD	41
4.1.3 TEST SETUP	41
4.1.4 EUT OPERATION CONDITIONS	41
4.1.5 TEST RESULTS	42
5 . BANDWIDTH TEST	49



Table of Contents	Page
5.1 APPLIED PROCEDURES / LIMIT	49
5.1.1 TEST PROCEDURE	49
5.1.2 EUT OPERATION CONDITIONS	49
5.1.3 TEST RESULTS	50
6 . PEAK OUTPUT POWER TEST	58
6.1 APPLIED PROCEDURES / LIMIT	58
6.1.1 TEST PROCEDURE	58
6.1.2 DEVIATION FROM STANDARD	58
6.1.3 TEST SETUP	58
6.1.4 EUT OPERATION CONDITIONS	58
6.1.5 TEST RESULTS	59
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	60
7.1 DEVIATION FROM STANDARD	60
7.2 TEST SETUP	60
7.3 EUT OPERATION CONDITIONS	60
7.4 TEST RESULTS	61
8 . ANTENNA REQUIREMENT	65
8.1 STANDARD REQUIREMENT	65
8.2 EUT ANTENNA	65
9 . EUT TEST PHOTO	66
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

Shenzhen STONE Testing Technology Co.,Ltd.

Add.: F/6, Bldg.12, Zhongxing Industrial City, Chuangye Rd., Nanshan District Shenzhen P.R. China

FCC Registration No.: 323508; IC Registration No.: 11043A

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	WiFi video door phone
Model Name	WiFi-601
Serial Model	N/A
Model Difference	N/A
WIFI	
Supported type:	802.11b/802.11g/802.11n(H20)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20): OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz
Channel number:	802.11b/802.11g/802.11n(H20): 11
Channel separation:	5MHz
Antenna type:	Internal Antenna
Antenna gain:	2.5 dBi
Ratings	DC 12V by adapter
Adapter	Model:DLL05122000 Input:100-240V,50/60Hz, 0.55A Output:12V , 2A
Battery	N/A
Connecting I/O Port(s)	Please refer to the User's Manual

Channel List for 802.11b/g/n(H20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power	11b/DSSS	1 Mbps	1/6/11
Power Spectral Density	11g/OFDM	6 Mbps	1/6/11
6dB Bandwidth	11n(20MHz)/OFDM	6.5Mbps	1/6/11
Spurious RF conducted emission	11b/DSSS	1 Mbps	1/11
Radiated Emission 9kHz~1GHz&	11g/OFDM	6 Mbps	1/11
Radiated Emission 1GHz~10th Harmonic	11n(H20)/OFDM	6.5Mbps	1/11
Band Edge			



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n(H20) CH1/ CH6/ CH11
Mode 4	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 3	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n(H20) CH1/ CH6/ CH11


Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT has been tested under typical operating condition. The Applicant provides command to control the EUT for staying in continuous transmitting and receiving mode for testing
- (3) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.




2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test



**2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	WiFi video door phone	N/A	WiFi-601	N/A	EUT
E-2	Adapter	N/A	N/A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014.07.06	2015.07.05	1 year
12	Power Meter	Anristu	ML2495A	1145054	2014.08.16	2015.08.15	1 year
13	Power Sensor	Anristu	MA2411B	1126096	2014.08.16	2015.08.15	1 year
14	Cable 30-1000MHz	R&S	ATT-R01	201309R047	2014.06.08	2015.06.07	1 year
15	Cable 1-26.5GHz	R&S	ATT-R02	201309R048	2014.06.08	2015.06.07	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2014.08.24	2015.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year
7	Attenuation	MCE	24-10-34	BN9258	2014.06.08	2015.06.07	1 year
8	Cable 0.009-30MHz	R&S	ATT-C01	201309C006	2014.06.08	2015.06.07	1 year



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.This operating condition was tested and used to collect the included data.




3.1.6 TEST RESULTS

EUT :	WiFi video door phone	Model Name. :	WiFi-601
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 12V by adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.202	46.05	10.44	56.49	63.52	-7.03	QP
0.202	36.72	10.44	47.16	53.52	-6.36	AVG
4.5899	32.22	10.64	42.86	56	-13.14	QP
4.6577	30.63	10.64	41.27	46	-4.73	AVG
16.1056	34.39	10.71	45.1	60	-14.9	QP
16.3059	26.66	10.71	37.37	50	-12.63	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.






EUT :	WiFi video door phone	Model Name. :	WiFi-601
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 12V by adapter AC 120V/60Hz	Test Mode :	Mode 4

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.2006	43.52	10.43	53.95	63.58	-9.63	QP
0.2028	37.51	10.43	47.94	53.49	-5.55	AVG
1.4697	33	10.45	43.45	46	-2.55	AVG
1.806	34.33	10.44	44.77	56	-11.23	QP
15.6379	35.87	10.73	46.6	50	-3.4	AVG
15.9739	43.24	10.73	53.97	60	-6.03	QP

Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

EUT:	WiFi video door phone	Model Name. :	WiFi-601
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V
Test Mode :	TX		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Below 1G							
35.63	23.66	8.87	32.53	40	-7.47	QP	Vertical
200.76	24.85	9.66	34.51	43.5	-8.99	QP	Vertical
278.88	27.48	11.38	38.86	46	-7.14	QP	Vertical
356.73	26.53	15.86	42.39	46	-3.61	QP	Vertical
400.58	19.68	21.44	41.12	46	-4.88	QP	Vertical
528.93	18.85	22.65	41.5	46	-4.5	QP	Vertical
48.84	22.757	12.85	35.607	40	-4.393	QP	Horizontal
98.88	25.28	8.85	34.13	40	-5.87	QP	Horizontal
184.97	26.77	12.47	39.24	43.5	-4.26	QP	Horizontal
266.85	25.27	14.85	40.12	46	-5.88	QP	Horizontal
367.88	26.88	15.77	42.65	46	-3.35	QP	Horizontal
598.75	18.94	22.73	41.67	46	-4.33	QP	Horizontal



**3.2.8 TEST RESULTS (ABOVE 1000 MHZ)**


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detect or Type	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2412 MHz)-Above 1G							
4824.25	52.66	10.14	62.8	74	-11.2	Pk	Vertical
4824.25	40.15	10.22	50.37	54	-3.63	Av	Vertical
7236.26	51.53	12.15	63.68	74	-10.32	Pk	Vertical
7236.26	39.36	12.21	51.57	54	-2.43	Av	Vertical
4824.29	49.82	10.26	60.08	74	-13.92	Pk	Horizontal
4824.29	35.52	10.37	45.89	54	-8.11	Av	Horizontal
7236.48	45.43	12.28	57.71	74	-16.29	Pk	Horizontal
7236.48	32.31	12.54	44.85	54	-9.15	Av	Horizontal
Mid Channel (2437 MHz)-Above 1G							
4874.21	54.47	10.26	64.73	74	-9.27	Pk	Vertical
4874.21	41.52	10.26	51.78	54	-2.22	Av	Vertical
7311.35	52.63	11.53	64.16	74	-9.84	Pk	Vertical
7311.35	38.66	11.53	50.19	54	-3.81	Av	Vertical
4874.46	50.64	11.28	61.92	74	-12.08	Pk	Horizontal
4874.46	37.52	11.28	48.8	54	-5.2	Av	Horizontal
7311.37	49.44	12.63	62.07	74	-11.93	Pk	Horizontal
7311.37	31.44	12.63	44.07	54	-9.93	Av	Horizontal
High Channel (2462 MHz)- Above 1G							
4924.44	53.16	10.39	63.55	74	-10.45	Pk	Vertical
4924.44	40.77	10.39	51.16	54	-2.84	Av	Vertical
7386.15	51.61	12.68	64.29	74	-9.71	Pk	Vertical
7386.15	38.39	12.68	51.07	54	-2.93	Av	Vertical
4924.26	48.62	10.39	59.01	74	-14.99	Pk	Horizontal
4924.26	36.73	10.39	47.12	54	-6.88	Av	Horizontal
7386.41	45.19	12.68	57.87	74	-16.13	Pk	Horizontal
7386.41	33.36	12.68	46.04	54	-7.96	Av	Horizontal

Note:"802.11b" mode is the worst mode.





Conducted Spurious Emissions at Antenna Port:
802.11b Low Channel










802.11b Middle Channel








802.11b High Channel








Ref 21 dBm * Att 30 dB SWT 1 s * RBW 100 kHz Marker 1 [T1]
* VBW 300 kHz -43.11 dBm
21.3976000000 GHz







802.11g Low Channel










802.11g Middle Channel










802.11g High Channel








802.11n(H20) Low Channel







* RBW 100 kHz Marker 1 [T1]
* VBW 300 kHz -43.15 dBm
SWT 1 s 22.185000000 GHz






802.11n(H20) Middle Channel







* RBW 100 kHz Marker 1 [T1]
* VBW 300 kHz -42.74 dBm
SWT 1 s 20.386000000 GHz




802.11n(H2O) High Channel





* RBW 100 kHz Marker 1 [T1]
* VBW 300 kHz -42.69 dBm
SWT 1 s 23.374006000 GHz





4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



4.1.5 TEST RESULTS


EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 12V
Test Mode :	TX b Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-13.21	8	PASS
2437 MHz	-13.08	8	PASS
2462 MHz	-13.21	8	PASS






TX CH06




TX CH11






EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 12V
Test Mode :	TX g Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-15.35	8	PASS
2437 MHz	-16.39	8	PASS
2462 MHz	-15.41	8	PASS






TX CH06




TX CH11







EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	DC 12V
Test Mode :	TX n(H20) Mode /CH01, CH06, CH11		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-16.47	8	PASS
2437 MHz	-16.83	8	PASS
2462 MHz	-16.16	8	PASS









5. BANDWIDTH TEST


5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



5.1.2 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




5.1.3 TEST RESULTS

EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX b Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	10.02	500	Pass
Middle	2437	10.00	500	Pass
High	2462	10.15	500	Pass










EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX g Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	15.67	500	Pass
Middle	2437	15.79	500	Pass
High	2462	16.56	500	Pass












EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX n(H20) Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.62	500	Pass
Middle	2437	17.68	500	Pass
High	2462	17.66	500	Pass









6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**6.1.5 TEST RESULTS**

EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 12V
Test Mode :	TX b/g/n(H20) Mode		

TX 802.11b Mode				
Test Channel	Frequency	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(AV)	LIMIT
	(MHz)	(dBm)	(dBm)	(dBm)
CH01	2412	13.26	9.41	30
CH06	2437	13.74	9.65	30
CH11	2462	13.66	9.54	30
TX 802.11g Mode				
CH01	2412	12.65	8.57	30
CH06	2437	12.73	8.66	30
CH11	2462	12.72	8.64	30
TX 802.11n(H20) Mode				
CH01	2412	11.17	7.36	30
CH06	2437	11.63	7.58	30
CH11	2462	11.61	7.61	30

Note: the highest AVG powers for:

802.11b: 1Mbps

802.11g: 6Mbps

802.11n(H20): 6.5Mbps



7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

7.1 DEVIATION FROM STANDARD

No deviation.

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



7.4 TEST RESULTS


EUT :	WiFi video door phone	Model Name :	WiFi-601
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	DC 12V

Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
802.11b			
Left-band	43.35	20	Pass
Right-band	42.16	20	Pass
802.11g			
Left-band	38.75	20	Pass
Right-band	42.27	20	Pass
802.11n(H20)			
Left-band	40.27	20	Pass
Right-band	41.17	20	Pass


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detect or Type	Comment
802.11b							
2390	47.84	9.86	57.7	74	-16.3	Pk	Vertical
2390	38.93	9.86	48.79	54	-5.21	Av	Vertical
2483.5	49.18	10.14	59.32	74	-14.68	Pk	Vertical
2483.5	38.03	10.14	48.17	54	-5.83	Av	Vertical
802.11g							
2390	49.17	9.86	59.03	74	-14.97	Pk	Vertical
2390	39.06	9.86	48.92	54	-5.08	Av	Vertical
2483.5	47.82	10.14	57.96	74	-16.04	Pk	Vertical
2483.5	36.93	10.14	47.07	54	-6.93	Av	Vertical
802.11n(H20)							
2390	48.94	9.86	58.8	74	-15.2	Pk	Vertical
2390	38.38	9.86	48.24	54	-5.76	Av	Vertical
2483.5	48.94	10.14	59.08	74	-14.92	Pk	Vertical
2483.5	36.04	10.14	46.18	54	-7.82	Av	Vertical



802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side






802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side






802.11n(H20): Band Edge, Left Side



802.11g(H20): Band Edge, Right Side





8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is PIFA Antenna. It comply with the standard requirement.



9. EUT TEST PHOTO

Radiated Measurement Photos





Conducted Measurement Photos

