


Test report No: 4392400.56

TEST REPORT

Radio Spectrum Matters (RF)

Identification of item tested	Prostate massager & Rabbit Vibrator
Trademark	Vector for 10000-02 Nova 2 for 10000-05
Model and /or type reference	10000-02, 10000-05
FCC ID	ZUE1000I
Features	Charging input: 5 Vdc Li-ion Battery: 3.7 Vdc
Applicant's name / address	WOW Tech Canada Ltd. 1545 Carling Avenue, Suite 401, Ottawa Ontario, K1Z 8P9, Canada
Test method requested, standard	FCC CFR Title 47 Part15 Subpart C Section 15.247; KDB558074 D01v05r02;
Verdict Summary	COMPLIANCE
Tested by (name & signature)	Jazz Liang 
Approved by (name & signature)	Tim Yan 
Date of issue	2022-08-26
Report template No	TRF_EMC 2017-06- FCC_Part15C_247

INDEX

	page
General conditions.....	4
Uncertainty.....	4
Environmental conditions.....	4
Possible test case verdicts	4
Definition of symbols used in this test report	5
Abbreviations	5
Document History	5
Remarks and Comments	5
1 General Information.....	6
1.1 General Description of the Item(s)	6
1.2 Test data	8
1.3 The environment(s) in which the EUT is intended to be used	8
1.4 Channel List	8
2 Description of Test Setup	9
2.1 Operating mode(s) used for tests.....	9
2.2 Support / Auxiliary equipment / unit / software for the EUT	9
2.3 Test Configuration / Block diagram used for tests	9
2.4 Measurement procedure	9
3 Verdict summary section	10
3.1 Standards	10
3.2 Deviation(s) from the Standard(s) / Test Specification(s)	10
3.3 Overview of results.....	10
4 Transmitter Test Results	11
4.1 AC Power Line Conducted Emission	11
4.2 Emissions in non-restricted frequency bands	16
4.3 Emissions in restricted frequency bands	31
4.4 Band Edge.....	42
4.5 Duty cycle.....	47
4.6 DTS Bandwidth	50
4.7 Fundamental emission output power	55
4.8 Power Density	59
5 Identification of the Equipment Under Test	62
Annex 1 – Measurement Uncertainty	63
Annex 2 - Used Equipment.....	64



Annex 3 - Test Photos65

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. This report will not be used for social proof function in China market.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in EN 55016-4-2 (CISPR 16-4-2), EN/IEC 61000-4 series or a product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not tested	N/T

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

☒ Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.			
☐ Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.			
Decimal separator used in this report	☒	Comma (,)	☐ Point (.)

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
Tx	: Transmitter
Rx	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report nr.	Date	Description
4392400.56	2022-08-26	First release.

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Description of the item	Prostate massager & Rabbit Vibrator
Trademark.....	Vector for 10000-02 Nova 2 for 10000-05
Model / Type number	10000-02, 10000-05
FCC ID	ZUE1000I
Hardware	10000-02, 10000-05
Software	510-00076, 510-00075
Firmware	N/A
Ratings.....	Charging input: 5 Vdc Li-ion Battery: 3.7 Vdc
Manufacturer	WOW Tech Europe GmbH. Hermann-Blankenstein-Str. 5, 10249 Berlin, Germany.
Factory	Seaco Technology(Dongguan)Co., Ltd. No.6, the 3rd Jin He Industrial Zone, Zhang Mutou Town Dongguan City Guangdong China

the characteristics of wireless module for BLE mode:

Operating frequency range(s).....	2402 MHz – 2480 MHz
Type of Modulation	GFSK
Maximum RF output power(conducted)	-2.9 dBm
EIRP(equivalent isotropically radiated power)	2.1 dBm
Antenna type.....	Integral Antenna
Operating Temperature Range.....	-40 – 85 °C
BT version.....	Bluetooth 5.1BLE
Antenna gain.....	5 dBi
Adaptive/ non-adaptive equipment	Adaptive

Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☒	DC: 5V					
	☒	Battery: 3.7V					
Mounting position.....	☐	Table top equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☒	Hand-held equipment					
	☐	Other:					

Intended use of the Equipment Under Test (EUT)

The apparatus as supplied for the test is Prostate massager & Rabbit Vibrator intended for residential use and the product contains electronic control circuitry, it is powered by battery.

According to customer description, models 10000-02, 10000-05 are identical except for the trade mark and the appearance of size. Both products share the same PCB, slightly different in PCBA, but there will be no change in radio parameters occurred.

After technical reviewed, model 10000-02 was chosen for full test, model 10000-05 was chosen to repeat Conducted Emission and radiated emissions for compliance verification.

Copy of marking plate:

No provide.

1.2 Test data

Test Location	DEKRA Testing and Certification (Shanghai) Ltd. Guangzhou Branch Block 5, No.3, Qiyun Road, Huangpu District, Guangzhou, Guangdong, China FCC Designation Number: CN1324;
Date of receipt of test item	2022-07-13
Date (s) of performance of tests	2022-07-13 to 2022-08-26
Test sample	Normal sample: 10000-02(Lab no.4392400-1), 10000-05(Lab no.4392400-4) RF conducted sample: 10000-02(Lab no.4392400-2), 10000-05(Lab no.4392400-5) RF radiated sample: 10000-02(Lab no.4392400-3), 10000-05(Lab no.4392400-6)

1.3 The environment(s) in which the EUT is intended to be used

The equipment under test (EUT) is intended to be used in the following environment(s):

☒	Residential (domestic) environment.
☒	Commercial and light-industrial environment.
☐	Industrial environment.

1.4 Channel List

The radio module (Bluetooth) operating channels are:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	-	-
13	2428	27	2456	-	-

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for methos	
		Conducted	Radiated
1	Transmitting at 1 Mbit/s,	☒	☒
2	Transmitting at 2 Mbit/s,	☒	☒
3	Charging mode	☒	☒
4			
<u>Supplemental information:</u> ---			

2.2 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Manufacturer	Supplied by
Laptop	Latitude 5488	DELL	DEKRA
Adaptor	ADC4501TM	XIAOMI	DEKRA
EMI_TEST(soft ware)	V2.0	-	Client
TELINK BDT(Burning and Debugging tool)	-	-	Client
<u>Supplemental information:</u> ---			

2.3 Test Configuration / Block diagram used for tests

Refer to Annex 3.

2.4 Measurement procedure

The EUT was controlled by a serial PCB(TELINK BDT) which provided by manufacturer which connected to laptop through the com port. After connected, run the software “EMI_TESTV2.0” supplied by manufacturer to control the EUT work in required test mode as below table.

RF Mode	Set_channel(MHz)	Set_power in software
BLE_1M	2402	11.3
	2440	11.3
	2480	11.3
BLE_2M	2402	11.3
	2440	11.3
	2480	11.3

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
FCC CFR Title 47 Part 15 Subpart C Section 15.247	2022	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
KDB 558074 D01 v05r02	2019	Guidance for performing compliance measurements on Digital Transmission System (DTS) operating under section 15.247
ANSI C63.10	2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

3.3 Overview of results

FCC measurement			
Requirement – Test case	Basic standard(s)	Verdict	Remark
AC Power Line Conducted Emission	FCC 15.207	PASS	---
Emissions in non-restricted frequency bands	FCC 15.247(d), FCC 15.209	PASS	---
Emissions in restricted frequency bands	FCC 15.247(b)(3)	PASS	---
Duty cycle	ANSI C63.10:2013	PASS	---
Band Edge	FCC 15.247(d)	PASS	---
Fundamental emission output power	FCC 15.247(d), FCC 15.209	PASS	---
DTS Bandwidth	FCC 15.247(a)(2)	PASS	---
Power Spectral Density	FCC 15.247(e)	PASS	---
Antenna Requirement	FCC 15.203	PASS	---
Supplementary information: ---			

The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to calculate the uncertainty associated with the measurement result.

4 TRANSMITTER TEST RESULTS


4.1 AC Power Line Conducted Emission	VERDICT: PASS
---	----------------------

Limits

FCC Part 15 Subpart C Paragraph 15.207				
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾	Limit: AV [dB(μV) ¹⁾	IF BW	Detector(s)
0,15 - 0,50	66 - 56 ²⁾	56 - 46 ²⁾	9 KHz	QP, AV
0,50 - 5,0	56	46	9 KHz	QP, AV
5,0 - 30	60	50	9 KHz	QP, AV

¹⁾ At the transition frequency, the lower limit applies.
²⁾ The limit decreases linearly with the logarithm of the frequency.

Test Configuration




Performed measurements

Port under test			Terminal							
☒	AC mains input power		☒	N	☒	L1	☐	L2	☐	L3
☐	DC input power		☐	Positive (+)			☐	Negative (-)		
Test method applied			☒	Artificial mains network						
			☐	Voltage probe						
Test setup			☒	Table top	☐	Artificial hand applied				
			☐	Floor standing	☐	Other:				
			Refer to the Annex 2 for test setup photo(s).							
Operating mode(s) used			Mode 3							
Envirment condition (temperature; humidity)			23,0 °C; 45,0 %							
Remark			---							

Model	10000-02
Operation Mode (worst case)	Mode 3
Test voltage	120 Vac, 60 Hz

Results

Live




EDIT PEAK LIST (Final Measurement Results)			
Trace1:	FCCBQ		
Trace2:	FCCBA		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	566 kHz	29.02	-26.97
2 Average	578 kHz	17.99	-28.00
1 Quasi Peak	1.002 MHz	25.75	-30.24
1 Quasi Peak	11.43 MHz	28.87	-31.12
2 Average	13.814 MHz	18.50	-31.49
2 Average	1.982 MHz	12.84	-33.15

Remarks:

- 1) Level (final measurement) = received value + transducer (Lisn+cable)
- 2) Delta = Level – Limit

No other significant emissions were measured at the frequency range of interest employing both the QP and AV detectors.

Neutral



EDIT PEAK LIST (Final Measurement Results)			
Trace1:	FCCBQ		
Trace2:	FCCBA		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB
2 Average	578 kHz	24.41	-21.59
1 Quasi Peak	578 kHz	33.25	-22.74
2 Average	978 kHz	18.85	-27.14
1 Quasi Peak	11.646 MHz	32.09	-27.90
1 Quasi Peak	990 kHz	26.86	-29.13
2 Average	11.822 MHz	20.25	-29.74

Remarks:


- 1) Level (final measurement) = received value + transducer (Lisn+cable)
- 2) Delta = Level – Limit

No other significant emissions were measured at the frequency range of interest employing both the QP and AV detectors.

Model	10000-05
Operation Mode (worst case)	Mode 3
Test voltage	120 Vac, 60 Hz

Results

Live




EDIT PEAK LIST (Final Measurement Results)			
Trace1:	FCCBQ		
Trace2:	FCCBA		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	562 kHz	30.14	-25.85
2 Average	570 kHz	19.02	-26.97
1 Quasi Peak	1.046 MHz	27.94	-28.05
1 Quasi Peak	11.05 MHz	31.39	-28.60
2 Average	13.902 MHz	19.58	-30.41
2 Average	1.03 MHz	15.26	-30.73

Remarks:

- Level (final measurement) = received value + transducer (Lisn+cable)
- Delta = Level – Limit

No other significant emissions were measured at the frequency range of interest employing both the QP and AV detectors.

Neutral



EDIT PEAK LIST (Final Measurement Results)			
Trace1:	FCCBQ		
Trace2:	FCCBA		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
2 Average	562 kHz	25.93	-20.06
1 Quasi Peak	566 kHz	35.92	-20.07
1 Quasi Peak	11.33 MHz	35.07	-24.92
2 Average	1.034 MHz	18.90	-27.09
1 Quasi Peak	1.018 MHz	28.26	-27.73
2 Average	11.31 MHz	21.34	-28.65

Remarks:


- 3) Level (final measurement) = received value + transducer (Lisn+cable)
- 4) Delta = Level – Limit

No other significant emissions were measured at the frequency range of interest employing both the QP and AV detectors.

4.2	Emissions in non-restricted frequency bands	VERDICT: PASS
------------	--	----------------------

Emissions Limit 15.209(a)			
Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Field strength (dB $\mu\text{V/m}$)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)
<p>Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).</p> <p>Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).</p>			

Test Configuration



Performed measurements


Port under test	Enclosure port	
Test method applied	☐	Conducted measurement
	☒	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1-3	
Remark	<p>1)The test frequency range, 9kHz~30MHz, 18GHz~26GHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report.</p> <p>2)The EUT are tested in three orientations. The record is the worst orientation which refer to the Annex 3 for test setup photo(s).</p>	

Results of 30 – 1000 MHz

Model	10000-02
Operation Mode	Mode 1 @2402MHz (worst case)
Test voltage	3.7 Vdc

Results

Horizontal




Freq (MHz)	Reading (dBuV)	C.F (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin=limit-result (dB)
58.20	9.79	15.37	25.16	40.00	14.84
95.76	10.68	12.10	22.78	43.50	20.72
131.76	11.41	9.30	20.71	43.50	22.79
215.27	10.83	11.60	22.43	43.50	21.07
300.37	10.38	13.80	24.18	46.00	21.82
508.26	9.73	18.13	27.86	46.00	18.14

Remarks:

- 1) C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
- 2) Result = Reading + C.F (Correction Factor)

No other significant emissions were measured at the frequency range of interest employing the QP detectors.

Vertical



Freq (MHz)	Reading (dBuV)	C.F (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin=limit-result (dB)
57.80	8.94	15.45	24.39	40.00	15.61
107.89	11.45	12.70	24.15	43.50	19.35
195.82	10.53	11.70	22.23	43.50	21.27
341.98	9.52	15.28	24.80	46.00	21.20
510.04	8.89	18.20	27.09	46.00	18.91
677.58	10.13	20.40	30.53	46.00	15.47

Remarks:

- 1) C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
- 2) Result = Reading + C.F (Correction Factor)


No other significant emissions were measured at the frequency range of interest employing the QP detectors.

Results of 1 – 18 GHz

Model	10000-02
Operation Mode (worst case)	Mode 1 @2402 MHz
Test voltage	3.7 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Model	10000-02
Operation Mode (worst case)	Mode 1 @2480 MHz
Test voltage	3.7 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)


No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Results of 30 – 1000 MHz

Model	10000-05
Operation Mode	Mode 1 @2402MHz (worst case)
Test voltage	3.7 Vdc

Results

Horizontal




Freq (MHz)	Reading (dBuV)	C.F (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin=limit-result (dB)
58.82	9.26	14.98	24.24	40.00	15.76
109.80	8.65	12.45	21.10	43.50	22.40
333.69	13.00	14.85	27.85	46.00	18.15
356.68	16.03	15.45	31.48	46.00	14.52
513.63	10.81	18.27	29.08	46.00	16.92
682.35	10.97	20.30	31.27	46.00	14.73

Remarks:

- 3) C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
- 4) Result = Reading + C.F (Correction Factor)

No other significant emissions were measured at the frequency range of interest employing the QP detectors.

Vertical



Freq (MHz)	Reading (dBuV)	C.F (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin=limit-result (dB)
59.86	10.44	14.33	24.77	40.00	15.23
92.79	11.40	11.70	23.10	43.50	20.40
137.42	12.49	8.77	21.26	43.50	22.24
209.31	12.01	11.39	23.40	43.50	20.10
331.36	9.93	14.75	24.68	46.00	21.32
492.47	11.10	17.90	29.00	46.00	17.00

Remarks:

- 3) C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
- 4) Result = Reading + C.F (Correction Factor)


No other significant emissions were measured at the frequency range of interest employing the QP detectors.

Results of 1 – 18 GHz

Model	10000-05
Operation Mode (worst case)	Mode 1 @2402 MHz
Test voltage	3.7 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Model	10000-05
Operation Mode (worst case)	Mode 1 @2480 MHz
Test voltage	3.7 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

4.3	Emissions in restricted frequency bands	VERDICT: PASS
------------	--	----------------------

Restricted Bands of operation of FCC			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			
Restricted Bands of operation for IC			
0.090 - 0.110	13.36 - 13.41	960 - 1427	9.0 - 9.2
0.495 - 0.505	16.42 - 16.423	1435 - 1626.5	9.3 - 9.5
2.1735 - 2.1905	16.69475 - 16.69525	1645.5 - 1646.5	10.6 - 12.7
3.020 - 3.026	16.80425 - 16.80475	1660 - 1710	13.25 - 13.4
4.125 - 4.128	25.5 - 25.67	1718.8 - 1722.2	14.47 - 14.5
4.17725 - 4.17775	37.5 - 38.25	2200 - 2300	15.35 - 16.2
4.20725 - 4.20775	73 - 74.6	2310 - 2390	17.7 - 21.4
5.677 - 5.683	74.8 - 75.2	2483.5 - 2500	22.01 - 23.12
6.215 - 6.218	108 - 138	2655 - 2900	23.6 - 24.0
6.26775 - 6.26825	149.9 - 150.05	3260 - 3267	31.2 - 31.8
6.31175 - 6.31225	156.52475 - 156.52525	3332 - 3339	36.43 - 36.5
8.291 - 8.294	156.7 - 156.9	3345.8 - 3358	Above 38.6
8.362 - 8.366	162.0125 - 167.17	3500 - 4400	
8.37625 - 8.38675	167.72 - 173.2	4500 - 5150	
8.41425 - 8.41475	240 - 285	5350 - 5460	
12.29 - 12.293	322 - 335.4	7250 - 7750	
12.51975 - 12.52025	399.9 - 410	8025 - 8500	
12.57675 - 12.57725	608 - 614	--	


Restricted Band Emissions Limit

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

Test Configuration




Performed measurements

Port under test	Enclosure port	
Test method applied	☐	Conducted measurement
	☒	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1-2	
Remark	---	

Model	10000-02
Operation Mode (worst case)	Mode 2 @2402 MHz
Test voltage	3.7 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Model	10000-02
Operation Mode (worst case)	Mode 2 @2480 MHz
Test voltage	3.7 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Model	10000-05
Operation Mode	Mode 2 @2402 MHz
Test voltage	3.7 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Model	10000-05
Operation Mode	Mode 2 @2480 MHz
Test voltage	3.7 Vdc

Results


Horizontal



Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

Vertical




Remarks: Y-Value = received value + Correction Factor (Antenna factor + Cable loss - Preamp gain)

No other significant emissions were measured at the frequency range of interest employing the PK and AV detectors.

4.4 Band Edge	VERDICT: PASS
----------------------	----------------------

Standard	FCC Part 15 Subpart C Paragraph 15.247(d)
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)
Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD by level in 100 kHz (i.e., 30 dBc). Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD by level in 100 kHz (i.e., 20 dBc).	


Test Configuration



Performed measurements

Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	---	

Results of mode 1 @2402 MHz



Inband Peak


Frequency (MHz)	Level (dBm)
2402.0000	-0.3

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2349.675000	-56.9	36.6	-20.3	PASS
2344.325000	-57.1	36.8	-20.3	PASS
2344.275000	-57.1	36.8	-20.3	PASS
2349.725000	-57.3	37.1	-20.3	PASS
2344.825000	-57.5	37.2	-20.3	PASS
2383.975000	-57.5	37.2	-20.3	PASS
2355.725000	-57.5	37.3	-20.3	PASS
2392.275000	-57.6	37.3	-20.3	PASS
2317.425000	-57.6	37.3	-20.3	PASS
2383.925000	-57.6	37.4	-20.3	PASS
2388.525000	-57.7	37.4	-20.3	PASS
2374.675000	-57.7	37.5	-20.3	PASS
2392.325000	-57.7	37.5	-20.3	PASS
2352.575000	-57.7	37.5	-20.3	PASS
2379.825000	-57.8	37.5	-20.3	PASS

Results of mode 1 @2480 MHz

Band Edge




Inband Peak

Frequency (MHz)	Level (dBm)
2480.0000	0.1

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2487.575000	-57.2	37.3	-19.9	PASS
2487.625000	-57.4	37.5	-19.9	PASS
2483.725000	-58.3	38.3	-19.9	PASS
2483.625000	-58.5	38.5	-19.9	PASS
2489.975000	-58.5	38.6	-19.9	PASS
2489.875000	-58.6	38.7	-19.9	PASS
2487.525000	-58.6	38.7	-19.9	PASS
2483.675000	-58.8	38.9	-19.9	PASS
2489.925000	-58.8	38.9	-19.9	PASS
2486.175000	-58.9	38.9	-19.9	PASS
2486.125000	-58.9	39.0	-19.9	PASS
2485.375000	-59.0	39.0	-19.9	PASS
2485.675000	-59.0	39.1	-19.9	PASS
2483.575000	-59.0	39.1	-19.9	PASS
2483.875000	-59.0	39.1	-19.9	PASS

Results of mode 2 @2402 MHz




Inband Peak

Frequency (MHz)	Level (dBm)
2402.0000	-1.0

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2399.975000	-31.7	10.7	-21.0	PASS
2399.925000	-31.8	10.8	-21.0	PASS
2399.875000	-33.1	12.1	-21.0	PASS
2399.825000	-34.1	13.1	-21.0	PASS
2399.775000	-35.9	14.9	-21.0	PASS
2399.725000	-37.8	16.8	-21.0	PASS
2399.675000	-39.8	18.8	-21.0	PASS
2399.625000	-42.1	21.2	-21.0	PASS
2399.575000	-44.3	23.3	-21.0	PASS
2399.525000	-47.0	26.1	-21.0	PASS
2399.475000	-47.6	26.6	-21.0	PASS
2399.425000	-48.1	27.1	-21.0	PASS
2399.375000	-50.6	29.6	-21.0	PASS
2399.325000	-52.7	31.7	-21.0	PASS
2399.125000	-53.2	32.2	-21.0	PASS

Results of mode 2 @2480 MHz



Inband Peak


Frequency (MHz)	Level (dBm)
2480.0000	-1.4

Measurements

Frequency (MHz)	Level (dBm)	Margin (dB)	Limit (dBm)	Result
2498.625000	-58.0	36.6	-21.4	PASS
2498.675000	-58.2	36.8	-21.4	PASS
2487.225000	-59.0	37.6	-21.4	PASS
2487.275000	-59.1	37.7	-21.4	PASS
2496.425000	-59.1	37.7	-21.4	PASS
2495.525000	-59.1	37.7	-21.4	PASS
2496.475000	-59.2	37.8	-21.4	PASS
2495.575000	-59.2	37.8	-21.4	PASS
2483.775000	-59.3	37.9	-21.4	PASS
2483.675000	-59.3	37.9	-21.4	PASS
2483.725000	-59.3	37.9	-21.4	PASS
2483.575000	-59.3	37.9	-21.4	PASS
2488.325000	-59.3	37.9	-21.4	PASS
2495.675000	-59.3	37.9	-21.4	PASS
2483.875000	-59.4	38.0	-21.4	PASS

4.5	Duty cycle	VERDICT: PASS
------------	-------------------	----------------------

Test Configuration



Performed measurements


Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	---	


Results

Test Mode	Tx On (ms)	Tx On + Tx Off (ms)	Duty Cycle
Mode 1	---	---	100%

Note 1: T means the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control Level for the tested mode of operation.

Note 2: According to KDB 558074, when test for Radiated Emission Band Edge and Radiated Emission, for average detector set: VBW $\geq 1/T$ will be used.






4.6	DTS Bandwidth	VERDICT: PASS
------------	----------------------	----------------------

Standard	FCC Part 15 Subpart C Paragraph 15.247 (a)(2)
Systems using digital modulation techniques operate in the 2400-2483.5 MHz .The minimum 6 dB bandwidth shall be at by least 500 kHz	

Test Configuration



Performed measurements


Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	---	

Results

Mode	CH.	Test Freq. (MHz)	6dB Occupied Bandwidth (kHz)	Limit (kHz)	Result
1	1	2402	712,87	>500	Pass
	39	2480	732,48	>500	Pass


6dB Occupied Bandwidth
Mode 1 / CH1 (2402MHz)

6 dB Bandwidth



Mode 1 / CH39 (2480MHz)


6 dB Bandwidth



Mode	CH.	Test Freq. (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
1	1	2402	1.02	Within frequency range	Pass
	39	2480	1.03	Within frequency range	Pass


99% Occupied Bandwidth
Mode 1 / CH1 (2402 MHz)

99 % Bandwidth



Mode 1 / CH39 (2480 MHz)

99 % Bandwidth




Mode	CH.	Test Freq. (MHz)	6dB Occupied Bandwidth (kHz)	Limit (kHz)	Result
2	1	2402	1545	>500	Pass
	39	2480	1505	>500	Pass

6dB Occupied Bandwidth


Mode 2 / CH1 (2402MHz)

6 dB Bandwidth



Mode 2 / CH39 (2480MHz)

6 dB Bandwidth




Mode	CH.	Test Freq. (MHz)	99% Occupied Bandwidth (MHz)	Limit	Result
2	1	2402	2,04	Within frequency range	Pass
	39	2480	2,05	Within frequency range	Pass

99% Occupied Bandwidth


Mode 2 / CH1 (2402 MHz)

99 % Bandwidth



Mode 2 / CH39 (2480 MHz)


99 % Bandwidth



4.7	Fundamental emission output power	VERDICT: PASS
------------	--	----------------------

Standard		FCC Part 15 Subpart C Paragraph 15.247 (b)(3)
☒	GTX < 6dBi	Pout≤30dBm
☐	GTX > 6dBi	
☐	Non-Fix point-point	Pout≤30-(GTX -6)
☐	Fix point-point	Pout≤30-[(GTX-6)]/3
☐	Point-to-multipoint	Pout≤30-(GTX-6)
☐	Overlap Beams	Pout≤30-[(GTX-6)]/3
☐	Aggregate power transmitted simultaneously on all beams	Pout≤30-[(GTX-6)]/3
☐	single LE directional beam	Pout≤30-[(GTX-6)]/3+8dB
Note 1 : GTX directional gain of transmitting antennas. Note 2 : Pout is maximum peak conducted output power .		

Test Configuration



Performed measurements


Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	---	

Results

Mode	Channel	Test Frequency (MHz)	Power Output (dBm)	Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)	Result
Mode 1	1	2402	-3,2	≤30	1,8	≤36	Pass
	17	2440	-4,2	≤30	0,8	≤36	Pass
	39	2480	-4,9	≤30	0,1	≤36	Pass
Mode 2	1	2402	-2,9	≤30	2,1	≤36	Pass
	17	2440	-3,1	≤30	1,9	≤36	Pass
	39	2480	-4,9	≤30	0,1	≤36	Pass


Data of Mode 1

Peak Power




— Connector 1 X Peak Connector 1

Peak Power



— Connector 1 X Peak Connector 1


Peak Power



Connector 1 × Peak Connector 1


Data of Mode 2

Peak Power




Connector 1 × Peak Connector 1

Peak Power



Connector 1 X Peak Connector 1

Peak Power




Connector 1 X Peak Connector 1

4.8 Power Density	VERDICT: PASS
--------------------------	----------------------

Standard	FCC Part 15 Subpart C Paragraph 15.247 (b)(3)
Power Spectral Density $\leq 8 \text{ dBm/3kHz}$	

Test Configuration



Performed measurements


Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	---	

Results

Mode	Channel	Test Frequency (MHz)	Power Output (dBm)	Limit (dBm/3kHz)	Result
Mode 1	1	2402	-8,45	≤ 8	Pass
	17	2440	-9,83	≤ 8	Pass
	39	2480	-9,92	≤ 8	Pass
Mode 2	1	2402	-8,86	≤ 8	Pass
	17	2440	-10,05	≤ 8	Pass
	39	2480	-10,28	≤ 8	Pass


Data of Mode 1

Peak Power Spectral Density




— Limit — Sum Level ◆ PSD

Peak Power Spectral Density



— Limit — Sum Level ◆ PSD


Peak Power Spectral Density




— Limit — Sum Level ◆ PSD

Data of Mode 2


Peak Power Spectral Density



Peak Power Spectral Density



Peak Power Spectral Density



5 IDENTIFICATION OF THE EQUIPMENT UNDER TEST

The photographs show the tested device.

Refer to documents External photo and Internal photo.

ANNEX 1 – MEASUREMENT UNCERTAINTY

Test Item	Uncertainty
Occupied Channel Bandwidth	$\pm 0,7\%$
RF Output power, conducted	$\pm 0,6\text{dB}$
Power Spectral Density, Conducted	$\pm 0,6\text{dB}$
Unwanted Emissions, Conducted	$\pm 0.7\text{dB}$
Spurious (30-1000MHz)	$\pm 4,4\text{dB}$
Spurious (1-12,75GHz)	$\pm 4,4\text{dB}$

ANNEX 2 - USED EQUIPMENT

Continuous disturbances conducted (150 kHz to 30 MHz)

Item	Instrumentation	Manufacturer	Model No.	Serial No.	DEKRA No.	Cal. Due date
1	EMI Receiver	R&S	ESCI	101206	G/L858	2023/07/21
2	LISN	R&S	ENV216	101336	G/L859	2023/07/21
3	Shielding Room	Changzhou Feite	/	/	G/L861	2023/06/17

Emissions in non-restricted frequency bands/ Emissions in restricted frequency bands

Item	Instrumentation	Manufacturer	Model No.	Serial No.	DEKRA No.	Cal. Due date
1	EMI receiver	R&S	ESCI	101205	G/L857	2023/07/21
2	Antenna (30MHz-3GHz)	SCHWARZBECK	VULB9163	506	G/L864	2022/10/26
3	Chamber	ETS	/	/	G/L856	2024/06/10
4	Antenna (1GHz-18GHz)	R&S	HF907	102306	G/L1236	2023/02/23
5	Horn antenna preamplifier	Schwarzbeek	SCU-18	102234	G/L1236-1	2023/02/21
6	Spectrum analyzer	R&S	FSV	SN101012	G/L1235	2023/01/17
7	HF antenna (18 – 26.5 GHz)	ETS	3160-09	00164643	G/L1237	2023/01/16
8	High frequency antenna preamplifier (18 – 26.5 GHz)	Schwarzbeck	SCU-26	1879064	G/L1237-1	2023/01/10
9	Broadband horn antenna (15 – 40 GHz)	Schwarzbeck	BBHA9170	00908	GZ1901	2023/05/06
10	High frequency antenna preamplifier (18 – 26.5 GHz)	Schwarzbeck	SCU-26	1879064	G/L1237-1	2023/01/10
11	Annular magnetic field antenna	TESEQ	HLA6121	540045	GZ1905	2023/05/12

Duty cycle/Band Edge/Fundamental emission output power/DTS Bandwidth/Power Spectral Density

Item	Instrumentation	Manufacturer	Model	Serial no.	DEKRA No.	Cal Due date
1	Spectrum analyzer	R&S	FSV	SN101012	G/L1235	2023/01/17
2	Chamber	ETS	/	/	G/L856	2024/06/10
3	OSP	R&S	OSP 150	101907	GZ1894	2023/04/27

ANNEX 3 - TEST PHOTOS

Refer to document Test setup.

--- END ---