



MPE Test Report

Report No.: BAGZ-ESH-P21060930B-7

FCC ID: ZUERWVG3A

Product: We-Vibe Remote

Model: R-WVG3A

Received Date: Jun.09, 2021

Test Date: Jun.10 to Aug.02, 2021

Issued Date: Aug.06, 2021

Applicant: WOW Tech Canada Ltd.

Address: 1545 Carling Avenue, Suit 401, Ottawa, Ontario, Canada, K1Z 8P9

Manufacturer: WOW Tech Canada Ltd.

Address: 1545 Carling Avenue, Suit 401, Ottawa, Ontario, Canada, K1Z 8P9

Issued By: BUREAU VERITAS ADT (Shanghai) Corporation

Lab Address: No. 829, Xinzhuang Road, Shanghai, P.R.China (201612)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 General Information	5
2.1 General Description of EUT	5
3 RF Exposure	6
3.1 Classification	6
3.2 SAR Test Exclusion Thresholds	6



Release Control Record

Issue No.	Description	Date Issued
BAGZ-ESH-P21060930B-7	Original release	Aug.06, 2021

1 Certificate of Conformity

Product: We-Vibe Remote

Brand: 

Model: R-WVG3A

Applicant: WOW Tech Canada Ltd.

Test Date: Jun.10 to Aug.02, 2021

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1-1992

The above equipment has been tested by **BUREAU VERITAS ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



, Date: Aug.06, 2021

Yuan ZHANG

Project Engineer

Approved by :



, Date: Aug.06, 2021

Daniel SUN

EMC Lab Manager



2 General Information

2.1 General Description of EUT

Product	We-Vibe Remote
Brand	
Test Model	R-WVG3A
Power Rating	Powered by battery(3V CR2032)
Modulation Type	GFSK
Modulation Technology	Bluetooth Low Energy 5.0
Operating Frequency	2402 ~ 2480MHz
Number of Channel	40
Antenna Type	Wire Antenna
Antenna Gain	2dBi

Note:

1. For more details, please refer to the User's manual of the EUT.

3 RF Exposure

The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:

a) [Threshold at 50 mm in step1) + (test separation distance - 50 mm) · ($f(\text{MHz})/150$)] mW, at 100MHz to 1500 MHz

b) [Threshold at 50 mm in step1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.

a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for test separation distances > 50 mm and < 200 mm.

b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances ≤ 50 mm.

c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

3.1 Classification

The antenna of this product, under normal use condition, is at less than 20cm from the body of the user. So the device is classified as **Portable Device**.

3.2 SAR Test Exclusion Thresholds

The tuned conducted Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT-LE(GFSK)	2402-2480	4.5	± 1	3.5	5.5

The measured conducted Power

Mode	Frequency (MHz)	Max. Conducted Output power(dBm)
BT-LE(GFSK)	2402	5.09

SAR Test Exclusion Thresholds

Frequency Band (MHz)	Max. Conducted output power(dBm)	Distance (mm)	Result of Eq. 1	Limit for 1-g SAR	Limit for 10-g Extremity SAR	Verdict
2402-2480	5.5	5	1.0998	3	7.5	Exempt from SAR

Conclusion:

Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.

--- END ---