

FCC RF EXPOSURE REPORT

FCC ID: ZVAPS000017

Project No. : 1503C087
Equipment : SHOUT Dual Mode WiFi/Bluetooth Smart Speaker
Model : IS0101
Applicant : TCL Technoly Electronics(Huizhou) Co.,Ltd.
Address : Section 37, Zhongkai High-tech Development Zone, Huizhou City, Guang Dong Province, China, 516006

According: : FCC Guidelines for Human Exposure IEEE C95.1

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Internal	N/A	3.97

TEST RESULTS

EUT :	SHOUT Dual Mode WiFi/Bluetooth Smart Speaker	Model Name :	IS0101
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode _1Mbps		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.97	2.4946	1.01	1.2618	0.00062654	1	Complies
3.97	2.4946	1.3	1.3490	0.00066981	1	Complies
3.97	2.4946	0.94	1.2417	0.00061652	1	Complies

EUT :	SHOUT Dual Mode WiFi/Bluetooth Smart Speaker	Model Name :	IS0101
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode _3Mbps		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3.97	2.4946	0.76	1.1912	0.00059149	1	Complies
3.97	2.4946	0.79	1.1995	0.00059559	1	Complies
3.97	2.4946	0.61	1.1508	0.00057141	1	Complies

Note: the calculated distance is 20 cm.