

RF EXPOSURE REPORT

FOR

Applicant	:	Tonly Technology Co., Ltd.
Address	:	Section37, Zhongkai High-tech Development Zone, Huizhou City, Guangdong Province, P.R.China
Equipment under Test	:	Subwoofer
Model No.	:	SV210M-0808 Subwoofer
Trade Mark	:	VIZIO
FCC ID	:	ZVASB000028
Manufacturer	:	Tonly Technology Co., Ltd.
Address	:	Section37, Zhongkai High-tech Development Zone, Huizhou City, Guangdong Province, P.R.China

Issued By: Guangdong Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory.....	5
2.	RF Exposure Evaluation	6
2.1.	Requirement.....	6
2.2.	Calculation method	6
2.3.	Estimation result.....	7

Test Report Declare

Applicant	:	Tonly Technology Co., Ltd.
Address	:	Section37, Zhongkai High-tech Development Zone, Huizhou City, Guangdong Province, P.R.China
Equipment under Test	:	Subwoofer
Model No.	:	SV210M-0808 Subwoofer
Trade mark	:	VIZIO
Manufacturer	:	Tonly Technology Co., Ltd.
Address	:	Section37, Zhongkai High-tech Development Zone, Huizhou City, Guangdong Province, P.R.China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above.

The assessed results are contained in this report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-RE23070308-2E06		
Date of Receipt:	Aug. 29, 2023	Date of Test:	Aug. 29, 2023 ~ Oct. 11, 2023

Prepared By:

Johnny Wang

Johnny Wang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Oct. 11, 2023	

1. General Information

1.1. Description of equipment

EUT Name	: Subwoofer
Model Number	: SV210M-0808 Subwoofer
EUT Function Description	: Please reference user manual of this device
Power supply	: Input: 100V-240V ~ 50Hz-60Hz
Radio Specification	: 2.4GHz SRD
Operation Frequency	: 2404 MHz - 2476 MHz
Modulation	: GFSK
Data Rate	: 2 Mbps
Antenna	: FPC antenna, maximum PK gain: 3.33 dBi
Sample Number	: S23070308-04 for conductive, S23070308-05 for radiation

1.2. Assess laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d= 0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

Mode	PK Output power (dBm)	Output power (mW)	tune up power (dBm)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
SRD	-2.57	0.55	-1.57	3.33	2.15	0.00030	1

Note: The estimation distance is 20 cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

END OF REPORT