



Test Report No.: FM180801N043

RF EXPOSURE REPORT

Applicant	ZhongShan Longde S&T Techonology CO.,LTD
Address	No.33 Middle industry Aveneue,XiaoLan Town,ZhongShan City,GuangDong Province, China.

Manufacturer or Supplier	ZhongShan Longde S&T Techonology CO.,LTD
Address	No.33 Middle industry Aveneue,XiaoLan Town,ZhongShan City,GuangDong Province, China.
Product	Vanity Mirror Round LED 9inch with Speaker Bluetooth
Brand Name	Sharper Image
Model	1005839
Additional Model & Model Difference	1006922, 1006306, 1007078
Date of tests	Aug. 01, 2018 ~ Sep. 04, 2018

☒ **FCC Part 2 (Section 2.1091)**☒ **KDB 447498 D01**☒ **IEEE C95.1****CONCLUSION: The submitted sample was found to COMPLY with the test requirement**Tested by Breeze Jiang
Project Engineer / EMC DepartmentApproved by Glyn He
Supervisor/ EMC Department

Date: Sep. 11, 2018

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan BranchNo. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, ChinaTel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FM180801N043

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM180801N043	Original release	Sep. 11, 2018



Test Report No.: FM180801N043

1. CERTIFICATION

FCC ID:	ZWPBSM09A
PRODUCT:	Vanity Mirror Round LED 9inch with Speaker Bluetooth
BRAND NAME:	N/A
MODEL NO.:	1005839
ADDITIONAL NO.:	1006922, 1006306, 1007078
APPLICANT:	ZhongShan Longde S&T Techonology CO.,LTD
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

Note: Additional models 1006922, 1006306, 1007078 are identical with the test model 1005839 except the model number for marketing purpose.



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	3	PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	-5	+/-2	-7	-3
8DPSK	2402-2480	-6	+/-2	-8	-4

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
GFSK	2441	-4.97
8DPSK	2441	-5.79

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2402-2480	-3	3	20	0.000199	1.0

--- END ---