

TEST REPORT

Product Name : BLE Module
Brand Mark : Shinwa
Model No. : BT-MP62-SH1
Extension Model : BT-MP62-1
FCC ID : ZWYP6222
Report Number : BLA-EMC-202209-A2103
Date of Sample Receipt : 2022/9/7
Date of Test : 2022/9/7 to 2022/9/20
Date of Issue : 2022/9/20
Test Standard : KDB447498D04 General RF Exposure
Guidance v01
Test Result : Pass

Prepared for:

Dongguan Hele Electronics Co.,Ltd
No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province
China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: *charlie*

Review by: *Sueels*

Approved by: *Blue Zhong*

Date:

2022/9/20



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/9/20	Original

BlueAsia

TABLE OF CONTENTS

1 GENERAL INFORMATION	4
2 GENERAL DESCRIPTION OF E.U.T.....	4
3 LABORATORY LOCATION	5
4 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
<i>Standard Requirement</i>	6
<i>Limits</i>	6

1 GENERAL INFORMATION

Applicant	Shinwa industries(China)ltd.
Address	No.26,HuiFeng West 2 Road,Zhongkai High-Tech Park,Huizhou,Guangdong,China
Manufacturer	Shinwa industries(China)ltd.
Address	No.26,HuiFeng West 2 Road,Zhongkai High-Tech Park,Huizhou,Guangdong,China
Factory	Shinwa industries(China)ltd.
Address	No.26,HuiFeng West 2 Road,Zhongkai High-Tech Park,Huizhou,Guangdong,China
Product Name	BLE Module
Test Model No.	BT-MP62-SH1
Extension Model	BT-MP62-1
Remark	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

2 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.0
Software Version	N/A
Operation Frequency:	2402MHz-2480MHz
Data Rata	1Mbps; 2Mbps
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	-0.62dBi(Provided by the customer)

3 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

4 RF EXPOSURE COMPLIANCE REQUIREMENT

4.1 RF EXPOSURE COMPLIANCE REQUIREMENT

Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$EIRP = p_t \times g_t = (EXd)^{2/30}$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10((dBuV/m)/20)/106$

d = measurement distance in meters (m)---3m

$$S_{opt} = (EXd)^{2/30} \times g_t$$

$$\text{Ant gain} = -0.62 \text{ dBi}$$

$$\text{Max Output power} = -2.351 \text{ dBm @ } 2402 \text{ MHz}$$

$$\text{ERP} = -2.351 \text{ dBm} + -0.62 \text{ dBi} - 2.15 = -5.121 \text{ dBm}$$

So

Output power is worse case

$$10^{-0.2351} = 0.582 \text{ mW} < 2.715 \text{ mW} \quad (\text{evaluate at } 5 \text{ mm distance})$$

Comply with SAR exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.