



Test Report No.: FS160420N003

RF EXPOSURE REPORT

Applicant	Zhongshan Leetac Electronics Co.,Ltd
Address	No.15 Danli Road, South District, Zhongshan, Guangdong, China.

Manufacturer or Supplier	Zhongshan Leetac Electronics Co.,Ltd
Address	No.15 Danli Road, South District, Zhongshan, Guangdong, China.
Product	Wooden Music Center with Bluetooth
Brand Name	Innovative Technology, Victrola, Leetac
Model	E-69E5
Additional Model & Model Difference	VTA-600B, VTA-abcd, ITVS-600B, ITVS-abcd, E-69Ex ("a, b, c, d" can be replaced by digit "0-9" , letter "A-Z"; "x" can be replaced by digit "6-9" , letter "C-Z")
Date of tests	Apr. 20, 2016 ~ May 19, 2016

☒ FCC Part 2 (Section 2.1091)☒ KDB 447498 D01☒ IEEE C95.1**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Chris Chen Manager / EMC Department
	 Date: May 19, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FS160420N003

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS160420N003	Original release	May 19, 2016

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: FS160420N003

1. CERTIFICATION

FCC ID:	ZXNLEETACE69E5
PRODUCT:	Wooden Music Center with Bluetooth
BRAND NAME:	Innovative Technology, Victrola, Leetac
MODEL NO.:	E-69E5
ADDITIONAL NO.:	VTA-600B, VTA-abcd, ITVS-600B, ITVS-abcd, E-69Ex ("a, b, c, d" can be replaced by digit "0-9" , letter "A-Z"; "x" can be replaced by digit "6-9" , letter "C-Z")
TEST SAMPLE:	Engineering Sample
APPLICANT:	Zhongshan Leetac Electronics Co.,Ltd
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	0	Integral PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2402-2480MHz	0.9727	0	20	0.0002	1.0

--- END ---