

Prüfbericht-Nr.: Test report no.:	CN20VTHZ 001	Auftrags-Nr.: Order no.:	168287287	Seite 1 von 25 Page 1 of 25
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2020-09-21	
Auftraggeber: Client:	Guangdong Leetac Electronics Technology Co., Ltd. No.15 Danli Road, South District, Zhongshan City, Guangdong province China			
Prüfgegenstand: Test item:	Bluetooth Stereo Turntable			
Bezeichnung / Typ-Nr.: Identification / Type no.:	NS-BTST21 (Trademark: INSIGNIA)			
Auftrags-Inhalt: Order content:	FCC approval			
Prüfgrundlage: Test specification:	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 CFR47 FCC Part 2.1091			
Wareneingangsdatum: Date of sample receipt:	2020-10-22	Please refer to photo documents		
Prüfmuster-Nr.: Test sample no.:	A002932518-001			
Prüfzeitraum: Testing period:	2020-11-19 – 2020-12-09			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd. Testing Center			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	genehmigt von: authorized by:			
Datum: Date: 2020-12-28	Ausstellungsdatum: Issue date: 2020-12-28			
Stellung / Position	Senior Project Engineer	Stellung / Position	Department Manager	
Sonstiges / Other: FCC ID: ZNXLEETACEE500				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:		Prüfmuster vollständig und unbeschädigt Test item complete and undamaged:		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specifications(s) F(ail) = failed a.m. test specifications(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.4 RADIATED SPURIOUS EMISSION

RESULT: Pass

5.1.5 20dB BANDWIDTH

RESULT: Pass

5.1.6 CARRIER FREQUENCY SEPARATION

RESULT: Pass

5.1.7 NUMBER OF HOPPING FREQUENCY

RESULT: Pass

5.1.8 TIME OF OCCUPANCY

RESULT: Pass

5.1.9 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

6.1.1 ELECTROMAGNETIC FIELDS

RESULT: Pass

Contents

1	GENERAL REMARKS	4
1.1	COMPLEMENTARY MATERIALS	4
2	TEST SITES	4
2.1	TEST FACILITIES	4
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	5
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	11
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	11
3.5	SUBMITTED DOCUMENTS.....	11
4	TEST SET-UP AND OPERATION MODES	12
4.1	PRINCIPLE OF CONFIGURATION SELECTION	12
4.2	TEST OPERATION AND TEST SOFTWARE	12
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	12
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	12
4.5	TEST SETUP DIAGRAM	13
5	TEST RESULTS	15
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	15
5.1.1	<i>Antenna Requirement</i>	<i>15</i>
5.1.2	<i>Maximum Peak Conducted Output Power</i>	<i>16</i>
5.1.3	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>17</i>
5.1.4	<i>Radiated Spurious Emission</i>	<i>18</i>
5.1.5	<i>20dB Bandwidth</i>	<i>19</i>
5.1.6	<i>Carrier Frequency Separation</i>	<i>20</i>
5.1.7	<i>Number of Hopping Frequency</i>	<i>21</i>
5.1.8	<i>Time of Occupancy</i>	<i>22</i>
5.1.9	<i>Conducted Emission on AC Mains.....</i>	<i>23</i>
6	SAFETY HUMAN EXPOSURE	24
6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE	24
6.1.1	<i>Electromagnetic Fields</i>	<i>24</i>
7	PHOTOGRAPHS OF THE TEST SET-UP	25
8	LIST OF TABLES.....	25

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of Conducted Testing

Appendix C: Test Results of Radiated Testing & AC Mains Conducted Emission

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, People's Republic of China

FCC Registration No.: 694916

IC Registration No.: 25069

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

TÜV Rheinland (Shenzhen) Co., Ltd.

Radio Spectrum Testing				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Wireless Connectivity Tester	Rohde & Schwarz	CMW270	101375	2021-08-30
Signal Analyzer	Rohde & Schwarz	FSV 40	101441	2021-08-30
Vector Signal Generator	Rohde & Schwarz	SMBV100A	263301	2021-08-30
Signal Generator	Rohde & Schwarz	SMB100A	115186	2021-08-30
OSP	Rohde & Schwarz	OSP 150	101017	2021-12-20
Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A
Test Software	Rohde & Schwarz	WMS32 (V10.40.10)	N/A	N/A
Power Meter	Rohde & Schwarz	NRP2	107105	2021-12-20
Wideband Power Sensor	Rohde & Schwarz	NRP-Z81	105350	2021-12-20
Unwanted Emission Testing				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
Signal Generator	Rohde & Schwarz	SMB100A	180840	2021-08-30
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	165339	2021-08-30
Signal Analyzer	Rohde & Schwarz	FSV 40	101440	2021-08-30
System Controller Interface	Rohde & Schwarz	SCI-100	S10010036	N/A
Filterbank	Rohde & Schwarz	CDMA	100751	2021-08-30
Filterbank	Rohde & Schwarz	GSM	100811	2021-08-30
OSP	Rohde & Schwarz	OSP 120	102041	N/A
OSP	Rohde & Schwarz	OSP 150	101385	N/A
Pre-amplifier	Rohde & Schwarz	SCU08F1	08320030	2021-08-30
Amplifier	Rohde & Schwarz	SCU-18F	180079	2021-08-30
Amplifier	Rohde & Schwarz	SCU40A	100450	2021-09-03
Trilog Broadband Antenna (30 MHz - 1 GHz)	Schwarzbeck	VULB9162	192	2021-09-02
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218719	2021-09-02
Wideband Ridged Horn Antenna (12- 18 GHz)	Steatite	QMS-00208	18312	2021-09-02
Wideband Ridged Horn Antenna (18- 40 GHz)	Steatite	QMS-00880	19066	2021-09-02
Biconical Broadband	Schwarzbeck	VUBA 9117	357	2021-09-02

Prüfbericht - Nr.: CN20VTHZ 001
Test Report No.:

Seite 6 von 25

Page 6 of 25

Antenna (30 MHz - 1 GHz)				
Double Ridged Broadband Horn Antenna (1 – 18 GHz)	Schwarzbeck	BBHA 9120 D	01760	2021-09-02
Broadband Horn Antenna (15 – 40 GHz)	Schwarzbeck	BBHA 9170	00862	2021-09-02
Test software	Rohde & Schwarz	EMC32 (V10.40.00)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NW9P2	N/A
Conducted Emissions				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
EMI Test Receiver	R&S	ESR3	102428	2021-08-19
Artificial Mains Network	R&S	ENV216	102333	2021-08-19

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table

Item		Extended Uncertainty
Conducted Emission		± 2.74 dB
Radiated Emission (30-1000MHz)	Field strength (dB μ V/m)	4.27dB
Radiated Emission (above 1000MHz)	Field strength (dB μ V/m)	4.46dB
Radio Spectrum		± 1.5 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a Bluetooth Stereo Turntable which supports Bluetooth (BDR&EDR) technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	Bluetooth Stereo Turntable
Type Designation	NS-BTST21
Trade Mark	INSIGNIA
FCC ID	ZXNLEETACEE500
Operating Voltage	AC 120V, 60Hz
Testing Voltage	AC 120V, 60Hz
Technical Specification of Bluetooth	
Technical Specification	Value
Operating Frequency	2402 - 2480 MHz
Type of Modulation	GFSK, $\pi/4$ DQPSK, 8DPSK
Channel Number	BDR & EDR mode:79 channels
Channel Separation	BDR & EDR mode:1MHz
Antenna Type	PCB layout antenna
Max. Antenna Gain	0.00 dBi

Table 3: RF Channel and Frequency of Bluetooth

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2402.00	20	2422.00	40	2442.00	60	2462.00
01	2403.00	21	2423.00	41	2443.00	61	2463.00
02	2404.00	22	2424.00	42	2444.00	62	2464.00
03	2405.00	23	2425.00	43	2445.00	63	2465.00
04	2406.00	24	2426.00	44	2446.00	64	2466.00
05	2407.00	25	2427.00	45	2447.00	65	2467.00
06	2408.00	26	2428.00	46	2448.00	66	2468.00
07	2409.00	27	2429.00	47	2449.00	67	2469.00
08	2410.00	28	2430.00	48	2450.00	68	2470.00
09	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	78	2480.00
19	2421.00	39	2441.00	59	2461.00	--	--

Table 4: Frequency Hopping Information

Technical Specification	Description
Hopping Range	Hereby we declare that the frequency range of this device is 2402-2480MHz.
Hopping Sequence	Example of a 79 hopping sequence in data mode: 33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73,07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56,69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43,15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47..
Receiver input bandwidth	The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings. Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

3.3 Independent Operation Modes

The basic operation modes are:

- A. On
 - 1. Bluetooth transmitting mode (BDR & EDR mode)
 - a) Low Channel
 - b) Middle Channel
 - c) High Channel
- B. On, Transmitting on Hopping channel
- C. On, Phono playing + Bluetooth connecting
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------------------|
| - Application Form | - FCC/IC Label and Location Info |
| - Block Diagram | - Photo Document |
| - Schematics | - User Manual |
| - Technical Description | |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N
Notebook	Lenovo	ThinkPad 260	PC0GP71G
Earphone	TUV Sample	N/A	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Pass****Test Specification**

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has an integral antenna, the directional gain of antenna is 0 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(b)(1)
 Basic standard : ANSI C63.10: 2013
 Limits : FHSS<0.125W(Maximum peak conducted output power)
 Kind of test site : Shielded Room

Test Setup

Date of testing : 09.12.2020
 Input voltage : AC 120V, 60Hz
 Operation mode : A.1
 Test channel : Low / Middle / High
 Ambient temperature : 24.5 °C
 Relative humidity : 49 %
 Atmospheric pressure : 101 kPa

Table 6: Test Result of Maximum Peak Conducted Output Power

Test Mode	Channel Frequency (MHz)	Measured Peak Output Power		Limit (W)
		(dBm)	(W)	
BDR	2402	-5.5	0.00028	< 0.125
	2441	-4.7	0.00034	
	2480	-3.9	0.00041	
EDR	2402	-2.8	0.00052	< 0.125
	2441	-1.4	0.00072	
	2480	-1.1	0.00078	

5.1.3 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d)
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power);
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 08.12.2020
Input voltage	: AC 120V, 60Hz
Operation mode	: A.1, B
Test channel	: Low / Middle / High
Ambient temperature	: 24.5 °C
Relative humidity	: 49 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to following test plot, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

5.1.4 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d) & FCC Part 15.205
Basic standard	: ANSI C63.10: 2013
Limits	: Refer to 15.209(a) of FCC part 15.247(d)
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 19.11.2020 -
Input voltage	: AC 120V, 60Hz
Operation mode	: A.1
Test channel	: Low / Middle / High
Ambient temperature	: 23 °C
Relative humidity	: 49 %
Atmospheric pressure	: 101 kPa

Remark:

During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions. After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation shown in the test set-up photos.

Testing was carried out within frequency range 9kHz to the tenth harmonics.

For the measurement records, refer to the appendix C.

5.1.5 20dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(1)
 Basic standard : ANSI C63.10: 2013
 Kind of test site : Shielded Room

Test Setup

Date of testing : 08.12.2020
 Input voltage : AC 120V, 60Hz
 Operation mode : A.1
 Test channel : Low / Middle / High
 Ambient temperature : 24.5 °C
 Relative humidity : 49 %
 Atmospheric pressure : 101 kPa

Table 7: Test Result of 20dB Bandwidth

Test Mode	Channel Frequency (MHz)	20dB Bandwidth (kHz)	2/3 of 20dB Bandwidth (kHz)	Limit (MHz)
BDR	2402	930	620.000	/
	2441	930	620.000	
	2480	930	620.000	
EDR	2402	1265	843.333	/
	2441	1270	846.667	
	2480	1270	846.667	

For the measurement records, refer to the appendix B.

5.1.6 Carrier Frequency Separation

RESULT:
Pass
Test Specification

Test standard	: FCC Part 15.247(a)(1)
Basic standard	: ANSI C63.10: 2013
Limits	: $\geq 25\text{kHz}$ or $2/3$ of 20dB bandwidth, whichever is greater
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 08.12.2020
Input voltage	: AC 120V, 60Hz
Operation mode	: B
Test channel	: Low / Middle / High
Ambient temperature	: 24.5 °C
Relative humidity	: 49 %
Atmospheric pressure	: 101 kPa

Table 8: Test Result of Carrier Frequency Separation

Test Mode	Channel	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)	Result
BDR	Low Channel	2401.995050	0.980198	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
	Adjacency Channel	2402.975248			
	Middle Channel	2440.995050	0.980198		Pass
	Adjacency Channel	2441.975248			
	High Channel	2478.995050	1.009900		Pass
	Adjacency Channel	2480.004950			
EDR	Low Channel	2402.024752	0.980198	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
	Adjacency Channel	2403.004950			
	Middle Channel	2440.995050	1.009900		Pass
	Adjacency Channel	2442.004950			
	High Channel	2479.024752	1.009901		Pass
	Adjacency Channel	2480.034653			

Note:

The limit is maximum $2/3$ of the 20 dB bandwidth: 846.667 KHz.

For the measurement records, refer to the appendix B.

5.1.7 Number of Hopping Frequency

RESULT:**Pass****Test Specification**

Test standard	: FCC part 15.247(a)(1)(iii)
Basic standard	: ANSI C63.10: 2013
Limits	: ≥ 15 non-overlapping channels
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 08.12.2020
Input voltage	: AC 120V, 60Hz
Operation mode	: B
Ambient temperature	: 24.5 °C
Relative humidity	: 49 %
Atmospheric pressure	: 101 kPa

Table 9: Test Result of Number of Hopping Frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
2402 to 2480 MHz	79	≥ 15	Pass

For the measurement records, refer to the appendix B.

5.1.8 Time of Occupancy

RESULT:
Pass
Test Specification

Test standard : FCC part 15.247(a)(1)(iii)
 Basic standard : ANSI C63.10: 2013
 Limits : < 0.4s
 Kind of test site : Shielded Room

Test Setup

Date of testing : 08.12.2020
 Input voltage : AC 120V, 60Hz
 Operation mode : B
 Test channel : Low / Middle / High
 Ambient temperature : 24.5 °C
 Relative humidity : 49 %
 Atmospheric pressure : 101 kPa

Table 10: Test Result of Time of Occupancy

Test Mode	Channel	Data Packet	Pulse width (ms)	Measured Dwell time(s)	Limit (s)
BDR	2441	DH1	0.383	0.123	< 0.4s
		DH3	1.639	0.262	
		DH5	2.887	0.308	
EDR	2441	2DH1	0.392	0.125	< 0.4s
		2DH3	1.642	0.263	
		2DH5	2.893	0.309	

Note:

Dwell time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 x 79 (channel) = 31.6 seconds

5.1.9 Conducted Emission on AC Mains

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.207(a)
Basic standard	: ANSI C63.10: 2013
Frequency range	: 0.15 – 30MHz
Limits	: FCC Part 15.207(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 22.11.2020
Input voltage	: AC 120V/60Hz
Operation mode	: C
Earthing	: Not connected
Ambient temperature	: 22 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix C.

6 Safety Human Exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:**Pass****Test Specification**

Test standard : CFR47 FCC Part 2.1091
FCC KDB Publication 447498 v06

Limit : CFR47 FCC Part 1.1310

FCC requirement: Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20cm normally can be maintained between the user and the device.

MPE Calculation Method according to OET Bulletin 65

Power Density: $S_{(mW/cm^2)} = PG/4\pi R^2$ or $EIRP/4\pi R^2$

Where:

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

The nominal maximum conducted output power specified:

BLuetooth: -1.10 dBm

From the peak RF output power, the minimum mobile separation distance, d=20 cm, as well as the antenna gain (0.00 dBi), the RF power density can be calculated as below:

For BLuetooth: $S_{(mW/cm^2)} = PG/4\pi R^2 = 0.00015 \text{ mW/cm}^2$

Limits for Maximum Permissible Exposure (MPE) according to FCC Part 1.1310: 1.0 mW/cm²

“RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons.”

7 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

8 List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Technical Specification of EUT	8
Table 3: RF Channel and Frequency of Bluetooth	9
Table 4: Frequency Hopping Information.....	10
Table 5: List of Accessories and Auxiliary Equipment.....	12
Table 6: Test Result of Maximum Peak Conducted Output Power.....	16
Table 7: Test Result of 20dB Bandwidth.....	19
Table 8: Test Result of Carrier Frequency Separation	20
Table 9: Test Result of Number of Hopping Frequency	21
Table 10: Test Result of Time of Occupancy	22

Appendix B

Test Results of Conducted Testing


APPENDIX B	1
APPENDIX B.1: TEST PLOTS OF 20dB BANDWIDTH	2
<i>BDR Mode, DH1</i>	2
<i>EDR Mode, 3DH1</i>	3
APPENDIX B.2: TEST PLOTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 kHz BANDWIDTH	5
<i>BDR Mode, Low Channel</i>	5
<i>BDR Mode, Middle Channel</i>	6
<i>BDR Mode, High Channel</i>	7
<i>BDR, Hopping</i>	8
<i>EDR Mode, Low Channel</i>	9
<i>EDR Mode, Middle Channel</i>	10
<i>EDR Mode, High Channel</i>	11
<i>EDR, Hopping</i>	12
<i>BDR Mode, Band Edge, Low Channel</i>	13
<i>BDR Mode, Band Edge, High Channel</i>	13
<i>BDR Mode, Hopping Band Edge</i>	14
<i>EDR Mode, Band Edge, Low Channel</i>	15
<i>EDR Mode, Band Edge, High Channel</i>	15
<i>EDR Mode, Hopping Band Edge</i>	16
APPENDIX B.3: TEST PLOTS OF CARRIER FREQUENCY SEPARATION	17
<i>BDR, Low Channel</i>	17
<i>BDR, Middle Channel</i>	17
<i>BDR, High Channel</i>	18
<i>EDR, Low Channel</i>	18
<i>EDR, Middle Channel</i>	19
<i>EDR, High Channel</i>	19
APPENDIX B.4: TEST PLOTS OF NUMBER OF HOPPING FREQUENCY	20
<i>BDR, Hopping</i>	20
<i>EDR, Hopping</i>	20
APPENDIX B.5: TEST PLOTS OF TIME OF OCCUPANCY	21
<i>BDR Mode, DH1, Middle Channel</i>	21
<i>BDR Mode, DH3, Middle Channel</i>	21
<i>BDR Mode, DH5, Middle Channel</i>	22
<i>EDR Mode, 3DH1, Middle Channel</i>	22
<i>EDR Mode, 3DH3, Middle Channel</i>	23
<i>EDR Mode, 3DH5, Middle Channel</i>	23

Appendix B.1: Test Plots of 20dB Bandwidth


BDR Mode, DH1

RBW=10KHz VBW=30KHz


20 dB Bandwidth



20 dB Bandwidth




20 dB Bandwidth




EDR Mode, 3DH1

RBW=30KHz VBW=100KHz


20 dB Bandwidth



20 dB Bandwidth




20 dB Bandwidth




Appendix B.2: Test Plots of Conducted Spurious Emissions Measured in 100 kHz Bandwidth

BDR Mode, Low Channel




Date: 8.DEC.2020 07:30:05




Date: 8.DEC.2020 07:34:49

BDR Mode, Middle Channel




Date: 8.DEC.2020 07:30:37




Date: 8.DEC.2020 07:35:37

BDR Mode, High Channel




Date: 8.DEC.2020 07:31:00




Date: 8.DEC.2020 07:36:50

BDR, Hopping




Date: 8.DEC.2020 07:24:11




Date: 8.DEC.2020 07:28:16

EDR Mode, Low Channel





Date: 8.DEC.2020 07:41:35




Date: 8.DEC.2020 07:43:01


EDR Mode, Middle Channel



EDR Mode, High Channel





Date: 8.DEC.2020 07:44:53




Date: 8.DEC.2020 07:46:07


EDR, Hopping





BDR Mode, Band Edge, Low Channel




BDR Mode, Band Edge, High Channel




BDR Mode, Hopping Band Edge




EDR Mode, Band Edge, Low Channel




EDR Mode, Band Edge, High Channel



EDR Mode, Hopping Band Edge



Date: 8.DEC.2020 07:38:49




Date: 8.DEC.2020 07:39:19

Appendix B.3: Test Plots of Carrier Frequency Separation


BDR, Low Channel

RBW=300KHz, VBW=300KHz




BDR, Middle Channel

RBW=300KHz, VBW=300KHz




BDR, High Channel
RBW=300KHz, VBW=300KHz

CFS




EDR, Low Channel
RBW=300KHz, VBW=300KHz


CFS



EDR, Middle Channel
RBW=300KHz, VBW=300KHz




EDR, High Channel
RBW=300KHz, VBW=300KHz



Appendix B.4: Test Plots of Number of Hopping Frequency


BDR, Hopping

RBW=200KHzM, VBW=200KHz




EDR, Hopping

RBW=200KHzM, VBW=200KHz




Appendix B.5: Test Plots of Time of Occupancy

BDR Mode, DH1, Middle Channel
RBW=500KHzM, VBW=1MHz




BDR Mode, DH3, Middle Channel
RBW=500KHzM, VBW=1MHz




BDR Mode, DH5, Middle Channel
RBW=500KHzM, VBW=1MHz

Time of Channel Occupancy(3)




EDR Mode, 3DH1, Middle Channel
RBW=500KHzM, VBW=1MHz

Time of Channel Occupancy




EDR Mode, 3DH3, Middle Channel
RBW=500KHzM, VBW=1MHz

Time of Channel Occupancy(2)



EDR Mode, 3DH5, Middle Channel
RBW=500KHzM, VBW=1MHz

Time of Channel Occupancy(3)



Appendix C

Test Results of Radiated Emission & AC Mains Conducted Emission

APPENDIX C	1
APPENDIX C.1: TEST PLOTS OF RADIATED SPURIOUS EMISSION	2
<i>BDR mode, 30MHz - 1GHz</i>	2
<i>BDR mode, 1GHz - 6.2GHz</i>	6
<i>BDR mode, 6.2GHz - 18GHz</i>	12
<i>EDR mode, 1GHz - 6.2GHz</i>	18
<i>EDR mode, 6.2GHz - 18GHz</i>	24
APPENDIX C.2: TEST PLOTS OF BAND EDGE (RADIATED)	30
<i>BDR mode, Low Channel</i>	30
<i>BDR mode, High Channel</i>	32
<i>EDR mode, Low Channel</i>	34
<i>EDR mode, High Channel</i>	36
APPENDIX C.3: TEST PLOTS OF AC MAINS CONDUCTED EMISSION	38


Note: The radiated spurious emission were measured from 9KHz to 26.5GHz, the measurement results below 30MHz and above 18GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

Appendix C.1: Test Plots of Radiated Spurious Emission

BDR mode, 30MHz - 1GHz

EUT Information

EUT Name:	Bluetooth Stereo Turntable
Model:	NS-BTST21
Test Mode:	TX_DH5_Low channel
Test Voltage::	AC AC 120V/60Hz
Remark:	Temp 23 Humi:49%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.965500	21.62	---	40.00	18.38	100.0	V	1.0	-21.6
55.947500	23.86	---	40.00	16.14	100.0	V	0.0	-18.5
107.988000	26.87	---	43.50	16.63	100.0	V	120.0	-18.9
728.400000	27.70	---	46.00	18.30	100.0	V	5.0	-7.5

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Low channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
107.988000	25.80	---	43.50	17.70	100.0	H	181.0	-18.9
143.975000	25.73	---	43.50	17.77	100.0	H	151.0	-22.2
179.962000	24.66	---	43.50	18.84	100.0	H	132.0	-20.5
275.992000	22.46	---	46.00	23.54	100.0	H	111.0	-16.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.965500	29.87	---	40.00	10.13	100.0	V	341.0	-21.6
59.973000	25.51	---	40.00	14.49	100.0	V	175.0	-19.0
107.988000	27.41	---	43.50	16.09	100.0	V	144.0	-18.9

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.965500	18.58	---	40.00	21.42	100.0	H	9.0	-21.6
107.988000	25.58	---	43.50	17.92	100.0	H	72.0	-18.9
215.997500	26.72	---	43.50	16.78	100.0	H	286.0	-18.7
728.836500	27.30	---	46.00	18.70	100.0	H	64.0	-7.5

BDR mode, 1GHz - 6.2GHz

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Low channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4804.000000	53.30	---	74.00	20.70	100.0	V	78.0	11.8
4804.000000	---	47.40	54.00	6.60	100.0	V	78.0	11.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Low channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4803.500000	51.82	---	74.00	22.18	100.0	H	273.0	11.8
4804.000000	---	46.33	54.00	7.67	100.0	H	273.0	11.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Mid channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4886.000000	52.60	---	74.00	21.40	100.0	H	265.0	11.8
4886.000000	---	47.37	54.00	6.63	100.0	H	265.0	11.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Mid channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4886.000000	53.80	---	74.00	20.20	100.0	V	82.0	11.8
4886.000000	---	48.34	54.00	5.66	100.0	V	82.0	11.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4959.797222	55.19	---	74.00	18.81	100.0	V	64.0	11.8

rodunkte
Products

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4959.500000	53.92	---	74.00	20.08	100.0	H	276.0	11.8
4960.000000	---	49.30	54.00	4.70	100.0	H	266.0	11.8

BDR mode, 6.2GHz - 18GHz

EUT Information

EUT Name:	Bluetooth Stereo Turntable
Model:	NS-BTST21
Test Mode:	TX_DH5_Low channel
Test Voltage::	AC 120V/60Hz
Remark:	Temp 23 Humi:49%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10595.500000	46.90	---	74.00	27.10	100.0	V	197.0	12.1
10635.325000	---	36.55	54.00	17.45	100.0	V	197.0	12.0

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Low channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10653.516667	---	36.99	54.00	17.01	100.0	H	199.0	12.0
10654.991667	46.88	---	74.00	27.12	100.0	H	157.0	12.0

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Mid channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10599.925000	46.31	---	74.00	27.69	100.0	V	300.0	12.1
10615.658333	---	37.08	54.00	16.92	100.0	V	260.0	12.0

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Mid channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10641.225000	---	36.99	54.00	17.01	100.0	H	6.0	12.0
10663.841667	47.06	---	74.00	26.94	100.0	H	114.0	11.9

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10634.341667	---	36.71	54.00	17.29	100.0	V	0.0	12.0
10636.308333	46.51	---	74.00	27.49	100.0	V	184.0	12.0

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10644.666667	---	36.69	54.00	17.31	100.0	H	0.0	12.0
10653.516667	46.47	---	74.00	27.53	100.0	H	184.0	12.0

EDR mode, 1GHz - 6.2GHz

EUT Information

EUT Name:	Bluetooth Stereo Turntable
Model:	NS-BTST21
Test Mode:	TX_3DH5_Low channel
Test Voltage::	AC 120V/60Hz
Remark:	Temp 23 Humi:49%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4803.500000	56.56	---	74.00	17.44	100.0	V	85.0	11.8
4803.500000	---	49.33	54.00	4.67	100.0	V	85.0	11.8

EUT Information

EUT Name: Wireless sprots earbuds
Model: NS-BTST21
Test Mode: TX
Test Voltage:: DC 3.3V From USB
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4803.500000	52.50	---	74.00	21.50	100.0	H	233.0	11.8
4804.000000	---	43.73	54.00	10.28	100.0	H	233.0	11.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_Mid channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4804.000000	55.83	---	74.00	18.17	100.0	V	56.0	11.8
4804.000000	---	48.92	54.00	5.08	100.0	V	56.0	11.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_Mid channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4804.000000	52.66	---	74.00	21.34	100.0	H	249.0	11.8
4804.000000	---	44.51	54.00	9.49	100.0	H	249.0	11.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4959.500000	57.93	---	74.00	16.07	100.0	V	76.0	11.8
4960.000000	---	50.85	54.00	3.15	100.0	V	76.0	11.8

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4960.000000	58.50	---	74.00	15.50	100.0	H	235.0	11.8
4960.000000	---	49.69	54.00	4.31	100.0	H	235.0	11.8

EDR mode, 6.2GHz - 18GHz

EUT Information

EUT Name:	Bluetooth Stereo Turntable
Model:	NS-BTST21
Test Mode:	TX_3DH5_Low channel
Test Voltage::	AC 120V/60Hz
Remark:	Temp 23 Humi:49%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10601.400000	47.88	---	74.00	26.12	100.0	V	84.0	12.1
10662.366667	---	37.54	54.00	16.46	100.0	V	98.0	11.9

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_Low channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10655.975000	47.57	---	74.00	26.43	100.0	H	252.0	12.0
10657.450000	---	37.07	54.00	16.93	100.0	H	96.0	12.0

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_Mid channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9190.316667	---	35.37	54.00	18.63	100.0	V	192.0	10.6
9220.800000	46.34	---	74.00	27.66	100.0	V	52.0	10.7

roducte
Products

EUT Information

EUT Name:	Bluetooth Stereo Turntable
Model:	NS-BTST21
Test Mode:	TX_3DH5_Mid channel
Test Voltage::	AC 120V/60Hz
Remark:	Temp 23 Humi:49%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10625.983333	---	36.99	54.00	17.01	100.0	H	275.0	12.0
10671.708333	47.29	---	74.00	26.71	100.0	H	262.0	11.9

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11751.408333	47.86	---	74.00	26.14	100.0	V	175.0	13.3
11761.241667	---	38.05	54.00	15.95	100.0	V	49.0	13.4

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10635.816667	---	37.28	54.00	16.72	100.0	H	163.0	12.0
10650.075000	46.75	---	74.00	27.25	100.0	H	15.0	12.0

Appendix C.2: Test Plots of Band Edge (Radiated)

BDR mode, Low Channel

EUT Information

EUT Name:	Bluetooth Stereo Turntable
Model:	NS-BTST21
Test Mode:	TX_DH5_Low channel
Test Voltage::	AC 120V/60Hz
Remark:	Temp 23 Humi:49%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2375.787500	---	39.45	54.00	14.55	100.0	V	356.0	6.9
2381.333125	49.39	---	74.00	24.61	100.0	V	316.0	7.0

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_Low channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2375.876563	48.65	---	74.00	25.35	100.0	H	68.0	6.9
2376.161563	---	39.76	54.00	14.24	100.0	H	135.0	6.9

BDR mode, High Channel

EUT Information

EUT Name:	Bluetooth Stereo Turntable
Model:	NS-BTST21
Test Mode:	TX_DH5_High channel
Test Voltage::	AC 120V/60Hz
Remark:	Temp 23 Humi:49%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2487.010375	49.56	---	74.00	24.44	100.0	V	152.0	7.4
2488.421125	---	40.45	54.00	13.55	100.0	V	0.0	7.4

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2485.746750	---	40.23	54.00	13.77	100.0	H	0.0	7.4
2487.231750	50.05	---	74.00	23.95	100.0	H	300.0	7.4

EDR mode, Low Channel

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_Mid channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2379.189688	---	39.49	54.00	14.51	100.0	V	0.0	7.0
2383.874375	49.17	---	74.00	24.83	100.0	V	324.0	7.0

roducte
Products

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_Low channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2366.759063	49.25	---	74.00	24.75	100.0	H	331.0	6.9
2376.130313	---	39.52	54.00	14.48	100.0	H	321.0	6.9

EDR mode, High Channel

EUT Information

EUT Name:	Bluetooth Stereo Turntable
Model:	NS-BTST21
Test Mode:	TX_3DH5_High channel
Test Voltage::	AC 120V/60Hz
Remark:	Temp 23 Humi:49%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2484.394375	---	40.41	54.00	13.59	100.0	V	322.0	7.4
2486.935375	49.82	---	74.00	24.19	100.0	V	346.0	7.4

rodunkte
Products

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: TX_3DH5_High channel
Test Voltage:: AC 120V/60Hz
Remark: Temp 23 Humi:49%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2484.937750	50.02	---	74.00	23.98	100.0	H	271.0	7.4
2487.919750	---	40.19	54.00	13.81	100.0	H	359.0	7.4

Appendix C.3: Test Plots of AC Mains Conducted Emission

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: Phono+BT
Test Voltage: AC 120V/60Hz
Test By: Mac Xie
Review By: Gary Chen
Remark: SR1




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.640000	---	12.86	46.00	33.14	L1	9.7
0.732000	23.71	---	56.00	32.29	L1	9.7
0.900000	---	12.93	46.00	33.07	L1	9.7
0.932000	25.46	---	56.00	30.54	L1	9.7
1.316000	25.29	---	56.00	30.71	L1	9.7
1.836000	---	13.49	46.00	32.51	L1	9.7
3.440000	25.61	---	56.00	30.39	L1	9.8
3.568000	---	14.85	46.00	31.15	L1	9.8
3.712000	26.81	---	56.00	29.19	L1	9.8
4.432000	---	15.26	46.00	30.74	L1	9.8
19.752000	---	14.79	50.00	35.21	L1	10.5
20.288000	27.74	---	60.00	32.26	L1	10.5

rodunkte
Products

EUT Information

EUT Name: Bluetooth Stereo Turntable
Model: NS-BTST21
Test Mode: Phono+BT
Test Voltage: AC 120V/60Hz
Test By: Mac Xie
Review By: Gary Chen
Remark: SR1



Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.508000	---	13.08	46.00	32.92	N	9.7
0.644000	24.37	---	56.00	31.63	N	9.7
0.860000	---	12.86	46.00	33.14	N	9.7
0.936000	23.66	---	56.00	32.34	N	9.7
1.140000	---	12.20	46.00	33.80	N	9.7
1.716000	---	13.51	46.00	32.49	N	9.7
1.932000	23.88	---	56.00	32.12	N	9.7
2.344000	25.53	---	56.00	30.47	N	9.7
3.488000	---	14.62	46.00	31.38	N	9.8
4.180000	26.33	---	56.00	29.67	N	9.8
4.984000	---	15.37	46.00	30.63	N	9.9
27.852000	27.83	---	60.00	32.17	N	10.5