

FCC Part15.247 Test Report

Product Name : GSM Mobile Phone

Model No. : DN212

FCC ID : ZXTALVODN212

Applicant : SHENZHEN UNITED TIME TECHNOLOGY CO., LTD

Address : Room 1001 Microprofit Building, 6 Gaoxin South
Road, High-Tech Park, Nanshan district, Shenzhen,
P.R.China

Date of Receipt : 27/08/2011

Test Date : 28/08/2011~04/09/2011

Issued Date : 05/09/2011

Report No. : 118S081R-RF-US-P06V01

Report Version : V 2.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of QuieTek Corporation.

Test Report Certification

Issued Date : 05/09/2011

Report No. : 118S081R-RF-US-P06V01



Product Name : GSM Mobile Phone

Applicant : SHENZHEN UNITED TIME TECHNOLOGY CO., LTD

Address : Room 1001 Microprofit Building, 6 Gaoxin South Road,
High-Tech Park, Nanshan District, Shenzhen, P.R.China

Manufacturer : HUIZHOU UNITED TIME TECHNOLOGY CO., LTD

Address : 2# Songbai Road, South Zone, Cyber Park, Huizhou,
Guangdong, China

Model No. : DN212

FCC ID : ZXTALVODN212

Trade Name : ALVO

EUT Voltage : DC: 3.7V

Applicable Standard : FCC CFR Title 47 Part 15 Subpart C: 2008
ANSI C63.4: 2009
ANSI C63.10: 2009

Test Result : Complied

Performed Location : Suzhou EMC Laboratory
No.99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech
Development Zone., Suzhou, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Registration Number: 800392

Documented By : Alice Ni
(Engineering ADM: Alice Ni)

Reviewed By : Robin Wu
(Senior Engineer: Robin Wu)

Approved By : Marlin Chen
(Engineering Supervisor: Marlin Chen)

Laboratory Information

We, **Quietek Corporation**, are an independent EMC and safety consultancy that was established the whole facility in our laboratories. The test facility has been accredited/accepted(audited or listed) by the following related bodies in compliance with ISO 17025, EN 45001 and specified testing scope:

Taiwan R.O.C.	: BSMI, NCC, TAF
Germany	: TUV Rheinland
Norway	: Nemko, DNV
USA	: FCC, NVLAP
Japan	: VCCI

The related certificate for our laboratories about the test site and management system can be downloaded from Quietek Corporation's Web Site : <http://www.quietek.com/tw/ctg/cts/accreditations.htm>
The address and introduction of Quietek Corporation's laboratories can be founded in our Web site : <http://www.quietek.com/>
If you have any comments, Please don't hesitate to contact us. Our contact information is as below:

HsinChu Testing Laboratory :

No.75-2, 3rd Lin, Wangye Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C.
TEL:+886-3-592-8858 / FAX:+886-3-592-8859 E-Mail : service@quietek.com



LinKou Testing Laboratory :

No. 5-22, Ruei-Shu Valley, Ruei-Ping Tsuen, Lin-Kou Shiang, Taipei, Taiwan, R.O.C.
TEL : 886-2-8601-3788 / FAX : 886-2-8601-3789 E-Mail : service@quietek.com



Suzhou (China) Testing Laboratory :

No. 99 Hongye Rd., Suzhou Industrial Park Loufeng Hi-Tech Development Zone., Suzhou,China.
TEL : +86-512-6251-5088 / FAX : +86-512-6251-5098 E-Mail : service@quietek.com



TABLE OF CONTENTS

Description	Page
1. General Information.....	7
1.1. EUT Description	7
1.2. Mode of Operation	9
1.3. Tested System Details.....	10
1.4. Configuration of Tested System	11
1.5. EUT Exercise Software	12
2. Technical Test.....	13
2.1. Summary of Test Result	13
2.2. Test Environment	14
3. Conducted Emission	15
3.1. Test Equipment	15
3.2. Test Setup	15
3.3. Limit.....	16
3.4. Test Procedure	16
3.5. Uncertainty	16
3.6. Test Result	17
4. Radiated Emission	19
4.1. Test Equipment	19
4.2. Test Setup	20
4.3. Limit.....	21
4.4. Test Procedure	21
4.5. Uncertainty	21
4.6. Test Result	22
5. 20dB Bandwidth	25
5.1. Test Equipment	25
5.2. Test Setup	25
5.3. Limit.....	25
5.4. Test Procedure	26
5.5. Uncertainty	26
5.6. Test Result	27
6. Carrier Frequency Separation	33
6.1. Test Equipment	33
6.2. Test Setup	33
6.3. Limit.....	33
6.4. Test Procedure	34
6.5. Uncertainty	34
6.6. Test Result	35

7.	Number of Hopping Frequencies	41
7.1.	Test Equipment	41
7.2.	Test Setup	41
7.3.	Limit.....	41
7.4.	Test Procedure	42
7.5.	Uncertainty	42
7.6.	Test Result	43
8.	Time of Occupancy (Dwell Time).....	52
8.1.	Test Equipment	52
8.2.	Test Setup	52
8.3.	Limit.....	52
8.4.	Test Procedure	53
8.5.	Uncertainty	53
8.6.	Test Result	54
9.	Peak Output Power	60
9.1.	Test Equipment	60
9.2.	Test Setup	60
9.3.	Limit.....	60
9.4.	Test Procedure	61
9.5.	Uncertainty	61
9.6.	Test Result	62
10.	Band-edge Compliance of RF Conducted Emissions	68
10.1.	Test Equipment	68
10.2.	Test Setup	68
10.3.	Limit.....	68
10.4.	Test Procedure	69
10.5.	Uncertainty	69
10.6.	Test Result	70
11.	Spurious RF Conducted Emissions.....	74
11.1.	Test Equipment	74
11.2.	Test Setup	74
11.3.	Limit.....	74
11.4.	Test Procedure	75
11.5.	Uncertainty	75
11.6.	Test Result	76
12.	Radiated Emission Band Edge.....	82
12.1.	Test Equipment	82
12.2.	Test Setup	83

12.3. Limit.....83

12.4. Test Procedure83

12.5. Uncertainty84

12.6. Test Result85

1. General Information

1.1. EUT Description

Product Name	GSM Mobile Phone
Model No.	DN212
Device Category	Portable
RF Exposure Environment	Uncontrolled
Antenna Type	Internal
2G	
Support Band	GSM850/GSM900/DCS1800/PCS1900
GPRS Type	Class B
GPRS Class	Class 12
Tx Frequency Range	GSM 850: 824~849MHz PCS 1900: 1850~1910MHz
Rx Frequency Range	GSM 850: 869~894MHz PCS 1900: 1930~1990MHz
Release Version	GSM: R99
Type of modulation	GMSK for GSM/GPRS
Antenna Gain	0.8dBi
Bluetooth	
Bluetooth Frequency	2402~2480MHz
Bluetooth Version	V2.1 + EDR
Type of modulation	FHSS
Data Rate	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Gain	0.2dBi
AC Adapter	Brand Name: ALVO M/N: DN212 Input: 100-240V~50/60Hz 0.2A Output: 5Vdc, 500mA

Bluetooth Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

1.2. Mode of Operation

Quietek has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmitter-1Mbps(GFSK_DH5)
Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)
Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Note:


1. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.
2. For portable device, radiated spurious emission was verified over X, Y, Z axis, and shown the worst case on this report.
3. This device is a composite device in accordance with Part 15 Subpart B regulations.

1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product		Manufacturer	Model No.	Serial No.	Power Cord
1	N/A	N/A	N/A	N/A	N/A

1.4. Configuration of Tested System



1.5. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	Execute the software provided by applicant on the phone.
4	Select test channel and test mode to test.

2. Technical Test

2.1. Summary of Test Result

☒ No deviations from the test standards

☐ Deviations from the test standards as below description:

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.207	Yes	No
Radiated Emission	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.209	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)(iii)	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(a)(1)(iii)	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.247(b)(1)	Yes	No
Band-edge Compliance of RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2008 Section 15.215(c), 15.247(d)	Yes	No
Spurious RF Conducted Emissions	FCC CFR Title 47 Part 15 Subpart C: 2008 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2008 15.247(d)	Yes	No

2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

3. Conducted Emission


3.1. Test Equipment

Conducted Emission / TR-1

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100726	2012.04.23
Two-Line V-Network	R&S	ENV216	100043	2012.04.29
Two-Line V-Network	R&S	ENV216	100044	2011.09.07
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2012.05.05
50ohm Termination	SHX	TF2	07081401	2011.09.27
Temperature/Humidity Meter	zhicheng	ZC1-2	TR1-TH	2012.01.14

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

According to FCC ANSI C63.4: 2009 & ANSI C63.10: 2009.

The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)

Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

3.5. Uncertainty

The measurement uncertainty is defined as ± 2.02 dB


3.6. Test Result

Site: TR1	Time: 2011/09/04 - 15:31
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101043(0.009-30MHz)	Polarity: Line
EUT: GSM Mobile Phone	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.150	52.192	42.604	-13.808	66.000	9.588	QP
2		0.150	25.912	16.324	-30.088	56.000	9.588	AV
3		0.354	32.327	22.647	-26.541	58.868	9.680	QP
4		0.354	20.779	11.099	-28.089	48.868	9.680	AV
5		0.610	35.192	25.502	-20.808	56.000	9.690	QP
6		0.610	25.599	15.909	-20.401	46.000	9.690	AV
7		0.762	32.316	22.630	-23.684	56.000	9.686	QP
8		0.762	22.070	12.384	-23.930	46.000	9.686	AV
9		1.530	29.903	20.197	-26.097	56.000	9.706	QP
10		1.530	19.323	9.617	-26.677	46.000	9.706	AV
11		2.130	29.505	19.774	-26.495	56.000	9.731	QP
12		2.130	19.333	9.602	-26.667	46.000	9.731	AV

Site: TR1	Time: 2011/09/04 - 15:37
Limit: FCC_Part15.207_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101043(0.009-30MHz)	Polarity: Neutral
EUT: GSM Mobile Phone	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1	*	0.154	47.472	37.727	-18.310	65.781	9.744	QP
2		0.154	19.973	10.229	-35.808	55.781	9.744	AV
3		0.190	42.915	33.240	-21.121	64.037	9.676	QP
4		0.190	20.010	10.335	-34.026	54.037	9.676	AV
5		0.250	37.510	27.858	-24.247	61.757	9.652	QP
6		0.250	17.130	7.478	-34.627	51.757	9.652	AV
7		0.314	34.011	24.358	-25.853	59.864	9.654	QP
8		0.314	21.647	11.994	-28.217	49.864	9.654	AV
9		0.610	30.172	20.491	-25.828	56.000	9.681	QP
10		0.610	20.832	11.151	-25.168	46.000	9.681	AV
11		1.302	24.439	14.722	-31.561	56.000	9.717	QP
12		1.302	14.637	4.920	-31.363	46.000	9.717	AV

4. Radiated Emission

4.1. Test Equipment

☒ Radiated Emission / AC-1 - Below 30MHz

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100175	2012.04.23
Loop Antenna	R&S	HFH2-Z2	833799/003	2011.11.22
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC1-TH	2012.01.14

☒ Radiated Emission / AC-2 - 30~1000MHz


Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100573	2012.04.23
Bilog Antenna	Teseg GmbH	CBL6112D	27611	2011.10.18
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2012.05.05
Temperature/Humidity Meter	Zhicheng	ZC1-2	AC2-TH	2012.01.14

☒ Radiated Emission / AC-5 – Above 1GHz


Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2012.04.23
EMI Test Receiver	R&S	ESCI	100573	2012.04.23
Preamplifier	Quietek	AP-025C	CHM-0511006	2012.05.05
Preamplifier	Quietek	AP-180C	CHM-0602013	2012.05.05
Bilog Type Antenna	Schaffner	CBL6112B	2932	2011.11.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2012.06.11
High-Pass Filter	Wainwright	WHKX2.8/18G-12SS	SN1	2012.03.03
Band Reject Filter	Wainwright	WRCG2400/2485-2375/2510-60/11SS	SN9	2012.03.03
High-Pass Filter	Wainwright	WHKX7.0/18G-8SS	SN16	2012.03.03
Low-Pass Filter	Wainwright	WLKS4500-9SS	SN2	2012.03.03
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2011.05.05
Temperature/Humidity Meter	zhicheng	ZC1-2	AC5-TH	2012.01.14

4.2. Test Setup


Below 30MHz Test Setup



Below 1GHz Test Setup:



Above 1GHz Test Setup:



4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209		
Frequency (MHz)	Distance (m)	Level (dBuV/m)
30 - 88	3	40
88 - 216	3	43.5
216 - 960	3	46
Above 960	3	54

Note 1: The lower limit shall apply at the transition frequency.

Note 2: Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

Note 3: E field strength (dBuV/m) = 20 log E field strength (uV/m)

4.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.4: 2009 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn antenna will be bended down a little (as horn antenna has the narrow beamwidth) in order to keeping the antenna in the "cone of radiation" of EUT. The 3dB beamwidth is 60~10 degrees for H-plane and 90~10 degrees for E-plane.

4.5. Uncertainty

The measurement uncertainty above 1G is defined as ± 3.9 dB
below 1G is defined as ± 3.8 dB

4.6. Test Result

Note: for below 30MHz, the emission levels are >20 dB below the limit and are not reported in this result.

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;

Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Measure Level = Reading Level + Cable Loss + Antenna Factor – Preamplifier Gain

Mode 1: Transmitter-1Mbps(GFSK_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	V	2401.9	64.9	31.2	96.1	Fundamental	/	PK
	H	416.9	4.4	18.3	22.7	46	-23.3	QP
	H	586.5	5.7	20.9	26.6	46	-19.4	QP
	V	3397.0	52.7	-16.1	36.6	54(Note)	-17.4	PK
	H	4808.0	57.6	-11.9	45.7	54(Note)	-8.3	PK
	H	7288.0	47.9	-3.5	44.4	54(Note)	-9.6	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	V	2441.1	64.7	31.2	95.9	Fundamental	/	PK
	V	320.2	5.2	15.4	20.6	46	-25.4	QP
	V	562.6	4.4	20.8	25.2	46	-20.8	QP
	V	3269.5	52.8	-16.1	36.7	54(Note)	-17.3	PK
	V	4884.5	61.9	-11.7	50.2	54(Note)	-3.8	PK
	V	7323.0	44.0	-3.0	41.0	54(Note)	-13.0	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
78	V	2480.1	64.5	31.2	95.7	Fundamental	/	PK
	H	313.7	4.9	15.2	20.1	46	-25.9	QP
	H	449.6	6.0	18.3	24.3	46	-21.7	QP
	H	3218.5	49.8	-15.9	33.9	54(Note)	-20.1	PK
	V	4961.0	59.4	-11.4	48.0	54(Note)	-6.0	PK
	H	7440.0	45.6	-2.6	43.0	54(Note)	-11.0	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 2: Transmitter-2Mbps(Pi/4 DQPSK _DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	V	2401.9	65.0	31.2	96.2	Fundamental	/	PK
	V	338.7	5.1	15.7	20.8	46	-25.2	QP
	V	511.2	5.7	19.5	25.2	46	-20.8	QP
	V	3218.5	50.9	-15.9	35.0	54(Note)	-19.0	PK
	H	4808.0	57.3	-11.9	45.4	54(Note)	-8.6	PK
	H	7265.0	47.7	-3.4	44.3	54(Note)	-9.7	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	V	2441.0	65.6	31.2	96.8	Fundamental	/	PK
	H	381.3	4.9	17.2	22.1	46	-23.9	QP
	H	437.4	5.5	18.3	23.8	46	-22.2	QP
	V	3218.5	51.5	-15.9	35.6	54(Note)	-18.4	PK
	H	4884.5	58.6	-11.7	46.9	54(Note)	-7.1	PK
	H	7264.0	48.0	-3.3	44.7	54(Note)	-9.3	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
78	V	2480.0	66.4	31.2	97.6	Fundamental	/	PK
	V	423.9	4.6	18.3	22.9	46	-23.1	QP
	V	546.1	4.4	20.4	24.8	46	-21.2	QP
	H	3218.5	51.7	-15.9	35.8	54(Note)	-18.2	PK
	H	4961.0	60.4	-11.4	49.0	54(Note)	-5.0	PK
	H	7440.0	46.5	-2.6	43.9	54(Note)	-10.1	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

Mode 3: Transmitter-3Mbps(8DPSK_DH5)

CH	Antenna	Frequency (MHz)	Reading Level (dBuV/m)	Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
0	H	2402.0	60.2	32.0	92.2	Fundamental	/	PK
	H	304.6	4.3	15.2	19.5	46	-26.5	QP
	H	658.0	3.9	21.2	25.1	46	-20.9	QP
	V	3122.5	52.0	-18.2	33.8	54(Note)	-20.2	PK
	H	4804.0	42.2	2.6	44.8	54(Note)	-9.2	PK
	H	7206.0	42.2	9.2	51.4	54(Note)	-2.6	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
39	H	2441.0	60.7	32.0	92.7	Fundamental	/	PK
	V	332.1	3.4	15.5	18.9	46	-27.1	QP
	V	701.4	4.7	21.5	26.2	46	-19.8	QP
	H	3122.5	53.1	-18.2	34.9	54(Note)	-19.1	PK
	H	4882.0	41.4	2.8	44.2	54(Note)	-9.8	PK
	H	7323.0	41.3	9.2	50.5	54(Note)	-3.5	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK
78	H	2480.0	61.6	31.9	93.5	Fundamental	/	PK
	V	390.1	3.4	17.2	20.6	46	-25.4	QP
	V	850.4	4.7	21.9	26.6	46	-19.4	QP
	H	3122.5	50.7	-18.1	32.6	54(Note)	-21.4	PK
	H	4960.0	41.3	2.9	44.2	54(Note)	-9.8	PK
	V	7440.0	41.0	9.2	50.2	54(Note)	-3.8	PK
	H	24000.0	59.1	-8.9	50.2	54(Note)	-3.8	PK

Note : This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.

5. 20dB Bandwidth


5.1 Test Equipment

20dB Bandwidth / TR8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

5.2 Test Setup



5.3 Limit

- For frequency hopping systems operating in 2400-2483.5 MHz band, no limitation.
- For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

5.4 Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize.

Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

5.5 Uncertainty


The measurement uncertainty is defined as ± 1 kHz

5.6 Test Result


Product	:	Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	934.78	868.61
39	2441	922.32	846.67
78	2480	930.05	876.51


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1257.0	1164.2
39	2441	1310.0	1187.0
78	2480	1277.0	1184.7


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	Mobile Phone
Test Item	:	Occupied Bandwidth
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1261.0	1154.7
39	2441	1265.0	1163.1
78	2480	1294.0	1201.0


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



6. Carrier Frequency Separation


6.1. Test Equipment

Carrier Frequency Separation / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

6.2. Test Setup



6.3. Limit

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudorandomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping

channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

6.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span

Video (or Average) Bandwidth VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

6.6. Test Result


Product	:	GSM Mobile Phone
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Carrier Frequency Separation
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	>25 kHz or 2/3 of 20 dB BW	Pass
39	2441	1000	>25 kHz or 2/3 of 20 dB BW	Pass
78	2480	1000	>25 kHz or 2/3 of 20 dB BW	Pass


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7. Number of Hopping Frequencies


7.1. Test Equipment

Number of Hopping Frequencies / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

7.2. Test Setup



7.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
- For frequency hopping systems operating in 902-928 MHz band shall use at least 50 hopping frequencies.
- For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

7.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to bread the span up to sections, in order to clearly show all of the hopping frequencies.

7.5. Uncertainty


The measurement uncertainty is defined as ± 1 kHz

7.6. Test Result


Product	:	GSM Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	GSM Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz




2462 - 2480 MHz




Product	:	GSM Mobile Phone
Test Item	:	Number of Hopping Frequencies
Test Site	:	TR-8
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


2402 - 2421 MHz




2422 - 2441 MHz



2442 - 2461 MHz



2462 - 2480 MHz



8. Time of Occupancy (Dwell Time)


8.1. Test Equipment

Time of Occupancy (Dwell Time) / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

8.2. Test Setup



8.3. Limit

- For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
- Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75

hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

- Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.4. Test Procedure

According to ANSI C63.10: 2009.

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1MHz

VBW $\geq$ RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

8.5. Uncertainty

The measurement uncertainty is defined as ± 0.1 us

8.6. Test Result


Product	:	GSM Mobile Phone
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps(8DPSK_DH1)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	122.66	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6 \text{ sec}$, Hopping Times Within 1sec: $40/50 \text{ msec} = 800 \text{ hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(383.3 \mu \text{s} \times 800) / 79] \times 31.6 = 122.66 \text{ msec}$

Channel 39 (2441MHz)-(3DH1)






Product	:	GSM Mobile Phone
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps(8DPSK_DH3)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	258.72	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6\text{sec}$, Hopping Times Within 1sec: $20/50\text{msec} = 400\text{hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(1.617 \text{ ms} \times 400)/79] \times 31.6 = 258.72\text{msec}$

Channel 39 (2441MHz) - (3DH3)






Product	:	GSM Mobile Phone
Test Item	:	Time of Occupancy (Dwell Time)
Test Site	:	TR-8
Test Mode	:	Transmitter-3Mbps(8DPSK_DH5)


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	299.83	< 400	Pass

Test Time Period: $0.4 \times 79 = 31.6 \text{sec}$, Hopping Times Within 1sec: $13/50 \text{msec} = 260 \text{ hops/sec}$.

- 2441MHz, The Maximum Occupancy Time Within 31.6sec: $[(2.883 \text{ ms} \times 280)/79] \times 31.6 = 299.83 \text{msec}$

Channel 39 (2441MHz) - (3DH5)





9. Peak Output Power


9.1. Test Equipment

Peak Output Power / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

9.2. Test Setup



9.3. Limit

- For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
- For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

Note: the conducted output power limit specified above is based on the use the antennas with

directional gains that do not exceed 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values above, as appropriate, by the amount in dB that the directional gain of antenna exceeds 6 dBi.

9.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss).

9.5. Uncertainty


The measurement uncertainty is defined as ± 1.0 dB

9.6. Test Result


Product	:	GSM Mobile Phone
Test Item	:	Power Output
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	-1.10	30.00	Pass
39	2441	-1.82	30.00	Pass
78	2480	-3.06	30.00	Pass


DH5 2402MHz



DH5 2441MHz




DH5 2480MHz




Product	:	GSM Mobile Phone
Test Item	:	Power Output
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	-0.82	30.00	Pass
39	2441	-1.58	30.00	Pass
78	2480	-2.95	30.00	Pass


2DH5 2402MHz



2DH5 2441MHz




2DH5 2480MHz




Product	:	GSM Mobile Phone
Test Item	:	Power Output
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
0	2402	-0.94	30.00	Pass
39	2441	-1.60	30.00	Pass
78	2480	-2.97	30.00	Pass


3DH5 2402MHz



3DH5 2441MHz



3DH5 2480MHz



10. Band-edge Compliance of RF Conducted Emissions


10.1. Test Equipment

Band-edge Compliance of RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

10.2. Test Setup



10.3. Limit

- Intentional radiators operating under the alternative provisions to the general emission limits as contained in 15.217 through 15.257 and in Subpart E of FCC part 15, must be designed to ensure that 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz

bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) of FCC part 15 is not required.

10.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation.

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge.

Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.


10.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


10.6. Test Result

Product	:	GSM Mobile Phone
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)

Channel 00 (2402MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)

Channel 00 (2402MHz)





Channel 78 (2480MHz)



Product	:	GSM Mobile Phone
Test Item	:	Band-edge Compliance of RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps(8DPSK_DH5)

Hopping Mode



11. Spurious RF Conducted Emissions


11.1. Test Equipment

Spurious RF Conducted Emissions / TR-8

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2012.04.30
Temperature/Humidity Meter	Zhicheng	ZC1-2	TR8-TH	2012.05.04

Note: All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

11.2. Test Setup



11.3. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in

Section 15.209(a) of FCC part 15 is not required.

11.4. Test Procedure

According to ANSI C63.10: 2009.

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.


11.5. Uncertainty

The measurement uncertainty is defined as ± 1.0 dB


11.6. Test Result

Product	:	GSM Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 1: Transmitter-1Mbps(GFSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




Product	:	GSM Mobile Phone
Test Item	:	Spurious RF Conducted Emissions
Test Mode	:	Mode 3: Transmitter-3Mbps(8DPSK_DH5)


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)




12. Radiated Emission Band Edge

12.1. Test Equipment

☒ Radiated Emission Band Edge / AC-5

Instrument	Manufacturer	Type No.	Serial No.	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2012.04.23
EMI Test Receiver	R&S	ESCI	100573	2012.04.23
Preamplifier	Quietek	AP-025C	CHM-0511006	2012.05.05
Preamplifier	Quietek	AP-180C	CHM-0602013	2012.05.05
Bilog Type Antenna	Schaffner	CBL6112B	2932	2011.11.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	499	2012.06.11
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2012.05.05
Temperature/Humidity Meter	zhicheng	ZC1-2	AC5-TH	2012.01.14

12.2. Test Setup



12.3. Limit

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) of FCC part 15.

12.4. Test Procedure

According to ANSI C63.10: 2009.

This test is required for any spurious emission or modulation product that falls in a Restricted Band, as defined in Section 15.205 of FCC part 15. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.4 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being

corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b) of FCC part 15.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209 of FCC Part 15. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit of FCC part 15.

If the emission on which a radiated measurement must be made is located at the edge of the authorized band of operation, then the alternative “marker-delta” method may be employed.

12.5. Uncertainty

The measurement uncertainty above 1G is defined as $\pm 3.9 \text{ dB}$
below 1G is defined as $\pm 3.8 \text{ dB}$


12.6. Test Result

All of the test result shown indicates the worst case, and spectrum analyzer parameters setting as shown below:

Peak detector: RBW = 1MHz, VBW = 3MHz, sweep time = 200ms;


Average detector: RBW = 1MHz, VBW = 10Hz, sweep time = auto.

Site: AC5	Time: 2011/09/04 - 13:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	61.191	30.006	-12.809	74.000	31.185	PK
2		*	2401.930	91.519	60.337	N/A	N/A	31.181	PK

Site: AC5	Time: 2011/09/04 - 13:10
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.446	17.261	-5.554	54.000	31.185	AV
2		*	2401.977	84.050	52.868	N/A	N/A	31.181	AV

Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 13:02
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	61.675	30.490	-12.325	74.000	31.185	PK
2		*	2401.930	96.165	64.983	N/A	N/A	31.181	PK

Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 13:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2402MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.450	17.265	-5.550	54.000	31.185	AV
2		*	2401.977	86.442	55.260	N/A	N/A	31.181	AV

Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 13:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.969	92.213	61.006	N/A	N/A	31.206	PK
2			2483.500	60.321	29.112	-13.679	74.000	31.209	PK
3			2483.753	63.217	32.008	-10.783	74.000	31.209	PK

Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 13:14
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	85.089	53.882	N/A	N/A	31.206	AV
2			2483.500	48.806	17.597	-5.194	54.000	31.209	AV

Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 13:14
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	95.730	64.523	N/A	N/A	31.206	PK
2			2483.500	59.940	28.731	-14.060	74.000	31.209	PK
3			2483.808	66.773	35.564	-7.227	74.000	31.209	PK

Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 13:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 1: Transmit at channel 2480MHz by DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.013	87.245	56.038	N/A	N/A	31.206	AV
2			2483.500	48.855	17.646	-5.145	54.000	31.209	AV

Engineer: Sunny	
Site: AC5	Time: 2011/09/04 - 15:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	59.117	27.932	-14.883	74.000	31.185	PK
2		*	2402.150	94.282	63.100	N/A	N/A	31.181	PK

Engineer: Sunny	
Site: AC5	Time: 2011/09/04 - 15:54
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.201	17.016	-5.799	54.000	31.185	AV
2		*	2402.008	86.193	55.011	N/A	N/A	31.181	AV

Engineer: Sunny	
Site: AC5	Time: 2011/09/04 - 15:55
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	58.608	27.423	-15.392	74.000	31.185	PK
2		*	2402.198	96.230	65.048	N/A	N/A	31.181	PK

Engineer: Sunny	
Site: AC5	Time: 2011/09/04 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.196	17.011	-5.804	54.000	31.185	AV
2		*	2402.008	86.633	55.451	N/A	N/A	31.181	AV

Engineer: Sunny	
Site: AC5	Time: 2011/09/04 - 15:57
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.167	95.047	63.840	N/A	N/A	31.206	PK
2			2483.500	58.925	27.716	-15.075	74.000	31.209	PK

Engineer: Sunny	
Site: AC5	Time: 2011/09/04 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	85.691	54.484	N/A	N/A	31.206	AV
2			2483.500	48.547	17.338	-5.453	54.000	31.209	AV

Engineer: Sunny	
Site: AC5	Time: 2011/09/04 - 16:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	97.637	66.430	N/A	N/A	31.206	PK
2			2483.500	59.667	28.458	-14.333	74.000	31.209	PK

Engineer: Sunny	
Site: AC5	Time: 2011/09/04 - 16:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: By Battery
Note: Mode 2: Transmit at channel 2480MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	88.505	57.298	N/A	N/A	31.206	AV
2			2483.500	48.531	17.322	-5.469	54.000	31.209	AV

Profile: 116S074R	Page No.: 53
Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 17:14
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: DC 3.7V
Note: Mode 3: Transmit at channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	61.449	30.264	-12.551	74.000	31.185	PK
2		*	2401.930	92.197	61.015	N/A	N/A	31.181	PK

Profile: 116S074R	Page No.: 54
Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 17:18
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: DC 3.7V
Note: Mode 3: Transmit at channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.449	17.264	-5.551	54.000	31.185	AV
2		*	2401.930	75.865	44.683	N/A	N/A	31.181	AV

Profile: 116S074R	Page No.: 55
Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 17:19
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: DC 3.7V
Note: Mode 3: Transmit at channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	61.317	30.132	-12.683	74.000	31.185	PK
2		*	2401.930	90.183	59.001	N/A	N/A	31.181	PK

Profile: 116S074R	Page No.: 56
Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 17:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: DC 3.7V
Note: Mode 3: Transmit at channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2390.000	48.395	17.210	-5.605	54.000	31.185	AV
2		*	2402.023	77.313	46.131	N/A	N/A	31.181	AV

Profile: 116S074R	Page No.: 57
Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 17:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: DC 3.7V
Note: Mode 3: Transmit at channel 2480MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	93.488	62.281	N/A	N/A	31.206	PK
2			2483.500	61.604	30.395	-12.396	74.000	31.209	PK

Profile: 116S074R	Page No.: 58
Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 17:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Horizontal
EUT: GSM Mobile Phone	Power: DC 3.7V
Note: Mode 3: Transmit at channel 2480MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.969	80.226	49.019	N/A	N/A	31.206	AV
2			2483.500	48.242	17.033	-5.758	54.000	31.209	AV

Profile: 116S074R	Page No.: 59
Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 17:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: DC 3.7V
Note: Mode 3: Transmit at channel 2480MHz by 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	93.631	62.424	N/A	N/A	31.206	PK
2			2483.500	60.971	29.762	-13.029	74.000	31.209	PK

Profile: 116S074R	Page No.: 60
Engineer: Jack	
Site: AC5	Time: 2011/09/04 - 17:31
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_499(1-18GHz)	Polarity: Vertical
EUT: GSM Mobile Phone	Power: DC 3.7V
Note: Mode 3: Transmit at channel 2480MHz by 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.002	80.275	49.068	N/A	N/A	31.206	AV
2			2483.500	48.181	16.972	-5.819	54.000	31.209	AV