


RF EXPOSURE REPORT



Report No.: 18070151-FCC-H

Applicant	Dayton Audio Division of Parts Express	
Product Name	Amplifier	
Model No.	DTA-120BT	
Serial No.	N/A	
Test Standard	FCC 2.1091:2017	
Test Date	February 01 to February 28, 2018	
Issue Date	March 01, 2018	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
Aaron Liang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	18070151-FCC-H
Page	3 of 10

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)	7
6.1 APPLICABLE STANDARD	7
6.2 TEST RESULT	8

1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070151-FCC-H	NONE	Original	March 01, 2018

2. Customer information

Applicant Name	Dayton Audio Division of Parts Express
Applicant Add	725 Pleasant Valley Rd Springboro, Ohio 45066 USA
Manufacturer	Vistron (Dong Guan) Audio Equipment Co.,Ltd
Manufacturer Add	NO.17 Ji Cai Street, Song Gang District, Qing Xi Town, Dong Guan City, Guang Dong Province, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Labview of SIEMIC version 2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Amplifier
Main Model:	DTA-120BT
Serial Model:	N/A
Equipment Category :	DTS
Antenna Gain:	Bluetooth/BLE: 0dBi
Antenna Type:	External Antenna
Input Power:	Adapter: Model: MKS-2405000C8 Input: 100-240V, 50/60Hz, 2.0A Max Output: 24V-5.0A
Trade Name :	N/A
FCC ID:	ZXZDTA-120BT
Type of Modulation:	Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	Bluetooth&BLE: 2402-2480 MHz
Number of Channels:	Bluetooth: 79CH BLE: 40CH
Port:	Please refer to user manual
Date EUT received:	January 31, 2018
Test Date(s):	February 01 to February 28, 2018

5. FCC §2.1091 - Maximum Permissible exposure (MPE)

6.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission' s guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

6.2 Test Result

Bluetooth Mode:

Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)
Output power	GFSK	Low	2402	1.811	2.5±1
		Mid	2441	2.208	2.5±1
		High	2480	3.177	2.5±1
	π /4 DQPSK	Low	2402	-0.995	0±1
		Mid	2441	0.812	0±1
		High	2480	0.664	0±1
	8DPSK	Low	2402	-0.558	0.4±1
		Mid	2441	1.073	0.4±1
		High	2480	0.930	0.4±1

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

Maximum output power at antenna input terminal: 3.5(dBm)

Maximum output power at antenna input terminal: 2.239(mW)

Prediction distance: >20 (cm)

Predication frequency: 2480 (MHz) High frequency

Antenna Gain (typical): 0 (dBi)

The worst case is power density at predication frequency at 20 cm: 0.000446(mW/cm²)

MPE limit for general population exposure at prediction frequency: 1.0 (mW/cm²)

0.000446 (mW/cm²) < 1.0 (mW/cm²)

Result: Pass

BLE Mode:

Type	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)
Output power	Low	2402	3.718	3.5±1
	Mid	2440	3.821	3.5±1
	High	2480	4.230	3.5±1

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

Maximum output power at antenna input terminal: 4.5(dBm)

Maximum output power at antenna input terminal: 2.818(mW)

Prediction distance: >20 (cm)

Predication frequency: 2480(MHz) High frequency

Antenna Gain (typical): 0(dBi)

The worst case is power density at predication frequency at 20 cm: 0.000561(mW/cm²)

MPE limit for general population exposure at prediction frequency: 1.0(mW/cm²)

0.000561(mW/cm²) < 1 (mW/cm²)

Result: Pass