



FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

Amcrest 4MP Pan/Tilt Wi-Fi Indoor Security Camera

MODEL NUMBER: IP4M-1041B

ADDITIONAL MODEL NUMBER: IP4M-1041W

PROJECT NUMBER: 4790465786-5

REPORT NUMBER: 4790465786-5-1

FCC ID: ZZ2-IP4M-1041

ISSUE DATE: Jul. 22, 2022

Prepared for

Amcrest Technologies LLC.

Prepared by

UL-CCIC COMPANY LIMITED

No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China

Tel: + 86-512-6808 6400

Fax: + 86-512-6808 4099

Website: www.ul.com

Form-ULID-008536-9 V1.0

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	07/22/2022	Initial Issue	



TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION.....	7
4.2. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT.....	8
5.2. MAXIMUM OUTPUT POWER.....	9
5.3. CHANNEL LIST	9
5.4. TEST CHANNEL CONFIGURATION.....	10
5.5. THE WORSE CASE POWER SETTING PARAMETER.....	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS.....	11
5.7. THE WORSE CASE CONFIGURATIONS.....	11
5.8. DESCRIPTION OF TEST SETUP.....	12
5.9. MEASURING INSTRUMENT AND SOFTWARE USED.....	13
6. MEASUREMENT METHODS.....	14
7. ANTENNA PORT TEST RESULTS	15
7.1. TEST ENVIRONMENT.....	15
7.2. ON TIME AND DUTY CYCLE.....	16
7.3. 6 dB BANDWIDTH.....	19
7.4. CONDUCTED POWER.....	27
7.5. POWER SPECTRAL DENSITY.....	29
7.6. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS.....	37
7.7. RADIATED TEST RESULTS	68
7.7.1. LIMITS AND PROCEDURE	68
7.7.2. RESTRICTED BANDEDGE	73
7.7.3. SPURIOUS EMISSIONS.....	90
8. AC POWER LINE CONDUCTED EMISSIONS.....	147
9. ANTENNA REQUIREMENTS	150



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Amcrest Technologies LLC.
Address: 16727 Park Row Dr, Houston, TX 77084, United States of America

Manufacturer Information

Company Name: Amcrest Technologies LLC.
Address: 16727 Park Row Dr, Houston, TX 77084, United States of America

EUT Description

Product Name: Amcrest 4MP Pan/Tilt Wi-Fi Indoor Security Camera
Model Name: IP4M-1041B
Additional No.: IP4M-1041W
Sample Number: 5102652
Data of Receipt Sample: Jun 28, 2022
Date Tested: Jun 28, 2022~ Jul. 21, 2022

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR Part 15 Subpart C	PASS



Summary of Test Results			
Clause	Test Items	FCC Rules	Test Results
1	6db DTS Bandwidth	FCC 15.247 (a) (2)	Complied
2	Conducted Power	FCC 15.247 (b) (3)	Complied
3	Power Spectral Density	FCC 15.247 (e)	Complied
4	Conducted Band edge And Spurious emission	FCC 15.247 (d)	Complied
5	Radiated Band edges and Spurious emission	FCC 15.247 (d) FCC 15.209 FCC 15.205	Complied
6	Conducted Emission Test For AC Power Port	FCC 15.207	Complied
7	Antenna Requirement	FCC 15.203	Complied
Remark: The measurement result for the sample received is <Pass> according to < ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15C> when <Accuracy Method> decision rule is applied.			

Prepared By:

Tom Tang

Tom Tang

Reviewed By:

Leon Wu

Leon Wu

Authorized By:

Chris Zhong

Chris Zhong
Laboratory Leader



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056; CAB No.:CN0073) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
---------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.1dB
Radiation Emission test(include Fundamental emission) (9KHz-30MHz)	3.4dB
Radiation Emission test(include Fundamental emission) (30MHz-1GHz)	3.4dB
Radiation Emission test (1GHz to 26GHz)(include Fundamental emission)	3.7dB (1GHz-18Gz)
	4.0dB (18GHz-26.5Gz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Product Name:	Amcrest 4MP Pan/Tilt Wi-Fi Indoor Security Camera
Model No.:	IP4M-1041B
Operating Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Type of Modulation:	IEEE for 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE for 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n (HT20 and HT40): OFDM (64QAM, 16QAM, QPSK, BPSK)
Channels Step:	Channels with 5MHz step
Test software of EUT:	Secure CRT (manufacturer declare)
Antenna Type	IFA Antenna
Antenna Gain:	2.84 dBi Remark: This data is provided by customer and our lab isn't responsible for this data
Test Voltage	AC120V

Remark:

Model No.:

No.:	Name:	No.:	Name:
1	IP4M-1041B	2	IP4M-1041W

Only the main model **IP4M-1041B** was tested and only the data of this model is shown in this test report. Since Their material, types of enclosure, antenna location, electrical circuit design, layout, components used and internal wiring are identical, only the name and color of the models are different.



5.2. MAXIMUM OUTPUT POWER

Number of Transmit Chains (NTX)	IEE Std. 802.11	Channel Number	Max AV Conducted Power (dBm)
1	IEEE 802.11B SISO	1-11[11]	15.28
1	IEEE 802.11G SISO	1-11[11]	12.97
1	IEEE 802.11nHT20	1-11[11]	11.93
1	IEEE 802.11nHT40	3-9[7]	9.67

5.3. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452		

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447		



5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
WiFi TX(802.11b)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11g)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT20)	CH 1, CH 6, CH 11	2412MHz, 2437MHz, 2462MHz
WiFi TX(802.11n HT40)	CH 3, CH 6, CH 9	2422MHz, 2437MHz, 2452MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		Secure CRT (manufacturer declare)					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	N/A	N/A	N/A	/		
802.11g	1	N/A	N/A	N/A			
802.11n HT20	1	N/A	N/A	N/A			
802.11n HT40	1	/			N/A	N/A	N/A

Remark: Although this EUT looks like it has two antennas, but the only one antenna is working, another is no function just for decoration.



5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2400-2483.5	IFA Antenna	2.84

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.
IEEE 802.11g	☒ 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.
IEEE 802.11N (HT20)	☒ 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.
IEEE 802.11N (HT40)	☒ 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.

5.7. THE WORSE CASE CONFIGURATIONS

For the product, there only one transmission antenna, and worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0



**5.9. MEASURING INSTRUMENT AND SOFTWARE USED**

Conducted Emissions (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
☒	EMI Test Receiver	R&S	ESR3	126700	2020-12-05	2021-12-04	2022-12-03
☒	Two-Line V- Network	R&S	ENV216	126701	2020-12-05	2021-12-04	2022-12-03
Software							
Used	Description		Manufacturer		Name	Version	
☒	Test Software for Conducted disturbance		R&S		EMC32	Ver. 9.25	
Radiated Emissions (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
☒	Spectrum Analyzer	Keysight	N9010B	155727	2021-05-09	2022-04-09	2023-04-08
☒	EMI test receiver	R&S	ESR26	126703	2020-12-05	2021-12-04	2022-12-03
☒	Receiver Antenna (9kHz-30MHz)	Schwarzbeck	FMZB 1513	155456	2018-06-15	2021-06-03	2024-06-02
☒	Receiver Antenna (30MHz-1GHz)	SunAR RF Motion	JB1	177821	2019-01-28	2022-01-18	2025-01-17
☒	Receiver Antenna (1GHz-18GHz)	R&S	HF907	126705	2018-01-29	2022-02-28	2025-02-27
☒	Receiver Antenna (18GHz-26.5GHz)	ETS	3160-10	155565	2019-01-05	2021-07-15	2024-07-14
☒	Pre-amplification (To 18GHz)	Compliance Direction System Inc.	PAP-1G18- 50	177825	2021-03-18	2022-03-01	2023-02-28
☒	Pre-amplification (To 26.5GHz)	R&S	SCU-26D	135391	2021-12-05	2022-12-04	2022-12-03
☒	Band Reject Filter	Wainwright	WRCJV8- 2350-2400- 2483.5- 2533.5-40SS	1	2021-05-09	2022-04-09	2023-04-08
☒	Highpass Filter	Wainwright	WHKX10- 2700-3000- 18000-40SS	2	2021-05-09	2022-04-09	2023-04-08
Software							
Used	Description		Manufacturer	Name		Version	
☒	Test Software for Radiated disturbance		Tonscend	JS36-RSE		4.0.0.1	
Other instruments							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
☒	Spectrum Analyzer	Keysight	N9010B	155368	2021-05-09	2022-04-09	2023-04-08
☒	Power Meter	Keysight	U2021XA	155370	2021-05-09	2022-04-09	2023-04-08



6. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6dB Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Conducted Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.2.3 (Method AVGPM)
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4 (Method PKPSD)
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7
7	Conducted Emission Test For AC Power Port	ANSI C63.10-2013	6.2



7. ANTENNA PORT TEST RESULTS

7.1. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests
Relative Humidity	56.3%
Atmospheric Pressure:	101kPa
Temperature	23.1°C



7.2. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

FCC KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



RESULTS



Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (KHz)	Final Minimum VBW (KHz)
11B	12.42	12.60	0.986	98.6	0.06	/	0.01(Note4)
11G	2.06	2.30	0.896	89.6	0.48	0.49	1
11N HT20	1.92	2.18	0.881	88.1	0.55	0.52	1
11N HT40	0.95	1.19	0.798	79.8	0.98	1.05	2

Note: 1) Duty Cycle Correction Factor= $10\log(1/x)$.

2) Where: x is Duty Cycle(Linear)

3) Where: T is On Time (transmit duration)



4) The minimum VBW should be 10Hz if the duty cycle is over 98%.



Form-ULID-008536-9 V1.0

UL-CCIC COMPANY LIMITED

This report shall not be reproduced except in full, without the written approval of UL-CCIC COMPANY LIMITED.





7.3. 6 dB BANDWIDTH

LIMITS

FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247(a)(2)	6dB Bandwidth	$\geq 500\text{KHz}$	2400-2483.5


TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyzer and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	For 6dB Bandwidth :100K
VBW	For 6dB Bandwidth : $\geq 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


TEST SETUP












RESULTS



Test Mode	Test Channel	6dB bandwidth (MHz)	Result
11B	LCH	9.040	Pass
	MCH	9.040	Pass
	HCH	9.040	Pass
11G	LCH	16.320	Pass
	MCH	16.360	Pass
	HCH	16.360	Pass
11N HT20	LCH	17.600	Pass
	MCH	17.560	Pass
	HCH	17.200	Pass
11N HT40	LCH	35.440	Pass
	MCH	34.320	Pass
	HCH	35.760	Pass


















7.4. CONDUCTED POWER


LIMITS

FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5

TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power Meter.
Measure the power of each channel.
AVG Detector use for AVG result.

TEST SETUP





RESULTS

Test Mode	Test Channel	Measurement Output Power (AV)	10log(1/x) Factor	Maximum Conducted Output Power (AV)	Result
		dBm	dB	dBm	
11B	LCH	14.87	N/A(Remark3)	14.87	Pass
	MCH	15.28	N/A(Remark3)	15.28	Pass
	HCH	14.41	N/A(Remark3)	14.41	Pass
11G	LCH	12.26	0.48	12.74	Pass
	MCH	11.83	0.48	12.31	Pass
	HCH	12.49	0.48	12.97	Pass
11N HT20	LCH	11.38	0.55	11.93	Pass
	MCH	10.54	0.55	11.09	Pass
	HCH	10.75	0.55	11.30	Pass
11N HT40	LCH	8.50	0.98	9.48	Pass
	MCH	8.69	0.98	9.67	Pass
	HCH	8.64	0.98	9.62	Pass

Remark:

- 1) For all the test results has been adjusted the duty cycle factor.
- 2) For Correction Factor is refer to the result in section 7.2
- 3) For duty cycle is higher than 98% and according to KDB 558074, it is not required to be adjusted with duty factor for output power



7.5. POWER SPECTRAL DENSITY

LIMITS

FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE


Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


TEST SETUP





RESULTS

Test Mode	Test Channel	Maximum Peak power spectral density (dBm/30kHz)	Result
11B	LCH	2.04	Pass
	MCH	2.82	Pass
	HCH	1.34	Pass
11G	LCH	-2.94	Pass
	MCH	-3.8	Pass
	HCH	-3.97	Pass
11N HT20	LCH	-3.08	Pass
	MCH	-3.27	Pass
	HCH	-4.14	Pass
11N HT40	LCH	-6.18	Pass
	MCH	-4.99	Pass
	HCH	-5.24	Pass



Test Mode	Test Channel	Verdict
11B	LCH	PASS

Spectrum Analyzer 1
Swept SA

KEYSIGHT Input: RF Coupling: DC Align: Auto

#Atten: 20 dB PNO: Best Wide Gate: Off #Avg Type: Power (RMS) 1 2 3 4 5 6
Corrections: Off Preamp: Off Avg Hold: 200/200 M W W W W W W W
Freq Ref: Int (S) IF Gain: Low Trig: Free Run P P P P P P P

Center Frequency: 2.412000000 GHz Settings

Span: 13.5600000 MHz
Sweep Span
Zero Span
Full Span

Start Freq: 2.405220000 GHz
Stop Freq: 2.418780000 GHz
AUTO TUNE



CF Step: 1.356000 MHz
Auto Man
Freq Offset: 0 Hz
X Axis Scale: Log Lin
Signal Track: (Span Zoom)



1 Spectrum
Scale Div 10 dB
Ref Lvl Offset 8.15 dB
Ref Level 10.00 dBm
Mkr1 2.410508 GHz
2.04 dBm



Center 2.412000 GHz
#Res BW 30 kHz
#Video BW 100 kHz
Span 13.56 MHz
Sweep 14.3 ms (1001 pts)



Jun 30, 2022 4:59:05 PM



Form-ULID-008536-9 V1.0













7.6. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

LIMITS

FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	At least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100K
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


settings:

Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100K
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

TEST SETUP







Part I :Conducted Bandedge



RESULTS TABLE



Test Mode	Test Antenna	Test Channel	Test Result	Verdict
11B	Antenna 1	LCH	See the test graphs	PASS
		HCH	See the test graphs	PASS
11G	Antenna 1	LCH	See the test graphs	PASS
		HCH	See the test graphs	PASS
11N HT20	Antenna 1	LCH	See the test graphs	PASS
		HCH	See the test graphs	PASS
11N HT40	Antenna 1	LCH	See the test graphs	PASS
		HCH	See the test graphs	PASS





TEST GRAPHS











Part II :Conducted Emission

Test Result Table

Test Mode	Test Antenna	Channel	Pref(dBm)	Puw(dBm)	Verdict
11B SISO	Antenna 1	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS
11G SISO	Antenna 1	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS
11N HT20	Antenna 1	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS
11N HT40	Antenna 1	LCH	See the test graphs	<Limit	PASS
		MCH	See the test graphs	<Limit	PASS
		HCH	See the test graphs	<Limit	PASS



Test Plots

Test Mode	Channel	Verdict
11B	LCH	PASS


Pref test Plot





Puw test Plot

LCH SPURIOUS EMISSION 30MHz~1GHz



LCH SPURIOUS EMISSION 1GHz~26GHz





Test Mode	Channel	Verdict
11B	MCH	PASS


Pref test Plot





Puw test Plot

MCH SPURIOUS EMISSION 30MHz~1GHz



MCH SPURIOUS EMISSION 1GHz~26GHz





Test Mode	Channel	Verdict
11B	HCH	PASS


Pref test Plot





Puw test Plot

HCH SPURIOUS EMISSION 30MHz~1GHz



HCH SPURIOUS EMISSION 1GHz~26GHz





Test Mode	Channel	Verdict
11G	LCH	PASS

Pref test Plot

