



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM161100948202

Page: 1 of 85

FCC REPORT

Application No.: SZEM1611009482CR
Applicant: Camino International Limited
Manufacturer: Camino International Limited
Factory: Camino Industrial (Huizhou) Co. Ltd.
Product Name:
1. IRONMAN MARK XLVI Helmet Bluetooth Wireless Speaker
2. STAR WARS- Darth Vader Bluetooth Wireless Speaker
3. STAR WARS- Rogue One K-2SO Helmet Mini Bluetooth Wireless Speaker
4. STAR WARS- Deathtrooper Bluetooth Wireless Speaker
5. STAR WARS - Stormtrooper Bluetooth Wireless Speaker
Model No.(EUT): 761555
Add Model No.: 761566, 761554, 761568, 761567
Trade Mark: Disney
FCC ID: ZZX555
Standards: 47 CFR Part 15, Subpart C (2015)
Date of Receipt: 2016-11-10
Date of Test: 2016-11-21 to 2016-11-25
Date of Issue: 2016-11-28

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2016-11-28		Original

Authorized for issue by:				
Tested By		 (Peter Geng) /Project Engineer		2016-11-25
				Date
Checked By		 (Eric Fu) /Reviewer		2016-11-28
				Date



3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS



4 Contents

	Page
1 COVER PAGE	1
2 VERSION.....	2
3 TEST SUMMARY	3
4 CONTENTS.....	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST ENVIRONMENT.....	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST LOCATION	7
5.6 TEST FACILITY	8
5.7 DEVIATION FROM STANDARDS	8
5.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	8
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	8
5.10 EQUIPMENT LIST	9
6 TEST RESULTS AND MEASUREMENT DATA.....	11
6.1 ANTENNA REQUIREMENT.....	11
6.2 CONDUCTED EMISSIONS	12
6.3 CONDUCTED PEAK OUTPUT POWER.....	16
6.4 20dB OCCUPY BANDWIDTH.....	23
6.5 CARRIER FREQUENCIES SEPARATION	29
6.6 HOPPING CHANNEL NUMBER	33
6.7 DWELL TIME	36
6.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS	47
6.9 SPURIOUS RF CONDUCTED EMISSIONS	54
6.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	69
6.11 RADIATED SPURIOUS EMISSION	71
6.11.1 Radiated Emission below 1GHz.....	74
6.11.2 Transmitter Emission above 1GHz.....	76
6.12 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	78
7 PHOTOGRAPHS - EUT TEST SETUP.....	84
7.1 CONDUCTED EMISSION	84
7.2 RADIATED EMISSION	84
7.3 RADIATED SPURIOUS EMISSION	85
8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....	85



5 General Information

5.1 Client Information

Applicant:	Camino International Limited
Address of Applicant:	Flat A, 3rd Floor, International Industrial Building, 501-503 Castle Peak Road, Cheung Sha Wan, Kowloon, Hong Kong
Manufacturer:	Camino International Limited
Address of Manufacturer:	Flat A, 3rd Floor, International Industrial Building, 501-503 Castle Peak Road, Cheung Sha Wan, Kowloon, Hong Kong
Factory:	Camino Industrial (Huizhou) Co. Ltd.
Address of Factory:	Lidong Industrial Estate, Jiutan, Yuanzhou, Boluo, Huizhou, Guangdong, China

5.2 General Description of EUT

Product Name:	1. IRONMAN MARK XLVI Helmet Bluetooth Wireless Speaker 2. STAR WARS- Darth Vader Bluetooth Wireless Speaker 3. STAR WARS- Rogue One K-2SO Helmet Mini Bluetooth Wireless Speaker 4. STAR WARS- Deathtrooper Bluetooth Wireless Speaker 5. STAR WARS - Stormtrooper Bluetooth Wireless Speaker
Model No.:	76155
Trade Mark:	Disney
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth 4.1 single
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Sample Type:	Portable production
Antenna Type:	Chip Antenna
Antenna Gain:	0dBi
Power Supply	DC 3.7V, 850mAh rechargeable battery which charged by AC adapter
Cable:	USB charging line: 78cm, unshielded

Remark:

Model No.: 761555, 761566, 761554, 761568, 761567

Only the model 761555 was tested, since the circuit design, PCB layout, electrical components used, internal wiring and functions were identical for the above models, only different on model number and exterior.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 6 of 85

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz



5.3 Test Environment

Operating Environment:	
Temperature:	24.0 °C
Humidity:	55 % RH
Atmospheric Pressure:	1010 mbar

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Adapter	Apple	A1357 W010A051

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 9 of 85

5.10 Equipment List

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2016-09-28	2017-09-28
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2016-09-28	2017-09-28
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2016-09-28	2017-09-28
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2016-05-13	2017-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2016-10-09	2017-10-09
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2014-11-01	2017-11-01
4	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17
5	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEM003-12	2014-11-24	2017-11-24
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2016-04-25	2017-04-25
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
9	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015-05-13	2018-05-13



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM161100948202

Page: 10 of 85

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2016-07-19	2017-07-19
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2014-11-24	2017-11-24
7	Horn Antenna(26GHz-40GHz)	A.H.Systems, inc.	SAS-573	SEM003-13	2015-02-12	2018-02-12
8	Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
9	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.	



6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 13 of 85

Test Setup:	
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel. Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation at the lowest channel is the worst case. Charge + Transmitting mode Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM161100948202
Page: 14 of 85

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



Site : Shielding Room
Condition : CE LINE
Job NO : 9482CR
Mode : Charging+Tx


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.43511	0.02	9.60	34.48	44.09	57.15	-13.06	QP
2	0.43511	0.02	9.60	22.83	32.45	47.15	-14.70	AVERAGE
3	1.310	0.03	9.60	29.96	39.59	56.00	-16.41	QP
4	1.310	0.03	9.60	18.43	28.06	46.00	-17.94	AVERAGE
5	2.088	0.03	9.64	23.06	32.72	46.00	-13.28	AVERAGE
6	2.088	0.03	9.64	32.16	41.82	56.00	-14.18	QP
7	3.943	0.02	9.63	30.00	39.65	56.00	-16.35	QP
8	3.943	0.02	9.63	19.97	29.62	46.00	-16.38	AVERAGE
9	5.249	0.03	9.65	28.45	38.13	50.00	-11.87	AVERAGE
10	5.249	0.03	9.65	34.90	44.58	60.00	-15.42	QP
11	7.446	0.09	9.68	37.54	47.32	60.00	-12.68	QP
12	7.446	0.09	9.68	24.91	34.68	50.00	-15.32	AVERAGE



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 15 of 85

Neutral line:



Site : Shielding Room
Condition : CE NEUTRAL
Job NO : 9482CR
Mode : Charging+Tx


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.43742	0.02	9.62	35.48	45.12	57.11	-11.99	QP
2	0.43742	0.02	9.62	24.86	34.50	47.11	-12.61	AVERAGE
3	0.57923	0.02	9.63	23.69	33.34	46.00	-12.66	AVERAGE
4	0.57923	0.02	9.63	33.96	43.61	56.00	-12.39	QP
5	1.338	0.03	9.65	29.41	39.09	56.00	-16.91	QP
6	1.338	0.03	9.65	21.40	31.08	46.00	-14.92	AVERAGE
7	2.190	0.03	9.66	24.87	34.56	46.00	-11.44	AVERAGE
8	2.190	0.03	9.66	31.03	40.72	56.00	-15.28	QP
9	4.797	0.02	9.71	37.06	46.79	56.00	-9.21	QP
10	4.797	0.02	9.71	25.82	35.55	46.00	-10.45	AVERAGE
11	6.988	0.08	9.74	35.91	45.72	50.00	-4.28	AVERAGE
12	6.988	0.08	9.74	39.16	48.98	60.00	-11.02	QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.



6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.5
Test Setup:	 <i>Remark:</i> Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	20.97dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 17 of 85

Measurement Data

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-0.09	20.97	Pass
Middle	0.08	20.97	Pass
Highest	0.11	20.97	Pass
$\pi/4$ DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-1.78	20.97	Pass
Middle	-1.60	20.97	Pass
Highest	-1.56	20.97	Pass
8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-1.63	20.97	Pass
Middle	-1.45	20.97	Pass
Highest	-1.43	20.97	Pass




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM161100948202
Page: 18 of 85

Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 19 of 85

Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 20 of 85

Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 21 of 85

Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------



Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------






SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch


Report No.: SZEM161100948202
Page: 22 of 85

Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------





6.4 20dB Occupancy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.7
Test Setup:	
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data

Test channel	20dB Occupancy Bandwidth (kHz)		
	GFSK	$\pi/4$ DQPSK	8DPSK
Lowest	928	1221	1221
Middle	923	1221	1221
Highest	928	1221	1216




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202


Page: 24 of 85

Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------



Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 25 of 85

Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------



Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 26 of 85

Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 27 of 85

Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------



Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM161100948202

Page: 28 of 85

Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------



6.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.2
Test Setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 30 of 85

GFSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Middle	1002	619	Pass
$\pi/4$ DQPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Middle	1002	814	Pass
8DPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Middle	1002	814	Pass

Note: According to section 6.4,

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	928	619
$\pi/4$ DQPSK	1221	814
8DPSK	1221	814




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202


Page: 31 of 85

Test plot as follows:

Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------



Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------






SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch


Report No.: SZEM161100948202
Page: 32 of 85

Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------





6.6 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.3
Test Setup:	
Limit:	At least 15 channels
Test Mode:	Hopping transmitting with all kind of modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data

Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM161100948202
Page: 34 of 85

Test plot as follows

Test mode:	GFSK
------------	------



Test mode:	$\pi/4$ DQPSK
------------	---------------






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202


Page: 35 of 85

Test mode:	8DPSK
------------	-------





6.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013 Section 7.8.4
Test Setup:	
Instruments Used:	Refer to section 5.10 for details
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Measurement Data

Mode	Packet	Dwell time (second)	Limit (second)
GFSK	DH1	0.11	≤0.4
	DH3	0.23	≤0.4
	DH5	0.38	≤0.4
π/4DQPSK	2-DH1	0.11	≤0.4
	2-DH3	0.23	≤0.4
	2-DH5	0.38	≤0.4
8DPSK	3-DH1	0.11	≤0.4
	3-DH3	0.23	≤0.4
	3-DH5	0.38	≤0.4



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM161100948202

Page: 37 of 85

Remark:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

On (ms)*total number=dwell time (ms)

The middle channel (2441MHz), as below:

DH1 time slot=0.396 (ms)*total number=106.92 (ms)

DH3 time slot=1.655 (ms)* total number = 231.70 (ms)

DH5 time slot=2.917 (ms)* total number = 379.21 (ms)

2-DH1 time slot=0.408 (ms)*total number=110.16 (ms)

2-DH3 time slot=1.651 (ms)* total number = 231.14 (ms)

2-DH5 time slot=2.913 (ms)* total number = 378.69 (ms)

3-DH1 time slot=0.408 (ms)*total number=110.16 (ms)

3-DH3 time slot=1.659 (ms)* total number = 232.26 (ms)

3-DH5 time slot=2.909 (ms)* total number = 378.17 (ms)





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 38 of 85

Test plot as follows:

Test Packet:	DH1
--------------	-----









SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 39 of 85

Test Packet:	DH3
--------------	-----



Test Packet:	DH5
--------------	-----









SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 41 of 85

Test Packet:	2-DH1
--------------	-------



Test Packet:	2-DH3
--------------	-------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 43 of 85

Test Packet:	2-DH5
--------------	-------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch



Report No.: SZEM161100948202
Page: 44 of 85

Test Packet:	3-DH1
--------------	-------



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Test Packet:	3-DH3
--------------	-------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM161100948202
Page: 46 of 85

Test Packet:	3-DH5
--------------	-------





6.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 Section 7.8.6
Test Setup:	 Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 48 of 85

Test plot as follows:

Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 49 of 85

Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 50 of 85

Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 51 of 85

Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 52 of 85

Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM161100948202
Page: 53 of 85

Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------





6.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 Section 7.8.8
Test Setup:	 Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 55 of 85

Test plot as follows:


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 56 of 85



Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 57 of 85







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 58 of 85

Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 59 of 85




Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------





Page: 60 of 85





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 61 of 85

Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 62 of 85





Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 63 of 85







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 64 of 85


Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 65 of 85



Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 66 of 85







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 67 of 85

Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------







6.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:
The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section. The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.	
Compliance for section 15.247(a)(1)	
According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. • Number of shift register stages: 9 • Length of pseudo-random sequence: $2^9 - 1 = 511$ bits • Longest sequence of zeros: 8 (non-inverted signal) <i>Linear Feedback Shift Register for Generation of the PRBS sequence</i> An example of Pseudorandom Frequency Hopping Sequence as follow: Each frequency used equally on the average by each transmitter. According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.	
Compliance for section 15.247(g)	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM161100948202

Page: 70 of 85

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



6.11 Radiated Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Site:	Below 1GHz: Measurement Distance: 3m (Semi-Anechoic Chamber) Above 1GHz: Measurement Distance: 3m (Full-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202


Page: 73 of 85

	EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel (2402MHz), the middle channel (2441MHz), the Highest channel (2480MHz) i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode, Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass



6.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Charge + Transmitting	Vertical



Condition: 3m VERTICAL

Job No. : 9482CR

Test mode: Charge + TX mode


		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	31.95	0.60	17.61	27.35	37.79	28.65	40.00	-11.35
2	54.26	0.80	8.06	27.28	33.31	14.89	40.00	-25.11
3	96.10	1.16	8.94	27.21	35.18	18.07	43.50	-25.43
4	263.82	1.74	12.58	26.50	30.09	17.91	46.00	-28.09
5	601.43	2.70	19.84	27.54	26.98	21.98	46.00	-24.02
6	900.15	3.60	23.20	26.78	26.33	26.35	46.00	-19.65



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202
Page: 75 of 85

Test mode:	Charge + Transmitting	Horizontal
------------	-----------------------	------------



Condition: 3m HORIZONTAL

Job No. : 9482CR

Test mode: Charge + TX mode

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	31.95	0.60	17.61	27.35	28.45	19.31	40.00	-20.69
2	83.23	1.10	8.02	27.22	31.58	13.48	40.00	-26.52
3	96.10	1.16	8.94	27.21	31.16	14.05	43.50	-29.45
4	267.55	1.76	12.65	26.49	27.98	15.90	46.00	-30.10
5	457.51	2.44	17.17	27.48	26.78	18.91	46.00	-27.09
6	982.62	3.68	23.60	26.40	25.20	26.08	54.00	-27.92



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 76 of 85

6.11.2 Transmitter Emission above 1GHz

Test mode:		GFSK(DH1)		Test channel:		Lowest		Remark:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3831.060	32.93	7.75	38.62	45.63	47.69	74	-26.31	Vertical	
4804.000	34.10	8.87	39.03	49.33	53.27	74	-20.73	Vertical	
6051.874	34.73	10.49	38.97	44.71	50.96	74	-23.04	Vertical	
7206.000	35.60	10.68	38.18	45.09	53.19	74	-20.81	Vertical	
9608.000	37.10	12.50	36.99	39.23	51.84	74	-22.16	Vertical	
12050.440	37.63	14.52	38.35	39.40	53.20	74	-20.80	Vertical	
3825.521	32.93	7.75	38.62	45.98	48.04	74	-25.96	Horizontal	
4804.000	34.10	8.87	39.03	53.14	57.08	74	-16.92	Horizontal	
6069.413	34.74	10.47	38.96	44.64	50.89	74	-23.11	Horizontal	
7206.000	35.60	10.68	38.18	44.43	52.53	74	-21.47	Horizontal	
9608.000	37.10	12.50	36.99	39.70	52.31	74	-21.69	Horizontal	
12067.890	37.63	14.50	38.37	39.59	53.35	74	-20.65	Horizontal	

Test mode:		GFSK(DH1)		Test channel:		Middle		Remark:	Average
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Cable Loss (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit (dB)	Polarization	
4804.000	34.10	8.87	39.03	47.01	50.95	54	-3.05	Horizontal	

Test mode:		GFSK(DH1)		Test channel:		Middle		Remark:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Cable Loss (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit (dB)	Polarization	
3329.395	31.80	7.59	38.38	48.99	50.00	74	-24.00	Vertical	
4882.000	34.18	8.98	39.06	51.24	55.34	74	-18.66	Vertical	
6078.201	34.74	10.46	38.95	43.62	49.87	74	-24.13	Vertical	
7323.000	35.54	10.72	38.06	44.34	52.54	74	-21.46	Vertical	
9764.000	37.10	12.58	36.91	40.45	53.22	74	-20.78	Vertical	
11605.530	37.50	14.13	37.92	39.68	53.39	74	-20.61	Vertical	
3836.607	32.94	7.75	38.63	44.49	46.55	74	-27.45	Horizontal	
4882.000	34.18	8.98	39.06	51.65	55.75	74	-18.25	Horizontal	
6078.201	34.74	10.46	38.95	44.06	50.31	74	-23.69	Horizontal	
7323.000	35.54	10.72	38.06	44.44	52.64	74	-21.36	Horizontal	
9764.000	37.10	12.58	36.91	39.08	51.85	74	-22.15	Horizontal	
11860.170	37.53	14.41	38.17	39.65	53.42	74	-20.58	Horizontal	



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 77 of 85

Test mode:		GFSK(DH1)		Test channel:	Middle		Remark:		Average
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Cable Loss (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit (dB)	Polarization	
4882.000	34.18	8.98	39.06	46.31	50.41	54	-3.59	Vertical	
4882.000	34.18	8.98	39.06	46.61	50.71	54	-3.29	Horizontal	

Test mode:		GFSK(DH1)		Test channel:		Highest		Remark:		Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit (dB)	Polarization		
3898.160	33.00	7.78	38.66	45.15	47.27	74	-26.73	Vertical		
4960.000	34.26	9.09	39.09	49.60	53.86	74	-20.14	Vertical		
6087.002	34.74	10.45	38.94	44.82	51.07	74	-22.93	Vertical		
7440.000	35.60	10.77	37.94	43.78	52.21	74	-21.79	Vertical		
9920.000	37.22	12.67	36.84	39.76	52.81	74	-21.19	Vertical		
11980.900	37.59	14.54	38.28	39.96	53.81	74	-20.19	Vertical		
3776.027	32.81	7.73	38.60	45.09	47.03	74	-26.97	Horizontal		
4960.000	34.26	9.09	39.09	49.02	53.28	74	-20.72	Horizontal		
6274.796	34.80	10.21	38.83	44.38	50.56	74	-23.44	Horizontal		
7440.000	35.60	10.77	37.94	44.36	52.79	74	-21.21	Horizontal		
9920.000	37.22	12.67	36.84	40.11	53.16	74	-20.84	Horizontal		
12368.410	37.70	14.26	38.68	40.19	53.47	74	-20.53	Horizontal		

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the above measurements were shown in the report.



6.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013		
Test Site:	Below 1GHz: Measurement Distance: 3m (Semi-Anechoic Chamber) Above 1GHz: Measurement Distance: 3m (Full-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 79 of 85

Test Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel h. Test the EUT in the lowest channel , the Highest channel i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode, Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 80 of 85

Test plot as follows:

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	------------	---------------	--------	---------	------	----------



Condition: 3m Vertical

Job No: : 9482CR

Mode: : 2402 Band edge

: BT P=5

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	28.57	38.14	64.90	60.67	74.00	-13.33
2	av 2390.000	5.34	28.57	38.14	49.85	45.62	54.00	-8.38
3	pp 2401.843	5.35	28.61	38.15	97.50	93.31	74.00	19.31




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 81 of 85

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	------------	---------------	--------	---------	------	------------



Condition: 3m HORIZONTAL

Job No: : 9482CR

Mode: : 2402 Band edge

: BT P=5

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	28.57	38.14	59.02	54.79	74.00	-19.21
2 av	2390.000	5.34	28.57	38.14	46.41	42.18	54.00	-11.82
3 pp	2402.250	5.35	28.61	38.15	93.59	89.40	74.00	15.40




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 82 of 85

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	------------	---------------	---------	---------	------	----------



Condition: 3m Vertical

Job No: : 9482CR

Mode: : 2480 Band edge

: BT P=5

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2480.204	5.41	28.97	38.15	95.93	92.16	74.00	18.16
2	2483.500	5.41	28.98	38.15	73.95	70.19	74.00	-3.81
3 av	2483.500	5.41	28.98	38.15	54.39	50.63	54.00	-3.37




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM161100948202

Page: 83 of 85

Worse case mode:	GFSK(DH5)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	-----------	---------------	---------	---------	------	------------



Condition: 3m HORIZONTAL

Job No: : 9482CR

Mode: : 2480 Band edge

: BT P=5

		Cable	Ant	Preamp	Read	Limit	Over
	Freq	Loss	Factor	Factor	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp	2479.855	5.41	28.97	38.15	92.51	88.74	74.00 14.74
2	2483.500	5.41	28.98	38.15	68.63	64.87	74.00 -9.13
3 av	2483.500	5.41	28.98	38.15	54.33	50.57	54.00 -3.43

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor




7 Photographs - EUT Test Setup

Test Model No.: 761555

7.1 Conducted Emission




7.2 Radiated Emission





7.3 Radiated Spurious Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1611009482CR.