



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170100039203
Page: 1 of 92

TEST REPORT

Application No.: SZEM1701000392CR
Applicant: Camino International Limited
Address of Applicant: Flat A, 3rd Floor, International Industrial Building, 501-503 Castle Peak Road, Cheung Sha Wan, Kowloon, Hong Kong
Manufacturer: Camino International Limited
Address of Manufacturer: Flat A, 3rd Floor, International Industrial Building, 501-503 Castle Peak Road, Cheung Sha Wan, Kowloon, Hong Kong
Factory: Camino Industrial (Huizhou) Co. Ltd.
Address of Factory: Lidong Industrial Estate, Jiutan, Yuanzhou, Boluo, Huizhou, Guangdong, China
Equipment Under Test (EUT):
EUT Name: Beauty and the Beast Wireless Bluetooth Speaker
Model No.: 761579
Trade Mark: Disney
FCC ID: ZZX579
Standards: 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2017-01-16
Date of Test: 2017-01-20 to 2017-02-21
Date of Issue: 2017-02-24

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 2 of 92

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-02-24		Original

Authorized for issue by:			
Tested By			
	Peter Geng /Project Engineer	2017-02-21	Date
Checked By			
	Eric Fu /Reviewer	2017-02-24	Date



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Disturbance at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	6
4.3 MEASUREMENT UNCERTAINTY	6
4.4 STANDARDS APPLICABLE FOR TESTING.....	7
4.5 TEST LOCATION.....	8
4.6 TEST FACILITY	8
4.7 DEVIATION FROM STANDARDS	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	8
5 EQUIPMENT LIST.....	9
6 RADIO SPECTRUM TECHNICAL REQUIREMENT	12
6.1 ANTENNA REQUIREMENT	12
6.1.1 Test Requirement:.....	12
6.1.2 Conclusion.....	12
6.2 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM HOPPING SEQUENCE	13
6.2.1 Test Requirement:.....	13
6.2.2 Conclusion.....	13
7 RADIO SPECTRUM MATTER TEST RESULTS	15
7.1 CONDUCTED DISTURBANCE AT AC POWER LINE(150kHz-30MHz)	15
7.1.1 E.U.T. Operation.....	16
7.1.2 Test Setup Diagram	16
7.1.3 Measurement Data.....	16
7.2 20dB BANDWIDTH	19
7.2.1 E.U.T. Operation.....	19
7.2.2 Test Setup Diagram	19
7.2.3 Measurement Data.....	19
7.3 CONDUCTED PEAK OUTPUT POWER	20
7.3.1 E.U.T. Operation.....	21
7.3.2 Test Setup Diagram	21
7.3.3 Measurement Data.....	21
7.4 CARRIER FREQUENCIES SEPARATION	22
7.4.1 E.U.T. Operation.....	22
7.4.2 Test Setup Diagram	22
7.4.3 Measurement Data.....	22
7.5 HOPPING CHANNEL NUMBER	23
7.5.1 E.U.T. Operation.....	24
7.5.2 Test Setup Diagram	24
7.5.3 Measurement Data.....	24
7.6 DWELL TIME.....	25
7.6.1 E.U.T. Operation.....	26
7.6.2 Test Setup Diagram	26
7.6.3 Measurement Data.....	26
7.7 CONDUCTED SPURIOUS EMISSIONS.....	27
7.7.1 E.U.T. Operation.....	27



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 5 of 92

7.7.2	Test Setup Diagram	27
7.7.3	Measurement Data	27
7.8	RADIATED SPURIOUS EMISSIONS	28
7.8.1	E.U.T. Operation	29
7.8.2	Test Setup Diagram	29
7.8.3	Measurement Data	30
7.9	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	36
7.9.1	E.U.T. Operation	36
7.9.2	Test Setup Diagram	36
7.9.3	Measurement Data	37
7.10	CONDUCTED BAND EDGES MEASUREMENT	42
7.10.1	E.U.T. Operation	42
7.10.2	Test Setup Diagram	42
7.10.3	Measurement Data	42
8	PHOTOGRAPHS	43
8.1	RADIATED DISTURBANCE(30MHZ-1GHZ) TEST SETUP	43
8.2	RADIATED DISTURBANCE(ABOVE 1GHZ) TEST SETUP	43
8.3	CONDUCTED EMISSIONS TEST SETUP	44
8.4	EUT CONSTRUCTIONAL DETAILS	44
9	APPENDIX	45
9.1	APPENDIX 15.247	45-92



4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.7V 1000mAh rechargeable battery which charged by AC adapter
Cable:	USB charging line: 75cm, unshielded
Bluetooth version:	V 4.0 dual mode, this report is for classic.
Operation frequency:	2402-2480MHz
Modulation type:	GFSK, pi/4 DQPSK, 8DPSK
Channel number:	79
Channel separation:	1MHz
Antenna type:	Integral antenna
Antenna Gain:	0dBi

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	Apple	A1357 W010A051	REF. No.SEA0500

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 ⁻⁸
2	Timeout	2s
3	Duty cycle	0.37%
4	Occupied Bandwidth	3%
5	RF conducted power	0.75dB
6	RF power density	2.84dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	4.5dB (below 1GHz)
		4.8dB (above 1GHz)
9	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
10	Supply voltages	1.5%
11	Time	3%



4.4 Standards Applicable for Testing

Table 1 : Tests Carried Out Under 47 CFR Part 15, Subpart C 15.247

Item	Status
Conducted Disturbance at AC Power Line(150kHz-30MHz)	√
20dB Bandwidth	√
Conducted Peak Output Power	√
Carrier Frequencies Separation	√
Hopping Channel Number	√
Dwell Time	√
Minimum 6dB Bandwidth	×
Power Spectrum Density	×
Conducted Spurious Emissions	√
Radiated Spurious Emissions	√
Radiated Emissions which fall in the restricted bands	√
Conducted Band Edges Measurement	√
Antenna Requirement	√
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	√

× Indicates that the test is not applicable
√ Indicates that the test is applicable



4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Disturbance at AC Power Line(150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13
LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25
8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2016-09-28	2017-09-28
4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2016-09-28	2017-09-28
2 Line ISN	Fischer Custom	FCC-TLISN-T2-02	EMC0122	2016-09-28	2017-09-28

20dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Carrier Frequencies Separation					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 10 of 92

Hopping Channel Number					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Dwell Time					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 11 of 92

Radiated Disturbance(30MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2016-05-13	2017-05-13
EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESR	SEM004-03	2016-04-25	2017-04-25
Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-18	2016-06-29	2019-06-29
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-07-06	2017-07-06

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2016-05-18	2017-05-18

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247


6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247

6.2.2 Conclusion

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):


According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203

Page: 14 of 92

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



7 Radio Spectrum Matter Test Results

7.1 Conducted Disturbance at AC Power Line(150kHz-30MHz)

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Exploratory Test Mode: Non-hopping transmitting mode with all kind of modulation and all kind of data type at the lowest, middle, high channel.


Transmitting +Charging mode.

Final Test Mode: Through Pre-scan, find the DH1 of data type and GFSK modulation at the lowest channel is the worst case.

Transmitting +Charging mode

Only the worst case is recorded in the report.

7.1.2 Test Setup Diagram



7.1.3 Measurement Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 17 of 92

Mode:d;Line:Live Line



Site : Shielding Room

Condition : CE LINE

Job NO : 0392CR

Mode : d

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15240	0.02	9.64	34.00	43.66	55.87	-12.21	Peak
2	0.19654	0.02	9.64	31.49	41.15	53.76	-12.60	Peak
3	0.60431	0.02	9.65	27.39	37.07	46.00	-8.93	Peak
4	1.593	0.03	9.66	19.32	29.01	46.00	-16.99	Peak
5	3.107	0.03	9.69	16.97	26.68	46.00	-19.32	Peak
6	7.769	0.10	9.81	20.27	30.17	50.00	-19.83	Peak




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 18 of 92

Mode:d;Line:Neutral Line



Site : Shielding Room
Condition : CE NEUTRAL
Job NO : 0392CR
Mode : d

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15080	0.02	9.64	36.42	46.08	55.96	-9.87	Peak
2	0.19654	0.02	9.63	32.56	42.21	53.76	-11.54	Peak
3	0.60431	0.02	9.63	29.11	38.76	46.00	-7.24	Peak
4	0.75894	0.03	9.64	24.27	33.94	46.00	-12.06	Peak
5	1.928	0.03	9.66	20.62	30.31	46.00	-15.69	Peak
6	7.606	0.09	9.79	22.19	32.07	50.00	-17.93	Peak

7.2 20dB Bandwidth

Test Requirement: 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 7.8.7

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Pretest these mode to find the worst case: Non-hopping transmitting with all kind of modulation and all kind of data type.
Transmitting mode and Transmitting + Charging mode

The worst case for final test: Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
Transmitting mode is the worst case.
Only the worst case is reported.

7.2.2 Test Setup Diagram



7.2.3 Measurement Data

The detailed test data see: Appendix 15.247



7.3 Conducted Peak Output Power

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 7.8.5

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for < 50 hopping channels
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar


Pretest these mode to find the worst case: Non-hopping transmitting with all kind of modulation and all kind of data type.
 Transmitting mode and Transmitting + Charging mode

The worst case for final test: Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.

Transmitting mode is the worst case.

Only the worst case is reported.

7.3.2 Test Setup Diagram



7.3.3 Measurement Data

The detailed test data see: Appendix 15.247

7.4 Carrier Frequencies Separation

Test Requirement: 47 CFR Part 15, Subpart C 15.247
 Test Method: ANSI C63.10 (2013) Section 7.8.2
 Limit: 2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Pretest these mode to find the worst case: Hopping transmitting with all kind of modulation and all kind of data type.
 Transmitting mode and Transmitting + Charging mode

The worst case for final test: Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.
 Transmitting mode is the worst case.
 Only the worst case is reported.

7.4.2 Test Setup Diagram



7.4.3 Measurement Data

The detailed test data see: Appendix 15.247



7.5 Hopping Channel Number

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 7.8.3

Limit:

Frequency range(MHz)	Channel Number(minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
2725-5850	75


7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Test Mode: Hopping transmitting with all kind of modulation

7.5.2 Test Setup Diagram



7.5.3 Measurement Data

The detailed test data see: Appendix 15.247



7.6 Dwell Time

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 7.8.4

Limit:

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S
5725-5850	0.4S within a 30S period


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Test Mode: Hopping transmitting with all kind of modulation and all kind of data type.

7.6.2 Test Setup Diagram



7.6.3 Measurement Data

The detailed test data see: Appendix 15.247

7.7 Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15, Subpart C 15.247
Test Method:	ANSI C63.10 (2013) Section 7.8.8
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar

Exploratory Test Mode: Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type.


Transmitting mode, Transmitting + Charging mode

Final Test Mode: Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.

Transmitting + Charging mode is the worst case.

Only the worst case is reported.

7.7.2 Test Setup Diagram



7.7.3 Measurement Data

The detailed test data see: Appendix 15.247



7.8 Radiated Spurious Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.247
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6
Measurement Distance: 10m
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 24.0 °C Humidity: 54 % RH Atmospheric Pressure: 1020 mbar

Pretest these mode to find the worst case: Non-hopping transmitting mode with all kind of modulation and all kind of data type

worst case: Transmitting mode, Transmitting + Charging mode,




The worst case for final test: Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case.

Pretest the EUT at Transmitting mode and Transmitting + Charging mode and found Transmitting + Charging mode is worse case

For below 1GHz part, through pre-scan, the worst case is the lowest channel.

Only the worst case is recorded in the report.

7.8.2 Test Setup Diagram






7.8.3 Measurement Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 and 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel (2402MHz), the middle channel (2441MHz), the Highest channel (2480MHz)
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.



Mode:d;Polarization:Horizontal



Condition: 10m HORIZONTAL

Job No. : 00392CR

Test Mode: d

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	35.25	6.71	11.67	32.98	28.95	14.35	29.50	-15.15
2	64.43	7.00	11.88	32.93	26.65	12.60	29.50	-16.90
3	166.65	7.50	12.53	32.73	30.21	17.51	33.00	-15.49
4	543.27	8.76	18.43	32.60	26.95	21.54	35.60	-14.06
5	675.21	9.09	21.25	32.60	26.60	24.34	35.60	-11.26
6 pp	938.83	9.55	23.30	32.50	27.10	27.45	35.60	-8.15




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 32 of 92

Mode:d;Polarization:Vertical



Condition: 10m VERTICAL

Job No. : 00392CR

Test Mode: d

	Freq	Cable	Ant	Preamp	Read	Limit	Over	
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	31.07	6.70	11.70	32.97	30.51	15.94	29.50	-13.56
2	47.83	6.86	12.49	33.00	29.06	15.41	29.50	-14.09
3	110.96	7.26	10.48	32.78	34.01	18.97	33.00	-14.03
4 pp	154.82	7.48	13.00	32.74	35.59	23.33	33.00	-9.67
5	601.43	8.90	20.04	32.60	27.01	23.35	35.60	-12.25
6	860.04	9.40	22.70	32.54	25.75	25.31	35.60	-10.29



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203

Page: 33 of 92

Below 1GHz

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L_3 : Level @ 3m distance. Unit: uV/m;

L_{10} : Level @ 10m distance. Unit: uV/m;

D_3 : 3m distance. Unit: m

D_{10} : 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
31.07	15.94	6.27	20.89	26.40	40.00	-13.60	V
47.83	15.41	5.90	19.65	25.87	40.00	-14.13	V
110.96	18.97	8.88	29.61	29.43	43.50	-14.07	V
154.82	23.33	14.67	48.91	33.79	43.50	-9.71	V
601.43	23.35	14.71	49.02	33.81	46.00	-12.19	V
860.04	25.31	18.43	61.43	35.77	46.00	-10.23	V
35.25	14.35	5.22	17.39	24.81	40.00	-15.19	H
64.43	12.60	4.27	14.22	23.06	40.00	-16.94	H
166.65	17.51	7.51	25.03	27.97	43.50	-15.53	H
543.27	21.54	11.94	39.80	32.00	46.00	-14.00	H
675.21	24.34	16.48	54.94	34.80	46.00	-11.20	H
938.83	27.45	23.58	78.59	37.91	46.00	-8.09	H



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203

Page: 34 of 92

Above 1GHz

Test mode:		GFSK(DH1)		Test channel:		Lowest		Remark:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3589.562	32.46	7.66	37.96	44.83	46.99	74	-27.01	Vertical	
4804.000	34.16	8.87	38.40	48.51	53.14	74	-20.86	Vertical	
5939.103	34.66	10.39	38.31	44.51	51.25	74	-22.75	Vertical	
7206.000	36.42	10.68	37.11	42.13	52.12	74	-21.88	Vertical	
9608.000	37.52	12.50	35.10	37.30	52.22	74	-21.78	Vertical	
12102.870	38.66	14.47	35.85	35.87	53.15	74	-20.85	Vertical	
3842.163	33.18	7.76	37.98	45.62	48.58	74	-25.42	Horizontal	
4804.000	34.16	8.87	38.40	48.95	53.58	74	-20.42	Horizontal	
5887.766	34.63	10.25	38.32	45.04	51.60	74	-22.40	Horizontal	
7206.000	36.42	10.68	37.11	42.59	52.58	74	-21.42	Horizontal	
9608.000	37.52	12.50	35.10	37.54	52.46	74	-21.54	Horizontal	
12440.210	38.86	14.20	36.66	37.35	53.75	74	-20.25	Horizontal	

Test mode:		GFSK(DH1)		Test channel:		Middle		Remark:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Cable Loss (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit (dB)	Polarization	
3781.495	33.01	7.73	37.98	45.10	47.86	74	-26.14	Vertical	
4882.000	34.30	8.98	38.44	48.15	52.99	74	-21.01	Vertical	
6078.201	34.76	10.46	38.22	44.70	51.70	74	-22.30	Vertical	
7323.000	36.37	10.72	37.01	42.98	53.06	74	-20.94	Vertical	
9764.000	37.55	12.58	35.02	37.50	52.61	74	-21.39	Vertical	
12102.870	38.66	14.47	35.85	36.33	53.61	74	-20.39	Vertical	
3754.236	32.94	7.72	37.98	44.35	47.03	74	-26.97	Horizontal	
4882.000	34.30	8.98	38.44	46.10	50.94	74	-23.06	Horizontal	
6087.002	34.77	10.45	38.21	44.62	51.63	74	-22.37	Horizontal	
7323.000	36.37	10.72	37.01	42.91	52.99	74	-21.01	Horizontal	
9764.000	37.55	12.58	35.02	37.79	52.90	74	-21.10	Horizontal	
12208.390	38.73	14.39	36.10	36.15	53.17	74	-20.83	Horizontal	



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 35 of 92

Test mode:		GFSK(DH1)		Test channel:	Highest		Remark:		Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp factor (dB)	Reading Level (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Over limit (dB)	Polarization	
3792.453	33.04	7.74	37.98	44.15	46.95	74	-27.05	Vertical	
4960.000	34.43	9.09	38.48	46.11	51.15	74	-22.85	Vertical	
6087.002	34.77	10.45	38.21	44.45	51.46	74	-22.54	Vertical	
7440.000	36.32	10.77	36.90	43.69	53.88	74	-20.12	Vertical	
9920.000	37.58	12.67	34.94	36.75	52.06	74	-21.94	Vertical	
12208.390	38.73	14.39	36.10	36.07	53.09	74	-20.91	Vertical	
3847.726	33.19	7.76	37.98	45.17	48.14	74	-25.86	Horizontal	
4960.000	34.43	9.09	38.48	46.72	51.76	74	-22.24	Horizontal	
5964.939	34.68	10.46	38.31	44.72	51.55	74	-22.45	Horizontal	
7440.000	36.32	10.77	36.90	41.74	51.93	74	-22.07	Horizontal	
9920.000	37.58	12.67	34.94	37.05	52.36	74	-21.64	Horizontal	
12120.390	38.67	14.46	35.89	36.56	53.80	74	-20.20	Horizontal	

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

7.9 Radiated Emissions which fall in the restricted bands

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 6.10.5

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C

Humidity: 56 % RH

Atmospheric Pressure: 1020 mbar




Exploratory Test Mode: Non-hopping transmitting mode with all kind of modulation and all kind of data type
 Transmitting mode, Transmitting + Charging mode

Final Test Mode: Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case.

Transmitting + Charging mode is worse case

Only the worst case is recorded in the report.

7.9.2 Test Setup Diagram





7.9.3 Measurement Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 and 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel (2402MHz), the middle channel (2441MHz), the Highest channel (2480MHz)
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 38 of 92

Mode:d; Polarization:Horizontal



Condition: 3m HORIZONTAL

Job No: : 0392CR

Mode: : 2402 Bandedge

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2376.027	5.33	29.04	37.96	52.83	49.24	74.00	-24.76	
2	2390.000	5.34	29.08	37.96	50.90	47.36	74.00	-26.64	
3 pp	2402.148	5.35	29.11	37.96	109.22	105.72	74.00	31.72	




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 39 of 92

Mode:d; Polarization:Vertical



Condition: 3m VERTICAL

Job No: : 0392CR

Mode: : 2402 Bandedge

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2323.845	5.29	28.88	37.97	52.55	48.75	74.00	-25.25	
2	2390.000	5.34	29.08	37.96	50.32	46.78	74.00	-27.22	
3	pp 2402.148	5.35	29.11	37.96	104.45	100.95	74.00	26.95	




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 40 of 92

Mode:d; Polarization:Horizontal



Condition: 3m HORIZONTAL

Job No: : 0392CR

Mode: : 2480 Bandedge

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2479.855	5.41	29.34	37.95	108.35	105.15	74.00	31.15
2	2483.500	5.41	29.35	37.95	55.87	52.68	74.00	-21.32




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203

Page: 41 of 92

Mode:d; Polarization:Vertical



Condition: 3m VERTICAL

Job No: : 0392CR

Mode: : 2480 Bandedge

: BT

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2479.830	5.41	29.34	37.95	103.15	99.95	74.00	25.95	
2	2483.500	5.41	29.35	37.95	52.44	49.25	74.00	-24.75	

7.10 Conducted Band Edges Measurement

Test Requirement: 47 CFR Part 15, Subpart C 15.247

Test Method: ANSI C63.10 (2013) Section 7.8.6

7.10.1 E.U.T. Operation

Operating Environment:

Temperature: 23.0 °C

Humidity: 56 % RH

Atmospheric Pressure: 1020 mbar


Exploratory Test Mode: Non-hopping transmitting with all kind of modulation and all kind of data type
 Transmitting mode, Transmitting+ Charging mode

Final Test Mode: Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.

Transmitting + Charging mode is the worst case

Only the worst case is reported.

7.10.2 Test Setup Diagram



7.10.3 Measurement Data


The detailed test data see: Appendix 15.247

8 Photographs


8.1 Radiated Disturbance(30MHz-1GHz) Test Setup



8.2 Radiated Disturbance(above 1GHz) Test Setup



8.3 Conducted emissions Test Setup



8.4 EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1701000392CR.



9 Appendix

9.1 Appendix 15.247

1.20 dB Bandwidth

Test Mode	Test Channel	EBW[MHz]	Limit	Verdict
DH5	2402	0.954	---	PASS
DH5	2441	0.946	---	PASS
DH5	2480	0.950	---	PASS
2DH5	2402	1.204	---	PASS
2DH5	2441	1.204	---	PASS
2DH5	2480	1.206	---	PASS
3DH5	2402	1.214	---	PASS
3DH5	2441	1.206	---	PASS
3DH5	2480	1.206	---	PASS




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM170100039203
Page: 46 of 92

TEST PLOT

Occupied Bandwidth_DH5_2402




Occupied Bandwidth_DH5_2441






Occupied Bandwidth_DH5_2480




Occupied Bandwidth_2DH5_2402






Occupied Bandwidth_2DH5_2441



Occupied Bandwidth_2DH5_2480







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203
Page: 49 of 92

Occupied Bandwidth_3DH5_2402




Occupied Bandwidth_3DH5_2441





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203
Page: 50 of 92






2. Conducted Peak Output Power

Test Mode	Test Channel	Power[dBm]	Limit[dBm]	Verdict
DH5	2402	6.15	<30	PASS
DH5	2441	8.45	<30	PASS
DH5	2480	8.86	<30	PASS
2DH5	2402	4.08	<30	PASS
2DH5	2441	7.15	<30	PASS
2DH5	2480	7.53	<30	PASS
3DH5	2402	4.29	<30	PASS
3DH5	2441	7.43	<30	PASS
3DH5	2480	7.84	<30	PASS




TEST PLOT

Maximum peak conducted output power_DH5_2402




Maximum peak conducted output power_DH5_2441






Maximum peak conducted output power_DH5_2480




Maximum peak conducted output power_2DH5_2402






Maximum peak conducted output power_2DH5_2441




Maximum peak conducted output power_2DH5_2480







Maximum peak conducted output power_3DH5_2402



Maximum peak conducted output power_3DH5_2441









3.Carrier Frequency Separation

Test Mode	Test Channel	Result[MHz]	Verdict
DH5	2441	0.993	PASS
2DH5	2441	0.996	PASS
3DH5	2441	1.020	PASS






Carrier Frequency Separation_2DH5_2441




Carrier Frequency Separation_3DH5_2441







4.Dwell Time

Test Mode	Test Channel	Burst Width[ms/hop/ch]	Total Hops[hop*ch]	Dwell Time[s]	Limit[s]	Verdict
DH1	2402	0.4	320	0.128	<0.4	PASS
DH3	2402	1.66	160	0.266	<0.4	PASS
DH5	2402	2.9	100	0.29	<0.4	PASS
2DH1	2402	0.41	320	0.131	<0.4	PASS
2DH3	2402	1.67	160	0.267	<0.4	PASS
2DH5	2402	2.9	110	0.319	<0.4	PASS
3DH1	2402	0.41	320	0.131	<0.4	PASS
3DH3	2402	1.67	160	0.267	<0.4	PASS
3DH5	2402	2.91	110	0.32	<0.4	PASS










SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203
Page: 63 of 92







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203
Page: 64 of 92

Dwell Time_2DH3_2402







SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203

Page: 65 of 92

Dwell Time_2DH5_2402








SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203

Page: 66 of 92

Dwell Time_3DH1_2402









SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203

Page: 68 of 92


Dwell Time_3DH5_2402






5.Hopping Channel Number

Test Mode	Test Channel	Number of Hopping Channel[N]	Limit[N]	Verdict
DH5	2402	79	>=15	PASS
2DH5	2402	79	>=15	PASS
3DH5	2402	79	>=15	PASS






Hopping Channel Number_2DH5_2402



Hopping Channel Number_3DH5_2402





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM170100039203

Page: 71 of 92


6.Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Hopping	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit[dBm]	Verdict
DH5	2402	5.430	-59.164	<-14.57	PASS	DH5
DH5	2480	8.290	-51.639	<-11.71	PASS	DH5
2DH5	2402	2.170	-59.354	<-17.83	PASS	2DH5
2DH5	2480	5.020	-56.236	<-14.98	PASS	2DH5
3DH5	2402	2.360	-60.527	<-17.64	PASS	3DH5
3DH5	2480	5.920	-56.593	<-14.08	PASS	3DH5
DH5	2402	3.800	-55.496	<-16.2	PASS	DH5
DH5	2480	5.120	-53.874	<-14.88	PASS	DH5
2DH5	2402	0.650	-55.211	<-19.35	PASS	2DH5
2DH5	2480	5.300	-54.359	<-14.7	PASS	2DH5
3DH5	2402	3.100	-56.351	<-16.9	PASS	3DH5
3DH5	2480	4.650	-53.528	<-15.35	PASS	3DH5




TEST PLOT

Band-edge for RF Conducted Emissions_DH5_2402_Hopping Off




Band-edge for RF Conducted Emissions_DH5_2480_Hopping Off






Band-edge for RF Conducted Emissions_2DH5_2402_Hopping Off




Band-edge for RF Conducted Emissions_2DH5_2480_Hopping Off






Band-edge for RF Conducted Emissions_3DH5_2402_Hopping Off




Band-edge for RF Conducted Emissions_3DH5_2480_Hopping Off






Band-edge for RF Conducted Emissions_DH5_2402_Hopping On



Band-edge for RF Conducted Emissions_DH5_2480_Hopping On






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM170100039203

Page: 76 of 92

Band-edge for RF Conducted Emissions_2DH5_2402_Hopping On




Band-edge for RF Conducted Emissions_2DH5_2480_Hopping On






Band-edge for RF Conducted Emissions_3DH5_2402_Hopping On



Band-edge for RF Conducted Emissions_3DH5_2480_Hopping On






SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch


Report No.: SZEM170100039203


Page: 78 of 92


7.RF Conducted Spurious Emissions


Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
DH5	2402	30	10000	1000	3000	5.52	-42.460	<-14.48	PASS
DH5	2402	10000	25000	1000	3000	5.52	-60.300	<-14.48	PASS
DH5	2441	30	10000	1000	3000	7.96	-41.540	<-12.04	PASS
DH5	2441	10000	25000	1000	3000	7.96	-59.630	<-12.04	PASS
DH5	2480	30	10000	1000	3000	8.38	-39.970	<-11.62	PASS
DH5	2480	10000	25000	1000	3000	8.38	-59.820	<-11.62	PASS
2DH5	2402	30	10000	1000	3000	2.22	-44.290	<-17.78	PASS
2DH5	2402	10000	25000	1000	3000	2.22	-59.930	<-17.78	PASS
2DH5	2441	30	10000	1000	3000	5.03	-44.870	<-14.97	PASS
2DH5	2441	10000	25000	1000	3000	5.03	-59.700	<-14.97	PASS
2DH5	2480	30	10000	1000	3000	5.84	-43.790	<-14.16	PASS
2DH5	2480	10000	25000	1000	3000	5.84	-59.610	<-14.16	PASS
3DH5	2402	30	10000	1000	3000	2.2	-44.080	<-17.8	PASS
3DH5	2402	10000	25000	1000	3000	2.2	-59.160	<-17.8	PASS
3DH5	2441	30	10000	1000	3000	5.42	-44.760	<-14.58	PASS
3DH5	2441	10000	25000	1000	3000	5.42	-59.700	<-14.58	PASS
3DH5	2480	30	10000	1000	3000	5.92	-43.320	<-14.08	PASS
3DH5	2480	10000	25000	1000	3000	5.92	-59.790	<-14.08	PASS





































SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170100039203
Page: 92 of 92

