


Prüfbericht-Nr.: Test report no.:	CN260830 001	Auftrags-Nr.: Order no.:	27245636	Seite 1 von 20 Page 1 of 20
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2026-07-15	
Auftraggeber: Client:	Shenzhen Shuye Technology Co., Ltd. Room1301, Building T7, Qianwan 1st Road No.399, Qianhai Kerry Business Center, Nanshan, Shenzhen Guangdong P.R. China			
Prüfgegenstand: Test item:	Laifen Glowy Vanity Mirror			
Bezeichnung / Typ-Nr.: Identification / Type no.:	LFMM M8 (Trademark: laifen)			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	Item 8, Paragraph 1, Article 2 MIC Notification No. 88, Annex 22-16 / ARIB STD-T73 Ver. 3.0			
Wareneingangsdatum: Date of sample receipt:	2026-08-04			
Prüfmuster-Nr.: Test sample no.:	A004354880-001			
Prüfzeitraum: Testing period:	2026-08-04 - 2026-08-24			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:	Hardy X  Suo		genehmigt von: authorized by:	Lin Lin X 
Datum: Date:	2026-08-26	Ausstellungsdatum: Issue date:	2026-08-26	
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN260830 001
Test report no.:

Seite 2 von 20
Page 2 of 20

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 3 von 20
Page 3 of 20

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	UNCERTAINTY OF MEASUREMENT	8
3	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE.....	9
3.2	RATINGS AND SYSTEM DETAILS	9
3.3	ANTENNA PATTERN	9
3.4	PRODUCT HOUSING	10
3.5	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	10
3.6	SUBMITTED DOCUMENTS.....	10
4	TEST SET-UP AND OPERATION MODES	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	11
5	TEST RESULTS	12
5.1	ANTENNA REQUIREMENT	12
5.1.1	Limit of Antenna	12
5.1.2	Test Results	12
5.2	OPERATING FREQUENCY AND TOLERANCE OF FREQUENCY.....	13
5.2.1	Limits of Operating Frequency and Tolerance of Frequency.....	13
5.2.2	Test Setup	13
5.2.3	Test Procedure.....	13
5.2.4	Test Results	13
5.3	OCCUPIED FREQUENCY BANDWIDTH (99%OBW)	14
5.3.1	Limits of Occupied Frequency Bandwidth (99%OBW)	14
5.3.2	Test Setup	14
5.3.3	Test Procedure.....	14
5.3.4	Test Results	14
5.4	THE PERMISSIBLE VALUES FOR THE STRENGTH OF SPURIOUS EMISSIONS OR UNWANTED EMISSIONS (Tx).....	15
5.4.1	Limits of Spurious Emissions of Tx	15
5.4.2	Test Setup	15
5.4.3	Test Procedure.....	15
5.4.4	Test Results	15
5.5	LIMIT ON SECONDARY RADIATED EMISSIONS (Rx)	16
5.5.1	Limits of Spurious Emissions of Rx.....	16
5.5.2	Test Setup	16
5.5.3	Test Procedure.....	16

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 4 von 20
Page 4 of 20

5.5.4	Test Results	16
5.6	ANTENNA POWER AND TOLERANCE OF ANTENNA POWER	17
5.6.1	Limits of Antenna Power and Tolerance of Antenna Power	17
5.6.2	Test Setup	17
5.6.3	Test Procedure	17
5.6.4	Test Results	17
5.7	INTERFERENCE PREVENTION FUNCTION	18
6	PHOTOGRAPHS OF THE TEST SET-UP	19
7	LIST OF TABLES	20
8	LIST OF PHOTOGRAPHS	20

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 5 von 20
Page 5 of 20

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:
Appendix A: Test result.

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 6 von 20
Page 6 of 20

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China

A2LA Certificate Number: 5162.01

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (TS8997)							
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until	Calibration Body	Calibration Method*
Wireless Connectivity Tester	R&S	CMW270	101375	2025-09-23	2026-09-22	CCIC	c
Signal Analyzer	R&S	FSV 40	101441	2025-09-23	2026-09-22	CCIC	c
Vector Signal Generator	R&S	SMBV100A	263301	2025-10-30	2026-10-29	CCIC	c
Signal Generator	R&S	SMB100A	115186	2025-09-23	2026-09-22	CCIC	c
OSP	R&S	OSP 150	101017	2025-10-30	2026-10-29	CCIC	c
Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A	N/A	N/A	c
Test Software	R&S	WMS32 (V11.00.00)	N/A	N/A	N/A	N/A	c
Power Meter	R&S	NRP2	107105	2025-10-30	2026-10-29	CCIC	c
Wideband Power Sensor	R&S	NRP-Z81	105677	2025-09-23	2026-09-22	CCIC	c
High Low Temperature Test Chamber	KOWINTEST	TH-30FJX	KW-21040497	2025-09-23	2026-09-22	CCIC	c
Shielding Room	Albatross	SR1	APC17151-SR1	2024-09-14	2027-09-13	GRGTEST	c
Unwanted Emission Testing (TS8996)							
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until	Calibration Body	Calibration Method*
Signal Generator	R&S	SMB100A	180840	2025-09-22	2026-09-21	GRGTEST	c
Wideband Radio Communication Tester	R&S	CMW500	165339	2025-09-22	2026-09-21	GRGTEST	c
Signal Analyzer	R&S	FSV 40	101440	2025-09-22	2026-09-21	GRGTEST	c
System Controller Interface	R&S	SCI-100	S10010036	N/A	N/A	N/A	c
OSP	R&S	OSP 120	102041	N/A	N/A	N/A	c
OSP	R&S	OSP 150	101385	2025-10-30	2026-10-29	GRGTEST	c
Pre-amplifier	R&S	SCU08F1	08320030	2025-09-22	2026-09-21	GRGTEST	c
Amplifier	R&S	SCU-18F	180079	2025-09-22	2026-09-21	GRGTEST	c
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	192	2024-10-07	2026-10-06	GRGTEST	c
Double-Ridged Antenna (1 - 18 GHz)	ETS-LINDGREN	3117	00218719	2024-10-07	2026-10-06	GRGTEST	c
Wideband Ridged Horn Antenna (12-18 GHz)	Steatite	QMS-00208	18312	2024-10-07	2026-10-06	GRGTEST	c

Prüfbericht - Nr.: **CN26O83O 001**
Test Report No.:

Seite 7 von 20
Page 7 of 20

Biconical Broadband Antenna (30 MHz - 1 GHz)	Schwarzbeck	VUBA 9117	357	2024-10-07	2026-10-06	GRGTEST	c
Double Ridged Broadband Horn Antenna (1 -18 GHz)	Schwarzbeck	BBHA 9120 D	01760	2024-10-07	2026-10-06	GRGTEST	c
Test software	R&S	EMC32 (V10.50.40)	N/A	N/A	N/A	N/A	c
Control PC	Dell	OptiPlex 7050	36NW9P2	N/A	N/A	N/A	c
3m Fully Anechoic Chamber	Albatross	FAC-3m	APC17151-FAC	2024-09-14	2027-09-13	GRGTEST	c

Calibration Method:

- a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1)
- b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992)
- c) Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1)
- d) Calibration conducted by using measuring instruments and other equipment listed in the right column of Table No. 3 attached hereto, which shall have been given any of calibration, etc. listed above from a) to c)

Prüfbericht - Nr.: **CN26O83O 001**
Test Report No.:

Seite 8 von 20
Page 8 of 20

2.3 Uncertainty of Measurement

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
Radiated Emission of Transmitter, valid up to 26.5 GHz	± 3.68 dB
Radiated Emission of Receiver, valid up to 26.5 GHz	± 3.68 dB

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 9 von 20
Page 9 of 20

3 General Product Information

3.1 Product Function and Intended Use

The product is a Laifen Glowly Vanity Mirror supports 24GHz radar function operating within 24.05-24.25GHz.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Laifen Glowly Vanity Mirror
Type Designation:	LFMM M8
Rating(s):	DC 5V, Max. 1.7A, Max. 8.5W Battery Capacity: DC 4.34V, 5500mAh
Operating Temperature Range:	0°C ~ +35 °C
Hardware Version:	V10
Software Version:	V1.0.8
Technical Specification of 24GHz radar	
Assigned Band:	24.05-24.25GHz
Operation Frequency Range:	24.05-24.25GHz
Type of Modulation:	FMCW
Antenna Type:	Integral Antenna
Antenna Gain:	4.59dBi (Provided by the Client)
Rated Antenna Power:	0.2mW
Test voltage:	DC 4.34V

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

Table 4: Antenna Gain

Ant. Type	Connector Type	Highest Peak Gain (dBi)
Integral Antenna	Soldered on PCB	4.59dBi

3.3 Antenna Pattern

Please refer to the product antenna report.

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 10 von 20
Page 10 of 20

3.4 Product Housing

The RF circuits are located inside of the EUT. As the RF circuit was sutured by ultrasound, it won't be easy to open. Frequency Band, operation channels and modulation parameters are fixed inside the wireless module. So, they cannot be easily edited or modified by end-user.

3.5 Noise Generating and Noise Suppressing Parts

For details refer to the Circuit Diagram.

3.6 Submitted Documents

- Application Form
- Rating Label
- User Manual
- Operation Description

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 11 von 20
Page 11 of 20

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5 and chapter 6.

According to clause 3.2, all tests were performed on model *LFMM M8* in this report.

Table 5: Test Conditions

Test conditions	Value
Voltage _{normal}	*4.34V dc
Voltage _{max}	4.774V dc
Voltage _{min}	3.906V dc
Temperature	+25°C
Temperature _{max}	+50°C
Temperature _{min}	-20 °C

*Note: When the input supply voltage to the EUT from the external power source is varied by +/- 10%, the output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/-1%, and the DC power fluctuation at the power input PIN of the RF chip is equal to or less than +/-1%. So, exempt extremely high and low supply voltage condition tests, EUT only operated in normal voltage to test all regulations.

4.3 Special Accessories and Auxiliary Equipment

Table 6: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N
Laptop	Lenovo	T480	PF-16A6N8

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 12 von 20
Page 12 of 20

5 Test Results

5.1 Antenna Requirement

5.1.1 Limit of Antenna


(1) Antenna structures

- There is no specific provision for the antenna structure.

(2) Gain of the antenna

- The absolute gain of the transmitting antenna shall be 24dB or less.
- In case, the equivalent isotropically radiated power (e.i.r.p.) is not more than the value that induces 13dBm (0.02W) of antenna power into the antenna with absolute gain 24dB, the difference could be compensated by the gain of the antenna. (refer to Antenna power).

5.1.2 Test Results



- The Max antenna gain is 4.59dBi.

Result

PASS

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:


Seite 13 von 20
Page 13 of 20

5.2 Operating Frequency and Tolerance of Frequency

5.2.1 Limits of Operating Frequency and Tolerance of Frequency

Item	Limit
Operating Frequency and Tolerance of Frequency	Within 24.05-24.25GHz

5.2.2 Test Setup



5.2.3 Test Procedure

- Test Conditions
Spectrum Analyzer is used for measurement.
- EUT Conditions
The EUT is operated in continuous transmission mode. The centre frequency of the spectrum analyser is set to the fundamental frequency.
- Spectrum Analyzer conditions
Frequency: Test Frequency
RBW=1%*99%OBW
VBW=RBW
Span=2~3.5 * 40MHz
Sweep Time=Auto
Sweep Point≥400
Detector mode=Positive peak
Indication mode=Max hold
- Repeat at normal and extreme conditions respectively.

5.2.4 Test Results

Result **PASS**

For the measurement records, refer to appendix A.

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:


Seite 14 von 20
Page 14 of 20

5.3 Occupied Frequency Bandwidth (99%OBW)

5.3.1 Limits of Occupied Frequency Bandwidth (99%OBW)

Item	Limit
Occupied Frequency Bandwidth	≤200MHz

5.3.2 Test Setup



5.3.3 Test Procedure

- Test Conditions
Spectrum Analyzer is used for measurement.
- EUT Conditions
The EUT is operated in continuous transmission mode. The centre frequency of the spectrum analyser is set to the fundamental frequency.
- Spectrum Analyzer conditions
Frequency: Test Frequency
RBW=1%*99%OBW
VBW=RBW
Span=2~3.5 * 40MHz
Sweep Time=Auto
Sweep Point≥400
Detector mode=Positive peak
Indication mode=Max hold

5.3.4 Test Results

Result **PASS**

For the measurement records, refer to appendix A.

Prüfbericht - Nr.: **CN26O83O 001**
Test Report No.:


Seite 15 von 20
Page 15 of 20

5.4 The permissible values for the strength of spurious emissions or unwanted emissions (Tx)

5.4.1 Limits of Spurious Emissions of Tx

Frequencies	Limit
Below 1GHz	$\leq 2.5\mu\text{W}/100\text{kHz}$
1G-5G	$\leq 2.5\mu\text{W}/1\text{MHz}$

5.4.2 Test Setup



5.4.3 Test Procedure

- Test Conditions
Spectrum Analyzer is used for measurement.
- EUT conditions
The EUT is operated in continuous transmission mode. The centre frequency of the spectrum analyser is set to the fundamental frequency.
- Spectrum Analyzer conditions
Step 1
All spurious are measured from 30MHz to 40GHz by peak mode.
Step 2
IF the value measured by Step1 is 3dB or less, measure in average mode.
Spectrum Analyzer conditions:
Frequency range: 30MHz-40GHz, RBW=1MHz, VBW=3MHz
Sweep Time: Auto
Detector mode: Positive peak
Indication mode: Max hold

5.4.4 Test Results

Result **PASS**

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: **CN26O83O 001**
Test Report No.:


Seite 16 von 20
Page 16 of 20

5.5 Limit on Secondary Radiated Emissions (Rx)

5.5.1 Limits of Spurious Emissions of Rx

Frequencies	Limit
Below 1GHz	$\leq 2.5\mu\text{W}/100\text{kHz}$
1G-5G	$\leq 2.5\mu\text{W}/1\text{MHz}$

5.5.2 Test Setup



5.5.3 Test Procedure

- Test Conditions
Spectrum Analyzer is used for measurement.
- EUT conditions
The EUT is operated in continuous receiving mode. The centre frequency of the spectrum analyser is set to the fundamental frequency.
- Spectrum Analyzer conditions
Step 1
All spurious are measured from 30MHz to 40GHz by peak mode.
Step 2
If the value measured by Step1 is 2 dB or less, measure in average mode.
Spectrum Analyzer conditions:
Frequency range: 30MHz-40GHz, RBW=1MHz, VBW=3MHz
Sweep Time: Auto
Detector mode: Positive peak
Indication mode: Max hold

5.5.4 Test Results

Result ***PASS**

For the measurement records, refer to appendix A (Appendix A.3 Test Results of spurious emissions or unwanted emissions (Tx)).

*Note: The Spurious Emissions of Rx are emissions at any frequency when the equipment is in receive mode. Consequently, Spurious Emissions of Rx testing applies only when the equipment can work in a receive-only mode or is a receive only device. In cases where receivers are used in combination with permanently co-located transmitters the receivers will be tested together with the transmitter in operating mode as part of the Spurious Emissions of Tx.

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 17 von 20
Page 17 of 20


5.6 Antenna Power and Tolerance of Antenna Power

5.6.1 Limits of Antenna Power and Tolerance of Antenna Power

The antenna power shall be 0.02 W or less.

The antenna power shall be +50% in the upper limit and -50% in the lower limit.

5.6.2 Test Setup



5.6.3 Test Procedure

- Test Conditions

Spectrum Analyzer is used for measurement.

- EUT conditions

The EUT is operated in continuous transmission mode. The centre frequency of the spectrum analyser is set to the fundamental frequency.

- Spectrum Analyzer conditions:

Step 1. Search for peak power frequency

Frequency: Test Frequency

Span: $\geq$ Twice the occupied bandwidth;

RBW :1MHz

VBW :3MHz

Sweep Time: Auto

Detector mode: Positive peak

Indication mode: Max hold

Step 2. Measurement of average antenna power

Center frequency: Frequency of peak power found using

Span: 0Hz

RBW: 1MHz

VBW :3MHz

Detector mode: Sample

Sweep time: Minimum time required to make an accurate measurement.

For burst type (intermittent) transmission, sweep time shall be greater than one burst interval.

Sweep data points: 1001 or greater.

5.6.4 Test Results

Result

PASS

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: **CN26O83O 001**
Test Report No.:

Seite 18 von 20
Page 18 of 20

5.7 Interference Prevention Function

1) Measurement system diagram



2) Test Procedures

- Set the EUT in the usual operation condition.
- The radio equipment with automatic transmitting function of identification code.
 - Transmit the assigned identification code from the radio equipment.
 - Confirm the identification code received by the demodulator.
- The radio equipment with automatic receiving function of identification code
 - Transmit the assigned identification code from the opposite equipment.
 - Confirm that the usual communication is available.
 - Transmit the identification code distinct from the assigned one from the opposite equipment.
 - Confirm that the radio equipment is stopped or an indication is displayed as the identification code is different.
- The identification function shall be recorded with "Good" or "No".

Items	Test Record
Transmitting/Receiving of Identification Code	The device has the function of automatic transmission or reception of identification code.

Result


PASS

Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 19 von 20
Page 19 of 20

6 Photographs of the Test Set-Up

Photograph 1: Set-up for Radio Spectrum Spurious Testing



Photograph 2: Set-up for Radio Spectrum Testing



Prüfbericht - Nr.: CN26O83O 001
Test Report No.:

Seite 20 von 20
Page 20 of 20

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	8
Table 3: Technical Specification of EUT.....	9
Table 4: Antenna Gain.....	9
Table 5: Test Conditions.....	11
Table 6: List of Accessories and Auxiliary Equipment.....	11

8 List of Photographs

Photograph 1: Set-up for Radio Spectrum Spurious Testing.....	19
Photograph 2: Set-up for Radio Spectrum Testing, Normal and Extreme Condition	19

Appendix A: Test Results

APPENDIX A: TEST RESULTS	1
APPENDIX A.1: TEST RESULTS OF OCCUPIED FREQUENCY BANDWIDTH (99%OBW) AND TOLERANCE OF FREQUENCY	2
<i>Test Results</i>	2
<i>Test Graphs</i>	3
APPENDIX A.2: TEST RESULTS OF ANTENNA POWER	5
<i>Test Results</i>	5
APPENDIX A.3: TEST RESULTS OF SPURIOUS EMISSIONS OR UNWANTED EMISSIONS (Tx)	6
<i>Below 1GHz</i>	6
<i>1GHz - 40GHz</i>	8
<i>Above 40GHz</i>	20



Appendix A.1: Test Results of Occupied Frequency Bandwidth (99%OBW) and Tolerance of Frequency


Test Results

Temperature	Center Frequency (GHz)	Occupied Frequency Bandwidth (MHz)	Occupied Frequency Bandwidth Limit (MHz)	Tolerance of Frequency	Tolerance of Frequency Limit (GHz)	Verdict
+50°C	24.15	137.482	≤200MHz	The Lower Frequency (T1) and Upper Frequency (T2) are within the frequency band Within 24.05-24.25GHz (detail test data refer to following test graphs)	24.05 ~ 24.25	Pass
+25°C		137.482				Pass
-20°C		137.482				Pass

Note: the tests were performed on various temperature and EUT on vibration conditions, only the worst case is recorded in this report.

Test Graphs





**Appendix A.2: Test Results of Antenna Power***Test Results*


Channel frequency (GHz)	Antenna power (dBm)	Antenna power (W)	Antenna power Limit (W)	Rated antenna power (W)	Tolerance of antenna power (%)	Tolerance Limit	Verdict	Remark
24.15	-8.73	0.00013	≤0.02	0.0002	-33.0%	-50% to +50%	Pass	/

Appendix A.3: Test Results of spurious emissions or unwanted emissions (Tx)

Below 1GHz

EUT Information

EUT Name:	Laifen Glowly Vanity Mirror
Model:	LFMM M8
Sample No:	A004354880-001
Test Mode:	TX_24G
Test Voltage:	Battery
Remark:	Temp:23.4°C;Humi:50%
Test standard:	EN 305550
Tested By:	Lich Chen
Reviewed by	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
80.351818	-68.04	-26.00	42.04	190.0	H	42.0	-126.0
231.275000	-83.22	-26.00	57.22	190.0	H	148.0	-117.7
397.100909	-83.11	-26.00	57.11	190.0	H	182.0	-114.9
749.960455	-78.49	-26.00	52.49	190.0	H	81.0	-105.8



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
Model: LFMM M8
Sample No: A004354880-001
Test Mode: TX_24G
Test Voltage: Battery
Remark: Temp:23.4°C;Humi:50%
Test standard: EN 305550
Tested By: Lich Chen
Reviewed by: Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
93.314546	-69.77	-26.00	43.77	190.0	V	44.0	-121.3
156.232273	-85.80	-26.00	59.80	190.0	V	97.0	-123.3
324.086364	-85.26	-26.00	59.26	190.0	V	51.0	-115.2
600.404091	-81.64	-26.00	55.64	190.0	V	86.0	-109.7

1GHz - 40GHz

Note: The highest waveform in the figure is 24.15GHz Wireless Fundamental.

EUT Information

EUT Name:	Laifen Glowly Vanity Mirror
Model:	LFMM M8
Sample No:	A004354880-001
Test Mode:	TX_24G
Test Voltage:	Battery
Remark:	Temp:23.4°C;Humi:50%
Test standard:	EN 305550
Tested By:	Lich Chen
Reviewed by:	Terry Yin




Critical Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1535.546667	-70.85	-26.00	44.85	190.0	H	275.0	-98.6
3084.000000	-58.13	-26.00	32.13	190.0	H	108.0	-95.1
4676.000000	-56.80	-26.00	30.80	190.0	H	259.0	-92.9
9144.500000	-52.52	-26.00	26.52	190.0	H	3.0	-87.6

EUT Information

EUT Name: Laifen Glowly Vanity Mirror
Model: LFMM M8
Sample No: A004354880-001
Test Mode: TX_24G
Test Voltage: Battery
Remark: Temp:23.4°C;Humi:50%
Test standard: EN 305550
Tested By: Lich Chen
Reviewed by: Terry Yin




Critical_Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
2540.640000	-62.74	-26.00	36.74	190.0	V	147.0	-91.8
4406.000000	-56.45	-26.00	30.45	190.0	V	6.0	-93.7
7891.000000	-53.99	-26.00	27.99	190.0	V	88.0	-88.7
13012.000000	-48.44	-26.00	22.44	190.0	V	57.0	-81.5



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
 Model: LFMM M8
 Sample No: A004354880-001
 Test Mode: TX_24G
 Test Voltage: Battery
 Remark: Temp:23.4°C;Humi:50%
 Test standard: EN 305550
 Tested By: Lich Chen
 Reviewed by: Terry Yin




Critical Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
23901.562500	-68.17	-26.00	42.17	150.0	H	150.0	-105.4

EUT Information

EUT Name: Laifen Glowly Vanity Mirror
Model: LFMM M8
Sample No: A004354880-001
Test Mode: TX_24G
Test Voltage: Battery
Remark: Temp:23.4°C;Humi:50%
Test standard: EN 305550
Tested By: Lich Chen
Reviewed by: Terry Yin




Critical Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
23752.312500	-71.47	-26.00	45.47	150.0	V	67.0	-108.7



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
Model: LFMM M8
Sample No: A004354880-001
Test Mode: TX_24G
Test Voltage: Battery
Remark: Temp:23.4°C;Humi:50%
Test standard: EN 305550
Tested By: Lich Chen
Reviewed by: Terry Yin




Critical Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
24453.687500	-67.49	-26.00	41.49	150.0	H	91.0	-104.8



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
Model: LFMM M8
Sample No: A004354880-001
Test Mode: TX_24G
Test Voltage: Battery
Remark: Temp:23.4°C;Humi:50%
Test standard: EN 305550
Tested By: Lich Chen
Reviewed by: Terry Yin




Critical Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
24448.000000	-69.75	-26.00	43.75	150.0	V	352.0	-107.6



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
Model: LFMM M8
Sample No: A004354880-001
Test Mode: TX_24G
Test Voltage: Battery
Remark: Temp:23.4°C;Humi:50%
Test standard: EN 305550
Tested By: Lich Chen
Reviewed by: Terry Yin




Critical Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
22152.500000	-68.28	-26.00	42.28	150.0	H	278.0	-106.5
31321.458333	-64.57	-26.00	38.57	150.0	H	168.0	-103.0



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
 Model: LFMM M8
 Sample No: A004354880-001
 Test Mode: TX_24G
 Test Voltage: Battery
 Remark: Temp:23.4°C;Humi:50%
 Test standard: EN 305550
 Tested By: Lich Chen
 Reviewed by: Terry Yin




Critical_Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
21352.708333	-71.25	-26.00	45.25	150.0	V	247.0	-110.5
30015.208333	-68.35	-26.00	42.35	150.0	V	9.0	-106.9



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
 Model: LFMM M8
 Sample No: A004354880-001
 Test Mode: TX_24G
 Test Voltage: Battery
 Remark: Temp:23.4°C;Humi:50%
 Test standard: EN 305550
 Tested By: Lich Chen
 Reviewed by: Terry Yin




Critical_Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
23901.562500	-68.17	-26.00	42.17	150.0	H	150.0	-105.4



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
 Model: LFMM M8
 Sample No: A004354880-001
 Test Mode: TX_24G
 Test Voltage: Battery
 Remark: Temp:23.4°C;Humi:50%
 Test standard: EN 305550
 Tested By: Lich Chen
 Reviewed by: Terry Yin




Critical_Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
23752.312500	-71.47	-26.00	45.47	150.0	V	67.0	-108.7



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
Model: LFMM M8
Sample No: A004354880-001
Test Mode: TX_24G
Test Voltage: Battery
Remark: Temp:23.4°C;Humi:50%
Test standard: EN 305550
Tested By: Lich Chen
Reviewed by: Terry Yin




Critical_Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
24453.687500	-67.49	-26.00	41.49	150.0	H	91.0	-104.8



EUT Information

EUT Name: Laifen Glowly Vanity Mirror
Model: LFMM M8
Sample No: A004354880-001
Test Mode: TX_24G
Test Voltage: Battery
Remark: Temp:23.4°C;Humi:50%
Test standard: EN 305550
Tested By: Lich Chen
Reviewed by: Terry Yin



Critical_Freqs

Frequency (MHz)	RMS (dBm)	Limit (dBm)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
24448.000000	-69.75	-26.00	43.75	150.0	V	352.0	-107.6




Prüfbericht - Produkte


Test Report - Products

Above 40GHz


Condition	Mk No.	Det	Frequency (MHz)	RBW (MHz)	VBW (MHz)	Level (dBm)	Ant. Polarity (H/V)	Ant. Height (m)	Test Distance
NTNV	M1	RMS	49020.000	1	3	-44.511	H	1.5	1m
NTNV	M1	RMS	48960.000	1	3	-44.480	V	1.5	1m
NTNV	M1	RMS	69930.000	1	3	-38.933	H	1.5	1m
NTNV	M1	RMS	69975.000	1	3	-39.267	V	1.5	1m




PASS



PASS



PASS



PASS