Company: Hewlett Packard Enterprise

Test of: APINH303
To: Taiwan LP0002 Section 3.10 (ISM Bands)

Report No.: HWPD85-T11 Rev A Bluetooth BLE

TEST REPORT

FROM

Test of: Hewlett Packard Enterprise APINH303

To: Taiwan LP0002 Section 3.10 (ISM Bands)

Note: this report contains data with regard to 2400-2483.5 MHz Bluetooth BLE operational mode of the Hewlett Packard Enterprise APINH303 Wireless Access Point

Test Report Serial No.: HWPD85-T11 Rev A Bluetooth BLE

This report supersedes: NONE

Applicant: 慧與科技股份有限公司
11568 台北市南港區經貿二路66號10樓之1

Product Function: 802.11 a/b/g/n/ac Wireless Access Point with BLE

Issue Date: 21st September 2017

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com

ACCREDITED
TESTING CERT #2381.01

MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

Table of Contents

1. ACCREDITATION, LISTINGS & RECOGNITION 4
1.1. Testing Accreditation 4
1.2. Recognition 5
1.3. Product Certification 6
2. DOCUMENT HISTORY 7
3. TEST RESULT CERTIFICATE 8
4. REFERENCES AND MEASUREMENT UNCERTAINTY 9
4.1. Normative References 9
4.2. Test and Uncertainty Procedure 10
5. PRODUCT DETAILS AND TEST CONFIGURATIONS 11
5.1. Technical Details 11
5.2. Scope Of Test Program 12
5.3. Equipment Model(s) and Serial Number(s) 13
5.4. Antenna Details 13
5.5. Cabling and I/O Ports 13
5.6. Test Configurations 13
5.7. Equipment Modifications 13
5.8. Deviations from the Test Standard 13
6. TEST SUMMARY 14
7. TEST EQUIPMENT CONFIGURATION(S) 15
7.1. Conducted 15
7.2. Radiated Emissions - 3m Chamber 17
8. MEASUREMENT AND PRESENTATION OF TEST DATA 19
9. TEST RESULTS 20
9.1. 6 dB & 99% Bandwidth 20
9.2. Conducted Output Power 22
9.3 Conducted Spurious Emissions 25
9.3.1 Conducted Emissions 25
9.3.2 Conducted Band-Edge Emissions 27
Low Band-Edge Emissions 27
High Band-Edge Emissions 28
9.4 Power Spectral Density 29
9.5 Radiated Emissions 31
9.5.1 Restricted Band Emissions 33
9.5.2 Restricted Band-Edge Emissions 36
A. APPENDIX - GRAPHICAL IMAGES 39
A.1. 6 dB & 99% Bandwidth 40
A.2. Conducted Emissions 43
A.2.1 Conducted Spurious Emissions 43
A.2.2 Conducted Band Edge Emissions 46
A.3. Power Spectral Density 48
A.4. Radiated Emissions 54
A.4.1. TX Spurious & Restricted Band Emissions 54
A.4.2. Restricted Edge & Band-Edge Emissions 57

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

1. ACCREDITATION, LISTINGS & RECOGNITION

1.1. Testing Accreditation

MiCOM Labs, Inc. is an accredited Electrical testing laboratory per the international standard ISO/IEC 17025:2005. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; http://www.a2la.org/scopepdf/2381-01.pdf

ilac-MRA A2LA

Accredited Laboratory

A2LA has accredited

MICOM LABS

Pleasanton, CA

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (*refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009*).

Presented this 4th day of February 2016.

Senior Director of Quality & Communications
For the Accreditation Council
Certificate Number 2381.01
Valid to November 30, 2017

For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

1.2. Recognition

MiCOM Labs, Inc. has widely recognized wireless testing capabilities. Our international recognition includes Conformity Assessment Body designation by APEC MRA countries. MiCOM Labs test reports are accepted globally.

Country	Recognition Body	Status	Phase	Identification No.
USA	Federal Communications Commission (FCC)	TCB	-	US0159 Listing #: 102167
Canada	Industry Canada (IC)	FCB	APEC MRA 2	US0159 Listing #: 4143A-2 4143A-3
Japan	MIC (Ministry of Internal Affairs and Communication)	CAB	APEC MRA 2	RCB 210
	VCCI	--	--	A-0012
Europe	European Commission	NB	EU MRA	NB 2280
Australia	Australian Communications and Media Authority (ACMA)	CAB	APEC MRA 1	US0159
Hong Kong	Office of the Telecommunication Authority (OFTA)	CAB	APEC MRA 1	
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)	CAB	APEC MRA 1	
Singapore	Infocomm Development Authority (IDA)	CAB	APEC MRA 1	
Taiwan	National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI)	CAB	APEC MRA 1	
Vietnam	Ministry of Communication (MIC)	CAB	APEC MRA 1	

EU MRA – European Union Mutual Recognition Agreement.
NB – Notified Body
APEC MRA – Asia Pacific Economic Community Mutual Recognition Agreement. Recognition agreement under which test lab is accredited to regulatory standards of the APEC member countries.

Phase I - recognition for product testing
Phase II – recognition for both product testing and certification

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

1.3. Product Certification

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard ISO/IEC 17065:2012. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.02. MiCOM Labs test schedule is available at the following URL; http://www.a2la.org/scopepdf/2381-02.pdf

Accredited Product Certification Body

A2LA has accredited

MICOM LABS

Pleasanton, CA

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC 17065:2012 *Requirements for bodies certifying products, processes and services*. This accreditation demonstrates technical competence for a defined scope and the operation of a management system.

Presented this 4th day of February 2016.

Senior Director of Quality & Communications
For the Accreditation Council
Certificate Number 2381.02
Valid to November 30, 2017

For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation.

United States of America – Telecommunication Certification Body (TCB)

Industry Canada – Certification Body, CAB Identifier – US0159

Europe – Notified Body (NB), NB Identifier - 2280

Japan – Recognized Certification Body (RCB), RCB Identifier - 210

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

2. DOCUMENT HISTORY

Report History		
Revision	**Date**	**Comments**
Rev A	21st September 2017	Initial release.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

3. TEST RESULT CERTIFICATE

Manufacturer:	Hewlett Packard Enterprise 3000 Hanover St. Palo Alto California 94304 USA	**Tested By:**	MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA
Model:	APINH303	**Telephone:**	+1 925 462 0304
		Fax:	+1 925 462 0306
Type Of Equipment:	802.11a/b/g/n/ac Wireless Access Point with BLE		
S/N's:	CNC7K2R00X		
Test Date(s):	31st October – 4th November 2016	**Website:**	www.micomlabs.com

STANDARD(S)	TEST RESULTS
Taiwan LP0002 Section 3.10 (ISM Bands)	EQUIPMENT COMPLIES

MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Notes:

1. This document reports conditions under which testing was conducted and the results of testing performed.

2. Details of test methods used have been recorded and kept on file by the laboratory.

3. Test results apply only to the item(s) tested.

A2LA ACCREDITED
TESTING CERT #2381.01

Approved & Released for MiCOM Labs, Inc. by:



Graeme Grieve
Quality Manager MiCOM Labs, Inc.

Gordon Hurst
President & CEO MiCOM Labs, Inc.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

4. REFERENCES AND MEASUREMENT UNCERTAINTY

4.1. Normative References

REF.	PUBLICATION	YEAR	TITLE
I	Taiwan LP0002	23rd Aug 2016	Low-power Radio-frequency Devices – Technical Regulations
II	KDB 662911 D01 v02r01	Oct 31 2013	Guidance for measurement of output emission of devices that employ single transmitter with multiple outputs or systems with multiple transmitters operating simultaneously in the same frequency band
III	KDB 558074 D01 v03r05	8th April, 2016	Guidance for performing compliance measurements on Digital Transmission Systems (DTS) operating under section 15.247.
IV	A2LA	February 2016	R105 - Requirement's When Making Reference to A2LA Accreditation Status
V	ANSI C63.10	2013	American National Standard for Testing Unlicensed Wireless Devices
VI	ANSI C63.4	2014	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
VII	CISPR 22	2008	Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement
VIII	ETSI TR 100 028	2001-12	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
IX	FCC 47 CFR Part 15.247	2014	Radio Frequency Devices; Subpart C – Intentional Radiators
X	M 3003	Edition 3 Nov. 2012	Expression of Uncertainty and Confidence in Measurements
XI	FCC 47 CFR Part 2.1033	2014	FCC requirements and rules regarding photographs and test setup diagrams.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

4.2. Test and Uncertainty Procedure

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor k = 2, providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5. PRODUCT DETAILS AND TEST CONFIGURATIONS

5.1. Technical Details

Details	Description
Purpose:	Test of the Hewlett Packard Enterprise APINH303 to Taiwan's LP0002 Low-power Radio-frequency Devices – Technical Regulations
Applicant:	慧與科技股份有限公司 11568 台北市南港區經貿二路66號10樓之1
Manufacturer:	Hewlett Packard Enterprise 3000 Hanover St., Palo Alto California 94304 USA
Laboratory performing the tests:	MiCOM Labs, Inc. 575 Boulder Court, Pleasanton California 94566 USA
Test report reference number:	HWPD85-T11
Date EUT received:	31st October 2016
Standard(s) applied:	Taiwan LP0002
Dates of test (from - to):	31st October – 4th November 2016
No of Units Tested:	2
Type of Equipment:	802.11 a/b/g/n/ac Wireless Access Point with BLE
Product Family Name:	802.11 a/b/g/n/ac Wireless Access Point
Model(s):	APINH303
Location for use:	Indoor
Declared Frequency Range(s):	2400 - 2483.5 MHz;
Primary function of equipment:	Transmission of voice and/ or data
Secondary function of equipment:	None Provided
Type of Modulation:	GFSK
EUT Modes of Operation:	GFSK
Transmit/Receive Operation:	Transceiver - Full Duplex
Rated Input Voltage and Current:	AC/ DC adaptor (adaptor NOT sold with unit) 48Vdc
Operating Temperature Range:	Declared Range 0°C to 40°C
ITU Emission Designator:	BLE: 1M1G1D
Equipment Dimensions:	150mm x 86mm X 38mm
Weight:	0.26kg (0.6 lbs)
Hardware Rev:	P2-2
Software Image:	ipq40xxqdart.ari.abeaudin-rd-sw-inst2-wip (Time Stamp 11/03/16 14:08)
Firmware	Smart RF Studio 7 2.2.1 (firmware Rev. 0025)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5.2. Scope Of Test Program

Hewlett Packard Enterprise APINH303

The scope of the test program was to test the Hewlett Packard Enterprise APINH303 Bluetooth BLE configurations in the frequency ranges 2400 - 2483.5 MHz; for compliance against the following specifications:

Taiwan LP0002 Section 3.10 ISM Bands
Low-power Radio-frequency Devices – Technical Regulations

Hewlett Packard Enterprise APINH303
EUT MAIN PICTURE



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5.3. Equipment Model(s) and Serial Number(s)

Type	Description	Manufacturer	Model	Serial no.	Delivery Date
EUT	802.11 a/b/g/n/ac/ac Wireless Access Point & BLE	Hewlett Packard Enterprise	APINH303	CNC7K2R00X	31st October 2016
Support	Laptop PC	DELL	E7450	None	N/A

5.4. Antenna Details

Type	Manufacturer	Model	Family	Gain (dBi)	BF Gain	Dir BW	X-Pol	Frequency Band (MHz)
integral	Aruba	Metal sheet	PCB	0.85	--	360	-	2400 - 2483.5

BF Gain - Beamforming Gain
Dir BW - Directional BeamWidth
X-Pol - Cross Polarization

5.5. Cabling and I/O Ports

Port Type	Max Cable Length	# Of Ports	Screened	Conn Type	Data Type
Ethernet	100	3	N	RJ45	Packet Data

5.6. Test Configurations

Results for the following configurations are provided in this report:

Operational Mode(s) (GFSK)	Data Rate with Highest Power MBit/s	Channel Frequency (MHz)		
		Low	Mid	High
2400 - 2483.5 MHz				
GFSK	1.00	2402.00	2440.00	2480.00

5.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:
1. NONE

5.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:
1. NONE

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

6. TEST SUMMARY

List of Measurements

Test Header	Result	Data Link
Conducted Results		
Section 3.10.1 (6.2.1): 6 dB & 99% Bandwidth	Complies	View Data
Section 3.10.1 (2.3): Conducted Output Power	Complies	View Data
Section 3.10.1 (5): Emissions		
(1) Conducted Emissions		
(i) Conducted Spurious Emissions	Complies	View Data
(ii) Conducted Band-Edge Emissions	Complies	View Data
Section 3.10.1 (6.2.2): Power Spectral Density	Complies	View Data
Radiated Emissions		
Section 2.7 & 2.8: (2) Radiated Emissions		
(i) 15.205 Restricted Band Emissions	Complies	View Data
(ii) 15.205 Restricted Band-Edge Emissions	Complies	View Data
Digital Emissions	See Report HWPD85-G3 (CNS 13438)	
Section 2.7 & 2.8: (3) Digital Emissions	Complies	
AC Wireline	See Report HWPD85-G3 (CNS 13438)	
Section 2.3: AC Wireline Emissions	Complies	
Antenna Specification(s)		
Antenna Specifications for Bluetooth BLE **Section 3.10.1 (3) (4):** EUT operate with integral antennas which can be observed in the antenna photographs, they are in accordance with Section 3.10.1 (3) (4) of the standard	Complies	--

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

7. TEST EQUIPMENT CONFIGURATION(S)

7.1. Conducted

Conducted RF Emission Test Set-up(s)
The following tests were performed using the conducted test set-up shown in the diagram below.
1. 6 dB & 99% Bandwidth
2. Peak Output Power
3. Power Spectral Density- Peak
4. Conducted Low Band-Edge Emission - Peak
5. Conducted Spurious Emissions - Peak
6. Conducted High Band-Edge Emission - Peak



Conducted Test Measurement Setup

A full system calibration was performed on the test station and any resulting system losses (or gains) were taken into account in the production of all final measurement data.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Asset#	Description	Manufacturer	Model#	Serial#	Calibration Due Date
158	Barometer/Thermometer	Control Company	4196	E2846	01 Dec 2016
248	Resistance Thermometer	Thermotronics	GR2105-02	9340 #1	21 Oct 2017
376	USB 10MHz - 18GHz Average Power Sensor	Agilent	U2000A	MY51440005	23 Oct 2017
378	Rohde & Schwarz 40 GHz Receiver with Generator	Rhode & Schwarz	ESIB40	100107/040	04 Aug 2017
381	4x4 RF Switch Box	MiCOM Labs	MiTest RF Switch Box	MIC002	18 Nov 2016
419	Laptop with Labview Software	Lenova	W520	TS02	Not Required
420	USB to GPIB Interface	National Instruments	GPIB-USB HS	1346738	Not Required
440	USB Wideband Power Sensor	Boonton	55006	9178	25 Dec 2016
442	USB Wideband Power Sensor	Boonton	55006	9181	06 Oct 2017
445	PoE Injector	D-Link	DPE-101GL	QTAH1E2000625	Not Required
460	Dell Computer	Dell	Optiplex330	BC944G1	Not Required
493	USB Wideband Power Sensor	Boonton	55006	9634	10 Mar 2017
494	USB Wideband Power Sensor	Boonton	55006	9726	10 Mar 2017
RF#2 GPIB#1	GPIB cable to Power Supply	HP	GPIB	None	Not Required
RF#2 SMA#1	EUT to Mitest box port 1	Flexco	SMA Cable port1	None	18 Nov 2016
RF#2 SMA#2	EUT to Mitest box port 2	Flexco	SMA Cable port2	None	18 Nov 2016
RF#2 SMA#3	EUT to Mitest box port 3	Flexco	SMA Cable port3	None	18 Nov 2016
RF#2 SMA#4	EUT to Mitest box port 4	Flexco	SMA Cable port4	None	18 Nov 2016
RF#2 SMA#SA	Mitest box to SA	Flexco	SMA Cable SA	None	18 Nov 2016
RF#2 USB#1	USB Cable to Mitest Box	Dynex	USB Cable	None	Not Required

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

7.2. Radiated Emissions - 3m Chamber

The following tests were performed using the radiated test set-up shown in the diagram below.

Radiated emissions below 1GHz.
Radiated Emissions above 1GHz.



Radiated Emission Test Setup

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A full system calibration was performed on the test station and any resulting system losses (or gains) were taken into account in the production of all final measurement data.

Asset#	Description	Manufacturer	Model#	Serial#	Calibration Due Date
158	Barometer/Thermometer	Control Company	4196	E2846	01 Dec 2016
170	Video System Controller for Semi Anechoic Chamber	Panasonic	WV-CU101	04R08507	Not Required
287	Rohde & Schwarz 40 GHz Receiver	Rhode & Schwarz	ESIB40	100201	02 May 2017
338	Sunol 30 to 3000 MHz Antenna	Sunol	JB3	A052907	15 Aug 2017
396	2.4 GHz Notch Filter	Microtronics	BRM50701	001	16 Aug 2017
397	Amp 10 - 2500MHz	MiCOM Labs	Amp 10 - 2500 MHz	NA	09 Jun 2017
399	ETS 1-18 GHz Horn Antenna	ETS	3117	00154575	10 Jan 2017
406	Amplifier for Radiated Emissions	MiCOM Labs	40dB 1 to 18GHz Amp	0406	09 Jun 2017
410	Desktop Computer	Dell	Inspiron 620	WS38	Not Required
411	Mast/Turntable Controller	Sunol Sciences	SC98V	060199-1D	Not Required
412	USB to GPIB Interface	National Instruments	GPIB-USB HS	11B8DC2	Not Required
413	Mast Controller	Sunol Science	TWR95-4	030801-3	Not Required
415	Turntable Controller	Sunol Sciences	Turntable Controller	None	Not Required
447	Rad Emissions Test Software	MiCOM	Version 1.0.109	447	Not Required
462	Schwarzbeck cable from Antenna to Amplifier.	Schwarzbeck	AK 9513	462	31 May 2017
463	Schwarzbeck cable from Amplifier to Bulkhead.	Schwarzbeck	AK 9513	463	31 May 2017
464	Schwarzbeck cable from Bulkhead to Receiver	Schwarzbeck	AK 9513	464	31 May 2017
465	Low Pass Filter DC-1000 MHz	Mini-Circuits	NLP-1200+	VUU01901402	02 Jun 2017
480	Cable - Bulkhead to Amp	SRC Haverhill	157-157-3050360	480	02 Jun 2017
481	Cable - Bulkhead to Receiver	SRC Haverhill	151-151-3050787	481	02 Jun 2017
482	Cable - Amp to Antenna	SRC Haverhill	157-157-3051574	482	02 Jun 2017

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

8. MEASUREMENT AND PRESENTATION OF TEST DATA

The measurement and graphical data presented in this test report was generated automatically using state-of-the-art technology creating an easy to read report structure. Numerical measurement data is separated from supporting graphical data (plots) through hyperlinks. Numerical measurement data can be reviewed without scrolling through numerous graphical pages to arrive at the next data matrix.

Plots have been relegated into the Appendix 'Graphical Data'.

Test and report automation was performed by MiTest. MiTest is an automated test system developed by MiCOM Labs. MiTest is the first cloud based modular test system enabling end-to-end automation of regulatory compliance testing.

The MiCOM Labs "MiTest" Automated Test System" (Patent Pending)

9. TEST RESULTS

9.1. 6 dB & 99% Bandwidth

Conducted Test Conditions for 6 dB and 99% Bandwidth			
Standard:	Taiwan LP0002	**Ambient Temp. (ºC):**	24.0 - 27.5
Test Heading:	6 dB and 99 % Bandwidth	**Rel. Humidity (%):**	32 - 45
Standard Section(s):	3.10.1 (6.2.1)	**Pressure (mBars):**	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for 6 dB and 99% Bandwidth Measurement
The bandwidth at 6 dB and 99 % was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

Testing was performed under ambient conditions at nominal voltage. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured and reported.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits for 6 dB and 99% Bandwidth

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(2) Systems using digital modulation techniques may operate in the 902-928 MHz and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Equipment Configuration for 6 dB & 99% Bandwidth			
Variant:	GFSK	**Duty Cycle (%):**	99
Data Rate:	1.00 MBit/s	**Antenna Gain (dBi):**	Not Applicable
Modulation:	GFSK	**Beam Forming Gain (Y)(dB):**	Not Applicable
TPC:	Not Applicable	**Tested By:**	CC
Engineering Test Notes:	None		

Test Measurement Results

Test Frequency	Measured 6 dB Bandwidth (MHz) Port(s)				6 dB Bandwidth (MHz)		Limit	Lowest Margin
MHz	a	b	c	d	Highest	Lowest	KHz	MHz
2402.0	0.709	--	--	--	0.709	0.709	≥500.0	-0.21
2440.0	0.709	--	--	--	0.709	0.709	≥500.0	-0.21
2480.0	0.709	--	--	--	0.709	0.709	≥500.0	-0.21

Test Frequency	Measured 99% Bandwidth (MHz) Port(s)				Maximum 99% Bandwidth (MHz)		
MHz	a	b	c	d			
2402.0	1.074	--	--	--	1.074		
2440.0	1.078	--	--	--	1.078		
2480.0	1.078	--	--	--	1.078		

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

9.2. Conducted Output Power

Conducted Test Conditions for Fundamental Emission Output Power			
Standard:	Taiwan LP0002	**Ambient Temp. (ºC):**	24.0 - 27.5
Test Heading:	Output Power	**Rel. Humidity (%):**	32 - 45
Standard Section(s):	3.10.1 (2.3)	**Pressure (mBars):**	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Fundamental Emission Output Power Measurement
In the case of average power measurements an average power sensor was utilized.

For peak power measurements the spectrum analyzer built-in power function was used to integrate peak power over the 20 dB bandwidth.

Testing was performed under ambient conditions at nominal voltage only. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured, summed (Σ) and reported.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.
Supporting Information
Calculated Power = A + G + Y+ 10 log (1/x) dBm

A = Total Power [10*Log10 ($10^{a/10}$ + $10^{b/10}$ + $10^{c/10}$ + $10^{d/10}$)]
G = Antenna Gain
Y = Beamforming Gain
x = Duty Cycle (average power measurements only)

Limits for Fundamental Emission Output Power
(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following for non-frequency hopping systems:

(3) For systems using digital modulation in the 902-928 MHz and 2400-2483.5 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.
(1) Fixed point-to-point operation:
(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(iii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

(2) In addition to the provisions in paragraphs (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400-2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:

(i) Different information must be transmitted to each receiver.

(ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:

(A) The directional gain shall be calculated as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

(B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.

(iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.

(iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

Maximum Transmit (Conducted) Power Limits
EUT: Indoor operation - Wireless Access Point
Antenna gain: 0.85 dBi (< 6 dBi)
Beamforming Gain: Not Applicable
Limit: +30.0 dBm
Maximum EIRP: 30.0 + 0.85 = +30.85 dBm/EIRP

Modified Conducted Power Levels
During radiated emission testing (spurious and restricted band-edge) the power setting may have been reduced. Any reduction in output power (together with power settings) that was required to bring the EUT into compliance is reflected in the following tables.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Equipment Configuration for Peak Output Power			
Variant:	GFSK	**Duty Cycle (%):**	99.0
Data Rate:	1.00 MBit/s	**Antenna Gain (dBi):**	0.85
Modulation:	GFSK	**Beam Forming Gain (Y)(dB):**	Not Applicable
TPC:	Not Applicable	**Tested By:**	CC
Engineering Test Notes:	None		

Test Measurement Results

Test Frequency	Measured Output Power (dBm) Port(s)				Calculated Total Power Σ Port(s)	Limit	Margin	EUT Power Setting
MHz	a	b	c	d	dBm	dBm	dB	
2402.0	0.91	--	--	--	0.91	30.00	-29.09	4.00
2440.0	0.92	--	--	--	0.92	30.00	-29.08	4.00
2480.0	0.93	--	--	--	0.93	30.00	-29.07	4.00

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	±1.33 dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

9.3 Conducted Spurious Emissions

9.3.1 Conducted Emissions

Conducted Test Conditions for Transmitter Conducted Spurious and Band-Edge Emissions			
Standard:	Taiwan LP0002	**Ambient Temp. (ºC):**	24.0 - 27.5
Test Heading:	Max Unwanted Emission Levels	**Rel. Humidity (%):**	32 - 45
Standard Section(s):	3.10.1.5	**Pressure (mBars):**	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Transmitter Conducted Spurious and Band-Edge Emissions Measurement
Transmitter Conducted Spurious and Band-Edge emissions were measured at a limit of 30 dBc (average detector) or 20 dBc (peak detector) below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Measurements were made while EUT was operating in transmit mode of operation at the appropriate centre frequency closest to the band-edge. Emissions were maximized during the measurement and limits derived from the peak spectral power and drawn on each plot.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits Transmitter Conducted Spurious and Band-Edge Emissions
(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Equipment Configuration for Transmitter Conducted Spurious Emissions			
Variant:	GFSK	**Duty Cycle (%):**	99
Data Rate:	1.00 MBit/s	**Antenna Gain (dBi):**	0.85
Modulation:	GFSK	**Beam Forming Gain (Y):**	Not Applicable
TPC:	Not Applicable	**Tested By:**	CC
Engineering Test Notes:	None		

Test Measurement Results

Test Frequency	Frequency Range	Transmitter Conducted Spurious Emissions (dBm)							
		Port a		Port b		Port c		Port d	
MHz	MHz	SE	Limit	SE	Limit	SE	Limit	SE	Limit
2402.0	30.0 - 26000.0	-40.504	-20.00	--	--	--	--	--	--
2440.0	30.0 - 26000.0	-40.618	-20.00	--	--	--	--	--	--
2480.0	330.0 - 26000.0	-41.206	-22.00	--	--	--	--	--	--

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

9.3.2 Conducted Band-Edge Emissions

Low Band-Edge Emissions

Equipment Configuration for Conducted Low Band-Edge Emissions - Peak			
Variant:	GFSK	**Duty Cycle (%):**	99.0
Data Rate:	1.00 MBit/s	**Antenna Gain (dBi):**	0.85
Modulation:	GFSK	**Beam Forming Gain (Y)(dB):**	Not Applicable
TPC:	Not Applicable	**Tested By:**	CC
Engineering Test Notes:	None		

Test Measurement Results

Channel Frequency:	2402.0 MHz					
Band-Edge Frequency:	2400.0 MHz					
Test Frequency Range:	2350.0 - 2405.0 MHz					
Port(s)	**Band-Edge Markers and Limit**			**Revised Limit**		**Margin**
	M1 Amplitude (dBm)	**Plot Limit (dBm)**	**M2 Frequency (MHz)**	**Amplitude (dBm)**	**M2A Frequency (MHz)**	**(MHz)**
a	-39.98	-19.00	2401.40	--	--	-1.400

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

High Band-Edge Emissions

Equipment Configuration for Conducted High Band-Edge Emissions - Peak			
Variant:	GFSK	**Duty Cycle (%):**	99.0
Data Rate:	1.00 MBit/s	**Antenna Gain (dBi):**	Not Applicable
Modulation:	GFSK	**Beam Forming Gain (Y)(dB):**	Not Applicable
TPC:	Not Applicable	**Tested By:**	CC
Engineering Test Notes:	None		

Test Measurement Results

Channel Frequency:	2480.0 MHz					
Band-Edge Frequency:	2483.5 MHz					
Test Frequency Range:	2475.0 - 2524.0 MHz					
Port(s)	**Band-Edge Markers and Limit**			**Revised Limit**		**Margin**
	M3 Amplitude (dBm)	**Plot Limit (dBm)**	**M2 Frequency (MHz)**	**Amplitude (dBm)**	**M2A Frequency (MHz)**	**(MHz)**
a	-46.65	-20.00	2480.60	--	--	-2.900

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

9.4 Power Spectral Density

Conducted Test Conditions for Power Spectral Density			
Standard:	Taiwan LP0002	**Ambient Temp. (ºC):**	24.0 - 27.5
Test Heading:	Power Spectral Density	**Rel. Humidity (%):**	32 - 45
Standard Section(s):	3.10.1 (6.2.2)	**Pressure (mBars):**	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Power Spectral Density
The transmitter output was connected to a spectrum analyzer and the measured made in a 3 kHz resolution bandwidth using the analyzer auto-coupled sweep-time. A peak value was found over the full emission bandwidth and the spectrum downloaded for post processing purposes.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. The Peak Power Spectral Density is the highest level found across the emission bandwidth. With multiple antenna port measurements the numerical analyzer data from each port is summed (å) and a link to this additional graphic is provided.

Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Measure and sum the spectra across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The individual spectra are then summed mathematically in linear power units. Unlike in-band power measurements, in which the sum involves a single measured value (output power) from each output, measurements for compliance with PSD limits involve summing entire spectra across corresponding frequency bins on the various outputs. Consistency is maintained for any device with multiple transmitter outputs to be certain the individual outputs are all aligned with the same span and same number of points. In this instance, the linear power spectrum value within the first spectral bin of output 0 is summed with that in the first spectral bin of output 1, and the first spectral bin of output 2, and so on up to the Nth output to obtain the true value for the first frequency bin of the summed spectrum. The summed spectrum value for each frequency bin is computed in this fashion. These summed spectral values were post processed and the resulting numerical and graphical data presented.

NOTE:
It may be observed that the spectrum in some antenna port plots break the limit line however this in itself does NOT constitute a failure. In all cases a spectrum summation plot is provided in order to prove compliance. A failure occurs only after the summation of all spectrum plots have been summed and are found to be greater than the limit line.

Supporting Information
Calculated Power = A + 10 log (1/x) dBm
A = Total Power Spectral Density [10 Log10 ($10^{a/10} + 10^{b/10} + 10^{c/10} + 10^{d/10}$)]
x = Duty Cycle

Limits Power Spectral Density
For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Equipment Configuration for Power Spectral Density - Peak			
Variant:	GFSK	**Duty Cycle (%):**	99.0
Data Rate:	1.00 MBit/s	**Antenna Gain (dBi):**	0.85
Modulation:	GFSK	**Beam Forming Gain (Y)(dB):**	Not Applicable
TPC:	Not Applicable	**Tested By:**	CC
Engineering Test Notes:	None		

Test Measurement Results

Test Frequency	Measured Power Spectral Density Port(s) (dBm/3KHz)				Amplitude Summation	Limit	Margin
MHz	a	b	c	d	dBm/3KHz	dBm/3KHz	dB
2402.0	-11.230	--	--	--	-11.230	8.0	-19.2
2440.0	-12.802	--	--	--	-12.802	8.0	-20.8
2480.0	-12.996	--	--	--	-12.996	8.0	-21.0

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

9.5 Radiated Emissions

Radiated Test Conditions for Radiated Spurious and Band-Edge Emissions (Restricted Bands)			
Standard:	Taiwan LP0002	**Ambient Temp. (ºC):**	20.0 - 24.5
Test Heading:	Radiated Spurious and Band-Edge Emissions	**Rel. Humidity (%):**	32 - 45
Standard Section(s):	Section 2.8	**Pressure (mBars):**	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Radiated Spurious and Band-Edge Emissions (Restricted Bands)
Radiated emissions for restricted bands above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter and waveguide filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned. Measurements on any restricted band frequency or frequencies above 1 GHz are based on the use of measurement instrumentation employing peak and average detectors. All measurements were performed using a resolution bandwidth of 1 MHz.

Test configuration and setup for Radiated Spurious and Band-Edge Measurement were per the Radiated Test Set-up specified in this document.

Limits for Restricted Bands
Peak emission: 74 dBuV/m
Average emission: 54 dBuV/m

Field Strength Calculation
The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.
FS = R + AF + CORR - FO

where:
FS = Field Strength
R = Measured Spectrum analyzer Input Amplitude
AF = Antenna Factor
CORR = Correction Factor = CL – AG + NFL
CL = Cable Loss
AG = Amplifier Gain
FO = Distance Falloff Factor
NFL = Notch Filter Loss or Waveguide Loss

Example:
Given receiver input reading of 51.5 dBmV; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength (FS) of the measured emission is:

FS = 51.5 + 8.5 + 1.3 - 26.0 +1 = 36.3 dBmV/m

Conversion between dBmV/m (or dBmV) and mV/m (or mV) are as follows:
Level (dBmV/m) = 20 * Log (level (mV/m))

40 dBmV/m = 100 mV/m
48 dBmV/m = 250 mV/m

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Except as otherwise provided in this specification, the main frequency of any low-power RF motor shall not use the frequencies of the bands listed in the table below; Power RF motors fall within the bands listed in the table below, and the electric field strength must comply with the limits of Section 2.8 of LP0002.

Frequency Band			
MHz	**MHz**	**MHz**	**MHz**
0.090～0.110	108.00～138.00	1660.0～1770.0	8025.0～8500.0
0.490～0.510	149.90～150.05	1805.0～1865.0	9000.0～9200.0
2.172～2.198	156.70～156.90	1885.0～1900.0	9300.0～9500.0
3.013～3.033	162.01～167.17	1905.0～1985.0	10600～12700
4.115～4.198	167.72～173.20	2015.0～2025.0	13250～13400
5.670～5.690	240.00～285.00	2125.0～2165.0	14470～14500
6.200～6.300	322.00～335.40	2200.0～2300.0	15350～16200
8.230～8.400	399.90～410.00	2310.0～2390.0	17700～21400
12.265～12.600	485.00～510.00	2483.5～2900.0	22010～23120
13.340～13.430	608.00～614.00	3260.0～3267.0	23600～24000
14.965～15.020	703.00～748.00	3332.0～3339.0	31200～31800
16.700～16.755	758.00～803.00	3345.8～3358.0	36430～36500
19.965～20.020	825.00～915.00	3500.0～4400.0	38600 and above
25.500～25.700	930.00～1240.0	4500.0～5250.0	
37.475～38.275	1300.0～1427.0	5350.0～5460.0	
73.500～75.400	1435.0～1626.5	7250.0～7750.0	

Traceability

Test Methodology	Measurement Uncertainty
Measurements were made per work instruction WI-03 'Measurement of Radiated Emissions'	+5.6 / -4.5 dB

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

9.5.1 Restricted Band Emissions

Equipment Configuration for TX Spurious & Restricted Band Emissions			
Antenna:	Aruba Metal sheet	**Variant:**	BLE
Antenna Gain (dBi):	0.85	**Modulation:**	GFSK
Beam Forming Gain (Y):	Not Applicable	**Duty Cycle (%):**	99
Channel Frequency (MHz):	2402.00	**Data Rate:**	1.00 MBit/s
Power Setting:	4	**Tested By:**	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
#1	7205.55	48.49	4.26	-7.35	45.40	Peak (NRB)	Vertical	101	1	--	--	Pass
Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba Metal sheet	**Variant:**	BLE
Antenna Gain (dBi):	0.85	**Modulation:**	GFSK
Beam Forming Gain (Y):	Not Applicable	**Duty Cycle (%):**	99
Channel Frequency (MHz):	2440.00	**Data Rate:**	1.00 MBit/s
Power Setting:	4	**Tested By:**	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
#1	7319.24	55.14	4.26	-7.27	52.13	Max Peak	Horizontal	134	0	74.0	-21.9	Pass
#2	7319.24	44.75	4.26	-7.27	41.74	Max Avg	Horizontal	134	0	54.0	-12.3	Pass
Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	Aruba Metal sheet	**Variant:**	BLE
Antenna Gain (dBi):	0.85	**Modulation:**	GFSK
Beam Forming Gain (Y):	Not Applicable	**Duty Cycle (%):**	99
Channel Frequency (MHz):	2480.00	**Data Rate:**	1.00 MBit/s
Power Setting:	4	**Tested By:**	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
#1	7439.43	52.57	4.31	-7.13	49.75	Max Peak	Vertical	138	340	74.0	-24.3	Pass
#2	7439.43	42.04	4.31	-7.13	39.22	Max Avg	Vertical	138	340	54.0	-14.8	Pass
Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

9.5.2 Restricted Band-Edge Emissions

Aruba Metal sheet		Band-Edge Freq	Limit 74.0dBµV/m	Limit 54.0dBµV/m	Power Setting
Operational Mode	Operating Frequency (MHz)	MHz	dBµV/m	dBµV/m	
GFSK	2402.00	2390.00	60.90	46.16	4
GFSK	2480.00	2483.50	61.35	48.82	4

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Equipment Configuration for Radiated - Lower Restricted Band-Edge Emissions

Antenna:	Aruba Metal sheet	**Variant:**	GFSK
Antenna Gain (dBi):	0.85	**Modulation:**	GFSK
Beam Forming Gain (Y):	Not Applicable	**Duty Cycle (%):**	99
Channel Frequency (MHz):	2402.00	**Data Rate:**	1.00 MBit/s
Power Setting:	4	**Tested By:**	JMH

Test Measurement Results

2310.00 - 2410.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
#1	2382.16	26.24	2.69	31.97	60.90	Max Peak	Vertical	156	30	74.0	-13.1	Pass
#2	2390.00	11.43	2.69	32.04	46.16	Max Avg	Vertical	156	30	54.0	-7.8	Pass
#3	2390.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--
Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

Equipment Configuration for Radiated - Upper Restricted Band-Edge Emissions

Antenna:	Aruba Metal sheet	**Variant:**	GFSK
Antenna Gain (dBi):	0.85	**Modulation:**	GFSK
Beam Forming Gain (Y):	Not Applicable	**Duty Cycle (%):**	99
Channel Frequency (MHz):	2480.00	**Data Rate:**	1.00 MBit/s
Power Setting:	4	**Tested By:**	JMH

Test Measurement Results

2472.00 - 2500.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
#1	2483.50	13.72	2.73	32.37	48.82	Max Avg	Vertical	151	47	54.0	-5.2	Pass
#2	2483.50	26.25	2.73	32.37	61.35	Max Peak	Vertical	151	47	74.0	-12.7	Pass
#3	2483.50	--	--	--	--	Restricted-Band	--	--	--	--	--	--
Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A. APPENDIX - GRAPHICAL IMAGES

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.1. 6 dB & 99% Bandwidth

6 dB & 99% BANDWIDTH

Variant: GFSK, Channel: 2402.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 2401.649 MHz : -3.964 dBm M2 : 2402.255 MHz : 2.073 dBm Delta1 : 709 KHz : 0.189 dB T1 : 2401.469 MHz : -11.838 dBm T2 : 2402.543 MHz : -11.944 dBm OBW : 1.074 MHz	Measured 6 dB Bandwidth: 0.709 MHz Limit: ≥500.0 kHz Margin: -0.21 MHz

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

6 dB & 99% BANDWIDTH

Variant: GFSK, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 2439.645 MHz : -4.861 dBm M2 : 2440.251 MHz : 1.330 dBm Delta1 : 709 KHz : 0.565 dB T1 : 2439.465 MHz : -12.703 dBm T2 : 2440.543 MHz : -12.719 dBm OBW : 1.078 MHz	Measured 6 dB Bandwidth: 0.709 MHz Limit: ≥500.0 kHz Margin: -0.21 MHz

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

6 dB & 99% BANDWIDTH

Variant: GFSK, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 2479.645 MHz : -5.690 dBm M2 : 2479.762 MHz : 0.362 dBm Delta1 : 709 KHz : 0.212 dB T1 : 2479.465 MHz : -13.669 dBm T2 : 2480.543 MHz : -13.488 dBm OBW : 1.078 MHz	Measured 6 dB Bandwidth: 0.709 MHz Limit: ≥500.0 kHz Margin: -0.21 MHz

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.2. Conducted Emissions

A.2.1 Conducted Spurious Emissions

CONDUCTED SPURIOUS EMISSIONS - PEAK

Variant: GFSK, Channel: 2402.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 0.393 dBm M2 : 6535.511 MHz : -40.504 dBm	Limit: -20.00 dBm Margin: -20.50 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

CONDUCTED SPURIOUS EMISSIONS - PEAK

Variant: GFSK, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2424.028 MHz : -0.551 dBm M2 : 6951.864 MHz : -40.618 dBm	Limit: -20.00 dBm Margin: -20.62 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

CONDUCTED SPURIOUS EMISSIONS - PEAK

Variant: GFSK, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2476.072 MHz : -2.152 dBm M2 : 6639.599 MHz : -41.206 dBm	Limit: -22.00 dBm Margin: -19.21 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.2.2 Conducted Band Edge Emissions

Low Band-Edge Emissions



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -39.981 dBm M2 : 2401.363 MHz : -20.427 dBm M3 : 2402.355 MHz : 1.690 dBm	Channel Frequency: 2402.00 MHz

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

High Band-Edge Emissions

CONDUCTED HIGH BAND-EDGE EMISSION - PEAK

Variant: GFSK, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2480.204 MHz : 0.138 dBm M2 : 2480.597 MHz : -15.989 dBm M3 : 2483.500 MHz : -46.646 dBm	Channel Frequency: 2480.00 MHz

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.3. Power Spectral Density



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2402.104 MHz : -11.230 dBm	Limit: ≤ 8.000 dBm Margin: 19.23 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY - PEAK

Variant: GFSK, Channel: 2402.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2402.104 MHz : -11.230 dBm	Limit: ≤ 8.0 dBm Margin: -19.2 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY - PEAK

Variant: GFSK, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2440.206 MHz : -12.802 dBm	Limit: ≤ 8.000 dBm Margin: 20.80 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY - PEAK

Variant: GFSK, Channel: 2440.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2440.206 MHz : -12.802 dBm	Limit: ≤ 8.0 dBm Margin: -20.8 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY - PEAK

Variant: GFSK, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2480.026 MHz : -12.996 dBm	Limit: ≤ 8.000 dBm Margin: 21.00 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

POWER SPECTRAL DENSITY - PEAK

Variant: GFSK, Channel: 2480.00 MHz, SUM, Temp: 20, Voltage: 48 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2480.026 MHz : -12.996 dBm	Limit: ≤ 8.0 dBm Margin: -21.0 dB

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.4. Radiated Emissions

A.4.1. TX Spurious & Restricted Band Emissions



1000.00 - 18000.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
1	7205.55	48.49	4.26	-7.35	45.40	Peak (NRB)	Vertical	101	1	--	--	Pass

Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: GFSK, Test Freq: 2440.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 4, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
1	7319.24	55.14	4.26	-7.27	52.13	Max Peak	Horizontal	134	0	74.0	-21.9	Pass
2	7319.24	44.75	4.26	-7.27	41.74	Max Avg	Horizontal	134	0	54.0	-12.3	Pass

Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: GFSK, Test Freq: 2480.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 4, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
1	7439.43	52.57	4.31	-7.13	49.75	Max Peak	Vertical	138	340	74.0	-24.3	Pass
2	7439.43	42.04	4.31	-7.13	39.22	Max Avg	Vertical	138	340	54.0	-14.8	Pass

Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

A.4.2. Restricted Edge & Band-Edge Emissions

RADIATED - LOWER RESTRICTED BAND-EDGE EMISSIONS

Variant: GFSK, Test Freq: 2402.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 4, Duty Cycle (%): 99



2310.00 - 2410.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
1	2382.16	26.24	2.69	31.97	60.90	Max Peak	Vertical	156	30	74.0	-13.1	Pass
2	2390.00	11.43	2.69	32.04	46.16	Max Avg	Vertical	156	30	54.0	-7.8	Pass
3	2390.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

RADIATED - UPPER RESTRICTED BAND-EDGE EMISSIONS

Variant: GFSK, Test Freq: 2480.00 MHz, Antenna: Aruba Metal sheet, Power Setting: 4, Duty Cycle (%): 99



2472.00 - 2500.00 MHz												
Num	**Frequency MHz**	**Raw dBµV**	**Cable Loss dB**	**AF dB**	**Level dBµV/m**	**Measurement Type**	**Pol**	**Hgt cm**	**Azt Deg**	**Limit dBµV/m**	**Margin dB**	**Pass /Fail**
1	2483.50	13.72	2.73	32.37	48.82	Max Avg	Vertical	151	47	54.0	-5.2	Pass
2	2483.50	26.25	2.73	32.37	61.35	Max Peak	Vertical	151	47	74.0	-12.7	Pass
3	2483.50	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT on 150 cm table powered by host laptop via CC debugger.

back to matrix

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com